FCC RF Test Report

APPLICANT: Zebra Technologies Corporation

EQUIPMENT: Touch computer

BRAND NAME : Zebra

MODEL NAME : TC510K

FCC ID : UZ7TC510K

STANDARD : FCC Part 15 Subpart E §15.407

CLASSIFICATION : (NII) Unlicensed National Information Infrastructure

The product was received on Jun. 18, 2016 and testing was completed on Aug. 26, 2016. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 1 of 46
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01

Report No.: FR672014-01F

TABLE OF CONTENTS

RE	VISIO	N HISTORY	3
SU	MMAF	RY OF TEST RESULT	4
1	GENI	ERAL DESCRIPTION	5
	1.1 1.2 1.3 1.4 1.5 1.6	Applicant	5 6 7
2	TEST	CONFIGURATION OF EQUIPMENT UNDER TEST	9
	2.1 2.2 2.3 2.4 2.5 2.6 2.7	Carrier Frequency and Channel Pre-Scanned RF Power Test Mode Connection Diagram of Test System Support Unit used in test configuration and system EUT Operation Test Setup Measurement Results Explanation Example	101820
3	TEST	T RESULT	21
	3.1 3.2 3.3 3.4 3.5 3.6 3.7 3.8	6dB and 26dB and 99% Occupied Bandwidth Measurement Maximum Conducted Output Power Measurement Power Spectral Density Measurement Unwanted Emissions Measurement AC Conducted Emission Measurement Frequency Stability Measurement Automatically Discontinue Transmission Antenna Requirements	
4		OF MEASURING EQUIPMENT	
5		ERTAINTY OF EVALUATION	46
		DIX A. CONDUCTED TEST RESULTS	
		DIX B. RADIATED SPURIOUS EMISSION	
		DIX C. RADIATED SPURIOUS EMISSION PLOTS	
		DIX D. DUTY CYCLE PLOTS	
ΑP	PEND	DIX E. SETUP PHOTOGRAPHS	

Report No. : FR672014-01F

Report Version : Rev. 01

REVISION HISTORY

Report No. : FR672014-01F

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR672014-01F	Rev. 01	Initial issue of report	Sep. 19, 2016

 SPORTON INTERNATIONAL INC.
 Page Number
 : 3 of 46

 TEL: 886-3-327-3456
 Report Issued Date
 : Sep. 19, 2016

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

FCC ID : UZ7TC510K Report Template No.: BU5-FR15EWLB4 AC MA Version 1.4

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.403(i)	6dB, 26dB and 99% Occupied Bandwidth	> 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b)(4)(i) &15.209(a)	Pass	Under limit 1.55 dB at 5631.200 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 11.40 dB at 0.366 MHz
3.6	15.407(g)	Frequency Stability	Within Operation Band	Pass	-
3.7	15.407(c)	Automatically Discontinue Transmission	Discontinue Transmission	Pass	-
3.8	15.203 & 15.407(a)	Antenna Requirement	N/A	Pass	-

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 4 of 46
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01

Report No. : FR672014-01F

General Description

1.1 Applicant

Zebra Technologies Corporation

1 Zebra Plaza Holtsville, NY 11742

1.2 Manufacturer

Wistron Corporation

21F, No. 88, Sec. 1, Hsin Tai Wu Rd., Hsichih Dist, New Taipei City 221, Taiwan R.O.C.

1.3 Product Feature of Equipment Under Test

Product Feature					
Equipment	Touch computer				
Brand Name	Zebra				
Model Name	TC510K				
FCC ID	UZ7TC510K				
EUT supports Radios application	NFC WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE				
HW Version	EV2				
SW Version	91-10-03-MG-00				
FW Version	FUSION_BA_2.00.0.0.008				
EUT Stage	Engineering sample				

Report No.: FR672014-01F

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Specification of Accessories							
Adapter 1 (5V/2.5A)	Brand Name	Zebra	Model Number	SAWA-65-20005A			
Adapter 2 (5V/1.2A)	Brand Name	Zebra	Model Number	PS000081A01			
Headset Jumper 1	Brand Name	Zebra	Part Number	CBL-TC51-HDST25-01			
Headset Jumper 2	Brand Name	Zebra	Part Number	CBL-TC51-HDST35-01			
Battery	Brand Name	Zebra	Part Number	BT-000314-01			
2.5mm Earphone	Brand Name	Zebra	Part Number	HDST-25MM-PTVP-01			
3.5mm Earphone	Brand Name	Zebra	Part Number	HDST-35MM-PTVP-01			
Trigger Handle	Brand Name	Zebra	Part Number	TRG-TC51-SNP1-01			
USB cable	Brand Name	Zebra	Part Number	CBL-TC51-USB1-01			
Soft Holster	Brand Name	Zebra	Part Number	SG-TC51-HLSTR1-01			
Exoskeleton	Brand Name	Zebra	Part Number	SG-TC51-EX01-01			
Hand strap	Brand Name	Zebra	Part Number	SG-TC51-BHDSTP1-03			

SPORTON INTERNATIONAL INC.

Page Number : 5 of 46 TEL: 886-3-327-3456 Report Issued Date: Sep. 19, 2016 FAX: 886-3-328-4978 Report Version : Rev. 01

FCC ID: UZ7TC510K Report Template No.: BU5-FR15EWLB4 AC MA Version 1.4

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification					
Tx/Rx Channel Frequency Range	5745 MHz ~ 5825 MHz				
, and the same of	<ant. 1=""></ant.>				
	802.11a : 16.69 dBm / 0.0467 W				
	802.11n HT20 : 16.53 dBm / 0.0450 W				
	802.11n HT40 : 15.78 dBm / 0.0378 W				
	802.11ac VHT20: 16.54 dBm / 0.0451 W				
	802.11ac VHT40: 15.87 dBm / 0.0386 W				
	802.11ac VHT80: 15.18 dBm / 0.0330 W				
	<ant. 2=""></ant.>				
	802.11a : 16.37 dBm / 0.0434 W				
	802.11n HT20 : 16.37 dBm / 0.0434 W				
Maximum Output Power	802.11n HT40 : 15.54 dBm / 0.0358 W				
<cdd modes=""></cdd>	802.11ac VHT20: 16.38 dBm / 0.0435 W				
	802.11ac VHT40: 15.60 dBm / 0.0363 W				
	802.11ac VHT80: 14.89 dBm / 0.0310 W				
	MIMO <ant. +="" 1="" 2=""></ant.>				
	802.11a : 19.49 dBm / 0.0889 W				
	802.11n HT20 : 19.48 dBm / 0.0887 W				
	802.11n HT40 : 18.74 dBm / 0.0748 W				
	802.11ac VHT20: 19.49 dBm / 0.0889 W				
	802.11ac VHT40: 18.83 dBm / 0.0764 W				
	802.11ac VHT80: 18.03 dBm / 0.0640 W				
	MIMO <ant. +="" 1="" 2=""></ant.>				
	802.11n HT20 : 19.41 dBm / 0.0873 W				
Maximum Output Power	802.11n HT40 : 18.91 dBm / 0.0778 W				
<txbf modes=""></txbf>	802.11ac VHT20: 19.51 dBm / 0.0893 W				
	802.11ac VHT40: 19.06 dBm / 0.0805 W				
	802.11ac VHT80: 17.56 dBm / 0.0570 W				
	802.11a : 24.10 MHz				
	802.11n HT20 : 23.85 MHz				
99% Occupied Bandwidth	802.11n HT40 : 39.70 MHz				
<cdd modes=""></cdd>	802.11ac VHT20 : 25.00 MHz				
	802.11ac VHT40 : 38.40 MHz				
	802.11ac VHT80 : 76.08. MHz				
	802.11n HT20 : 19.85 MHz				
00% Counied Bandwidth	802.11n HT40 : 37.10 MHz				
99% Occupied Bandwidth <txbf modes=""></txbf>	802.11ac VHT20 : 19.75 MHz				
<iadt wioges=""></iadt>	802.11ac VHT40 : 37.30 MHz				
	802.11ac VHT80 : 76.20 MHz				

Report No. : FR672014-01F

 SPORTON INTERNATIONAL INC.
 Page Number
 : 6 of 46

 TEL: 886-3-327-3456
 Report Issued Date
 : Sep. 19, 2016

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

FCC ID : UZ7TC510K Report Template No.: BU5-FR15EWLB4 AC MA Version 1.4

Standards-related Product Specification						
Antenna Type / Gain	9 dBi 6 dBi					
Type of Modulation	Modulation 802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64Q 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64Q)					
Antenna Function Description	802.11 a/n/ac 802.11 a/n/ac MIMO	Ant. 1 V V	Ant. 2 V			

Report No.: FR672014-01F

Note: MIMO Ant. 1+2 is a calculated result from sum of the power MIMO Ant. 1 and MIMO Ant. 2.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	SPORTON INTERNATIONAL INC.				
	No. 52, Hwa Ya 1 st Rd., Hwa Ya Techn	ology Park,				
Test Site Location	Kwei-Shan District, Tao Yuan City, Taiv	van, R.O.C.				
rest Site Location	TEL: +886-3-327-3456					
	FAX: +886-3-328-4978					
Took Cita No	Sporton	Site No.				
Test Site No.	TH05-HY	CO05-HY				

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.			
	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Guishan Dist,			
Took Site Leastion	Taoyuan City, Taiwan (R.O.C.)			
Test Site Location	TEL: +886-3-327-0868			
	FAX: +886-3-327-0855			
Took Site No	Sporton Site No.			
Test Site No.	03CH12-HY			

Note: The test site complies with ANSI C63.4 2014 requirement.

SPORTON INTERNATIONAL INC.

Page Number : 7 of 46 TEL: 886-3-327-3456 Report Issued Date: Sep. 19, 2016 FAX: 886-3-328-4978 Report Version : Rev. 01

FCC ID: UZ7TC510K Report Template No.: BU5-FR15EWLB4 AC MA Version 1.4

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

Report No.: FR672014-01F

- FCC Part 15 Subpart E
- FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r03
- FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- FCC KDB 644545 D03 Guidance for IEEE 802 11ac New Rules v01
- ANSI C63.10-2013

Remark:

- All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 8 of 46
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane for CDD Mode ANT 2, CDD Mode MIMO Ant. 1+2 and TXBF MIMO Ant. 1+2, Z plane for CDD Mode Ant. 1) were recorded in this report.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
	149	5745	157	5785
5725-5850 MHz	151*	5755	159*	5795
Band 4 (U-NII-3)	153	5765	161	5805
(3 . 111 0)	155#	5775	165	5825

Note:

- 1. The above Frequency and Channel in "*" were 802.11n HT40 and 802.11ac VHT40.
- 2. The above Frequency and Channel in "#" were 802.11ac VHT80.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 9 of 46
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01

Report No.: FR672014-01F

2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test in the following tables. Final Output Power equals to Measured Output Power adds the duty factor.

Report No.: FR672014-01F

<CDD Modes>

<Ant. 1>

	802.11a mode									
Power vs. Channel					P	ower vs.	Data Rate			
	Frequency	Data Rate (bps)				Dat	a Rate (bp	os)		
Channel	(MHz)	6M	Channel	9M	12M	18M	24M	36M	48M	54M
CH 149	5745 MHz	16.60								
CH 157	5785 MHz	<mark>16.69</mark>	CH 157	16.62	16.59	16.58	16.62	16.60	16.60	16.61
CH 165	5825 MHz	16.52								

	802.11n HT20 mode												
Power vs. Channel					Р	ower vs.	Data Rate						
	Frequency	MCS Index	01 1			N	ICS Index						
Channel	(MHz)	MCS0	Channel -	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7			
CH 149	5745 MHz	16.52	CH 157 16.50	CH 157									
CH 157	5785 MHz	<mark>16.53</mark>			16.50	16.49	16.48	16.51	16.48	16.42	16.46		
CH 165	5825 MHz	16.38											

			-	802.11n H	T40 mode								
	Power vs. 0	Channel			F	Power vs.	Data Rate						
	Frequency	MCS Index	01 1	MCS Index									
Channel	(MHz)	MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7			
CH 151	5755 MHz	15.56	CH 450	15 74	15 71	15 75	15 75	15 71	15.60	15.70			
CH 159	5795 MHz	<mark>15.78</mark>	CH 159 15.74	15.71	15.75	15.75	15.71	15.69	15.70				

				802.11ac	VHT20 n	node					
F	Power vs. Cl	nannel				Power	/s. Data F	Rate			
	Frequency	MCS Index	Channal				MCS II	ndex			
Channel	(MHz)	MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8
CH 149	5745 MHz	16.53									
CH 157	5785 MHz	<mark>16.54</mark>	CH 157	16.51	16.52	16.48	16.51	16.53	16.46	16.52	16.43
CH 165	5825 MHz	16.45									

SPORTON INTERNATIONAL INC.

Page Number TEL: 886-3-327-3456 Report Issued Date: Sep. 19, 2016 FAX: 886-3-328-4978 Report Version : Rev. 01 FCC ID: UZ7TC510K

Report Template No.: BU5-FR15EWLB4 AC MA Version 1.4

: 10 of 46

				802.11	lac VHT	40 mode)					
F	Power vs. Cl	nannel				Pov	wer vs. I	Data Rat	е			
	Frequency MCS Index		01				М	CS Inde	x			
Channel	(MHz)	MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
CH 151	5755 MHz	15.71	CH 450	15.00	20 45 70	15 70	45.00	45.70	15 77	15.70	15 70	15.50
CH 159	5795 MHz	<mark>15.87</mark>	CH 159	15.80	15.79	15.72	15.82	15.79	15.77	15.70	15.78	15.59

				802.11ac VHT80 mode												
P	Power vs. Channel Power vs. Data Rate															
	Frequency	MCS Index	MCS Index													
Channel	(MHz)	MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9				
CH 155	55775MHz	<mark>15.18</mark>	CH 155 15.16 15.09 15.08 15.13 15.11 15.10 15.06 15.12								15.15					

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 11 of 46
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01

Report No. : FR672014-01F

<Ant. 2>

				802.11a	mode					
	Power vs. (Channel			P	ower vs.	Data Rate			
	Frequency	Data Rate (bps)	Ob	Data Rate (bps)						
Channel	(MHz)	6M	Channel	9M	12M	18M	24M	36M	48M	54M
CH 149	5745 MHz	<mark>16.37</mark>								
CH 157	5785 MHz	16.26	CH 149	16.35	16.33	16.30	16.34	16.34	16.34	16.36
CH 165	5825 MHz	16.30								

			8	02.11n H	Γ20 mode					
	Power vs. 0	Channel			Р	ower vs.	Data Rate			
	Frequency	MCS Index	01 1	MCS Index						
Channel	(MHz)	MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 149	5745 MHz	<mark>16.37</mark>								
CH 157	5785 MHz	16.16	CH 149	16.32	16.29	16.22	16.29	16.30	16.28	16.24
CH 165	5825 MHz	16.34								

			(802.11n H	T40 mode	•				
	Power vs. C	Channel			F	Power vs.	Data Rate)		
	annel Frequency MCS Index		Channal			N	ICS Index	(
Channel	(MHz)	MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 151	5755 MHz	<mark>15.54</mark>	CH 151	1E EO	15.47	15 10	15 16	15 51	1E E1	15 50
CH 159	5795 MHz	15.51	CH 151	1 15.50	15.47	15.49	15.46	15.51	15.51	15.52

				802.11ac	VHT20 r	node						
F	Power vs. Cl	nannel				Power	/s. Data F	Rate				
					MCS Index							
Channel	(MHz)	MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	
CH 149	5745 MHz	<mark>16.38</mark>										
CH 157	5785 MHz	16.13	CH 149	16.34	16.30	16.25	16.35	16.21	16.26	16.17	16.29	
CH 165	5825 MHz	16.36										

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 12 of 46
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01

Report No. : FR672014-01F

				802.11	lac VHT	40 mode)					
F	Power vs. Cl	nannel				Po	wer vs. I	Data Rat	е			
	Frequency	MCS Index	01				М	CS Inde	x			
Channel	(MHz)	MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
CH 151	5755 MHz	<mark>15.60</mark>	CH 151	H 151 15.59	9 15.54	15.52	15.56	3 15.55	15.50	15.51	15.42	15.50
CH 159	5795 MHz	15.48	CH 131	15.59		10.52	10.56	10.55	15.50	10.51	10.42	13.50

				802.1	1ac VHT	802.11ac VHT80 mode												
P	Power vs. Channel Power vs. Data Rate																	
	Frequency	MCS Index	01 1	MCS Index														
Channel	(MHz)	MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9						
CH 155	55775MHz	<mark>14.89</mark>	CH 155 14.88 14.84 14.76 14.76 14.81 14.83 14.87 14.83								14.82							

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 13 of 46
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01

Report No. : FR672014-01F

MIMO <Ant. 1+2>

				802.11a	mode					
	Power vs. (Channel			Р	ower vs.	Data Rate			
01	Frequency	Data Rate (bps)	Ob	Data Rate (bps)						
Channel	(MHz)	6M	Channel	9M	12M	18M	24M	36M	48M	54M
CH 149	5745 MHz	19.46	CH 165							
CH 157	5785 MHz	19.41		19.48	19.48	19.48	19.42	19.46	19.49	19.47
CH 165	5825 MHz	<mark>19.49</mark>								

			8	302.11n H	Γ20 mode					
	Power vs. 0	Channel			Р	ower vs.	Data Rate			
	Frequency	MCS Index	01 1	MCS Index						
Channel	(MHz)	MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 149	5745 MHz	<mark>19.48</mark>								
CH 157	5785 MHz	19.41	CH 149	19.48	19.47	19.47	19.48	19.47	19.46	19.47
CH 165	5825 MHz	19.47								

			8	302.11n H	T40 mode	•								
	Power vs. 0	Channel	Power vs. Data Rate											
	Frequency	MCS Index	Channal		MCS Index									
Channel	(MHz)	MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7				
CH 151	5755 MHz	18.67	CH 159	10.71	10.60	10.60	10.70	10.70	10.70	10.70				
CH 159	5795 MHz	<mark>18.74</mark>	CH 159	18.71	18.68	18.69	18.72	18.70	18.72	18.72				

				802.11ac	: VHT20 r	node						
F	Power vs. Cl	nannel	Power vs. Data Rate									
	Frequency	MCS Index					MCS I	ndex				
Channel	(MHz)	MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	
CH 149	5745 MHz	<mark>19.49</mark>										
CH 157	5785 MHz	19.46	CH 149	19.48	19.48	19.47	19.47	19.47	19.48	19.48	19.48	
CH 165	5825 MHz	19.48										

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 14 of 46
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01
Report Template No.: BU5-FR15EWLB4 AC MA Version 1.4

Report No. : FR672014-01F

	802.11ac VHT40 mode													
F	Power vs. Cl	nannel		Power vs. Data Rate										
	Frequency	MCS Index	01		MCS Index									
Channel	(MHz)	MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9		
CH 151	5755 MHz	<mark>18.83</mark>	CU 151	10.00	10.01	10.70	10.01	10.70	10.76	10.77	10.01	10.70		
CH 159	5795 MHz	18.76	CH 151	18.80	18.81	18.79	18.81	31 18.79	18.76	18.77	18.81	18.79		

	802.11ac VHT80 mode												
P	ower vs. Ch	nannel		Power vs. Data Rate									
	Frequency				MCS Index								
Channel	(MHz)	MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	
CH 155	55775MHz	<mark>18.03</mark>	CH 155 18.00 17.95 17.82 17.87 17.82 17.80 17.81 17.96 18.02										

Note: MIMO Ant. 1+2 is a calculated result from sum of the power MIMO Ant. 1 and MIMO Ant. 2.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 15 of 46
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01

Report No. : FR672014-01F

<TXBF Modes>

MIMO <Ant. 1+2>

	802.11n HT20 mode												
	Power vs. 0	Channel	Power vs. Data Rate										
	Frequency	MCS Index		MCS Index									
Channel	(MHz)	MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7			
CH 149	5745 MHz	19.36											
CH 157	5785 MHz	19.27	CH 165	19.37	19.36	19.36	19.32	19.37	19.36	19.31			
CH 165	5825 MHz	<mark>19.41</mark>											

			-	802.11n H	T40 mode								
	Power vs. C	Channel	Power vs. Data Rate										
	Frequency	MCS Index	01 1	MCS Index									
Channel	(MHz)	MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7			
CH 151	5755 MHz	18.66	CH 450	10.06	10.06	10.01	10.01	10.76	10.01	10.06			
CH 159	5795 MHz	<mark>18.91</mark>	CH 159	18.86	18.86	18.81	18.81	18.76	18.81	18.86			

				802.11ac	VHT20 r	node						
F	Power vs. Cl	nannel	Power vs. Data Rate									
	Frequency	MCS Index					MCS I	ndex				
Channel	(MHz)	MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	
CH 149	5745 MHz	19.46										
CH 157	5785 MHz	19.41	CH 165	19.47	19.41	19.37	19.37	19.36	19.32	19.36	19.41	
CH 165	5825 MHz	<mark>19.51</mark>										

	802.11ac VHT40 mode													
F	ower vs. Cl	nannel		Power vs. Data Rate										
	Frequency	MCS Index			MCS Index									
Channel	(MHz)	MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9		
CH 151	5755 MHz	18.81	CH 450	10.01	10.06	10.06	10.06	10.07	10.01	10.06	10.06	10.01		
CH 159	5795 MHz	<mark>19.06</mark>	CH 159	19.01	.01 18.96	18.96	18.96	18.97	18.91	18.96	18.86	18.81		

	802.11ac VHT80 mode												
P	ower vs. Ch	nannel		Power vs. Data Rate									
	Frequency				MCS Index								
Channel	(MHz)	MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	
CH 155	55775MHz	<mark>17.56</mark>	CH 155 17.51 17.46 17.46 17.41 17.41 17.46 17.51 17.46 17.41										

Note: MIMO Ant. 1+2 is a calculated result from sum of the power MIMO Ant. 1 and MIMO Ant. 2.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Rep Page Number : 16 of 46
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01

Report No. : FR672014-01F

2.3 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates from the power table described in section 2.2.

Report No. : FR672014-01F

Single Antenna

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0

MIMO Antenna

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0

	Test Cases
AC	Mode 1: WLAN (5GHz) Link + Bluetooth Link + Battery + Scanner + without
	Exoskeleton + Headset Jumper (CBL-TC51-HDST25-01) + Earphone
Conducted	(HDST-25MM-PTVP-01) + Rugged Charge/USB Cable + Adapter 1
Emission	(SAWA-65-20005A (5V/2.5A))

Ch. #		Band IV:5725-5850 MHz			
	Cn. #	802.11a	802.11n HT20	802.11n HT40	
L	Low	149	149	151	
М	Middle	157	157	-	
Н	High	165	165	159	


	Ch #	Band IV:5725-5850 MHz			
Ch. #		802.11ac VHT20	802.11ac VHT40	802.11ac VHT80	
L	Low	149	151	-	
M	Middle	157	-	155	
Н	High	165	159	-	

SPORTON INTERNATIONAL INC.


Page Number : 17 of 46 TEL: 886-3-327-3456 Report Issued Date: Sep. 19, 2016 FAX: 886-3-328-4978 Report Version : Rev. 01 FCC ID: UZ7TC510K Report Template No.: BU5-FR15EWLB4 AC MA Version 1.4

2.4 Connection Diagram of Test System

<WLAN Tx CDD Mode>



<WLAN Tx TXBF Mode>




SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 18 of 46
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01

Report No.: FR672014-01F

<AC Conducted Emission Mode>



TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 19 of 46
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01

Report No. : FR672014-01F

2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
3.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Notebook	Lenovo	M490S(E330)	QDS-BRCM1063	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A
6.	Touch computer	Zebra	TC510K	UZ7TC510K	N/A	N/A

Report No.: FR672014-01F

2.6 EUT Operation Test Setup

For WLAN CDD modes, programmed RF utility, "CMD" installed in the notebook make the EUT provide functions like channel selection and power level for continuous transmitting and receiving signals.

For WLAN MIMO TXBF modes, the EUT was tested under normal operation and link to another device with power, modulation modes and data rates controlled by engineer mode command lines. The "CMD" software tool was used to make EUT continuous transmitting signals.

2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

 $Offset(dB) = RF \ cable \ loss(dB) + attenuator \ factor(dB).$ = 4.2 + 10 = 14.2 (dB)

SPORTON INTERNATIONAL INC.

: 20 of 46 Page Number TEL: 886-3-327-3456 Report Issued Date: Sep. 19, 2016 FAX: 886-3-328-4978 Report Version : Rev. 01

FCC ID: UZ7TC510K Report Template No.: BU5-FR15EWLB4 AC MA Version 1.4

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz. 26dB and 99% Occupied bandwidth are reporting only.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

- The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r03.
 Section C) Emission bandwidth for the band 5.725-5.85GHz
- 2. Set RBW = 100kHz.
- 3. Set the VBW \geq 3 x RBW.
- 4. Detector = Peak.
- 5. Trace mode = max hold
- 6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
- 7. Measure and record the results in the test report.

3.1.4 Test Setup



SPORTON INTERNATIONAL INC. TEL: 886-3-327-3456


FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 21 of 46
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01


Report No.: FR672014-01F

3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.


<CDD Modes>





TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 22 of 46
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01

Report No.: FR672014-01F



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.


TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 23 of 46
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01


Report No. : FR672014-01F




Report No. : FR672014-01F

<TXBF Modes>





TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 24 of 46
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 25 of 46
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01

Report No. : FR672014-01F

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

CDD modes

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r03.

Method PM (Measurement using an RF average power meter):

- 1. Measurement is performed using a wideband RF power meter.
- The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
- 3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.

TXBF modes

The testing follows Method PM-G of FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r03 for TXBF modes.

Method PM-G (Measurement using a gated RF average power meter):


- 1. Measurement is performed using a wideband RF power meter.
- 2. The EUT is configured to transmit at its maximum power control level.
- 3. Measure the average power of the transmitter
- 4. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

Page Number : 26 of 46
Report Issued Date : Sep. 19, 2016

Report No.: FR672014-01F

Report Version : Rev. 01

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 27 of 46
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01

Report No. : FR672014-01F

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

Report No.: FR672014-01F

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r03. Section F) Maximum power spectral density.

CDD modes

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 300 kHz.
- Set VBW ≥ 1 MHz.
- Number of points in sweep ≥ 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add 10 log(500kHz/RBW) to the test result.
- Add 10 log(1/x), where x is the duty cycle, to the measured power in order to compute the
 average power during the actual transmission times. For example, add 10 log(1/0.25) = 6
 dB if the duty cycle is 25 percent.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 28 of 46
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01

TXBF modes

Method SA-3

(power averaging (rms) detection with max hold):

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 300 kHz.
- Set VBW ≥ 1 MHz.
- Number of points in sweep ≥ 2 Span / RBW.
- Sweep time ≤ (number of points in sweep) × T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Report No.: FR672014-01F

: 29 of 46


Page Number

- Detector = power averaging (rms).
- Trace mode = max hold.
- Allow max hold to run for at least 60 seconds, or longer as needed to allow the trace to stabilize.
- 1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
- 2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.
- For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter 3. Output v02r01.

Method (c): Measure and add 10 log(N_{ANT}) dB.

With this technique, spectrum measurements are performed at each output of the device, but rather than summing the spectra or the spectral peaks across the outputs, the quantity 10 log(N_{ANT}) dB is added to each spectrum value before comparing to the emission limit. The addition of 10 log(N_{ANT}) dB serves to apportion the emission limit among the N_{ANT} outputs so that each output is permitted to contribute no more than 1/N_{ANT} th of the PSD limit.

3.3.4 Test Setup



SPORTON INTERNATIONAL INC.


TEL: 886-3-327-3456 Report Issued Date: Sep. 19, 2016 FAX: 886-3-328-4978 Report Version : Rev. 01


FCC ID: UZ7TC510K Report Template No.: BU5-FR15EWLB4 AC MA Version 1.4

3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

<CDD Modes>







TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 30 of 46
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01

Report No.: FR672014-01F

FCC RF Test Report

<TXBF Modes>





TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 31 of 46
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01

Report No.: FR672014-01F

3.4 Unwanted Emissions Measurement

This section as specified in FCC Part 15.407(b) is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement. The unwanted emissions shall comply with 15.407(b)(1) to (6), and restricted bands per FCC Part15.205.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5.725-5.85 GHz band: 15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
- (2) Unwanted spurious emissions fallen in restricted bands per FCC Part15.205 shall comply with the general field strength limits set forth in § 15.209 as below table,

Frequency	Field Strength	Measurement Distance	
(MHz)	(microvolts/meter)	(meters)	
0.009 - 0.490	2400/F(kHz)	300	
0.490 – 1.705	24000/F(kHz)	30	
1.705 – 30.0	30	30	
30 – 88	100	3	
88 – 216	150	3	
216 - 960	200	3	
Above 960	500	3	

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3}$$
 µV/m, where P is the eirp (Watts)

EIRP (dBm)	Field Strength at 3m (dBμV/m)
-17	78.3
- 27	68.3

(3) KDB 789033 D02 General UNII Test Procedures New Rules v01r03 G)2)c) As specified in 15.407(b), emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz (or -17 dBm/MHz as specified in 15.407(b)(4)). However, an out-of-band emission that complies with both the average and peak limits of 15.209 is not required to satisfy the -27 dBm/MHz or -17 dBm/MHz peak emission limit.

SPORTON INTERNATIONAL INC.
TEL: 886-3-327-3456

FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 32 of 46
Report Issued Date : Sep. 19, 2016

Report No.: FR672014-01F

Report Version : Rev. 01

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r03. Section G) Unwanted emissions measurement.

Report No.: FR672014-01F

- (1) Procedure for Unwanted Emissions Measurements Below 1000MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold
- (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW ≥ 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold
- (3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW \geq 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
- The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
- The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
- 5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
- For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.

SPORTON INTERNATIONAL INC.


Page Number : 33 of 46 TEL: 886-3-327-3456 Report Issued Date: Sep. 19, 2016 FAX: 886-3-328-4978 Report Version : Rev. 01

FCC ID: UZ7TC510K Report Template No.: BU5-FR15EWLB4 AC MA Version 1.4


For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K


: 34 of 46 Page Number Report Issued Date: Sep. 19, 2016 Report Version : Rev. 01

Report No.: FR672014-01F


rt Report No. : FR672014-01F

For radiated emissions above 1GHz

CDD modes



TXBF mode



TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 35 of 46
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01

3.4.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

Report No.: FR672014-01F

: 36 of 46

3.4.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B and C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix B and C.

SPORTON INTERNATIONAL INC.
Page Number
TEL: 886-3:327-3456
Page Number

 TEL: 886-3-327-3456
 Report Issued Date : Sep. 19, 2016

 FAX: 886-3-328-4978
 Report Version : Rev. 01

 FCC ID: UZ7TC510K
 Report Template No.: BU5-FR15EWLB4 AC MA Version 1.4

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)				
Frequency of emission (MHZ)	Quasi-peak	Average			
0.15-0.5	66 to 56*	56 to 46*			
0.5-5	56	46			
5-30	60	50			

^{*}Decreases with the logarithm of the frequency.

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- 2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- 3. All the support units are connecting to the other LISN.
- 4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- 5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- 6. Both sides of AC line were checked for maximum conducted interference.
- 7. The frequency range from 150 kHz to 30 MHz was searched.
- 8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.


SPORTON INTERNATIONAL INC.
TEL: 886-3-327-3456

FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 37 of 46
Report Issued Date : Sep. 19, 2016

Report No.: FR672014-01F

Report Version : Rev. 01

3.5.4 Test Setup



AMN = Artificial mains network (LISN)

AE = Associated equipment

EUT = Equipment under test

ISN = Impedance stabilization network

SPORTON INTERNATIONAL INC.


TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 38 of 46
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01

Report No.: FR672014-01F

3.5.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	24~25℃		
Test Engineer :	Kai-Chun Chu	Relative Humidity :	45~46%		
Test Voltage :	120Vac / 60Hz	Phase: Line			
	WLAN (5GHz) Link + Bluetooth Link + Battery + Scanner + without Exoskeleton +				

Function Type: Headset Jumper (CBL-TC51-HDST25-01) + Earphone (HDST-25MM-PTVP-01) + Rugged Charge/USB Cable + Adapter 1 (SAWA-65-20005A (5V/2.5A))



Final Result: QuasiPeak

Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	47.4	Off	L1	19.6	18.2	65.6
0.198000	45.6	Off	L1	19.6	18.1	63.7
0.286000	40.1	Off	L1	19.6	20.5	60.6
0.366000	45.6	Off	L1	19.6	13.0	58.6
0.638000	34.4	Off	L1	19.6	21.6	56.0
1.222000	32.3	Off	L1	19.7	23.7	56.0
3.774000	30.4	Off	L1	19.8	25.6	56.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	35.6	Off	L1	19.6	20.0	55.6
0.198000	33.7	Off	L1	19.6	20.0	53.7
0.286000	33.6	Off	L1	19.6	17.0	50.6
0.366000	37.2	Off	L1	19.6	11.4	48.6
0.638000	27.4	Off	L1	19.6	18.6	46.0
1.222000	25.4	Off	L1	19.7	20.6	46.0
3.774000	21.9	Off	L1	19.8	24.1	46.0

SPORTON INTERNATIONAL INC.


TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 39 of 46
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01

Report No.: FR672014-01F

SPORTON LAB.	FCC RF Test F

Test Mode :	Mode 1	Temperature :	24~25℃				
Test Engineer :	Kai-Chun Chu	Relative Humidity :	45~46%				
Test Voltage :	120Vac / 60Hz	Phase :	Neutral				
	WLAN (5GHz) Link + Bluetooth Link + Battery + Scanner + without Exoskeleton +						
F	LILLE TO THE TOP	Level 1 and 1 (OD). TOTAL IDOTOS OA) a Familiary (UDOT OSMMA DT) (D.O.A) a					

Function Type: | Headset Jumper (CBL-TC51-HDST25-01) + Earphone (HDST-25MM-PTVP-01) + Rugged Charge/USB Cable + Adapter 1 (SAWA-65-20005A (5V/2.5A))



Final Result: QuasiPeak

Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.166000	45.6	Off	N	19.6	19.6	65.2
0.206000	43.0	Off	N	19.6	20.4	63.4
0.238000	43.7	Off	N	19.6	18.5	62.2
0.318000	39.9	Off	N	19.6	19.9	59.8
0.374000	38.0	Off	N	19.6	20.4	58.4
0.814000	35.6	Off	N	19.6	20.4	56.0
1.462000	33.0	Off	N	19.6	23.0	56.0
3.342000	27.2	Off	N	19.7	28.8	56.0

Final Result : Average

mai Kesuit . Average							
Frequency (MHz)	Average (dBµV)	Filter	Line	Corr.	Margin (dB)	Limit (dBµV)	
(IVITZ)	(ασμν)			(ub)	(ub)	(ασμν)	
0.166000	34.0	Off	N	19.6	21.2	55.2	
0.206000	32.7	Off	N	19.6	20.7	53.4	
0.238000	31.6	Off	N	19.6	20.6	52.2	
0.318000	32.5	Off	N	19.6	17.3	49.8	
0.374000	31.0	Off	N	19.6	17.4	48.4	
0.814000	27.9	Off	N	19.6	18.1	46.0	
1.462000	25.7	Off	N	19.6	20.3	46.0	
3.342000	20.3	Off	N	19.7	25.7	46.0	

: 40 of 46 Page Number Report Issued Date: Sep. 19, 2016 Report Version : Rev. 01

Report No.: FR672014-01F

3.6 Frequency Stability Measurement

3.6.1 Limit of Frequency Stability

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

- To ensure emission at the band edge is maintained within the authorized band, those values shall
 be measured by radiation emissions at upper and lower frequency points, and finally
 compensated by frequency deviation as procedures below.
- 2. The EUT was operated at the maximum output power, and connected to the spectrum analyzer, which is set to maximum hold function and peak detector. The peak value of the power envelope was measured and noted. The upper and lower frequency points were respectively measured relatively 10dB lower than the measured peak value.
- The frequency deviation was calculated by adding the upper frequency point and the lower frequency point divided by two. Those detailed values of frequency deviation are provided in table below.

3.6.4 Test Setup



3.6.5 Test Result of Frequency Stability

Please refer to Appendix A.

Page Number : 41 of 46
Report Issued Date : Sep. 19, 2016

Report No.: FR672014-01F

Report Version : Rev. 01

3.7 Automatically Discontinue Transmission

Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

Report No.: FR672014-01F

3.7.2 **Measuring Instruments**

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Result of Automatically Discontinue Transmission

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K

Page Number Report Issued Date: Sep. 19, 2016 Report Version : Rev. 01

: 42 of 46

3.8 Antenna Requirements

3.8.1 Standard Applicable

According to FCC 47 CFR Section 15.407(a)(1)(2) ,if transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Report No.: FR672014-01F

3.8.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.8.3 Antenna Gain

CDD Modes

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = $10 \log(N_{ANT}/N_{SS}=1) dB$.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \le 4$.

Directional gain may be calculated by using the formulas applicable to equal gain antennas with GANT set equal to the gain of the antenna having the highest gain;

The EUT supports CDD mode.

For power, the directional gain G_{ANT} is set equal to the antenna having the highest gain, i.e., F)2)f)i).

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

			DG	DG	Power	PSD
			for	for	Limit	Limit
	Ant 1	Ant 2	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
Band IV	1.59	2.86	2.86	5.26	0.00	0.00

Power limit reduction = Composite gain - 6dBi, (min = 0)

PSD limit reduction = Composite gain + PSD Array gain - 6dBi, (min = 0)

 SPORTON INTERNATIONAL INC.
 Page Number
 : 43 of 46

 TEL: 886-3-327-3456
 Report Issued Date
 : Sep. 19, 2016

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

FCC ID : UZ7TC510K Report Template No.: BU5-FR15EWLB4 AC MA Version 1.4

TXBF modes

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

$$Directional Gain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^{2}}{N_{ANT}} \right]$$

Report No.: FR672014-01F

where

Each antenna is driven by no more than one spatial stream;

 N_{SS} = the number of independent spatial streams of data;

 N_{ANT} = the total number of antennas

 $g_{j,k} = 10^{G_k/20}$ if the kth antenna is being fed by spatial stream j, or zero if it is not; G_k is the gain in dBi of the kth antenna.

The EUT supports beamforming for 802.11ac modes.

The directional gain calculation is following F)2)e)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

			DG	DG	Power	PSD
			for	for	Limit	Limit
	Ant 1	Ant 2	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
Band IV	1.59	2.86	5.26	5.26	0.00	0.00

Power Limit Reduction = DG(Power) - 6dBi, (min = 0)

PSD Limit Reduction = DG(PSD) - 6dBi, (min = 0)

 SPORTON INTERNATIONAL INC.
 Page Number
 : 44 of 46

 TEL: 886-3-327-3456
 Report Issued Date
 : Sep. 19, 2016

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

FCC ID : UZ7TC510K Report Template No.: BU5-FR15EWLB4 AC MA Version 1.4

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Anritsu	ML2495A	1132003	300MHz~40GHz	Aug. 12, 2015	Jun. 18, 2016 ~ Jul. 31, 2016	Aug. 11, 2016	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	1126017	300MHz~40GHz	Aug. 12, 2015	Jun. 18, 2016 ~ Jul. 31, 2016	Aug. 11, 2016	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 23, 2015	Jun. 18, 2016 ~ Jul. 31, 2016	Nov. 22, 2016	Conducted (TH05-HY)
Temperature Chamber	ESPEC	SU-241	92003713	-30℃ ~95℃	Jun. 06, 2016	Jun. 18, 2016 ~ Jul. 31, 2016	Jun. 05, 2017	Conducted (TH05-HY)
Power Sensor	DARE	RadiPower	15I00041SN O09	10MHz~6GHz	May 03, 2016	Jun. 18, 2016 ~ Jul. 31, 2016	May 02, 2017	Conducted (TH05-HY)
Power Sensor	DARE	RadiPower	15I00041SN O10	10MHz~6GHz	May 03, 2016	Jun. 18, 2016 ~ Jul. 31, 2016	May 02, 2017	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Aug. 26, 2016	N/A	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 02, 2015	Aug. 26, 2016	Dec. 01, 2016	Conduction (CO05-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY54130085	20Hz ~ 8.4GHz	Nov. 04, 2015	Aug. 26, 2016	Nov. 03, 2016	Conduction (CO05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Sep. 02, 2015	Jul. 02, 2016 ~ Jul. 28, 2016	Sep. 01, 2016	Radiation (03CH12-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200486	10Hz ~ 44GHZ	Sep. 24, 2015	Jul. 02, 2016 ~ Jul. 28, 2016	Sep. 23, 2016	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D	37059	30MHz~1GHz	Dec. 29, 2015	Jul. 02, 2016 ~ Jul. 28, 2016	Dec. 28, 2016	Radiation (03CH12-HY)
EMI Test Receiver	Rohde & Schwarz	ESU26	100390	20Hz~26.5GHz	Dec. 21, 2015	Jul. 02, 2016 ~ Jul. 28, 2016	Dec. 20, 2016	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120D	9120D-1328	1GHz ~ 18GHz	Nov. 02, 2015	Jul. 02, 2016 ~ Jul. 28, 2016	Nov. 01, 2016	Radiation (03CH12-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1815698	1GHz~18GHz	Dec. 14, 2015	Jul. 02, 2016 ~ Jul. 28, 2016	Dec. 13, 2016	Radiation (03CH12-HY)
Preamplifier	Keysight	83017A	MY53270148	1GHz~26.5GHz	Jan. 30, 2016	Jul. 02, 2016 ~ Jul. 28, 2016	Jan. 29, 2017	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Jul. 02, 2016 ~ Jul. 28, 2016	N/A	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Jul. 02, 2016 ~ Jul. 28, 2016	N/A	Radiation (03CH12-HY)
Preamplifier	MITEQ	JS44-1800400 0-33-8P	1840917	18GHz ~ 40GHz	Jun. 14, 2016	Jul. 02, 2016 ~ Jul. 28, 2016	Jun. 13, 2017	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA917058 4	18GHz- 40GHz	Nov. 02, 2015	Jul. 02, 2016 ~ Jul. 28, 2016	Nov. 01, 2016	Radiation

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : 45 of 46
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01

Report No. : FR672014-01F

Uncertainty of Evaluation 5

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence	2.70
of 95% (U = 2Uc(y))	2.70

Report No.: FR672014-01F

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence	5.10
of 95% (U = 2Uc(y))	

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence	5.20
of 95% (U = 2Uc(y))	5.20

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

_		<u>-</u>
	Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.70

SPORTON INTERNATIONAL INC. Page Number TEL: 886-3-327-3456

Report Issued Date: Sep. 19, 2016 FAX: 886-3-328-4978 Report Version : Rev. 01 FCC ID: UZ7TC510K

Report Template No.: BU5-FR15EWLB4 AC MA Version 1.4

: 46 of 46

Appendix A. Conducted Test Results

<CDD Modes>

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : A1-1 of 1
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01

Report No. : FR672014-01F

<TXBF Modes>

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7TC510K Page Number : A2-1 of 1
Report Issued Date : Sep. 19, 2016
Report Version : Rev. 01

Report Template No.: BU5-FR15EWLB4 AC MA Version 1.4

Report No. : FR672014-01F