



FCC RF Test Report

APPLICANT : Zebra Technologies Corporation
EQUIPMENT : Touch computer
BRAND NAME : Zebra
MODEL NAME : TC75EK
FCC ID : UZ7TC75EK
STANDARD : FCC Part 15 Subpart E §15.407
CLASSIFICATION : (NII) Unlicensed National Information Infrastructure

The product was received on Jul. 28, 2016 and testing was completed on Sep. 09, 20. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL : 886-3-327-3456

FAX : 886-3-328-4978

FCC ID : UZ7TC75EK

Page Number : 1 of 61

Report Issued Date : Oct. 07, 2016

Report Version : Rev. 03

Report Template No.: BU5-FR15EWLB4 AC MA Version 1.4



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	7
1.6 Testing Location	7
1.7 Applicable Standards.....	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1 Carrier Frequency and Channel	9
2.2 Pre-Scanned RF Power.....	10
2.3 Test Mode.....	18
2.4 Connection Diagram of Test System.....	19
2.5 Support Unit used in test configuration and system	20
2.6 EUT Operation Test Setup	21
2.7 Measurement Results Explanation Example.....	21
3 TEST RESULT	22
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement	22
3.2 Maximum Conducted Output Power Measurement	27
3.3 Power Spectral Density Measurement	29
3.4 Unwanted Emissions Measurement	33
3.5 AC Conducted Emission Measurement.....	38
3.6 Frequency Stability Measurement.....	55
3.7 Automatically Discontinue Transmission	56
3.8 Antenna Requirements.....	57
4 LIST OF MEASURING EQUIPMENT	59
5 UNCERTAINTY OF EVALUATION	61
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. RADIATED SPURIOUS EMISSION	
APPENDIX C. RADIATED SPURIOUS EMISSION PLOTS	
APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX E. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR672834F	Rev. 01	Initial issue of report	Sep. 29, 2016
FR672834E	Rev. 02	Detail changes list as below : 1. Adding the applied standard in the section 1.7 and the specification of accessories 2. Updating average power in appendix A	Oct. 05, 2016
FR672834E	Rev. 03	Revising the Adapter information in specification of accessories.	Oct. 07, 2016

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.403(i)	6dB, 26dB and 99% Occupied Bandwidth	> 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b)(4)(i) & 15.209(a)	Pass	Under limit 4.67 dB at 149.340 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 3.20 dB at 0.758 MHz
3.6	15.407(g)	Frequency Stability	Within Operation Band	Pass	-
3.7	15.407(c)	Automatically Discontinue Transmission	Discontinue Transmission	Pass	-
3.8	15.203 & 15.407(a)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

Zebra Technologies Corporation
1 Zebra Plaza Holtsville, NY 11742

1.2 Manufacturer

Wistron Corporation
21F, No. 88, Sec. 1, Hsin Tai Wu Rd., Hsichih Dist, New Taipei City 221, Taiwan R.O.C.

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Touch computer
Brand Name	Zebra
Model Name	TC75EK
FCC ID	UZ7TC75EK
EUT supports Radios application	CDMA/EV-DO/GSM/EGPRS/WCDMA/HSPA/LTE/NFC WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
HW Version	DV
SW Version	Android version 6.0.1
FW Version	91-10-01-MG-00
MFD	14JUL16
EUT Stage	Engineering sample

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Specification of Accessories				
AC Adapter	Brand Name	Zebra	Part Number	PWR-BUA5V16W0WW
Snap-On USB/Charge Cable	Brand Name	Symbol	Part Number	CBL-TC7X-USB1-01
Snap-On Charging Cable Cup	Brand Name	Symbol	Part Number	CHG-TC7X-CBL1-01
Battery	Brand Name	Zebra	Part Number	BT-000318-01
Earphone 1	Brand Name	Zebra	Part Number	HDST-35MM-PTVP-01
Earphone 2	Brand Name	Zebra	Part Number	HS2100-OTH
Earphone 3	Brand Name	Zebra	Part Number	HS3100-OTH
Snap-on 3.5MM Audio Nugget	Brand Name	Symbol	Part Number	ADP-TC7X-AUD35-01
3.5mm Jack 43"(1.1m) Standard Cable	Brand Name	Zebra	Part Number	CBL-HS2100-3MS1-01
Soft Holster	Brand Name	Zebra	Part Number	SG-TC7X-HLSTR1-01
Rigid Holster	Brand Name	Zebra	Part Number	SG-TC7X-RHLSTR1-01
Power Cord	Brand Name	LOROM	Part Number	50-16000-182R
Cable line	Brand Name	Zebra	Part Number	CBL-DC-383A1-01

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification												
Tx/Rx Channel Frequency Range		5745 MHz ~ 5825 MHz										
Maximum Output Power <CDD Modes>		<5745 MHz ~ 5825 MHz> <Ant. 1> 802.11a : 15.93 dBm / 0.0392 W 802.11n HT20 : 15.90 dBm / 0.0389 W 802.11n HT40 : 15.30 dBm / 0.0339 W 802.11ac VHT20: 15.93 dBm / 0.0392 W 802.11ac VHT40: 15.37 dBm / 0.0344 W 802.11ac VHT80: 14.35 dBm / 0.0272 W <Ant. 2> 802.11a : 17.60 dBm / 0.0575 W 802.11n HT20 : 17.64 dBm / 0.0581 W 802.11n HT40 : 17.05 dBm / 0.0507 W 802.11ac VHT20: 17.68 dBm / 0.0586 W 802.11ac VHT40: 17.07 dBm / 0.0509 W 802.11ac VHT80: 16.10 dBm / 0.0407 W MIMO <Ant. 1 + 2> 802.11a : 19.95 dBm / 0.0989 W 802.11n HT20 : 19.88 dBm / 0.0973 W 802.11n HT40 : 19.39 dBm / 0.0869 W 802.11ac VHT20: 19.90 dBm / 0.0977 W 802.11ac VHT40: 19.45 dBm / 0.0881 W 802.11ac VHT80: 18.37 dBm / 0.0687 W										
Maximum Output Power <TXBF Modes>		<5745 MHz ~ 5825 MHz> MIMO <Ant. 1 + 2> 802.11n HT20 : 19.59 dBm / 0.0910 W 802.11n HT40 : 19.04 dBm / 0.0802 W 802.11ac VHT20: 19.75 dBm / 0.0944 W 802.11ac VHT40: 19.19 dBm / 0.0830 W 802.11ac VHT80: 17.85 dBm / 0.0610 W										
99% Occupied Bandwidth <CDD Modes>		802.11a : 20.85 MHz 802.11ac VHT20 : 20.30 MHz 802.11ac VHT40 : 38.80 MHz 802.11ac VHT80 : 76.08 MHz										
99% Occupied Bandwidth <TXBF Modes>		802.11ac VHT20 : 19.40 MHz 802.11ac VHT40 : 37.00 MHz 802.11ac VHT80 : 75.84 MHz										
Type of Modulation		802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)										
Antenna Type / Gain		<Ant. 1> : IFA Antenna with gain 3.90 dBi <Ant. 2> : IFA Antenna with gain 3.80 dBi										
Antenna Function Description		<table><tr><td></td><td>Ant. 1</td><td>Ant. 2</td></tr><tr><td>802.11 a/n/ac</td><td>V</td><td>V</td></tr><tr><td>802.11 a/n/ac MIMO</td><td>V</td><td>V</td></tr></table>			Ant. 1	Ant. 2	802.11 a/n/ac	V	V	802.11 a/n/ac MIMO	V	V
	Ant. 1	Ant. 2										
802.11 a/n/ac	V	V										
802.11 a/n/ac MIMO	V	V										

Note: MIMO Ant. 1+2 is a calculated result from sum of the power MIMO Ant. 1 and MIMO Ant. 2.



1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Guishan Dist, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	03CH12-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.



1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r03
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ FCC KDB 644545 D03 Guidance for IEEE 802.11ac New Rules v01
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst position for each mode was recorded in the appendix of this test report.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155 [#]	5775	165	5825

Note:

1. The above Frequency and Channel in "*" were 802.11n HT40 and 802.11ac VHT40.
2. The above Frequency and Channel in "[#]" were 802.11ac VHT80.



2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test in the following tables. Final Output Power equals to Measured Output Power adds the duty factor.

<Ant. 1>

<CDD Modes>

WLAN 802.11a RF Average Output Power (dBm)										
Power vs. Channel			Power vs. Data Rate							
Channel	Frequency (MHz)	Data Rate (bps)	Channel	Data Rate (bps)						
		6M		9M	12M	18M	24M	36M	48M	54M
Duty Cycle (%)		92.86		89.72	86.75	81.67	78.48	71.11	64.87	63.57
CH 149	5745 MHz	15.84		CH 157	15.85	15.82	15.90	15.78	15.90	15.88
CH 157	5785 MHz	15.93								
CH 165	5825 MHz	15.88								

WLAN 802.11n HT20 RF Average Output Power (dBm)										
Power vs. Channel			Power vs. Data Rate							
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index						
		MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Duty Cycle (%)		92.86		87.34	81.94	78.21	70.79	66.22	63.83	61.94
CH 149	5745 MHz	15.82		CH 157	15.83	15.76	15.81	15.86	15.84	15.79
CH 157	5785 MHz	15.90								
CH 165	5825 MHz	15.78								

WLAN 802.11n HT40 RF Average Output Power (dBm)										
Power vs. Channel			Power vs. Data Rate							
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index						
		MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Duty Cycle (%)		98.01			95.31	94.44	92.06	90.39	88.37	86.25
CH 151	5755 MHz	15.30	CH 151	15.21	15.20	15.14	15.20	15.22	15.19	15.18
CH 159	5795 MHz	15.24								



WLAN 802.11ac VHT20 RF Average Output Power (dBm)											
Power vs. Channel			Power vs. Data Rate								
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index							
		MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8
Duty Cycle (%)		92.86		86.87	81.25	78.21	71.91	66.23	63.89	61.77	59.59
CH 149	5745 MHz	15.84	CH 157	15.86	15.82	15.83	15.80	15.91	15.76	15.84	15.83
CH 157	5785 MHz	15.93									
CH 165	5825 MHz	15.80									

WLAN 802.11ac VHT40 RF Average Output Power (dBm)												
Power vs. Channel			Average Power vs. Data Rate									
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index								
		MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
Duty Cycle (%)		98.02		96.47	93.41	93.06	90.48	87.50	86.59	85.53	85.29	83.97
CH 151	5755 MHz	15.37	CH 151	15.31	15.30	15.31	15.23	15.22	15.18	15.18	15.11	15.10
CH 159	5795 MHz	15.34										

WLAN 802.11ac VHT80 RF Average Output Power (dBm)												
Power vs. Channel			Power vs. Data Rate									
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index								
		MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
	Duty Cycle (%)			95.95	92.65	89.90	86.91	84.85	82.76	81.48	78.85	77.08
CH 155	5775MHz	14.35	CH 155	14.23	14.21	14.20	14.20	14.14	14.17	14.18	14.27	14.32



<Ant. 2>

WLAN 802.11a RF Average Output Power (dBm)										
Power vs. Channel			Power vs. Data Rate							
Channel	Frequency (MHz)	Data Rate (bps)	Channel	Data Rate (bps)						
		6M		9M	12M	18M	24M	36M	48M	54M
Duty Cycle (%)		92.86		89.72	87.95	81.82	78.39	71.11	66.22	64.29
CH 149	5745 MHz	17.53	CH 157	17.58	17.51	17.57	17.56	17.58	17.59	17.57
CH 157	5785 MHz	17.60								
CH 165	5825 MHz	17.57								

WLAN 802.11n HT20 RF Average Output Power (dBm)										
Power vs. Channel			Power vs. Data Rate							
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index						
		MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Duty Cycle (%)		92.86		86.08	81.25	77.92	70.79	66.67	63.83	62.69
CH 149	5745 MHz	17.53		CH 165	17.55	17.56	17.54	17.55	17.56	17.53
CH 157	5785 MHz	17.48								
CH 165	5825 MHz	17.64								

WLAN 802.11n HT40 RF Average Output Power (dBm)										
Power vs. Channel			Power vs. Data Rate							
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index						
		MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Duty Cycle (%)		98.01								
CH 151	5755 MHz	17.05	CH 151	17.00	17.01	17.02	16.99	16.97	16.89	16.98
CH 159	5795 MHz	16.95								

WLAN 802.11ac VHT20 RF Average Output Power (dBm)											
Power vs. Channel			Power vs. Data Rate								
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index							
		MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8
Duty Cycle (%)		92.28		86.87	82.29	78.07	71.11	65.79	65.28	62.50	59.52
CH 149	5745 MHz	17.63	CH 165	17.63	17.62	17.60	17.63	17.62	17.66	17.54	17.67
CH 157	5785 MHz	17.51									
CH 165	5825 MHz	17.68									



WLAN 802.11ac VHT40 RF Average Output Power (dBm)												
Power vs. Channel			Power vs. Data Rate									
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index								
		MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
Duty Cycle (%)		98.21		95.35	94.44	92.36	90.48	88.64	86.59	85.53	85.29	84.85
CH 151	5755 MHz	17.07	CH 151	17.05	17.02	17.05	17.01	17.00	16.98	17.00	17.01	17.03
CH 159	5795 MHz	17.03										

WLAN 802.11ac VHT80 RF Average Output Power (dBm)												
Power vs. Channel			Power vs. Data Rate									
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index								
		MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
Duty Cycle (%)		95.05		92.65	90.00	88.10	83.33	82.76	81.48	80.77	77.08	76.34
CH 155	5775MHz	16.10	CH 155	16.06	16.04	16.05	16.07	15.99	15.94	15.88	16.03	16.06



MIMO <Ant. 1+2>

WLAN 802.11a RF Average Output Power (dBm)										
Power vs. Channel			Power vs. Data Rate							
Channel	Frequency (MHz)	Data Rate (bps)	Channel	Data Rate (bps)						
		6M		9M	12M	18M	24M	36M	48M	54M
CH 149	5745 MHz	19.93	CH 157	19.89	19.86	19.90	19.83	19.92	19.93	19.94
CH 157	5785 MHz	19.95								
CH 165	5825 MHz	19.87								

WLAN 802.11n HT20 RF Average Output Power (dBm)										
Power vs. Channel			Power vs. Data Rate							
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index						
		MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 149	5745 MHz	19.85	CH 157	19.79	19.76	19.79	19.79	19.78	19.73	19.81
CH 157	5785 MHz	19.88								
CH 165	5825 MHz	19.85								

WLAN 802.11n HT40 RF Average Output Power (dBm)										
Power vs. Channel			Power vs. Data Rate							
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index						
		MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 151	5755 MHz	19.36	CH 159	19.36	19.37	19.34	19.34	19.34	19.31	19.35
CH 159	5795 MHz	19.39								

WLAN 802.11ac VHT20 RF Average Output Power (dBm)											
Power vs. Channel			Power vs. Data Rate								
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index							
		MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8
CH 149	5745 MHz	19.87	CH 157	19.89	19.86	19.86	19.88	19.89	19.88	19.86	19.88
CH 157	5785 MHz	19.90									
CH 165	5825 MHz	19.89									

WLAN 802.11ac VHT40 RF Average Output Power (dBm)												
Power vs. Channel			Power vs. Data Rate									
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index								
		MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
CH 151	5755 MHz	19.45	CH 151	19.44	19.45	19.38	19.42	19.44	19.43	19.45	19.39	19.37
CH 159	5795 MHz	19.41										

WLAN 802.11ac VHT80 RF Average Output Power (dBm)												
Power vs. Channel			Power vs. Data Rate									
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index								
		MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
CH 155	5775MHz	18.37	CH 155	18.35	18.28	18.26	18.34	18.32	18.27	18.24	18.31	18.34

Note: MIMO Ant. 1+2 is a calculated result from sum of the power MIMO Ant. 1 and MIMO Ant. 2.

**<TXBF Modes>****MIMO <Ant. 1+2>**

WLAN 802.11n HT20 RF Average Output Power (dBm)										
Power vs. Channel			Power vs. Data Rate							
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index						
		MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 149	5745 MHz	19.52	CH 165	19.55	19.52	19.52	19.46	19.55	19.49	19.46
CH 157	5785 MHz	19.52								
CH 165	5825 MHz	19.59								

WLAN 802.11n HT40 RF Average Output Power (dBm)										
Power vs. Channel			Power vs. Data Rate							
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index						
		MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 151	5755 MHz	19.04	CH 151	19.00	18.97	18.97	18.91	18.94	18.94	18.97
CH 159	5795 MHz	19.02								



WLAN 802.11ac VHT20 RF Average Output Power (dBm)											
Power vs. Channel			Power vs. Data Rate								
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index							
		MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8
CH 149	5745 MHz	19.62	CH 165	19.71	19.69	19.69	19.71	19.69	19.71	19.65	19.71
CH 157	5785 MHz	19.69									
CH 165	5825 MHz	19.75									

WLAN 802.11ac VHT40 RF Average Output Power (dBm)												
Power vs. Channel			Power vs. Data Rate									
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index								
		MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
CH 151	5755 MHz	19.14	CH 159	19.15	19.15	19.12	19.06	19.06	19.15	19.12	19.06	19.12
CH 159	5795 MHz	19.19										

WLAN 802.11ac VHT80 RF Average Output Power (dBm)												
Power vs. Channel			Power vs. Data Rate									
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index								
		MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
CH 155	5775MHz	17.85	CH 155	17.81	17.79	17.79	17.82	17.79	17.81	17.82	17.79	17.81

Note: MIMO Ant. 1+2 is a calculated result from sum of the power MIMO Ant. 1 and MIMO Ant. 2.

2.3 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates from the power table described in section 2.2.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0


AC Conducted Emission	Mode 1 : NFC Link + AC Adapter + Charging only Cable + Bluetooth Link + WLAN (5GHz) Link + Earphone 1 with Audio Adaptor connect to EUT
	Mode 2 : NFC Link + AC Adapter + Snap on USB Cable Data Link with Notebook + WLAN (5GHz) Link + Bluetooth Link with Earphone 3 + Copy data from Notebook to EDA (SD Card)
	Mode 3 : NFC Link + AC Adapter + Charging only Cable + Bluetooth Link + WLAN (5GHz) Link + Earphone 2 with Audio Adaptor connect to EUT
	Remark: The worst case of conducted emission is mode 2; only the test data of it was reported.

Ch. #		Band IV : 5725-5850 MHz		
		802.11a	802.11n HT20	802.11n HT40
L	Low	149	149	151
M	Middle	157	157	-
H	High	165	165	159


Ch. #		Band IV : 5725-5850 MHz		
		802.11ac VHT20	802.11ac VHT40	802.11ac VHT80
L	Low	149	151	-
M	Middle	157	-	155
H	High	165	159	-


2.4 Connection Diagram of Test System

<WLAN Tx CDD Mode>



<WLAN Tx TXBF Mode>



<AC Conducted Emission Mode>

2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
2.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
3.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Notebook	DELL	P20G	FCC DoC/ Contains FCC ID: QDS-BRCM1051	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A
6.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A
7.	NFC Card	Metro Taipei	Easy Card	N/A	N/A	N/A

2.6 EUT Operation Test Setup

For WLAN CDD modes, programmed RF utility, "CMD" installed in the notebook make the EUT provide functions like channel selection and power level for continuous transmitting and receiving signals.

For WLAN MIMO TXBF modes, the EUT was tested under normal operation and link to another device with power, modulation modes and data rates controlled by engineer mode command lines. The CMD software tool was used to make EUT continuous transmitting signals.

2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r03.
Section C) Emission bandwidth for the band 5.725-5.85GHz
2. Set RBW = 100kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.

3.1.4 Test Setup








3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

<CDD Modes>








Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



<TXBF Modes>





Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

CDD modes

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r03.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.


TXBF modes

The testing follows Method PM-G of FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r03 for TXBF modes.

Method PM-G (Measurement using a gated RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit at its maximum power control level.
3. Measure the average power of the transmitter
4. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r03.
Section F) Maximum power spectral density.

CDD modes

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 300 kHz.
- Set VBW $\geq$ 1 MHz.
- Number of points in sweep $\geq$ 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add $10 \log(500\text{kHz}/\text{RBW})$ to the test result.
- Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.

TXBF modes

Method SA-3


(power averaging (rms) detection with max hold):

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
 - Set RBW = 300 kHz.
 - Set VBW $\geq$ 1 MHz.
 - Number of points in sweep $\geq$ 2 Span / RBW.
 - Sweep time $\leq$ (number of points in sweep) $\times$ T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
 - Detector = power averaging (rms).
 - Trace mode = max hold.
 - Allow max hold to run for at least 60 seconds, or longer as needed to allow the trace to stabilize.
1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
 2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.
 3. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

Method (c): Measure and add $10 \log(N_{\text{ANT}})$ dB.

With this technique, spectrum measurements are performed at each output of the device, but rather than summing the spectra or the spectral peaks across the outputs, the quantity $10 \log(N_{\text{ANT}})$ dB is added to each spectrum value before comparing to the emission limit. The addition of $10 \log(N_{\text{ANT}})$ dB serves to apportion the emission limit among the N_{ANT} outputs so that each output is permitted to contribute no more than $1/N_{\text{ANT}}^{\text{th}}$ of the PSD limit.



3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density



Please refer to Appendix A.

<CDD Modes>





<TXBF Modes>



3.4 Unwanted Emissions Measurement

This section as specified in FCC Part 15.407(b) is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement. The unwanted emissions shall comply with 15.407(b)(1) to (6), and restricted bands per FCC Part15.205.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

- (2) Unwanted spurious emissions fallen in restricted bands per FCC Part15.205 shall comply with the general field strength limits set forth in § 15.209 as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \text{ } \mu\text{V/m, where P is the eirp (Watts)}$$

EIRP (dBm)	Field Strength at 3m (dBμV/m)
-17	78.3
- 27	68.3

- (3) KDB 789033 D02 General UNII Test Procedures New Rules v01r03 G)2)c) As specified in 15.407(b), emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz (or -17 dBm/MHz as specified in 15.407(b)(4)). However, an out-of-band emission that complies with both the average and peak limits of 15.209 is not required to satisfy the -27 dBm/MHz or -17 dBm/MHz peak emission limit.

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r03. Section G) Unwanted emissions measurement.
 - (1) Procedure for Unwanted Emissions Measurements Below 1000MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold
 - (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW $\geq$ 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold
 - (3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix B and C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B and C.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

For terminal test result, the testing follows FCC KDB 174176.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.


3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

<Original Test Result>

Test Mode :	Mode 1	Temperature :	22~24℃
Test Engineer :	Arthur Hsieh	Relative Humidity :	51~53%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	NFC Link + AC Adapter + Charging only Cable + Bluetooth Link + WLAN (5GHz) Link + Earphone 1 with Audio Adaptor connect to EUT		



Final Result : QuasiPeak


Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	44.7	Off	L1	19.6	20.9	65.6
0.214000	43.3	Off	L1	19.6	19.7	63.0
0.470000	40.1	Off	L1	19.6	16.4	56.5
0.590000	37.5	Off	L1	19.6	18.5	56.0
0.694000	43.8	Off	L1	19.6	12.2	56.0
0.750000	47.9	Off	L1	19.6	8.1	56.0
1.270000	37.8	Off	L1	19.6	18.2	56.0
4.182000	35.7	Off	L1	19.7	20.3	56.0
13.558000	66.0	Off	L1	19.8	-6.0	60.0

Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	35.1	Off	L1	19.6	20.5	55.6
0.214000	33.6	Off	L1	19.6	19.4	53.0
0.470000	32.2	Off	L1	19.6	14.3	46.5
0.590000	29.7	Off	L1	19.6	16.3	46.0
0.694000	34.8	Off	L1	19.6	11.2	46.0
0.750000	41.4	Off	L1	19.6	4.6	46.0
1.270000	29.4	Off	L1	19.6	16.6	46.0
4.182000	26.1	Off	L1	19.7	19.9	46.0
13.558000	64.7	Off	L1	19.8	-14.7	50.0



Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Arthur Hsieh	Relative Humidity :	51~53%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	NFC Link + AC Adapter + Charging only Cable + Bluetooth Link + WLAN (5GHz) Link + Earphone 1 with Audio Adaptor connect to EUT		

**Final Result : QuasiPeak**


Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.182000	48.0	Off	N	19.6	16.4	64.4
0.254000	43.6	Off	N	19.6	18.0	61.6
0.462000	38.0	Off	N	19.6	18.7	56.7
0.574000	39.4	Off	N	19.6	16.6	56.0
0.694000	43.9	Off	N	19.6	12.1	56.0
0.742000	43.3	Off	N	19.6	12.7	56.0
1.614000	35.9	Off	N	19.6	20.1	56.0
2.998000	36.7	Off	N	19.5	19.3	56.0
13.558000	65.4	Off	N	19.8	-5.4	60.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.182000	37.3	Off	N	19.6	17.1	54.4
0.254000	35.5	Off	N	19.6	16.1	51.6
0.462000	30.7	Off	N	19.6	16.0	46.7
0.574000	31.6	Off	N	19.6	14.4	46.0
0.694000	40.0	Off	N	19.6	6.0	46.0
0.742000	38.2	Off	N	19.6	7.8	46.0
1.614000	28.0	Off	N	19.6	18.0	46.0
2.998000	26.9	Off	N	19.5	19.1	46.0
13.558000	64.0	Off	N	19.8	-14.0	50.0

<Terminal Test Result>

Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Arthur Hsieh	Relative Humidity :	51~53%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	NFC Link + AC Adapter + Charging only Cable + Bluetooth Link + WLAN (5GHz) Link + Earphone 1 with Audio Adaptor connect to EUT		



Final Result : QuasiPeak

Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.558000	25.3	Off	L1	19.8	34.7	60.0

Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.558000	19.3	Off	L1	19.8	30.7	50.0

Test Mode :	Mode 1	Temperature :	22~24℃
Test Engineer :	Arthur Hsieh	Relative Humidity :	51~53%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	NFC Link + AC Adapter + Charging only Cable + Bluetooth Link + WLAN (5GHz) Link + Earphone 1 with Audio Adaptor connect to EUT		


Final Result : QuasiPeak

Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.558000	31.4	Off	N	19.8	28.6	60.0


Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.558000	19.5	Off	N	19.8	30.5	50.0



<Original Test Result>


Test Mode :	Mode 2	Temperature :	22~24℃
Test Engineer :	Arthur Hsieh	Relative Humidity :	51~53%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	NFC Link + AC Adapter + Snap on USB Cable Data Link with Notebook + WLAN (5GHz) Link + Bluetooth Link with Earphone 3 + Copy data from Notebook to EDA (SD Card)		



Final Result : QuasiPeak


Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	50.5	Off	L1	19.6	15.5	66.0
0.238000	44.8	Off	L1	19.6	17.4	62.2
0.486000	39.4	Off	L1	19.6	16.8	56.2
0.582000	40.6	Off	L1	19.6	15.4	56.0
0.694000	44.5	Off	L1	19.6	11.5	56.0
0.758000	48.6	Off	L1	19.6	7.4	56.0
2.902000	41.3	Off	L1	19.5	14.7	56.0
3.150000	38.3	Off	L1	19.6	17.7	56.0
3.750000	37.0	Off	L1	19.7	19.0	56.0
7.678000	40.9	Off	L1	19.7	19.1	60.0
13.558000	78.0	Off	L1	19.8	-18.0	60.0

Test Mode :	Mode 2	Temperature :	22~24°C
Test Engineer :	Arthur Hsieh	Relative Humidity :	51~53%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	NFC Link + AC Adapter + Snap on USB Cable Data Link with Notebook + WLAN (5GHz) Link + Bluetooth Link with Earphone 3 + Copy data from Notebook to EDA (SD Card)		


Final Result : Average


Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	38.4	Off	L1	19.6	17.6	56.0
0.238000	34.1	Off	L1	19.6	18.1	52.2
0.486000	32.0	Off	L1	19.6	14.2	46.2
0.582000	27.5	Off	L1	19.6	18.5	46.0
0.694000	35.8	Off	L1	19.6	10.2	46.0
0.758000	42.6	Off	L1	19.6	3.4	46.0
2.902000	29.1	Off	L1	19.5	16.9	46.0
3.150000	24.4	Off	L1	19.6	21.6	46.0
3.750000	23.1	Off	L1	19.7	22.9	46.0
7.678000	25.4	Off	L1	19.7	24.6	50.0
13.558000	77.7	Off	L1	19.8	-27.7	50.0

Test Mode :	Mode 2	Temperature :	22~24°C
Test Engineer :	Arthur Hsieh	Relative Humidity :	51~53%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	NFC Link + AC Adapter + Snap on USB Cable Data Link with Notebook + WLAN (5GHz) Link + Bluetooth Link with Earphone 3 + Copy data from Notebook to EDA (SD Card)		


Final Result : QuasiPeak

Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	52.2	Off	N	19.6	13.8	66.0
0.222000	47.5	Off	N	19.6	15.2	62.7
0.238000	47.2	Off	N	19.6	15.0	62.2
0.486000	40.7	Off	N	19.6	15.5	56.2
0.566000	41.3	Off	N	19.6	14.7	56.0
0.606000	42.9	Off	N	19.6	13.1	56.0
0.710000	45.6	Off	N	19.6	10.4	56.0
0.758000	50.3	Off	N	19.6	5.7	56.0
0.870000	43.6	Off	N	19.6	12.4	56.0
0.918000	39.8	Off	N	19.6	16.2	56.0
1.510000	41.3	Off	N	19.6	14.7	56.0
2.910000	39.0	Off	N	19.5	17.0	56.0
3.838000	33.6	Off	N	19.6	22.4	56.0
13.558000	78.2	Off	N	19.8	-18.2	60.0


Test Mode :	Mode 2	Temperature :	22~24°C
Test Engineer :	Arthur Hsieh	Relative Humidity :	51~53%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	NFC Link + AC Adapter + Snap on USB Cable Data Link with Notebook + WLAN (5GHz) Link + Bluetooth Link with Earphone 3 + Copy data from Notebook to EDA (SD Card)		


Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	40.8	Off	N	19.6	15.2	56.0
0.222000	37.8	Off	N	19.6	14.9	52.7
0.238000	37.4	Off	N	19.6	14.8	52.2
0.486000	33.3	Off	N	19.6	12.9	46.2
0.566000	33.7	Off	N	19.6	12.3	46.0
0.606000	34.7	Off	N	19.6	11.3	46.0
0.710000	37.1	Off	N	19.6	8.9	46.0
0.758000	42.8	Off	N	19.6	3.2	46.0
0.870000	31.7	Off	N	19.6	14.3	46.0
0.918000	31.4	Off	N	19.6	14.6	46.0
1.510000	32.3	Off	N	19.6	13.7	46.0
2.910000	25.3	Off	N	19.5	20.7	46.0
3.838000	23.0	Off	N	19.6	23.0	46.0
13.558000	78.0	Off	N	19.8	-28.0	50.0

<Terminal Test Result>

Test Mode :	Mode 2	Temperature :	22~24℃
Test Engineer :	Arthur Hsieh	Relative Humidity :	51~53%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	NFC Link + AC Adapter + Snap on USB Cable Data Link with Notebook + WLAN (5GHz) Link + Bluetooth Link with Earphone 3 + Copy data from Notebook to EDA (SD Card)		



Final Result : QuasiPeak

Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.558000	28.2	Off	L1	19.8	31.8	60.0

Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.558000	22.5	Off	L1	19.8	27.5	50.0

Test Mode :	Mode 2	Temperature :	22~24°C
Test Engineer :	Arthur Hsieh	Relative Humidity :	51~53%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	NFC Link + AC Adapter + Snap on USB Cable Data Link with Notebook + WLAN (5GHz) Link + Bluetooth Link with Earphone 3 + Copy data from Notebook to EDA (SD Card)		


Final Result : QuasiPeak


Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.558000	27.4	Off	N	19.8	32.6	60.0

Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.558000	22.4	Off	N	19.8	27.6	50.0

<Original Test Result>

Test Mode :	Mode 3	Temperature :	22~24°C
Test Engineer :	Arthur Hsieh	Relative Humidity :	51~53%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	NFC Link + AC Adapter + Charging only Cable + Bluetooth Link + WLAN (5GHz) Link + Earphone 2 with Audio Adapter connect to EUT		


Final Result : QuasiPeak


Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.190000	44.9	Off	L1	19.6	19.1	64.0
0.246000	45.1	Off	L1	19.6	16.8	61.9
0.462000	41.0	Off	L1	19.6	15.7	56.7
0.582000	42.0	Off	L1	19.6	14.0	56.0
0.630000	42.7	Off	L1	19.6	13.3	56.0
0.686000	43.2	Off	L1	19.6	12.8	56.0
0.750000	48.1	Off	L1	19.6	7.9	56.0
0.886000	37.3	Off	L1	19.6	18.7	56.0
1.270000	37.7	Off	L1	19.6	18.3	56.0
13.558000	66.7	Off	L1	19.8	-6.7	60.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.190000	35.5	Off	L1	19.6	18.5	54.0
0.246000	35.8	Off	L1	19.6	16.1	51.9
0.462000	33.2	Off	L1	19.6	13.5	46.7
0.582000	32.4	Off	L1	19.6	13.6	46.0
0.630000	35.9	Off	L1	19.6	10.1	46.0
0.686000	34.3	Off	L1	19.6	11.7	46.0
0.750000	42.2	Off	L1	19.6	3.8	46.0
0.886000	28.1	Off	L1	19.6	17.9	46.0
1.270000	29.7	Off	L1	19.6	16.3	46.0
13.558000	66.7	Off	L1	19.8	-16.7	50.0




Test Mode :	Mode 3	Temperature :	22~24°C
Test Engineer :	Arthur Hsieh	Relative Humidity :	51~53%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	NFC Link + AC Adapter + Charging only Cable + Bluetooth Link + WLAN (5GHz) Link + Earphone 2 with Audio Adapter connect to EUT		



Final Result : QuasiPeak

Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	45.8	Off	N	19.6	19.8	65.6
0.190000	45.3	Off	N	19.6	18.7	64.0
0.238000	44.2	Off	N	19.6	18.0	62.2
0.462000	38.4	Off	N	19.6	18.3	56.7
0.590000	37.4	Off	N	19.6	18.6	56.0
0.694000	43.6	Off	N	19.6	12.4	56.0
0.750000	44.8	Off	N	19.6	11.2	56.0
2.014000	35.6	Off	N	19.6	20.4	56.0
2.318000	37.1	Off	N	18.6	18.9	56.0
3.078000	38.9	Off	N	19.5	17.1	56.0
13.558000	66.1	Off	N	19.8	-6.1	60.0


Test Mode :	Mode 3	Temperature :	22~24°C
Test Engineer :	Arthur Hsieh	Relative Humidity :	51~53%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	NFC Link + AC Adapter + Charging only Cable + Bluetooth Link + WLAN (5GHz) Link + Earphone 2 with Audio Adapter connect to EUT		


Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	35.2	Off	N	19.6	20.4	55.6
0.190000	34.8	Off	N	19.6	19.2	54.0
0.238000	35.6	Off	N	19.6	16.6	52.2
0.462000	30.8	Off	N	19.6	15.9	46.7
0.590000	29.2	Off	N	19.6	16.8	46.0
0.694000	36.5	Off	N	19.6	9.5	46.0
0.750000	37.8	Off	N	19.6	8.2	46.0
2.014000	28.0	Off	N	19.6	18.0	46.0
2.318000	28.4	Off	N	18.6	17.6	46.0
3.078000	27.2	Off	N	19.5	18.8	46.0
13.558000	64.7	Off	N	19.8	-14.7	50.0

<Terminal Test Result>

Test Mode :	Mode 3	Temperature :	22~24℃
Test Engineer :	Arthur Hsieh	Relative Humidity :	51~53%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	NFC Link + AC Adapter + Charging only Cable + Bluetooth Link + WLAN (5GHz) Link + Earphone 2 with Audio Adapter connect to EUT		



Final Result : QuasiPeak

Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.558000	25.8	Off	L1	19.8	34.2	60.0

Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.558000	19.5	Off	L1	19.8	30.5	50.0

Test Mode :	Mode 3	Temperature :	22~24°C
Test Engineer :	Arthur Hsieh	Relative Humidity :	51~53%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	NFC Link + AC Adapter + Charging only Cable + Bluetooth Link + WLAN (5GHz) Link + Earphone 2 with Audio Adapter connect to EUT		


Final Result : QuasiPeak

Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.558000	24.7	Off	N	19.8	35.3	60.0

Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.558000	19.9	Off	N	19.8	30.1	50.0

3.6 Frequency Stability Measurement

3.6.1 Limit of Frequency Stability

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. To ensure emission at the band edge is maintained within the authorized band, those values shall be measured by radiation emissions at upper and lower frequency points, and finally compensated by frequency deviation as procedures below.
2. The EUT was operated at the maximum output power, and connected to the spectrum analyzer, which is set to maximum hold function and peak detector. The peak value of the power envelope was measured and noted. The upper and lower frequency points were respectively measured relatively 10dB lower than the measured peak value.
3. The frequency deviation was calculated by adding the upper frequency point and the lower frequency point divided by two. Those detailed values of frequency deviation are provided in table below.

3.6.4 Test Setup



3.6.5 Test Result of Frequency Stability

Please refer to Appendix A.



3.7 Automatically Discontinue Transmission

3.7.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Result of Automatically Discontinue Transmission

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

3.8 Antenna Requirements

3.8.1 Standard Applicable

According to FCC 47 CFR Section 15.407(a)(1)(2) ,if transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.8.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.8.3 Antenna Gain

CDD modes

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = $10 \log(N_{ANT}/N_{SS}=1)$ dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

Directional gain may be calculated by using the formulas applicable to equal gain antennas with G_{ANT} set equal to the gain of the antenna having the highest gain;

The EUT supports CDD mode.

For power, the directional gain G_{ANT} is set equal to the antenna having the highest gain, i.e., F)2)f)i).

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

			DG for Power	DG for PSD	Power Limit Reduction	PSD Limit Reduction
	Ant 1 (dBi)	Ant 2 (dBi)	(dBi)	(dBi)	(dB)	(dB)
Band IV	3.90	3.80	3.90	6.86	0.00	0.86

Power limit reduction = Composite gain – 6dBi, (min = 0)

PSD limit reduction = Composite gain + PSD Array gain – 6dBi, (min = 0)

TXBF modes

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k/20}$ if the k th antenna is being fed by spatial stream j , or zero if it is not;
 G_k is the gain in dBi of the k th antenna.

The EUT supports beamforming for 802.11ac modes.

The directional gain calculation is following F)2)e)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

			DG	DG	Power	PSD
			for	for	Limit	Limit
	Ant 1	Ant 2	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
Band IV	3.90	3.80	6.86	6.86	0.86	0.86

Power Limit Reduction = DG(Power) – 6dBi, (min = 0)

PSD Limit Reduction = DG(PSD) – 6dBi, (min = 0)



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Anritsu	ML2495A	1132003	300MHz~40GHz	Aug. 04, 2016	Aug. 18, 2016 ~ Sep. 16, 2016	Aug. 03, 2017	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	1126017	300MHz~40GHz	Aug. 04, 2016	Aug. 18, 2016 ~ Sep. 16, 2016	Aug. 03, 2017	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 23, 2015	Aug. 18, 2016 ~ Sep. 16, 2016	Nov. 22, 2016	Conducted (TH05-HY)
Temperature Chamber	ESPEC	SU-241	92003713	-30℃ ~95℃	Jun. 06, 2016	Aug. 18, 2016 ~ Sep. 16, 2016	Jun. 05, 2017	Conducted (TH05-HY)
Power Sensor	DARE	RadiPower	15I00041SN O09	10MHz~6GHz	May. 03, 2016	Sep. 10, 2016 ~ Sep. 16, 2016	May. 02, 2017	Conducted (TH05-HY)
Power Sensor	DARE	RadiPower	15I00041SN O10	10MHz~6GHz	May. 03, 2016	Sep. 10, 2016 ~ Sep. 16, 2016	May. 02, 2017	Conducted (TH05-HY)
Temperature Chamber	ESPEC	SH-641	92013720	-40℃ ~90℃	Sep. 01, 2016	Sep. 10, 2016 ~ Sep. 16, 2016	Aug. 31, 2017	Conducted (TH05-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL890094	1V~20V 0.5A~5A	Oct. 12, 2015	Sep. 10, 2016 ~ Sep. 16, 2016	Oct. 11, 2016	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Sep. 06, 2016 ~ Sep. 20, 2016	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 30, 2016	Sep. 06, 2016 ~ Sep. 20, 2016	Aug. 29, 2017	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 08, 2016	Sep. 06, 2016 ~ Sep. 20, 2016	Jan. 07, 2017	Conduction (CO05-HY)
Bilog Antenna	TESEQ	CBL 6111D	35419	30MHz to 1GHz	Jan. 13, 2016	Aug. 23, 2016 ~ Sep. 09, 2016	Jan. 12, 2017	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Aug. 19, 2016	Aug. 23, 2016 ~ Sep. 09, 2016	Aug. 18, 2017	Radiation (03CH07-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY54130085	20Hz ~ 8.4GHz	Nov. 04, 2015	Aug. 23, 2016 ~ Sep. 09, 2016	Nov. 03, 2016	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Sep. 02, 2015	Aug. 23, 2016 ~ Sep. 09, 2016	Sep. 01, 2017	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590075	1GHz ~ 18GHz	Apr. 15, 2016	Aug. 23, 2016 ~ Sep. 09, 2016	Apr. 14, 2017	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz-1GHz	Mar. 18, 2016	Aug. 23, 2016 ~ Sep. 09, 2016	Mar. 17, 2017	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A02362	1GHz~ 26.5GHz	Oct. 19, 2015	Aug. 23, 2016 ~ Sep. 09, 2016	Oct. 18, 2016	Radiation (03CH07-HY)
Spectrum Analyzer	Agilent	N9010A	MY53470118	10Hz~44GHz	Feb. 27, 2016	Aug. 23, 2016 ~ Sep. 09, 2016	Feb. 26, 2017	Radiation (03CH07-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	N/A	Aug. 23, 2016 ~ Sep. 09, 2016	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Aug. 23, 2016 ~ Sep. 09, 2016	N/A	Radiation (03CH07-HY)
Loop Cable	Rohde & Schwarz	N/A	N/A	9KHz~30MHz	Dec. 03, 2015	Aug. 23, 2016 ~ Sep. 09, 2016	Dec. 02, 2016	Radiation (03CH07-HY)
Preamplifier	MITEQ	JS44-1800400 0-33-8P	1840917	18GHz ~ 40GHz	Jun. 14, 2016	Aug. 23, 2016 ~ Sep. 09, 2016	Jun. 13, 2017	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA917058 4	18GHz- 40GHz	Nov. 02, 2015	Aug. 23, 2016 ~ Sep. 09, 2016	Nov. 01, 2016	Radiation (03CH07-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.70
--	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.70
--	------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.50
--	------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.20
--	------



Appendix A. Conducted Test Results

<CDD Modes>

Report Number : FR672834F

Test Engineer:	Tommy Lee / Luffy Lin / Kai Liao	Temperature:	21~25	°C
Test Date:	2016/8/18 ~ 2016/09/18	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

Band IV													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)		Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745	18.60	18.90	27.52	37.93	16.32	16.32	0.5	0.5	Pass
11a	6Mbps	1	157	5785	18.75	19.05	36.38	39.60	16.32	16.32	0.5	0.5	Pass
11a	6Mbps	1	165	5825	18.80	19.55	35.44	38.80	16.32	16.28	0.5	0.5	Pass
11a	6Mbps	2	149	5745	18.90	19.35	35.40	39.60	16.32	16.32	0.5	0.5	Pass
11a	6Mbps	2	157	5785	19.10	20.85	39.12	42.00	16.32	16.32	0.5	0.5	Pass
11a	6Mbps	2	165	5825	19.05	19.65	37.36	41.16	16.30	16.32	0.5	0.5	Pass
VHT20	MCS0	2	149	5745	19.50	19.75	34.72	42.77	17.56	17.56	0.5	0.5	Pass
VHT20	MCS0	2	157	5785	19.10	19.75	38.24	43.36	17.56	17.60	0.5	0.5	Pass
VHT20	MCS0	2	165	5825	19.50	20.30	37.92	46.69	17.56	17.60	0.5	0.5	Pass
VHT40	MCS0	2	151	5755	36.80	37.40	66.40	94.78	36.32	36.32	0.5	0.5	Pass
VHT40	MCS0	2	159	5795	37.00	38.80	73.60	91.20	36.32	36.32	0.5	0.5	Pass
VHT80	MCS0	2	155	5775	76.08	76.08	82.32	#####	75.44	75.20	0.5	0.5	Pass

TEST RESULTS DATA
Average Power Table

Band IV														
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745	0.32	0.32	15.84	17.53		30.00	30.00	3.90	3.80	Pass
11a	6Mbps	1	157	5785	0.32	0.32	15.93	17.60		30.00	30.00	3.90	3.80	Pass
11a	6Mbps	1	165	5825	0.32	0.32	15.88	17.57		30.00	30.00	3.90	3.80	Pass
HT20	MCS0	1	149	5745	0.32	0.32	15.82	17.53		30.00	30.00	3.90	3.80	Pass
HT20	MCS0	1	157	5785	0.32	0.32	15.90	17.48		30.00	30.00	3.90	3.80	Pass
HT20	MCS0	1	165	5825	0.32	0.32	15.78	17.64		30.00	30.00	3.90	3.80	Pass
HT40	MCS0	1	151	5755	0.09	0.09	15.30	17.05		30.00	30.00	3.90	3.80	Pass
HT40	MCS0	1	159	5795	0.09	0.09	15.24	16.95		30.00	30.00	3.90	3.80	Pass
VHT20	MCS0	1	149	5745	0.32	0.35	15.84	17.63		30.00	30.00	3.90	3.80	Pass
VHT20	MCS0	1	157	5785	0.32	0.35	15.93	17.51		30.00	30.00	3.90	3.80	Pass
VHT20	MCS0	1	165	5825	0.32	0.35	15.80	17.68		30.00	30.00	3.90	3.80	Pass
VHT40	MCS0	1	151	5755	0.09	0.08	15.37	17.07		30.00	30.00	3.90	3.80	Pass
VHT40	MCS0	1	159	5795	0.09	0.08	15.34	17.03		30.00	30.00	3.90	3.80	Pass
VHT80	MCS0	1	155	5775	0.18	0.22	14.35	16.10		30.00	30.00	3.90	3.80	Pass
11a	6Mbps	2	149	5745	0.32	0.32	15.85	17.77	19.93	30.00		3.90		Pass
11a	6Mbps	2	157	5785	0.32	0.32	15.98	17.73	19.95	30.00		3.90		Pass
11a	6Mbps	2	165	5825	0.32	0.32	15.90	17.65	19.87	30.00		3.90		Pass
HT20	MCS0	2	149	5745	0.32	0.32	15.84	17.65	19.85	30.00		3.90		Pass
HT20	MCS0	2	157	5785	0.32	0.32	15.94	17.63	19.88	30.00		3.90		Pass
HT20	MCS0	2	165	5825	0.32	0.32	15.80	17.67	19.85	30.00		3.90		Pass
HT40	MCS0	2	151	5755	0.09	0.09	15.32	17.19	19.36	30.00		3.90		Pass
HT40	MCS0	2	159	5795	0.09	0.09	15.28	17.26	19.39	30.00		3.90		Pass
VHT20	MCS0	2	149	5745	0.32	0.32	15.86	17.67	19.87	30.00		3.90		Pass
VHT20	MCS0	2	157	5785	0.32	0.32	15.97	17.64	19.90	30.00		3.90		Pass
VHT20	MCS0	2	165	5825	0.32	0.32	15.85	17.70	19.89	30.00		3.90		Pass
VHT40	MCS0	2	151	5755	0.09	0.09	15.39	17.29	19.45	30.00		3.90		Pass
VHT40	MCS0	2	159	5795	0.09	0.09	15.31	17.27	19.41	30.00		3.90		Pass
VHT80	MCS0	2	155	5775	0.18	0.18	14.38	16.16	18.37	30.00		3.90		Pass

TEST RESULTS DATA
Power Spectral Density

Band IV																	
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		10log (500kHz /RBW) Factor (dB)		Average Power Density (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail	
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2		
11a	6Mbps	1	149	5745	0.32	0.32	2.22	2.22	1.70	3.93		30.00	30.00	3.90	3.80	Pass	
11a	6Mbps	1	157	5785	0.32	0.32	2.22	2.22	1.48	2.78		30.00	30.00	3.90	3.80	Pass	
11a	6Mbps	1	165	5825	0.32	0.32	2.22	2.22	1.48	3.18		30.00	30.00	3.90	3.80	Pass	
11a	6Mbps	2	149	5745	0.32	0.32	2.22					7.10	29.14		6.86		Pass
11a	6Mbps	2	157	5785	0.32	0.32	2.22					5.56	29.14		6.86		Pass
11a	6Mbps	2	165	5825	0.32	0.32	2.22					6.31	29.14		6.86		Pass
VHT20	MCS0	2	149	5745	0.32	0.32	2.22					6.78	29.14		6.86		Pass
VHT20	MCS0	2	157	5785	0.32	0.32	2.22					5.40	29.14		6.86		Pass
VHT20	MCS0	2	165	5825	0.32	0.32	2.22					6.12	29.14		6.86		Pass
VHT40	MCS0	2	151	5755	0.09	0.09	2.22					2.45	29.14		6.86		Pass
VHT40	MCS0	2	159	5795	0.09	0.09	2.22					3.13	29.14		6.86		Pass
VHT80	MCS0	2	155	5775	0.18	0.18	2.22					-0.89	29.14		6.86		Pass

TEST RESULTS DATA
Frequency Stability

Band IV										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Center Frequency (MHz)	Frequency Deviation (MHz)	Frequency Stability (ppm)	Temperature (°C)	Voltage (V)	Note
11a	6Mbps	1	149	5745	5745.000	0.000	0.00	60	3.9	
11a	6Mbps	1	149	5745	5745.000	0.000	0.00	-30	3.9	
11a	6Mbps	1	149	5745	5745.000	0.000	0.00	20	4.2	
11a	6Mbps	1	149	5745	5745.000	0.000	0.00	20	3.7	
11a	6Mbps	1	149	5745	5745.025	0.025	4.35	20	3.9	



<TXBF Modes>

Test Engineer:	Kai Liao / Tommy Lee	Temperature:	21~25	°C
Test Date:	2016/09/03 ~ 2016/09/16	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

Band IV													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)		Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
VHT20	MCS0	2	149	5745	19.00	19.25	31.70	37.80	17.56	17.56	0.5		Pass
VHT20	MCS0	2	157	5785	19.15	19.25	33.60	37.00	17.56	17.56	0.5		Pass
VHT20	MCS0	2	165	5825	19.05	19.40	30.70	38.00	17.56	17.54	0.5		Pass
VHT40	MCS0	2	151	5755	36.70	36.90	40.86	49.32	36.24	35.40	0.5		Pass
VHT40	MCS0	2	159	5795	36.80	37.00	57.06	64.26	36.32	35.96	0.5		Pass
VHT80	MCS0	2	155	5775	75.84	75.84	80.32	80.00	70.72	76.32	0.5		Pass

TEST RESULTS DATA
Average Power Table

Band IV												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
HT20	MCS0	2	149	5745	15.40	17.40	19.52	29.14		6.86		Pass
HT20	MCS0	2	157	5785	15.40	17.40	19.52	29.14		6.86		Pass
HT20	MCS0	2	165	5825	15.40	17.50	19.59	29.14		6.86		Pass
HT40	MCS0	2	151	5755	14.60	17.10	19.04	29.14		6.86		Pass
HT40	MCS0	2	159	5795	14.90	16.90	19.02	29.14		6.86		Pass
VHT20	MCS0	2	149	5745	15.50	17.50	19.62	29.14		6.86		Pass
VHT20	MCS0	2	157	5785	15.50	17.60	19.69	29.14		6.86		Pass
VHT20	MCS0	2	165	5825	15.50	17.70	19.75	29.14		6.86		Pass
VHT40	MCS0	2	151	5755	14.70	17.20	19.14	29.14		6.86		Pass
VHT40	MCS0	2	159	5795	15.00	17.10	19.19	29.14		6.86		Pass
VHT80	MCS0	2	155	5775	13.60	15.80	17.85	29.14		6.86		Pass

TEST RESULTS DATA
Power Spectral Density

Band IV														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	10log (500kHz /RBW) Factor (dB)		Average Power Density (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
VHT20	MCS0	2	149	5745	2.22					8.57	29.14	6.86		Pass
VHT20	MCS0	2	157	5785	2.22					8.76	29.14	6.86		Pass
VHT20	MCS0	2	165	5825	2.22					8.19	29.14	6.86		Pass
VHT40	MCS0	2	151	5755	2.22					5.20	29.14	6.86		Pass
VHT40	MCS0	2	159	5795	2.22					5.65	29.14	6.86		Pass
VHT80	MCS0	2	155	5775	2.22					1.33	29.14	6.86		Pass



Appendix B. Radiated Spurious Emission

Test Engineer :	Luke Chang, Ken Wu, Derreck Chen, Jesse Wang, and James Chiu	Temperature :	21~24℃
		Relative Humidity :	50~55%

<CDD Modes>

Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		5616.2	49.56	-18.64	68.2	38.33	34.6	11.89	35.26	244	299	P	H
		5699	56.24	-48.22	104.46	44.92	34.6	12	35.28	244	299	P	H
		5719	61.93	-48.59	110.52	50.55	34.6	12.06	35.28	244	299	P	H
		5722.6	69.02	-47.71	116.73	57.64	34.6	12.06	35.28	244	299	P	H
	*	5745	106.66	-	-	95.24	34.6	12.11	35.29	244	299	P	H
	*	5745	99.11	-	-	87.69	34.6	12.11	35.29	244	299	A	H
													H
													H
		5602	49.31	-18.89	68.2	38.08	34.6	11.89	35.26	218	26	P	V
		5698.4	52.42	-51.6	104.02	41.1	34.6	12	35.28	218	26	P	V
		5719.4	57.54	-53.09	110.63	46.16	34.6	12.06	35.28	218	26	P	V
		5722.6	66.34	-50.39	116.73	54.96	34.6	12.06	35.28	218	26	P	V
	*	5745	103.95	-	-	92.53	34.6	12.11	35.29	218	26	P	V
	*	5745	96.35	-	-	84.93	34.6	12.11	35.29	218	26	A	V
													V
													V



WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 157 5785MHz		5603.6	49.67	-18.53	68.2	38.44	34.6	11.89	35.26	252	301	P	H
		5690.4	49.51	-48.61	98.12	38.19	34.6	12	35.28	252	301	P	H
		5712.8	50.66	-58.13	108.79	39.28	34.6	12.06	35.28	252	301	P	H
		5725	51.97	-70.23	122.2	40.59	34.6	12.06	35.28	252	301	P	H
	*	5785	104.72	-	-	93.25	34.6	12.17	35.3	252	301	P	H
	*	5785	97.14	-	-	85.67	34.6	12.17	35.3	252	301	A	H
		5850.2	49.96	-71.78	121.74	38.39	34.6	12.28	35.31	252	301	P	H
		5865	49.6	-58.4	108	37.92	34.6	12.39	35.31	252	301	P	H
		5920.8	51.63	-19.67	71.3	39.84	34.6	12.51	35.32	252	301	P	H
		5937.8	49.52	-18.68	68.2	37.74	34.6	12.51	35.33	252	301	P	H
													H
													H
		5601	50.24	-17.96	68.2	39.01	34.6	11.89	35.26	226	26	P	V
		5669.6	49.25	-33.49	82.74	37.92	34.6	12	35.27	226	26	P	V
		5717.6	49.43	-60.7	110.13	38.05	34.6	12.06	35.28	226	26	P	V
		5723.2	50.49	-67.61	118.1	39.11	34.6	12.06	35.28	226	26	P	V
	*	5785	101.85	-	-	90.38	34.6	12.17	35.3	226	26	P	V
	*	5785	94.26	-	-	82.79	34.6	12.17	35.3	226	26	A	V
		5852.8	49.29	-66.53	115.82	37.72	34.6	12.28	35.31	226	26	P	V
		5858.4	50.99	-58.86	109.85	39.42	34.6	12.28	35.31	226	26	P	V
		5886.2	50.47	-46.41	96.88	38.8	34.6	12.39	35.32	226	26	P	V
		5938.6	50.66	-17.54	68.2	38.88	34.6	12.51	35.33	226	26	P	V
													V
													V



WiFi Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 165 5825MHz	*	5825	105.93	-	-	94.36	34.6	12.28	35.31	248	299	P	H
	*	5825	98.35	-	-	86.78	34.6	12.28	35.31	248	299	A	H
		5851.6	61.92	-56.63	118.55	50.35	34.6	12.28	35.31	248	299	P	H
		5855.4	59.17	-51.52	110.69	47.6	34.6	12.28	35.31	248	299	P	H
		5878	52.32	-50.65	102.97	40.65	34.6	12.39	35.32	248	299	P	H
		5927.8	49.58	-18.62	68.2	37.8	34.6	12.51	35.33	248	299	P	H
													H
													H
	*	5825	103.75	-	-	92.18	34.6	12.28	35.31	198	22	P	V
	*	5825	96.14	-	-	84.57	34.6	12.28	35.31	198	22	A	V
		5851.8	59.15	-58.95	118.1	47.58	34.6	12.28	35.31	198	22	P	V
		5855	56.38	-54.42	110.8	44.81	34.6	12.28	35.31	198	22	P	V
		5882	50.78	-49.22	100	39.11	34.6	12.39	35.32	198	22	P	V
		5937.6	50.16	-18.04	68.2	38.38	34.6	12.51	35.33	198	22	P	V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		11490	43.33	-30.67	74	44.24	39.27	17.16	57.34	100	0	P	H
		17232	46.56	-21.64	68.2	39.26	42.43	20.76	55.89	100	0	P	H
													H
													H
		11490	42.11	-31.89	74	43.02	39.27	17.16	57.34	100	0	P	V
		17232	46.46	-21.74	68.2	39.16	42.43	20.76	55.89	100	0	P	V
													V
													V
802.11a CH 157 5785MHz		11570	43.64	-30.36	74	44.47	39.2	17.16	57.19	100	0	P	H
		17352	45.4	-22.8	68.2	38.26	42.24	20.84	55.94	100	0	P	H
													H
													H
		11570	42.02	-31.98	74	42.85	39.2	17.16	57.19	100	0	P	V
		17352	46.49	-21.71	68.2	39.35	42.24	20.84	55.94	100	0	P	V
													V
													V
802.11a CH 165 5825MHz		11650	41.54	-32.46	74	42.35	39.11	17.16	57.08	100	0	P	H
		17472	45.91	-22.29	68.2	38.92	42.05	20.93	55.99	100	0	P	H
													H
													H
		11650	42.31	-31.69	74	43.12	39.11	17.16	57.08	100	0	P	V
		17472	46.99	-21.21	68.2	40	42.05	20.93	55.99	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

5GHz WIFI 802.11a (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
5GHz 802.11a LF		144.75	38.7	-4.8	43.5	50.16	17.86	1.78	31.1	100	268	P	H
		225.48	30.95	-15.05	46	43	16.88	2.07	31	-	-	P	H
		298.11	35.55	-10.45	46	44.47	19.78	2.32	31.02	-	-	P	H
		579.3	28.14	-17.86	46	30.52	25.06	3.24	30.68	-	-	P	H
		794.2	32.41	-13.59	46	31.18	27.64	3.9	30.31	-	-	P	H
		986	34.52	-19.48	54	30.52	30.27	3.98	30.25	-	-	P	H
													H
													H
													H
													H
													H
													H
		77.25	34.3	-5.7	40	50.65	13.57	1.28	31.2	100	45	P	V
		99.66	33	-10.5	43.5	46.42	16.4	1.28	31.1	-	-	P	V
		220.62	30.24	-15.76	46	42.69	16.48	2.07	31	-	-	P	V
		329.4	28.8	-17.2	46	36.76	20.63	2.41	31	-	-	P	V
		651.4	29.33	-16.67	46	30.34	25.92	3.57	30.5	-	-	P	V
		963.6	34.45	-19.55	54	30.5	30.23	4.07	30.35	-	-	P	V
													V
													V
												V	
												V	
												V	
												V	
												V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 149 5745MHz		5603.6	49.26	-18.94	68.2	38.03	34.6	11.89	35.26	198	58	P	H
		5698.2	58.26	-45.61	103.87	46.94	34.6	12	35.28	198	58	P	H
		5718.4	68.85	-41.5	110.35	57.47	34.6	12.06	35.28	198	58	P	H
		5724.6	78.2	-43.09	121.29	66.82	34.6	12.06	35.28	198	58	P	H
	*	5745	109.67	-	-	98.25	34.6	12.11	35.29	198	58	P	H
	*	5745	101.28	-	-	89.86	34.6	12.11	35.29	198	58	A	H
													H
													H
		5648.2	51.05	-17.15	68.2	39.77	34.6	11.95	35.27	200	58	P	V
		5698	56.42	-47.31	103.73	45.1	34.6	12	35.28	200	58	P	V
		5718.4	67.38	-42.97	110.35	56	34.6	12.06	35.28	200	58	P	V
		5724.8	76.13	-45.61	121.74	64.75	34.6	12.06	35.28	200	58	P	V
	*	5745	106.96	-	-	95.54	34.6	12.11	35.29	200	58	P	V
	*	5745	98.79	-	-	87.37	34.6	12.11	35.29	200	58	A	V
													V
													V



WIFI Ant. 2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 157 5785MHz		5619.4	50.64	-17.56	68.2	39.41	34.6	11.89	35.26	193	57	P	H
		5673.2	51.25	-34.16	85.41	39.92	34.6	12	35.27	193	57	P	H
		5719.8	54.18	-56.56	110.74	42.8	34.6	12.06	35.28	193	57	P	H
		5725	53.88	-68.32	122.2	42.5	34.6	12.06	35.28	193	57	P	H
	*	5785	109.81	-	-	98.34	34.6	12.17	35.3	193	57	P	H
	*	5785	101.57	-	-	90.1	34.6	12.17	35.3	193	57	A	H
		5850.8	51.96	-68.42	120.38	40.39	34.6	12.28	35.31	193	57	P	H
		5861.2	51.28	-57.78	109.06	39.6	34.6	12.39	35.31	193	57	P	H
		5877.2	50.75	-52.82	103.57	39.08	34.6	12.39	35.32	193	57	P	H
		5949.8	51.33	-16.87	68.2	39.44	34.6	12.62	35.33	193	57	P	H
													H
													H
		5645.8	51.06	-17.14	68.2	39.78	34.6	11.95	35.27	204	57	P	V
		5692.6	50.37	-49.37	99.74	39.05	34.6	12	35.28	204	57	P	V
		5705.2	52	-54.66	106.66	40.62	34.6	12.06	35.28	204	57	P	V
		5722.2	52.44	-63.38	115.82	41.06	34.6	12.06	35.28	204	57	P	V
	*	5785	107.2	-	-	95.73	34.6	12.17	35.3	204	57	P	V
	*	5785	98.89	-	-	87.42	34.6	12.17	35.3	204	57	A	V
		5850.2	51.01	-70.73	121.74	39.44	34.6	12.28	35.31	204	57	P	V
		5874.6	49.93	-55.38	105.31	38.25	34.6	12.39	35.31	204	57	P	V
		5879.8	50.84	-50.79	101.63	39.17	34.6	12.39	35.32	204	57	P	V
		5938	50.28	-17.92	68.2	38.5	34.6	12.51	35.33	204	57	P	V
													V
													V



WIFI Ant. 2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 165 5825MHz	*	5825	109.93	-	-	98.36	34.6	12.28	35.31	200	58	P	H
	*	5825	101.72	-	-	90.15	34.6	12.28	35.31	200	58	A	H
		5851.8	71.05	-47.05	118.1	59.48	34.6	12.28	35.31	200	58	P	H
		5856.2	64.71	-45.75	110.46	53.14	34.6	12.28	35.31	200	58	P	H
		5878.4	55.39	-47.28	102.67	43.72	34.6	12.39	35.32	200	58	P	H
		5945.8	51.61	-16.59	68.2	39.72	34.6	12.62	35.33	200	58	P	H
													H
													H
	*	5825	106.28	-	-	94.71	34.6	12.28	35.31	204	58	P	V
	*	5825	98.08	-	-	86.51	34.6	12.28	35.31	204	58	A	V
		5851.2	64.25	-55.21	119.46	52.68	34.6	12.28	35.31	204	58	P	V
		5858.2	61.01	-48.89	109.9	49.44	34.6	12.28	35.31	204	58	P	V
		5878.8	51.5	-50.88	102.38	39.83	34.6	12.39	35.32	204	58	P	V
		5928.8	51.36	-16.84	68.2	39.58	34.6	12.51	35.33	204	58	P	V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		11490	43.22	-30.78	74	44.13	39.27	17.16	57.34	100	0	P	H
		17235	53.84	-14.36	68.2	46.54	42.43	20.76	55.89	100	0	P	H
													H
													H
		11490	43.37	-30.63	74	44.28	39.27	17.16	57.34	100	0	P	V
		17235	57.68	-10.52	68.2	50.38	42.43	20.76	55.89	100	321	P	V
													V
													V
802.11a CH 157 5785MHz		11570	42.98	-31.02	74	43.81	39.2	17.16	57.19	100	0	P	H
		17352	50.87	-17.33	68.2	43.73	42.24	20.84	55.94	100	0	P	H
													H
													H
		11570	43.93	-30.07	74	44.76	39.2	17.16	57.19	100	0	P	V
		17364	52.35	-15.85	68.2	45.25	42.21	20.84	55.95	100	0	P	V
													V
													V
802.11a CH 165 5825MHz		11650	43.55	-30.45	74	44.36	39.11	17.16	57.08	100	0	P	H
		17475	51.22	-16.98	68.2	44.23	42.05	20.93	55.99	100	0	P	H
													H
													H
		11650	45.01	-28.99	74	45.82	39.11	17.16	57.08	100	0	P	V
		17475	52.55	-15.65	68.2	45.56	42.05	20.93	55.99	-	-	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

5GHz WIFI 802.11a (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
5GHz 802.11a LF		149.07	38.5	-5	43.5	50.09	17.73	1.78	31.1	100	305	P	H
		225.48	30.75	-15.25	46	42.8	16.88	2.07	31	-	-	P	H
		297.3	35.83	-10.17	46	44.76	19.78	2.32	31.03	-	-	P	H
		491.1	27.1	-18.9	46	30.76	23.99	3.04	30.69	-	-	P	H
		826.4	32.68	-13.32	46	30.7	28.23	4.1	30.35	-	-	P	H
		947.5	34.91	-11.09	46	31.08	30.15	4.07	30.39	-	-	P	H
													H
													H
													H
													H
													H
													H
		77.52	35.04	-4.96	40	51.39	13.57	1.28	31.2	100	55	P	V
		100.2	33.25	-10.25	43.5	46.4	16.4	1.55	31.1	-	-	P	V
		221.7	29.97	-16.03	46	42.34	16.56	2.07	31	-	-	P	V
		335	28.53	-17.47	46	36.35	20.77	2.41	31	-	-	P	V
		612.9	29.33	-16.67	46	31.01	25.53	3.36	30.57	-	-	P	V
		976.9	34.23	-19.77	54	30.2	30.25	4.07	30.29	-	-	P	V
													V
													V
												V	
												V	
												V	
												V	
												V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 149 5745MHz		5648.6	50.29	-17.91	68.2	39.01	34.6	11.95	35.27	378	51	P	H
		5697.6	57.9	-45.53	103.43	46.58	34.6	12	35.28	378	51	P	H
		5719	70.96	-39.56	110.52	59.58	34.6	12.06	35.28	378	51	P	H
		5724	77.69	-42.23	119.92	66.31	34.6	12.06	35.28	378	51	P	H
	*	5745	110.37	-	-	98.95	34.6	12.11	35.29	378	51	P	H
	*	5745	102.23	-	-	90.81	34.6	12.11	35.29	378	51	A	H
													H
													H
		5623	50.22	-17.98	68.2	38.93	34.6	11.95	35.26	239	32	P	V
		5697.4	58.6	-44.68	103.28	47.28	34.6	12	35.28	239	32	P	V
		5716.6	70.58	-39.27	109.85	59.2	34.6	12.06	35.28	239	32	P	V
		5725	75.3	-46.9	122.2	63.92	34.6	12.06	35.28	239	32	P	V
	*	5745	110.78	-	-	99.36	34.6	12.11	35.29	239	32	P	V
	*	5745	102.38	-	-	90.96	34.6	12.11	35.29	239	32	A	V
													V
													V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 157 5785MHz		5617	49.32	-18.88	68.2	38.09	34.6	11.89	35.26	351	40	P	H
		5682	50.64	-41.28	91.92	39.32	34.6	12	35.28	351	40	P	H
		5714.8	49.68	-59.67	109.35	38.3	34.6	12.06	35.28	351	40	P	H
		5724.8	50.99	-70.75	121.74	39.61	34.6	12.06	35.28	351	40	P	H
	*	5785	110.32	-	-	98.85	34.6	12.17	35.3	351	40	P	H
	*	5785	102.67	-	-	91.2	34.6	12.17	35.3	351	40	A	H
		5850.8	49.81	-70.57	120.38	38.24	34.6	12.28	35.31	351	40	P	H
		5863.6	50.5	-57.89	108.39	38.82	34.6	12.39	35.31	351	40	P	H
		5911.4	51.16	-27.07	78.23	39.37	34.6	12.51	35.32	351	40	P	H
		5936.6	50.98	-17.22	68.2	39.2	34.6	12.51	35.33	351	40	P	H
													H
													H
		5647.6	50.37	-17.83	68.2	39.09	34.6	11.95	35.27	219	27	P	V
		5661.8	50.43	-26.53	76.96	39.1	34.6	12	35.27	219	27	P	V
		5717	52.7	-57.26	109.96	41.32	34.6	12.06	35.28	219	27	P	V
		5724.2	53.19	-67.19	120.38	41.81	34.6	12.06	35.28	219	27	P	V
	*	5785	110.39	-	-	98.92	34.6	12.17	35.3	219	27	P	V
	*	5785	101.97	-	-	90.5	34.6	12.17	35.3	219	27	A	V
		5854.4	49.94	-62.23	112.17	38.37	34.6	12.28	35.31	219	27	P	V
		5856.4	50.33	-60.08	110.41	38.76	34.6	12.28	35.31	219	27	P	V
		5883.2	50.71	-48.4	99.11	39.04	34.6	12.39	35.32	219	27	P	V
		5939	49.84	-18.36	68.2	38.06	34.6	12.51	35.33	219	27	P	V
													V
													V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 165 5825MHz	*	5825	110.65	-	-	99.08	34.6	12.28	35.31	380	42	P	H
	*	5825	102.81	-	-	91.24	34.6	12.28	35.31	380	42	A	H
		5853	67.25	-48.11	115.36	55.68	34.6	12.28	35.31	380	42	P	H
		5855.8	64.49	-46.09	110.58	52.92	34.6	12.28	35.31	380	42	P	H
		5877.2	53.44	-50.13	103.57	41.77	34.6	12.39	35.32	380	42	P	H
		5938.6	51.2	-17	68.2	39.42	34.6	12.51	35.33	380	42	P	H
													H
													H
	*	5825	108.88	-	-	97.31	34.6	12.28	35.31	223	28	P	V
	*	5825	101.35	-	-	89.78	34.6	12.28	35.31	223	28	A	V
		5852.6	65.66	-50.61	116.27	54.09	34.6	12.28	35.31	223	28	P	V
		5856.2	64.08	-46.38	110.46	52.51	34.6	12.28	35.31	223	28	P	V
		5877	51.99	-51.72	103.71	40.32	34.6	12.39	35.32	223	28	P	V
		5946.6	50.13	-18.07	68.2	38.24	34.6	12.62	35.33	223	28	P	V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		11490	43.13	-30.87	74	44.04	39.27	17.16	57.34	380	0	P	H
		17235	56.72	-11.48	68.2	49.42	42.43	20.76	55.89	100	0	P	H
													H
													H
		11490	43.83	-30.17	74	44.74	39.27	17.16	57.34	380	0	P	V
		17235	55.44	-12.76	68.2	48.14	42.43	20.76	55.89	100	0	P	V
													V
													V
802.11a CH 157 5785MHz		11570	44.59	-29.41	74	45.42	39.2	17.16	57.19	100	0	P	H
		17355	52.94	-15.26	68.2	45.8	42.24	20.84	55.94	100	0	P	H
													H
													H
		11570	42.71	-31.29	74	43.54	39.2	17.16	57.19	100	0	P	V
		17355	52.35	-15.85	68.2	45.21	42.24	20.84	55.94	100	0	P	V
													V
													V
802.11a CH 165 5825MHz		11650	44.27	-29.73	74	45.08	39.11	17.16	57.08	100	0	P	H
		17472	54.81	-13.39	68.2	47.82	42.05	20.93	55.99	100	0	P	H
													H
													H
		11650	43.35	-30.65	74	44.16	39.11	17.16	57.08	100	0	P	V
		17472	52.29	-15.91	68.2	45.3	42.05	20.93	55.99	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT20 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT20 CH 149 5745MHz		5623.2	50.01	-18.19	68.2	38.72	34.6	11.95	35.26	376	53	P	H
		5699.8	58.75	-46.3	105.05	47.43	34.6	12	35.28	376	53	P	H
		5720	72.47	-38.33	110.8	61.09	34.6	12.06	35.28	376	53	P	H
		5724.6	80.14	-41.15	121.29	68.76	34.6	12.06	35.28	376	53	P	H
	*	5745	108.39	-	-	96.97	34.6	12.11	35.29	376	53	P	H
	*	5745	101.07	-	-	89.65	34.6	12.11	35.29	376	53	A	H
													H
													H
		5613.8	49.58	-18.62	68.2	38.35	34.6	11.89	35.26	220	31	P	V
		5697.4	57.88	-45.4	103.28	46.56	34.6	12	35.28	220	31	P	V
		5719.8	69.09	-41.65	110.74	57.71	34.6	12.06	35.28	220	31	P	V
		5724.6	79.7	-41.59	121.29	68.32	34.6	12.06	35.28	220	31	P	V
	*	5745	108.78	-	-	97.36	34.6	12.11	35.29	220	31	P	V
	*	5745	101.29	-	-	89.87	34.6	12.11	35.29	220	31	A	V
													V
													V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT20 CH 157 5785MHz		5628.4	50.33	-17.87	68.2	39.05	34.6	11.95	35.27	333	40	P	H
		5699.6	51.07	-53.84	104.91	39.75	34.6	12	35.28	333	40	P	H
		5702.4	51.31	-54.56	105.87	39.93	34.6	12.06	35.28	333	40	P	H
		5724.2	55.91	-64.47	120.38	44.53	34.6	12.06	35.28	333	40	P	H
	*	5785	109.32	-	-	97.85	34.6	12.17	35.3	333	40	P	H
	*	5785	101.44	-	-	89.97	34.6	12.17	35.3	333	40	A	H
		5850.8	50.86	-69.52	120.38	39.29	34.6	12.28	35.31	333	40	P	H
		5869	51.51	-55.37	106.88	39.83	34.6	12.39	35.31	333	40	P	H
		5891.4	50.37	-42.66	93.03	38.7	34.6	12.39	35.32	333	40	P	H
		5945.6	49.89	-18.31	68.2	38	34.6	12.62	35.33	333	40	P	H
													H
													H
		5636.4	49.31	-18.89	68.2	38.03	34.6	11.95	35.27	202	28	P	V
		5670	51.03	-32.01	83.04	39.7	34.6	12	35.27	202	28	P	V
		5715	51.66	-57.74	109.4	40.28	34.6	12.06	35.28	202	28	P	V
		5721.4	54.86	-59.13	113.99	43.48	34.6	12.06	35.28	202	28	P	V
	*	5785	108.97	-	-	97.5	34.6	12.17	35.3	202	28	P	V
	*	5785	100.53	-	-	89.06	34.6	12.17	35.3	202	28	A	V
		5852.4	49.73	-67	116.73	38.16	34.6	12.28	35.31	202	28	P	V
		5855.4	50.72	-59.97	110.69	39.15	34.6	12.28	35.31	202	28	P	V
		5892	50.04	-42.54	92.58	38.37	34.6	12.39	35.32	202	28	P	V
		5947.4	51.37	-16.83	68.2	39.48	34.6	12.62	35.33	202	28	P	V
													V
													V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT20 CH 165 5825MHz	*	5825	109.79	-	-	98.22	34.6	12.28	35.31	380	42	P	H
	*	5825	101.39	-	-	89.82	34.6	12.28	35.31	380	42	A	H
		5850.2	67.81	-53.93	121.74	56.24	34.6	12.28	35.31	380	42	P	H
		5857.6	63.87	-46.2	110.07	52.3	34.6	12.28	35.31	380	42	P	H
		5876.4	54.84	-49.32	104.16	43.17	34.6	12.39	35.32	380	42	P	H
		5931.8	50.85	-17.35	68.2	39.07	34.6	12.51	35.33	380	42	P	H
													H
													H
	*	5825	108.81	-	-	97.24	34.6	12.28	35.31	219	28	P	V
	*	5825	100.53	-	-	88.96	34.6	12.28	35.31	219	28	A	V
		5850	67.06	-55.14	122.2	55.49	34.6	12.28	35.31	219	28	P	V
		5855.2	63.23	-47.51	110.74	51.66	34.6	12.28	35.31	219	28	P	V
		5881.8	55.78	-44.37	100.15	44.11	34.6	12.39	35.32	219	28	P	V
		5941	49.65	-18.55	68.2	37.76	34.6	12.62	35.33	219	28	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT20 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT20 CH 149 5745MHz		11490	43.3	-30.7	74	44.21	39.27	17.16	57.34	100	0	P	H
		17235	54.62	-13.58	68.2	47.32	42.43	20.76	55.89	100	0	P	H
													H
													H
		11490	43.37	-30.63	74	44.28	39.27	17.16	57.34	100	0	P	V
		17235	55.77	-12.43	68.2	48.47	42.43	20.76	55.89	100	0	P	V
													V
													V
802.11ac VHT20 CH 157 5785MHz		11570	43.73	-30.27	74	44.56	39.2	17.16	57.19	100	0	P	H
		17355	52.81	-15.39	68.2	45.67	42.24	20.84	55.94	100	0	P	H
													H
													H
		11570	43.37	-30.63	74	44.2	39.2	17.16	57.19	100	0	P	V
		17355	52.55	-15.65	68.2	45.41	42.24	20.84	55.94	100	0	P	V
													V
													V
802.11ac VHT20 CH 165 5825MHz		11650	44.87	-29.13	74	45.68	39.11	17.16	57.08	100	0	P	H
		17475	53.46	-14.74	68.2	46.47	42.05	20.93	55.99	100	0	P	H
													H
													H
		11650	42.68	-31.32	74	43.49	39.11	17.16	57.08	100	0	P	V
		17475	52.1	-16.1	68.2	45.11	42.05	20.93	55.99	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT40 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT40 CH 151 5755MHz		5647.6	53.82	-14.38	68.2	42.54	34.6	11.95	35.27	373	52	P	H
		5697.2	60.57	-42.57	103.14	49.25	34.6	12	35.28	373	52	P	H
		5719.6	79.51	-31.18	110.69	68.13	34.6	12.06	35.28	373	52	P	H
		5720.2	78.31	-32.95	111.26	66.93	34.6	12.06	35.28	373	52	P	H
	*	5755	105.92	-	-	94.5	34.6	12.11	35.29	373	52	P	H
	*	5755	97.49	-	-	86.07	34.6	12.11	35.29	373	52	A	H
		5851.4	51.12	-67.89	119.01	39.55	34.6	12.28	35.31	373	52	P	H
		5870.6	51.39	-55.04	106.43	39.71	34.6	12.39	35.31	373	52	P	H
		5913.6	51.78	-24.83	76.61	39.99	34.6	12.51	35.32	373	52	P	H
		5936.4	49.96	-18.24	68.2	38.18	34.6	12.51	35.33	373	52	P	H
													H
													H
		5648.6	53.57	-14.63	68.2	42.29	34.6	11.95	35.27	212	31	P	V
		5697.2	62.32	-40.82	103.14	51	34.6	12	35.28	212	31	P	V
		5717.4	77.97	-32.1	110.07	66.59	34.6	12.06	35.28	212	31	P	V
		5723.2	81.24	-36.86	118.1	69.86	34.6	12.06	35.28	212	31	P	V
	*	5755	105.74	-	-	94.32	34.6	12.11	35.29	212	31	P	V
	*	5755	97.61	-	-	86.19	34.6	12.11	35.29	212	31	A	V
		5852.2	51.69	-65.49	117.18	40.12	34.6	12.28	35.31	212	31	P	V
		5868.8	51.74	-55.19	106.93	40.06	34.6	12.39	35.31	212	31	P	V
		5882.4	51.58	-48.12	99.7	39.91	34.6	12.39	35.32	212	31	P	V
		5935	49.83	-18.37	68.2	38.05	34.6	12.51	35.33	212	31	P	V
													V
													V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT40 CH 159 5795MHz		5634.4	50.44	-17.76	68.2	39.16	34.6	11.95	35.27	348	36	P	H
		5695.4	55.71	-46.1	101.81	44.39	34.6	12	35.28	348	36	P	H
		5717.4	57.66	-52.41	110.07	46.28	34.6	12.06	35.28	348	36	P	H
		5724	58.86	-61.06	119.92	47.48	34.6	12.06	35.28	348	36	P	H
	*	5795	106.66	-	-	95.19	34.6	12.17	35.3	348	36	P	H
	*	5795	98.13	-	-	86.66	34.6	12.17	35.3	348	36	A	H
		5853.8	60.28	-53.26	113.54	48.71	34.6	12.28	35.31	348	36	P	H
		5860	59.03	-50.37	109.4	47.46	34.6	12.28	35.31	348	36	P	H
		5877	54.25	-49.46	103.71	42.58	34.6	12.39	35.32	348	36	P	H
		5933	52.84	-15.36	68.2	41.06	34.6	12.51	35.33	348	36	P	H
													H
													H
		5606	49.77	-18.43	68.2	38.54	34.6	11.89	35.26	220	30	P	V
		5698	57.1	-46.63	103.73	45.78	34.6	12	35.28	220	30	P	V
		5718	58.34	-51.9	110.24	46.96	34.6	12.06	35.28	220	30	P	V
		5723	60.32	-57.32	117.64	48.94	34.6	12.06	35.28	220	30	P	V
	*	5795	105.72	-	-	94.25	34.6	12.17	35.3	220	30	P	V
	*	5795	97.07	-	-	85.6	34.6	12.17	35.3	220	30	A	V
		5851.4	59.66	-59.35	119.01	48.09	34.6	12.28	35.31	220	30	P	V
		5856	58.52	-52	110.52	46.95	34.6	12.28	35.31	220	30	P	V
		5875.6	53.54	-51.21	104.75	41.87	34.6	12.39	35.32	220	30	P	V
		5949.8	50.47	-17.73	68.2	38.58	34.6	12.62	35.33	220	30	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT40 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT40 CH 151 5755MHz		11510	43.67	-30.33	74	44.51	39.3	17.16	57.3	100	0	P	H
		17268	50.59	-17.61	68.2	43.34	42.37	20.79	55.91	100	0	P	H
													H
													H
		11510	43.59	-30.41	74	44.43	39.3	17.16	57.3	100	0	P	V
		17268	51.02	-17.18	68.2	43.77	42.37	20.79	55.91	100	0	P	V
													V
													V
802.11ac VHT40 CH 159 5795MHz		11590	43.61	-30.39	74	44.43	39.18	17.16	57.16	100	0	P	H
		17388	48.98	-19.22	68.2	41.87	42.19	20.87	55.95	100	0	P	H
													H
													H
		11590	44.39	-29.61	74	45.21	39.18	17.16	57.16	100	0	P	V
		17388	48.94	-19.26	68.2	41.83	42.19	20.87	55.95	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 155 5775MHz		5643.8	59.77	-8.43	68.2	48.49	34.6	11.95	35.27	351	41	P	H
		5700	74.95	-30.25	105.2	63.63	34.6	12	35.28	351	41	P	H
		5718	79.32	-30.92	110.24	67.94	34.6	12.06	35.28	351	41	P	H
		5723.6	77.78	-41.23	119.01	66.4	34.6	12.06	35.28	351	41	P	H
	*	5775	104.01	-	-	92.6	34.6	12.11	35.3	351	41	P	H
	*	5775	95.53	-	-	84.12	34.6	12.11	35.3	351	41	A	H
		5852.8	73.45	-42.37	115.82	61.88	34.6	12.28	35.31	351	41	P	H
		5856.2	72.72	-37.74	110.46	61.15	34.6	12.28	35.31	351	41	P	H
		5875.2	68.16	-36.89	105.05	56.49	34.6	12.39	35.32	351	41	P	H
		5941.6	53.64	-14.56	68.2	41.75	34.6	12.62	35.33	351	41	P	H
													H
													H
		5647.8	61.25	-6.95	68.2	49.97	34.6	11.95	35.27	224	30	P	V
		5698	75.42	-28.31	103.73	64.1	34.6	12	35.28	224	30	P	V
		5715.8	78.92	-30.71	109.63	67.54	34.6	12.06	35.28	224	30	P	V
		5722.8	79.2	-37.98	117.18	67.82	34.6	12.06	35.28	224	30	P	V
	*	5775	102.82	-	-	91.41	34.6	12.11	35.3	224	30	P	V
	*	5775	94.6	-	-	83.19	34.6	12.11	35.3	224	30	A	V
		5853.2	73.03	-41.87	114.9	61.46	34.6	12.28	35.31	224	30	P	V
		5857.8	72.64	-37.37	110.01	61.07	34.6	12.28	35.31	224	30	P	V
		5875.4	65.14	-39.76	104.9	53.47	34.6	12.39	35.32	224	30	P	V
		5932.6	52.38	-15.82	68.2	40.6	34.6	12.51	35.33	224	30	P	V
													V
													V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												


Band 4 5725~5850MHz
WIFI 802.11ac VHT80 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 155 5775MHz		11550	42.32	-31.68	74	43.15	39.23	17.16	57.22	100	0	P	H
		17328	47.32	-20.88	68.2	40.15	42.29	20.81	55.93	100	0	P	H
													H
													H
		11550	42.62	-31.38	74	43.45	39.23	17.16	57.22	100	0	P	V
		17328	47.22	-20.98	68.2	40.05	42.29	20.81	55.93	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

5GHz WIFI 802.11n VHT80 (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
5GHz 802.11n VHT80 LF		148.8	38.62	-4.88	43.5	50.19	17.75	1.78	31.1	100	298	P	H
		225.48	30.6	-15.4	46	42.65	16.88	2.07	31	-	-	P	H
		297.57	35.29	-10.71	46	44.21	19.78	2.32	31.02	-	-	P	H
		456.1	27.21	-18.79	46	31.87	23.23	2.89	30.78	-	-	P	H
		764.8	31.53	-14.47	46	30.73	27.35	3.82	30.37	-	-	P	H
		930.7	33.94	-12.06	46	30.43	29.75	4.12	30.36	-	-	P	H
													H
													H
													H
													H
													H
													H
		76.98	34.33	-5.67	40	50.79	13.46	1.28	31.2	100	88	P	V
		115.59	33.17	-10.33	43.5	45.13	17.63	1.55	31.14	-	-	P	V
		268.68	29.29	-16.71	46	38.51	19.46	2.32	31	-	-	P	V
		319.6	29.16	-16.84	46	37.38	20.37	2.41	31	-	-	P	V
		632.5	29.59	-16.41	46	30.84	25.72	3.57	30.54	-	-	P	V
		931.4	33.68	-12.32	46	30.17	29.75	4.12	30.36	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



<TXBF Modes>

Band 4 - 5725~5850MHz

WIFI 802.11ac VHT20 (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preampl Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11ac VHT20 CH 149 5745MHz		5640.8	50.67	-17.53	68.2	39.39	34.6	11.95	35.27	335	0	P	H
		5694.2	53.18	-47.74	100.92	41.86	34.6	12	35.28	335	0	P	H
		5719.8	66.49	-44.25	110.74	55.11	34.6	12.06	35.28	335	0	P	H
		5723.4	68.05	-50.5	118.55	56.67	34.6	12.06	35.28	335	0	P	H
	*	5745	108.82	-	-	97.4	34.6	12.11	35.29	335	0	P	H
	*	5745	101.06	-	-	89.64	34.6	12.11	35.29	335	0	A	H
													H
													H
		5626.6	50.58	-17.62	68.2	39.3	34.6	11.95	35.27	118	298	P	V
		5699.4	56.72	-48.04	104.76	45.4	34.6	12	35.28	118	298	P	V
		5712.8	66.5	-42.29	108.79	55.12	34.6	12.06	35.28	118	298	P	V
		5721.8	72.95	-41.95	114.9	61.57	34.6	12.06	35.28	118	298	P	V
	*	5745	110.89	-	-	99.47	34.6	12.11	35.29	118	298	P	V
	*	5745	103.43	-	-	92.01	34.6	12.11	35.29	118	298	A	V
													V
													V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT20 CH 157 5785MHz		5629.2	51.09	-17.11	68.2	39.81	34.6	11.95	35.27	345	0	P	H
		5666.2	49.77	-30.45	80.22	38.44	34.6	12	35.27	345	0	P	H
		5717.6	50.25	-59.88	110.13	38.87	34.6	12.06	35.28	345	0	P	H
		5720.8	48.14	-64.48	112.62	36.76	34.6	12.06	35.28	345	0	P	H
	*	5785	108.94	-	-	97.47	34.6	12.17	35.3	345	0	P	H
	*	5785	101.13	-	-	89.66	34.6	12.17	35.3	345	0	A	H
		5854	48.74	-64.34	113.08	37.17	34.6	12.28	35.31	345	0	P	H
		5865.4	49.55	-58.34	107.89	37.87	34.6	12.39	35.31	345	0	P	H
		5890.2	50.09	-43.83	93.92	38.42	34.6	12.39	35.32	345	0	P	H
		5949.6	49.81	-18.39	68.2	37.92	34.6	12.62	35.33	345	0	P	H
													H
													H
		5636.8	49.91	-18.29	68.2	38.63	34.6	11.95	35.27	118	338	P	V
		5693.8	51.48	-49.15	100.63	40.16	34.6	12	35.28	118	338	P	V
		5718.4	50.48	-59.87	110.35	39.1	34.6	12.06	35.28	118	338	P	V
		5724.4	49.62	-71.21	120.83	38.24	34.6	12.06	35.28	118	338	P	V
	*	5785	110.2	-	-	98.73	34.6	12.17	35.3	118	338	P	V
	*	5785	102.05	-	-	90.58	34.6	12.17	35.3	118	338	A	V
		5850.2	49.65	-72.09	121.74	38.08	34.6	12.28	35.31	118	338	P	V
		5861.2	49.73	-59.33	109.06	38.05	34.6	12.39	35.31	118	338	P	V
		5885.6	49.67	-47.66	97.33	38	34.6	12.39	35.32	118	338	P	V
		5942.2	50.2	-18	68.2	38.31	34.6	12.62	35.33	118	338	P	V
													V
													V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT20 CH 165 5825MHz	*	5825	107.13	-	-	95.56	34.6	12.28	35.31	246	360	P	H
	*	5825	99.04	-	-	87.47	34.6	12.28	35.31	246	360	A	H
		5850.8	61.94	-58.44	120.38	50.37	34.6	12.28	35.31	246	360	P	H
		5857	57.5	-52.74	110.24	45.93	34.6	12.28	35.31	246	360	P	H
		5877.4	52.46	-50.96	103.42	40.79	34.6	12.39	35.32	246	360	P	H
		5931.2	49.48	-18.72	68.2	37.7	34.6	12.51	35.33	246	360	P	H
													H
													H
	*	5825	110.66	-	-	99.09	34.6	12.28	35.31	102	341	P	V
	*	5825	102.74	-	-	91.17	34.6	12.28	35.31	102	341	A	V
		5851.2	62.14	-57.32	119.46	50.57	34.6	12.28	35.31	102	341	P	V
		5857.2	56.2	-53.98	110.18	44.63	34.6	12.28	35.31	102	341	P	V
		5876.6	53.37	-50.64	104.01	41.7	34.6	12.39	35.32	102	341	P	V
		5940.8	50.24	-17.96	68.2	38.35	34.6	12.62	35.33	102	341	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT20 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT20 CH 149 5745MHz		11490	41.73	-32.27	74	42.64	39.27	17.16	57.34	100	0	P	H
		17235	51.59	-16.61	68.2	44.29	42.43	20.76	55.89	100	0	P	H
													H
													H
		11490	43.39	-30.61	74	44.3	39.27	17.16	57.34	100	0	P	V
		17235	54.28	-13.92	68.2	46.98	42.43	20.76	55.89	100	0	P	V
													V
													V
802.11ac VHT20 CH 157 5785MHz		11570	42.43	-31.57	74	43.26	39.2	17.16	57.19	100	0	P	H
		17355	50.96	-17.24	68.2	43.82	42.24	20.84	55.94	100	0	P	H
													H
													H
		11570	42.81	-31.19	74	43.64	39.2	17.16	57.19	100	0	P	V
		17355	50.53	-17.67	68.2	43.39	42.24	20.84	55.94	100	0	P	V
													V
													V
802.11ac VHT20 CH 165 5825MHz		11650	42.12	-31.88	74	42.93	39.11	17.16	57.08	100	0	P	H
		17475	53.05	-15.15	68.2	46.06	42.05	20.93	55.99	100	0	P	H
													H
													H
		11650	41.76	-32.24	74	42.57	39.11	17.16	57.08	100	0	P	V
		17475	51.12	-17.08	68.2	44.13	42.05	20.93	55.99	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT40 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT40 CH 151 5755MHz		5632.8	50.32	-17.88	68.2	39.04	34.6	11.95	35.27	380	0	P	H
		5697.2	54.89	-48.25	103.14	43.57	34.6	12	35.28	380	0	P	H
		5720	62.43	-48.37	110.8	51.05	34.6	12.06	35.28	380	0	P	H
		5723.2	62.6	-55.5	118.1	51.22	34.6	12.06	35.28	380	0	P	H
	*	5755	105.26	-	-	93.84	34.6	12.11	35.29	380	0	P	H
	*	5755	97.67	-	-	86.25	34.6	12.11	35.29	380	0	A	H
		5853.4	49.17	-65.28	114.45	37.6	34.6	12.28	35.31	380	0	P	H
		5859.4	49.66	-59.91	109.57	38.09	34.6	12.28	35.31	380	0	P	H
		5910.2	50.14	-28.98	79.12	38.35	34.6	12.51	35.32	380	0	P	H
		5946.2	49.99	-18.21	68.2	38.1	34.6	12.62	35.33	380	0	P	H
													H
													H
		5642.8	52.29	-15.91	68.2	41.01	34.6	11.95	35.27	106	299	P	V
		5694.6	61.27	-39.95	101.22	49.95	34.6	12	35.28	106	299	P	V
		5719.8	68.98	-41.76	110.74	57.6	34.6	12.06	35.28	106	299	P	V
		5724.6	70.58	-50.71	121.29	59.2	34.6	12.06	35.28	106	299	P	V
	*	5755	106.92	-	-	95.5	34.6	12.11	35.29	106	299	P	V
	*	5755	98.99	-	-	87.57	34.6	12.11	35.29	106	299	A	V
		5851	50.98	-68.94	119.92	39.41	34.6	12.28	35.31	106	299	P	V
		5862.8	50.47	-58.14	108.61	38.79	34.6	12.39	35.31	106	299	P	V
		5903.6	50.37	-33.63	84	38.58	34.6	12.51	35.32	106	299	P	V
		5931.2	50.4	-17.8	68.2	38.62	34.6	12.51	35.33	106	299	P	V
													V
													V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT40 CH 159 5795MHz		5616.2	49.45	-18.75	68.2	38.22	34.6	11.89	35.26	328	0	P	H
		5683	52.04	-40.62	92.66	40.72	34.6	12	35.28	328	0	P	H
		5715.8	52.93	-56.7	109.63	41.55	34.6	12.06	35.28	328	0	P	H
		5722	53.74	-61.62	115.36	42.36	34.6	12.06	35.28	328	0	P	H
	*	5795	106.14	-	-	94.67	34.6	12.17	35.3	328	0	P	H
	*	5795	97.42	-	-	85.95	34.6	12.17	35.3	328	0	A	H
		5850	52.52	-69.68	122.2	40.95	34.6	12.28	35.31	328	0	P	H
		5861	51.25	-57.87	109.12	39.57	34.6	12.39	35.31	328	0	P	H
		5878.2	50.53	-52.29	102.82	38.86	34.6	12.39	35.32	328	0	P	H
		5933.8	50.67	-17.53	68.2	38.89	34.6	12.51	35.33	328	0	P	H
													H
													H
		5629	49.77	-18.43	68.2	38.49	34.6	11.95	35.27	119	301	P	V
		5697	51.49	-51.5	102.99	40.17	34.6	12	35.28	119	301	P	V
		5711.4	55.14	-53.25	108.39	43.76	34.6	12.06	35.28	119	301	P	V
		5721.4	56.03	-57.96	113.99	44.65	34.6	12.06	35.28	119	301	P	V
	*	5795	108.43	-	-	96.96	34.6	12.17	35.3	119	301	P	V
	*	5795	98.73	-	-	87.26	34.6	12.17	35.3	119	301	A	V
		5851	56.11	-63.81	119.92	44.54	34.6	12.28	35.31	119	301	P	V
		5858.8	54.85	-54.88	109.73	43.28	34.6	12.28	35.31	119	301	P	V
		5877.4	51.88	-51.54	103.42	40.21	34.6	12.39	35.32	119	301	P	V
		5939.4	49.44	-18.76	68.2	37.66	34.6	12.51	35.33	119	301	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT40 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT40 CH 151 5755MHz		11510	42.19	-31.81	74	43.03	39.3	17.16	57.3	100	0	P	H
		17265	48.79	-19.41	68.2	41.54	42.37	20.79	55.91	100	0	P	H
													H
													H
		11510	42.41	-31.59	74	43.25	39.3	17.16	57.3	100	0	P	V
		17265	50.75	-17.45	68.2	43.5	42.37	20.79	55.91	100	0	P	V
													V
													V
802.11ac VHT40 CH 159 5795MHz		11590	43.21	-30.79	74	44.03	39.18	17.16	57.16	100	0	P	H
		17385	45.96	-22.24	68.2	38.85	42.19	20.87	55.95	100	0	P	H
													H
													H
		11590	43.51	-30.49	74	44.33	39.18	17.16	57.16	100	0	P	V
		17385	47.57	-20.63	68.2	40.46	42.19	20.87	55.95	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 155 5775MHz		5627	52.01	-16.19	68.2	40.73	34.6	11.95	35.27	320	0	P	H
		5687.8	60.22	-35.98	96.2	48.9	34.6	12	35.28	320	0	P	H
		5719.8	60.15	-50.59	110.74	48.77	34.6	12.06	35.28	320	0	P	H
		5723.2	59.93	-58.17	118.1	48.55	34.6	12.06	35.28	320	0	P	H
	*	5775	100.92	-	-	89.51	34.6	12.11	35.3	320	0	P	H
	*	5775	93.32	-	-	81.91	34.6	12.11	35.3	320	0	A	H
		5854	62.06	-51.02	113.08	50.49	34.6	12.28	35.31	320	0	P	H
		5859.4	57.96	-51.61	109.57	46.39	34.6	12.28	35.31	320	0	P	H
		5898.8	50.49	-37.06	87.55	38.82	34.6	12.39	35.32	320	0	P	H
		5945.6	49.88	-18.32	68.2	37.99	34.6	12.62	35.33	320	0	P	H
													H
													H
		5630	53.5	-14.7	68.2	42.22	34.6	11.95	35.27	100	340	P	V
		5697	64.77	-38.22	102.99	53.45	34.6	12	35.28	100	340	P	V
		5711	65.72	-42.56	108.28	54.34	34.6	12.06	35.28	100	340	P	V
		5723.4	67.43	-51.12	118.55	56.05	34.6	12.06	35.28	100	340	P	V
	*	5775	102.77	-	-	91.36	34.6	12.11	35.3	100	340	P	V
	*	5775	94.66	-	-	83.25	34.6	12.11	35.3	100	340	A	V
		5854.2	60.06	-52.56	112.62	48.49	34.6	12.28	35.31	100	340	P	V
		5865.8	57.77	-50	107.77	46.09	34.6	12.39	35.31	100	340	P	V
		5881	53.88	-46.86	100.74	42.21	34.6	12.39	35.32	100	340	P	V
		5948.2	51.02	-17.18	68.2	39.13	34.6	12.62	35.33	100	340	P	V
													V
													V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												

**Band 4 5725~5850MHz****WIFI 802.11ac VHT80 (Harmonic @ 3m)**

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 155 5775MHz		11550	43.86	-30.14	74	44.69	39.23	17.16	57.22	100	0	P	H
		17325	46.39	-21.81	68.2	39.22	42.29	20.81	55.93	100	0	P	H
													H
													H
		11550	43.77	-30.23	74	44.6	39.23	17.16	57.22	100	0	P	V
		17325	47.81	-20.39	68.2	40.64	42.29	20.81	55.93	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

5GHz WIFI 802.11n VHT80 (LF @ 3m)

[illegible]



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.





Appendix C. Radiated Spurious Emission Plots

Test Engineer :	Luke Chang, Ken Wu, Derreck Chen, Jesse Wang, and James Chiu	Temperature :	21~24°C
		Relative Humidity :	50~55%

<CDD Modes>

Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
1	Horizontal	Fundamental
Peak	 File: 300M11-1V Condition: PCAN_300M_15-24 3m HP ANT 13000 HORIZONTAL Detector: Peak Project: 672834 Mode: H	 File: 300M11-1V Condition: PCAN_300M_15-24 3m HP ANT 13000 HORIZONTAL Detector: Peak Project: 672834 Mode: H






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
1	Vertical	Fundamental
Peak		



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
1	Horizontal	Fundamental
Peak	Horizontal spectrum plot showing a peak at 5785 MHz. The plot includes a red trace for the signal and a blue trace for the noise floor. The peak is labeled with a value of 10.00 dBm. The x-axis is Frequency (MHz) and the y-axis is Power (dBm).	Fundamental spectrum plot showing a peak at 5785 MHz. The plot includes a red trace for the signal and a blue trace for the noise floor. The peak is labeled with a value of 10.00 dBm. The x-axis is Frequency (MHz) and the y-axis is Power (dBm).
Peak	Horizontal spectrum plot showing a peak at 5785 MHz. The plot includes a red trace for the signal and a blue trace for the noise floor. The peak is labeled with a value of 10.00 dBm. The x-axis is Frequency (MHz) and the y-axis is Power (dBm).	Left blank





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
1	Vertical	Fundamental
Peak	 File: 20081114 Condition: PCAR_200811_15-04_3m RF-44F_15000 VERTICAL Detector: Peak Preamp: 472034 Mode: 12	 File: 20081114 Condition: PCAR_200811_15-04_3m RF-44F_15000 VERTICAL Detector: Peak Preamp: 472034 Mode: 12
Peak	 File: 20081114 Condition: PCAR_200811_15-04_3m RF-44F_15000 VERTICAL Detector: Peak Preamp: 472034 Mode: 12	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
1	Horizontal	Fundamental
Peak	File: 200817-01 Condition: PCAN_200817-01-04 3m HP-44F 13000 HORIZONTAL Detector: Peak Preamp: 47dB Mode: 10	File: 200817-01 Condition: PCAN_200817-01-04 3m HP-44F 13000 HORIZONTAL Detector: Peak Preamp: 47dB Mode: 10





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
1	Vertical	Fundamental
Peak	 Size : 300MHz Condition : PCAN_80211a_16-04_3m HP 44E 13000 VERTICAL Detector : 100.00dBm 100.00dBm 100.00dBm 100.00dBm Project : 4728H Model : 10	 Size : 300MHz Condition : PCAN_80211a_16-04_3m HP 44E 13000 VERTICAL Detector : 100.00dBm 100.00dBm 100.00dBm 100.00dBm Project : 4728H Model : 10





Band 4 - 5725~5850MHz



WIFI 802.11a (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH149 5745MHz	
1	Horizontal	Vertical
Peak Avg.	 File : 200817.RV Condition : PCA4000 3m 5W CHF_11429 HORIZONTAL Detector : Peak Project : 12024 Mode : H	 File : 200817.RV Condition : PCA4000 3m 5W CHF_11429 VERTICAL Detector : Peak Project : 12024 Mode : H



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH157 5785MHz	
1	Horizontal	Vertical
Peak Avg.	 File : 20150828 Condition : PCALUW80 5m 5MHz CH157 HORIZONTAL Detector : Peak Preamp : 67DB Mode : 12	 File : 20150828 Condition : PCALUW80 5m 5MHz CH157 VERTICAL Detector : Peak Preamp : 67DB Mode : 12





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH165 5825MHz	
1	Horizontal	Vertical
Peak Avg.	 File : 20150828 Condition : PCAL0000 3m 5MHz CH165 HORIZONTAL Detector : Peak Preamp : 60dB Mode : IS	 File : 20150828 Condition : PCAL0000 3m 5MHz CH165 VERTICAL Detector : Peak Preamp : 60dB Mode : IS



Emission below 1GHz



5GHz WIFI 802.11a (LF)

WIFI	5GHz 5725~5850MHz	
ANT	802.11a LF	
1	Horizontal	Vertical
QP / Peak		



Band 4 - 5725~5850MHz




WIFI 802.11a (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
2	Horizontal	Fundamental
Peak	 Horizontal Peak	 Fundamental Peak





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
2	Vertical	Fundamental
Peak	File: 20181114_01_01 Condition: 20181114_01_01 Date: 2018-11-14 Time: 10:00:00 Power: 105.0 dBm Frequency: 5745 MHz Mode: 20	File: 20181114_01_01 Condition: 20181114_01_01 Date: 2018-11-14 Time: 10:00:00 Power: 105.0 dBm Frequency: 5745 MHz Mode: 20





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
2	Horizontal	Fundamental
Peak		
Peak		Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
2	Vertical	Fundamental
Peak	Size: 300MHz Condition: PCAN_300MHz_15.04_3m HP-44F_15000 VERTICAL Detector: Peak Preamp: 57dB Mode: 20	Size: 300MHz Condition: PCAN_300MHz_15.04_3m HP-44F_15000 VERTICAL Detector: Peak Preamp: 57dB Mode: 20
Peak	Size: 300MHz Condition: PCAN_300MHz_15.04_3m HP-44F_15000 VERTICAL Detector: Peak Preamp: 57dB Mode: 20	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
2	Horizontal	Fundamental
Peak	 File: 20081114 Condition: 20081114 15:34 3m HP-ANT 15000 HORIZONTAL Detector: Peak Preamp: 67DB Mode: -20	 File: 20081114 Condition: 20081114 15:34 3m HP-ANT 15000 HORIZONTAL Detector: Peak Preamp: 67DB Mode: -20





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
2	Vertical	Fundamental
Peak	 File : 200417-01 Condition : PCAR_2004_15-04_3m RF-46F_13000 VERTICAL Setup : 1000 80MHz VSW 2000 600Hz SHOT-Aus Detector : Peak Preprod : 5725H Mode : 20	 File : 200417-01 Condition : PCAR_2004_15-04_3m RF-46F_13000 VERTICAL Setup : 1000 80MHz VSW 2000 600Hz SHOT-Aus Detector : Peak Preprod : 5725H Mode : 20





Band 4 - 5725~5850MHz



WIFI 802.11a (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH149 5745MHz	
2	Horizontal	Vertical
Peak Avg.	 Site : 300M11V Condition : PCAUSP86 3m 5W CH149 HORIZONTAL Detector : Peak Project : 572834 Mode : 25	 Site : 300M11V Condition : PCAUSP86 3m 5W CH149 VERTICAL Detector : Peak Project : 572834 Mode : 25



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH157 5785MHz	
2	Horizontal	Vertical
Peak Avg.	 Date: 2018.08.03 Condition: 200MHz BW Device: 802.11a CH157 Project: 5785MHz Mode: Peak	 Date: 2018.08.03 Condition: 200MHz BW Device: 802.11a CH157 Project: 5785MHz Mode: Peak



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH165 5825MHz	
2	Horizontal	Vertical
Peak Avg.	 File : 20160801 Condition : PCAL0000 5m 5MHz CH165 HORIZONTAL Detector : Peak Preamp : 5700H Mode : 2N	 File : 20160801 Condition : PCAL0000 5m 5MHz CH165 VERTICAL Detector : Peak Preamp : 5700H Mode : 2N



Emission below 1GHz


5GHz WIFI 802.11a (LF)

WIFI	5GHz 5725~5850MHz	
ANT	802.11a LF	
2	Horizontal	Vertical
QP / Peak		
	Site : 000817-497 Condition : QP 5m LF-ANT.30x180cm HORIZONTAL Detector : Peak Project : 672834 Mode : 1dB	Site : 000817-497 Condition : QP 5m LF-ANT.30x180cm VERTICAL Detector : Peak Project : 672834 Mode : 1dB





Band 4 - 5725~5850MHz




WIFI 802.11a (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
1+2	Horizontal	Fundamental
Peak	 File: 20081101 Condition: 20081101 10:04 3m HP-44E 15000 HORIZONTAL Ref: 1000 8000Hz VSW 2000 0000Hz SWT Auto Detector: Peak Project: 672834 Mode: 89	 File: 20081101 Condition: 20081101 10:04 3m HP-44E 15000 HORIZONTAL Ref: 1000 8000Hz VSW 2000 0000Hz SWT Auto Detector: Peak Project: 672834 Mode: 89






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
1+2	Vertical	Fundamental
Peak	 Date: 2016-08-26 Condition: PCAR_802.11a_15-24_3m RF-44F_13000 VERTICAL Detector: Peak Project: 872834 Mode: RF	 Date: 2016-08-26 Condition: PCAR_802.11a_15-24_3m RF-44F_13000 VERTICAL Detector: Peak Project: 872834 Mode: RF





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
1+2	Horizontal	Fundamental
Peak	 Date: 2008/11/14 Condition: PCAL, 300MHz, 10-24 Jm HP-AMF, 13000 HORIZONTAL Detector: Peak Preamp: 4700H Mode: 00	 Date: 2008/11/14 Condition: PCAL, 300MHz, 10-24 Jm HP-AMF, 13000 HORIZONTAL Detector: Peak Preamp: 4700H Mode: 00
Peak	 Date: 2008/11/14 Condition: PCAL, 300MHz, 10-24 Jm HP-AMF, 13000 HORIZONTAL Detector: Peak Preamp: 4700H Mode: 00	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
1+2	Vertical	Fundamental
Peak		
Peak		Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
1+2	Horizontal	Fundamental
Peak	Size: 200MHz Condition: PCAN_80211a_16-04_3m HF-AHF_13000 HORIZONTAL Detector: 80Hz 1000 809Hz VSW 2000 6000Hz SWT Auto Project: Peak Probe: 8720H Mode: 01	Size: 200MHz Condition: PCAN_80211a_16-04_3m HF-AHF_13000 FUNDAMENTAL Detector: 80Hz 1000 809Hz VSW 2000 6000Hz SWT Auto Project: Peak Probe: 8720H Mode: 01





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
1+2	Vertical	Fundamental
Peak	 File: 100M1-RV Condition: 70CAW_30204_16-04_3m HP-44E_13003 VERTICAL Reference: 1000 800kHz VSW 2000 6000Hz SHIT-Ashy Detector: Peak Prepared: 4/2/2011 Mark: 01	 File: 100M1-RV Condition: 70CAW_30204_16-04_3m HP-44E_13003 VERTICAL Reference: 1000 800kHz VSW 2000 6000Hz SHIT-Ashy Detector: Peak Prepared: 4/2/2011 Mark: 01





Band 4 5725~5850MHz
WIFI 802.11ac VHT20 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT20 CH149 5745MHz	
1+2	Horizontal	Fundamental
Peak	 File: 20081109 Condition: PCAN_200811_15_24_1m HP ANT_15000 HORIZONTAL Detector: Peak Preamp: AT20H Mode: IS	 File: 20081109 Condition: PCAN_200811_15_24_1m HP ANT_15000 HORIZONTAL Detector: Peak Preamp: AT20H Mode: IS






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT20 CH149 5745MHz	
1+2	Vertical	Fundamental
Peak Avg.	 Date: 2016.08.26 PCAN_2016_10-04 3m HP 400 13000 VERTICAL	 Date: 2016.08.26 PCAN_2016_10-04 3m HP 400 13000 VERTICAL



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT20 CH157 5785MHz	
1+2	Horizontal	Fundamental
Peak	 Date: 2018.08.20 Condition: PCAN_802.11ac VHT20 CH157 5785MHz Detector: Peak Prepared: AT2018 Model: 80	 Date: 2018.08.20 Condition: PCAN_802.11ac VHT20 CH157 5785MHz Detector: Peak Prepared: AT2018 Model: 80
Peak	 Date: 2018.08.20 Condition: PCAN_802.11ac VHT20 CH157 5785MHz Detector: Peak Prepared: AT2018 Model: 80	Left blank





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT20 CH157 5785MHz	
1+2	Vertical	Fundamental
Peak	 File: 200817-01 Condition: PCAR_3C04_15-04_3m HP-44F_13000 VERTICAL Detector: Peak Preprod: 872834 Mode: 01	 File: 200817-01 Condition: PCAR_3C04_15-04_3m HP-44F_13000 VERTICAL Detector: Peak Preprod: 872834 Mode: 01
Peak	 File: 200817-01 Condition: PCAR_3C04_15-04_3m HP-44F_13000 VERTICAL Detector: Peak Preprod: 872834 Mode: 01	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT20 CH165 5825MHz	
1+2	Horizontal	Fundamental
Peak	File: 200817-01 Condition: PCAN_802.11ac VHT20 CH165 5825MHz HORIZONTAL Detector: Peak Prepared: AT2024 Mode: 01	File: 200817-01 Condition: PCAN_802.11ac VHT20 CH165 5825MHz FUNDAMENTAL Detector: Peak Prepared: AT2024 Mode: 01






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT20 CH165 5825MHz	
1+2	Vertical	Fundamental
Peak Avg.	 File : 100M1-RV Condition : PCAN_30204_16-04_3m HP-46F_13000 VERTICAL Reference : 1000 8000Hz VSW 2000 6000Hz SHIT-Ashy Detector : Peak Prepared : 4/20/21 Mark : 00	 File : 100M1-RV Condition : PCAN_30204_16-04_3m HP-46F_13000 VERTICAL Reference : 1000 8000Hz VSW 2000 6000Hz SHIT-Ashy Detector : Peak Prepared : 4/20/21 Mark : 00



Band 4 5725~5850MHz
WIFI 802.11ac VHT40 (Band Edge @ 3m)




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT40 CH151 5755MHz	
1+2	Horizontal	Fundamental
Peak	 File: 130CH14V Condition: PCAN 30204 15.24 5m HP ANT 13020 HORIZONTAL Sweep: 1000 500Hz 100Hz 3000 500Hz 500Hz Detector: Peak Project: 17102H Mode: 00	 File: 130CH14V Condition: PCAN30204 5m HP ANT 13020 HORIZONTAL Sweep: 1000 500Hz 100Hz 3000 500Hz 500Hz Detector: Peak Project: 17102H Mode: 00
Peak	 File: 130CH14V Condition: PCAN 30204 15.24 5m HP ANT 13020 HORIZONTAL Sweep: 1000 500Hz 100Hz 3000 500Hz 500Hz Detector: Peak Project: 17102H Mode: 00	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT40 CH151 5755MHz	
1+2	Vertical	Fundamental
Peak	 File: 20181101_01_01 Condition: PCAN_20181101_01_01 Detector: Peak Preamp: 67dBm Mode: 60	 File: 20181101_01_01 Condition: PCAN_20181101_01_01 Detector: Peak Preamp: 67dBm Mode: 60
Peak	 File: 20181101_01_01 Condition: PCAN_20181101_01_01 Detector: Peak Preamp: 67dBm Mode: 60	Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT40 CH159 5795MHz	
1+2	Horizontal	Fundamental
Peak	Date: 2024-07-19 Condition: PCAN_2024_19-04 3m HP-44F 15000 HORIZONTAL Detector: NORM 800Hz VSW 3000 6000Hz 50V Auto Project: 5725H Mode: 90	Date: 2024-07-19 Condition: PCAN_2024_19-04 3m HP-44F 15000 HORIZONTAL Detector: NORM 800Hz VSW 3000 6000Hz 50V Auto Project: 5725H Mode: 90
Peak	Date: 2024-07-19 Condition: PCAN_2024_19-04 3m HP-44F 15000 HORIZONTAL Detector: NORM 800Hz VSW 3000 6000Hz 50V Auto Project: 5725H Mode: 90	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT40 CH159 5795MHz	
1+2	Vertical	Fundamental
Peak		
Peak		Left blank



Band 4 5725~5850MHz
WIFI 802.11ac VHT80 (Band Edge @ 3m)



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1+2	Horizontal	Fundamental
Peak	File: 150817-01 Condition: 700W, 3000Hz, 10-24, 3m HP ANT, 15000 HORIZONTAL Ref: 1000 8000Hz VSW 2000 6000Hz SWT Auto Detector: Peak Project: 672834 Mode: 01	File: 150817-01 Condition: 700W, 3000Hz, 10-24, 3m HP ANT, 15000 HORIZONTAL Ref: 1000 8000Hz VSW 2000 6000Hz SWT Auto Detector: Peak Project: 672834 Mode: 01
Peak	File: 150817-01 Condition: 700W, 3000Hz, 10-24, 3m HP ANT, 15000 HORIZONTAL Ref: 1000 8000Hz VSW 2000 6000Hz SWT Auto Detector: Peak Project: 672834 Mode: 01	Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1+2	Vertical	Fundamental
Peak	 Date: 200807-09 Condition: PCAN_80204_15-04_3m HP-44F 15000 VERTICAL Detector: 80Hz 1000 800Hz VSW 3000 6000Hz SWIFT Auto Project: Peak Preset: 5720H Mode: 0F	 Date: 200807-09 Condition: PCAN80204_3m HP-44F 15000 VERTICAL Detector: 80Hz 1000 800Hz VSW 3000 6000Hz SWIFT Auto Project: Peak Preset: 5720H Mode: 0F
Peak	 Date: 200807-09 Condition: PCAN_80204_15-04_3m HP-44F 15000 VERTICAL Detector: 80Hz 1000 800Hz VSW 3000 6000Hz SWIFT Auto Project: Peak Preset: 5720H Mode: 0F	Left blank





Band 4 - 5725~5850MHz



WIFI 802.11a (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH149 5745MHz	
1+2	Horizontal	Vertical
Peak Avg.	 File : 20180801 Condition : 20180801_5745MHz_HORIZONTAL Detector : Peak Project : 47024 Mode : 01	 File : 20180801 Condition : 20180801_5745MHz_VERTICAL Detector : Peak Project : 47024 Mode : 01





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH157 5785MHz	
1+2	Horizontal	Vertical
Peak Avg.		



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH165 5825MHz	
1+2	Horizontal	Vertical
Peak Avg.		





Band 4 5725~5850MHz
WIFI 802.11ac VHT20 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT20 CH149 5745MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Power (dBm) Frequency (MHz) File : 200817.RF Condition : 200817.RF_5m_SMP_CNF_14920_HORIZONTAL Detector : Peak Project : 472034 Mode : 02	 Power (dBm) Frequency (MHz) File : 200817.RF Condition : 200817.RF_5m_SMP_CNF_14920_VERTICAL Detector : Peak Project : 472034 Mode : 02



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT20 CH157 5785MHz	
1+2	Horizontal	Vertical
Peak Avg.	File : 200817.RV Condition : PCA0098 5m SWF CHF_01529 HORIZONTAL Detector : Peak Project : 42934 Mode : N	File : 200817.RV Condition : PCA0098 5m SWF CHF_01529 VERTICAL Detector : Peak Project : 42934 Mode : N





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT20 CH165 5825MHz	
1+2	Horizontal	Vertical
Peak Avg.	 File : 200817.WY Condition : 20CA0096 3m SHF CHF_ CH165 HORIZONTAL Detector : Peak Project : 672834 Mode : N	 File : 200817.WY Condition : 20CA0096 3m SHF CHF_ CH165 VERTICAL Detector : Peak Project : 672834 Mode : N



Band 4 5725~5850MHz
WIFI 802.11ac VHT40 (Harmonic @ 3m)



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT40 CH151 5755MHz	
1+2	Horizontal	Vertical
Peak Avg.		



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT40 CH159 5795MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site: 300MT-RV Condition: PCA4098 5m SWF CH159 HORIZONTAL Detector: Peak Project: 87034 Mode: N	 Site: 300MT-RV Condition: PCA4098 5m SWF CH159 VERTICAL Detector: Peak Project: 87034 Mode: N





Band 4 5725~5850MHz
WIFI 802.11ac VHT80 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Date: 2016.08.01 Time: 14:00:00 File: 20160801_140000_01.fcs Condition: PCA80986 5m SWF CH155 HORIZONTAL Detector: Peak Project: 47934 Mode: RT	 Date: 2016.08.01 Time: 14:00:00 File: 20160801_140000_01.fcs Condition: PCA80986 5m SWF CH155 VERTICAL Detector: Peak Project: 47934 Mode: RT



Emission below 1GHz

5GHz WIFI 802.11ac VHT80 (LF)

WIFI	5GHz 5725~5850MHz	
ANT	802.11ac VHT80 LF	
1+2	Horizontal	Vertical
QP / Peak	 Site : 000817-09 Condition : QP 5m LP-ANT.30x180cm HORIZONTAL Detector : Peak Project : 672834 Mode : 1dB	 Site : 000817-09 Condition : QP 5m LP-ANT.30x180cm VERTICAL Detector : Peak Project : 672834 Mode : 1dB

<TXBF Modes>




Band 4 - 5725~5850MHz

WIFI 802.11ac VHT20 (Band Edge @ 3m)




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT20 CH149 5745MHz	
1+2	Horizontal	Fundamental
Peak	Title: 2019-08-08 File: 2019-08-08 Date: 2019-08-08 Time: 10:00:00 Author: 1300MT-4V Condition: PCAW_3C30A_16-04_3m HP-4M 130029 HORIZONTAL Detector: 800Hz 1000 800Hz VSW 3000 6000Hz SWT Auto Project: Peak Mark: 4702H Mark: 48	Title: 2019-08-08 File: 2019-08-08 Date: 2019-08-08 Time: 10:00:00 Author: 1300MT-4V Condition: PCAW3000_3m HP-4M 130029 FUNDAMENTAL Detector: 800Hz 1000 800Hz VSW 3000 6000Hz SWT Auto Project: Peak Mark: 4702H Mark: 48

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT20 CH149 5745MHz	
1+2	Vertical	Fundamental
Peak Avg.	Date: 2018.08.08 PCAN_8204L 15.04 3m HP-4MF 13000 VERTICAL RES: 1000 800Hz VSW 2000 6000Hz SHF Axis Detector Peak Preprod 67023H Mode 68	Date: 2018.08.08 PCAN8204L 3m HP-4MF 13000 VERTICAL RES: 1000 800Hz VSW 2000 6000Hz SHF Axis Detector Peak Preprod 67023H Mode 68





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT20 CH157 5785MHz	
1+2	Horizontal	Fundamental
Peak	 File: 200817-01 Condition: PCAR_05041_15-24 3m HP-44F 13000 HORIZONTAL Reference: 1000 8000Hz VSW 2000 6000Hz SW1-Auto Detector: Peak Preamp: 47dBH Mode: 01	 File: 200817-01 Condition: PCAR_05041_15-24 3m HP-44F 13000 HORIZONTAL Reference: 1000 8000Hz VSW 2000 6000Hz SW1-Auto Detector: Peak Preamp: 47dBH Mode: 01
Peak	 File: 200817-01 Condition: PCAR_05041_15-24 3m HP-44F 13000 HORIZONTAL Reference: 1000 8000Hz VSW 2000 6000Hz SW1-Auto Detector: Peak Preamp: 47dBH Mode: 01	Left blank





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT20 CH157 5785MHz	
1+2	Vertical	Fundamental
Peak		
Peak		Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT20 CH165 5825MHz	
1+2	Horizontal	Fundamental
Peak	 File: 20081101 Condition: PCAN_200811_16_04_3m HP ANT_10000 HORIZONTAL Detector: Peak Preamp: 40dB Mask: 02	 File: 20081101 Condition: PCAN_200811_16_04_3m HP ANT_10000 HORIZONTAL Detector: Peak Preamp: 40dB Mask: 02






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT20 CH165 5825MHz	
1+2	Vertical	Fundamental
Peak Avg.	 Date: 2020/11/17 Condition: 2020/11/17, 10:04, 3m HP-44F, 15000 VERTICAL Detector: Peak Preamp: 67dB Mode: 62	 Date: 2020/11/17 Condition: 2020/11/17, 10:04, 3m HP-44F, 15000 VERTICAL Detector: Peak Preamp: 67dB Mode: 62



Band 4 5725~5850MHz
WIFI 802.11ac VHT40 (Band Edge @ 3m)




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT40 CH151 5755MHz	
1+2	Horizontal	Fundamental
Peak	 File: 200817-01 Condition: PCAN_2024_15.24 3m HP ANT 15000 HORIZONTAL Reference: 100.000000 100.000000 100.000000 Detector: Peak Project: 4702H Mode: 15	 File: 200817-01 Condition: PCAN_2024_15.24 3m HP ANT 15000 HORIZONTAL Reference: 100.000000 100.000000 100.000000 Detector: Peak Project: 4702H Mode: 15
Peak	 File: 200817-01 Condition: PCAN_2024_15.24 3m HP ANT 15000 HORIZONTAL Reference: 100.000000 100.000000 100.000000 Detector: Peak Project: 4702H Mode: 15	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT40 CH151 5755MHz	
1+2	Vertical	Fundamental
Peak	 File: 20081101 Condition: 20081101 10:04 3m HP-ANT 15000 VERTICAL Detector: Peak Preamp: 67DB Mode: 15	 File: 20081101 Condition: 20081101 10:04 3m HP-ANT 15000 VERTICAL Detector: Peak Preamp: 67DB Mode: 15
Peak	 File: 20081101 Condition: 20081101 10:04 3m HP-ANT 15000 VERTICAL Detector: Peak Preamp: 67DB Mode: 15	Left blank




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT40 CH159 5795MHz	
1+2	Horizontal	Fundamental
Peak	Date: 2019-08-08 Condition: 200MHz VHT40 15.15 3m HP 40dB 130dB HORIZONTAL Detector: Peak Project: 5795H Mode: 34	Date: 2019-08-08 Condition: 200MHz VHT40 15.15 3m HP 40dB 130dB FUNDAMENTAL Detector: Peak Project: 5795H Mode: 34
Peak	Date: 2019-08-08 Condition: 200MHz VHT40 15.15 3m HP 40dB 130dB HORIZONTAL Detector: Peak Project: 5795H Mode: 34	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT40 CH159 5795MHz	
1+2	Vertical	Fundamental
Peak	 File: 000MT-01V Condition: PCAR_05041_16.04 3m HP-ANT 15000 VERTICAL Reference: 1000 dBm/Hz VSW 2000 6000Hz SWT-Avg Detector: Peak Preamp: 67DB Mode: SA	 File: 000MT-01V Condition: PCAR_05041_16.04 3m HP-ANT 15000 VERTICAL Reference: 1000 dBm/Hz VSW 2000 6000Hz SWT-Avg Detector: Peak Preamp: 67DB Mode: SA
Peak	 File: 000MT-01V Condition: PCAR_05041_16.04 3m HP-ANT 15000 VERTICAL Reference: 1000 dBm/Hz VSW 2000 6000Hz SWT-Avg Detector: Peak Preamp: 67DB Mode: SA	Left blank



Band 4 5725~5850MHz
WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1+2	Horizontal	Fundamental
Peak	 File: 20191101_01_01 Condition: PCAR_300MHz_15-24 3m HP ANT 13000 HORIZONTAL Detector: Peak Project: 5775H Mode: 15	 File: 20191101_01_01 Condition: PCAR_300MHz_15-24 3m HP ANT 13000 HORIZONTAL Detector: Peak Project: 5775H Mode: 15
Peak	 File: 20191101_01_01 Condition: PCAR_300MHz_15-24 3m HP ANT 13000 HORIZONTAL Detector: Peak Project: 5775H Mode: 15	Left blank





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1+2	Vertical	Fundamental
Peak	 File: 20081101 Condition: 20081101 10:04 3m HP-ANT 15000 VERTICAL Reference: 1000 dBm/Hz VSW 2000 6000Hz SWT Avg Detector: Peak Preamp: 67DB Mode: 66	 File: 20081101 Condition: 20081101 10:04 3m HP-ANT 15000 VERTICAL Reference: 1000 dBm/Hz VSW 2000 6000Hz SWT Avg Detector: Peak Preamp: 67DB Mode: 66
Peak	 File: 20081101 Condition: 20081101 10:04 3m HP-ANT 15000 VERTICAL Reference: 1000 dBm/Hz VSW 2000 6000Hz SWT Avg Detector: Peak Preamp: 67DB Mode: 66	Left blank



Band 4 - 5725~5850MHz



WIFI 802.11ac VHT20 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m																					
ANT	802.11ac VHT20 CH149 5745MHz																					
1+2	Horizontal	Vertical																				
Peak Avg.	 <table><tr><td>Date</td><td>2008/11/17</td></tr><tr><td>Condition</td><td>2008/11/17, 3m, 5745MHz, CH149 HORIZONTAL</td></tr><tr><td>Detector</td><td>Peak</td></tr><tr><td>Project</td><td>572834</td></tr><tr><td>Mode</td><td>IS</td></tr></table>	Date	2008/11/17	Condition	2008/11/17, 3m, 5745MHz, CH149 HORIZONTAL	Detector	Peak	Project	572834	Mode	IS	 <table><tr><td>Date</td><td>2008/11/17</td></tr><tr><td>Condition</td><td>2008/11/17, 3m, 5745MHz, CH149 VERTICAL</td></tr><tr><td>Detector</td><td>Peak</td></tr><tr><td>Project</td><td>572834</td></tr><tr><td>Mode</td><td>IS</td></tr></table>	Date	2008/11/17	Condition	2008/11/17, 3m, 5745MHz, CH149 VERTICAL	Detector	Peak	Project	572834	Mode	IS
	Date	2008/11/17																				
Condition	2008/11/17, 3m, 5745MHz, CH149 HORIZONTAL																					
Detector	Peak																					
Project	572834																					
Mode	IS																					
Date	2008/11/17																					
Condition	2008/11/17, 3m, 5745MHz, CH149 VERTICAL																					
Detector	Peak																					
Project	572834																					
Mode	IS																					





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT20 CH157 5785MHz	
1+2	Horizontal	Vertical
Peak Avg.	Horizontal Peak Spectrum Plot showing Power Spectral Density (dBm/100kHz) vs Frequency (MHz). The plot displays a series of peaks across the 5725-5850 MHz range. The y-axis ranges from -100 to 100 dBm/100kHz. The x-axis ranges from 5725 to 5850 MHz. A red line indicates the noise floor. The plot is titled 'Horizontal Peak Spectrum Plot'. File: 200817.WY Condition: 200817.WY 3m SWF CH157 CH157 HORIZONTAL Detector: Peak Project: 672834 Mode: S1	Vertical Peak Spectrum Plot showing Power Spectral Density (dBm/100kHz) vs Frequency (MHz). The plot displays a series of peaks across the 5725-5850 MHz range. The y-axis ranges from -100 to 100 dBm/100kHz. The x-axis ranges from 5725 to 5850 MHz. A red line indicates the noise floor. The plot is titled 'Vertical Peak Spectrum Plot'. File: 200817.WY Condition: 200817.WY 3m SWF CH157 CH157 VERTICAL Detector: Peak Project: 672834 Mode: S1



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT20 CH165 5825MHz	
1+2	Horizontal	Vertical
Peak Avg.	 File : 200817.WY Condition : 20CA0906 3m SHF CH165 HORIZONTAL Detector : Peak Project : 472934 Mode : 12	 File : 200817.WY Condition : 20CA0906 3m SHF CH165 VERTICAL Detector : Peak Project : 472934 Mode : 12



Band 4 5725~5850MHz
WIFI 802.11ac VHT40 (Harmonic @ 3m)



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT40 CH151 5755MHz	
1+2	Horizontal	Vertical
Peak Avg.	 File : 00001111 Condition : 00001111 (in 5MHz CH151 HORIZONTAL) Detector : Peak Project : 00001111 Mode : 00	 File : 00001111 Condition : 00001111 (in 5MHz CH151 VERTICAL) Detector : Peak Project : 00001111 Mode : 00



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT40 CH159 5795MHz	
1+2	Horizontal	Vertical
Peak Avg.	Horizontal Peak Spectrum Plot showing Power Spectral Density (dBm/100kHz) vs Frequency (MHz). The plot displays a series of peaks across the 5725-5850 MHz range. The y-axis ranges from -100 to 100 dBm/100kHz. The x-axis ranges from 5725 to 5850 MHz. A red line indicates the noise floor. The plot is titled 'Horizontal Peak Spectrum'. File: 200817.VY Condition: 2CA40000 3m SHF CH159 HORIZONTAL Detector: Peak Project: 672834 Mode: SA	Vertical Peak Spectrum Plot showing Power Spectral Density (dBm/100kHz) vs Frequency (MHz). The plot displays a series of peaks across the 5725-5850 MHz range. The y-axis ranges from -100 to 100 dBm/100kHz. The x-axis ranges from 5725 to 5850 MHz. A red line indicates the noise floor. The plot is titled 'Vertical Peak Spectrum'. File: 200817.VY Condition: 2CA40000 3m SHF CH159 VERTICAL Detector: Peak Project: 672834 Mode: SA



Band 4 5725~5850MHz
WIFI 802.11ac VHT80 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Date: 2018.08.08 Site: 300MT-RV Condition: PCAUSP86 3m 5W CHF_13129 HORIZONTAL Detector: Peak Project: 172EM Mode: 1A	 Date: 2018.08.08 Site: 300MT-RV Condition: PCAUSP86 3m 5W CHF_13129 VERTICAL Detector: Peak Project: 172EM Mode: 1A



Emission below 1GHz
5GHz WIFI 802.11ac VHT20 (LF)

WIFI	5GHz 5725~5850MHz	
ANT	802.11ac VHT20 LF	
1+2	Horizontal	Vertical
QP / Peak		


Appendix D. Duty Cycle Plots

Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
1	802.11a	92.86	1430	0.699300699	1kHz
2	802.11a	92.86	1430	0.699300699	1kHz
1+2	802.11a for Ant 1	92.86	1430	0.699300699	1kHz
1+2	802.11a for Ant 2	92.86	1430	0.699300699	1kHz
1	5GHz 802.11n HT20	92.86	1430	0.699300699	1kHz
2	5GHz 802.11n HT20	92.86	1430	0.699300699	1kHz
1+2	5GHz 802.11n HT20 for Ant 1	92.86	1430	0.699300699	1kHz
1+2	5GHz 802.11n HT20 for Ant 2	92.86	1430	0.699300699	1kHz
1	5GHz 802.11n HT40	98.01	-	-	10Hz
2	5GHz 802.11n HT40	98.01	-	-	10Hz
1+2	5GHz 802.11n HT40 for Ant 1	97.91	945	1.058201058	3kHz
1+2	5GHz 802.11n HT40 for Ant 2	98.00	-	-	10Hz
1	5GHz 802.11ac VHT20	92.86	1354.167	0.738461357	1kHz
2	5GHz 802.11ac VHT20	92.28	1341.34	0.745523134	1kHz
1+2	5GHz 802.11ac VHT20 for Ant 1	92.83	1347.756	0.741974067	1kHz
1+2	5GHz 802.11ac VHT20 for Ant 2	92.82	1346.154	0.742857058	1kHz
1	5GHz 802.11ac VHT40	98.02	-	-	10Hz
2	5GHz 802.11ac VHT40	98.21	-	-	10Hz
1+2	5GHz 802.11ac VHT40 for Ant 1	98.02	-	-	10Hz
1+2	5GHz 802.11ac VHT40 for Ant 2	98.03	-	-	10Hz
1	5GHz 802.11ac VHT80	95.95	455.769231	2.194092826	3kHz
2	5GHz 802.11ac VHT80	95.05	461.538462	2.166666665	3kHz
1+2	5GHz 802.11ac VHT80 for Ant 1	95.96	456.730768	2.18947369	3kHz
1+2	5GHz 802.11ac VHT80 for Ant 2	95.96	456.730769	2.189473685	3kHz




<Ant. 1>

802.11a



Date: 18.AUG.2016 20:03:34


802.11n HT20



Date: 18.AUG.2016 21:16:39




802.11n HT40



Date: 18.AUG.2016 22:32:42


802.11ac VHT20



Date: 18.AUG.2016 23:33:33




802.11ac VHT40



Date: 18.AUG.2016 23:41:03

802.11ac VHT80




Date: 18.AUG.2016 23:49:55




<Ant. 2>

802.11a



Date: 18.AUG.2016 20:04:56


802.11n HT20



Date: 18.AUG.2016 21:18:23




802.11n HT40



Date: 18.AUG.2016 22:34:54


802.11ac VHT20



Date: 18.AUG.2016 23:35:37




802.11ac VHT40



Date: 18.AUG.2016 23:42:22

802.11ac VHT80




Date: 18.AUG.2016 23:51:32




MIMO <Ant. 1+2(1)>

802.11a



Date: 18.AUG.2016 20:19:15


802.11n HT20



Date: 18.AUG.2016 21:33:22




802.11n HT40



Date: 18.AUG.2016 22:39:15


802.11ac VHT20



Date: 18.AUG.2016 23:37:50




802.11ac VHT40




Date: 18.AUG.2016 23:44:03


802.11ac VHT80



Date: 18.AUG.2016 23:53:54

MIMO <Ant. 1+2(2)>
802.11a



Date: 18.AUG.2016 20:20:08

802.11n HT20


Date: 18.AUG.2016 21:35:22




802.11n HT40



Date: 18.AUG.2016 22:38:16


802.11ac VHT20



Date: 18.AUG.2016 23:39:03




802.11ac VHT40



Date: 18.AUG.2016 23:45:26

802.11ac VHT80



Date: 18.AUG.2016 23:54:39