

# TEST REPORT

<b>DT&amp;C Co., Ltd.</b> 42, Yurim-ro, 154Beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel : 031-321-2664, Fax : 031-321-1664	Report No : DRTFCC1608-0115 Pages:(1) / (37) page	
---	--	---

## 1. Customer

- Name : GT Telecom Co., Ltd.
- Address : 848-16 Gupyeong-Dong, Gyeongbuk Gumi-City South Korea

## 2. Use of Report : Class II Permissive Change

## 3. Product Name (FCCID) : Bluetooth Stereo Earset (UZCGBH-S3100)



## 4. Date of Test : 2016-08-02 ~ 2016-08-10

## 5. Test Method Used: FCC Part 15 Subpart C.247

## 6. Testing Environment : See appended test report

## 7. Test Result : Pass Fail

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This Test Report cannot be reproduced, except in full.

Affirmation	Tested by Name : Donghyun Kang 	Technical Manager Name : WonJung Lee 
-------------	--	--

2016 . 08 . 11 .

**DT&C Co., Ltd.**

\* If this test report is required to confirmation of authenticity, please contact to [report@dtnc.net](mailto:report@dtnc.net)

## Test Report Version

Test Report No.	Date	Description
DRTFCC1608-0115	Aug. 11, 2016	Initial issue

## Table of Contents

<b>1. General Information</b> .....	<b>4</b>
1.1 Testing Laboratory .....	4
1.2 Details of Applicant .....	4
1.3 Description of EUT .....	4
1.4 Declaration by the applicant / manufacturer .....	4
1.5 Information about the FHSS characteristics .....	5
1.6 Test conditions .....	5
1.7 Test Equipment List.....	6
1.8 Summary of Test Results.....	7
1.9 Conclusion of worst-case and operation mode.....	8
<b>2. Maximum Peak Output Power Measurement</b> .....	<b>9</b>
2.1 Test Setup .....	9
2.2 Limit.....	9
2.3 Test Procedure.....	9
2.4 Test Results .....	10
<b>3. 20 dB BW</b> .....	<b>16</b>
3.1 Test Setup .....	16
3.2 Limit.....	16
3.3 Test Procedure.....	16
3.4 Test Results .....	16
<b>4. Carrier Frequency Separation</b> .....	<b>17</b>
4.1 Test Setup .....	17
4.2 Limit.....	17
4.3 Procedure.....	17
4.4 Test Results .....	17
<b>5. Number of Hopping Frequencies</b> .....	<b>18</b>
5.1 Test Setup .....	18
5.2 Limit.....	18
5.3 Procedure.....	18
5.4 Test Results .....	18
<b>6. Time of Occupancy (Dwell Time)</b> .....	<b>19</b>
6.1 Test Setup .....	19
6.2 Limit.....	19
6.3 Test Procedure.....	19
6.4 Test Results .....	19
<b>7. Transmitter Radiated Spurious Emissions and Conducted Spurious Emission</b> .....	<b>20</b>
7.1 Test Setup .....	20
7.2 Limit.....	20
7.3. Test Procedures.....	21
7.3.1. Test Procedures for Radiated Spurious Emissions .....	21
7.3.2. Test Procedures for Conducted Spurious Emissions.....	22
7.3.3. Test Plot .....	22
7.4. Test Results .....	23
7.4.1. Radiated Emissions .....	23
<b>8. Transmitter AC Power Line Conducted Emission</b> .....	<b>26</b>
8.1 Test Setup .....	26
8.2 Limit.....	26
8.3 Test Procedures.....	26
8.4 Test Results .....	26
<b>9. Antenna Requirement.</b> .....	<b>27</b>
<b>10. Occupied Bandwidth (99 %)</b> .....	<b>28</b>
10.1 Test Setup .....	28
10.2 Limit.....	28
10.3 Test Procedure.....	28
10.4 Test Results .....	28
<b>APPENDIX I</b> .....	<b>29</b>
<b>APPENDIX II</b> .....	<b>30</b>

## 1. General Information

### 1.1 Testing Laboratory

DT&C Co., Ltd.			
	Standard	Site number	Address
FCC	<input checked="" type="checkbox"/>	165783	42, Yurim-ro 154 beon-gil, Cheoin -gu, Yongin-si, Gyeonggi -do, South Korea 449-935
	<input type="checkbox"/>	804488	42, Yurim-ro 154 beon-gil, Cheoin -gu, Yongin-si, Gyeonggi -do, South Korea 449-935
	<input type="checkbox"/>	596748	42, Yurim-ro 154 beon-gil, Cheoin -gu, Yongin-si, Gyeonggi -do, South Korea 449-935
	<input type="checkbox"/>	678747	683-3, Yubang-dong, Cheoin-gu, Yongin-si, Kyeonggi-do, Korea, 449-080
IC	<input type="checkbox"/>	5740A-3	42, Yurim-ro 154 beon-gil, Cheoin -gu, Yongin-si, Gyeonggi -do, South Korea 449-935
	<input type="checkbox"/>	5740A-2	683-3, Yubang-dong, Cheoin-gu, Yongin-si, Kyeonggi-do, Korea, 449-080
<a href="http://www.dtnc.net">www.dtnc.net</a>			
Telephone		: + 82-31-321-2664	
FAX		: + 82-31-321-1664	

### 1.2 Details of Applicant

Applicant : GT Telecom Co., Ltd.  
 Address : 848-16 Gupyeong-Dong, Gyeongbuk Gumi-City South Korea  
 Contact person : Hodong Ryu

### 1.3 Description of EUT

<b>EUT</b>	Bluetooth Stereo Earset
<b>Model Name</b>	GBH-S3100
<b>Add Model Name</b>	GBH-S3300, GBH-S3400, GBH-S3500, Byron BT
<b>Serial Number</b>	Identical prototype
<b>Power Supply</b>	DC 3.7V
<b>Frequency Range</b>	2402 MHz ~ 2480 MHz
<b>Modulation Technique</b>	GFSK, π/4-DQPSK, 8DPSK
<b>Number of Channels</b>	79
<b>Antenna Type</b>	Internal Antenna
<b>Antenna Gain</b>	PK : 3.29 dBi

### 1.4 Declaration by the applicant / manufacturer

- NA

## 1.5 Information about the FHSS characteristics

- This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following :
  - A) The hopping sequence is pseudorandom
  - B) All channels are used equally on average
  - C) The receiver input bandwidth equals the transmit bandwidth
  - D) The receiver hops in sequence with the transmit signal
- 15.247(g) : In accordance with the Bluetooth Industry Standard, the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.
- 15.247(h) : In accordance with the Bluetooth Industry Standard, the system does not coordinate its channels selection / hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.
- 15.247(h) : The EUT employs Adaptive Frequency Hopping (AFH) which identifies sources of interference namely devices operating in 802.11 WLAN and excludes them from the list of available channels. The process of re-mapping reduces the number of test channels from 79 channels to a minimum number of 20 channels.

## 1.6 Test conditions

Ambient Condition	
▪ Temperature	+24 °C ~ +25 °C
▪ Relative Humidity	42 % ~ 44 %

## 1.7 Test Equipment List

Type	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next.Cal.Date (yy/mm/dd)	S/N
MXA Signal Analyzer	Agilent Technologies	N9020A	16/03/11	17/03/11	MY50200828
Dynamic Measurement DC Source	Agilent Technologies	66332A	15/10/19	16/10/19	MY43000394
DC Power Supply	SMtechno	SDP30-5D	15/09/23	16/09/23	305DMG291
Thermohygrometer	BODYCOM	BJ5478	16/04/22	17/04/22	120612-1
Power Meter & Wide Bandwidth Sensor	Anritsu	ML2495A	15/10/20	16/10/20	1338003
		MA2490A			1249304
Loop Antenna	Schwarzbeck	FMZB1513	16/04/22	18/04/22	1513-128
BILOG ANTENNA	Schwarzbeck	CBL6112B	14/12/10	16/12/10	2737
Horn Antenna	ETS-LINDGREN	3117	16/05/03	17/05/03	00140394
Horn Antenna	A.H.Systems Inc.	SAS-574	15/04/30	17/04/30	154
Highpass Filter	Wainwright Instruments	WHKX12-2580-3000-18000-80SS	15/09/23	16/09/23	3
Highpass Filter	Wainwright Instruments	WHNX6-6320-8000-26500-40CC	15/09/23	16/09/23	1
PreAmplifier	Agilent	8449B	16/02/24	17/02/24	3008A00370
Low Noise Pre Amplifier	TSJ	MLA-010K01-B01-27	16/03/10	17/03/10	1844539
EMI Test Receiver	Rohde Schwarz	ESU	15/07/14	16/07/14	100469
Signal Generator	Rohde Schwarz	SMF100A	16/06/23	17/06/23	102341
Multimeter	HP	34401A	16/02/25	17/02/25	3146A13475

## 1.8 Summary of Test Results

FCC Part RSS Std.	Parameter	Limit (Using in 2400~ 2483.5 MHz)	Test Condition	Status Note 1
15.247(a) RSS-247(5.1)	Carrier Frequency Separation	>= 20 dB BW or >= Two thirds of the 20 dB BW, whichever is greater.	Conducted	NT Note4
	Number of Hopping Frequencies	>= 15 hops		NT Note4
	20 dB Bandwidth	N/A		NT Note4
	Dwell Time	=< 0.4 seconds		NT Note4
15.247(b) RSS-247(5.4)	Transmitter Output Power	<b>For FCC</b> =< 1 Watt , if CHs >= 75 Others = < 0.125 W <b>For IC</b> if CHs >= 75 =< 1 Watt For Conducted Power =< 4 Watt For e.i.r.p, Others =< 0.125 W For Conducted Power. =< 0.5 Watt For e.i.r.p	Conducted	C
15.247(d) RSS-247(5.5)	Conducted Spurious Emissions	The radiated emission to any 100 kHz of out-band shall be at least 20 dB below the highest in-band spectral density.		NT Note4
RSS Gen(6.6)	Occupied Bandwidth (99 %)	N/A	Radiated	NA
15.205 & 209 RSS-247(5.5) RSS-Gen (8.9 & 8.10)	Radiated Spurious Emissions	FCC 15.209 Limits RSS-Gen 8.9		C Note2
15.207 RSS-Gen(8.8)	AC Conducted Emissions	FCC 15.207 Limits	AC Line Conducted	NT Note4
15.203 RSS-Gen(8.3)	Antenna Requirements	FCC 15.203	-	C
Note 1 : <b>C</b> = Comply <b>NC</b> = Not Comply <b>NT</b> = Not Tested <b>NA</b> = Not Applicable				
Note 2 : This test item was performed in each axis and the worst case data was reported.				
Note 3 : The sample was tested according to the following specifications : - ANSI C63.10-2013				
Note 4: This model is Class II Permissive Change. Therefore this test was performed "Transmitter Output Power" and "Radiated Spurious Emissions".				

## 1.9 Conclusion of worst-case and operation mode

The EUT has three type of modulation (GFSK,  $\pi/4$ DQPSK and 8DPSK).

Therefore all applicable requirements were tested with all the modulations.

The field strength of spurious emission was measured in three orthogonal EUT positions (X-axis, Y-axis and Z-axis).

Tested frequency information,

- Hopping Function : Enable

	TX Frequency (MHz)	RX Frequency (MHz)
<b>Hopping Band</b>	2402 ~ 2480	2402 ~ 2480

- Hopping Function : Disable

	TX Frequency (MHz)	RX Frequency (MHz)
<b>Lowest Channel</b>	2402	2402
<b>Middle Channel</b>	2441	2441
<b>Highest Channel</b>	2480	2480

## 2. Maximum Peak Output Power Measurement

### 2.1 Test Setup

Refer to the APPENDIX I.

### 2.2 Limit

#### FCC Requirements

The maximum peak output power of the intentional radiator shall not exceed the following :

1. §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.
2. §15.247(b)(1), For frequency hopping systems operating in the 2400 – 2483.5 MHz employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725 – 5805 MHz band : 1 Watt.

#### IC Requirements

1. RSS-247(5.4), For FHSS operating in the band 2400 - 2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W and the e.i.r.p. shall not exceed 4 W if the hopset uses 75 or more hopping channels the maximum peak conducted output power shall not exceed 0.125 W and the e.i.r.p. shall not exceed 0.5 W if the hopset uses less than 75 hopping channels

### 2.3 Test Procedure

1. The RF output power was measured with a spectrum analyzer connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate center frequency, A spectrum analyzer was used to record the shape of the transmit signal.

2. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using ;

Span = approximately 5 times of the 20 dB bandwidth, centered on a hopping channel

RBW  $\geq$  20 dB BW

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold


## 2.4 Test Results

Modulation	Tested Channel	Peak Output Power	
		dBm	mW
<u>GFSK</u>	Lowest	7.46	5.572
	Middle	<b>8.22</b>	<b>6.637</b>
	Highest	8.02	6.339
<u><math>\pi/4</math>DQPSK</u>	Lowest	5.60	3.631
	Middle	<b>7.34</b>	<b>5.420</b>
	Highest	7.21	5.260
<u>8DPSK</u>	Lowest	5.85	3.846
	Middle	<b>7.56</b>	<b>5.702</b>
	Highest	7.40	5.495

Note 1 : See next pages for actual measured spectrum plots.


## Peak Output Power



## **Lowest Channel & Modulation : GFSK**





## Peak Output Power

## **Middle Channel & Modulation : GFSK**




**Peak Output Power****Highest Channel & Modulation : GFSK****Peak Output Power****Lowest Channel & Modulation : π/4DQPSK**

**Peak Output Power****Middle Channel & Modulation :  $\pi/4$ DQPSK****Peak Output Power****Highest Channel & Modulation :  $\pi/4$ DQPSK**


## Peak Output Power

## **Lowest Channel & Modulation : 8DPSK**




## Peak Output Power

## **Middle Channel & Modulation : 8DPSK**



## Peak Output Power

## Highest Channel &amp; Modulation : 8DPSK



## 3. 20 dB BW

### 3.1 Test Setup

Refer to the APPENDIX I.

### 3.2 Limit

Limit : Not Applicable

### 3.3 Test Procedure

1. The 20 dB bandwidth were measured with a spectrum analyzer connected to RF antenna Connector (conducted measurement) while EUT was operating in transmit mode. The analyzer center frequency was set to the EUT carrier frequency, using the analyzer.
2. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using below setting: RBW shall be in the range of 1% to 5% of the 20 dB bandwidth and  $VBW \geq 3 \times RBW$ , Span = between two times and five times the 20 dB bandwidth.

### 3.4 Test Results

**NT**

## 4. Carrier Frequency Separation

## 4.1 Test Setup

Refer to the APPENDIX I.

## 4.2 Limit

Limit :  $\geq$  25 kHz or  $\geq$  Two-Thirds of the 20 dB BW whichever is greater.

### 4.3 Procedure

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

The spectrum analyzer is set to :

Span = wide enough to capture the peaks of two adjacent channels

**RBW** = Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.

VBW  $\geq$  RBW      Sweep = auto  
Detector function = peak      Trace = max hold

## 4.4 Test Results

NT

## 5. Number of Hopping Frequencies

### 5.1 Test Setup

Refer to the APPENDIX I.

### 5.2 Limit

Limit :  $\geq 15$  hops

### 5.3 Procedure

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

To get higher resolution, two frequency ranges for FH mode within the 2400 ~ 2483.5 MHz were examined.

The spectrum analyzer is set to :

Span for FH mode = 50 MHz      Start Frequency = 2391.5 MHz,   Stop Frequency = 2441.5 MHz  
    Start Frequency = 2441.5 MHz,   Stop Frequency = 2491.5 MHz

Span for AFH mode = 30 MHz      Start Frequency = 2396.0 MHz,   Stop Frequency = 2426.0 MHz

RBW = To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW  $\geq$  RBW      Sweep = auto

Detector function = peak      Trace = max hold

### 5.4 Test Results

NT

#### - Minimum Standard :

At least 15 hopes

## 6. Time of Occupancy (Dwell Time)

### 6.1 Test Setup

Refer to the APPENDIX I.

### 6.2 Limit

The maximum permissible time of occupancy is 400 ms within a period of 400 ms multiplied by the number of hopping channels employed.

### 6.3 Test Procedure

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to :

Center frequency = 2441 MHz

Span = zero

RBW = 1 MHz (RBW shall be  $\leq$  channel spacing and where possible RBW should be set  $\gg 1 / T$ , where  $T$  is the expected dwell time per channel)

VBW  $\geq$  RBW

Detector function = peak

Trace = max hold

### 6.4 Test Results

**NT**

## 7. Transmitter Radiated Spurious Emissions and Conducted Spurious Emission

### 7.1 Test Setup

Refer to the APPENDIX I.

### 7.2 Limit

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in section §15.209(a) is not required. In addition, radiated emission which in the restricted band, as defined in section §15.205(a), must also comply the radiated emission limits specified in section §15.209(a) (see section §15.205(c))

According to § 15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table

Frequency (MHz)	Limit (uV/m)	Measurement Distance (meter)
0.009 ~ 0.490	2400/F (kHz)	300
0.490 ~ 1705	24000/F (kHz)	30
1705 ~ 30.0	30	30
30 ~ 88	100 **	3
88 ~ 216	150 **	3
216 ~ 960	200 **	3
Above 960	500	3

\*\* Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 - 72 MHz, 76 - 88 MHz, 174 - 216 MHz or 470 - 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

According to § 15.205(a) and (b), only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	MHz	GHz	GHz
0.009 ~ 0.110	8.41425 ~ 8.41475	108 ~ 121.94	1300 ~ 1427	4.5 ~ 5.15	14.47 ~ 14.5
0.495 ~ 0.505	12.29 ~ 12.293	123 ~ 138	1435 ~ 1626.5	5.35 ~ 5.46	15.35 ~ 16.2
2.1735 ~ 2.1905	12.51975 ~ 12.52025	149.9 ~ 150.05	1645.5 ~ 1646.5	7.25 ~ 7.75	17.7 ~ 21.4
4.125 ~ 4.128	12.57675 ~ 12.57725	156.52475 ~ 156.52525	1660 ~ 1710	8.025 ~ 8.5	22.01 ~ 23.12
4.17725 ~ 4.17775	13.36 ~ 13.41	156.7 ~ 156.9	1718.8 ~ 1722.2	9.0 ~ 9.2	23.6 ~ 24.0
4.20725 ~ 4.20775	16.42 ~ 16.423	162.0125 ~ 167.17	2200 ~ 2300	9.3 ~ 9.5	31.2 ~ 31.8
6.215 ~ 6.218	16.69475 ~ 16.69525	167.72 ~ 173.2	2310 ~ 2390	10.6 ~ 12.7	36.43 ~ 36.5
6.26775 ~ 6.26825	16.80425 ~ 16.80475	240 ~ 285	2483.5 ~ 2500	13.25 ~ 13.4	Above 38.6
6.31175 ~ 6.31225	25.5 ~ 25.67	322 ~ 335.4	2655 ~ 2900		
8.291 ~ 8.294	37.5 ~ 38.25	399.90 ~ 410	3260 ~ 3267		
8.362 ~ 8.366	73 ~ 74.6	608 ~ 614	3332 ~ 3339		
8.37625 ~ 8.38675	74.8 ~ 75.2	960 ~ 1240	3345.8 ~ 3358		
			3600 ~ 4400		

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

## 7.3. Test Procedures

### 7.3.1. Test Procedures for Radiated Spurious Emissions

1. The EUT is placed on a non-conductive table. For emission measurements at or below 1 GHz, the table height is 80 cm. For emission measurements above 1 GHz, the table height is 1.5 m. The table was rotated 360 degrees to determine the position of the highest radiation.
2. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 1 or 3 meter away from the interference-receiving antenna.
3. For measurements above 1GHz absorbers are placed on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1 GHz, the absorbers are removed.
4. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
5. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
6. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
7. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.

NOTE 2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1 GHz.

NOTE 3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 1 kHz for Average detection (AV) at frequency above 1 GHz.

### 7.3.2. Test Procedures for Conducted Spurious Emissions

1. The transmitter output was connected to the spectrum analyzer.
2. The **reference level** of the fundamental frequency was measured with the spectrum analyzer using RBW = 100 kHz, VBW = 300 kHz.
3. The conducted spurious emission was tested each ranges were set as below.

**Frequency range : 9 kHz ~ 30 MHz**

RBW = 100 kHz, VBW = 300 kHz, SWEEP TIME = AUTO, DETECTOR = PEAK, TRACE = MAX HOLD, SWEEP POINT : 40001

**Frequency range : 30 MHz ~ 10 GHz, 10 GHz ~ 25 GHz**

RBW = 1 MHz, VBW = 3 MHz, SWEEP TIME = AUTO, DETECTOR = PEAK, TRACE = MAX HOLD, SWEEP POINT : 40001

**LIMIT LINE = 20 dB below of the reference level of above measurement procedure Step 2. (RBW = 100 kHz, VBW = 300 kHz)**

If the emission level with above setting was close to the limit (ie, less than 3 dB margin) then zoom scan is required using RBW = 100 kHz, VBW = 300 kHz, SPAN = 100 MHz and BINS = 2001 to get accurate emission level within 100 kHz BW.

Also the path loss for conducted measurement setup was used as described on the Appendix I of this test report.

### 7.3.3. Test Plot

Refer to the APPENDIX II

## 7.4. Test Results

### 7.4.1. Radiated Emissions

#### 9 kHz ~ 25 GHz Data (Modulation : GFSK)

- Lowest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2375.93	V	Z	PK	50.19	0.66	N/A	N/A	50.85	74.00	23.15
2375.97	V	Z	AV	41.34	0.66	-24.79	N/A	17.21	54.00	36.79
4804.27	H	X	PK	58.59	7.63	N/A	N/A	66.22	74.00	7.78
4804.03	H	X	AV	57.07	7.63	-24.79	N/A	39.91	54.00	14.09

- Middle Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4882.32	H	X	PK	57.31	7.30	N/A	N/A	64.61	74.00	9.39
4882.03	H	X	AV	56.36	7.30	-24.79	N/A	38.87	54.00	15.13

- Highest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.51	V	X	PK	49.39	1.10	N/A	N/A	50.49	74.00	23.51
2483.51	V	X	AV	39.08	1.10	-24.79	N/A	15.39	54.00	38.61
4959.70	V	Y	PK	55.84	7.48	N/A	N/A	63.32	74.00	10.68
4960.01	V	Y	AV	53.29	7.48	-24.79	N/A	35.98	54.00	18.02

- Note

1. No other spurious and harmonic emissions were found greater than listed emissions on above table.

2. Information of Distance Factor

For finding emissions, the test distance might be reduced from 3m to 1m. In this case, the distance factor(-9.54dB) is applied to the result.

- Calculation of distance factor =  $20 \log( \text{applied distance} / \text{required distance} ) = 20 \log( 1 \text{ m} / 3 \text{ m} ) = -9.54 \text{ dB}$

When distance factor is "N/A", the distance is 3 m and distance factor is not applied.

3. D.C.F Calculation. (D.C.F = Duty Cycle Correction Factor)

- Time to cycle through all channels =  $\Delta t = T \text{ [ms]} \times 20 \text{ minimum hopping channels}$ , where  $T = \text{pulse width} = 2.88 \text{ ms}$

-  $100 \text{ ms} / \Delta t \text{ [ms]} = H \rightarrow \text{Round up to next highest integer, to account for worst case, } H' = 100 / ( 2.88 \times 20 ) = 1.736 \approx 2$

- The Worst Case Dwell Time =  $T \text{ [ms]} \times H' = 2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$

-  $D.C.F = 20 \log( \text{Worst Case Dwell Time} / 100 \text{ ms} ) \text{ dB} = 20 \log( 5.76 / 100 ) = -24.79 \text{ dB}$

4. Sample Calculation.

Margin = Limit – Result / Result = Reading + T.F + D.C.F / T.F = AF + CL – AG

Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain.

**9 kHz ~ 25 GHz Data (Modulation :  $\pi/4$ DQPSK)**
**▪ Lowest Channel**

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2375.52	V	Z	PK	50.40	0.66	N/A	N/A	51.06	74.00	22.94
2375.97	V	Z	AV	38.82	0.66	-24.79	N/A	14.69	54.00	39.31
4804.21	H	X	PK	55.60	7.63	N/A	N/A	63.23	74.00	10.77
4804.12	H	X	AV	49.14	7.63	-24.79	N/A	31.98	54.00	22.02

**▪ Middle Channel**

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4882.11	V	Y	PK	54.18	7.30	N/A	N/A	61.48	74.00	12.52
4882.03	V	Y	AV	48.06	7.30	-24.79	N/A	30.57	54.00	23.43

**▪ Highest Channel**

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.54	H	Y	PK	51.30	1.10	N/A	N/A	52.40	74.00	21.60
2483.54	H	Y	AV	39.38	1.10	-24.79	N/A	15.69	54.00	38.31
4959.53	H	X	PK	55.24	7.48	N/A	N/A	62.72	74.00	11.28
4960.01	H	X	AV	49.28	7.48	-24.79	N/A	31.97	54.00	22.03

**▪ Note**

1. No other spurious and harmonic emissions were found greater than listed emissions on above table.

2. Information of Distance Factor

For finding emissions, the test distance might be reduced from 3m to 1m. In this case, the distance factor(-9.54dB) is applied to the result.

- Calculation of distance factor =  $20 \log( \text{applied distance} / \text{required distance} ) = 20 \log( 1 \text{ m} / 3 \text{ m} ) = -9.54 \text{ dB}$

When distance factor is "N/A", the distance is 3 m and distance factor is not applied.

3. D.C.F Calculation. (D.C.F = Duty Cycle Correction Factor)

- Time to cycle through all channels =  $\Delta t = T \text{ [ms]} \times 20 \text{ minimum hopping channels}$ , where  $T = \text{pulse width} = 2.88 \text{ ms}$

-  $100 \text{ ms} / \Delta t \text{ [ms]} = H \rightarrow \text{Round up to next highest integer, to account for worst case, } H' = 100 / ( 2.88 \times 20 ) = 1.736 \approx 2$

- The Worst Case Dwell Time =  $T \text{ [ms]} \times H' = 2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$

- D.C.F =  $20 \log( \text{Worst Case Dwell Time} / 100 \text{ ms} ) \text{ dB} = 20 \log( 5.76 / 100 ) = -24.79 \text{ dB}$

4. Sample Calculation.

Margin = Limit – Result / Result = Reading + T.F + D.C.F / T.F = AF + CL – AG

Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain.

**9 kHz ~ 25 GHz Data (Modulation : 8DPSK)**
**▪ Lowest Channel**

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2376.16	H	Z	PK	49.32	0.66	N/A	N/A	49.98	74.00	24.02
2376.04	H	Z	AV	38.66	0.66	-24.79	N/A	14.53	54.00	39.47
4803.84	H	X	PK	55.91	7.63	N/A	N/A	63.54	74.00	10.46
4804.05	H	X	AV	49.87	7.63	-24.79	N/A	32.71	54.00	21.29

**▪ Middle Channel**

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4881.63	V	Y	PK	54.11	7.30	N/A	N/A	61.41	74.00	12.59
4882.02	V	Y	AV	48.50	7.30	-24.79	N/A	31.01	54.00	22.99

**▪ Highest Channel**

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.52	V	X	PK	49.22	1.10	N/A	N/A	50.32	74.00	23.68
2483.51	V	X	AV	39.62	1.10	-24.79	N/A	15.93	54.00	38.07
4959.96	H	X	PK	54.65	7.48	N/A	N/A	62.13	74.00	11.87
4960.00	H	X	AV	48.66	7.48	-24.79	N/A	31.35	54.00	22.65

**▪ Note**

1. No other spurious and harmonic emissions were found greater than listed emissions on above table.

2. Information of Distance Factor

For finding emissions, the test distance might be reduced from 3m to 1m. In this case, the distance factor(-9.54dB) is applied to the result.

- Calculation of distance factor =  $20 \log( \text{applied distance} / \text{required distance} ) = 20 \log( 1 \text{ m} / 3 \text{ m} ) = -9.54 \text{ dB}$

When distance factor is "N/A", the distance is 3 m and distance factor is not applied.

3. D.C.F Calculation. (D.C.F = Duty Cycle Correction Factor)

- Time to cycle through all channels =  $\Delta t = T \text{ [ms]} \times 20 \text{ minimum hopping channels}$ , where  $T = \text{pulse width} = 2.88 \text{ ms}$

-  $100 \text{ ms} / \Delta t \text{ [ms]} = H \rightarrow \text{Round up to next highest integer, to account for worst case, } H' = 100 / ( 2.88 \times 20 ) = 1.736 \approx 2$

- The Worst Case Dwell Time =  $T \text{ [ms]} \times H' = 2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$

-  $D.C.F = 20 \log( \text{Worst Case Dwell Time} / 100 \text{ ms} ) \text{ dB} = 20 \log( 5.76 / 100 ) = -24.79 \text{ dB}$

4. Sample Calculation.

Margin = Limit – Result / Result = Reading + T.F + D.C.F / T.F = AF + CL – AG

Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain.

## 8. Transmitter AC Power Line Conducted Emission

### 8.1 Test Setup

**Not Applicable**

### 8.2 Limit

According to §15.207(a) for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 uH/50 ohm line impedance stabilization network (LISN).

Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

\* Decreases with the logarithm of the frequency

### 8.3 Test Procedures

Conducted emissions from the EUT were measured according to the ANSI C63.10.

1. The test procedure is performed in a 6.5 m × 3.5 m × 3.5 m (L × W × H) shielded room. The EUT along with its peripherals were placed on a 1.0 m (W) × 1.5 m (L) and 0.8 m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.
2. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room.
3. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.
4. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.

### 8.4 Test Results

**NT**

## 9. Antenna Requirement

Describe how the EUT complies with the requirement that either its antenna is permanently attached, or that it employs a unique antenna connector, for every antenna proposed for use with the EUT.

**Conclusion: Comply**

**The antenna is permanently attached. (Refer to Internal photo file.)**

**- Minimum Standard :**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions.

## 10. Occupied Bandwidth (99 %)

### 10.1 Test Setup

Refer to the APPENDIX I.

### 10.2 Limit

Limit : Not Applicable

### 10.3 Test Procedure

The 99 % power bandwidth was measured with a calibrated spectrum analyzer.

The resolution bandwidth (RBW) shall be in the range of 1 % to 5 % of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately  $3 \times$  RBW.

Spectrum analyzer plots are included on the following pages.


### 10.4 Test Results

**Not Applicable**


## APPENDIX I

### Test set up diagrams

#### ▪ Radiated Measurement



#### ▪ Conducted Measurement



#### Path loss information

Frequency (GHz)	Path Loss (dB)	Frequency (GHz)	Path Loss (dB)
0.03	0.18	15	5.16
1	1.08	20	5.61
2.402 & 2.441 & 2.480	1.75	25	7.00
5	2.57	-	-
10	4.13	-	-

Note 1 : The path loss from EUT to Spectrum analyzer were measured and used for test.

Path loss ( S/A's Correction factor) = Cable A


## APPENDIX II

### Restricted band edge (Test plot of radiated)

Note: The offset was not include in test plot. (Reading value). The results refer to the clause 7.4.1.


GFSK & Lowest & Z & Ver

Detector Mode : PK




GFSK & Lowest & Z & Ver

Detector Mode : AV



## GFSK &amp; Highest &amp; X &amp; Ver

Detector Mode : PK




## GFSK &amp; Highest &amp; X &amp; Ver

Detector Mode : AV




## π/4DQPSK &amp; Lowest &amp; Z &amp; Ver

Detector Mode : PK




## π/4DQPSK &amp; Lowest &amp; Z &amp; Ver

Detector Mode : AV



## π/4DQPSK &amp; Highest &amp; Y &amp; Hor

Detector Mode : PK




## π/4DQPSK &amp; Highest &amp; Y &amp; Hor

Detector Mode : AV



## 8DPSK &amp; Lowest &amp; Z &amp; Hor

Detector Mode : PK




## 8DPSK &amp; Lowest &amp; Z &amp; Hor

Detector Mode : AV




## 8DPSK &amp; Highest &amp; X &amp; Ver

Detector Mode : PK



## 8DPSK &amp; Highest &amp; X &amp; Ver

Detector Mode : AV




## Spurious emission.(Plot of radiated)

Note: Attached plot of worst data.

The offset was not include in test plot.(Reading value) The results refer to the clause 7.4.1.


### GFSK & Lowest & X & Hor

Detector Mode : PK



### $\pi/4$ DQPSK & Lowest & X & Hor

Detector Mode : PK



## 8DPSK &amp; Lowest &amp; X &amp; Hor

Detector Mode : PK

