

FCC PART 15.249
MEASUREMENT AND TEST REPORT
FOR

SHENZHEN XIANDAO ELECTRONICS CO., LTD.

**Suite 203-204, 1st Building Overseas Chinese High-Tech Venture Park,
Longgang, Shenzhen, Guangdong, China**

FCC ID: UZGT618

Report Concerns: Original Report	Equipment Type: Leadsoft open wireless interactive whiteboard
Model: <u>T618</u>	
Report No.: <u>STR07018045I</u>	
Test/Witness Engineer: <u>Innaz Lee</u>	
Test Date: <u>2007-01-27</u>	
Prepared By: Shenzhen SEM.Test Compliance Service Co., Ltd Room 609-610, Baotong Building, Baomin 1 st Road, Baoan District, Shenzhen, Guangdong, P.R.C. (518133)	
Approved & Authorized By:  _____ PSQ Manager / Jandy So	

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permission by SEM.Test Compliance Service Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS	3
1.3 RELATED SUBMITTAL(S)/GRANT(S).....	3
1.4 TEST METHODOLOGY	4
1.5 TEST FACILITY	4
1.6 EUT EXERCISE SOFTWARE	4
1.7 ACCESSORIES EQUIPMENT LIST AND DETAILS	4
1.8 EUT CABLE LIST AND DETAILS.....	4
2. SUMMARY OF TEST RESULTS	5
3. §15.203 - ANTENNA REQUIREMENT	6
3.1 STANDARD APPLICABLE	6
3.2 TEST RESULT	6
4. §15.205, §15.209, §15.249 (A)- RADIATED EMISSION.....	7
4.1 MEASUREMENT UNCERTAINTY	7
4.2 STANDARD APPLICABLE	7
4.3 TEST EQUIPMENT LIST AND DETAILS	8
4.4 TEST PROCEDURE.....	8
4.5 CORRECTED AMPLITUDE & MARGIN CALCULATION	9
4.6 ENVIRONMENTAL CONDITIONS	9
4.7 SUMMARY OF TEST RESULTS/PLOTS.....	9
5. §15.249(B) OUT OF BAND EMISSIONS	12
5.1 STANDARD APPLICABLE	12
5.2 TEST EQUIPMENT LIST AND DETAILS	12
5.3 TEST PROCEDURE.....	12
5.4 ENVIRONMENTAL CONDITIONS	12
5.5 SUMMARY OF TEST RESULTS/PLOTS.....	12

EXHIBITION INCLUDING:

- EXHIBIT 1- FCC ID LABELING
- EXHIBIT 2 - EUT EXTERNAL PHOTOGRAPHS
- EXHIBIT 3 - EUT INTERNAL PHOTOGRAPHS
- EXHIBIT 4 - TEST SETUP PHOTOGRAPHS
- EXHIBIT 5 - BLOCK DIARGRAM
- EXHIBIT 6 - OPERATION DESCRIPTIONS
- EXHIBIT 7 - USERS MANUAL

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Shenzhen Xiandao Electronics Co., Ltd.
Address of applicant: Suite 203-204, 1st Building Overseas Chinese High-Tech Venture Park, Longgang, Shenzhen, Guangdong, China

Manufacturer: Shenzhen Xiandao Electronics Co., Ltd.
Address of manufacturer: Suite 203-204, 1st Building Overseas Chinese High-Tech Venture Park, Longgang, Shenzhen, Guangdong, China

General Description of E.U.T

Items	Description
EUT Description:	Leadsoft open wireless interactive whiteboard
Trade Name:	/
Model No.:	T618
Rated Voltage:	DC 3V Battery
Output Power:	<0 dBm
Frequency Range:	2432 MHz
No. of Channel:	1
Antenna Type:	Integral Antenna
Size:	32.0X26.0X2.80 cm

For more information refer to the circuit diagram form and the user's manual.

The test data gathered are from a production sample, provided by the manufacturer.

1.2 Test Standards

The following report is prepared on behalf of Shenzhen Xiandao Electronics Co., Ltd. in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.249 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.249 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Related Submittal(s)/Grant(s)

No Related Submittal(s).

1.4 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

The equipment under test (EUT) was configured to measure its highest possible emission level. Test is carried out with transmitting mode, accordingly in reference to the Operating Instructions.

1.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

United States of American Federal Communications Commission (FCC), and the registration number is **274801**(semi anechoic chamber).

Voluntary Control Council for Interference by Information Technology Equipment (VCCI), and the registration number is **R-1966** (semi anechoic chamber).

Industry Canada (IC), and the registration number is **IC4174**.

All measurement required was performed at laboratory of Shenzhen Academy of Metrology and Quality Inspection, Bldg. of Metrology & Quality Inspection, Longzhu Road, Nanshan District, Shenzhen, Guangdong, China.

1.6 EUT Exercise Software

The EUT exercise program used during the testing was designed to exercise the system components. The test software is started while the whole system is on.

1.7 Accessories Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

1.8 EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Cord/Without Cord
/	/	/	/

2. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.203	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.209	Radiated Emission	Compliant
§15.249(a)	Field Strength	Compliant
§15.249(d)	Out of Band Emission	Compliant

3. §15.203 - ANTENNA REQUIREMENT

3.1 Standard Applicable

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has a permanent antenna, fulfill the requirement of this section.

4. §15.205, §15.209, §15.249 (a)- RADIATED EMISSION

4.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is ± 3.0 dB.

4.2 Standard Applicable

According to §15.249(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Field strength of fundamental (milli-volts/meter)	Field strength of fundamental (micro-volts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply.

According to §15.205 and §15.209 the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

FIELD STRENGTH of Fundamental: 902-928MHz 2.4-2.4835GHz 127.38dBuV/m @3m	FIELD STRENGTH of Harmonics: 127.37dBuV/m @3m 54 dBuV/m @3m	Section 15.209: 30 - 88 MHz 40 dBuV/m @3M 88 -216 MHz 43.5 dBuV/m @3M 216 -960 MHz 46 dBuV/m @3M Above 960 MHz 54dBuV/m @3M

EMISSIONS RADIATED OUTSIDE OF THE SPECIFIED FREQUENCY BANDS, EXCEPT FOR HARMONICS, SHALL BE ATTENUATED BY AT LEAST 20 dB BELOW THE LEVEL OF THE FUNDAMENTAL OR TO THE GENERAL RADIATED EMISSION LIMITS IN 15.209, WHICHEVER IS THE LESSER ATTENUATION.

Emissions that fall in the restricted bands (15.205) must be less than 54dBuV/m otherwise the spurious and harmonics must be attenuated by at least 20dB.

4.3 Test Equipment List and Details


Manufacturer	Description	Model	Serial Number	Cal. Date	Due. Date
Rohde & Schwarz	EMI Test Receiver	ESI26	830245/009	2006-1-26	2007-1-25
ETS	Multi_Device Controller	2090	57230	2006-1-26	2007-1-25
ETS	Receiver Antenna	2175	57337	2006-1-26	2007-1-25
ETS	50 ohm Coaxial Cable	SUCOFLEX 104	25498514	2006-1-26	2007-1-25
Rohde & Schwarz	Horn Antenna	HF906	100014	2006-1-26	2007-1-25
Albatross Projects	3m chamber	9X6X6	----	2006-1-24	2007-1-25

Statement of Traceability: All calibrations have been performed per the NVLAP requirements traceable to the NIST.

4.4 Test Procedure

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.205 15.249(a) and FCC Part 15.209 Limit.

Testing is carried out with 3-orthogonal axis for collecting the worse case.



4.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

4.6 Environmental Conditions

Temperature:	21° C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

4.7 Summary of Test Results/Plots


According to the data below, the FCC Part 15.205, 15.209 and 15.249 standards, and had the worst margin of:


-2.80 dB μ V at 4864.00 MHz in the Horizontal polarization, 30 MHz to 25 GHz, 3Meters

Frequency MHz	Meter Reading dBuV	Meter Reading Detector PK/ QP/AV	Direction Degree	Height Meter	Polar H / V	Antenna Loss dB	Cable loss dB	Amplifier Gain dB	FCC Part 15.249 & 15.209		
									Limit dBuV/m	Margin dB	
7296.0	30.4	AV	98	1.2	H	36.3	6	33.40	39.3	54.0	-14.7
4864.0	33.8	AV	45	1.2	H	32.5	4.9	32.00	39.2	54.0	-14.8
7296.0	29.7	AV	43	1.0	V	36.3	6	33.40	38.6	54.0	-15.4
144.0	38.5	QP	66	1.0	H	13.8	1.1	25.58	27.8	43.5	-15.7
4864.0	32.7	AV	90	1.5	V	32.5	4.9	32.00	38.1	54.0	-15.9
204.1	38.5	QP	135	1.2	H	12.6	1.3	25.18	27.2	43.5	-16.3
204.1	35.5	QP	60	2.0	V	12.6	1.3	25.18	24.2	43.5	-19.3
216.4	38.5	QP	45	1.0	H	11.4	1.3	25.06	26.1	46.0	-19.9
144.0	33.7	QP	56	1.4	V	13.8	1.1	25.58	23.0	43.5	-20.5
216.4	35.8	QP	266	1.0	V	11.4	1.3	25.06	23.4	46.0	-22.6
2432(Fund.)	59.6	AV	60	1.3	H	29	3.7	31.20	61.1	94.0	-32.9
2432(Fund.)	49.0	AV	185	1.2	V	29	3.7	31.20	50.5	94.0	-43.5

Note: Testing is carried out with frequency rang 30MHz to the tenth harmonics, which above 5th Harmonics is close to the noise base even antenna close up to 1meter distance according the measurement of ANSI C63.4.

PK detector according to FCC 15.35 is deemed to meet the requirements.

Plot of Radiation Emissions Test*Radiated Disturbance**EUT: Leadsoft open wireless interactive whiteboard**M/N: T618**Operating Condition: Transmitting (30MHz to 1GHz)**Test Specification: Vertical & Horizontal**Comment: DC 3V Battery*

*Radiated Disturbance**EUT: Leadsoft open wireless interactive whiteboard**M/N: T618**Operating Condition: Transmitting (1GHz to 18GHz)**Test Specification: Vertical & Horizontal**Comment: DC 3V Battery*

5. §15.249(b) OUT OF BAND EMISSIONS

5.1 Standard Applicable

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

5.2 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date	Due. Date
Agilent	Spectrum Analyzer	E4402B	US41192821	2006-06-30	2007-06-29
ETS	Receiver Antenna	2175	57337	2007-01-26	2008-01-25
ETS	50 ohm Coaxial Cable	SUCOFLEX 104	25498514	2007-01-26	2008-01-25
Rohde & Schwarz	Horn Antenna	HF906	100014	2007-01-26	2008-01-25
Albatross Projects	3m chamber	9X6X6	----	2007-01-24	2008-01-23

Statement of Traceability: All calibrations have been performed per the NVLAP requirements traceable to the NIST.

5.3 Test Procedure

As the radiation test, set the EUT on transmitting mode, observed the outside band of 2400MHz to 2438.5MHz, than mark the band edge frequency and observe whether any higher emission for comparing with the FCC rules.

5.4 Environmental Conditions

Temperature:	18° C
Relative Humidity:	52%
ATM Pressure:	1011 mbar

5.5 Summary of Test Results/Plots

Frequency MHz	Emission dB μ V/m	Limit dB μ V/m
2400.0	40.12	54
2438.5	40.40	54

Note: The corrected factor is under considering and the reading is using PK detector.

Test Result: Pass

Refer to the attached plots.

