# Project 17510

## **Model TM500-315**

# **Wireless Certification Report**

Prepared for:

TowMate 15827 Serenity Point Lane Rogers, Arkansas 72756 By

Professional Testing (EMI), Inc. 1601 North A.W. Grimes Blvd., Suite B Round Rock, Texas 78665

21 Dec 2015

Reviewed by

Larry Finn Chief Technology Officer Written by

Eric Lifsey EMC Engineer

# **Revision History**

<b>Revision Number</b>	Description	Date
00	Initial draft.	21 Dec 2015
01	Revised with product details.	21 Dec 2015

## Corrections

In all cases where the model appears at 315 MHz Wireless Towlight or similar it represents the model TM500-315.

17510 Page 2 of 21

## **Table of Contents**

Revision	History	2
Certifica	ate of Compliance	4
1.0 In	troduction	5
1.1	Scope	5
1.2	EUT Description	5
1.3	EUT Operation	5
1.4	Modifications to Equipment	
1.5	Radiated Measurement Calculation	5
2.0 A <sub>1</sub>	pplicable Documents and Clauses	
2.1	Test Site	
3.0 Fu	ındamental Field Strength	7
3.1	Test Procedure	7
3.2	Test Criteria	
3.3	Test Results	
4.0 Tr	ansmitter Duty Cycle and Shutoff Time	8
4.1	Test Procedure	8
4.2	Test Criteria	8
4.3	Test Results	8
4.	3.1 Transmitter On Time	
4.	3.2 Transmitter Period	9
5.0 Oc	ccupied Bandwidth	. 10
5.1	Test Procedure	. 10
5.2	Test Criteria	. 10
5.3	Test Results	. 10
	3.1 Bandwidth Plot	
6.0 Ra	adiated Spurious Emissions	. 12
6.1	Test Procedure	. 12
6.2	Test Criteria	. 12
6.3	Test Results	. 12
6	3.1 Below 1 GHz, Vertical Polarity	. 13
6	3.2 Below 1 GHz, Horizontal Polarity	. 14
6	3.3 Above 1 GHz, Vertical Polarity	. 15
6	3.4 Above 1 GHz, Horizontal Polarity	. 16
7.0 Aı	ntenna Construction Requirements	. 17
7.1	Procedure	. 17
7.2	Criteria	. 17
7.3	Results	. 17
8.0 Ec	quipment Lists	. 18
8.1	Equipment for Fundamental Power and Spurious Radiated Emissions	. 18
8.2	Equipment for Timings and Bandwidth	. 19
	ix: Policy, Rationale, and Evaluation of EMC Measurement Uncertainty	
End of I	Report	. 21

NOTICE: (1) This Report must not be used to claim product endorsement, by NVLAP, NIST, the FCC or any other Agency. This report also does not warrant certification by NVLAP or NIST. (2) This report shall not be reproduced except in full, without the written approval of Professional Testing (EMI), Inc. (3) The significance of this report is dependent on the representative character of the test sample submitted for evaluation and the results apply only in reference to the sample tested. The manufacturer must continuously implement the changes shown herein to attain and maintain the required degree of compliance.



# **Certificate of Compliance**

Applicant	Device & Test Identification	
TowMate (William Anderson)	FCC ID:	UZVTM315
15827 Serenity Point Lane	Industry Canada ID:	Not Applicable
Rogers, Arkansas 72756	Model(s):	TM500-315
Certificate Date: 21 Dec 2015	Laboratory Project ID:	17510

The device model(s) listed above were tested utilizing the following documents and found to be in compliance with the required criteria.

47 CFR (USA)   Industry Canada RSS-210 & RSS-Gen			
Section Reference FCC   IC	Parameter		
15.231(a)   RSS-210 Is. 8 A1.1, Table A	Fundamental Field Strength		
15.231(a)   RSS-210 Is. 8 A1.1, Table A	Harmonic & Spurious Emissions		
15.231(a)(1)   RSS-210 Is. 8 A1.1.1	Maximum Transmit Time		
15.231(c)   RSS-210 ls. 8 A1.1.3	Bandwidth		
15.203   RSS-Gen Is. 3	Antenna Requirements		

I, Eric Lifsey, for Professional Testing (EMI), Inc., being familiar with the above rules and test procedures have reviewed the test setup, measured data, and this report. I believe them to be true and accurate.

Eric Lifsey EMC Engineer

This report has been reviewed and accepted by the Applicant. The undersigned is responsible for ensuring that this device will continue to comply with the rules listed above.

D. C.A. I'

Representative of Applicant

17510 Page 4 of 21

#### 1.0 Introduction

## 1.1 Scope

This report describes the extent to which the equipment under test (EUT) conformed to the intentional radiator requirements of North America.

Professional Testing (EMI), Inc., (PTI) follows the guidelines of National Institute of Standards and Technology (NIST) for all uncertainty calculations, estimates, and expressions thereof for electromagnetic compatibility testing. The procedures of ANSI C63.4: 2009 were used for making all radiated enclosure and mains emission measurements.

### 1.2 EUT Description

This device is part of a wireless extension of the rear signal lights of a towing vehicle. It will be used in multiple products by the manufacturer on a limited-modular basis; it is not intended for sale to other parties.

**Table 1.2.1: Equipment Under Test** 

Manufacturer	Model	Serial #	Description
TowMate	TM500-315	None	Transmitter

The device is composed of an approximately square circuit board 3.3 x 4.3 cm and typically housed in a rigid plastic case or in a plastic connector of the style used to connect a towed vehicle to the towing vehicle. As tested it was circuit board only. The device only transmits when it receives power; it has no receive mode.

In operation the device is activated/powered by the usual rear signal lights from the towing vehicle and transmits this information to a separate device attached to the towed vehicle and replicates the light signals for other traffic to observe. When no vehicle lamps are powered, the transmitter is also not powered.

## **1.3** EUT Operation

The EUT was exercised in a manner consistent with normal operations.

### 1.4 Modifications to Equipment

The EUT transmit power was reduced, and duty cycle extended, during the performance of the test program.

#### 1.5 Radiated Measurement Calculation

## Raw Measured Level + Antenna Factor + Cable Losses - Amplifier Gain = Corrected Level

When measurement distance differs from the specified limit distance the correct extrapolation factor is applied.

17510 Page 5 of 21

# 2.0 Applicable Documents and Clauses

Table 2.0.1: Applicable Documents		
Document	Title/Description	
47 CFR (USA)	Part 15 – Section 15.231	
ANSI C63.4 2009	American National Standard for Methods of Measurement of Radio-Noise	
ANSI C05.4 2009	Emissions from Low Voltage Electrical and Electronic Equipment	
RSS-Gen Issue 3	General Requirements and Information for the Certification of Radio Apparatus	
RSS-210 Issue 8	Licence-exempt Radio Apparatus (All Frequency Bands):	
K22-510 ISSUE 9	Category I Equipment	

Table 2.0.2: Applicable Clauses			
47 CFR (USA)   Industry Canada RSS-210 & RSS-Gen			
Section Reference FCC   IC	Parameter		
15.231(a)   RSS-210 A1.1, Table A	Fundamental Field Strength		
15.231(a)   RSS-210 A1.1, Table A	Harmonic & Spurious Emissions		
15.231(a)(1)   RSS-210 A1.1.1	Maximum Transmit Time		
15.231(c)   RSS-210 A1.1.3	Bandwidth		
15.203   RSS-Gen	Antenna Requirements		

Table 2.0.3: Supplemental Statements			
Section Number FCC			
Section Number	Clause Subject	Statement	
IC			
FCC 15.231(a)(3)	Periodic	The EUT makes no periodic transmission and is strictly activated by the vehicle lighting/indicator including brake and turn signals.	
RSS-210 A1.1.1(c)	Transmissions	Transmission only occurs while the lights are engaged and ceases immediately when light power is removed.	

### 2.1 Test Site

Measurements were made at the PTI semi-anechoic facility designated Site 45 (FCC 459644, IC 3036B-1) in Austin, Texas. The site is registered with the FCC under Section 2.948 and Industry Canada per RSS-GEN, and is subsequently confirmed by laboratory accreditation (NVLAP). The test site is located at 11400 Burnet Road, Austin, Texas 78758, while the main office is located at 1601 North A.W. Grimes Boulevard, Suite B, Round Rock, Texas, 78665.

17510 Page 6 of 21

# 3.0 Fundamental Field Strength

### 3.1 Test Procedure

EUT is placed on a non-conductive surface 80 cm above a reference plane and measurements of emissions are made to find maximum emission level.

### 3.2 Test Criteria

Section Reference FCC   IC	Parameter	Date(s)
15.231(a)   RSS210 A1.1	Frequency 315.0 MHz Radiated Output Power, 10,333.33μV/m @ 3 m Restated as 80.28 dBμV/m @ 3 m Or extrapolated as 69.8 dBμV/m @ 10 m	14 Dec 2015

## 3.3 Test Results

Table 3.3.1: Field Strength at 10 Meters				
Frequency MHz	Antenna Polarity	Corrected Level (Measured Peak Level) dBµV/m	Detector Mode	
315	V	80.94	Peak	
315	Н	81.40	Peak	

Resolution bandwidth 120 kHz. Video bandwidth 120 kHz. Detector mode is peak.

Duty cycle is such that the emission average level is calculated from the duty cycle factor applied to the measured peak level.

Table 3.3.2: Corrected Field Strength				
Limit At <b>10</b> meters dBµV/m (Average Detection)	Maximum Corrected Level (Measured Peak Level) dBµV/m	Duty Cycle Factor dB	Calculated Average Level dBµV/m	Margin dB
65.17	81.4	-19.82	61.58	-3.59

The EUT was found to be in compliance with the applicable criteria.

17510 Page 7 of 21

# 4.0 Transmitter Duty Cycle and Shutoff Time

#### 4.1 Test Procedure

EUT is placed into normal transmit operation to observe and record transmitter time domain performance.

### 4.2 Test Criteria

Measurement is based on intervals not to exceed 100 msec. Maximum transmitter on time is divided by the lesser of 100 msec or the actual measured minimum transmitter interval time. The result is converted to dB and applied as needed to peak measurements of transmitter artifacts to determine average power. This is not a pass/fail measurement.

Section Reference FCC   IC	Parameter	Date(s)
15.231(a)(1)   RSS210 A1.1.1	Maximum Transmit Time Duty Cycle	14 Dec 2015

### 4.3 Test Results

Table 4.3.1 Duty Cycle Results and Average Duty Cycle Factor Result									
Measured On Time (msec)	Measured Time Interval (msec)	Duty Cycle Factor Calculation	Result (dB)	Duty Cycle Factor Allowed (dB)					
8.28	81.125	= 20 * Log <sub>10</sub> (8.28 msec / 81.125 msec )	-19.82	-19.82					


Table 4.3.2 Exposure Source Duty Cycle Results									
Measured On Time (msec)	Measured Time Interval (msec)	Exposure Duty Cycle Factor Calculation	Result (dB)	Duty Cycle Factor Allowed (dB)					
8.28	81.125	= 10 * Log <sub>10</sub> (8.28 msec / 81.125 msec )	-9.91	-9.91					

Table 4.3.3: Maximum Transmit Shutoff Time, Limit and Measured							
Limit Transmit Time	Maximum Measured Transmit Time						
5 seconds	Transmission ends immediately as all power is removed when all vehicle light signals stop functioning.						


See plotted results of duty cycle time appear below.

17510 Page 8 of 21

# 4.3.1 Transmitter On Time



# 4.3.2 Transmitter Period



17510 Page 9 of 21

# 5.0 Occupied Bandwidth

## **5.1** Test Procedure

The EUT is configured for best signal/power and the bandwidth then is measured. A recording of the results is included.

# 5.2 Test Criteria

Section Reference FCC IC	Parameter	Date(s)
15.231(c), 2.1049   RSS210 A1.1.3	Bandwidth, 20 dB	15 Dec 2015


## 5.3 Test Results

Table 5.3.1: Bandwidth Limit and Measurement							
Limit 15.231(c) 20 dB BW For Fundamental = 315 MHz 0.25% of Fundamental kHz	Measured BW 20 dB kHz						
0.0025 · 315.0 = 787.5	11.4						

EUT was found to be in compliance with applicable requirements.

17510 Page 10 of 21

# 5.3.1 Bandwidth Plot



17510 Page 11 of 21

## **6.0** Radiated Spurious Emissions

#### **6.1** Test Procedure

The EUT was placed on a non-conductive table 0.8 meters above the ground plane. The table was centered on a rotating turntable at a distance of 1 meter from the measurement antenna.

Spurious emissions below 1 GHz were measured with quasi-peak detection with a resolution bandwidth of 120 kHz. A diagram showing the test setup is given in the figure below.

Harmonic emissions above 1 GHz peak were measured with peak detection, a resolution bandwidth of 1 MHz, and at a distance of 3 meters. If peak measurements exceeded average limits, the peak limit was applicable and duty cycle factor was then applied for average level calculation. Emissions were investigated up to at least the 10<sup>th</sup> harmonic of the transmitter fundamental.

Non-harmonic spurious emissions must satisfy the average limit and the peak limit (20 dB above average).

#### 6.2 Test Criteria

Section Number FCC   IC	Clause Subject	Date
15.231(a), 15.209   RSS-210 A1.1 Table A	Field Strength of Radiated Spurious/Harmonic Emissions	14 Dec 2015

#### 6.3 Test Results

Emissions were measured in peak detection mode. All recorded emissions were harmonics of the fundamental. For each emission the average duty cycle factor (-19.82 dB) would apply. Therefore, the emissions must remain under the peak limit of  $85~dB\mu V/m$  to also satisfy the average limit. All emissions remained under the peak and therefore under the average limits.

The EUT satisfied the criteria. Recorded data is presented below.

17510 Page 12 of 21

# 6.3.1 Below 1 GHz, Vertical Polarity

			Profes	sional Te	sting, EN	VII, Inc.					
Test Meth	od:			ds of Measurer e Range of 9 kH					•		t
In accorda	nce with:	FCC Part 15 Limits	.209 - Code of	Federal Regulat	ions Part 47, S	Subpart C - Int	entional F	Radiators	, Radiate	ed Emiss	sions
Section:		15.209									
Test Date	(s):	12/14/20	15		EUT Serial	<b>#</b> :	N/A				
Customer	:		(TowMate)		EUT Part #:		0				
Project Nu	ımber:	17510-15			Test Techni	ician:	Eric Lifs	ey			
Purchase		0			Supervisor:		Lisa Arn	dt			
Equip. Un	der Test:	315 MHz	Wireless Tow	/light	Witness' Na	ame:	None				
	ı	Radiated E	missions Test	t Results Data	Sheet			Page:	1	of	1
EUT	Line Voltage	:	14 VDC		EUT Pow	er Frequen	cy:	0	N/A		
Anteni	na Orientatio	on:	Vertic	al	Frequ	ency Range:		301	∕lHz to	1GHz	
	EUT N	Mode of O	peration:				Transm	nit			
Frequency Measured (MHz)		EUT Direction (Degrees)	Antenna Height (Meters)	Detector Function	Recorded Amplitude (dBµV)	Corrected Level (dBµV/m)	Limit Lev (dBµV/r	_	argin (dB)	Test R	esults
30.3142	10	81	3.43	Quasi-peak	24	12.573	29.5	-	16.9	Pa	SS
59.0488	10	11	3.58	Quasi-peak	31.4	13.299	29.5	-	16.2	Pa	SS
630.27	10	144	1.93	Quasi-peak	22.1	20.316	35.6	-	15.3	Pa	SS
Radiate 30MHz 100 90 (m/A n 80 60 60 50 50 50 50 50 50 50 50 50 50 50 50 50	ssional Testing, d Emissions, 10m D z - 1GHz Vertical F	Distance	d Emissions				asi-peak Lim Trected Lim Trected Peak Trected Peak Rre Verifica III 13:231 p	t Level peak Readi Value Read con Limit eak	i 🔤	SSIONAL	
-	or: Eric Lifsey	ous til	100M Mode: T	Free Cransmitting	quency		EUT: 315 MH	-		16	3

Dark red line is average limit of 15.231; green line is peak limit assuming 20 dB duty cycle factor.

17510 Page 13 of 21

# 6.3.2 Below 1 GHz, Horizontal Polarity

				Profess	sional Te	sting, EN	VII, Inc.					
Test Method:  ANSI C63.4–2003: "Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz" (incorporated by reference, see §15.38).									d			
In accord	lance with:	FCC Part	t 15.20	9 - Code of I	ederal Regulat	ions Part 47, S	Subpart C - Inte	entional	Radiat	ors, Radiato	ed Emis	sions
Section:		15.209										
Test Dat	e(s):	12/14/	2015			EUT Serial	<u>#:                                    </u>	N/A				
Custome	er:	4L-Des	ign (To	owMate)		EUT Part #:		0				
Project I		17510-	·15			Test Techni		Eric Life				
	Order #:	0				Supervisor:		Lisa Ar	ndt			
Equip. U	nder Test:	315 MI	Hz Wir	reless Tow	light	Witness' Na	ame:	None				
		Radiate	d Emis	sions Test	Results Data	Sheet			Page	e: 1	of	1
EU.	Γ Line Voltag	e:	14	VDC		EUT Pow	er Frequenc	:y:	0	N/A		
Ante	nna Orientat	on:		Horizon	ntal	Freque	ency Range:		3	0MHz to	1GHz	
	EUT	Mode of	Opera	ation:				Transı	mit			
Frequence Measure (MHz)	-	EU1 Directi (Degre	ion	Antenna Height (Meters)	Detector Function	Recorded Amplitude (dBµV)	Corrected Level (dBµV/m)	Limit Le (dBμV/		Margin (dB)	Test R	lesults
39.187	9 10	33		1.25	Quasi-peak	24	6.898	29.5	5	-22.6	Pa	iss
58.905	10	326	ŝ	1.37	Quasi-peak	23.1	5.024	29.5	5	-24.5	Pa	ISS
630.21	3 10	78		1.53	Quasi-peak	33.8	32.109	35.6	5	-3.5	Pa	ISS
Radi	fessional Testing ated Emissions, 10m Hz - 1GHz Horizon	Distance		Emissions			— Quas	i-peak Lin ected Qua Limit Lea ected Pea fied Low-P F Verifica L 12-721	nit Level Si-peak R Velyalue Repalue I Gook		SIONAL	
100			-					1_13,231_1	Cak			
90 (m 80 70											_	
ngth (dB v/m) 20 20 20 20 20 20 20 20 20 20										X		
Field Stre												
를 30	×	×								<b>1</b>		
E 20	Way		-				The second secon					
10		Manage of the Party of the Part	Annual Printers and Administration in which the Party of	The state of the last of the l		Address to the State of the Sta						
0 <sup>±</sup> 30N	I ator: Eric Lifsey	<u>"  </u>	-	100M	Free	uency	EU	T: 315 MI	Hz Towli	ght	16	ř
Oper												

Dark red line is average limit of 15.231; green line is peak limit assuming 20 dB duty cycle factor.

17510 Page 14 of 21

# 6.3.3 Above 1 GHz, Vertical Polarity

			Profess	sional Te	esting, El	MI, Inc.			
Test Metho	d:				ment of Radio Hz to 40 GHz"			•	
In accordar	ce with:	FCC Part 15. Limits	209 - Code of I	ederal Regula	ations Part 47,	Subpart C - Int	entional Radi	ators, Radiato	ed Emissions
Section:		15.209							
Test Date(s	):	12/14/201			EUT Serial		N/A		
Customer:		4L-Design	(TowMate)		EUT Part #:		0		
Project Nur		17510-15			Test Techn		Eric Lifsey		
Purchase O		0			Supervisor		Lisa Arndt		
quip. Und	er Test:	315 MHz V	Vireless Tow	light	Witness' N	ame:	None		
	F	Radiated En	nissions Test	Results Da	ta Sheet		Pa	ge: 1	of 1
EUT Li	ne Voltage	: 1	L4 VDC		EUT Pov	ver Frequen	cy:	N/A	
Antenna	Orientatio	n:	Vertic	al	Frequ	ency Range:		Above 1	GHz
	EUT N	/lode of Op	eration:				Transmit		
Frequency Measured (MHz)	Test Distance (Meters)	EUT Direction (Degrees)	Antenna Height (Meters)	Detector Function	Recorded Amplitude (dBµV)	Corrected Level (dBµV/m)	Limit Level (dBµV/m)	Margin (dB)	Test Results
1261.76	3	229	1	Peak	44.7	32.604	74.0	-41.4	Pass
1571.47	3	275	1	Peak	44.5	33.557	74.0	-40.4	Pass
1888.84	3	323	1	Peak	43.9	34.481	74.0	-39.5	Pass
1261.76	3	229	1	Average	34.3	22.164	54.0	-31.8	Pass
1571.47	3	275	1	Average	35.6	24.624	54.0	-29.3	Pass
1888.84	3	323	1	Average	34.1	24.719	54.0	-29.2	Pass
Radiated	ional Testing, Emissions, 3m Dis Vertical Polarity		ns			→ Ave	erage Limit Level reffed Average R Fernander en Read reffed Feak Read 11 - 25-71 Peak R HORNY P&k		SIONAL
30	t hardware and produced and an	Market Market Market	hal a district has a group of a last of the	the design of the second of th	Address of the Assess of the	a de contrata de la contrata del contrata del contrata de la contrata del contrata de la contrata de la contrata del contrata de la contrata de la contrata de la contrata de la contrata del contrat	i yaye ili asarta sarinci is	and the state of t	the detection of the second
20 <sup>±</sup> 1G Operator	: Eric Lifsey			Fre	equency	E	CUT: 315 MHz Tov	vlight	4G

Detector mode peak. Resolution bandwidth 1 MHz. Video bandwidth 3 MHz.

17510 Page 15 of 21

# 6.3.4 Above 1 GHz, Horizontal Polarity

			Profess	sional Te	sting, El	VII, Inc.			
Test Metho	d:			ds of Measure e Range of 9 kH				•	
In accordan	ice with:	FCC Part 15.2 Limits	209 - Code of I	ederal Regula	tions Part 47, S	Subpart C - Int	entional Radia	ators, Radiate	ed Emissions
Section:		15.209			1		-		
Test Date(s	):	12/14/201			EUT Serial		N/A		
Customer:		4L-Design (	TowMate)		EUT Part #:		0		
Project Nur		17510-15			Test Techn		Eric Lifsey		
Purchase O		0			Supervisor:		Lisa Arndt		
Equip. Und	er Test:	315 MHz W	/ireless Tow	light	Witness' N	ame:	None		
	R	Radiated Em	issions Test	Results Dat	a Sheet		Pa	ge: 1	of 1
EUT Li	ne Voltage:	1	4 VDC		EUT Pow	er Frequen	cy: (	N/A	
Antenna	Orientatio	n:	Horizor	ntal	Frequ	ency Range:		Above 1	GHz
	EUT N	lode of Ope	eration:				Transmit		
Frequency Measured (MHz)	Test Distance (Meters)	EUT Direction (Degrees)	Antenna Height (Meters)	Detector Function	Recorded Amplitude (dBμV)	Corrected Level (dBµV/m)	Limit Level (dBµV/m)	Margin (dB)	Test Results
1266.36	3	89	1	Peak	43.9	31.784	74.0	-42.2	Pass
1572.23	3	272	1	Peak	44.5	33.499	74.0	-40.5	Pass
1877.58	3	242	1	Peak	42.4	32.906	74.0	-41.1	Pass
1266.36	3	89	1	Average	33.9	21.789	54.0	-32.2	Pass
1572.23	3	272	1	Average	35	24.018	54.0	-29.9	Pass
1877.58	3	242	1	Average	34	24.471	54.0	-29.5	Pass
Radiated 1-6GHz I 90 80 (m// ngp) 418 (m// ngp) 60 60 60 60 60 60 60 60 60 60 60 60 60	sional Testing, Emissions, 3m Dist Horizontal Polarit		ions			→ Ave   → Point   → Poi	rage Limit Level Terfied Average R Terfied Yeak Read ill 13:731 Peak R HORW P.K.	eading ing PROFES	SIONAL
30 20 1G Operator 17510_12	: Eric Lifsey 1415_RE02_Spurio AM, Monday, Dec		Mode: T Power: 1 2.05k	ransmitting	quency	P	CUT: 315 MHz Tov roject Number: 17 lient: TowMate	-	4G

Detector mode peak. Resolution bandwidth 1 MHz. Video bandwidth 3 MHz.

17510 Page 16 of 21

# **7.0** Antenna Construction Requirements

### 7.1 Procedure

A direct examination of the antenna construction is performed and compared to rule criteria that prevents wireless device antennas from being modified by end users in ways that would void their authorization to use the device.

#### 7.2 Criteria

Section Number FCC   IC	Clause Subject	Date
15.203   RSS-Gen	Antenna Construction	18 Dec 2015

### 7.3 Results

# Antenna Manufacturer, Details

Manufactured by:

TowMate

Antenna is a fixed length of insulated wire soldered directly to the circuit

Length = 23.5 cm

board.

No external connector.

The antenna is not subject to user replacement or substitution.

The antenna design satisfies the requirements of the rules.

17510 Page 17 of 21

# 8.0 Equipment Lists

# 8.1 Equipment for Fundamental Power and Spurious Radiated Emissions

Professional Testing, EMI, Inc.											
Test Method:			oise Emissions from Low-Voltage								
	Electrical and Electronic Equipm	Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz" (incorporated by reference,									
	FCC Part 15.209 - Code of Federal Regulations Part 47, Subpart C - Intentional Radiators,										
In accordance with:	Radiated Emissions Limits	Radiated Emissions Limits									
Section:	15.209										
Test Date(s):	12/14/2015	EUT Serial #:	N/A								
Customer:	4L-Design (TowMate)	EUT Part #:	0								
Project Number:	17510-15	Test Technician:	Eric Lifsey								
Purchase Order #:	0	Supervisor:	Lisa Arndt								
Equip. Under Test:	315 MHz Wireless Towlight	Witness' Name:	None								

### **Radiated Emissions Test Equipment List**

Tile! Software Version: 4.2.A, May 23, 2010, 08:38:52 AM

Test Profile: 2015 Rad Emissions\_ClassA - LowPRF\_072715.til or 2015 Rad Emissions\_ClassB - LowPRF\_072715.til

Asset # Manufacturer N		Model	Equipment Nomenclature	Serial Number	Calibration Due Date				
1509A	Braden	N/A	TDK 10M Chamber, NSA < 1 GHz	DAC-012915-005	2/5/2016				
1890	HP	8447F	Preamp/Amp, 9kHz-1300MHz, 28/25dB	1 3313A05298 I					
1937	Agilent	E4440A	Spectrum Analyzer, 3 Hz - 26.5 GHz	MY44303298	1/2/2016				
1926	ETS-Lindgren	3142D	Antenna, Biconilog, 26 MHz - 6 GHz	135454	1/25/2017				
C027D	none	RG214	Cable Coax, N-N, 25m	none	10/1/2016				
1327	EMCO	1050	Controller, Antenna Mast	none	N/A				
0942	EMCO	11968D	Turntable, 4ft.	9510-1835	N/A				
1969	HP	11713A	Attenuator/Switch Driver	3748A04113	N/A				
1509B	Braden	N/A	TDK 10M Chamber, VSWR > 1 GHz	DAC-012915-005	3/13/2016				
2004	Miteq	AFS44-00101800- 2S-10P-44	Amplifier, 40dB, .1-18GHz	0	12/29/2015				
C030	none	none	Cable Coax, N-N, 30m	none	10/1/2016				
1325	EMCO	1050	Controller, Antenna Mast	9003-1461	N/A				
1780	ETS-Lindgren	3117	Antenna, Double Ridged Guide Horn, 1 - 18 GHz	110313	2/25/2017				

17510 Page 18 of 21

# 8.2 Equipment for Timings and Bandwidth

Asset #	Manufacturer	Model #	Description	Calibration Due
None	PTI	None	SMA Sleeve Antenna	Not Required
ALN-077	Rohde & Schwarz	FSP-30	Spectrum Analyzer	16 Dec 2016

17510 Page 19 of 21

#### Appendix: Policy, Rationale, and Evaluation of EMC Measurement Uncertainty

All uncertainty calculations, estimates and expressions thereof shall be in accordance with NIST policy. Since PTI operates in accordance with NIST (NVLAP) Handbook 150-11: 2007, all instrumentation having an effect on the accuracy or validity of tests shall be periodically calibrated or verified traceable to national standards by a competent calibration laboratory. The certificates of calibration or verification on this instrumentation shall include estimates of uncertainty as required by NIST Handbook 150-11.

#### 1. Rationale and Summary of Expanded Uncertainty.

Each piece of instrumentation at PTI that is used in making measurements for determining conformance to a standard (or limit), shall be assessed to evaluate its contribution to the overall uncertainty of the measurement in which it is used. The assessment of each item will be based on either a type A evaluation or a type B evaluation. Most of the evaluations will be type B, since they will be based on the manufacturer's statements or specifications of the calibration tolerances, or uncertainty will be stated along with a brief rationale for the type of evaluation and the resulting stated uncertainties.

The individual uncertainties included in the combined standard uncertainty for a specific test result will depend on the configuration in which the item of instrumentation is used. The combination will always be based on the law of propagation of uncertainty. Any systematic effects will be accommodated by including their uncertainties, in the calculation of the combined standard uncertainty; except that if the direction and amount of the systematic effect cannot be determined and separated from its uncertainty, the whole effect will be treated as uncertainty and combined along with the other elements of the test setup.

Type A evaluations of standard uncertainty will usually be based on calculating the standard deviation of the mean of a series of independent observations, but may be based on a least-squares curve fit or the analysis of variance for unusual situations. Type B evaluations of standard uncertainty will usually be based on manufacturer's specifications, data provided in calibration reports, and experience. The type of probability distribution used (normal, rectangular, a priori, or u-shaped) will be stated for each Type B evaluation.

In the evaluation of the uncertainty of each type of measurement, the uncertainty caused by the operator will be estimated. One notable operator contribution to measurement uncertainty is the manipulation of cables to maximize the measured values of radiated emissions. The operator contribution to measurement uncertainty is evaluated by having several operators independently repeat the same test. This results in a Type A evaluation of operator-contributed measurement uncertainty.

A summary of the expanded uncertainties of PTI measurements is shown as Table 1. These are the worst-case uncertainties considering all operative influence factors.

Table 1: Summary of Measurement Uncertainties for Site 45

Type of Measurement	Frequency Range	Meas. Dist.	Expanded Uncertainty U, dB (k=2)
Mains Conducted Emissions	150 kHz to 30 MHz	N/A	2.9
Telecom Conducted Emissions	150 kHz to 30 MHz	N/A	2.8
Radiated Emissions	30 to 1,000 MHz	10 m	4.8
Radiated Emissions	1 to 18 GHz	3 m	5.7

17510 Page 20 of 21

# **End of Report**

(This page intentionally left blank.)

17510 Page 21 of 21