

APPLICATION FOR CERTIFICATION
On Behalf of

ZHANXIANG TECHNOLOGY(HUI ZHOU)CO.,LTD

Flat Panel TV Bracket

Model Number: ZX-C33A

FCC ID: V26ZX-C33A

Prepared for : ZHANXIANG TECHNOLOGY(HUI ZHOU)CO.,LTD
XIALIAO VILLAGE, LONGQIAO ROAD, LONGXI
TOWN, BOLUO COUNTY, HUIZHOU CITY, CHINA

Prepared By : Audix Technology (Shenzhen) Co., Ltd.
No. 6, Ke Feng Rd., 52 Block,
Shenzhen Science & Industrial Park,
Nantou, Shenzhen, Guangdong, China

Tel: (0755) 26639496

Report Number : ACS-F08458
Date of Test : Nov.20~23, 2008
Date of Report : Jan.08, 2009

TABLE OF CONTENTS

Description	Page
1. SUMMARY OF STANDARDS AND RESULTS	1-1
1.1. Description of Standards and Results.....	1-1
2. GENERAL INFORMATION.....	2-1
2.1. Description of Device (EUT)	2-1
2.2. Test Facility.....	2-2
2.3. Measurement Uncertainty(95% confidence levels, k=2)	2-2
3. POWER LINE CONDUCTED EMISSION TEST.....	3-1
3.1. Test Equipments.....	3-1
3.2. Block Diagram of Test Setup	3-1
3.3. Power Line Conducted Emission Test Limits.....	3-1
3.4. Configuration of EUT on Test	3-1
3.5. Operating Condition of EUT.....	3-2
3.6. Test Procedure.....	3-2
3.7. Power Line Conducted Emission Test Results.....	3-2
4. RADIATED EMISSION TEST.....	4-1
4.1. Test Equipment	4-1
4.2. Block Diagram of Test Setup	4-1
4.3. Radiated Emission Limit.....	4-2
4.4. EUT Configuration on Test.....	4-3
4.5. Operating Condition of EUT.....	4-3
4.6. Test Procedure.....	4-3
4.7. Radiated Emission Measurement Result.....	4-4
5. DEVIATION TO TEST SPECIFICATIONS	5-1
6. PHOTOGRAPH OF TEST	6-1
6.1. Photos of Power Line Conducted Emission Test	6-1
6.2. Photos of Radiated Emission Test (In Anechoic Chamber)	6-2
7. PHOTOGRAPH OF EUT	7-1

TEST REPORT CERTIFICATION

Applicant : ZANXIANG TECHNOLOGY(HUI ZHOU)CO.,LTD
 Manufacturer : ZANXIANG TECHNOLOGY(HUI ZHOU)CO.,LTD
 EUT Description : Flat Panel TV Bracket
 FCC ID : V26ZX-C33A
 (2) MODEL NO. : ZX-C33A
 (B) POWER SUPPLY. : DC 24V
 (C) TEST VOLTAGE : DC 24V Adapter Input AC 120V/60Hz

Test Procedure Used:

FCC Rules and Regulations Part 15 Subpart B Class B 2007, ANSI C63.4-2003

The device described above is tested by Audix Technology (Shenzhen) Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart B Class B limits for radiated and conducted emissions. The test results are contained in this test report and Audix Technology (Shenzhen) Co., Ltd. is assumed full responsibility for the accuracy and completeness of tests. Also, this report shows that EUT is technically compliant with FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Audix Technology (Shenzhen) Co., Ltd.

Date of Test : _____ Nov.20~23, 2008

Prepared by : _____ *Edie Huang*
Edie Huang / Assistant

Reviewer : _____ *Jamy Yu*
Jamy Yu / Senior Engineer



Approved & Authorized Signer : _____ Ken Lu / Deputy Manager

1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION			
Description of Test Item	Standard	Limits	Results
Power Line Conducted Emission Test	FCC Part 15: 2007 ANSI C63.4: 2003	Class B	PASS
Radiated Emission Test	FCC Part 15: 2007 ANSI C63.4: 2003	Class B	PASS

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

Description : Flat Panel TV Bracket
(Note: This equipment contains a 433.92MHz super-regenerative receiver)

Model Number : ZX-C33A

FCC ID : V26ZX-C33A

Applicant : ZHANXIANG TECHNOLOGY(HUI ZHOU)CO.,LTD
XIALIAO VILLAGE, LONGQIAO ROAD, LONGXI TOWN,
BOLUO COUNTY, HUIZHOU CITY, CHINA

Manufacturer : ZHANXIANG TECHNOLOGY(HUI ZHOU)CO.,LTD
XIALIAO VILLAGE, LONGQIAO ROAD, LONGXI TOWN,
BOLUO COUNTY, HUIZHOU CITY, CHINA

Power Adapter : Manufacturer: Ktec
M/N: KSAFK2400300T1M2
Cable: Unshielded, Detachable, 4m (with one core)

Remote Control : Manufacturer: ZHANXIANG TECHNOLOGY(HUI ZHOU)CO.,LTD

Date of Test : Nov.20~23, 2008

Date of Receipt : Nov.20, 2008

Sample Type : Prototype production

Remark : The base insert holes of post assembly is for power input, TV signal input, Video and Audio signal input. The top insert holes of post assembly is only to connect the terminal of power input, TV signal input, Video and Audio signal input of TV. So they are transferred for convenience and direct connection.

2.2. Test Facility

Site Description	:	Audix Technology (Shenzhen) Co., Ltd.
Name of Firm	:	No. 6, Ke Feng Rd., 52 Block, Shenzhen Science & Industrial Park, Nantou, Shenzhen, Guangdong, China
3m Anechoic Chamber	:	Jun. 13, 2006 File on Federal Communication Commission Registration Number: 90454
3m & 10m Anechoic Chamber	:	Jan. 31, 2007 File on Federal Communication Commission Registration Number: 794232
EMC Lab.	:	Accredited by DATech, German Registration Number: DAT-P-091/99-01 Dec. 20, 2007
		Accredited by NVLAP, USA NVLAP Code: 200372-0 Apr.01, 2008

2.3. Measurement Uncertainty(95% confidence levels, k=2)

No.	Item	MU	Remark
1	Uncertainty for Conducted Emission Test	2.02dB	
2	Uncertainty for Radiation Emission test in 3m chamber	3.44 dB	Polarize: V
		3.96 dB	Polarize: H
3	Uncertainty for Radiation Emission test in 10m chamber	3.86dB	Distance: 10m Polarize: V
		4.18dB	Distance: 10m Polarize: H
		4.02dB	Distance: 3m Polarize: V
		4.36dB	Distance: 3m Polarize: H


3. POWER LINE CONDUCTED EMISSION TEST

3.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESCI	100842	Oct.24, 08	1 Year
2.	L.I.S.N.#2	Kyoritsu	KNW-407	8-1636-1	May 10,08	1 Year
3.	Terminator	Hubersuhner	50Ω	No. 2	May 10,08	1 Year
4.	RF Cable	Fujikura	3D-2W	LISN Cable 1#	Nov.10, 08	1/2 Year
5.	Coaxial Switch	Anritsu	MP59B	M55367	Nov.01, 08	1/2 Year
6.	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100341	Nov.10, 08	1/2 Year

3.2. Block Diagram of Test Setup

3.2.1. Block diagram of connection between the EUT and simulators



(EUT: Flat Panel TV Bracket)

3.3. Power Line Conducted Emission Test Limits

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(µV)	Average Level dB(µV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

3.4. Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

3.4.1. Flat Panel TV Bracket (EUT)

Model Number : ZX-C33A

Serial Number : N/A

3.4.2. Support Equipment : As Tested Supporting System Detail, in Section 2.2.

3.5.Operating Condition of EUT

- 3.5.1. Setup the EUT and simulator as shown as Section 3.2.
- 3.5.2. Turned on the power of all equipment.
- 3.5.3. Let the EUT worked in test mode (Running) and measured it.

3.6. Test Procedure

The EUT was placed on the ground plane. The EUT Power connected to the power mains through a line impedance stabilization network (L.I.S.N. #2). This provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.4: 2003 on conducted Emission test.

The bandwidth of the R&S Test Receiver ESCI was set at 10kHz.

The frequency range from 150kHz to 30MHz was checked using a peak detector.

The all reading of measurement was with the Quasi-Peak detector and Average detector. (Remark: If the Average limit is met when using a Quasi-Peak detector, the Average detector is unnecessary)

EUT: Flat Panel TV Bracket Model No. : ZX-C33A

Model No. : ZX-C33A

Test Date: Nov.23, 2008

Temperature: 23 °C Humidity: 54%

The details of test modes are as follow:

No.	Test Mode	Reference Test Data No.	
		VA	VB
1.	Running	#1	#2

3.7. Power Line Conducted Emission Test Results

PASSED




NO.6 Ke Feng Road,Block 52,
Shenzhen Science&Industry Park
Nantou, Shenzhen,Guang dong, China.
Tel:+86-755-26639495
Fax:+86-755-26632877
Postcode:518057

Data: 1

File: D:\DATA\2008 Report\Z\Zhanxiang\ACS8Q1532R1.EMI (10)

Date: 2008-11-23



Site no :Audix No.1 Conduction Data no :1
 Dis./Ant. :-- KNW407 1# VA LISN phase:
 Limit :FCC PART 15 B
 Env./Ins. :Temp:23'C Humi:54% ESCI Engineer :MARK
 EUT :Flat Panel TV Bracket M/N:ZX-C33A
 Power Rating :DC 24V Adapter Input AC 120V/60Hz
 Test Mode :Running
 Memo :

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission			
					Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.15	0.24	9.67	41.24	51.15	66.00	14.85	QP
2	0.21	0.11	9.91	35.89	45.91	63.22	17.31	QP
3	0.42	0.18	9.87	22.93	32.98	57.47	24.49	QP
4	7.58	0.07	9.95	31.94	41.96	60.00	18.04	QP
5	9.46	0.09	9.97	32.37	42.43	60.00	17.57	QP
6	17.88	0.36	10.06	28.80	39.22	60.00	20.78	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.

2.If the average limit is met when useing a quasi-peak detector.
the EUT shall be deemed to meet both limits and measurement
with average detector is unnecessary.




NO.6 Ke Feng Road,Block 52,
Shenzhen Science&Industry Park
Nantou, Shenzhen,Guang dong, China.
Tel:+86-755-26639495
Fax:+86-755-26632877
Postcode:518057

Data: 2

File: D:\DATA\2008 Report\Z\Zhanxiang\ACS8Q1532R1.EMI (10)

Date: 2008-11-23



Site no :Audix No.1 Conduction Data no :2
 Dis./Ant. :-- KNW407 1# VB LISN phase:
 Limit :FCC PART 15 B
 Env./Ins. :Temp:23'C Humi:54% ESCI Engineer :MARK
 EUT :Flat Panel TV Bracket M/N:ZX-C33A
 Power Rating :DC 24V Adapter Input AC 120V/60Hz
 Test Mode :Running
 Memo :

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission			
					Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.18	0.29	9.82	34.77	44.88	64.49	19.61	QP
2	0.36	0.24	9.88	30.26	40.38	58.75	18.37	QP
3	0.84	0.15	9.88	20.86	30.89	56.00	25.11	QP
4	1.64	0.10	9.90	13.46	23.46	56.00	32.54	QP
5	7.94	0.20	9.96	30.50	40.66	60.00	19.34	QP
6	16.30	0.33	10.04	29.83	40.20	60.00	19.80	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.

2.If the average limit is met when useing a quasi-peak detector.
the EUT shall be deemed to meet both limits and measurement
with average detector is unnecessary.

4. RADIATED EMISSION TEST

4.1. Test Equipment

The following test equipments are used during the radiated emission test:

4.1.1. For frequency range 30MHz~1000MHz (At Anechoic Chamber)


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	3#Chamber	AUDIX	N/A	N/A	Jun.09,08	1/2 Year
2.	EMI Spectrum	Agilent	E7403A	MY42000106	May 10, 08	1 Year
3.	Test Receiver	Rohde & Schwarz	ESVS10	834468/011	May 10, 08	1 Year
4.	Amplifier	HP	8447D	2648A04738	Nov.04, 08	1/2 Year
5.	Bilog Antenna	Schaffner	CBL6112D	25237	Feb.21, 08	1 Year
6.	RF Cable	JINGCHENG	JBY400	3# Chamber No.1	Nov.01, 08	1/2 Year
7.	RF Cable	JINGCHENG	JBY400	3# Chamber No.2	Nov.01, 08	1/2 Year
8.	RF Cable	JINGCHENG	JBY400	3# Chamber No.3	Nov.01, 08	1/2 Year
9.	Coaxial Switch	Anritsu	MP59B	M73989	Nov.01, 08	1/2 Year

4.1.2. For frequency range Above 1000MHz (At Anechoic Chamber)

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	E4446A	US44300459	May,10, 08	1 Year
2.	Horn Antenna	EMCO	3115	9607-4877	May, 27, 08	1.5 Year
3.	Horn Antenna	EMCO	3116	00060088	May 27, 08	1 Year
4.	Amplifier	Agilent	8449B	3008A02495	Nov.06.08	1 Year
5.	RF Cable	Hubersuhner	SUCOFLEX 102	28620/2	May.28, 08	1 Year
6.	RF Cable	Hubersuhner	SUCOFLEX 102	271471/4	May.28, 08	1 Year
7.	RF Cable	Hubersuhner	SUCOFLEX 102	29086/2	May.28, 08	1 Year

4.2. Block Diagram of Test Setup


4.2.1. Block diagram of connection between the EUT and simulators



(EUT: Flat Panel TV Bracket)


4.2.2.In Anechoic Chamber

ANTENNA TOWER



4.2.3.In Anechoic (3m) Chamber Test Setup Diagram for 1-5GHz

ANTENNA TOWER



4.3.Radiated Emission Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μ V/m	dB(μ V)/m
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μ V)/m (Peak) 54.0 dB(μ V)/m (Average)	

Remark :

- (1) Emission level $\text{dB}\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) The emissions above 1GHz should comply with average limit and peak limit.

4.4.EUT Configuration on Test

The following equipment are installed on Radiated Emission Test to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

4.4.1. Flat Panel TV Bracket (EUT)

Model Number : ZX-C33A
 Serial Number : N/A

4.4.2. Support Equipment : As Tested Supporting System Detail, in Section 2.2.

4.5. Operating Condition of EUT

4.5.1. Setup the EUT and simulator as shown as Section 4.2.

4.5.2. Turned on the power of all equipment.

4.5.3. Let the EUT worked in test mode (Running) and measured it.

4.6. Test Procedure

The EUT was placed on the ground plane inside a semi-anechoic chamber. An antenna was located 3m from the EUT on an adjustable mast. A pre-scan was first performed in order to find prominent radiated emissions. For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.4: 2003 on Radiated Emission test.

A Signal Generator was set to the test sample operating Frequency (433.92MHz). An un-Modulated continuous wave (CW) signal was radiated at the Super-regenerative Receiver operating frequency to cohere the characteristic broadband emission from the receiver.

The bandwidth setting on the test receiver (R&S TEST RECEIVER ESVS10) is 120 kHz.

The resolution bandwidth of the Agilent Spectrum Analyzer E4407B was set at 1MHz. (For above 1GHz)

The frequency range from 30MHz to 1000MHz was pre-scanned with a peak detector and all final readings of measurement from Test Receiver are Quasi-Peak values.

The frequency range from 1GHz to 5GHz was checked with peak detector.

Finally, selected operating situations at Anechoic Chamber measurement, all the test results are listed in section 4.7.

4.7.Radiated Emission Measurement Result

PASSED. (All emissions not reported below are too low against the prescribed limits.)

EUT: Flat Panel TV Bracket Model No. : ZX-C33A

For frequency range 30MHz~1000MHz

The EUT with the following test modes were tested and selected (mode 1) to read Q.P values, all the test results listed in next pages.

No.	Test Mode	Reference Test Data No.	
		Horizontal	Vertical
1.	Running	#1	#2

For frequency range 1GHz~5GHz

The EUT with below test mode 1 was measured within Anechoic Chamber and the test results listed in next pages


All the PK emissions were comply with average limit, So the average level were deemed to comply with average limit

Test Date: Nov.20, 2008 Temperature: 23°C Humidity: 54%

No.	Test Mode	Reference Test Data No.	
		Horizontal	Vertical
1.	Running	#5	#6

Super-regenerative Receiver stabilization plot:


Signal Generator frequency: 433.92MHz





No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 1 File: E:\2008 report data\z\zhanxiang\acs8q1532R1.EMI.EM6 (8)



Trace: (Discrete)

Site no. : 3# Chamber Data no. : 1
 Dis. / Ant. : 3m CBL6112D Ant. pol. : HORIZONTAL
 Limit : FCC PART15 B
 Env. / Ins. : 29.5°C/55% ESVS 20 Engineer : Leidy
 EUT : Flat Panel TV Bracket M/N:ZX-C33A
 Power Rating : DC 12V Adaptor Input AC 120V/60Hz
 Test mode : Running
 Memo :

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Emission				
			Reading (dB μ V)	Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Remark
1 179.380	9.45	1.28	12.04	22.77	43.50	20.73	QP
2 433.920	0.00	0.00	40.97	40.97	46.00	5.03	QP
3 565.440	18.64	2.16	10.56	31.36	46.00	14.64	QP
4 638.190	18.86	2.39	11.94	33.19	46.00	12.81	QP
5 749.740	19.42	2.59	11.80	33.81	46.00	12.19	QP
6 769.140	19.53	2.23	13.08	34.84	46.00	11.16	QP


Remarks:

1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. The emission levels that are 20dB below the official limit are not reported.
3. The worst emission was detected at 433.920 MHz with corrected signal level of 47.97dB μ V/m (Limit is 46.00dB μ V/m) when the antenna was at horizontal polarization and at 1m high and the turntable was at 330°.
4. 0° was the table front facing the antenna. Degree is calculated from 0° clockwise facing the antenna.



No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 2 File: E:\2008 report data\z\zhanxiang\acs8q1532R1.EMI.EM6 (8)



Trace: (Discrete)

Site no. : 3# Chamber Data no. : 2
Dis. / Ant. : 3m CBL6112D Ant. pol. : VERTICAL
Limit : FCC PART15 B
Env. / Ins. : 29.5°C/55% ESVS 20 Engineer : Leidy
EUT : Flat Panel TV Bracket M/N:ZX-C33A
Power Rating : DC 12V Adaptor Input AC 120V/60Hz
Test mode : Running
Memo :

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Emission				
			Reading (dB μ V)	Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Remark
1 58.130	6.90	0.90	28.10	35.90	40.00	4.10	QP
2 187.140	9.27	1.30	23.51	34.08	43.50	9.42	QP
3 288.990	12.80	1.53	20.26	34.59	46.00	11.41	QP
4 433.920	0.00	0.00	41.81	41.81	46.00	4.19	QP
5 504.330	17.78	2.07	16.65	36.50	46.00	9.50	QP
6 755.560	19.45	2.47	14.18	36.10	46.00	9.90	QP

Remarks:


1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. The emission levels that are 20dB below the official limit are not reported.
3. The worst emission was detected at 433.920 MHz with corrected signal level of 47.81 dB μ V/m (Limit is 46.00dB μ V/m) when the antenna was at vertical polarization and at 1m high and the turntable was at 150°.
4. 0° was the table front facing the antenna. Degree is calculated from 0° clockwise facing the antenna.



No.6, Ke Feng Road, Block 52,
Shenzhen Science&Industry Park
Nantou Shenzhen, Guangdong, China
Tel:+86-755-26639495
Fax:+86-755-26632877
Postcode:518057

Data: 5

File: D:\2008 Report Data\Z\zhangxiang\acs8q1532R1.EMI (6)



Trace: (Discrete)

Site no. : 3# Chamber Data no. : 5
Dis. / Ant. : 3m 3115 FACTOR Ant. pol. : HORIZONTAL
Limit : FCC PART 15B PEAK
Env. / Ins. : 23°C/54% Engineer : Leidy
EUT : Flat Panel TV Bracket M/N:ZX-C33A
Power Rating : DC 12V Adaptor Input AC 120V/60Hz
Test Mode : Running

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Emission				
			Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 1732.00	26.63	5.23	49.95	46.26	74.00	27.74	Peak
2 3040.00	31.09	7.18	38.48	41.76	74.00	32.24	Peak
3 3472.00	32.28	7.80	39.72	44.94	74.00	29.06	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




No.6, Ke Feng Road, Block 52,
Shenzhen Science&Industry Park
Nantou Shenzhen, Guangdong, China
Tel:+86-755-26639495
Fax:+86-755-26632877
Postcode:518057

Data: 6

File: D:\2008 Report Data\Z\zhangxiang\acs8q1532R1.EMI (6)

Date: 2008-11-20



Trace: (Discrete)

Site no. : 3# Chamber Data no. : 6
Dis. / Ant. : 3m 3115 FACTOR Ant. pol. : VERTICAL
Limit : FCC PART 15B PEAK
Env. / Ins. : 23°C/54% Engineer : Leidy
EUT : Flat Panel TV Bracket M/N:ZX-C33A
Power Rating : DC 12V Adaptor Input AC 120V/60Hz
Test Mode : Running

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Emission				
			Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 1300.00	25.00	4.65	46.25	39.97	74.00	34.03	Peak
2 1732.00	26.63	5.23	43.34	39.65	74.00	34.35	Peak
3 3472.00	32.28	7.80	42.08	47.30	74.00	26.70	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

5. DEVIATION TO TEST SPECIFICATIONS


[NONE]

6. PHOTOGRAPH OF TEST

6.1.Photos of Power Line Conducted Emission Test



6.2.Photos of Radiated Emission Test (In Anechoic Chamber)



(At Anechoic Chamber Test 1GHz-5GHz)



7. PHOTOGRAPH OF EUT

Figure 1

General Appearance of the EUT



Figure 2

General Appearance of the EUT



Figure 3
General Appearance of the EUT



Figure 4
Inside of the EUT



Figure 5
Inside of the EUT




Figure 6
Inside of the EUT




Figure 7
Inside of the EUT



Figure 8
Inside of the EUT




Figure 9
Inside of the EUT




Figure 10
Inside of the EUT




Figure 11
Inside of the EUT




Figure 12
Inside of the EUT




Figure 13
Inside of the EUT




Figure 14
Inside of the EUT




Figure 15
Power Adapter



Figure 16
Power Adapter



Figure 17
Remote Control

