

Report No.: ER/2008/10038 Issue Date: Mar. 04, 2008

Page: 1 of 27

ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT

INTENTIONAL RADIATOR CERTIFICATION TO FCC PART 15 SUBPART C REQUIREMENT

0F

USB Receivr Product Name:

Brand Name: N/A

Model Name: TD1J

FCC ID: V2L-TD1J

ER/2008/10038 **Report No.:**

Issue Date: Mar. 04, 2008

§15.249 **FCC Rule Part:**

Prepared for: YI-PHONE INC.

7F-1, No. 286-1, Hsin-Ya Rd. Chien-Chen

District Kaohsiung, Taiwan.

Prepared by: SGS Taiwan Ltd.

Electronics & Communication Laboratory

No. 134, Wu Kung Rd., Wuku Industrial

Zone, Taipei County, Taiwan.



Note: This report shall not be reproduced except in full, without the written approval of SGS Taiwan Ltd. This document may be altered or revised by SGS Taiwan Ltd. personnel only, and shall be noted in the revision section of the document.

This document is issued by the Company subject to its General Conditions of Service printed overleaf or available on request and accessible at www.sgs.com. Attention is drawn to the limitations of liability, indemnification, and Jurisdictional issued defined therein. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, without prior approval of Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful and offenders may be prosecuted to the fullest extent of the law. 此報告是遵循本公司訂定之通用服務條款所製作發放,請注意此條 款列印於背面,亦可在www.sgs.com中查閱。將本公司之義務,免責,管轄權皆明確規範之。除非另有說明,此報告結果僅對檢驗之樣品負責。本報告未經本公司書面許可,

不可部份複製。對本報告內容或外觀之任何未經授權之變更、僞造、竄改皆屬非法,違犯者將會被依法追訴。

SGS Taiwan Ltd.
台灣檢驗科技股份有限公司

t (886-2) 2299-3939

f (886-2) 2298-2698

www.sgs.com.tw



Report No.: ER/2008/10038 Issue Date: Mar. 04, 2008

Page: 2 of 32

VERIFICATION OF COMPLIANCE

Applicant: YI-PHONE INC.

7F-1, No. 286-1, Hsin-Ya Rd. Chien-Chen District Kaohsiung, Taiwan.

Product Description: USB Receivr

Brand Name: N/A

FCC ID Number: V2L-TD1J

Model No.: TD1J

Model Difference: N/A

File Number: ER/2008/10038

Date of test: Jan. 18, 2008 ~ Feb. 27, 2008

Date of EUT Received: Jan. 17, 2008

We hereby certify that:

The above equipment was tested by SGS Taiwan Ltd. Electronics & Communication Laboratory The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2003) and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.249.

The test results of this report relate only to the tested sample identified in this report.

| Test By: | Sky Wang, | Date | Mar. 04, 2008 | |
|--------------|-----------------------------|------|---------------|--|
| Prepared By: | Sky Wang / Sr. Engineer | Date | Mar. 04, 2008 | |
| Approved By: | Gigi Yeh/Clerk Timent Sv | | Mar. 04, 2008 | |
| - | Vincent Su / Manager | | | |

This document is issued by the Company subject to its General Conditions of Service printed overleaf or available on request and accessible at www.sgs.com. Attention is drawn to the limitations of liability, indemnification, and Jurisdictional issued defined therein. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, without prior approval of Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful and offenders may be prosecuted to the fullest extent of the law. 此報告是遵循本公司訂定之通用服務條款所製作發放, 請注意此條款列印於背面,亦可在www.sgs.com中查閱。將本公司之義務,免責,管轄權皆明確規範之。除非另有說明,此報告結果僅對檢驗之樣品負責。本報告未經本公司書面許可,不可部份複製。對本報告內容或外觀之任何未經授權之變更、僞造、竄改皆屬非法,違犯者將會被依法追訴。



Report No.: ER/2008/10038 Issue Date: Mar. 04, 2008

Page: 3 of 32

Version

| Version No. | Date |
|-------------|---------------|
| 00 | Mar. 04, 2008 |
| | |



CENEDAL INFORMATION

FCC ID: V2L-TD1J

Report No.: ER/2008/10038 Issue Date: Mar. 04, 2008

Page: 4 of 32

Table of Contents

| 1. | GENERAL INFORMATION | |
|-------|--|----|
| 1.1 | PRODUCT DESCRIPTION | 5 |
| 1.2 | RELATED SUBMITTAL(S) / GRANT (S) | 5 |
| 1.3 | TEST METHODOLOGY | 5 |
| 1.4 | TEST FACILITY | 5 |
| 1.5 | SPECIAL ACCESSORIES | |
| 1.6 | EQUIPMENT MODIFICATIONS | 5 |
| 2. | SYSTEM TEST CONFIGURATION | 6 |
| 2.1 | EUT CONFIGURATION | 6 |
| 2.2 | EUT Exercise | 6 |
| 2.3 | TEST PROCEDURE | 6 |
| 2.4 | LIMITATION | 7 |
| 2.5 | CONFIGURATION OF TESTED SYSTEM | 9 |
| 3. | SUMMARY OF TEST RESULTS | 10 |
| 4. | CONDUCTED EMISSIONS TEST | 11 |
| 4.1 | MEASUREMENT PROCEDURE: | 11 |
| 4.2 | TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) | 11 |
| 4.3 | MEASUREMENT EQUIPMENT USED: | 11 |
| 4.4 | MEASUREMENT RESULT: | 11 |
| 5. | RADIATED EMISSION TEST | 14 |
| 5.1 | MEASUREMENT PROCEDURE | 14 |
| 5.2 | TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) | 14 |
| 5.3 | MEASUREMENT EQUIPMENT USED: | 15 |
| 5.4 | FIELD STRENGTH CALCULATION | 15 |
| 5.5 | MEASUREMENT RESULT | 16 |
| 6. | 26 DB BAND WIDTH MEASUREMENT | 25 |
| 6.1 | MEASUREMENT PROCEDURE | 25 |
| 6.2 | TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) | 25 |
| 6.3 | MEASUREMENT EQUIPMENT USED: | 25 |
| 6.4 | MEASUREMENT RESULTS: | 25 |
| APPEN | NDIX 1 PHOTOGRAPHS OF SET UP | 28 |
| APPEN | NDIX 2 PHOTOGRAPHS OF EUT | 31 |

This document is issued by the Company subject to its General Conditions of Service printed overleaf or available on request and accessible at www.sgs.com. Attention is drawn to the limitations of liability, indemnification, and Jurisdictional issued defined therein. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, without prior approval of Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful and offenders may be prosecuted to the fullest extent of the law. 此報告是遵循本公司訂定之通用服務條款所製作發放, 請注意此條款列印於背面,亦可在www.sgs.com中查閱。將本公司之義務,免責,管轄權皆明確規範之。除非另有說明,此報告結果僅對檢驗之樣品負責。本報告未經本公司書面許可,不可部份複製。對本報告內容或外觀之任何未經授權之變更、僞造、窳改皆屬非法,違犯者將會被依法追訴。

Report No.: ER/2008/10038 Issue Date: Mar. 04, 2008

Page: 5 of 32

1. GENERAL INFORMATION

1.1 Product Description

The YI-PHONE INC., Model: TD1J (referred to as the EUT in this report) is a Response Receiver.

A major technical descriptions of EUT is described as following:

A). Operation Frequency: 2402~2438MHz, 38 channels, 1MHz step

B). Modulation Type: DSSS (GFSK)C). Power Supply: 5V from USB port

1.2 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: <u>V2L-TD1J</u> filing to comply with Section 15.249 of the FCC Part 15, Subpart C Rules.

1.3 Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4 (2003). Radiated testing was performed at an antenna to EUT distance 3 meters.

1.4 Test Facility

The measurement facilities used to collect the 3m Radiated Emission and AC power line conducted data are located on the address of SGS Taiwan Ltd. No. 134, Wu Kung Rd., Wuku Industrial Zone, Taipei Country, Taiwan which are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2003. FCC Registration Number are: 990257 and 236194, Canada Registration Number: 4620A-1

The 10 m Open Area Test Sites located on the address of SGS Taiwan Ltd. No. 29, Pau-Tou-Tsuo Valley Chia-Pau Tsuen, Linkou Hsiang, Taipei county, which is constructed and calibrated to meet the CISPR 22/EN 55022 requirements. SGS Site No. 1(3 &10 meters) and FCC Registration Number: 94644.

1.5 Special Accessories

Not available for this EUT intended for grant.

1.6 Equipment Modifications

Not available for this EUT intended for grant.



Report No.: ER/2008/10038 Issue Date: Mar. 04, 2008

Page: 6 of 32

2. System Test Configuration

EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

EUT Exercise

The Transmitter was operated in the engineering operating mode, the Tx frequency was fixed which was for the purpose of the measurements.

Test Procedure

2.3.1Conducted Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. According to the requirements in Section 7 and 13 of ANSI C63.4-2003. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and Average detector mode.

2.3.2Radiated Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. The turn

shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was

through three orthogonal axes and measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made "while keeping the antenna in the 'cone of radiation' from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response." is still within the 3dB illumination BW of the measurement antenna. according to the requirements

in Section 8 and 13 and Subclause 8.3.1.2 of ANSI C63.4-2003.



Report No.: ER/2008/10038 Issue Date: Mar. 04, 2008

Page: 7 of 32

Limitation

(1) Conducted Emission

According to section 15.207(a) Conducted Emission Limits is as following.

| Frequency | Conducted 1 | Limit (dBuV) |
|------------|-------------|--------------|
| (MHz) | Quasi-Peak | Average |
| 0.15 - 0.5 | 66 - 56 | 56 - 46 |
| 0.5 - 5 | 56 | 46 |
| 5 - 30 | 60 | 50 |

(2) Radiated Emission 15.249(a)

The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following.

| Frequency (MHz) | Field strength of Fundamental | Field strength of Harmonics | Distance (m) |
|------------------|----------------------------------|--------------------------------|--------------|
| 902 - 928 | 50 mV/m | 500 uV/m | 3 |
| | (94dBuV/m) | (54dBuV/m) | |
| 2400 – 2483.5 | 50 mV/m | 500 uV/m | 3 |
| | (94dBuV/m) | (54dBuV/m) | |
| 5725 – 5875 | 50 mV/m | 500 uV/m | 3 |
| | (94dBuV/m) | (54dBuV/m) | |
| 24.0 – 24.25 GHz | 250 mV/m | 2500 uV/m | 3 |
| | (107.95dBuV/m) | (67.95dBuV/m) | |



Report No.: ER/2008/10038 Issue Date: Mar. 04, 2008

Page: 8 of 32

(3) Radiated Emission15.249 (d)

Emission Radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in Section 15.209 as below, whichever is the lesser attenuation.

| Frequency | Field strength | Distance (m) | Field strength at 3m |
|-----------|----------------|--------------|----------------------|
| (MHz) | μV/m | | dBμV/m |
| 1.705-30 | 30 | 30 | 69.54 |
| 30-88 | 100 | 3 | 40 |
| 88-216 | 150 | 3 | 43.5 |
| 216-960 | 200 | 3 | 46 |
| Above 960 | 500 | 3 | 54 |

(4) Radiated Emission 15.249(e)

For frequencies above 1000MHz, the above field strength limits are based on average limits. The peak filed strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20dB under any condition of modulation.

Remark: 1. Emission level in dBuV/m=20 log (uV/m)

- 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
- 3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of ξ 15.205
- 4. Emission spurious frequency which appearing within the Restricted Bands specified in provision of ξ 15.205, then the general radiated emission limits in ξ 15.209 apply.



Report No.: ER/2008/10038 Issue Date: Mar. 04, 2008

Page: 9 of 32

Configuration of Tested System

Fig. 2-1 Configuration of TX




Table 2-2 Equipment Used in Tested System

| Item | Equipment | Mfr/Brand | Model/ Type No. | FCC ID | Series No. | Data Cable | Power Cord |
|------|-----------|-----------|--------------------|--------|------------|------------|------------|
| 1. | NoteBook | IBM | T40 | N/A | 99HCYF4 | N/A | N/A |

Note: All the above equipment/cables were placed in worse case positions to maximize emission signals during emission test.

Grounding: Grounding was in accordance with the manufacturer's requirements and conditions for the intended use.



Report No.: ER/2008/10038 Issue Date: Mar. 04, 2008

Page: 10 of 32

3. Summary of Test Results

| FCC Rules | Description Of Test | Result | |
|---------------|-----------------------------|-----------|--|
| §15.207 | Conducted Emission | Compliant | |
| §15.249(a)(e) | Radiated Emission | Compliant | |
| §15.249(d) | 26dB band width Measurement | Compliant | |

Description of test modes

Frequency 2402MHz, 2420MHz and 2438MHz are chosen for full testing. The X, Y and Z-axis of EUT were pre-test; X mode is the worst case and reported.



Report No.: ER/2008/10038 Issue Date: Mar. 04, 2008


Page: 11 of 32

4. Conducted Emissions Test

Measurement Procedure:

- 1. The EUT was placed on a table which is 0.8m above ground plane.
- 2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 3. Repeat above procedures until all frequency measured were complete.

Test SET-UP (Block Diagram of Configuration)



Measurement Equipment Used:

| | Conducted Emission Test Site | | | | | | |
|-------------------|------------------------------|-----------|------------|------------|------------|--|--|
| EQUIPMENT | MFR | MODEL | SERIAL | LAST | CAL DUE. | | |
| TYPE | | NUMBER | NUMBER | CAL. | | | |
| EMC Analyzer | НР | 8594EM | 3624A00203 | 09/02/2007 | 09/03/2008 | | |
| EMI Test Receiver | R&S | ESCS30 | 828985/004 | 06/09/2007 | 06/10/2008 | | |
| Transient Limiter | НР | 11947A | 3107A02062 | 09/02/2007 | 09/03/2008 | | |
| LISN | Rolf-Heine | NNB-2/16Z | 99012 | 12/31/2007 | 12/30/2008 | | |
| LISN | Rolf-Heine | NNB-2/16Z | 99013 | 12/24/2007 | 12/23/2008 | | |
| Coaxial Cables | N/A | No. 3, 4 | N/A | 12/01/2007 | 12/01/2208 | | |

Measurement Result:

This document is issued by the Company subject to its General Conditions of Service printed overleaf or available on request and accessible at www.sgs.com. Attention is drawn to the limitations of liability, indemnification, and Jurisdictional issued defined therein. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, without prior approval of Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful and offenders may be prosecuted to the fullest extent of the law. 此報告是遵循本公司訂定之通用服務條款所製作發放, 請注意此條款列印於背面,亦可在www.sgs.com中查閱。將本公司之義務,免責,管轄權皆明確規範之。除非另有說明,此報告結果僅對檢驗之樣品負責。本報告未經本公司書面許可,不可部份複製。對本報告內容或外觀之任何未經授權之變更、僞造、竄改皆屬非法,違犯者將會被依法追訴。




Report No.: ER/2008/10038 Issue Date: Mar. 04, 2008

Page: 12 of 32

AC POWER LINE CONDUCTED EMISSION TEST DATA

| Operation Mode: | Operation mode | | | Test Date: | Jan 25, 2008 |
|-----------------|----------------|-----------|------|------------|--------------|
| Temperature: | 25 | Humidity: | 62 % | Test By: | Sky |



Site SGS CONDUCTED #1

Limit: CISPR22 Class B Conduction(QP)

EUT: Miniature Physiologic Recorder

M/N: KY-1A Note: OPERATION

| Phase: | L1 | Temperature: | 25 °C |
|----------|--------------|--------------|-------|
| Power: | AC 120V/60Hz | Humidity: | 62 % |
| Distance | t. | Air Pressure | hpa |

| No. Mk. | Freq. | Reading Level | Factor | Measure- ment | Limit | Over | | |
|---------|--------|------------------|--------|------------------|-------|--------|----------|---------|
| | MHz | dBu∀ | dB | dBu∀ | dBu∀ | dB | Detector | Comment |
| 1 | 0.2514 | 42.48 | 0.02 | 42.50 | 61.71 | -19.21 | QP | |
| 2 | 0.2514 | 26.39 | 0.02 | 26.41 | 51.71 | -25.30 | AVG | |
| 3 | 0.2909 | 46.38 | 0.02 | 46.40 | 60.50 | -14.10 | QP | |
| 4 | 0.2909 | 35.41 | 0.02 | 35.43 | 50.50 | -15.07 | AVG | |
| 5 | 0.3149 | 46.65 | 0.02 | 46.67 | 59.84 | -13.17 | QP | |
| 6 | 0.3149 | 33.84 | 0.02 | 33.86 | 49.84 | -15.98 | AVG | |
| 7 | 0.3945 | 44.42 | 0.02 | 44.44 | 57.97 | -13.53 | QP | |
| 8 | 0.3945 | 34.15 | 0.02 | 34.17 | 47.97 | -13.80 | AVG | |
| 9 * | 0.4686 | 44.63 | 0.02 | 44.65 | 56.54 | -11.89 | QP | |
| 10 | 0.4686 | 30.28 | 0.02 | 30.30 | 46.54 | -16.24 | AVG | |
| 11 | 0.5716 | 43.83 | 0.02 | 43.85 | 56.00 | -12.15 | QP | |
| 12 | 0.5716 | 30.27 | 0.02 | 30.29 | 46.00 | -15.71 | AVG | |


This document is issued by the Company subject to its General Conditions of Service printed overleaf or available on request and accessible at www.sgs.com. Attention is drawn to the limitations of liability, indemnification, and Jurisdictional issued defined therein. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, without prior approval of Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful and offenders may be prosecuted to the fullest extent of the law. 此報告是遵循本公司訂定之通用服務條款所製作發放,請注意此條款列印於背面,亦可在www.sgs.com中查閱。將本公司之義務,免責,管轄權皆明確規範之。除非另有說明,此報告結果僅對檢驗之樣品負責。本報告未經本公司書面許可,不可部份複製。對本報告內容或外觀之任何未經授權之變更、僞造、竄改皆屬非法,違犯者將會被依法追訴。



Report No.: ER/2008/10038 Issue Date: Mar. 04, 2008

Page: 13 of 32

Conducted Emission Measurement



Site SGS CONDUCTED #1

Limit: CISPR22 Class B Conduction(QP) EUT: Miniature Physiologic Recorder

M/N: KY-1A Note: OPERATION

25 °C Phase: N Temperature: AC 120V/60Hz Humidity: Power: Distance: Air Pressure: hpa

| No. Mk. | Freq. | Reading Level | Factor | Measure- ment | Limit | Over | | |
|---------|--------|------------------|--------|------------------|-------|--------|----------|---------|
| | MHz | dBu∀ | dB | dBu√ | dBu∀ | dB | Detector | Comment |
| 1 | 0.3027 | 46.14 | 0.02 | 46.16 | 60.17 | -14.01 | QP | |
| 2 | 0.3027 | 35.34 | 0.02 | 35.36 | 50.17 | -14.81 | AVG | |
| 3 | 0.3234 | 46.45 | 0.02 | 46.47 | 59.62 | -13.15 | QP | |
| 4 | 0.3234 | 25.99 | 0.02 | 26.01 | 49.62 | -23.61 | AVG | |
| 5 | 0.4051 | 45.52 | 0.02 | 45.54 | 57.75 | -12.21 | QP | |
| 6 | 0.4051 | 35.74 | 0.02 | 35.76 | 47.75 | -11.99 | AVG | |
| 7 | 0.4686 | 45.32 | 0.02 | 45.34 | 56.54 | -11.20 | QP | |
| 8 | 0.4686 | 31.39 | 0.02 | 31.41 | 46.54 | -15.13 | AVG | |
| 9 * | 0.5716 | 44.96 | 0.02 | 44.98 | 56.00 | -11.02 | QP | |
| 10 | 0.5716 | 30.44 | 0.02 | 30.46 | 46.00 | -15.54 | AVG | |
| 11 | 0.6973 | 39.76 | 0.02 | 39.78 | 56.00 | -16.22 | QP | |
| 12 | 0.6973 | 26.63 | 0.02 | 26.65 | 46.00 | -19.35 | AVG | |

This document is issued by the Company subject to its General Conditions of Service printed overleaf or available on request and accessible at www.sgs.com. Attention is drawn to the limitations of liability, indemnification, and Jurisdictional issued defined therein. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, without prior approval of Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful and offenders may be prosecuted to the fullest extent of the law. 此報告是遵循本公司訂定之通用服務條款所製作發放,請注意此條款列 印於背面,亦可在<u>www.sgs.com</u>中查閱。將本公司之義務,免責,管轄權皆明確規範之。除非另有說明,此報告結果僅對檢驗之樣品負責。本報告未經本公司書面許可,不可 部份複製。對本報告內容或外觀之任何未經授權之變更、僞造、竄改皆屬非法,違犯者將會被依法追訴。



Report No.: ER/2008/10038 Issue Date: Mar. 04, 2008

Page: 14 of 32


5. Radiated Emission Test

Measurement Procedure


- 1. The EUT was placed on a turntable that is 0.8m above ground plane.
- 2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 4. Repeat above procedures until all frequency measured were complete.

Test SET-UP (Block Diagram of Configuration)

(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(B) Radiated Emission Test Set-UP Frequency Over 1 GHz



This document is issued by the Company subject to its General Conditions of Service printed overleaf or available on request and accessible at www.sgs.com. Attention is drawn to the limitations of liability, indemnification, and Jurisdictional issued defined therein. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, without prior approval of Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful and offenders may be prosecuted to the fullest extent of the law. 此報告是遵循本公司訂定之通用服務條款所製作發放, 請注意此條款列印於背面,亦可在www.sgs.com中查閱。將本公司之義務,免責,管轄權皆明確規範之。除非另有說明,此報告結果僅對檢驗之樣品負責。本報告未經本公司書面許可,不可部份複製。對本報告內容或外觀之任何未經授權之變更、僞造、竄改皆屬非法,違犯者將會被依法追訴。



Report No.: ER/2008/10038 Issue Date: Mar. 04, 2008

Page: 15 of 32

Measurement Equipment Used:

| | 9 | 66 Chamber | | | |
|-------------------|--------------|------------------------|------------|------------|------------|
| EQUIPMENT | MFR | MODEL | SERIAL | LAST | CAL DUE. |
| TYPE | | NUMBER | NUMBER | CAL. | |
| Spectrum Analyzer | Agilent | E4446A | MY43360126 | 03/29/2007 | 03/28/2008 |
| Spectrum Analyzer | Agilent | E7405A | US41160416 | 08/27/2007 | 08/26/2008 |
| Bilog Antenna | SCHWAZBECK | VULB9163 | 152 | 06/03/2007 | 06/02/2008 |
| Horn antenna | Schwarzbeck | BBHA 9120D | 309/320 | 08/16/2007 | 08/15/2008 |
| Horn antenna | Schwarzbeck | BBHA 9170 | 184/185 | 07/04/2007 | 07/03/2008 |
| Pre-Amplifier | HP | 8447D | 2944A09469 | 07/19/2007 | 07/18/2008 |
| Pre-Amplifier | HP | 8449B | 3008A00578 | 02/26/2008 | 02/25/2009 |
| Turn Table | HD | DT420 | N/A | N.C.R | N.C.R |
| Antenna Tower | HD | MA240-N | 240/657 | N.C.R | N.C.R |
| Controller | HD | HD100 | N/A | N.C.R | N.C.R |
| Low Loss Cable | HUBER+SUHNER | SUCOFLEX 104PEA-10M | 10m | 10/09/2007 | 10/08/2008 |
| Low Loss Cable | HUBER+SUHNER | SUCOFLEX 104PEA-3M | 3m | 10/09/2007 | 10/08/2008 |
| Site NSA | SGS | 966 chamber | N/A | 11/17/2007 | 11/16/2008 |

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

| Where | FS = Field Strength | CL = Cable Attenuation Factor (Cable Loss) |
|-------|------------------------|--|
| | RA = Reading Amplitude | AG = Amplifier Gain |
| | AF = Antenna Factor | |

This document is issued by the Company subject to its General Conditions of Service printed overleaf or available on request and accessible at www.sgs.com. Attention is drawn to the limitations of liability, indemnification, and Jurisdictional issued defined therein. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, without prior approval of Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful and offenders may be prosecuted to the fullest extent of the law. 此報告是遵循本公司訂定之通用服務條款所製作發放, 請注意此條款列印於背面,亦可在www.sgs.com中查閱。將本公司之義務,免責,管轄權皆明確規範之。除非另有說明,此報告結果僅對檢驗之樣品負責。本報告未經本公司書面許可,不可部份複製。對本報告內容或外觀之任何未經授權之變更、僞造、竄改皆屬非法,違犯者將會被依法追訴。

SGS Taiwan Ltd. No. 134, Wu Kung Rd., Wuku Industrial Zone, Taipei Country, Taiwan. / 台灣檢驗科技股份有限公司 t (886-2) 2299-3939 f (886-2) 2298-2698 www.sgs.com.tw



Report No.: ER/2008/10038 Issue Date: Mar. 04, 2008

Page: 16 of 32

Measurement Result

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode TX Low **Test Date** Feb. 12, 2008

Fundamental Frequency 2402MHz Test By Sky Pol Temperature Ver./Hor 25

Humidity 65 %

| Freq. | Ant.Pol. | Detector Mode | Reading | Factor | Actual FS | Limit3m | Safe Margin |
|--------|----------|------------------|---------|--------|-----------|----------|----------------|
| (MHz) | H/V | (PK/QP) | (dBuV) | (dB) | (dBuV/m) | (dBuV/m) | (dB) |
| 65.89 | V | Peak | 45.84 | -15.09 | 30.75 | 40.00 | -9.25 |
| 101.78 | V | Peak | 49.39 | -16.87 | 32.52 | 43.50 | -10.98 |
| 211.39 | V | Peak | 42.31 | -15.22 | 27.09 | 43.50 | -16.41 |
| | | | | | | | |
| 64.92 | Н | Peak | 45.29 | -14.83 | 30.46 | 40.00 | -9.54 |
| 119.24 | Н | Peak | 44.97 | -15.32 | 29.65 | 43.50 | -13.85 |
| 516.94 | Н | Peak | 39.35 | -8.17 | 31.18 | 46.00 | -14.82 |

- (1) Measuring frequencies from 30 MHz to the 1GHz •
- (2) Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak/QP detector mode.
- (3) Datas of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (4) The IF bandwidth of SPA between 30MHz to 1GHz was 100KHz, VBW=300KHz.



Report No.: ER/2008/10038 **Issue Date: Mar. 04, 2008**

Page: 17 of 32

Radiated Spurious Emission Measurement Result (below 1GHz)

TX Mid Operation Mode Feb. 12, 2008 Test Date

Fundamental Frequency 2420MHz Test By Sky Ver./Hor Temperature Pol 25

65 % Humidity

| Freq. | Ant.Pol. | Detector Mode | Reading | Factor | Actual FS | Limit3m | Safe Margin |
|--------|----------|------------------|---------|--------|-----------|----------|----------------|
| (MHz) | H/V | (PK/QP) | (dBuV) | (dB) | (dBuV/m) | (dBuV/m) | (dB) |
| 101.78 | V | Peak | 49.21 | -16.87 | 32.34 | 43.50 | -11.16 |
| 198.78 | V | Peak | 43.16 | -15.56 | 27.60 | 43.50 | -15.90 |
| | | | | | | | |
| 65.89 | Н | Peak | 45.72 | -15.09 | 30.63 | 40.00 | -9.37 |
| 119.24 | Н | Peak | 43.98 | -15.32 | 28.66 | 43.50 | -14.84 |
| 468.44 | Н | Peak | 43.18 | -8.55 | 34.63 | 46.00 | -11.37 |

- (1) Measuring frequencies from 30 MHz to the 1GHz \circ
- (2) Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak/QP detector mode.
- (3) Datas of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (4) The IF bandwidth of SPA between 30MHz to 1GHz was 100KHz, VBW=300KHz.



Report No.: ER/2008/10038 **Issue Date: Mar. 04, 2008**

Page: 18 of 32

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode TX High Feb. 12, 2008 Test Date

Fundamental Frequency 2438MHz Test By Sky Ver./Hor Temperature 25 Pol

65 % Humidity

| Freq. | Ant.Pol. | Detector Mode | Reading | Factor | Actual FS | Limit3m | Safe Margin |
|--------|----------|------------------|---------|--------|-----------|----------|----------------|
| (MHz) | H/V | (PK/QP) | (dBuV) | (dB) | (dBuV/m) | (dBuV/m) | (dB) |
| 65.89 | V | Peak | 46.30 | -15.09 | 31.21 | 40.00 | -8.79 |
| 101.78 | V | Peak | 48.05 | -16.87 | 31.18 | 43.50 | -12.32 |
| 211.39 | V | Peak | 47.67 | -15.22 | 32.45 | 43.50 | -11.05 |
| | | | | | | | |
| 65.89 | Н | Peak | 46.86 | -15.09 | 31.77 | 40.00 | -8.23 |
| 119.24 | Н | Peak | 43.81 | -15.32 | 28.49 | 43.50 | -15.01 |
| 492.69 | Н | Peak | 40.65 | -8.50 | 32.15 | 46.00 | -13.85 |

- (1) Measuring frequencies from 30 MHz to the 1GHz •
- (2) Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak/QP detector mode.
- (3) Datas of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (4) The IF bandwidth of SPA between 30MHz to 1GHz was 100KHz, VBW=300KHz.



Report No.: ER/2008/10038 Issue Date: Mar. 04, 2008

Page: 19 of 32

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode: TX Low Test Date: Feb. 21, 2008

Fundamental Frequency: 2402MHz

Test By: Sky

Temperature: 25

Pol: Vertical

Humidity: 65 %

| | | Peak | $\mathbf{A}\mathbf{V}$ | | Actual | Actual | Peak Limit | AV Limit | | |
|---------|----------|---------|------------------------|--------|----------|---------|------------|----------|--------|---|
| Freq. | Ant.Pol. | Reading | Reading | Factor | Peak FS | AV FS | at 3m | at 3m | Margin | |
| (MHz) | H/V | (dBuV) | (dBuV) | (dB) | (dBuV/m) | (dBuV/m | (dBuV/m) | (dBuV/m) | (dB) | |
| 2402.0 | V | 88.66 | | -1.30 | 87.36 | | 114.00 | 94.00 | -6.64 | F |
| 2390.0 | V | 35.30 | | -1.39 | 33.91 | | 74.00 | 54.00 | -20.09 | |
| | | | | | | | | | | |
| 4796.0 | V | 45.14 | | 5.99 | 51.13 | | 74.00 | 54.00 | -2.87 | S |
| 7201.0 | V | 39.27 | | 12.89 | 52.16 | | 74.00 | 54.00 | -1.84 | S |
| 4804.0 | V | | | | | | 74.00 | 54.00 | | Н |
| 7206.0 | V | | | | | | 74.00 | 54.00 | | Н |
| 9608.0 | V | | | | | | 74.00 | 54.00 | | Н |
| 12010.0 | V | | | | | | 74.00 | 54.00 | | Н |
| 14412.0 | V | | | | | | 74.00 | 54.00 | | Н |
| 16814.0 | V | | | | | | 74.00 | 54.00 | | Н |
| 19216.0 | V | | | | | | 74.00 | 54.00 | | Н |
| 21618.0 | V | | | | | | 74.00 | 54.00 | | Н |
| 24020.0 | V | | | | | | 74.00 | 54.00 | | Н |

- (1) Measuring frequencies from 30MHz to the 10tth of fundamental frequency •
- Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB
- (3) "F" denotes fundamental frequency; "H" denotes harmonics frequency. "S" denotes spurious frequency.
- (4) Datas of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) Spectrum Peak mode IF bandwidth Setting: 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- (6) Spectrum AV mode IF B bandwidth Setting: 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.



Report No.: ER/2008/10038 Issue Date: Mar. 04, 2008

Page: 20 of 32

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode: TX Low Test Date: Feb. 21, 2008

Fundamental Frequency: 2402MHz Test By: Sky

Temperature: 25 Pol: Horizontal

Humidity: 65 %

| | | Peak | AV | | Actual | Actual | Peak Limit | AV Limit | | |
|---------|---------|---------|---------|--------|----------|---------|------------|----------|--------|---|
| Freq. | Ant.Pol | Reading | Reading | Factor | Peak FS | AV FS | at 3m | at 3m | Margin | |
| (MHz) | H/V | (dBuV) | (dBuV) | (dB) | (dBuV/m) | (dBuV/m | (dBuV/m) | (dBuV/m) | (dB) | |
| 2402.0 | Н | 93.12 | | -1.30 | 91.82 | | 114.00 | 94.00 | -2.18 | F |
| 2390.0 | Н | 33.43 | | -1.39 | 32.04 | | 74.00 | 54.00 | -21.96 | |
| | | | | | | | | | | |
| 4796.0 | Н | 48.88 | 38.77 | 5.99 | 54.87 | 44.76 | 74.00 | 54.00 | -9.24 | S |
| 4804.0 | H | | | | | | 74.00 | 54.00 | | Н |
| 7206.0 | Н | | | | | | 74.00 | 54.00 | | Н |
| 9608.0 | H | | | | | | 74.00 | 54.00 | | Н |
| 12010.0 | H | | | | | | 74.00 | 54.00 | | Н |
| 14412.0 | Н | | | | | | 74.00 | 54.00 | | Н |
| 16814.0 | Н | | | | | | 74.00 | 54.00 | | Н |
| 19216.0 | Н | | | | | | 74.00 | 54.00 | | Н |
| 21618.0 | Н | | | | | | 74.00 | 54.00 | | Н |
| 24020.0 | Н | | | | | | 74.00 | 54.00 | | Н |

- (1) Measuring frequencies from 30MHz to the 10tth of fundamental frequency •
- (2) Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB
- (3) "F" denotes fundamental frequency; "H" denotes harmonics frequency. "S" denotes spurious frequency.
- (4) Datas of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) Spectrum Peak mode IF bandwidth Setting: 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- (6) Spectrum AV mode IF B bandwidth Setting: 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.



Report No.: ER/2008/10038 Issue Date: Mar. 04, 2008

Page: 21 of 32

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode: TX Mid Test Date: Feb. 21, 2008

Fundamental Frequency: 2420MHz

Test By: Sky

Temperature: 25

Pol: Vertical

Humidity: 65 %

| | | Peak | AV | | Actual | Actual | Peak Limit | AV Limit | | |
|---------|---------|---------|---------|--------|----------|---------|------------|----------|--------|---|
| Freq. | Ant.Pol | Reading | Reading | Factor | Peak FS | AV FS | at 3m | at 3m | Margin | |
| (MHz) | H/V | (dBuV) | (dBuV) | (dB) | (dBuV/m) | (dBuV/m | (dBuV/m) | (dBuV/m) | (dB) | |
| 2402.0 | V | 90.54 | | -1.12 | 89.42 | | 114.00 | 94.00 | -4.58 | F |
| | | | | | | | | | | |
| 4828.5 | V | 46.13 | 33.58 | 6.05 | 52.18 | 39.63 | 74.00 | 54.00 | -14.37 | S |
| 7253.0 | V | 38.69 | | 12.91 | 51.60 | | 74.00 | 54.00 | -2.40 | S |
| 4804.0 | V | | | | | | 74.00 | 54.00 | | Н |
| 7206.0 | V | | | | | | 74.00 | 54.00 | | Н |
| 9608.0 | V | | | | | | 74.00 | 54.00 | | Н |
| 12010.0 | V | | | | | | 74.00 | 54.00 | | Н |
| 14412.0 | V | | | | | | 74.00 | 54.00 | | Н |
| 16814.0 | V | | | | | | 74.00 | 54.00 | | Н |
| 19216.0 | V | | | | | | 74.00 | 54.00 | | Н |
| 21618.0 | V | | | | | | 74.00 | 54.00 | | Н |
| 24020.0 | V | | | | | | 74.00 | 54.00 | | Н |

- (1) Measuring frequencies from 30MHz to the 10tth of fundamental frequency \circ
- (2) Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB
- (3) "F" denotes fundamental frequency; "H" denotes harmonics frequency. "S" denotes spurious frequency.
- (4) Datas of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) Spectrum Peak mode IF bandwidth Setting: 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- (6) Spectrum AV mode IF B bandwidth Setting: 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.



Report No.: ER/2008/10038 Issue Date: Mar. 04, 2008

Page: 22 of 32

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode: TX Mid Test Date: Feb. 21, 2008

Fundamental Frequency: 2420MHz Test By: Sky

Temperature: 25 Pol: Horizontal

Humidity: 65 %

| | | Peak | AV | | Actual | Actual | Peak Limit | AV Limit | | |
|---------|---------|---------|---------|--------|----------|---------|------------|----------|---------------|---|
| Freq. | Ant.Pol | Reading | Reading | Factor | Peak FS | AV FS | at 3m | at 3m | Margin | |
| (MHz) | H/V | (dBuV) | (dBuV) | (dB) | (dBuV/m) | (dBuV/m | (dBuV/m) | [dBuV/m] | (dB) | |
| 2402.0 | Н | 93.82 | | -1.22 | 92.60 | | 114.00 | 94.00 | -1.40 | F |
| | | | | | | | | | | |
| 4828.5 | Н | 44.85 | 34.38 | 6.05 | 50.90 | 40.43 | 74.00 | 54.00 | -13.57 | S |
| 4804.0 | Н | | | | | | 74.00 | 54.00 | | Η |
| 7206.0 | Н | | | | | | 74.00 | 54.00 | | Η |
| 9608.0 | Н | | | | | | 74.00 | 54.00 | | Η |
| 12010.0 | Н | | | | | | 74.00 | 54.00 | | Н |
| 14412.0 | Н | | | | | | 74.00 | 54.00 | | Η |
| 16814.0 | Н | | | | | | 74.00 | 54.00 | | Н |
| 19216.0 | Н | | | | | | 74.00 | 54.00 | | Н |
| 21618.0 | Н | | | | | | 74.00 | 54.00 | | Н |
| 24020.0 | Н | | | | | | 74.00 | 54.00 | | Н |

- (1) Measuring frequencies from 30MHz to the 10tth of fundamental frequency •
- Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB
- (3) "F" denotes fundamental frequency; "H" denotes harmonics frequency. "S" denotes spurious frequency.
- (4) Datas of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) Spectrum Peak mode IF bandwidth Setting: 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- (6) Spectrum AV mode IF B bandwidth Setting: 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.



Report No.: ER/2008/10038 Issue Date: Mar. 04, 2008

Page: 23 of 32

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode: TX High Test Date: Feb. 21, 2008

Fundamental Frequency: 2438MHz

Test By: Sky

Temperature: 25

Pol: Vertical

Humidity: 65 %

| | | Peak | AV | | Actual | Actual | Peak Limit | AV Limit | | |
|---------|----------|---------|---------|--------|----------|---------|------------|----------|--------|---|
| Freq. | Ant.Pol. | Reading | Reading | Factor | Peak FS | AV FS | at 3m | at 3m | Margin | |
| (MHz) | H/V | (dBuV) | (dBuV) | (dB) | (dBuV/m) | (dBuV/m | (dBuV/m) | (dBuV/m) | (dB) | |
| 2438.0 | V | 90.19 | | -1.13 | 89.06 | | 114.00 | 94.00 | -4.94 | F |
| 2483.6 | V | 33.14 | | -0.92 | 32.22 | | 114.00 | 94.00 | -61.78 | |
| | | | | | | | | | | |
| 4880.5 | V | 45.27 | 33.89 | 6.17 | 51.44 | 40.06 | 74.00 | 54.00 | -13.94 | S |
| 4876.0 | V | | | | | | 74.00 | 54.00 | | Н |
| 7314.0 | V | | | | | | 74.00 | 54.00 | | Н |
| 9752.0 | V | | | | | | 74.00 | 54.00 | | Н |
| 12190.0 | V | | | | | | 74.00 | 54.00 | | Н |
| 14628.0 | V | | | | | | 74.00 | 54.00 | | Н |
| 17066.0 | V | | | | | | 74.00 | 54.00 | | Н |
| 19504.0 | V | | | | | | 74.00 | 54.00 | | Н |
| 21942.0 | V | | | | | | 74.00 | 54.00 | | Н |
| 24380.0 | V | | | | | | 74.00 | 54.00 | | Н |

- (1) Measuring frequencies from 30MHz to the 10tth of fundamental frequency \circ
- (2) Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB
- (3) "F" denotes fundamental frequency; "H" denotes harmonics frequency. "S" denotes spurious frequency.
- (4) Datas of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) Spectrum Peak mode IF bandwidth Setting: 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- (6) Spectrum AV mode IF B bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.



Report No.: ER/2008/10038 Issue Date: Mar. 04, 2008

Page: 24 of 32

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode: TX High Test Date: Feb. 21, 2008

Fundamental Frequency: 2438MHz Test By: Sky

Temperature: 25 Pol: Horizontal

Humidity: 65 %

| | | Peak | AV | | Actual | Actual | Peak Limit | AV Limit | | |
|---------|--------|---------|---------|--------|----------|--------|------------|----------|--------|---|
| Freq. | \nt.Po | Reading | Reading | Factor | Peak FS | AV FS | at 3m | at 3m | Margin | |
| (MHz) | H/V | (dBuV) | (dBuV) | (dB) | (dBuV/m) | dBuV/m | (dBuV/m) | (dBuV/m) | (dB) | |
| 2438.0 | Н | 93.96 | | -1.13 | 92.83 | | 114.00 | 94.00 | -1.17 | F |
| 2483.6 | Н | 33.59 | | -0.92 | 32.67 | | 114.00 | 94.00 | -61.33 | |
| | | | | | | | | | | |
| 4880.5 | Н | 47.46 | 33.99 | 6.17 | 53.63 | 40.16 | 74.00 | 54.00 | -13.84 | S |
| 4876.0 | Н | | | | | | 74.00 | 54.00 | | Н |
| 7314.0 | Н | | | | | | 74.00 | 54.00 | | Н |
| 9752.0 | Н | | | | | | 74.00 | 54.00 | | Н |
| 12190.0 | Н | | | | | | 74.00 | 54.00 | | Н |
| 14628.0 | Н | | | | | | 74.00 | 54.00 | | Н |
| 17066.0 | Н | | | | | | 74.00 | 54.00 | | Н |
| 19504.0 | Н | | | | | | 74.00 | 54.00 | | Н |
| 21942.0 | Н | | | | | | 74.00 | 54.00 | | Н |
| 24380.0 | Н | | | | | | 74.00 | 54.00 | | Н |

- (1) Measuring frequencies from 30MHz to the 10tth of fundamental frequency •
- (2) Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB
- (3) "F" denotes fundamental frequency; "H" denotes harmonics frequency. "S" denotes spurious frequency.
- (4) Datas of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) Spectrum Peak mode IF bandwidth Setting: 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- (6) Spectrum AV mode IF B bandwidth Setting: 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.



Report No.: ER/2008/10038 Issue Date: Mar. 04, 2008

Page: 25 of 32

6. 26 dB Band Width Measurement

Measurement Procedure

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. Set ETU normal operating mode.
- 3. Set SPA Center Frequency = fundamental frequency, RBW, VBW = 100KHz, Span = 3MHz
- 4. Set SPA Max hold. Mark peak, -26dB.

Test SET-UP (Block Diagram of Configuration)

Same as 4.2 Radiated Emission Measurement.

Measurement Equipment Used:

Same as 4.2 Radiated Emission Measurement.

Measurement Results:

Channel Lowest = 843.154MHz Channel Mid = 726.389MHz

Channel Highest = 963.055MHz


Refer to attached data chart.



Report No.: ER/2008/10038 Issue Date: Mar. 04, 2008

Page: 26 of 32

26dB Band Width test Plot (CH Low)



26dB Band Width test Plot (CH Mid)



This document is issued by the Company subject to its General Conditions of Service printed overleaf or available on request and accessible at www.sgs.com. Attention is drawn to the limitations of liability, indemnification, and Jurisdictional issued defined therein. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, without prior approval of Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful and offenders may be prosecuted to the fullest extent of the law. 此報告是遵循本公司訂定之通用服務條款所製作發放, 請注意此條款列印於背面,亦可在www.sgs.com中查閱。將本公司之義務,免責,管轄權皆明確規範之。除非另有說明,此報告結果僅對檢驗之樣品負責。本報告未經本公司書面許可,不可部份複製。對本報告內容或外觀之任何未經授權之變更、僞造、竄改皆屬非法,違犯者將會被依法追訴。



Report No.: ER/2008/10038 Issue Date: Mar. 04, 2008

Page: 27 of 32

26dB Band Width test Plot (CH High)

