



國際電器認證中心有限公司 International Electrical Certification Centre Ltd.

提供電器產品測試國際認證及諮詢服務 Technical Services in Electrical Product Testing, International Certification & Information



Accredited Laboratory



Network Partner



Qualified Independent Laboratory

F C C -

TEST REPORT

REPORT NO.: 51422

Address 地址: Units 602-605, 6/F., 31 Lok Yip Rd., On Lok Tsuen, Fanling, N.T., Hong Kong.
香港新界粉嶺安樂村樂業路31號6樓602-605室
China 中國
Address 地址: IECC (Guangzhou) Services Co., Ltd. 廣州時並進技術服務有限公司
Flat A, 2/F., Block 3, 56 Shuiyin Road, Guangzhou, P.R. of China.
廣州市水盈路56號3樓2A室

Tel 電話: (852) 2305 2570
Fax 傳真: (852) 2766 4480

Tel 電話: (86-20) 8768 4838
Fax 傳真: (86-20) 8768 3918

E-mail 電子郵件: info@iecc.com.hk
Home Page 網頁: <http://www.iecc.com.hk>

E-mail 電子郵件: info@iecc.net.cn
Home Page 網頁: <http://www.iecc.net.cn>

FCC – Test Report

Date: 2008-12-17

No. 51422

Page 2 of 27

FCC listed testlab acc. to Section 2.948 of the FCC - Rules

Product : Self-Powered AM/FM Weather Band Radio with Built-In Flashlight

Product Class : Communication Receiver (Super Hetrodyne)

Model No. : TF-35, TF-37

Importer / Manufacturer : TEN FORWARD LTD

FCC ID No. : V2N35W



Accredited Laboratory



Network Partner



Qualified Independent Laboratory

FCC – Test Report

Date: 2008-12-17

No. 51422

Page 3 of 27

TABLE OF CONTENTS

1. Cover sheet
2. Introduction
3. Table of Contents
4. Laboratory Report
5. Test Location and Summary of Test Results
6. Test Equipment List
7. Radiated Emission Test Setup
8. Conducted Emission Test Setup
9. Test Procedure
10. Test Results
- 11-26. Measurement Data
27. Photo of sample

FCC – Test Report

Date: 2008-12-17


No. 51422

Page 4 of 27

LABORATORY - REPORT

APPLICANT: TEN FORWARD LTD.**ADDRESS:** Rm 1708-9, Lucida Industrial Building
43-47 Wang Lung Street
Tsuen Wan, N.T.
Hong Kong**DATE OF SAMPLE RECEIVED:** 2008-11-19**DATE OF TESTING:** 2008-11-20 to 2008-12-15**DESCRIPTION OF SAMPLE:**

Product: Self-Powered AM/FM Weather Band Radio with Built-In Flashlight
Product class: Communication Receiver (Super Hetrodyne)
Model No.: TF-35, TF-37
(Model TF-37 is identical with the test model TF-35 for circuit diagram and PCBs, but with different front panel)
FCC ID number: V2N35W
Band combination: AM / FM / Weather Band
Rating: AC/DC adaptor - Input : AC 120V 60Hz, Output : DC 6V; or
DC 4.5V (AA size battery x 3) or DC 3.6V (rechargeable batteries)

CONDITION OF TEST SAMPLE: The received sample was under good condition.**INVESTIGATIONS REQUESTED:** Measurements to the relevant clauses of F.C.C. Rules and Regulations
Part 15 Subpart B – 'Unintentional Radiators'**RESULTS:** See the attached test sheets**CONCLUSIONS:** From the measurement data obtained, the tested sample was considered to have COMPLIED with the requirements for the relevant clauses of Federal Communications Commission Rules as specified above.

Stephen C.N. Wong
Technical Manager

FCC – Test Report

Date: 2008-12-17

No. 51422

Page 5 of 27

Test Locations

Radiated Emission Test (30 – 1000 MHz) and Conducted Emission Test

International Electrical Certification Centre Ltd.
Unit 602-605, 31 Lok Yip Road, On Lok Tsuen, Fanling, N.T., Hong Kong
Tel : +852 23052570
Fax : +852 27564480
Email : info@iecc.com.hk

Radiation Emission Test (1000 – 2000 MHz)

Shenzhen Academy of Metrology & Quality Inspection
Bldg. of Shenzhen Academy of Metrology and Quality Inspection
Longzhu Road, Nanshan, Shenzhen, China
Tel : +86 755 26001806
Fax : +86 755 26001809
Email : certification@smq.com.cn

Summary of Test Results

Radiated Emission:

Test result: O.K.
Test data: See attached data sheet

Conducted Emission:

Test result: O.K.
Test data: See attached data sheet

**FCC – Test Report**

Date: 2008-12-17

No. 51422

Page 6 of 27

TEST EQUIPMENT LISTRadiated Emission Test (30 – 1000 MHz) and Conducted Emission Test

Equipment	Manufacturer	Model	Serial No.	Last Calibration Date	Next Calibration Date
Test Receiver	Rohde & Schwarz	ESCS 30	100388	26/8/2008	25/8/2009
Artificial Mains Network (LISN)	Schwarzbeck	NSLK 8127	8127312	2/12/2008	1/12/2009
Antenna	Schaffner	CBL6111C	2791	22/07/2008	21/07/2010
Antenna Mast System	Schwarzbeck	AM9104	--	--	--
Turntable with Controller	Drehtisch	DT312	--	--	--

Radiation Emission Test (1000 – 2000 MHz)


Equipment	Manufacturer	Model	Serial No.	Last Calibration Date	Next Calibration Date
Test Receiver	Rohde & Schwarz	SB3436	838786/013	24/1/2008	23/1/2009
Bilog Antenna	Chase	SB3440	2591	24/1/2008	23/1/2009

FCC – Test Report

Date: 2008-12-17

No. 51422

Page 7 of 27

Radiated Emission Test Setup (3 m diatance)


FCC – Test Report

Date: 2008-12-17

No. 51422

Page 8 of 27

Conducted Emission Test Setup



LEGEND:

- 1) Interconnecting cables that hang closer than 40 cm to the groundplane shall be folded back and forth in the center forming a bundle 30 to 40 cm long (see 6.1.4 and 11.2.4).
- 2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m (see 6.1.4).
- 3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω. LISN can be placed on top of, or immediately beneath, reference groundplane (see 5.2.3 and 7.2.1).
 - 3.1) All other equipment powered from additional LISN(s).
 - 3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - 3.3) LISN at least 80 cm from nearest part of EUT chassis.
- 4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use (See 6.2.1.3 and 11.2.4).
- 5) Non-EUT components of EUT system being tested (see also Figure 13).
- 6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop (see 6.2.1.1 and 6.2.1.2).
- 7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the groundplane (see 5.2.2 for options).

FCC – Test Report

Date: 2008-12-17

No. 51422

Page 9 of 27

Test Procedure

Radiated Emission :

The EUT was tested according to ANSI 63.4-2003 for the requirements of FCC Part 15 Subpart B Section 15.109.

During the test, the sample was placed on a turn table and operated under various modes with supply at rated AC voltage (i.e AC120V 60Hz) to the host AC/DC adaptor. The table is 0.8 meter above the reference ground plane on the Test Site and can rotate 360 degrees to determine the position of the maximum emission level. Broad-band antennas for the frequency range 30 - 2000 MHz, connected with 10 meters coaxial cable to the test receiver was used for measurement. The antenna is capable of measuring both horizontal and vertical polarizations. The antenna was raised from 1 to 4 meters to find out the maximum emission level from the EUT.

An initial pre-scan was performed to find out the maximum emission level of the sample placed at 3 orthogonal planes. Final measurement (30 MHz –2000 MHz) was then performed to record the data for the emissions under worst-case condition for combination of the antenna orientation / height and turn table position.

Note : 1. The Open Aera Test Site located at IECC was placed on file with the FCC Pursuant to Section 2.948 of the FCC Rules (FCC Registration No. : 97774).
2. The Chamber Test Site located at Shenzhen Academy of Metrology & Quality Inspection was placed on file with the FCC Pursuant to Section 2.948 of the FCC Rules (FCC Registration No. : 274801).

Conducted Emission :

The EUT was tested according to ANSI 63.4-2003 for the requirements of FCC Part 15 Subpart B Section 15.107.

During the test, the sample was placed on a wooden table and operated under various modes with supply at rated AC voltage (i.e AC120V 60Hz) via the LISN to the host AC/DC adaptor. The table is 0.8 meter above the floor. The LISN was connected to the test receiver for conducted emission measurement (150kHz – 30MHz).

Address 地址

Units 602-605, 6/F., 31 Lok Yip Rd., On Lok Tsuen, Fanling, N.T., Hong Kong.
香港新界粉嶺安樂村樂業路31號6樓602-605室

China 中國

IECC (Guangzhou) Services Co., Ltd. 廣州勝並達技術服務有限公司

Address 地址

Flat A, 2/F., Block 3, 56 Shuiyin Road, Guangzhou, P.R. of China

廣州市水蔭路56號3棟2A室

Tel 電話: (852) 2305 2570
Fax 傳真: (852) 2756 4480

E-mail 電子郵件: info@iecc.com.hk

Home Page 網頁: http://www.iecc.com.hk

Postcode 郵政編號: 510075

Tel 電話: (86-20) 8768 4838
Fax 傳真: (86-20) 8768 3918

E-mail 電子郵件: info@iecc.net.cn

Home Page 網頁: http://www.iecc.net.cn

FCC – Test Report

Date: 2008-12-17

No. 51422

Page 10 of 27

Test Results

Radiated Emission :

Test Requirement: FCC Part 15 Subpart B Section 15.109
Test Method: ANSI C63.4 : 2003
Deviations from Standard Test Method: Nil
Frequency Range: 30MHz – 1000MHz (FM mode)
30MHz – 2000MHz (Weather Band mode)
30MHz – 1000MHz (Other modes)
Measurement Distance: 3 m
Class: Class B
Detector: Quasi-Peak

Refer to page 11- 16 for measurement data.

Conducted Emission :

Test Requirement: FCC Part 15 Subpart B Section 15.107
Test Method: ANSI C63.4 : 2003
Deviations from Standard Test Method: Nil
Frequency Range: 150kHz – 30MHz
Class: Class B
Detector: Quasi-Peak / Average

Refer to page 17 - 26 for measurement data.

U1

Date : 2008-12-17

Page 11 of 27

Radiated Emission
According: FCC Part 15 Subpart B (15.109)

IECC Ref: 51422
Model: TF-35
Applicant: TEN FORWARD LTD
Ser.Nr.: --
Oper. Mode: FM Mode
InterFreq: 10.7 MHz

Test Equipment
 Receiver: Rohde & Schwarz ESCS 30
 Antenna: Schaffner CBL6111C

Receiving - frequency (MHz)	Oscillator-frequency (MHz)	Harmonics	Reading dB μ V	Polarization	Correction Factor (dB)	Test Result dB(μ V/m)	Limit dB(μ V/m)
89.8	100.5	1	18.0	H	10.1	28.1	43.5
	201.0	2	22.0	H	8.6	30.6	43.5
	301.5	3	23.0	H	13.9	36.9	46.0
	402.0	4	< 16.0	H	16.9	< 32.9	46.0
	502.5	5	< 16.0	H	19.2	< 35.2	46.0
	603.0	6	< 16.0	H	20.9	< 36.9	46.0
	703.5	7	< 16.0	H	22.6	< 38.6	46.0
	804.0	8	< 16.0	H	24.0	< 40.0	46.0
	904.5	9	< 16.0	H	25.6	< 41.6	46.0
98.3	109.0	1	< 16.0	H	10.6	< 26.6	43.5
	218.0	2	25.0	H	8.7	33.7	46.0
	327.0	3	26.0	H	14.6	40.6	46.0
	436.0	4	23.0	H	17.8	40.8	46.0
	545.0	5	< 16.0	H	20.7	< 36.7	46.0
	654.0	6	< 16.0	H	21.6	< 37.6	46.0
	763.0	7	< 16.0	H	24.1	< 40.1	46.0
	872.0	8	< 16.0	H	25.3	< 41.3	46.0
	981.0	9	< 16.0	H	26.9	< 42.9	54.0
108.0	118.7	1	< 16.0	H	11.1	< 27.1	43.5
	237.4	2	22.0	H	11.0	33.0	46.0
	356.1	3	24.0	H	15.5	39.5	46.0
	474.8	4	< 16.0	H	18.7	< 34.7	46.0
	593.5	5	< 16.0	H	20.6	< 36.6	46.0
	712.2	6	< 16.0	H	22.9	< 38.9	46.0
	830.9	7	< 16.0	H	24.8	< 40.8	46.0
	949.6	8	< 16.0	H	27.6	< 43.6	46.0

The measurement results indicate that the test unit meets the FCC requirements

Note :

1. The above measured data are in Quasi-Peak values
2. The above results were the worst case results with the sample positioned in all 3 axis during the test.

The worst case data were obtained with the sample placed normally on the table and with the telescopic antenna positioned horizontally.

Operator : KT

U1

Date : 2008-12-17

Page 12 of 27

Radiated Emission

According: FCC Part 15 Subpart B (15.109)

IECC Ref: 51422
Model: TF-35
Applicant: TEN FORWARD LTD

Ser.Nr.: --
Oper. Mode: FM Mode
InterFreq: 10.7 MHz

Test Equipment

Receiver: Rohde & Schwarz ESCS 30
Antenna: Schaffner CBL6111C

Receiving - frequency (MHz)	Oscillator-frequency (MHz)	Harmonics	Reading dB μ V	Polarization	Correction Factor (dB)	Test Result dB(μ V/m)	Limit dB(μ V/m)
89.8	100.5	1	23.0	V	10.1	33.1	43.5
	201.0	2	21.0	V	8.6	29.6	43.5
	301.5	3	20.0	V	13.9	33.9	46.0
	402.0	4	< 16.0	V	16.9	< 32.9	46.0
	502.5	5	< 16.0	V	19.2	< 35.2	46.0
	603.0	6	< 16.0	V	20.9	< 36.9	46.0
	703.5	7	< 16.0	V	22.6	< 38.6	46.0
	804.0	8	< 16.0	V	24.0	< 40.0	46.0
	904.5	9	< 16.0	V	25.6	< 41.6	46.0
98.3	109.0	1	23.0	V	10.6	33.6	43.5
	218.0	2	27.0	V	8.7	35.7	46.0
	327.0	3	25.0	V	14.6	39.6	46.0
	436.0	4	26.0	V	17.8	43.8	46.0
	545.0	5	< 16.0	V	20.7	< 36.7	46.0
	654.0	6	< 16.0	V	21.6	< 37.6	46.0
	763.0	7	< 16.0	V	24.1	< 40.1	46.0
	872.0	8	< 16.0	V	25.3	< 41.3	46.0
	981.0	9	< 16.0	V	26.9	< 42.9	54.0
108.0	118.7	1	20.0	V	11.1	31.1	43.5
	237.4	2	< 16.0	V	11.0	< 27.0	46.0
	356.1	3	24.0	V	15.5	39.5	46.0
	474.8	4	17.0	V	18.7	35.7	46.0
	593.5	5	< 16.0	V	20.6	< 36.6	46.0
	712.2	6	< 16.0	V	22.9	< 38.9	46.0
	830.9	7	< 16.0	V	24.8	< 40.8	46.0
	949.6	8	< 16.0	V	27.6	< 43.6	46.0

The measurement results indicate that the test unit meets the FCC requirements

Note :

1. The above measured data are in Quasi-Peak values
2. The above results were the worst case results with the sample positioned in all 3 axis during the test.
The worst case data were obtained with the sample placed normally on the table and with the telescopic antenna positioned vertically.

Operator : KT

IT 5/6

Date : 2008-12-17

Page 13 of 27

Radiated Emission
Acc: FCC Part 15 Subpart B (15.109)

IECC Ref:	51422	Test Equipment
Model:	TF-35	Receiver: Rohde & Schwarz ESCS 30
Applicant:	TEN FORWARD LTD	Antenna: Schaffner CBL6111C
Ser.Nr.:	--	
Set under test:	Self-Powered AM/FM Weather Band Radio with Built-in Flashlight	
Operating mode:	Weather Band + Light ON + DC Out (28 Ohm load)	

Weather Band (Channel 1) Receiving Frequency : 162.4 MHz

Frequency (MHz)	Horz. Reading dB(µV)	Vert. Reading dB(µV)	Corr. Factor (dB)	Horiz. Test Result dB(µV/m)	Vert. Test Result dB(µV/m)	Limit dB(µV/m)
30	< 16.0	< 16.0	19.1	< 35.1	< 35.1	40.0
100	< 16.0	< 16.0	9.5	< 25.5	< 25.5	43.5
151.75	18.0	< 16.0	11.4	29.4	< 27.4	43.5
303.45	22.0	< 16.0	14.3	36.3	< 30.3	46.0
455.2	18.0	< 16.0	18.6	36.6	< 34.6	46.0
606.95	< 16.0	< 16.0	20.7	< 36.7	< 36.7	46.0
800	< 16.0	< 16.0	23.8	< 39.8	< 39.8	46.0
900	< 16.0	< 16.0	24.4	< 40.4	< 40.4	46.0

1000	--	--	--	24.2	24.2	54.0
1213.65	--	--	--	35.0	34.4	54.0
1500	--	--	--	30.1	30.1	54.0
2000	--	--	--	34.3	34.2	54.0

The measurement results indicate that the test unit meets the FCC requirements.

Note :

1. The above measured data are in Quasi-Peak values.
2. The above results were the worst case results with the sample positioned in all 3 axis during the test.

The worst test data were obtained with the sample placed normally on the table and the telescopic antenna of the sample was positioned horizontally and vertically for horizontal and vertical measurement respectively.

Operator : TE

IT 5/6

Date : 2008-12-17

Page 14 of 27

Radiated Emission
Acc: FCC Part 15 Subpart B (15.109)

IECC Ref:	51422	Test Equipment
Model:	TF-35	Receiver: Rohde & Schwarz ESCS 30
Applicant:	TEN FORWARD LTD	Antenna: Schaffner CBL6111C
Ser.Nr.:	--	
Set under test:	Self-Powered AM/FM Weather Band Radio with Built-in Flashlight	
Operating mode:	Weather Band + Light ON + DC Out (28 Ohm load)	

Weather Band (Channel 4) Receiving Frequency : 162.475 MHz

Frequency (MHz)	Horz. Reading dB(µV)	Vert. Reading dB(µV)	Corr. Factor (dB)	Horiz. Test Result dB(µV/m)	Vert. Test Result dB(µV/m)	Limit dB(µV/m)
30	< 16.0	< 16.0	19.1	< 35.1	< 35.1	40.0
100	< 16.0	< 16.0	9.5	< 25.5	< 25.5	43.5
151.76	18.0	< 16.0	11.4	29.4	< 27.4	43.5
303.5	22.0	< 16.0	14.3	36.3	< 30.3	46.0
455.25	18.0	< 16.0	18.6	36.6	< 34.6	46.0
607.05	< 16.0	< 16.0	20.7	< 36.7	< 36.7	46.0
800	< 16.0	< 16.0	23.8	< 39.8	< 39.8	46.0
1000	< 16.0	< 16.0	26.2	< 42.2	< 42.2	54.0
1213.86	--	--	--	34.5	33.6	54.0
1365.58	--	--	--	35.2	--	54.0
1668.98	--	--	--	37.5	35.2	54.0
2000	--	--	--	33.0	33.1	54.0

The measurement results indicate that the test unit meets the FCC requirements.

Note :

1. The above measured data are in Quasi-Peak values.
2. The above results were the worst case results with the sample positioned in all 3 axis during the test.

The worst test data were obtained with the sample placed normally on the table and the telescopic antenna of the sample was positioned horizontally and vertically for horizontal and vertical measurement respectively.

Operator : TE

IT 5/6

Date : 2008-12-17

Page 15 of 27

Radiated Emission

Acc: FCC Part 15 Subpart B (15.109)

IECC Ref:	51422	Test Equipment
Model:	TF-35	Receiver: Rohde & Schwarz ESCS 30
Applicant:	TEN FORWARD LTD	Antenna: Schaffner CBL6111C
Ser.Nr.:	--	
Set under test:	Self-Powered AM/FM Weather Band Radio with Built-in Flashlight	
Operating mode:	Weather Band + Light ON + DC Out (28 Ohm load)	

Weather Band (Channel 7) Receiving Frequency : 162.55 MHz

Frequency (MHz)	Horz. Reading dB(µV)	Vert. Reading dB(µV)	Corr. Factor (dB)	Horiz. Test Result dB(µV/m)	Vert. Test Result dB(µV/m)	Limit dB(µV/m)
30	< 16.0	< 16.0	19.1	< 35.1	< 35.1	40.0
100	< 16.0	< 16.0	9.5	< 25.5	< 25.5	43.5
151.7	18.0	< 16.0	11.4	29.4	< 27.4	43.5
303.4	22.0	< 16.0	14.3	36.3	< 30.3	46.0
455.1	18.0	< 16.0	18.6	36.6	< 34.6	46.0
606.85	< 16.0	< 16.0	20.7	< 36.7	< 36.7	46.0
800	< 16.0	< 16.0	23.8	< 39.8	< 39.8	46.0
1000	< 16.0	< 16.0	26.2	< 42.2	< 42.2	54.0
1214.25	--	--	--	37.5	--	54.0
1366.03	--	--	--	35.4	--	54.0
1500	--	--	--	--	30.2	54.0
2000	--	--	--	33.7	34.3	54.0

The measurement results indicate that the test unit meets the FCC requirements.

Note :

1. The above measured data are in Quasi-Peak values.
2. The above results were the worst case results with the sample positioned in all 3 axis during the test.

The worst test data were obtained with the sample placed normally on the table and the telescopic antenna of the sample was positioned horizontally and vertically for horizontal and vertical measurement respectively.

Operator : TE



Accredited Laboratory



Network Partner



Qualified Independent Laboratory

IT 5/6

Date : 2008-12-17

Page 16 of 27

Radiated Emission
Acc: FCC Part 15 Subpart B (15.109)

IECC Ref: 51422
Model: TF-35
Applicant: TEN FORWARD LTD
Ser.Nr.: --
Set under test: Self-Powered AM/FM Weather Band Radio with
Built-in Flashlight
Operating mode: AUX IN (External MP3 source) + Light ON + DC Out (28 Ohm load)

Test Equipment

Receiver: Rohde & Schwarz ESCS 30

Antenna: Schaffner CBL6111C

Frequency (MHz)	Horz. Reading dB(µV)	Vert. Reading dB(µV)	Corr. Factor (dB)	Horiz. Test Result dB(µV/m)	Vert. Test Result dB(µV/m)	Limit dB(µV/m)
30	< 16.0	< 16.0	19.1	< 35.1	< 35.1	40.0
100	< 16.0	< 16.0	9.5	< 25.5	< 25.5	43.5
119.08	< 16.0	< 16.0	11.5	< 27.5	< 27.5	43.5
151.7	< 16.0	20.0	11.4	< 27.4	31.4	43.5
238.17	< 16.0	< 16.0	12.0	< 28.0	< 28.0	46.0
303.4	26.0	23.0	14.3	40.3	37.3	46.0
455.1	< 16.0	< 16.0	18.6	< 34.6	< 34.6	46.0
606.82	< 16.0	< 16.0	20.7	< 36.7	< 36.7	46.0
758.55	< 16.0	< 16.0	23.5	< 39.5	< 39.5	46.0
910.22	< 16.0	< 16.0	24.9	< 40.9	< 40.9	46.0
1000	< 16.0	< 16.0	26.2	< 42.2	< 42.2	54.0

The measurement results indicate that the test unit meets the FCC requirements.

Note :

1. The above measured data are in Quasi-Peak values.
2. The above results were the worst case results with the sample positioned in all 3 axis during the test.
The worst test data were obtained with the sample placed normally on the table and the telescopic antenna of the sample was positioned horizontally and vertically for horizontal and vertical measurement respectively.

Operator : TE

U 5/6

Interference Voltage 150 KHz ~ 30 MHz

acc. FCC PART 15 Subpart B Section 15.107 (a) Class B

Cabin 1

Model: TF-35

Spl./Ser.No.: 01 / --

Client : TEN FORWARD LTD.

Product: RADIO W/ FLASHLIGHT

IECC-No.: 51422

Date: 20 NOV 2008

Test equipment:

Rohde & Schwarz ESHS-30

Schwarzbeck NSLK8127

Connected sets:

--

Operating mode:

FM
(L)

--

RFI suppression parts:


--

* two dB safety margin for
type approval necessary

Operator: ED

Result: OK.

IECC



U 5 / 6

Interference Voltage 150 KHz - 30 MHz

acc. FCC PART 15 Subpart B Section 15.107 (a) Class B

Cabin 1

Model: TF-35

Spl./Ser.No.: 01 / --

Client : TEN FORWARD LTD.

Product: RADIO W/ FLASHLIGHT

IECC-No.: 51422

Date: 20 NOV 2008

Test equipment:

Rohde & Schwarz ESHS-30

Schwarzbeck NSLK8127

Connected sets:

--

Operating mode:

FM

(N)

--

RFI suppression parts:


--

* two dB safety margin for
type approval necessary

Operator: ED

Result: **O.K.**

IECC



U 5/6

Interference Voltage 150 KHz - 30 MHz

acc. FCC PART 15 Subpart B Section 15.107 (a) Class B

Cabin 1

Model: TF-35

Spl./Ser.No.: 01 / --

Client : TEN FORWARD LTD.

Product: RADIO W/ FLASHLIGHT

IECC-No.: 51422

Date: 20 NOV 2008

Test equipment:

Rohde & Schwarz ESHS-30

Schwarzbeck NSLK8127

Connected sets:

--

Operating mode:

WX

(L)

--

RFI suppression parts:


--

* two dB safety margin for
type approval necessary

Operator: ED

Result: OK

IECC



U 5 / 6

Interference Voltage 150 KHz - 30 MHz

acc. FCC PART 15 Subpart B Section 15.107 (a) Class B

Cabin 1

Model: TF-35

Spl./Ser.No.: 01 / --

Client : TEN FORWARD LTD.

Product: RADIO W/ FLASHLIGHT

IECC-No.: 51422

Date: 20 NOV 2008

Test equipment:

Rohde & Schwarz ESHS-30

Schwarzbeck NSLK8127

Connected sets:

--

Operating mode:

WX

(N)

--

RFI suppression parts:


--

* two dB safety margin for
type approval necessary

Operator: ED

Result: OK

IECC



U 5/6

Interference Voltage 150 KHz - 30 MHz

acc. FCC PART 15 Subpart B Section 15.107 (a) Class B

Cabin 1

Model: TF-35

Spl./Ser.No.: 01 / --

Client : TEN FORWARD LTD.

Product: RADIO W/ FLASHLIGHT

IECC-No.: 51422

Date: 20 NOV 2008

Test equipment:

Rohde & Schwarz ESHS-30

Schwarzbeck NSLK8127

Connected sets:

--

Operating mode:

AUX IN

(L)

--

RFI suppression parts:


--

* two dB safety margin for
type approval necessary

Operator: ED

Result: OK

IECC



U 5/6

Interference Voltage 150 KHz ~ 30 MHz

acc. FCC PART 15 Subpart B Section 15.107 (a) Class B

Cabin 1

Model: TF-35

Spl./Ser.No.: 01 / --

Client : TEN FORWARD LTD.

Product: RADIO W/ FLASHLIGHT

IECC-No.: 51422

Date: 20 NOV 2008

Test equipment:

Rohde & Schwarz ESHS-30

Schwarzbeck NSLK8127

Connected sets:

--

Operating mode:

AUX IN
(N)

--

RFI suppression parts:


--

* two dB safety margin for
type approval necessary

Operator: ED

Result: **OK**

IECC



U 5/6

Interference Voltage 150 KHz - 30 MHz

acc. FCC PART 15 Subpart B Section 15.107 (a) Class B

Cabin 1

Model: TF-35

Spl./Ser.No.: 01 / --

Client : TEN FORWARD LTD.

Product: RADIO W/ FLASHLIGHT

IECC-No.: 51422

Date: 20 NOV 2008

Test equipment:

Rohde & Schwarz ESHS-30

Schwarzbeck NSLK8127

Connected sets:

--

Operating mode:

OPERATE (LIGHT ON)
(L)
--

RFI suppression parts:


--

* two dB safety margin for
type approval necessary

Operator: EO

Result: **OK**

IECC



U 5 / 6

Interference Voltage 150 KHz - 30 MHz

acc. FCC PART 15 Subpart B Section 15.107 (a) Class B

Cabin 1

Model: TF-35

Spl./Ser.No.: 01 / --

Client : TEN FORWARD LTD.

Product: RADIO W/ FLASHLIGHT

IECC-No.: 51422

Date: 20 NOV 2008

Test equipment:

Rohde & Schwarz ESHS-30

Schwarzbeck NSLK8127

Connected sets:

--

Operating mode:

OPERATE (LIGHT ON)
(N)
--

RFI suppression parts:


--

* two dB safety margin for
type approval necessary

Operator: ED

Result: OK

IECC



U 5/6

Interference Voltage 150 KHz - 30 MHz

acc. FCC PART 15 Subpart B Section 15.107 (a) Class B

Cabin 1

Model: TF-35

Spl./Ser.No.: 01 / --

Client : TEN FORWARD LTD.

Product: RADIO W/ FLASHLIGHT

IECC-No.: 51422

Date: 20 NOV 2008

Test equipment:

Rohde & Schwarz ESHS-30

Schwarzbeck NSLK8127

Connected sets:

--

Operating mode:

DC OUT (LOAD AT 28 OHM)
(L)

--

RFI suppression parts:


--

* two dB safety margin for
type approval necessary

Operator: ED

Result: **OK**

IECC



U 5/6

Interference Voltage 150 KHz - 30 MHz

acc. FCC PART 15 Subpart B Section 15.107 (a) Class B

Cabin 1

Model: TF-35

Spl./Ser.No.: 01 / --

Client : TEN FORWARD LTD.

Product: RADIO W/ FLASHLIGHT

IECC-No.: 51422

Date: 20 NOV 2008

Test equipment:

Rohde & Schwarz ESHS-30

Schwarzbeck NSLK8127

Connected sets:

--

Operating mode:

DC OUT (LOAD AT 28 OHM)
(N)

--

RFI suppression parts:


--

* two dB safety margin for
type approval necessary

Operator: ED

Result: OK

IECC



FCC – Test Report

Date: 2008-12-17

No. 51422

Page 27 of 27

Photo of Sample



Model : TF-35



Model : TF-37