## MPE Calculation Method

 $E (V/m) = (30*P*G)^{0.5}/d$ 

Power Density: Pd  $(W/m2) = E^2/377$ 

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

 $Pd = (30*P*G) / (377*d^2)$ 

From the peak EUT RF output power, the minimum mobile separation distance, d=0.3m, as well as the gain of the used antenna, the RF power density can be obtained.

## For 5GHz operation:

Calculated Result and Limit (WORSE CASE IS AS BELOW)

Antenna	Peak Output	Power Density	Limit of Power	Test
Gain	Power (mW)	(S) (mW/cm2)	Density (S)	Result
(Numeric)			(mW/cm2)	
3.16(5dBi)	847(29.28dBm)	0.237	1	Compiles

## For 2.4GHz operation:

Calculated Result and Limit (WORSE CASE IS AS BELOW)

Antenna	Peak Output	Power Density	Limit of Power	Test
Gain	Power (mW)	(S) (mW/cm2)	Density (S)	Result
(Numeric)			(mW/cm2)	
3. 16(5dBi)	968 (29.86dBm )	0.271	1	Compiles

0.237+ 0.271=0.508<1