




Test report No:
24C0966R-RF-US-P06V03

FCC TEST REPORT

Product Name	Mobile Computer
Model and /or type reference	PM68
Trademark	N/A
FCC ID	V2X-PM68
Applicant's name / address	Point Mobile Co.,LTD. A-26F, Building Gasan Publik 178, Digital-ro, Geumcheon-gu Seoul, 08513 Republic of Korea
Test method requested, standard	47 CFR FCC Part 15 (Section 15.247) ANSI C63.10: 2013
Verdict Summary	IN COMPLIANCE
Documented by (name / position & signature)	Jun Xu/ Project Engineer 
Approved by (name / position & signature)	Frank He/ Manager 
Date of issue	2025-03-27
Report Version	V1.0
Report template No	Template_FCC Part 15C-RF-V1.0

INDEX

	page
General conditions	5
Environmental conditions	5
Possible test case verdicts	6
Abbreviations.....	6
Document History.....	7
Remarks and Comments	7
Used Equipment.....	8
Uncertainty	12
1 General Information	13
1.1 General Description of the Item(s).....	13
1.2 Antenna Information	14
1.3 Channel List.....	15
2 Description of Test Setup.....	16
2.1 Operating mode(s) used for tests	16
2.2 Auxiliary equipment / Test software for the EUT	16
2.3 Test Configuration / Block diagram used for tests.....	17
2.4 Testing process	19
3 Verdict summary section.....	20
3.1 Standards	20
3.2 Deviation(s) from the Standard(s) / Test Specification(s).....	20
3.3 Overview of results	21
3.4 Power setting in test	22
3.5 Test Matrix	22
3.6 Test Facility.....	23
4 Test Items Of Limit/Setup/Procedure.....	24
4.1 DTS Bandwidth	24
4.1.1 Limit	24
4.1.2 Test Setup	24
4.1.3 Test Procedure	24
4.2 Occupied Channel Bandwidth	25
4.2.1 Limit	25
4.2.2 Test Setup	25
4.2.3 Test Procedure	25
4.3 Maximum Conducted Output Power.....	26

4.3.1	Limit	26
4.3.2	Test Setup	26
4.3.3	Test Procedure	27
4.4	Maximum Power Spectral Density.....	28
4.4.1	Limit	28
4.4.2	Test Setup	28
4.4.3	Test Procedure	28
4.5	Band Edge Measurements	29
4.5.1	Limit	29
4.5.2	Test Setup	29
4.5.3	Test Procedure	29
4.6	Conducted Spurious Emission	30
4.6.1	Limit	30
4.6.2	Test Setup	30
4.6.3	Test Procedure	30
4.7	Duty cycle	31
4.7.1	Limit	31
4.7.2	Test Setup	31
4.7.3	Test Procedure	31
4.8	Emissions in Restricted Bands	32
4.8.1	Limit	32
4.8.2	Test Setup	34
4.8.3	Test Procedure	35
4.9	AC Power Line Conducted Emission.....	36
4.9.1	Limit	36
4.9.2	Test Setup	36
4.9.3	Test Procedure	36
4.10	Antenna Requirement.....	37
4.10.1	Limit:	37
4.10.2	Antenna Connector Construction:	37
5	Test setup photo and EUT Photo	37
6	Test Result.....	38
	Appendix A: DTS Bandwidth.....	38
	Appendix B: Maximum conducted output power	42
	Appendix C: Maximum power spectral density.....	43
	Appendix D: Band edge measurements	47
	Appendix E: Conducted Spurious Emission	63



Appendix F: Duty Cycle	111
Appendix G: Emissions in Restricted Bands	115
Appendix H: AC Power Line Conducted Emission	129

COMPETENCES AND GUARANTEES

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

GENERAL CONDITIONS

Test Location A	No. 99, Hongye Road, Suzhou Industrial Park Suzhou, 215006, P.R. China
Test Location B	No. 8213, Fanhua Avenue, Baohe District, Hefei City, Anhui Province, China
Date(receive sample)	Feb. 17, 2025
Date (start test)	Feb. 18, 2025
Date (finish test)	Mar. 18, 2025
Note: Radiated Emission and Radiated Emission Band Edge were completed at Test Location B, and other tests were completed at Test Location A.	

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.

ENVIRONMENTAL CONDITIONS

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

Ambient temperature	15 °C – 35 °C
Relative Humidity air	30% - 60%

If explicitly required in the basic standard or applied product / product family standard the climatic values are recorded and documented separately in this test report.

POSSIBLE TEST CASE VERDICTS

Test case does not apply to test object	N/A
Test object does meet requirement	P (Pass) / PASS
Test object does not meet requirement	F (Fail) / FAIL
Not measured	N/M

ABBREVIATIONS

For the purposes of the present document, the following abbreviations apply:

EUT	: Equipment Under Test
QP	: Quasi-Peak
CAV	: CISPR Average
AV	: Average
CDN	: Coupling Decoupling Network
SAC	: Semi-Anechoic Chamber
OATS	: Open Area Test Site
BW	: Bandwidth
AM	: Amplitude Modulation
PM	: Pulse Modulation
HCP	: Horizontal Coupling Plane
VCP	: Vertical Coupling Plane
U_N	: Nominal voltage
T_x	: Transmitter
R_x	: Receiver
N/A	: Not Applicable
N/M	: Not Measured

DOCUMENT HISTORY

Report No.	Version	Description	Issued Date
24C0966R-RF-US-P06V03	V1.0	Initial issue of report.	2025-03-27

REMARKS AND COMMENTS

1. The equipment under test (EUT) does meet the essential requirements of the stated standard(s)/test(s).
2. These test results on a sample of the device are for the purpose of demonstrating Compliance with 47 CFR FCC Part 15 (Section 15.247).
3. The measurement result is considered in conformance with the requirement if it is within the prescribed limit, It is not necessary to account the uncertainty associated with the measurement result.
4. The test results presented in this report relate only to the object tested.
5. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification (Suzhou) Co., Ltd.
6. This report will not be used for social proof function in China market.
7. DEKRA declines any responsibility with the following test data provided by customer that may affect the validity of result:
 - Chapter 1.1 General Description of the Item(s);
 - Chapter 1.2 Antenna Informaion;
 - Chapter 1.3 Channel List.

USED EQUIPMENT

Test Location A :Conducted Test/ TR8

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date	Firmware Version	Software version
Wireless Connectivity Tester	R&S	CMW 270	102593	2024.05.15	2025.05.14	V 4.0.60	N/A
Coaxial Cable	N/A	N/A	2477	2024.06.11	2025.06.10	N/A	N/A
Coaxial Cable	N/A	N/A	2478	2024.06.11	2025.06.10	N/A	N/A
High and low temperature and fast temperature change test box	ASTUOD	ASTD-FBT-225K	N/A	2024.04.21	2025.04.20	N/A	N/A
Temperature/Humidity Meter	RTS	RTS-8S	RF07	2024.07.04	2025.07.03	N/A	N/A
Test system							
Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date	Firmware Version	Software version
MAX Signal Analyzer	Keysight	N9010A	MY48030494	2024.10.26	2025.10.25	A.14.03	N/A
RF Control Unit	Tonscend	JS0806-2	22G8060594	2025.01.26	2026.01.25	N/A	N/A
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY61252529	2024.05.12	2025.05.11	B.01.96	N/A
Frequency extender for EXG or MXG	Keysight	N5182BX07	MY59362500	2024.05.12	2025.05.11	N/A	N/A
EXG-B MW Analog Signal Generator	Keysight	N5173B	MY61252566	2024.07.06	2025.07.05	B.01.95	N/A
Test Software	Tonscend	TS1120	JS1120-3	N/A	N/A	N/A	V3.0.22

Test Location A :AC Power Line Conducted Emission / TR1

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date	Firmware Version	Software version
EMI Test Receiver	R&S	ESCI	100726	2024.07.06	2025.07.05	4.42 SP1	N/A
Two-Line V-Network	R&S	ENV 216	101044	2024.10.26	2025.10.25	N/A	N/A
Two-Line V-Network	R&S	ENV 216	101189	2024.07.06	2025.07.05	N/A	N/A
50ohm Coaxial Switch	Anritsu	MP59B	6200464462	2024.04.20	2025.04.19	N/A	N/A
Coaxial Cable	Huber+Suhner	RG 223	TR1-C1	2024.04.27	2025.04.26	N/A	N/A
Impedance Stabilization Network	Teseq GmbH	ISN T800	57318	2024.02.27	2025.02.26	N/A	N/A
Impedance Stabilization Network	Teseq GmbH	ISN T800	57318	2025.02.25	2026.02.24	N/A	N/A
Temperature/Humidity Meter	RTS	RTS-8S	EMC01	2024.07.04	2025.07.03	N/A	N/A
Dekra test software	Dekra	N/A	N/A	N/A	N/A	N/A	N/A

Test Location A :Radiated Emission(9KHz-1GHz) / AC2

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date	Firmware Version	Software version
EMI Test Receiver	R&S	ESCI	100176	2024.05.12	2025.05.11	4.42 SP3	N/A
Loop Antenna	R&S	HFH2-Z2E	101149	2024.03.27	2025.03.26	N/A	N/A
Bilog Antenna	Teseq GmbH	CBL6112D	27613	2024.09.08	2025.09.07	N/A	N/A
Temperature/Humidity Meter	RTS	RTS-8S	AC2-TH	2024.07.04	2025.07.03	N/A	N/A
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC2-C	2024.04.27	2025.04.26	N/A	N/A
Dekra test software	Dekra	N/A	N/A	N/A	N/A	N/A	3

Test Location A: Radiated Emission (1GHz-40GHz) / AC5

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date	Firmware Version	Software version
EXA Spectrum Analyzer	Keysight	N9020B	MY60112218	2024.11.02	2025.11.01	A.31.05	N/A
Pre-Amplifier	SKET	LNPA_0118G-45	SK2021090101	2024.04.27	2025.04.26	N/A	N/A
Preamplifier	CHENGYI	EMC184045SE	980263	2024.07.06	2025.07.05	N/A	N/A
DRG Horn	ETS-Lindgren	3117	00167055	2024.08.29	2025.08.28	N/A	N/A
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	294	2024.05.30	2025.05.29	N/A	N/A
Filter Switch Box	MVE	MSW-F196	C070001S	2024.04.20	2025.04.19	N/A	N/A
Temperature/Humidity Meter	RTS	RTS-8S	THM-024	2024.05.17	2025.05.16	N/A	N/A
Coaxial Cable	ROSENBERGER	LA1-C011-2000/3000	AC5-40G	2025.01.18	2026.01.17	N/A	N/A
Coaxial Cable	ROSENBERGER	LA1-C011-2000/3000	AC5-40G-2	2024.05.26	2025.05.25	N/A	N/A
Cable	Rosenberger	LA1-C011-1000	0523	2024.05.26	2025.05.25	N/A	N/A
Dekra test software	Dekra	N/A	N/A	N/A	N/A	N/A	3

Test Location B: Radiated Emission Band Edge / AC103

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date	Firmware Version	Software version
Signal analyzer	keysight	N9020B	MY63490118	2024.07.26	2025.07.25	A 08.54	N/A
Bilog Antenna	TESEQ	CBL6112D	64164	2024.11.23	2025.11.22	N/A	N/A
Horn Antenna	RF SPIN	DRH18-E	KV2D11A18ES	2024.11.02	2025.11.01	N/A	N/A
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	01312	2024.10.28	2025.10.27	N/A	N/A
Amplifier	ESE	LNA0118	LNA23100009	2024.08.10	2025.08.09	N/A	N/A
Amplifier	Tonscend	TAP01018048S	AP23J8060307	2024.11.16	2025.11.15	N/A	N/A
Band Reject Filter Group	Tonscend	JS0806-F	23G806F0701	2024.11.20	2025.11.19	N/A	N/A
Temperature/Humidity Meter	RTS	RTS-8S	026	2024.09.04	2025.09.03	N/A	N/A
Test Software	Tonscend	JS36	N/A	N/A	N/A	N/A	5.0.0

UNCERTAINTY

Uncertainties have been calculated according to the DEKRA internal document. The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95% .

Test item Test Location A	Uncertainty
AC Power Line Conducted Emission	± 2.92 dB
Peak Power Output	± 1.13 dB
Radiated Emission(30MHz~1GHz)	Horizontal: 30MHz~200MHz: 4.60 dB 200MHz~1GHz: 4.10 dB Vertical: 30MHz~200MHz: 4.80 dB 200MHz~1GHz: 4.10 dB
Radiated Emission(1GHz~40GHz)	Horizontal: 1GHz~18GHz: 5.00 dB Vertical: 1GHz~18GHz: 4.80 dB Horizontal: 18GHz~40GHz: 4.70 dB Vertical: 18GHz~40GHz: 4.60 dB
RF antenna conducted test	± 1.13 dB
Radiated Emission Band Edge	± 5.00 dB
DTS Bandwidth	± 279 Hz
Occupied Bandwidth	± 279 Hz
Power Density	± 1.13 dB

Test item Test Location B	Uncertainty
Radiated Emission(30MHz~1GHz)	Horizontal: 30MHz~200MHz: 4.86 dB 300MHz~1GHz: 4.86 dB Vertical: 30MHz~200MHz: 4.92 dB 300MHz~1GHz: 4.92 dB
Radiated Emission(1GHz~40GHz)	Horizontal: 1GHz~18GHz: 5.99 dB Vertical: 1GHz~18GHz: 5.76 dB Horizontal: 18GHz~40GHz: 5.99 dB Vertical: 18GHz~40GHz: 5.76 dB
Radiated Emission Band Edge	± 5.99 dB

1 GENERAL INFORMATION

1.1 General Description of the Item(s)

Product Name	Mobile Computer
Model No.	PM68
Trademark.	N/A
FCC ID	V2X-PM68
Hardware Version	MP
Software Version	68.00
Manufacturer	Point Mobile Co.,LTD.
Manufacturer Address.....	A-26F, Building Gasan Publik 178, Digital-ro, Geumcheon-gu Seoul, 08513 Republic of Korea

Wireless specification.....	Bluetooth (LE)				
Operating frequency range(s)	2402~2480MHz				
Type of Modulation.....	GFSK & DPSK				
PHYs	☒	LE 1M	☒	LE 2M	☐ LE Coded S=2/8
Data Rate	☒	1Mbit/s	☒	2Mbit/s	☐ 500/125 Kbit/s
Number of channel.....	LE 1M : 40 LE 2M : 37				

Rated power supply :	Voltage and Frequency	
	☐	AC: 220 - 240 V, 50/60 Hz
	☐	AC: 110-130 V, 50/60 Hz, 13.5W
	☐	DC: 24 Vdc
	☒	Battery: 3.8V
	☒	Adapter: Input:100-240V, 50/60 Hz,0.3A; Output:5.0V,2.0A,10W
Mounting position :	☐	Tabletop equipment
	☐	Door mounted equipment
	☐	Floor standing equipment
	☒	Hand-held/Portable equipment
	☐	Other:

1.2 Antenna Information

Antenna model / type number	N/A		
Antenna serial number	N/A		
Antenna Delivery	☒	1TX + 1RX	
	☐	2TX + 2RX	
	☐	Others:	
Antenna technology	☒	SISO	
	☐	MIMO	☐ CDD
			☐ Beam-forming
Antenna Type	☐	External	☐ Dipole
			☐ Sectorized
	☒	Internal	☐ Ceramic Chip
			☒ PIFA
			☐ FPC
			☐ Others.....
Antenna Gain	2.95dBi		

1.3 Channel List

Bluetooth Working Frequency of Each Channel: (For LE 1M)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2404 MHz	02	2406 MHz	03	2408 MHz
04	2410 MHz	05	2412 MHz	06	2414 MHz	07	2416 MHz
08	2418 MHz	09	2420 MHz	10	2422 MHz	11	2424 MHz
12	2426 MHz	13	2428 MHz	14	2430 MHz	15	2432 MHz
16	2434 MHz	17	2436 MHz	18	2438 MHz	19	2440 MHz
20	2442 MHz	21	2444 MHz	22	2446 MHz	23	2448 MHz
24	2450 MHz	25	2452 MHz	26	2454 MHz	27	2456 MHz
28	2458 MHz	29	2460 MHz	30	2462 MHz	31	2464 MHz
32	2466 MHz	33	2468 MHz	34	2470 MHz	35	2472 MHz
36	2474 MHz	37	2476 MHz	38	2478 MHz	39	2480 MHz
Bluetooth Working Frequency of Each Channel: (For LE 2M)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2404 MHz	02	2406 MHz	03	2408 MHz	04	2410 MHz
05	2412 MHz	06	2414 MHz	07	2416 MHz	08	2418 MHz
09	2420 MHz	10	2422 MHz	11	2424 MHz	13	2428 MHz
14	2430 MHz	15	2432 MHz	16	2434 MHz	17	2436 MHz
18	2438 MHz	19	2440 MHz	20	2442 MHz	21	2444 MHz
22	2446 MHz	23	2448 MHz	24	2450 MHz	25	2452 MHz
26	2454 MHz	27	2456 MHz	28	2458 MHz	29	2460 MHz
30	2462 MHz	31	2464 MHz	32	2466 MHz	33	2468 MHz
34	2470 MHz	35	2472 MHz	36	2474 MHz	37	2476 MHz
38	2478 MHz	N/A	N/A	N/A	N/A	N/A	N/A

Note: The General Description of the Item , antenna information and Channel List for the EUT in clause 1 are provided and confirmed by the client.

2 DESCRIPTION OF TEST SETUP

2.1 Operating mode(s) used for tests

During the tests the following operating mode(s) has(have) been used.

Test Mode For Bluetooth	Mode 1: Transmit by LE_1Mbps
	Mode 2: Transmit by LE_2Mbps

Note 1: Regards to the frequency band operation: the lowest, middle and highest frequency channel were selected to perform the test, then shown on this report.


Note 2: For portable device, radiated tests was verified over X, Y, Z axis, and shown the worst case on this report.

2.2 Auxiliary equipment / Test software for the EUT


Auxiliary equipment	Type / Version	Manufacturer	Supplied by
(1) N/A	N/A	N/A	N/A
(2) N/A	N/A	N/A	N/A
(3) N/A	N/A	N/A	N/A
software	Type / Version	Manufacturer	Supplied by
N/A	N/A	N/A	N/A

2.3 Test Configuration / Block diagram used for tests


Test setup Diagram- AC Line Conducted Emission Test



Test setup Diagram- Conducted test



Test setup Diagram- Radiated Emission



2.4 Testing process

1	Setup the EUT shown in Section 2.3.
2	Enter the engineering code on the EUT.
3	Configure the test mode, the test channel, and the data rate.
4	Verify that the EUT works properly.

3 VERDICT SUMMARY SECTION

This chapter presents an overview of standards and results. Refer to the next chapters for details of measured test results and applied test levels.

3.1 Standards

Standard	Year	Description
CFR 47, FCC Part 15 C	2024	Operation within the bands 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz.
ANSI C63.10	2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

3.2 Deviation(s) from the Standard(s) / Test Specification(s)

The following deviation(s) was / were made from the published requirements of the listed standards: N/A.

(Please define the deviations from the standard(s) if applicable)

3.3 Overview of results

Requirement – Test Item of FCC	Standard(s)	Verdict	Remark
DTS Bandwidth	FCC 15.247(a)(2)	PASS	Test data please refer to Appendix A
Maximum conducted output power	15.247 (b)(3)	PASS	Test data please refer to Appendix B
Maximum power spectral density	FCC 15.247(e)	PASS	Test data please refer to Appendix C
Band edge measurements	FCC 15.247(d) FCC 15.205 FCC 15.209	PASS	Test data please refer to Appendix D
Conducted Spurious Emission	FCC 15.247(d), FCC 15.209	PASS	Test data please refer to Appendix E
Duty cycle	ANSI C63.10:2013	PASS	Test data please refer to Appendix F
Emissions in Restricted Bands	FCC 15.205 FCC 15.209	PASS	Test data please refer to Appendix G
AC Power Line Conducted Emission	FCC 15.207	PASS	Test data please refer to Appendix H
Antenna Requirement	FCC 15.203	PASS	---

3.4 Power setting in test

Mode	Channel	Frequency (MHz)	Power setting
Mode1	00	2402	6
	19	2440	6
	39	2480	6
Mode2	00	2404	6
	19	2440	6
	39	2478	6

3.5 Test Matrix

Test item	Model: PM68	
	1(#1)	2(#2)
DTS Bandwidth	☒	☐
Maximum conducted output power	☒	☐
Maximum power spectral density	☒	☐
Band edge measurements	☐	☒
Conducted Spurious Emission	☒	☐
Duty cycle	☒	☐
Emissions in Restricted Bands	☐	☒
AC Power Line Conducted Emission	☐	☒

Note1: The only difference between sample #1 and sample #2 is whether to keep the original antenna, sample #1 is a conduction test product that removes the original antenna and is equipped with SMA wires, and sample #2 is a complete product that retains the original antenna.

3.6 Test Facility

Tset Location A : FCC Designation Number: CN1199

Tset Location B : FCC Designation Number: CN1321

4 TEST ITEMS OF LIMIT/SETUP/PROCEDURE

4.1 DTS Bandwidth

VERDICT: PASS


4.1.1 Limit

Standard

FCC Part 15 Subpart C Paragraph 15.247 (a)(2);

Systems using digital modulation techniques operate in the 2400-2483.5 MHz. The minimum 6 dB bandwidth shall be at least 500 kHz

4.1.2 Test Setup



4.1.3 Test Procedure

	Reference Rule	Chapter	Description
☒	ANSI C63.10	11.8	DTS bandwidth
☒	ANSI C63.10	11.8.1	Option 1
☐	ANSI C63.10	11.8.2	Option 2

4.2 Occupied Channel Bandwidth

VERDICT: PASS


4.2.1 Limit

Standard

RSS-Gen Issue 5 Paragraph 6.7

The occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs

4.2.2 Test Setup



4.2.3 Test Procedure

	Reference Rule	Chapter	Description
☒	ANSI C63.10	6.9	Occupied bandwidth tests
☐	ANSI C63.10	6.9.2	Option 1
☒	ANSI C63.10	6.9.3	Option 2

4.3 Maximum Conducted Output Power

VERDICT: PASS


4.3.1 Limit

Standard		FCC Part 15 Subpart C Paragraph 15.247 (b)(3);
☒	GTX < 6dBi	Pout ≤ 30dBm
☐	GTX > 6dBi	
☐	Non-Fix point-point	Pout ≤ 30 - (GTX - 6)
☐	Fix point-point	Pout ≤ 30 - [(GTX - 6)]/3
☐	Point-to-multipoint	Pout ≤ 30 - (GTX - 6)
☐	Overlap Beams	Pout ≤ 30 - [(GTX - 6)]/3
☐	Aggregate power transmitted simultaneously on all beams	Pout ≤ 30 - [(GTX - 6)]/3
☐	single directional beam	Pout ≤ 30 - [(GTX - 6)]/3 + 8dB

Note 1 : GTX directional gain of transmitting antennas.

Note 2 : Pout is maximum peak conducted output power .

4.3.2 Test Setup



4.3.3 Test Procedure

	References Rule			Chapter	Description		
☒	ANSI C63.10			11.9	Fundamental emission output power		
	☐	ANSI C63.10			11.9.1	Maximum peak conducted output power	
		☐	ANSI C63.10	11.9.1.1	RBW ≥ DTS bandwidth		
		☐	ANSI C63.10	11.9.1.2	Integrated band power method		
		☐	ANSI C63.10	11.9.1.3	PKPM1 Peak power meter method		
	☒	ANSI C63.10			11.9.2	Maximum conducted (average) output power	
		☐	ANSI C63.10			11.9.2.2	Measurement using a spectrum analyzer (SA)
			☐	ANSI C63.10	11.9.2.2.2	Method AVGSA-1(Duty cycle ≥98%)	
			☐	ANSI C63.10	11.9.2.2.3	Method AVGSA-1A(Duty cycle ≥98%)	
			☐	ANSI C63.10	11.9.2.2.4	Method AVGSA-2(Duty cycle ≤98%)	
			☐	ANSI C63.10	11.9.2.2.5	Method AVGSA-2A(Duty cycle ≤98%)	
			☐	ANSI C63.10	11.9.2.2.4	Method AVGSA-3	
			☐	ANSI C63.10	11.9.2.2.5	Method AVGSA-3A	
		☒	ANSI C63.10			11.9.2.3	Measurement using a power meter (PM)
			☒	ANSI C63.10	11.9.2.3.1	Method AVGPM	
			☐	ANSI C63.10	11.9.2.3.2	Method AVGPM-G	

4.4 Maximum Power Spectral Density


VERDICT: PASS

4.4.1 Limit

Standard FCC Part 15 Subpart C Paragraph 15.247 (b)(3);

 Power Spectral Density $\leq 8\text{dBm}/3\text{kHz}$

4.4.2 Test Setup



4.4.3 Test Procedure

	References Rule		Chapter	Description
☒	ANSI C63.10		11.10	Maximum power spectral density level in the fundamental emission
	☒	ANSI C63.10	11.10.2	Method PKPSD (peak PSD)
	☐	ANSI C63.10	11.10.3	Method AVGPSD-1(Duty cycle $\geq 98\%$)
	☐	ANSI C63.10	11.10.4	Method AVGPSD-1A(Duty cycle $\geq 98\%$)
	☐	ANSI C63.10	11.10.5	Method AVGPSD-2(Duty cycle $< 98\%$)
	☐	ANSI C63.10	11.10.6	Method AVGPSD-2A(Duty cycle $< 98\%$)
	☐	ANSI C63.10	11.10.7	Method AVGPSD-3
	☐	ANSI C63.10	11.10.8	Method AVGPSD-3A

4.5 Band Edge Measurements

VERDICT: PASS


4.5.1 Limit

Standard		FCC Part 15 Subpart C Paragraph 15.247(d) , 15.209;		
Frequency bands (MHz)	Detector	Limit (dB μ V/m)	RBW (MHz)	Distance (m)
2310-2390	PK	74	1	3
2483.5-2500	AV	54	1	3

Note: The field strength of emissions appearing within these frequency bands shall not exceed the limits.

4.5.2 Test Setup

Above 1GHz Test Setup:



4.5.3 Test Procedure

	References Rule	Chapter	Description
☒	ANSI C63.10	6.10	Band-edge testing
☒	ANSI C63.10	6.10.5	Restricted-band band-edge measurements
☐	ANSI C63.10	6.10.6	Marker-delta method
☒	ANSI C63.10	11.12	Emissions in restricted frequency bands
☒	ANSI C63.10	11.12.1	Radiated emission measurements
☒	ANSI C63.10	11.12.2.7	Radiated spurious emission test
☐	ANSI C63.10	6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
☐	ANSI C63.10	6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
☒	ANSI C63.10	6.6	Radiated emissions from unlicensed wireless devices above 1 GHz

4.6 Conducted Spurious Emission

VERDICT: PASS


4.6.1 Limit

Standard	FCC Part 15 Subpart C Paragraph 15.247(d);
RF Output power (Detection methods)	Limit(dB)
RF Output power(Average detector)	30dBc(Note1)
RF Output power(PK detector)	20dBc(Note2)

Note 1: If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).

Note 2: If the maximum peak conducted output power procedure was used, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).

4.6.2 Test Setup



4.6.3 Test Procedure


References Rule	Chapter	Description
☒ ANSI C63.10	11.11	Emissions in non-restricted frequency bands
☒ ANSI C63.10	11.11.1	General
☒ ANSI C63.10	11.11.2	Reference level measurement
☒ ANSI C63.10	11.11.3	Emission level measurement

4.7 Duty cycle	VERDICT: PASS
-----------------------	----------------------

4.7.1 Limit

N/A

4.7.2 Test Setup



4.7.3 Test Procedure

References Rule	Chapter	Description
☒ ANSI C63.10	11.6	Duty cycle (D), transmission duration (T), and maximum power control level

4.8 Emissions in Restricted Bands**VERDICT: PASS****4.8.1 Limit****Standard** FCC Part 15 Subpart C Paragraph 15.205

Restricted Bands of operation

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 – 0.110	16.42 – 16.423	399.9 – 410	4.5 – 5.15
0.495 – 0.505	16.69475 – 16.69525	608 – 614	5.35 – 5.46
2.1735 – 2.1905	16.80425 – 16.80475	960 – 1240	7.25 – 7.75
4.125 – 4.128	25.5 – 25.67	1300 – 1427	8.025 – 8.5
4.17725 – 4.17775	37.5 – 38.25	1435 – 1626.5	9.0 – 9.2
4.20725 – 4.20775	73 – 74.6	1645.5 – 1646.5	9.3 – 9.5
6.215 – 6.218	74.8 – 75.2	1660 – 1710	10.6 – 12.7
6.26775 – 6.26825	108 – 121.94	1718.8 – 1722.2	13.25 – 13.4
6.31175 – 6.31225	123 – 138	2200 – 2300	14.47 – 14.5
8.291 – 8.294	149.9 – 150.05	2310 – 2390	15.35 – 16.2
8.362 – 8.366	156.52475 – 156.52525	2483.5 – 2500	17.7 – 21.4
8.37625 – 8.38675	156.7 – 156.9	2690 – 2900	22.01 – 23.12
8.81425 – 8.81475	162.0125 – 167.17	3260 – 3267	23.6 – 24.0
12.29 – 12.293	167.72 – 173.2	3332 – 3339	31.2 – 31.8
12.51975 – 12.52025	240 – 285	3345.8 – 3358	36.43 – 36.5
12.57675 – 12.57725	322 – 335.4	3600 – 4400	
13.36 – 13.41			

Restricted Band Emissions Limit

FCC Part 15 Subpart C Paragraph 15.209

Frequency (MHz)	Field strength (μV/m)	Field strength (dBμV/m)	Measurement distance (m)
0.009 - 0.49	2400/F(kHz)	48.5 – 13.8	300 _(Note 1)
0.49 - 1.705	24000/F(kHz)	33.8 - 23	30 _(Note 1)
1.705 - 30	30	29.5	30 _(Note 1)
30 - 88	100	40	3 _(Note 2)
88 - 216	150	43.5	3 _(Note 2)
216 - 960	200	46	3 _(Note 2)
Above 960	500	54	3 _(Note 2)


Note 1: At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade).

Note 2: At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be


performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

4.8.2 Test Setup


Below 30MHz Test Setup:



30MHz-1GHz Test Setup:



Above 1GHz Test Setup:




4.8.3 Test Procedure

	References Rule		Chapter	Description
☒	ANSI C63.10		11.12	Emissions in restricted frequency bands
	☒	ANSI C63.10	11.12.1	Radiated emission measurements
	☒	ANSI C63.10	11.12.2.7	Radiated spurious emission test
	☒	ANSI C63.10	6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
	☒	ANSI C63.10	6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
	☒	ANSI C63.10	6.6	Radiated emissions from unlicensed wireless devices above 1 GHz

4.9 AC Power Line Conducted Emission**VERDICT: PASS****4.9.1 Limit**

Standard	FCC Part 15 Subpart C Paragraph 15.207 ;	
Frequency range [MHz]	Limit: QP [dB(μV) ¹⁾	Limit: AV [dB(μV) ¹⁾
0,15 - 0,50	66 - 56 ²⁾	56 - 46 ²⁾
0,50 - 5,0	56	46
5,0 - 30	60	50

¹⁾ At the transition frequency, the lower limit applies.²⁾ The limit decreases linearly with the logarithm of the frequency.**NOTE 1:** The exclusion band for transmitters shall be considered for transmitters operating at frequencies below 30 MHz.**NOTE 2:** Where the AC output port is directly connected (or via a circuit breaker) to the AC power input port of the EUT the AC power output port need not to be tested.**4.9.2 Test Setup****4.9.3 Test Procedure**

	References Rule	Chapter	Item
☒	ANSI C63.10-2013	6.2	Standard test method for ac power-line conducted emissions from unlicensed wireless devices

4.10 Antenna Requirement**VERDICT: PASS****4.10.1 Limit:****Standard**

FCC Part 15 Subpart C Paragraph 15.203;

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

4.10.2 Antenna Connector Construction:

The use of a permanently attached antenna



The antenna use of a unique coupling to the intentional radiator



The use of a nonstandard antenna jack or electrical connector

Please refer to the attached document "Internal Photograph" to show the antenna connector.

5 TEST SETUP PHOTO AND EUT PHOTO

Remark: The test setup photo and EUT Photo please see appendix.


6 TEST RESULT

Appendix A: DTS Bandwidth


TestMode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.728	2401.640	2402.368	0.5	PASS
BLE_1M	Ant1	2440	0.680	2439.652	2440.332	0.5	PASS
BLE_1M	Ant1	2480	0.652	2479.676	2480.328	0.5	PASS
BLE_2M	Ant1	2404	1.104	2403.440	2404.544	0.5	PASS
BLE_2M	Ant1	2440	1.112	2439.440	2440.552	0.5	PASS
BLE_2M	Ant1	2478	1.196	2477.380	2478.576	0.5	PASS



BLE 1M-Ant1-2402-PASS



BLE_1M-Ant1-2440-PASS



BLE_1M-Ant1-2480-PASS



BLE_2M-Ant1-2404-PASS



BLE_2M-Ant1-2440-PASS



BLE_2M-Ant1-2478-PASS

Appendix B: Maximum conducted output power


Test Mode	Frequency (MHz)	Measured Power (dBm)	Conducted Limit[dBm]
Mode1	2402	1.90	≤ 30
	2440	3.42	≤ 30
	2480	2.54	≤ 30
Mode2	2404	2.10	≤ 30
	2440	3.49	≤ 30
	2478	2.56	≤ 30

Appendix C: Maximum power spectral density

TestMode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-14.28	≤8.00	PASS
BLE_1M	Ant1	2440	-12.84	≤8.00	PASS
BLE_1M	Ant1	2480	-13.56	≤8.00	PASS
BLE_2M	Ant1	2404	-16.56	≤8.00	PASS
BLE_2M	Ant1	2440	-15.16	≤8.00	PASS
BLE_2M	Ant1	2478	-16.02	≤8.00	PASS



BLE_1M-Ant1-2402-PASS




BLE_1M-Ant1-2440-PASS



BLE_1M-Ant1-2480-PASS



BLE_2M-Ant1-2404-PASS



BLE_2M-Ant1-2440-PASS



BLE_2M-Ant1-2478-PASS


Appendix D: Band edge measurements

Test Report

Project Information

Profile:	24C0966R	EUT:	Mobile Computer
Mode:	Mode1:Transmit at 2402MHz by LE 1M	Voltage:	By Battery
Environment:	Temp: 25°C; Humi:60%	Engineer	Yu Liu
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2386.38	33.40	37.03	3.63	54.00	16.97	AV	Horizo	PASS
2	2390.00	33.15	36.80	3.65	54.00	17.20	AV	Horizo	PASS

Test Report

Project Information

Profile:	24C0966R	EUT:	Mobile Computer
Mode:	Mode1:Transmit at 2402MHz by LE 1M	Voltage:	By Battery
Environment:	Temp: 25°C ; Humi:60%	Engineer	Yu Liu
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2382.58	33.51	37.13	3.62	54.00	16.87	AV	Vertic	PASS
2	2390.00	33.25	36.90	3.65	54.00	17.10	AV	Vertic	PASS

Test Report

Project Information

Profile:	24C0966R	EUT:	Mobile Computer
Mode:	Mode1:Transmit at 2402MHz by LE 1M	Voltage:	By Battery
Environment:	Temp: 25°C ; Humi:60%	Engineer	Yu Liu
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2386.95	45.23	48.86	3.63	74.00	25.14	PK	Horizo	PASS
2	2390.00	43.89	47.54	3.65	74.00	26.46	PK	Horizo	PASS

Test Report

Project Information

Profile:	24C0966R	EUT:	Mobile Computer
Mode:	Mode1:Transmit at 2402MHz by LE 1M	Voltage:	By Battery
Environment:	Temp: 25°C ; Humi:60%	Engineer	Yu Liu
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2381.73	46.10	49.71	3.61	74.00	24.29	PK	Vertic	PASS
2	2390.00	43.96	47.61	3.65	74.00	26.39	PK	Vertic	PASS

Test Report

Project Information

Profile:	24C0966R	EUT:	Mobile Computer
Mode:	Mode1:Transmit at 2480MHz by LE 1M	Voltage:	By Battery
Environment:	Temp: 25°C ; Humi:60%	Engineer	Yu Liu
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	34.44	38.53	4.09	54.00	15.47	AV	Horizo	PASS
2	2485.35	34.89	39.00	4.11	54.00	15.00	AV	Horizo	PASS

Test Report

Project Information

Profile:	24C0966R	EUT:	Mobile Computer
Mode:	Mode1:Transmit at 2480MHz by LE 1M	Voltage:	By Battery
Environment:	Temp: 25°C ; Humi:60%	Engineer	Yu Liu
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	34.18	38.27	4.09	54.00	15.73	AV	Vertic	PASS
2	2485.05	34.88	38.99	4.11	54.00	15.01	AV	Vertic	PASS

Test Report

Project Information

Profile:	24C0966R	EUT:	Mobile Computer
Mode:	Mode1:Transmit at 2480MHz by LE 1M	Voltage:	By Battery
Environment:	Temp: 25°C ; Humi:60%	Engineer	Yu Liu
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	44.34	48.43	4.09	74.00	25.57	PK	Horizo	PASS
2	2484.83	46.17	50.28	4.11	74.00	23.72	PK	Horizo	PASS

Test Report

Project Information

Profile:	24C0966R	EUT:	Mobile Computer
Mode:	Mode1:Transmit at 2480MHz by LE 1M	Voltage:	By Battery
Environment:	Temp: 25°C ; Humi:60%	Engineer	Yu Liu
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	44.64	48.73	4.09	74.00	25.27	PK	Vertic	PASS
2	2485.85	45.06	49.17	4.11	74.00	24.83	PK	Vertic	PASS

Test Report

Project Information

Profile:	24C0966R	EUT:	Mobile Computer
Mode:	Mode2:Transmit at 2404MHz by LE 2M	Voltage:	By Battery
Environment:	Temp: 25°C ; Humi:60%	Engineer	Yu Liu
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2383.44	33.96	37.58	3.62	54.00	16.42	AV	Horizo	PASS
2	2390.00	33.42	37.07	3.65	54.00	16.93	AV	Horizo	PASS

Test Report

Project Information

Profile:	24C0966R	EUT:	Mobile Computer
Mode:	Mode2:Transmit at 2404MHz by LE 2M	Voltage:	By Battery
Environment:	Temp: 25°C ; Humi:60%	Engineer	Yu Liu
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2388.66	33.85	37.49	3.64	54.00	16.51	AV	Vertic	PASS
2	2390.00	33.45	37.10	3.65	54.00	16.90	AV	Vertic	PASS

Test Report

Project Information

Profile:	24C0966R	EUT:	Mobile Computer
Mode:	Mode2:Transmit at 2404MHz by LE 2M	Voltage:	By Battery
Environment:	Temp: 25°C ; Humi:60%	Engineer	Yu Liu
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2387.81	45.23	48.86	3.63	74.00	25.14	PK	Horizo	PASS
2	2390.00	43.66	47.31	3.65	74.00	26.69	PK	Horizo	PASS

Test Report

Project Information

Profile:	24C0966R	EUT:	Mobile Computer
Mode:	Mode2:Transmit at 2404MHz by LE 2M	Voltage:	By Battery
Environment:	Temp: 25°C ; Humi:60%	Engineer	Yu Liu
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2385.72	45.35	48.98	3.63	74.00	25.02	PK	Vertic	PASS
2	2390.00	44.08	47.73	3.65	74.00	26.27	PK	Vertic	PASS

Test Report

Project Information

Profile:	24C0966R	EUT:	Mobile Computer
Mode:	Mode2:Transmit at 2478MHz by LE 2M	Voltage:	By Battery
Environment:	Temp: 25°C ; Humi:60%	Engineer	Yu Liu
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	35.17	39.26	4.09	54.00	14.74	AV	Horizo	PASS
2	2486.30	35.71	39.82	4.11	54.00	14.18	AV	Horizo	PASS

Test Report

Project Information

Profile:	24C0966R	EUT:	Mobile Computer
Mode:	Mode2:Transmit at 2478MHz by LE 2M	Voltage:	By Battery
Environment:	Temp: 25°C ; Humi:60%	Engineer	Yu Liu
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	35.14	39.23	4.09	54.00	14.77	AV	Vertic	PASS
2	2485.58	35.63	39.74	4.11	54.00	14.26	AV	Vertic	PASS

Test Report

Project Information

Profile:	24C0966R	EUT:	Mobile Computer
Mode:	Mode2:Transmit at 2478MHz by LE 2M	Voltage:	By Battery
Environment:	Temp: 25°C ; Humi:60%	Engineer	Yu Liu
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	44.75	48.84	4.09	74.00	25.16	PK	Horizo	PASS
2	2485.50	46.03	50.14	4.11	74.00	23.86	PK	Horizo	PASS

Test Report

Project Information

Profile:	24C0966R	EUT:	Mobile Computer
Mode:	Mode2:Transmit at 2478MHz by LE 2M	Voltage:	By Battery
Environment:	Temp: 25°C ; Humi:60%	Engineer	Yu Liu
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List

NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	44.69	48.78	4.09	74.00	25.22	PK	Vertic	PASS
2	2485.70	45.47	49.58	4.11	74.00	24.42	PK	Vertic	PASS

Note:

1.Level=Reading+Factor .

2. Margin=Limit-Level.

Appendix E: Conducted Spurious Emission

Reference level measurement :

TestMode	Antenna	Freq(MHz)	Max.Point[MHz]	Result[dBm]
BLE_1M	Ant1	2402	2402.24	1.58
BLE_1M	Ant1	2440	2440.25	3.28
BLE_1M	Ant1	2480	2480.24	2.22
BLE_2M	Ant1	2404	2404.00	1.43
BLE_2M	Ant1	2440	2440.01	2.62
BLE_2M	Ant1	2478	2478.01	1.82



BLE_1M-Ant1-2402-PASS



BLE_1M-Ant1-2440-PASS




BLE_1M-Ant1-2480-PASS



BLE_2M-Ant1-2404-PASS




BLE_2M-Ant1-2440-PASS




BLE_2M-Ant1-2478-PASS

Band edge measurements :


TestMode	Antenna	ChName	Frequency[MHz]	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	Low	2402	1.58	-56.36	≤-18.42	PASS
BLE_1M	Ant1	High	2480	2.22	-56.65	≤-17.78	PASS
BLE_2M	Ant1	Low	2404	1.43	-57.11	≤-18.57	PASS
BLE_2M	Ant1	High	2478	1.82	-56.21	≤-18.18	PASS




BLE_1M-Ant1-2402-PASS



BLE_1M-Ant1-2480-PASS



BLE_2M-Ant1-2404-PASS




BLE_2M-Ant1-2478-PASS


Conducted Spurious Emission :

TestMode	Antenna	Frequency[MHz]	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	30~1000	1.58	-60.75	≤-18.42	PASS
BLE_1M	Ant1	2402	1000~3000	1.58	-65.54	≤-18.42	PASS
BLE_1M	Ant1	2402	3000~5000	1.58	-64.95	≤-18.42	PASS
BLE_1M	Ant1	2402	5000~7000	1.58	-65.52	≤-18.42	PASS
BLE_1M	Ant1	2402	7000~9000	1.58	-66.88	≤-18.42	PASS
BLE_1M	Ant1	2402	9000~11000	1.58	-66.97	≤-18.42	PASS
BLE_1M	Ant1	2402	11000~13000	1.58	-66.4	≤-18.42	PASS
BLE_1M	Ant1	2402	13000~15000	1.58	-64.89	≤-18.42	PASS
BLE_1M	Ant1	2402	15000~17000	1.58	-64.25	≤-18.42	PASS
BLE_1M	Ant1	2402	17000~19000	1.58	-61.86	≤-18.42	PASS
BLE_1M	Ant1	2402	19000~21000	1.58	-62.35	≤-18.42	PASS
BLE_1M	Ant1	2402	21000~23000	1.58	-61.25	≤-18.42	PASS
BLE_1M	Ant1	2402	23000~25000	1.58	-58.69	≤-18.42	PASS
BLE_1M	Ant1	2440	30~1000	3.28	-60.7	≤-16.72	PASS
BLE_1M	Ant1	2440	1000~3000	3.28	-65.7	≤-16.72	PASS
BLE_1M	Ant1	2440	3000~5000	3.28	-65.33	≤-16.72	PASS
BLE_1M	Ant1	2440	5000~7000	3.28	-65.19	≤-16.72	PASS
BLE_1M	Ant1	2440	7000~9000	3.28	-66.72	≤-16.72	PASS
BLE_1M	Ant1	2440	9000~11000	3.28	-66.94	≤-16.72	PASS
BLE_1M	Ant1	2440	11000~13000	3.28	-66.97	≤-16.72	PASS
BLE_1M	Ant1	2440	13000~15000	3.28	-64.9	≤-16.72	PASS
BLE_1M	Ant1	2440	15000~17000	3.28	-63.96	≤-16.72	PASS
BLE_1M	Ant1	2440	17000~19000	3.28	-62.35	≤-16.72	PASS
BLE_1M	Ant1	2440	19000~21000	3.28	-62.41	≤-16.72	PASS
BLE_1M	Ant1	2440	21000~23000	3.28	-61.18	≤-16.72	PASS
BLE_1M	Ant1	2440	23000~25000	3.28	-58.33	≤-16.72	PASS
BLE_1M	Ant1	2480	30~1000	2.22	-63.9	≤-17.78	PASS
BLE_1M	Ant1	2480	1000~3000	2.22	-64.92	≤-17.78	PASS
BLE_1M	Ant1	2480	3000~5000	2.22	-59.91	≤-17.78	PASS
BLE_1M	Ant1	2480	5000~7000	2.22	-67.74	≤-17.78	PASS
BLE_1M	Ant1	2480	7000~9000	2.22	-66.54	≤-17.78	PASS
BLE_1M	Ant1	2480	9000~11000	2.22	-67.19	≤-17.78	PASS
BLE_1M	Ant1	2480	11000~13000	2.22	-66.52	≤-17.78	PASS
BLE_1M	Ant1	2480	13000~15000	2.22	-64.4	≤-17.78	PASS
BLE_1M	Ant1	2480	15000~17000	2.22	-63.57	≤-17.78	PASS
BLE_1M	Ant1	2480	17000~19000	2.22	-62.53	≤-17.78	PASS
BLE_1M	Ant1	2480	19000~21000	2.22	-62.41	≤-17.78	PASS
BLE_1M	Ant1	2480	21000~23000	2.22	-61.06	≤-17.78	PASS
BLE_1M	Ant1	2480	23000~25000	2.22	-58.81	≤-17.78	PASS
BLE_2M	Ant1	2404	30~1000	1.43	-62.68	≤-18.57	PASS
BLE_2M	Ant1	2404	1000~3000	1.43	-65.51	≤-18.57	PASS
BLE_2M	Ant1	2404	3000~5000	1.43	-63.18	≤-18.57	PASS
BLE_2M	Ant1	2404	5000~7000	1.43	-66.79	≤-18.57	PASS
BLE_2M	Ant1	2404	7000~9000	1.43	-66.38	≤-18.57	PASS
BLE_2M	Ant1	2404	9000~11000	1.43	-66.99	≤-18.57	PASS
BLE_2M	Ant1	2404	11000~13000	1.43	-66.46	≤-18.57	PASS
BLE_2M	Ant1	2404	13000~15000	1.43	-64.92	≤-18.57	PASS


BLE_2M	Ant1	2404	15000~17000	1.43	-64.49	≤-18.57	PASS
BLE_2M	Ant1	2404	17000~19000	1.43	-62.28	≤-18.57	PASS
BLE_2M	Ant1	2404	19000~21000	1.43	-61.32	≤-18.57	PASS
BLE_2M	Ant1	2404	21000~23000	1.43	-61.78	≤-18.57	PASS
BLE_2M	Ant1	2404	23000~25000	1.43	-58.26	≤-18.57	PASS
BLE_2M	Ant1	2440	30~1000	2.62	-61.91	≤-17.38	PASS
BLE_2M	Ant1	2440	1000~3000	2.62	-66.1	≤-17.38	PASS
BLE_2M	Ant1	2440	3000~5000	2.62	-63.3	≤-17.38	PASS
BLE_2M	Ant1	2440	5000~7000	2.62	-66.9	≤-17.38	PASS
BLE_2M	Ant1	2440	7000~9000	2.62	-66.77	≤-17.38	PASS
BLE_2M	Ant1	2440	9000~11000	2.62	-66.46	≤-17.38	PASS
BLE_2M	Ant1	2440	11000~13000	2.62	-66.33	≤-17.38	PASS
BLE_2M	Ant1	2440	13000~15000	2.62	-64.08	≤-17.38	PASS
BLE_2M	Ant1	2440	15000~17000	2.62	-63.96	≤-17.38	PASS
BLE_2M	Ant1	2440	17000~19000	2.62	-61.77	≤-17.38	PASS
BLE_2M	Ant1	2440	19000~21000	2.62	-61.98	≤-17.38	PASS
BLE_2M	Ant1	2440	21000~23000	2.62	-61.46	≤-17.38	PASS
BLE_2M	Ant1	2440	23000~25000	2.62	-58.99	≤-17.38	PASS
BLE_2M	Ant1	2478	30~1000	1.82	-62.05	≤-18.18	PASS
BLE_2M	Ant1	2478	1000~3000	1.82	-65.37	≤-18.18	PASS
BLE_2M	Ant1	2478	3000~5000	1.82	-63.21	≤-18.18	PASS
BLE_2M	Ant1	2478	5000~7000	1.82	-67.31	≤-18.18	PASS
BLE_2M	Ant1	2478	7000~9000	1.82	-66.87	≤-18.18	PASS
BLE_2M	Ant1	2478	9000~11000	1.82	-66.28	≤-18.18	PASS
BLE_2M	Ant1	2478	11000~13000	1.82	-66.75	≤-18.18	PASS
BLE_2M	Ant1	2478	13000~15000	1.82	-64.27	≤-18.18	PASS
BLE_2M	Ant1	2478	15000~17000	1.82	-64.06	≤-18.18	PASS
BLE_2M	Ant1	2478	17000~19000	1.82	-62.67	≤-18.18	PASS
BLE_2M	Ant1	2478	19000~21000	1.82	-62.22	≤-18.18	PASS
BLE_2M	Ant1	2478	21000~23000	1.82	-61.52	≤-18.18	PASS
BLE_2M	Ant1	2478	23000~25000	1.82	-58.01	≤-18.18	PASS




BLE_1M-Ant1-2402-30~1000-PASS




BLE_1M-Ant1-2402-1000~3000-PASS




BLE_1M-Ant1-2402-3000~5000-PASS




BLE_1M-Ant1-2402-5000~7000-PASS




BLE_1M-Ant1-2402-7000~9000-PASS




BLE_1M-Ant1-2402-9000~11000-PASS




BLE_1M-Ant1-2402-11000~13000-PASS




BLE_1M-Ant1-2402-13000~15000-PASS




BLE_1M-Ant1-2402-15000~17000-PASS




BLE_1M-Ant1-2402-17000~19000-PASS




BLE_1M-Ant1-2402-19000~21000-PASS




BLE_1M-Ant1-2402-21000~23000-PASS




BLE_1M-Ant1-2402-23000~25000-PASS




BLE_1M-Ant1-2440-30~1000-PASS




BLE_1M-Ant1-2440-1000~3000-PASS




BLE_1M-Ant1-2440-3000~5000-PASS




BLE_1M-Ant1-2440-5000~7000-PASS




BLE_1M-Ant1-2440-7000~9000-PASS




BLE_1M-Ant1-2440-9000~11000-PASS




BLE_1M-Ant1-2440-11000~13000-PASS




BLE_1M-Ant1-2440-13000~15000-PASS




BLE_1M-Ant1-2440-15000~17000-PASS




BLE_1M-Ant1-2440-17000~19000-PASS




BLE_1M-Ant1-2440-19000~21000-PASS




BLE_1M-Ant1-2440-21000~23000-PASS




BLE_1M-Ant1-2440-23000~25000-PASS




BLE_1M-Ant1-2480-30~1000-PASS




BLE_1M-Ant1-2480-1000~3000-PASS




BLE_1M-Ant1-2480-3000~5000-PASS




BLE_1M-Ant1-2480-5000~7000-PASS




BLE_1M-Ant1-2480-7000~9000-PASS




BLE_1M-Ant1-2480-9000~11000-PASS




BLE_1M-Ant1-2480-11000~13000-PASS




BLE_1M-Ant1-2480-13000~15000-PASS




BLE_1M-Ant1-2480-15000~17000-PASS




BLE_1M-Ant1-2480-17000~19000-PASS




BLE_1M-Ant1-2480-19000~21000-PASS




BLE_1M-Ant1-2480-21000~23000-PASS




BLE_1M-Ant1-2480-23000~25000-PASS




BLE_2M-Ant1-2404-30~1000-PASS




BLE_2M-Ant1-2404-1000~3000-PASS




BLE_2M-Ant1-2404-3000~5000-PASS




BLE_2M-Ant1-2404-5000~7000-PASS




BLE_2M-Ant1-2404-7000~9000-PASS




BLE_2M-Ant1-2404-9000~11000-PASS




BLE_2M-Ant1-2404-11000~13000-PASS




BLE_2M-Ant1-2404-13000~15000-PASS




BLE_2M-Ant1-2404-15000~17000-PASS




BLE_2M-Ant1-2404-17000~19000-PASS




BLE_2M-Ant1-2404-19000~21000-PASS




BLE_2M-Ant1-2404-21000~23000-PASS




BLE_2M-Ant1-2404-23000~25000-PASS




BLE_2M-Ant1-2440-30~1000-PASS




BLE_2M-Ant1-2440-1000~3000-PASS




BLE_2M-Ant1-2440-3000~5000-PASS




BLE_2M-Ant1-2440-5000~7000-PASS




BLE_2M-Ant1-2440-7000~9000-PASS




BLE_2M-Ant1-2440-9000~11000-PASS




BLE_2M-Ant1-2440-11000~13000-PASS



BLE_2M-Ant1-2440-13000~15000-PASS



BLE_2M-Ant1-2440-15000~17000-PASS



BLE_2M-Ant1-2440-17000~19000-PASS