



Test Report

Product Name	Wireless Audio Module
Model No	AVMD7211
FCC ID.	V3CAVMD7F11A

Applicant	Avnera Corporation
Address	16505 NW Bethany Court, Suite 100, Beaverton OR97006, U.S.A.

Date of Receipt	Dec. 15, 2008
Issue Date	Dec. 30, 2008
Report No.	08C219R-RFUSP13V01
Version	V1.0

The test results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.
This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Test Report Certification

Issue Date: Dec. 30, 2008

Report No.: 08C219R-RFUSP13V01



Accredited by NIST (NVLAP)
NVLAP Lab Code: 200533-0

Product Name	Wireless Audio Module
Applicant	Avnera Corporation
Address	16505 NW Bethany Court, Suite 100, Beaverton OR97006, U.S.A.
Manufacturer	Avnera Corporation
Model No.	AVMD7211
Rated Voltage	AC 120V/60Hz
Working Voltage	DC 5V
Trade Name	Avnera
Applicable Standard	FCC CFR Title 47 Part 15 Subpart C: 2007 ANSI C63.4: 2003
Test Result	Complied



The test results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Documented By : Rita Huang
(Engineering Adm. Specialist /
Rita Huang)



Tested By : Molin huang
(Engineer / Molin Huang)

Approved By : Vincent Lin
(Manager / Vincent Lin)



TABLE OF CONTENTS

Description	Page
1. GENERAL INFORMATION	5
1.1. EUT Description.....	5
1.2. Operational Description	6
1.3. Tested System Details.....	7
1.4. Configuration of Tested System	7
1.5. EUT Exercise Software	7
1.6. Test Facility	8
2. Conducted Emission.....	9
2.1. Test Equipment.....	9
2.2. Test Setup	9
2.3. Limits	10
2.4. Test Procedure	10
2.5. Uncertainty	10
2.6. Test Result of Conducted Emission.....	11
3. Peak Power Output	12
3.1. Test Equipment.....	12
3.2. Test Setup	12
3.3. Limits	12
3.4. Test Procedure	12
3.5. Uncertainty	12
3.6. Test Result of Peak Power Output.....	13
4. Radiated Emission.....	14
4.1. Test Equipment.....	14
4.2. Test Setup	15
4.3. Limits	16
4.4. Test Procedure	17
4.5. Uncertainty	17
4.6. Test Result of Radiated Emission.....	18
5. RF antenna conducted test.....	25
5.1. Test Equipment.....	25
5.2. Test Setup	25
5.3. Limits	25
5.4. Test Procedure	25
5.5. Uncertainty	26
5.6. Test Result of RF antenna conducted test.....	27
6. Band Edge	29
6.1. Test Equipment.....	29
6.2. Test Setup	29
6.3. Limits	29
6.4. Test Procedure	30
6.5. Uncertainty	30
6.6. Test Result of Band Edge	31

7.	Occupied Bandwidth	35
7.1.	Test Equipment.....	35
7.2.	Test Setup	35
7.3.	Limits	35
7.4.	Test Procedure	35
7.5.	Uncertainty	35
7.6.	Test Result of Occupied Bandwidth	36
8.	Power Density	39
8.1.	Test Equipment.....	39
8.2.	Test Setup	39
8.3.	Limits	39
8.4.	Test Procedure	39
8.5.	Uncertainty	39
8.6.	Test Result of Power Density	40
9.	EMI Reduction Method During Compliance Testing	43

Attachment 1: EUT Test Photographs

Attachment 2: EUT Detailed Photographs

1. GENERAL INFORMATION

1.1. EUT Description

Product Name	Wireless Audio Module
Trade Name	Avnera
Model No.	AVMD7211
FCC ID.	V3CAVMD7F11A
Frequency Range	2405 – 2477MHz
Type of Modulation	$\pi/4$ DQPSK (Differential Quadrature Phase Shift Keying)
Number of Channels	37
Channel Control	Auto
Antenna Type	Printed dipole
Antenna Gain	Refer to the table “Antenna List”

Antenna List

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	Avnera	AVTF57-01C	Printed dipole	3.12dBi in 2.4 GHz

Center Frequency of Each Channel:

Channel	Frequency	Channel	Frequency	Channel	Frequency
Channel 2:	2405 MHz	Channel 3:	2407 MHz	Channel 4:	2409 MHz
Channel 5:	2411 MHz	Channel 6:	2413 MHz	Channel 7:	2415 MHz
Channel 8:	2417 MHz	Channel 9:	2419 MHz	Channel 10:	2421 MHz
Channel 11:	2423 MHz	Channel 12:	2425 MHz	Channel 13:	2427 MHz
Channel 14:	2429 MHz	Channel 15:	2431 MHz	Channel 16:	2433 MHz
Channel 17:	2435 MHz	Channel 18:	2437 MHz	Channel 19:	2439 MHz
Channel 20:	2441 MHz	Channel 21:	2443 MHz	Channel 22:	2445 MHz
Channel 23:	2447 MHz	Channel 24:	2449 MHz	Channel 25:	2451 MHz
Channel 26:	2453 MHz	Channel 27:	2455 MHz	Channel 28:	2457 MHz
Channel 29:	2459 MHz	Channel 30:	2461 MHz	Channel 31:	2463 MHz
Channel 32:	2465 MHz	Channel 33:	2467 MHz	Channel 34:	2469 MHz
Channel 35:	2471 MHz	Channel 36:	2473 MHz	Channel 37:	2475 MHz
Channel 38:	2477 MHz				

Note:

1. The EUT is a Wireless Audio Module with a built-in 2.4GHz transceiver
2. These tests are conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15 Subpart C Paragraph 15.247.
3. Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test.
4. The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report.

1.2. Operational Description

The EUT is a Wireless Audio Module with a built-in 2.4GHz transceiver. The EUT operation frequency is 2.405GHz-2.477GHz. The signals modulated by $\pi/4$ DQPSK (Differential Quadrature Phase Shift Keying) are transmitted from the Printed dipole Antenna of the EUT.

Test Mode:	Mode 1: Transmitter
------------	---------------------


1.3. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product	Manufacturer	Model No.	Serial No.	Power Cord
(1) Notebook PC	DELL	PPT	N/A	Non-Shielded, 0.8m

Signal Cable Type	Signal cable Description
A USB Cable	Non-Shielded, 1.7m

1.4. Configuration of Tested System



1.5. EUT Exercise Software

- (1) Setup the EUT as shown in section 1.4.
- (2) Connect the EUT to a notebook via a USB.
- (3) Execute Avnera Wireless.exe on the notebook.
- (4) Double-click “Audio Suite Ver1.67” and select USB as a primary connection interface.
- (5) Setup the test channel and choose “diversity select high” of testing program.
- (6) Presses “Apply” to start the continuous transmit.
- (7) Verify that the EUT works correctly.

1.6. Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	50-65
Barometric pressure (mbar)	860-1060	950-1000

The related certificate for our laboratories about the test site and management system can be downloaded from QuieTek Corporation's Web Site : <http://tw.quietek.com/modules/myalbum/>
The address and introduction of QuieTek Corporation's laboratories can be founded in our Web site : <http://www.quietek.com/>

Site Description: File on
Federal Communications Commission
FCC Engineering Laboratory
7435 Oakland Mills Road
Columbia, MD 21046
Registration Number: 92195



Accreditation on NVLAP
NVLAP Lab Code: 200533-0



Site Name: Quietek Corporation
Site Address: No. 5-22, Ruei-Shu Valley, Ruei-Ping Tsuen,
Lin-Kou Shiang, Taipei,
Taiwan, R.O.C.
TEL: 886-2-8601-3788 / FAX : 886-2-8601-3789
E-Mail : service@quietek.com

FCC Accreditation Number: TW1014



2. Conducted Emission


2.1. Test Equipment

The following test equipment are used during the conducted emission test:

Item	Instrument	Manufacturer	Type No./Serial No	Last Cal.	Remark
1	Test Receiver	R & S	ESCS 30/825442/17	May, 2008	
2	L.I.S.N.	R & S	ESH3-Z5/825016/6	May, 2008	EUT
3	L.I.S.N.	Kyoritsu	KNW-407/8-1420-3	May, 2008	Peripherals
4	Pulse Limiter	R & S	ESH3-Z2	May, 2008	
5	No.1 Shielded Room			N/A	

Note: All instruments are calibrated every one year.

2.2. Test Setup



2.3. Limits

FCC Part 15 Subpart C Paragraph 15.207 (dBuV) Limit		
Frequency MHz	Limits	
	QP	AVG
0.15 - 0.50	66-56	56-46
0.50-5.0	56	46
5.0 - 30	60	50

2.4. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm /50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement.

Conducted emissions were invested over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

2.5. Uncertainty

± 2.26 dB

2.6. Test Result of Conducted Emission

The EUT is powered by batteries Owing to the DC operation. This test item is not performed

3. Peak Power Output

3.1. Test Equipment


The following test equipments are used during the radiated emission tests:

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X Power Meter	Anritsu	ML2495A/6K00003357	May, 2008
X Power Sensor	Anritsu	MA2491A/034457	May, 2008

Note: 1. All instruments are calibrated every one year.
2. The test instruments marked by "X" are used to measure the final test results.

3.2. Test Setup

Conducted Measurement



3.3. Limits

The maximum peak power shall be less 1 Watt.

3.4. Test Procedure

The EUT was tested according to DTS test procedure of Mar. 2005 KDB558074 for compliance to FCC 47CFR 15.247 requirements.

3.5. Uncertainty

± 1.27 dB

3.6. Test Result of Peak Power Output

Product : Wireless Audio Module
Test Item : Peak Power Output Data
Test Site : No.3 OATS
Test Mode : Mode 1: Transmitter

Channel No.	Frequency (MHz)	Measurement	Required Limit	Result
Channel 02	2405.00	2.855dBm	1 Watt= 30 dBm	Pass
Channel 20	2441.00	2.311dBm	1 Watt= 30 dBm	Pass
Channel 38	2477.00	1.833dBm	1 Watt= 30 dBm	Pass

4. Radiated Emission

4.1. Test Equipment

The following test equipment are used during the radiated emission test:


Test Site	Equipment		Manufacturer	Model No./Serial No.	Last Cal.
<input checked="" type="checkbox"/> Site # 3	X	Bilog Antenna	Schaffner Chase	CBL6112B/2673	Sep., 2008
	X	Pre-Amplifier	AGILENT	8447D/2944A09549	Sep., 2008
	X	Test Receiver	R & S	ESCS 30/ 825442/018	Sep., 2008
	X	Spectrum Analyzer	Advantest	R3162/91700283	Oct., 2008
	X	Coaxial Cable	QuieTek	QTK-CABLE/ CAB5	Feb., 2008
	X	Controller	QuieTek	QTK-CONTROLLER/ CTRL3	N/A
	X	Coaxial Switch	Anritsu	MP59B/6200265729	N/A

Note: 1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.


2. The test instruments marked with "X" are used to measure the final test results.

4.2. Test Setup

Radiated Emission Below 1GHz



Radiated Emission Above 1GHz



4.3. Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

FCC Part 15 Subpart C Paragraph 15.209(a) Limits		
Frequency MHz	uV/m @3m	dBuV/m@3m
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Remarks: 1. E field strength (dBuV/m) = 20 log E field strength (uV/m)

2. According to FCC 15.35 the frequencies above 1000MHz, as measured using instrumentation with a peak detector function was corresponding to 20dB above the maximum permitted average limit.

4.4. Test Procedure

The EUT was setup according to ANSI C63.4, 2003 and tested according to DTS test procedure of Mar. 2005 KDB558074 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned between 1 meter and 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4:2003 on radiated measurement.

The resolution bandwidth below 1GHz setting on the field strength meter is 120 kHz and above 1GHz is 1MHz.

Radiated emission measurements below 1GHz are made using broadband Bilog antenna and above 1GHz are made using Horn Antennas.

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with the measurement antenna kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. The antenna is pointed at an angle towards the source of the emission, and the EUT is rotated in both height and polarization to maximize the measured emission. The emission is kept within the illumination area of the 3 dB beamwidth of the antenna.

The worst radiated emission is measured in the Open Area Test Site on the Final Measurement.

The frequency range from 30MHz to 10th harmonics is checked.

4.5. Uncertainty

± 3.9 dB above 1GHz

± 3.8 dB below 1GHz

4.6. Test Result of Radiated Emission

Product : Wireless Audio Module
 Test Item : Fundamental Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter X axis position

Frequency MHz	Correct Factor	Reading Level dB	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal					
Peak Detector:					
2405.000	-2.303	95.040	92.737	N/A	N/A
2441.000	-2.128	97.380	95.251	N/A	N/A
2477.000	-1.966	95.980	94.015	N/A	N/A
Average					
Detector:					
--					
Vertical					
Peak Detector:					
2405.000	-2.303	82.430	80.127	N/A	N/A
2441.000	-2.128	82.390	80.261	N/A	N/A
2477.000	-1.966	81.690	79.725	N/A	N/A
Average					
Detector:					
--					

Product : Wireless Audio Module
 Test Item : Fundamental Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter Y axis position

Frequency	Correct Factor	Reading Level	Measurement Level	Margin	Limit
MHz	dB	dBuV	dBuV/m	dB	dBuV/m

Horizontal

Peak Detector:

2405.000	-2.303	94.560	92.257	N/A	N/A
2441.000	-2.128	94.500	92.371	N/A	N/A
2477.000	-1.966	94.060	92.095	N/A	N/A

Average Detector:

--

Vertical

Peak Detector:

2405.000	-2.303	84.100	81.797	N/A	N/A
2441.000	-2.128	84.600	82.471	N/A	N/A
2477.000	-1.966	83.770	81.805	N/A	N/A

Average Detector:

--

Product : Wireless Audio Module
 Test Item : Fundamental Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter Z axis position

Frequency	Correct Factor	Reading Level	Measurement Level	Margin	Limit
MHz	dB	dBuV	dBuV/m	dB	dBuV/m

Horizontal

Peak Detector:

2405.000	-2.303	83.640	81.337	N/A	N/A
2441.000	-2.128	83.730	81.601	N/A	N/A
2477.000	-1.966	81.880	79.915	N/A	N/A

Average

Detector:

--

Vertical

Peak Detector:

2405.000	-2.303	95.050	92.747	N/A	N/A
2441.000	-2.128	95.600	93.471	N/A	N/A
2477.000	-1.966	94.745	92.780	N/A	N/A

Average

Detector:

--

Product : Wireless Audio Module
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter X axis position (2405MHz)

Frequency	Correct Factor	Reading Level	Measurement Level	Margin	Limit
MHz	dB	dBuV	dBuV/m	dB	dBuV/m

Horizontal

Peak Detector:

4810.000	-0.214	43.790	43.577	-30.423	74.000
7215.000	3.233	46.000	49.232	-24.768	74.000
9620.000	5.722	41.340	47.061	-26.939	74.000

Average

Detector:

--

Vertical

Peak Detector:

4810.000	-0.214	40.620	40.407	-33.593	74.000
7215.000	3.233	42.330	45.562	-28.438	74.000
9620.000	5.722	42.210	47.931	-26.069	74.000

Average

Detector:

--

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ * ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : Wireless Audio Module
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter X axis position (2441 MHz)

Frequency	Correct Factor	Reading Level	Measurement Level	Margin	Limit
MHz	dB	dBuV	dBuV/m	dB	dBuV/m

Horizontal

Peak Detector:

4882.000	-0.276	43.160	42.884	-31.116	74.000
7323.000	3.330	41.390	44.719	-29.281	74.000
9764.000	6.262	40.700	46.963	-27.037	74.000

Average

Detector:

--

Vertical

Peak Detector:

4882.000	-0.276	43.080	42.804	-31.196	74.000
7323.000	3.330	41.360	44.689	-29.311	74.000
9764.000	6.262	40.330	46.593	-27.407	74.000

Average

Detector:

--

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : Wireless Audio Module
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter X axis position (2477 MHz)

Frequency	Correct Factor	Reading Level	Measurement Level	Margin	Limit
MHz	dB	dBuV	dBuV/m	dB	dBuV/m

Horizontal

Peak Detector:

4954.000	0.513	42.530	43.043	-30.957	74.000
7431.000	3.877	41.260	45.137	-28.863	74.000
9908.000	6.488	41.470	47.959	-26.041	74.000

Average

Detector:

--

Vertical

Peak Detector:

4954.000	0.513	41.920	42.433	-31.567	74.000
7431.000	3.877	41.580	45.457	-28.543	74.000
9908.000	6.488	41.470	47.959	-26.041	74.000

Average

Detector:

--

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : Wireless Audio Module
 Test Item : General Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter X axis position (2441 MHz)

Frequency MHz	Correct Factor	Reading dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal					
425.760	-0.290	34.685	34.395	-11.605	46.000
480.080	1.700	36.108	37.808	-8.192	46.000
540.220	3.300	34.261	37.561	-8.439	46.000
689.600	3.471	31.753	35.224	-10.776	46.000
782.720	5.154	29.966	35.120	-10.880	46.000
934.040	6.726	27.908	34.634	-11.366	46.000
Vertical					
474.260	-3.650	34.830	31.180	-14.820	46.000
528.580	0.970	33.986	34.956	-11.044	46.000
613.940	1.566	30.473	32.039	-13.961	46.000
716.760	-1.508	30.752	29.244	-16.756	46.000
837.040	1.310	29.359	30.669	-15.331	46.000
928.220	3.400	30.439	33.839	-12.161	46.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

5. RF antenna conducted test

5.1. Test Equipment


The following test equipments are used during the radiated emission tests:

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Spectrum Analyzer	R&S	FSP40 / 100170	Nov, 2008
Spectrum Analyzer	Agilent	E4407B / US39440758	May, 2008
X Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2008

Note: 1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with "X" are used to measure the final test results.

5.2. Test Setup

RF antenna Conducted Measurement:



5.3. Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

5.4. Test Procedure

The EUT was tested according to DTS test procedure of Mar. 2005 KDB558074 for compliance to FCC 47CFR 15.247 requirements.

Set RBW = 100 kHz, Set VBW > RBW, scan up through 10th harmonic.


5.5. **Uncertainty**

The measurement uncertainty
Conducted is defined as $\pm 1.27\text{dB}$


5.6. Test Result of RF antenna conducted test

Product : Wireless Audio Module
 Test Item : RF antenna conducted test
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter

Channel 02 (2405MHz) 30-25GHz



Channel 20 (2441MHz) 30-25GHz



Channel 38 (2477MHz) 30-25GHz



6. Band Edge

6.1. Test Equipment


The following test equipments are used during the band edge tests:

Test Site	Equipment		Manufacturer	Model No./Serial No.	Last Cal.
☒ Site # 3	X	Bilog Antenna	Schaffner Chase	CBL6112B/2673	Sep., 2008
	X	Pre-Amplifier	AGILENT	8447D/2944A09549	Sep., 2008
	X	Test Receiver	R & S	ESCS 30/ 825442/018	Sep., 2008
	X	Spectrum Analyzer	Advantest	R3162/91700283	Oct., 2008
	X	Coaxial Cable	Quietek	QTK-CABLE/ CAB5	Feb., 2008
	X	Controller	Quietek	QTK-CONTROLLER/ CTRL3	N/A
	X	Coaxial Switch	Anritsu	MP59B/6200265729	N/A

Note: 1. All instruments are calibrated every one year.
2. The test instruments marked by "X" are used to measure the final test results.

6.2. Test Setup

RF Radiated Measurement:



6.3. Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

6.4. Test Procedure

The EUT was setup according to ANSI C63.4, 2003 and tested according to DTS test procedure of Mar. 2005 KDB558074 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned between 1 meter and 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4:2003 on radiated measurement.

The resolution bandwidth below 1GHz setting on the field strength meter is 120 kHz and above 1GHz is 1MHz.

Radiated emission measurements below 1GHz are made using broadband Bilog antenna and above 1GHz are made using Horn Antennas.

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with the measurement antenna kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. The antenna is pointed at an angle towards the source of the emission, and the EUT is rotated in both height and polarization to maximize the measured emission. The emission is kept within the illumination area of the 3 dB beamwidth of the antenna.

6.5. The worst radiated emission is measured in the Open Area Test Site on the Final Measurement. Uncertainty

± 3.9 dB above 1GHz

± 3.8 dB below 1GHz

6.6. Test Result of Band Edge


Product : Wireless Audio Module
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
02 (Peak)	2387.100	-6.776	52.380	45.604	74.00	54.00	Pass
02 (Average)	--	--	--	--	74.00	54.00	Pass

Figure Channel 02:

Horizontal (Peak)




Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : Wireless Audio Module
Test Item : Band Edge Data
Test Site : No.3 OATS
Test Mode : Mode 1: Transmitter

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
02 (Peak)	2388.600	-6.772	50.592	43.820	74.00	54.00	Pass
02 (Average)	--	--	--	--	74.00	54.00	Pass

Figure Channel 02:**(Vertical) (Peak)****Note:**

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.


Product : Wireless Audio Module
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
38 (Peak)	2484.800	-6.467	44.641	38.175	74.00	54.00	Pass
38(Average)	--	--	--	--	74.00	54.00	Pass

Figure Channel 38:

Horizontal (Peak)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.


Product : Wireless Audio Module
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
38 (Peak)	2484.700	-6.467	44.721	38.254	74.00	54.00	Pass
38(Average)	--	--	--	--	74.00	54.00	Pass

Figure Channel 38:

Vertical (Peak)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ * ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

7. Occupied Bandwidth


7.1. Test Equipment

The following test equipments are used during the radiated emission tests:

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Spectrum Analyzer	R&S	FSP40 / 100170	Nov, 2008
Spectrum Analyzer	Agilent	E4407B / US39440758	May, 2008
X Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2008

Note: 1. All instruments are calibrated every one year.
2. The test instruments marked by "X" are used to measure the final test results.

7.2. Test Setup



7.3. Limits

The minimum bandwidth shall be at least 500 kHz.

7.4. Test Procedure

The EUT was setup according to ANSI C63.4, 2003; tested according to DTS test procedure of Mar. 2005 KDB558074 for compliance to FCC 47CFR 15.247 requirements.

Set RBW = 100 kHz, Span greater than RBW.

7.5. Uncertainty


± 150Hz

7.6. Test Result of Occupied Bandwidth

Product : Wireless Audio Module
 Test Item : Occupied Bandwidth Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (2405MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
02	2405.00	1080	>500	Pass


Figure Channel 02:



Product : Wireless Audio Module
 Test Item : Occupied Bandwidth Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (2441MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
20	2441.00	1090	>500	Pass


Figure Channel 20:



Product : Wireless Audio Module
 Test Item : Occupied Bandwidth Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (2477MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
38	2477.00	1090	>500	Pass

Figure Channel 38:



8. Power Density


8.1. Test Equipment

The following test equipments are used during the radiated emission tests:

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Spectrum Analyzer	R&S	FSP40 / 100170	Nov, 2008
Spectrum Analyzer	Agilent	E4407B / US39440758	May, 2008
X Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2008

Note: 1. All equipments are calibrated every one year.
2. The test instruments marked by "X" are used to measure the final test results.

8.2. Test Setup



8.3. Limits

The transmitted power density averaged over any 1 second interval shall not be greater +8dBm in any 3kHz bandwidth.

8.4. Test Procedure

The EUT was setup according to ANSI C63.4, 2003; tested according to DTS test procedure of Mar. 2005 KDB558074 for compliance to FCC 47CFR 15.247 requirements.
Set RBW= 3 kHz, VBW=10KHz, Sweep time=(SPAN/3KHz), detector=Peak detector

8.5. Uncertainty


± 1.27 dB

8.6. Test Result of Power Density

Product : Wireless Audio Module
 Test Item : Power Density Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (2405MHz)

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
02	2405.00	-17.41	< 8dBm	Pass


Figure Channel 02:



Product : Wireless Audio Module
 Test Item : Power Density Data
 Test Site : No.3OATS
 Test Mode : Mode 1: Transmitter (2441MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
20	2441.000	-19.08	< 8dBm	Pass


Figure Channel 20:



Product : Wireless Audio Module
 Test Item : Power Density Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (2477MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
38	2477.00	-20.22	< 8dBm	Pass

Figure Channel 38:



9. EMI Reduction Method During Compliance Testing

No modification was made during testing.