

## 7. RF Exposure Requirements

### 7. 1 Test Equipment

Please refer to Section 10 this report.

### 7. 2 Limit

According to FCC 15.247(i), Systems operating under provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commissions guidelines.

FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)(1) of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

### 7. 3 Test Result

Product	: Network Camera Baby Monitor	Test Mode	: IEEE 802.11b/g/n
Test Item	: RF Exposure	Temperature	: 25 °C
Test Voltage	: DC 12V (Power by DC Power Supply)	Humidity	: 56%RH
Test Result	: <b>PASS</b>		

Evaluation of RF Exposure Compliance Requirements MPE Prediction of MPE according to equation from page 19 of OET Bulletin 65, Edition 97-01	
RF Exposure Requirements	Compliance with FCC Rules
S=PG/4ΠR <sup>2</sup>  Where: S=Power density P=Power input to antenna G=Power gain of the antenna relative to an isotropic radiator R=Distance to the center of radiation of the antenna	Maximum output power at antenna input terminal: -22.00 dBm = 0.0063 mW (802.11b/g, 2412MHz) -24.08 dBm = 0.0039 mW (Draft n, 2412MHz)(20MHz) Prediction distance: 20 cm Antenna gain : 2.0 dBi MPE limit for uncontrolled exposure at prediction frequency: 10 W/m <sup>2</sup>  Power density at 20 cm:  802.11b/g: 0.000002 mW/m <sup>2</sup> Draft n : 0.000001 mW/m <sup>2</sup>

**MPE Evaluation**

Mode	Frequency (MHz)	OutputPower (dBm)	RF Power (mW)	Antenna Gain (dBi)	Distance (cm)	MPE (mW/cm2)	Limit MPE (mW/cm2)
802.11b	2412	-25.02	0.0031	2.00	20.0	0.00000099	1.0
	2437	-31.01	0.0008	2.00	20.0	0.00000025	1.0
	2462	-28.36	0.0015	2.00	20.0	0.00000046	1.0
Mode	Frequency (MHz)	OutputPower (dBm)	RF Power (mW)	Antenna Gain (dBi)	Distance (cm)	MPE (mW/cm2)	Limit MPE (mW/cm2)
802.11g	2412	-22.00	0.0063	2.00	20.0	0.00000199	1.0
	2437	-27.14	0.0019	2.00	20.0	0.00000061	1.0
	2462	-22.51	0.0056	2.00	20.0	0.00000177	1.0
Mode	Frequency (MHz)	OutputPower (dBm)	RF Power (mW)	Antenna Gain (dBi)	Distance (cm)	MPE (mW/cm2)	Limit MPE (mW/cm2)
Draft n 20MHz Ant.0	2412	-24.08	0.0039	2.00	20.0	0.00000123	1.0
	2437	-31.51	0.0007	2.00	20.0	0.00000022	1.0
	2462	-25.48	0.0028	2.00	20.0	0.00000089	1.0
Mode	Frequency (MHz)	OutputPower (dBm)	RF Power (mW)	Antenna Gain (dBi)	Distance (cm)	MPE (mW/cm2)	Limit MPE (mW/cm2)
Draft n 40MHz Ant.0	2412	-34.37	0.0004	2.00	20.0	0.00000012	1.0
	2437	-32.20	0.0006	2.00	20.0	0.00000019	1.0
	2452	-32.59	0.0006	2.00	20.0	0.00000017	1.0