



TEST REPORT

Applicant:	Dongguan Newmen Electronics Technology Co. ,LTD
Address:	No.5,Xifa road, Lin village, Tangxia Town, Dongguan, Guangdong, China

Manufacturer or Supplier	Dongguan Newmen Electronics Technology Co. ,LTD
Address	No.5,Xifa road, Lin village, Tangxia Town, Dongguan, Guangdong, China
Product:	Dongle
Brand Name:	HP
Model:	FM710-D
Additional Model & Model Difference:	N/A
Date of tests:	Jan. 08, 2015 ~ Jan. 27, 2015

the tests have been carried out according to the requirements of the following standard:

CONCLUSION: The submitted sample was found to **COMPLY** with the test requirement

Tested by Breeze Jiang Project Engineer / EMC Department	Approved by Glyn He Supervisor / EMC Department
preerl	Date: Jan. 27, 2015

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into

account to declare the compliance or non-compliance to the specification



TABLE OF CONTENTS

R	ELEASE	CONTROL RECORD	3
1	SUMI	MARY OF TEST RESULTS	4
2		SUREMENT UNCERTAINTY	
3		ERAL INFORMATION	
Ŭ		NERAL DESCRIPTION OF EUT	
		SCRIPTION OF TEST MODES	
		NERAL DESCRIPTION OF APPLIED STANDARDS	
		SCRIPTION OF SUPPORT UNITS	
4.	TEST	TYPES AND RESULTS	8
	4.1 CC	NDUCTED EMISSION MEASUREMENT	8
		LIMITS OF CONDUCTED EMISSION MEASUREMENT	
	4.1.2	TEST INSTRUMENTS	8
	4.1.3	TEST PROCEDURES	8
	4.1.4	DEVIATION FROM TEST STANDARD	9
	4.1.5	TEST SETUP	9
	4.1.6	EUT OPERATING CONDITIONS	9
	4.1.7	TEST RESULTS	10
	4.2 RA	DIATED EMISSION MEASUREMENT	12
	4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	
	4.2.2	TEST INSTRUMENTS	13
	4.2.3	TEST PROCEDURES	14
	4.2.4	DEVIATION FROM TEST STANDARD	14
	4.2.5	TEST SETUP	
	4.2.6	EUT OPERATING CONDITIONS	15
	4.2.7	TEST RESULTS	
	4.3 200	B BANDWIDTH MEASUREMENT	
	4.3.1	LIMITS OF 20dB BANDWIDTH MEASUREMENT	
	4.3.2	TEST INSTRUMENTS	
	4.3.3	TEST PROCEDURE	
	4.3.4		
	4.3.5		
	4.3.6		
	4.3.7	TEST RESULTS	22
5.	PHO1	OGRAPHS OF THE TEST CONFIGURATION	25
_	4 55-	NDIV A MODIFICATIONS DECORDED SEE ENGINEERING SHAN	F0 T0 T' -
6.		NDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANG	
	EUT B	Y THE LAB	26



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF150108N011-2	Original release	Jan. 27, 2015

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.249)					
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK		
§15.203	Antenna Requirement	PASS	No antenna connector is used		
§15.207 (a)	Conducted Emission	PASS	Compliant		
§15.205	Restricted Band of Operation	PASS	Compliant		
§15.209 §15.249(a)	Radiated Emission	PASS	Compliant		
§15.215(c)	20dB Bandwidth Test	PASS	Compliant		

2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY	
Conducted emissions	9kHz~30MHz	2.66dB	
	9KHz ~ 30MHz	2.74dB	
Radiated emissions	30MHz ~ 1GHz	3.55dB	
Radiated emissions	1GHz ~ 18GHz	4.84dB	
	18GHz ~ 40GHz	4.84dB	

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Dongle
MODEL NO.	FM710-D
FCC ID	V4P-FM710-D
NOMINAL VOLTAGE	DC 5V by USB
MODULATION TECHNOLOGY	GFSK
OPERATING FREQUENCY	2402-2476MHz
ANTENNA TYPE	PCB Antenna, with -2.0dBi gain
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	N/A

NOTE:

- 1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- 2. For the test results, the EUT had been tested with all conditions, but only the worst case was shown in test report.
- 3. Please refer to the EUT photo document (Reference No.:150108N011-2) for detailed product photo.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



3.2 DESCRIPTION OF TEST MODES

EUT CONFIGURE		APPLICA	ABLE TO		DESCRIPTION	
MODE	RE<1G	RE≥1G	PLC	BW	DESCRIPTION	
-	V	V	V	\checkmark	Powered by USB	

Where **RE<1G:** Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz

PLC: Power Line Conducted Emission

BW: 20db bandwidth

Following channel(s) was (were) selected for the test as listed below.

TESTED CHANNEL	TESTED FREQUENCY
Low	2402 MHz
Middle	2441 MHz
High	2476 MHz

Note: The more detailed channel, please refer to the product specifications

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.249 ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

NOTE: It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Doc) The test report has been issued separately.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Notebook	Lenovo	E430	MP-0DN27	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	AC Line: Unshielded, Detachable 1.5m; DC Line: Unshielded, Detachable 1.5m

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



S TOOL ROPOLL HOLL IN TOO TOO HOLL 2

4. TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBµV)			
	Quasi-peak	Average		
0.15 ~ 0.5	66 to 56	56 to 46		
0.5 ~ 5	56	46		
5 ~ 30	60	50		

NOTE: 1.The lower limit shall apply at the transition frequencies.

- 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
- All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

5 Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESCS30	100340	May 17,14	May 16,15
Artificial Mains Network	Rohde&Schwarz	ENV216	101173	May 13,14	May 12,15
Artificial Mains Network	Rohde&Schwarz	ESH3-Z5	100317	May 13,14	May 12,15
Test software	ADT	ADT_Cond_V7.3.7	N/A	N/A	N/A

NOTE:

- 1. The test was performed in shielded room 553.
- 2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit 20dB) were not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080


 $\pmb{\mathsf{Email} \colon \underline{\mathsf{customerservice.dg@cn.bureauveritas.com}}}$



4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN. 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

Set the EUT under transmission condition continuously at specific channel frequency.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080




4.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA: GFSK DH5

No	Freq. [MHz]	Corr. Factor	Reading Value [dB (uV)]			on Level (uV)]	Lir [dB (nit (uV)]		rgin B)
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16172	10.80	23.14	11.97	33.94	22.77	65.38	55.38	-31.44	-32.61
2	0.18125	10.72	20.78	10.10	31.50	20.82	64.43	54.43	-32.93	-33.61
3	0.44688	10.62	20.77	19.89	31.39	30.51	56.93	46.93	-25.55	-16.43
4	2.08984	10.01	21.71	12.21	31.72	22.22	56.00	46.00	-24.28	-23.78
5	2.43750	10.03	22.09	16.53	32.12	26.56	56.00	46.00	-23.88	-19.44
6	17.04688	10.24	21.33	15.08	31.57	25.32	60.00	50.00	-28.43	-24.68

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

- 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
- 3. The emission levels of other frequencies were very low against the limit.
- 4. Margin value = Emission level Limit value
- 5. Correction factor = Insertion loss + Cable loss
- 6. Emission Level = Correction Factor + Reading Value



Tel: +86 769 8593 5656 Fax: +86 769 8593 1080




|--|

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]			on Level (uV)]		nit (uV)]		rgin B)
		(GD)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18125	10.58	23.94	16.81	34.52	27.39	64.43	54.43	-29.90	-27.03
2	0.39219	10.59	20.48	8.13	31.07	18.72	58.02	48.02	-26.95	-29.30
3	0.44688	10.60	23.43	22.65	34.03	33.25	56.93	46.93	-22.90	-13.68
4	3.80078	9.82	21.59	13.66	31.41	23.48	56.00	46.00	-24.59	-22.52
5	7.14844	9.93	18.75	13.54	28.68	23.47	60.00	50.00	-31.32	-26.53
6	16.99609	10.23	24.35	19.54	34.58	29.77	60.00	50.00	-25.42	-20.23

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

- 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
- 3. The emission levels of other frequencies were very low against the limit.
- 4. Margin value = Emission level Limit value
- 5. Correction factor = Insertion loss + Cable loss
- 6. Emission Level = Correction Factor + Reading Value



Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

According to §15.249(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Field strength of fundamental (milli-volts/meter)	Field strength of harmonics (micro-volts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply.

NOTE:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



4.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Spectrum Analyzer	Agilent	E4446A	MY46180622	Apr. 29,14	Apr. 28,15
EMI Test Receiver	Rohde&Schwarz	ESVS10	841431/004	May 17,14	May 16,15
Loop antenna (9kHz~30MHz)	Daze	ZN30900A	0708	Dec. 05,14	Dec. 04,15
Bilog Antenna	Teseq	CBL 6111D	30643	Jul. 25, 14	Jul. 24, 15
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	00062558	May 30,14	May 29,15
Horn Antenna (15GHz-40GHz)	SCHWARZBECK	BBHA 9170	BBHA9170242	Feb. 13,14	Feb. 12,15
Pre-Amplifier (9kHz~1GHz)	SONOMA	310D	186955	Mar. 05,14	Mar. 04,15
Signal Amplifier	Agilent	8447D	2944A10488	Jun. 25,14	Jun. 24,15
Pre-Amplifier (100MHz-26.5GHz)	Agilent	8449B	3008A00409	May 13,14	May 12,15
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 20,14	Nov. 19,15
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	Apr. 19,14	Apr. 18,15
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 27,14	Oct. 26,15
Test Software	ADT	ADT_Radiated _V7.6.15.9.2	N/A	N/A	N/A

NOTE:

- 1. The test was performed in 966 Chamber.
- 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
- 3. The horn antenna are used only for the measurement of emission frequency above 1GHz if tested.
- 4. The FCC Site Registration No. is 502831.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength.
 Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
- 4. All modes of operation were investigated and the worst-case emissions are reported.


4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



4.2.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

- a) Turned on the power of all equipment.
- b) EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



4.2.7 TEST RESULTS


BELOW 1GHz WORST-CASE DATA

CHANNEL	TX Middle Channel	DETECTOR	Overi Bark (OB)
FREQUENCY RANGE	30MHz ~ 1GHz	FUNCTION	Quasi-Peak (QP)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	149.63	17.8 QP	43.5	-25.7	1.00 H	0	28.08	-10.24	
2	159.33	18.4 QP	43.5	-25.1	1.00 H	0	27.45	-9.02	
3	342.02	22.3 QP	46.0	-23.7	1.00 H	0	28.53	-6.27	
4	527.93	19.5 QP	46.0	-26.5	1.00 H	0	21.30	-1.79	
5	710.62	26.1 QP	46.0	-19.9	1.00 H	0	24.37	1.71	
6	893.30	29.1 QP	46.0	-16.9	1.00 H	0	24.43	4.63	

REMARKS:

- 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.



Tel: +86 769 8593 5656 Fax: +86 769 8593 1080




CHANNEL	TX Middle Channel	DETECTOR	Ougai Pagle (OP)
FREQUENCY RANGE	30MHz ~ 1GHz	FUNCTION	Quasi-Peak (QP)

	ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M							
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	149.63	26.5 QP	43.5	-17.0	1.00 V	0	31.53	-5.06
2	159.33	28.8 QP	43.5	-14.7	1.00 V	0	32.99	-4.19
3	188.43	28.6 QP	43.5	-14.9	1.00 V	0	36.97	-8.34
4	299.98	22.9 QP	46.0	-23.1	1.00 V	0	28.48	-5.61
5	342.02	28.6 QP	46.0	-17.5	1.00 V	0	32.97	-4.42
6	717.08	30.1 QP	46.0	-15.9	1.00 V	0	25.85	4.25

REMARKS:

- 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.



Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



ABOVE 1GHz WORST-CASE DATA:

CHANNEL	TX Low Channel	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M							
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2400.00	55.8 PK	74.0	-18.2	1.00 H	81	51.87	3.93
2	2400.00	31.7 AV	54.0	-22.3	1.00 H	81	27.77	3.93
3	*2402.00	91.9 PK	114.0	-22.1	1.00 H	81	87.96	3.94
4	*2402.00	67.8 AV	94.0	-26.2	1.00 H	81	63.86	3.94
5	4804.00	64.8 PK	74.0	-9.2	1.35 H	257	55.19	9.61
6	4804.00	40.7 AV	54.0	-13.3	1.35 H	257	31.09	9.61
7	7206.00	58.8 PK	74.0	-15.2	1.16 H	52	45.64	13.16
8	7206.00	34.7 AV	54.0	-19.3	1.16 H	52	21.54	13.16
		ANTENNA	POLARITY	& TEST DI	STANCE: V	ERTICAL A	T 3 M	
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2400.00	46.8 PK	74.0	-27.2	1.00 V	33	42.87	3.93
2	2400.00	22.7 AV	54.0	-31.3	1.00 V	33	18.77	3.93
3	*2402.00	83.8 PK	114.0	-30.2	1.00 V	33	79.86	3.94
4	*2402.00	59.7 AV	94.0	-34.3	1.00 V	33	55.76	3.94
5	4804.00	57.5 PK	74.0	-16.5	1.03 V	87	47.90	9.61
6	4804.00	33.4 AV	54.0	-20.6	1.03 V	87	23.80	9.61
7	7206.00	54.5 PK	74.0	-19.5	1.12 V	51	41.31	13.16
8	7206.00	30.4 AV	54.0	-23.6	1.12 V	51	17.21	13.16

REMARKS:

- 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.
- 5. " * ": Fundamental frequency.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



CHANNEL	TX Middle Channel	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M							
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	92.3 PK	114.0	-21.7	1.06 H	162	88.25	4.05
2	*2441.00	68.2 AV	94.0	-25.8	1.06 H	162	64.15	4.05
3	4882.00	62.2 PK	74.0	-11.8	1.20 H	44	52.46	9.74
4	4882.00	38.1 AV	54.0	-15.9	1.20 H	44	28.36	9.74
5	7323.00	57.1 PK	74.0	-16.9	1.12 H	88	43.96	13.14
6	7323.00	33.0 AV	54.0	-21.0	1.12 H	88	19.86	13.14
		ANTENNA	POLARITY	& TEST DI	STANCE: V	ERTICAL A	T 3 M	
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	86.2 PK	114.0	-27.8	1.32 V	224	82.15	4.05
2	*2441.00	62.1 AV	94.0	-31.9	1.32 V	224	58.05	4.05
3	4882.00	64.2 PK	74.0	-9.8	1.00 V	57	54.46	9.74
4	4882.00	40.1 AV	54.0	-13.9	1.00 V	57	30.36	9.74
5	7323.00	58.3 PK	74.0	-15.7	1.28 V	81	45.16	13.14
6	7323.00	34.2 AV	54.0	-19.8	1.28 V	81	21.06	13.14

REMARKS:

- 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.
- 5. " * ": Fundamental frequency.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



BUREAU Test Report No.: RF150108N011-2

CHANNEL	TX High Channel	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M							
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2476.00	91.6 PK	114.0	-22.4	1.00 H	217	87.44	4.16
2	*2476.00	63.5 AV	94.0	-30.5	1.00 H	217	59.34	4.16
3	2483.50	42.5 PK	74.0	-31.5	1.00 H	217	38.32	4.18
4	2483.50	18.4 AV	54.0	-35.6	1.00 H	217	14.22	4.18
5	4952.00	62.2 PK	74.0	-11.8	1.04 H	22	52.35	9.85
6	4952.00	38.1 AV	54.0	-15.9	1.04 H	22	28.25	9.85
7	7428.00	56.8 PK	74.0	-17.2	1.12 H	311	43.66	13.14
8	7428.00	32.7 AV	54.0	-21.3	1.12 H	311	19.56	13.14
		ANTENNA	POLARITY	& TEST DI	STANCE: V	ERTICAL A	T 3 M	
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2476.00	80.3 PK	114.0	-33.7	1.04 V	19	76.14	4.16
2	*2476.00	56.2 AV	94.0	-37.8	1.04 V	19	52.04	4.16
3	2483.50	42.9 PK	74.0	-31.1	1.04 V	19	38.72	4.18
4	2483.50	18.8 AV	54.0	-35.2	1.04 V	19	14.62	4.18
5	4952.00	58.6 PK	74.0	-15.4	1.42 V	124	48.75	9.85
6	4952.00	34.5 AV	54.0	-19.5	1.42 V	124	24.65	9.85
	7428.00	56.3 PK	74.0	-17.7	1.00 V	14	43.16	13.14
7	7420.00	30.3 PK	74.0	-17.7	1.00 V	14	43.10	10.14

REMARKS:

- 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.
- 5. " * ": Fundamental frequency.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



4.3 20dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 20dB BANDWIDTH MEASUREMENT

According to FCC 15.215(c), must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.3.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Spectrum Analyzer (10Hz–40GHz)	Rohde&Schwarz	FSV40	101003	Apr. 09,14	Apr. 08,15
Power Meter	Anritsu	ML2495A	1139001	Feb. 21,14	Feb. 20,15
Power Sensor	Anritsu	MA2411B	1126068	Feb. 21,14	Feb. 20,15
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 27,14	Oct. 26,15
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.04,14	Sep. 03,15
Oscilloscope	Agilent	DSO9254A	MY51260160	Oct. 17, 14	Oct. 16, 15
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 05,14	Nov. 04,15

NOTE:

- 1. The test was performed in RF Oven room.
- 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

4.3.3 TEST PROCEDURE

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.


Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



4.3.4 DEVIATION FROM TEST STANDARD

No deviation.

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

- a) Turned on the power of all equipment.
- b) EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.


4.3.7 TEST RESULTS

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
Low	2402	0.318
Middle	2441	0.344
High	2476	0.327


Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



Test Data: Low channel




Test Data: Middle channel



Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



Test Data: High channel



Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



PHOTOGRAPHS OF THE TEST CONFIGURATION 5.

Please refer to the attached file (Test Setup Photo).

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



6. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---

Email: customerservice.dg@cn.bureauveritas.com

Tel: +86 769 8593 5656

Fax: +86 769 8593 1080

Page 26 of 26