

FCC PART 15.225

TEST REPORT

For

Advanced Card Systems Ltd.

Unit 2010-2013, 20th Floor, Chevalier Commercial Centre, 8 Wang Hoi Road, Kowloon Bay, Hong Kong

FCC ID: V5MACR35

Report Type: **Product Type:** Original Report Smart Card Reader (NFC Device) Simon wang **Test Engineer:** Simon Wang Report Number: RSZ140325009-00 **Report Date:** 2014-04-11 Jimmy Xiao Jimmy xiao **Reviewed By:** RF Engineer Bay Area Compliance Laboratories Corp. (Shenzhen) **Prepared By:** 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	
OBJECTIVE	3
RELATED SUBMITTAL(s)/GRANT(s)	
TEST METHODOLOGYTEST FACILITY	
SYSTEM TEST CONFIGURATION	
JUSTIFICATION	
EUT EXERCISE SOFTWARE	
EQUIPMENT MODIFICATIONSLOCAL SUPPORT EQUIPMENT	
EXTERNAL I/O CABLE.	
BLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	6
FCC§15.203 - ANTENNA REQUIREMENT	7
APPLICABLE STANDARD	7
Antenna Connected Construction	7
FCC §15.207 – AC LINE CONDUCTED EMISSION	8
APPLICABLE STANDARD	
Measurement Uncertainty	
EUT SETUP	
EMI TEST RECEIVER SETUP.	
TEST EQUIPMENT LIST AND DETAILS	
TEST PROCEDURE	
TEST RESULTS SUMMARY	10
TEST DATA	
FCC§15.225, §15.205 & §15.209 - RADIATED EMISSIONS TEST	13
APPLICABLE STANDARD	
Measurement Uncertainty	
EUT SETUP	13
EMI TEST RECEIVER SETUP	14
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST EQUIPMENT LIST AND DETAILS TEST RESULTS SUMMARY	
TEST DATA	
FCC§15.225(E) - FREQUENCY STABILITY	
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	
§15.215(C) - 20DB EMISSION BANDWIDTH TESTING	19
REQUIREMENT	
TEST EQUIPMENT LIST AND DETAILS	
TEST PROCEDURE	
LENTIDATA	19

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The Advanced Card Systems Ltd.'s product, model number: ACR35 (FCC ID: V5MACR35) the "EUT" in this report is a smart card reader named ACR35 by applicant. The EUT was measured approximately: 60 mm (L) x 42 mm (W) x 13 mm (H). Rated input voltage: Li-ion battery DC 3.7V.

Report No.: RSZ140325009-00

* All measurement and test data in this report was gathered from production sample serial number: RR291-000023 (Assigned by the applicant). The EUT supplied by applicant was received on 2014-03-25.

Objective

This Type approval report is prepared on behalf of *Advanced Card Systems Ltd.* in accordance with Part 2-Subpart J, and Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The objective is to determine the compliance of the EUT with FCC rules, sec 15.203, 15.205, 15.207, 15.209 and 15.225.

Related Submittal(s)/Grant(s)

No Related Submittals.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Lab Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with radiated emission is 5.91 dB for 30MHz-1GHz.and 4.92 dB for above 1GHz, 1.95dB for conducted measurement.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp.(Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FCC Part 15.225 Page 3 of 20

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).

Report No.: RSZ140325009-00

EUT Exercise Software

ACR35 V1.03

Equipment Modifications

No modification on the EUT.

Local Support Equipment


Manufacturer	Description	Model	Serial Number
DELL	PC	DCSCSF	127BPX2
DELL	Monitor	E178WFPC	CN-OWY564-64180-7C4-2SQH
ECOM	Modem	5600pbs	1074256
DELL	Mouse	MOC5UO	G1B0096D
DELL	Keyboard	L100 CNORH656658907BL04T	
Advanced	Test Card	N/A	1403120
Apple	IPad	IPad mini	30-00021

External I/O Cable

Cable Description	Length (m)	From/Port	То
Unshielded Detachable AC Cable	1.0	Main	Monitor
Unshielded Detachable AC Cable	1.0	Main	PC
Shielded Detachable VGA Cable	1.5	Monitor	PC
Unshielded Detachable RS232 Cable	1.5	Modem	PC
Unshielded Undetachable DC Cable	1.0	Modem	Adapter
Unshielded Detachable AC Cable	1.0	Adapter	Main
Shielded Undetachable K/B Cable	1.5	Keyboard	PC
Shielded Undetachable Mouse Cable	1.5	Mouse	PC
Shielded Detachable USB Cable	0.8	EUT	PC

FCC Part 15.225 Page 4 of 20

Block Diagram of Test Setup



Smart Card

EUT

FCC Part 15.225 Page 5 of 20

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207	AC Line Conducted Emission	Compliance
\$15.225 \$15.209 \$15.205	Radiated Emission Test	Compliance
§15.225(e)	Frequency Stability	Compliance
§15.215(c)	20dB Emission Bandwidth Testing	Compliance

Report No.: RSZ140325009-00

FCC Part 15.225 Page 6 of 20

FCC§15.203 - ANTENNA REQUIREMENT

Applicable Standard

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Report No.: RSZ140325009-00

Antenna Connected Construction

The EUT has a printed antenna on PCB, which was permanently attached, the antenna gain is 0 dBi, fulfill the requirement of this section. Please see EUT photo for details.

FCC Part 15.225 Page 7 of 20

FCC §15.207 – AC LINE CONDUCTED EMISSION

Applicable Standard

FCC§15.207

Measurement Uncertainty


Input quantities to be considered for conducted disturbance measurements maybe receiver reading, attenuation of the connection between LISN and receiver, LISN voltage division factor, LISN VDF frequency interpolation and receiver related input quantities, etc.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of conducted disturbance test at Bay Area Compliance Laboratories Corp. (Shenzhen) is shown as below. And the uncertainty will not be taken into consideration for the test data recorded in the report

Report No.: RSZ140325009-00

Port	Expanded Measurement uncertainty
AC Mains	3.26 dB (k=2, 95% level of confidence)
CAT 3	3.70 dB (k=2, 95% level of confidence)
CAT 5	3.86 dB (k=2, 95% level of confidence)
CAT 6	4.64 dB (k=2, 95% level of confidence)

EUT Setup



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

FCC Part 15.225 Page 8 of 20

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.207.

Report No.: RSZ140325009-00

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The host PC was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2013-06-17	2014-06-17
Rohde & Schwarz	1st LISN	ENV216	3560.6650.12- 101613-Yb	2013-05-07	2014-05-07
Rohde & Schwarz	2nd LISN	ESH2-Z5	892107/021	2013-08-22	2014-08-22
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2013-10-15	2014-10-15
Rohde & Schwarz	CE Test software	EMC 32	V8.53	-	-

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Procedure

During the conducted emission test, the host PC was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

FCC Part 15.225 Page 9 of 20

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Correction Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Report No.: RSZ140325009-00

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the <u>FCC Part 15.207</u>, the worst margin reading as below:

8.3 dB at 8.849310 MHz in the Neutral conducted mode

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

in BACL., $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	22 ℃
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa

The testing was performed by Simon Wang on 2014-04-01.


Test Mode: Transmitting & Charging

FCC Part 15.225

AC 120V/60 Hz, Line:

EMI Auto Test L

Report No.: RSZ140325009-00




Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.201500	43.2	19.6	63.5	20.3	QP
0.201500	42.2	19.6	53.5	11.3	Ave.
0.301470	40.0	19.4	60.2	20.2	QP
0.301470	36.5	19.4	50.2	13.7	Ave.
1.105410	36.3	19.5	56.0	19.7	QP
1.105410	34.7	19.5	46.0	11.3	Ave.
8.447310	38.7	19.7	60.0	21.3	QP
8.447310	37.9	19.7	50.0	12.1	Ave.
8.847750	39.1	19.7	60.0	20.9	QP
8.847750	38.2	19.7	50.0	11.8	Ave.
9.349690	38.5	19.7	60.0	21.5	QP
9.349690	37.2	19.7	50.0	12.8	Ave.

FCC Part 15.225 Page 11 of 20

AC 120V/60 Hz, Neutral

EMI Auto Test N

Report No.: RSZ140325009-00



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.604970	35.8	19.6	56.0	20.2	QP
0.604970	35.6	19.6	46.0	10.4	Ave.
1.006850	35.3	19.5	56.0	20.7	QP
1.006850	34.5	19.5	46.0	11.5	Ave.
1.105410	37.8	19.5	56.0	18.2	QP
1.105410	37.2	19.5	46.0	8.8	Ave.
8.041250	39.5	19.8	60.0	20.5	QP
8.041250	37.4	19.8	50.0	12.6	Ave.
8.849310	42.4	19.8	60.0	17.6	QP
8.849310	41.7	19.8	50.0	8.3	Ave.
9.249690	41.8	19.8	60.0	18.2	QP
9.249690	40.8	19.8	50.0	9.2	Ave.

1) Correction Factor =LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation The corrected factor has been input into the transducer of the test software.

2) Corrected Amplitude = Reading + Correction Factor

3) Margin = Limit - Corrected Amplitude

FCC Part 15.225 Page 12 of 20

FCC§15.225, §15.205 & §15.209 - RADIATED EMISSIONS TEST

Applicable Standard

As per FCC Part 15.225

- (a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.
- (b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

Report No.: RSZ140325009-00


- (c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.
- (d) The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in $\S15.209$.

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Shenzhen) is 5.91 dB for 30MHz-1GHz.and 4.92 dB for above 1GHz. And it will not be taken into consideration for the test data recorded in the report

EUT Setup



FCC Part 15.225 Page 13 of 20

The radiated emission tests were performed in the 3-meter chamber a test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC Part Subpart C limits.

Report No.: RSZ140325009-00

The spacing between the peripherals was 10 cm.

The host PC was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

According to FCC Rules, 47 CFR 15.33, the EUT emissions were investigated up to 1000 MHz.

During the radiated emission test, the EMI test Receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
9 kHz – 150 kHz	300 Hz	1 kHz	/	QP
150 kHz –30 MHz	10 kHz	30 kHz	/	QP
30 MHz – 1000 MHz	100 kHz	300 kHz	/	QP

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Factor = Antenna Factor + Cable Loss- Amplifier Gain Corrected Amplitude = Meter Reading + Corrected Factor

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2013-09-17	2014-09-17
HP	Amplifier	8447E	1937A01046	2013-09-30	2014-09-30
Sunol Sciences	Bi-log Antenna	JB1	A040904-2	2011-11-28	2014-11-27
ETS	Passive Loop Antenna	6512	00029604	2011-11-30	2014-11-29

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC Part 15.225 Page 14 of 20

Test Results Summary

According to the data in the following table, the EUT complied with the <u>FCC Part 15.209</u>, the worst margin reading as below:

14.12 dB at 165.955625 MHz in the Horizontal polarization

Report No.: RSZ140325009-00

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	22 ℃
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa

The testing was performed by Simon Wang on 2014-04-01.

Test mode: Transmitting & Charging

FCC Part 15.225 Page 15 of 20

1) Spurious Emissions (9 kHz~30 MHz):

Indicated				Corre	ection Fa	ctor	Corrected	FCC P 15.225\1:	
Frequency (MHz)	Table Angle Degree	Antenna Height (m)	Detector PK/QP/Ave.	Ant. Factor (dB)	Cable Loss (dB)	Pre- Amp. Gain (dB)	Amplitude (dBµV/m) @3m	Limit (dBµV/m) @3m	Result
0.138	156	1.1	QP	64.6	0.21	0	65.33	104.81	Pass
27.61	61	1.1	QP	30.5	0.21	0	38.31	69.54	Pass

Report No.: RSZ140325009-00

2) Fundamental:

Indicat	ed				Corre	ection Fa	ctor	Corrected	FCC Part	15.225
Frequency Range (MHz)	Mark point (MHz)	Table Angle Degree	Antenna Height (m)	Detector PK/QP/Ave.	Ant. Factor (dB)	Cable Loss (dB)	Pre- Amp. Gain (dB)	Amplitude (dBµV/m) @3m	Limit (dBµV/m) @3m	Result
13.110-13.410	13.302	0	1.2	QP	32.1	0.21	0	41.25	80.5	Pass
13.410-13.553	13.552	0	1.2	QP	32.1	0.21	0	50.00	90.5	Pass
13.553-13.567	13.558	0	1.2	QP	32.1	0.21	0	66.51	124	Pass
13.567-13.710	13.568	0	1.2	QP	32.1	0.21	0	47.19	90.5	Pass
13.710-14.010	13.896	0	1.2	QP	32.1	0.21	0	41.07	80.5	Pass

3) Spurious Emissions (30 MHz ~1 GHz):

Frequency (MHz)	Corrected Amplitude (dBµV/m)	Detector PK/QP/Ave.	Antenna Height (m)	Antenna Polarity (H/V)	Turntable Position (deg)	Correction Factor (dB)	Limit (dBµV/m)	Margin (dB)
121.182500	23.72	QP	1.3	Н	52.0	-13.3	43.5	19.78
165.955625	29.38	QP	1.2	Н	39.0	-14.9	43.5	14.12
299.815750	28.55	QP	1.4	V	256.0	-13.0	46	17.45
398.212000	26.69	QP	1.2	Н	187.0	-11.2	46	19.31

FCC Part 15.225 Page 16 of 20

FCC§15.225(e) - FREQUENCY STABILITY

Applicable Standard

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

Report No.: RSZ140325009-00

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to PC, then to an external AC power supply and inductive antenna was connected to a Spectrum Analyzer. The EUT was placed inside the temperature chamber.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the Spectrum Analyzer.

Frequency Stability vs. Voltage: An external variable AC power supply Source. The voltage was set to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the end point. The output frequency was recorded for each voltage.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2013-09-17	2014-09-17
ESPEC	Temperature & Humidity Chamber	EL-10KA	09107726	2013-11-01	2014-11-01

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	22 ℃
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa

The testing was performed by Simon Wang on 2014-04-04.

Test Mode: Transmitting

Test Result: Pass

FCC Part 15.225 Page 17 of 20

Power Supply	Temperature (°C)	Measured Frequency (MHz)	Frequency Error	Part 15.225 Limit
	-20	13.56069	-0.0051%	±0.01%
	-10	13.56075	-0.0055%	±0.01%
	0	13.56070	-0.0052%	±0.01%
3.7V	10	13.56072	-0.0053%	±0.01%
3./V	20	13.56074	-0.0055%	±0.01%
	30	13.56071	-0.0052%	±0.01%
	40	13.56075	-0.0055%	±0.01%
	50	13.56056	-0.0041%	±0.01%
3.2V	20	13.56070	-0.0052%	±0.01%

Report No.: RSZ140325009-00

FCC Part 15.225 Page 18 of 20

§15.215(c) - 20dB EMISSION BANDWIDTH TESTING

Requirement

Per 15.215 (c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

Report No.: RSZ140325009-00

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2013-09-17	2014-09-17
ETS	Passive Loop Antenna	6512	00029604	2011-11-30	2014-11-29

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.

Test Data

Environmental Conditions

Temperature:	22 ℃
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa

The testing was performed by Simon Wang on 2014-04-01.


Test Mode: Transmitting

Test Result: Pass

FCC Part 15.225 Page 19 of 20

20 dB Emission Bandwidth

Report No.: RSZ140325009-00



EUT
Date: 1.APR.2014 23:27:48

***** END OF REPORT *****

FCC Part 15.225 Page 20 of 20