



# FCC TEST REPORT

**Product Name:** Smart Payment Terminal  
**Trade Mark:** PAX  
**Model No.:** A30  
**Report Number:** 25070818938RFC-5  
**Test Standards:** FCC 47 CFR Part 15 Subpart C  
**FCC ID:** V5PA30  
**Test Result:** PASS  
**Date of Issue:** August 14, 2025

Prepared for:

**PAX Technology Limited**  
**Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour Road, Wanchai,**  
**Hong Kong**

Prepared by:

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**  
**16/F, Block A, Building 6th, Baoneng Science and Technology Park,**  
**Longhua Street, Longhua District, Shenzhen, China**

**TEL: +86-755-2823 0888**

**FAX: +86-755-2823 0886**

Prepared by:

*David Chen*  
David Chen  
Senior Project Engineer

Reviewed by:

*Henry Lu*  
Henry Lu  
Team Leader

Approved by:

*KL*  
Kevin Liang  
Assistant Manager

Date: August 14, 2025

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.225-V1.1

**Version**

Version No.	Date	Description
V1.0	August 14, 2025	Original

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.225-V1.1

## CONTENTS

<b>1. GENERAL INFORMATION .....</b>	<b>4</b>
1.1 CLIENT INFORMATION .....	4
1.2 EUT INFORMATION .....	4
1.2.1 GENERAL DESCRIPTION OF EUT .....	4
1.2.2 DESCRIPTION OF ACCESSORIES.....	4
1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	5
1.4 OTHER INFORMATION.....	5
1.5 DESCRIPTION OF SUPPORT UNITS .....	5
1.6 TEST LOCATION.....	5
1.7 TEST FACILITY.....	6
1.8 DEVIATION FROM STANDARDS .....	6
1.9 ABNORMALITIES FROM STANDARD CONDITIONS.....	6
1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER .....	6
1.11 MEASUREMENT UNCERTAINTY .....	6
<b>2. TEST SUMMARY .....</b>	<b>7</b>
<b>3. EQUIPMENT LIST .....</b>	<b>8</b>
<b>4. TEST CONFIGURATION .....</b>	<b>9</b>
4.1 ENVIRONMENTAL CONDITIONS FOR TESTING .....	9
4.1.1 NORMAL OR EXTREME TEST CONDITIONS .....	9
4.1.2 RECORD OF NORMAL ENVIRONMENT AND TEST SAMPLE .....	9
4.2 TEST CHANNELS .....	9
4.3 EUT TEST STATUS .....	9
4.4 PRE-SCAN .....	10
4.5 TEST SETUP .....	11
4.5.1 FOR RADIATED EMISSIONS TEST SETUP.....	11
4.5.2 FOR CONDUCTED EMISSIONS TEST SETUP .....	12
4.5.3 FOR CONDUCTED RF TEST SETUP .....	12
4.6 SYSTEM TEST CONFIGURATION .....	14
<b>5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION .....</b>	<b>15</b>
5.1 REFERENCE DOCUMENTS FOR TESTING .....	15
5.2 ANTENNA REQUIREMENT .....	15
5.3 20DB BANDWIDTH .....	15
5.4 THE FIELD STRENGTH OF ANY EMISSIONS APPEARING OUTSIDE OF THE 13.110-14.010 MHZ BAND.....	17
5.5 FUNDAMENTAL FIELD STRENGTH AND EMISSION MASK 13.110 MHz TO 14.010 MHz .....	21
5.6 FREQUENCY TOLERANCE .....	23
5.7 CONDUCTED EMISSION .....	24
<b>APPENDIX 1 PHOTOS OF TEST SETUP .....</b>	<b>29</b>
<b>APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS.....</b>	<b>29</b>

## 1. GENERAL INFORMATION

### 1.1 CLIENT INFORMATION

<b>Applicant:</b>	PAX Technology Limited
<b>Address of Applicant:</b>	Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour Road, Wanchai, Hong Kong
<b>Manufacturer:</b>	PAX Computer Technology (Shenzhen) Co., Ltd.
<b>Address of Manufacturer:</b>	Room 701, PAX Technology Building, Shanxia Community, Pinghu Sub-district, Longgang District, Shenzhen, China

### 1.2 EUT INFORMATION

#### 1.2.1 General Description of EUT

<b>Product Name:</b>	Smart Payment Terminal				
<b>Model No.:</b>	A30				
<b>Trade Mark:</b>	PAX				
<b>DUT Stage:</b>	Identical Prototype				
<b>EUT Supports Function:</b> (Provided by the customer)	<b>GSM Bands:</b>	GSM850 / P-GSM 900 / DCS 1800			
	<b>UTRA Bands:</b>	WCDMA Band II/ IV / V / VIII			
	<b>E-UTRA Bands:</b>	FDD Band 2/ 4/ 5/ 7/ 8/ 28/ 66			
		TDD Band 41			
	<b>2.4 GHz ISM Band:</b>	IEEE 802.11b/g/n			
		Bluetooth 5.0			
	<b>5 GHz U-NII Bands:</b>	5 150 to 5 250 MHz	IEEE 802.11a/n/ac		
		5 250 to 5 350 MHz	IEEE 802.11a/n/ac		
		5 470 to 5 725 MHz	IEEE 802.11a/n/ac		
		5 725 to 5 850 MHz	IEEE 802.11a/n/ac		
	<b>RNSS Bands:</b>	1559-1610 MHz	BDS/ Galileo/ GLONASS/ GPS/ SBAS		
	<b>NFC:</b>	13.553 MHz to 13.567 MHz			
<b>Sample Received Date:</b>	July 8, 2025				
<b>Sample Tested Date:</b>	July 17, 2025 to August 6, 2025				
<b>Remark:</b> The above EUT's information was provided by customer. Please refer to the specifications or user's manual for more detailed description.					

#### 1.2.2 Description of Accessories

Adapter	
<b>Model No.:</b>	SW-0396A
<b>Input:</b>	100-240V~50/60Hz 0.5A
<b>Output:</b>	9.0V---1.0A

### 1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

Frequency Range:	13.110 MHz to 14.010 MHz
Nominal Operating Frequency:	13.56 MHz
Work in Modes:	<input type="checkbox"/> Card Emulation
	<input checked="" type="checkbox"/> Reader/Writer
	<input type="checkbox"/> Peer-to-Peer
NFC Type:	<input checked="" type="checkbox"/> NFC A Type
	<input checked="" type="checkbox"/> NFC B Type
	<input checked="" type="checkbox"/> NFC M Type
	<input type="checkbox"/> NFC V Type
Max. Data Rates:	848 Kbps
Type of Modulation:	ASK
Number of Channels:	1
Antenna Type:	Loop Antenna
Maximum Field Strength:	69.52 dB $\mu$ V/m at 3 meter
Normal Test Voltage:	9.0 VDC and 120V~60Hz
Extreme Test Voltage:	8.75 to 9.25 Vac
Extreme Test Temperature:	-20 °C to +55 °C

### 1.4 OTHER INFORMATION

None

### 1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested independently

### 1.6 TEST LOCATION

---

#### Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Telephone: +86 (0) 755 2823 0888

Fax: +86 (0) 755 2823 0886

---

#### Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.225-V1.1

## 1.7 TEST FACILITY

---

The test facility is recognized, certified, or accredited by the following organizations:

### **CNAS-Lab Code: L9069**

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

### **A2LA-Lab Certificate No.: 4312.01**

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

### **ISED Wireless Device Testing Laboratories**

CAB identifier: CN0032

### **FCC Accredited Lab.**

Designation Number: CN1194

Test Firm Registration Number: 259480

---

## 1.8 DEVIATION FROM STANDARDS

None.

## 1.9 ABNORMALITIES FROM STANDARD CONDITIONS

None.

## 1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

## 1.11 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9kHz-150kHz	±3.2 dB
2	Conducted emission 150kHz-30MHz	±2.7 dB
3	Radiated emission 9kHz-30MHz	±4.7 dB
4	Radiated emission 30MHz-1GHz	±4.6 dB
5	Radiated emission 1GHz-18GHz	±4.4 dB
6	Radiated emission 18GHz-40GHz	±4.6 dB
7	Occupied Bandwidth	± 1.86 %
8	Radio Frequency	± 7 x 10 <sup>-8</sup>

## **Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.225-V1.1

## 2. TEST SUMMARY

FCC 47 CFR Part 15 Subpart C Test Cases			
Test Item	Test Requirement	Test Method	Result
<b>Antenna Requirement</b>	FCC 47 CFR Part 15 Subpart C Section 15.203	N/A	PASS
<b>Conducted Emission</b>	FCC 47 CFR Part 15 Subpart C Section 15.207	ANSI C63.10-2013	PASS
<b>The field strength of any emissions appearing outside of the 13.110-14.010 MHz band</b>	FCC 47 CFR Part 15 Subpart C Section 15.225(d) /15.209	ANSI C63.10-2013	PASS
<b>Fundamental Field Strength and Emission Mask 13.110 MHz to 14.010 MHz</b>	FCC 47 CFR Part 15 Subpart C Section 15.227(a) (b) (c) /15.205	ANSI C63.10-2013	PASS
<b>20DB Bandwidth</b>	FCC 47 CFR Part 15 Subpart C Section 15.215(c)	ANSI C63.10-2013	PASS
<b>Frequency Tolerance</b>	FCC 47 CFR Part 15 Subpart C Section 15.225(e)	ANSI C63.10-2013	PASS

**Disclaimer and Explanations:**  
The declared of product specification and data (e.g., antenna gain, RF specification, etc) for EUT presented in the report are provided by the customer, and the customer takes all the responsibilities for the accuracy of product specification.

### 3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
<input checked="" type="checkbox"/>	3m SAC	ETS-LINDGREN	3M	Euroshiedpn-CT001270-1317	11-Nov-2023	10-Nov-2026
<input checked="" type="checkbox"/>	Receiver	R&S	ESIB26	100114	25-Oct-2024	24-Oct-2025
<input checked="" type="checkbox"/>	Loop Antenna	ETS-LINDGREN	6502	00202525	28-Oct-2024	27-Oct-2025
<input checked="" type="checkbox"/>	Broadband Antenna	ETS-LINDGREN	3142E	00201566	29-Oct-2024	28-Oct-2025
<input checked="" type="checkbox"/>	6dB Attenuator	Talent	RA6A5-N-18	18103001	29-Oct-2024	28-Oct-2025
<input checked="" type="checkbox"/>	Preamplifier	HP	8447F	2805A02960	25-Oct-2024	24-Oct-2025
<input checked="" type="checkbox"/>	Pre-amplifier	ETS-LINDGREN	00118384	00202652	28-Oct-2024	27-Oct-2025
<input checked="" type="checkbox"/>	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
<input checked="" type="checkbox"/>	Test Software	Audix	e3	Software Version: 9.160323		

Conducted Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
<input checked="" type="checkbox"/>	Receiver	R&S	ESCI3	1166.5950.03	25-Oct-2024	24-Oct-2025
<input checked="" type="checkbox"/>	LISN	R&S	EVN216	3560.6550.12	26-Sep-2024	25-Sep-2025
<input type="checkbox"/>	LISN	ETS-Lindgren	3816/2SH	00201088	25-Oct-2024	24-Oct-2025
<input checked="" type="checkbox"/>	Test Software	EZ-EMC	EZ-CON	Software Version: EMC-CON 3A1.1		

RF Conducted Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
<input checked="" type="checkbox"/>	Spectrum analyzer	R&S	FSV40-N	101653	28-Mar-2025	27-Mar-2026
<input checked="" type="checkbox"/>	Loop Antenna	ETS-LINDGREN	6502	00202525	28-Oct-2024	27-Oct-2025
<input checked="" type="checkbox"/>	DC Source	KIKUSUI	PWR400L	LK003024	19-Jul-2025	18-Jul-2026
<input checked="" type="checkbox"/>	Temp & Humidity chamber	Votisch	VT4002	58566133290020	28-Mar-2025	27-Mar-2026

## 4. TEST CONFIGURATION

### 4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

#### 4.1.1 Normal or Extreme Test Conditions

Test Environment	Selected Values During Tests		
	Ambient		
Test Condition	Temperature (°C)	Voltage (Vac)	Relative Humidity (%)
TN/VN	+15 to +35	9.0	20 to 75
TL/VL	-20	8.75	20 to 75
TH/VL	+55	8.75	20 to 75
TL/VH	-20	9.25	20 to 75
TH/VH	+55	9.25	20 to 75

**Remark:**

- 1) The EUT just work in such extreme temperature of -20 °C to +55 °C and the extreme voltage of 8.75 V to 9.25 V, so here the EUT is tested in the temperature of -20 °C to +55 °C and the voltage of 8.75 V to 9.25 V.
- 2) VN: Normal Voltage; TN: Normal Temperature;  
TL: Low Extreme Test Temperature; TH: High Extreme Test Temperature;  
VL: Low Extreme Test Voltage; VH: High Extreme Test Voltage.

#### 4.1.2 Record of Normal Environment and Test Sample

Test Item	Temp. (°C)	Relative Humidity (%)	Pressure (kPa)	Sample No.	Tested by
Conducted Emission	22.3	49.2	98.3	S202507086435-ZJA01/5	Linson Xie
The field strength of any emissions appearing outside of the 13.110-14.010 MHz band					
Fundamental Field Strength and Emission Mask 13.110 MHz to 14.010 MHz	24.5	58.4	99.2	S202507086435-ZJA05/5	Hank Wu
20DB Bandwidth					
Radiated Spurious Emissions	23.6	55.4	99.1	S202507086435-ZJA01/5	Leo Li

## 4.2 TEST CHANNELS

Frequency	Test RF Channel
13.56 MHz	Channel 1
	13.56 MHz

## 4.3 EUT TEST STATUS

Frequency	Tx Function	Description
13.56 MHz	1Tx	1. Keep the EUT in continuously transmitting during the test.

#### 4.4 PRE-SCAN



Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, work in modes and data rates. Selected for the final test as listed below.

Frequency	Work in Modes	Type	Data Rate (kbps)
13.56 MHz	<input type="checkbox"/> Card Emulation <input checked="" type="checkbox"/> Reader/Writer <input type="checkbox"/> Peer-to-Peer	<input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> F <input type="checkbox"/> V	<input checked="" type="checkbox"/> 106 <input type="checkbox"/> 212 <input type="checkbox"/> 424 <input type="checkbox"/> 848


**Remark:**  
The mark "" means is chosen for testing;  
The mark "" means is not chosen for testing.

## 4.5 TEST SETUP


### 4.5.1 For Radiated Emissions test setup




#### 4.5.2 For Conducted Emissions test setup



#### 4.5.3 For Conducted RF test setup





## 4.6 SYSTEM TEST CONFIGURATION

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, radiated emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario. It was powered by a 3.8Vdc rechargeable Li-on battery. Only the worst case data were recorded in this test report.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.



## 5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION

### 5.1 REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part 15	Radio Frequency Devices
2	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

### 5.2 ANTENNA REQUIREMENT

Standard Requirement
<b>15.203 requirement:</b> An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
<b>EUT Antenna:</b>
This product has a permanent antenna, fulfill the requirement of this section.

### 5.3 20DB BANDWIDTH

**Test Requirement:** FCC 47 CFR Part 15 Subpart C Section 15.215 (c)

**Test Method:** ANSI C63.10

**Limit:** Operation within the band 13.110 MHz to 14.010 MHz

**Requirement:** Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in subpart E of this part, must be designed to ensure that 20dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment complies with the 20dB attenuation specification may base on measurement at the intentional radiator's antenna output terminal unless the intentional radiator uses a permanently attached antenna, in which case compliance shall be. Demonstrated by measuring the radiated emissions.

**Test Procedure:** Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Use the following spectrum analyzer settings:

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency
- b) Span = approximately 2 to 5 times the OBW
- c) RBW = 1% to 5% of the OBW
- d) VBW  $\geq$  3\*RBW
- e) Sweep = auto;
- f) Detector function = peak
- g) Trace = max hold
- h) All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down bandwidth of the emission.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

**Test Setup:** Refer to section 4.5.3 for details.

**Instruments Used:** Refer to section 3 for details

**Test Mode:** Transmitter mode

**Test Results:** Pass

### Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886


E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.225-V1.1

Test Frequency	Reader Mode		Limit
	OBW (kHz)	20 dB BW (kHz)	
13.56 MHz_Type 1	543.0	27.0	Operation within the band 13.110 MHz to 14.010 MHz
13.56 MHz_Type 2	150.5	48.5	

The test plot as follows:



## 5.4 THE FIELD STRENGTH OF ANY EMISSIONS APPEARING OUTSIDE OF THE 13.110-14.010 MHZ BAND

**Test Requirement:** FCC 47 CFR Part 15 Subpart C Section 15.225(d) /15.209

**Test Method:** ANSI C63.10-2013 Section 6.6.4.3

### Receiver Setup:

Frequency	RBW
0.009 MHz-0.150 MHz	200/300 kHz
0.150 MHz -30 MHz	9/10 kHz
30 MHz-1 GHz	100/120 kHz
Above 1 GHz	1 MHz

### Limits:

The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in §15.209.

### Spurious Emissions

Frequency	Field strength (microvolt/meter)	Limit (dB $\mu$ V/m)	Remark	Measurement distance (m)
0.009 MHz-0.490 MHz	2400/F(kHz)	--	--	300
0.490 MHz-1.705 MHz	24000/F(kHz)	--	--	30
1.705 MHz-30 MHz	30	--	--	30
30 MHz-88 MHz	100	40.0	Quasi-peak	3
88 MHz-216 MHz	150	43.5	Quasi-peak	3
216 MHz-960 MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1 GHz	500	54.0	Average	3

### Remark:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB $\mu$ V/m) = 20 log Emission level ( $\mu$ V/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.
4. For Below 30MHz, the measured field strength was extrapolated to distance 30 meters, using the formula that the limit of field strength varies as the inverse distance square (40dB per decade of distance)

### Example:

$$\begin{aligned} \text{Field strength limit for 13.56MHz} &= 15848 \mu\text{V/m} && \text{at 30m} \\ &= 84 \text{ dB}\mu\text{V/m} && \text{at 30m} \\ &= 84 \text{ dB}\mu\text{V/m} + 40\log(30/3) \text{ dB} && \text{at 3m} \\ &= 124 \text{ dB}\mu\text{V/m} && \text{at 3m} \end{aligned}$$

**Test Setup:** Refer to section 4.5.1 for details.

### Test Procedures:

- 1) The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- 3) The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rota table table was turned from 0 degrees to 360 degrees to find the maximum reading.

### Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.225-V1.1


- 5) The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- 6) If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- 7) The radiation measurements are performed in X, Y, Z axis positioning. And found the Y axis positioning which it is worse case, only the test worst case mode is recorded in the report.(for portable and mobile devices)

**Equipment Used:** Refer to section 3 for details.


**Test Result:** Pass


#### Radiated Emission Test Data (9 kHz ~ 30 MHz):

##### Horizontal



No.	Frequency (MHz)	Reading (dB $\mu$ V)	Correction factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Detector
1	0.012	71.53	-11.91	59.62	126.37	-66.75	Peak
2	0.013	71.65	-12.12	59.53	125.82	-66.29	Peak
3	0.015	72.38	-12.68	59.70	124.53	-64.83	Peak
4	0.514	66.05	-18.39	47.66	73.39	-25.73	Peak
5	0.609	64.85	-18.39	46.46	71.91	-25.45	Peak
6	0.738	63.30	-18.39	44.91	70.26	-25.35	Peak
7	0.012	71.53	-11.91	59.62	126.37	-66.75	Peak





Remark:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result – Limit

## 5.5 FUNDAMENTAL FIELD STRENGTH AND EMISSION MASK 13.110 MHZ TO 14.010 MHZ

**Test Requirement:** FCC 47 CFR Part 15 Subpart C Section 15.227(a) (b) (c) /15.205

**Test Method:** ANSI C63.10

**Limits:**

- (a) The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.
- (b) Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
- (c) Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

**Remark:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level ( $\text{dB}\mu\text{V}/\text{m}$ ) = 20 log Emission level ( $\mu\text{V}/\text{m}$ ).
3. For Below 30MHz, the measured field strength was extrapolated to distance 30 meters, using the formula that the limit of field strength varies as the inverse distance square (40dB per decade of distance)

**Example:**

$$\begin{aligned}\text{Field strength limit for 13.56MHz} &= 15848 \mu\text{V}/\text{m} && \text{at 30m} \\ &= 84 \text{ dB}\mu\text{V}/\text{m} && \text{at 30m} \\ &= 84 \text{ dB}\mu\text{V}/\text{m} + 40\log(30/3) \text{ dB} && \text{at 3m} \\ &= 124 \text{ dB}\mu\text{V}/\text{m} && \text{at 3m}\end{aligned}$$

**Test Setup:** Refer to section 4.5.1 for details.

**Test Procedures:**

As the radiation test, set the RBW=10kHz VBW=30kHz, observed the outside band of 13.110 MHz to 14.010 MHz, than mark the higher-level emission for comparing with the FCC rules.

**Equipment Used:** Refer to section 3 for details.


**Test Result:** Pass

**Maximum Field Strength:**

Fundamental frequency	Detector	Result at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
13.56 MHz	Peak	69.52	124	-54.48

**Emission Mask:**

The worst-case test plots as below.



## 5.6 FREQUENCY TOLERANCE

**Test Requirement:** FCC 47 CFR Part 15 Subpart C Section 15.225(e)

**Test Method:** ANSI C63.10-2013

**Limits:**

The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  of the operating frequency over a temperature variation of -20 degrees to + 50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

**Test Setup:** Refer to section 4.5.3 for details.

**Test Procedures:**

- 1) The EUT was placed inside the environmental test chamber and powered by nominal DC voltage.
- 2) Turn the EUT on and couple its output to a spectrum analyzer.
- 3) Turn the EUT off and set the chamber to the highest temperature specified.
- 4) Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
- 5) Repeat step c) and d) with the temperature chamber set to the lowest temperature.
- 6) The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

**Equipment Used:** Refer to section 3 for details.

**Test Result:** Pass

Temp.(°C)	Voltage	Frequency Tolerance VS Temperature and Voltage							
		Test time (minutes)							
		0	2	5	10	0	2	5	10
Measured Frequency (MHz)									
50	VN	13.5602460	13.5602445	13.5602425	13.5602415	0.0018%	0.0018%	0.0018%	0.0018%
40	VN	13.5602457	13.5602448	13.5602421	13.5602412	0.0018%	0.0018%	0.0018%	0.0018%
30	VN	13.5602455	13.5602444	13.5602418	13.5602411	0.0018%	0.0018%	0.0018%	0.0018%
20	VN	13.5602456	13.5602442	13.5602419	13.5602410	0.0018%	0.0018%	0.0018%	0.0018%
	VL	13.5602453	13.5602441	13.5602417	13.5602408	0.0018%	0.0018%	0.0018%	0.0018%
	VH	13.5602451	13.5602446	13.5602418	13.5602409	0.0018%	0.0018%	0.0018%	0.0018%
10	VN	13.5602457	13.5602443	13.5602416	13.5602413	0.0018%	0.0018%	0.0018%	0.0018%
0	VN	13.5602458	13.5602442	13.5602419	13.5602411	0.0018%	0.0018%	0.0018%	0.0018%
-10	VN	13.5602456	13.5602441	13.5602418	13.5602404	0.0018%	0.0018%	0.0018%	0.0018%
-20	VN	13.5602453	13.5602440	13.5602417	13.5602407	0.0018%	0.0018%	0.0018%	0.0018%

**Limit:**  $\pm 0.01\%$

## 5.7 CONDUCTED EMISSION

**Test Requirement:** FCC 47 CFR Part 15 Subpart C Section 15.207

**Test Method:** ANSI C63.10-2013 Section 6.2

**Limits:**

Frequency range (MHz)	Limits (dB(μV))	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

**Remark:**

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz.

**Test Setup:** Refer to section 4.5.2 for details.

**Test Procedures:**

Test frequency range :150KHz-30MHz

- 7) The mains terminal disturbance voltage test was conducted in a shielded room.
- 8) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a  $50\Omega/50\mu\text{H} + 5\Omega$  linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 9) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 10) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 11) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

**Equipment Used:** Refer to section 3 for details.


**Test Result:** Pass

The measurement data as follows:


Quasi Peak and Average:

Mode: NFC (With Antenna)

Live Line




No.	Frequency (MHz)	Reading (dB $\mu$ V)	Correction factor(dB)	Result (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Detector
1	0.1590	33.87	9.83	43.70	65.52	-21.82	QP
2	0.1590	17.84	9.83	27.67	55.52	-27.85	AVG
3	0.4560	22.77	9.80	32.57	56.77	-24.20	QP
4	0.4560	12.14	9.80	21.94	46.77	-24.83	AVG
5	0.5639	26.51	9.79	36.30	56.00	-19.70	QP
6	0.5639	17.56	9.79	27.35	46.00	-18.65	AVG
7	18.2443	28.50	9.88	38.38	60.00	-21.62	QP
8	18.2443	20.79	9.88	30.67	50.00	-19.33	AVG
9	23.1270	33.40	9.90	43.30	60.00	-16.70	QP
10	23.1270	27.42	9.90	37.32	50.00	-12.68	AVG
11	26.6100	31.76	9.89	41.65	60.00	-18.35	QP
12	26.6100	26.96	9.89	36.85	50.00	-13.15	AVG




**Quasi Peak and Average:  
Mode: NFC (With Simulates the antenna)**

**Live Line**



No.	Frequency (MHz)	Reading (dB $\mu$ V)	Correction factor(dB)	Result (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Detector
1	0.1680	36.67	9.79	46.46	65.06	-18.60	QP
2	0.1680	14.30	9.79	24.09	55.06	-30.97	AVG
3	0.2084	34.46	9.80	44.26	63.27	-19.01	QP
4	0.2084	13.30	9.80	23.10	53.27	-30.17	AVG
5	0.3570	31.59	9.77	41.36	58.80	-17.44	QP
6	0.3570	4.79	9.77	14.56	48.80	-34.24	AVG
7	18.2443	27.28	9.88	37.16	60.00	-22.84	QP
8	18.2443	21.43	9.88	31.31	50.00	-18.69	AVG
9	23.1270	34.22	9.90	44.12	60.00	-15.88	QP
10	23.1270	26.77	9.90	36.67	50.00	-13.33	AVG
11	26.4884	31.41	9.89	41.30	60.00	-18.70	QP
12	26.4884	26.01	9.89	35.90	50.00	-14.10	AVG


**Remark:**

1. Correct Factor = LISN Factor + Cable Loss + Pulse Limiter Factor, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result - Limit
4. An initial pre-scan was performed on the Phase and neutral lines with peak detector. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.
5. All possible modes of operation were investigated, and testing at two nominal voltages of 240V~50Hz and 120V~60Hz, only the worst case emissions reported.

## APPENDIX 1 PHOTOS OF TEST SETUP

See test photos attached in Appendix 1 for the actual connections between Product and support equipment.

## APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal photos.

\*\*\* End of Report \*\*\*

---

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.

---