



FCC RF Test Report

APPLICANT : PAX Technology Limited
EQUIPMENT : Smart Payment Terminal
BRAND NAME : PAX
MODEL NAME : A30
FCC ID : V5PA30BW
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Apr. 02, 2020 and testing was completed on Jun. 03, 2020. We, Sporton International (ShenZhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (ShenZhen) Inc., the test report shall not be reproduced except in full.

Reviewed by: Derreck Chen / Supervisor

Approved by: Eric Shih / Manager



Sporton International (ShenZhen) Inc.

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055
People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	6
1.6 Testing Location	6
1.7 Test Software.....	7
1.8 Applicable Standards.....	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Carrier Frequency and Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	10
2.4 Support Unit used in test configuration and system	11
2.5 EUT Operation Test Setup	12
2.6 Measurement Results Explanation Example.....	12
3 TEST RESULT	13
3.1 6dB and 99% Bandwidth Measurement	13
3.2 Output Power Measurement.....	15
3.3 Power Spectral Density Measurement	16
3.4 Conducted Band Edges and Spurious Emission Measurement	18
3.5 Radiated Band Edges and Spurious Emission Measurement	31
3.6 AC Conducted Emission Measurement.....	35
3.7 Antenna Requirements.....	37
4 LIST OF MEASURING EQUIPMENT	38
5 UNCERTAINTY OF EVALUATION	39
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX E. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR040220C	Rev. 01	Initial issue of report	Jun. 16, 2020

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 30\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.17 dB at 2389.940 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 9.52 dB at 0.580 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Applicant

PAX Technology Limited

Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour Road, Wanchai, Hong Kong

1.2 Manufacturer

PAX Computer Technology (Shenzhen) Co., Ltd.

4/F, No.3 Building, Software Park, Second Central Science-Tech Road, High-Tech industrial Park, Shenzhen, Guangdong, P.R.C.

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Smart Payment Terminal
Brand Name	PAX
Model Name	A30
FCC ID	V5PA30BW
EUT supports Radios application	WLAN 2.4GHz 802.11b/g/n HT20/ HT40 WLAN 5GHz 802.11a/n HT20/ HT40 WLAN 5GHz 802.11ac VHT20/ VHT40/VHT80 Bluetooth BR/EDR/LE GNSS and NFC
HW Version	N/A
SW Version	N/A
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (AV) Output Power to antenna	802.11b : 13.20 dBm (0.0209 W) 802.11g : 13.50 dBm (0.0224 W) 802.11n HT20 : 13.10 dBm (0.0204 W) 802.11n HT40 : 12.80 dBm (0.0191 W)
99% Occupied Bandwidth	802.11b : 11.59MHz 802.11g : 20.48MHz 802.11n HT20 : 21.98MHz 802.11n HT40 : 42.16MHz
Antenna Type / Gain	Fixed Interna FPC Antenna type with gain 1.1 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International (Shenzhen) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International (Shenzhen) Inc.		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-SZ TH01-SZ	CN1256	421272

Test Firm	Sporton International (Shenzhen) Inc.		
Test Site Location	No. 3 Bldg the third floor of south, Shahe River west, Fengzeyuan Warehouse, Nanshan Shenzhen, 518055 People's Republic of China TEL: +86-755-33202398		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH01-SZ	CN1256	421272

1.7 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH01-SZ	AUDIX	E3	6.2009-8-24
2.	CO01-SZ	AUDIX	E3	6.120613b

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		

2.2 Test Mode


Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0


Test Cases	
AC Conducted Emission	Mode 1 :EUT + Bluetooth Link + WLAN 2.4G Link + Earphone + Battery + USB Cable(Charging from Adapter)
Remark: 1. For Radiated Test Cases, The tests were performance with Adapter, Battery, Earphone, USB Cable	

2.3 Connection Diagram of Test System

For Conducted Emission:



For Radiation:





2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	LABS ATGPS Simulator	RACELOGIC	RLLS03-2P	Fcc DoC	N/A	Unshielded,1.8m
3.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded,1.8m
4.	Notebook	Lenovo	E540	Fcc DoC	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
5.	NOTE BOOK	Lenovo	E540	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
6.	Bluetooth Earphone	Samsung	EO-MG900	CCAH14LP1680T5	N/A	N/A
7.	Earphone	Apple	MC690ZP/A	N/A	Shielded, 1.0m	N/A
8.	iPod	Apple	MC525 ZP/A	Fcc DoC	Shielded, 1.0m	N/A



2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.3 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.3 + 10 = 14.3 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1MHz and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.2 Method AVGPM-G method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures


1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.13
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges and Spurious Emission


Test Engineer :	Liu Qiu Qiu	Temperature :	21~25°C
		Relative Humidity :	51~54%

Test Mode :	802.11b	Test Channel :	01
-------------	---------	----------------	----






Test Mode :	802.11b	Test Channel :	06
-------------	---------	----------------	----






Test Mode :	802.11b	Test Channel :	11
-------------	---------	----------------	----






Test Mode :	802.11g	Test Channel :	01
-------------	---------	----------------	----


100kHz PSD reference Level




Channel Plot



Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz






Test Mode :	802.11g	Test Channel :	06
-------------	---------	----------------	----

100kHz PSD reference Level




Channel Plot

Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz






Test Mode :	802.11g	Test Channel :	11
-------------	---------	----------------	----






Test Mode :	802.11n HT20	Test Channel :	01
-------------	--------------	----------------	----





Test Mode :	802.11n HT20	Test Channel :	06
-------------	--------------	----------------	----







Test Mode : 802.11n HT20

Test Channel : 11


100kHz PSD reference Level




Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Test Mode : 802.11n HT40

Test Channel : 03


100kHz PSD reference Level




Channel Plot



Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz





Test Mode :	802.11n HT40	Test Channel :	06
-------------	--------------	----------------	----







Test Mode : 802.11n HT40

Test Channel : 09


100kHz PSD reference Level




Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 16, 2010	May 11, 2020	Apr. 15, 2021	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1207253	30MHz~40GHz	Dec. 26, 2019	May 11, 2020	Dec. 25, 2020	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Dec. 26, 2019	May 11, 2020	Dec. 25, 2020	Conducted (TH01-SZ)
EMI Test Receiver&SA	Agilent	N9038A	MY52260185	20Hz~26.5GHz	Jul. 22, 2019	May 11, 2020	Jul. 21, 2020	Radiation (03CH01-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Apr. 17, 2020	May 11, 2020	Apr. 16, 2021	Radiation (03CH01-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	May. 29, 2018	May 11, 2020	May. 28, 2020	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz~2GHz	Jul. 19, 2019	May 11, 2020	Jul. 18, 2020	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Aug. 27, 2019	May 11, 2020	Aug. 26, 2020	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Apr. 17, 2020	May 11, 2020	Apr. 16, 2021	Radiation (03CH01-SZ)
LF Amplifier	Burgeon	BPA-530	102209	0.01~3000Mhz	Apr. 17, 2020	May 11, 2020	Apr. 16, 2021	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	AMF-7D-0010 1800-30-10P-R	1943528	1GHz~18GHz	Oct. 18, 2019	May 11, 2020	Oct. 17, 2020	Radiation (03CH01-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270104	0.5GHz~26.5GHz	Dec. 27, 2019	May 11, 2020	Dec. 26, 2020	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 22, 2019	May 11, 2020	Jul. 21, 2020	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	May 11, 2020	NCR	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	May 11, 2020	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	May 11, 2020	NCR	Radiation (03CH01-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Dec. 26, 2018	Jun. 03, 2020	Dec. 25, 2020	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103912	9kHz~30MHz	Oct. 17, 2019	Jun. 03, 2020	Oct. 16, 2020	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	EMCO	3816/2SH	00103892	9kHz~30MHz	Oct. 17, 2019	Jun. 03, 2020	Oct. 16, 2020	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 23, 2019	Jun. 03, 2020	Jul. 22, 2020	Conduction (CO01-SZ)

NCR: No Calibration Required

5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.6dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.8dB
---	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.3dB
---	-------



Appendix A. Conducted Test Results

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Liu Qiu Qiu	Temperature:	21~25	°C
Test Date:	2020/5/11	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
					Ant 1	Ant 1		
11b	1Mbps	1	1	2412	11.34	9.03	0.50	Pass
11b	1Mbps	1	6	2437	11.49	9.03	0.50	Pass
11b	1Mbps	1	11	2462	11.59	9.05	0.50	Pass
11g	6Mbps	1	1	2412	20.48	15.64	0.50	Pass
11g	6Mbps	1	6	2437	16.73	15.70	0.50	Pass
11g	6Mbps	1	11	2462	19.13	15.70	0.50	Pass
HT20	MCS0	1	1	2412	21.98	16.26	0.50	Pass
HT20	MCS0	1	6	2437	17.68	16.32	0.50	Pass
HT20	MCS0	1	11	2462	19.63	16.30	0.50	Pass
HT40	MCS0	1	3	2422	35.56	28.77	0.50	Pass
HT40	MCS0	1	6	2437	36.16	28.85	0.50	Pass
HT40	MCS0	1	9	2452	42.16	36.32	0.50	Pass

TEST RESULTS DATA
Average Output Power

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
					Ant 1	Ant 1	Ant 1	Ant 1	Ant 1	
11b	1Mbps	1	1	2412	10.90	30.00	1.10	12.00	36.00	Pass
11b	1Mbps	1	6	2437	13.20	30.00	1.10	14.30	36.00	Pass
11b	1Mbps	1	11	2462	9.10	30.00	1.10	10.20	36.00	Pass
11g	6Mbps	1	1	2412	12.50	30.00	1.10	13.60	36.00	Pass
11g	6Mbps	1	6	2437	12.70	30.00	1.10	13.80	36.00	Pass
11g	6Mbps	1	11	2462	13.50	30.00	1.10	14.60	36.00	Pass
HT20	MCS0	1	1	2412	12.90	30.00	1.10	14.00	36.00	Pass
HT20	MCS0	1	6	2437	13.00	30.00	1.10	14.10	36.00	Pass
HT20	MCS0	1	11	2462	13.10	30.00	1.10	14.20	36.00	Pass
HT40	MCS0	1	3	2422	12.10	30.00	1.10	13.20	36.00	Pass
HT40	MCS0	1	6	2437	12.70	30.00	1.10	13.80	36.00	Pass
HT40	MCS0	1	9	2452	12.80	30.00	1.10	13.90	36.00	Pass

Note: Measured power (dBm) has offset with cable loss.


TEST RESULTS DATA
Peak Power Spectral Density

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm/3kHz)	DG (dBi)	Peak PSD Limit (dBm/3kHz)	Pass/Fail
					Ant 1	Ant 1	Ant 1	
11b	1Mbps	1	1	2412	-8.97	1.10	8.00	Pass
11b	1Mbps	1	6	2437	-6.72	1.10	8.00	Pass
11b	1Mbps	1	11	2462	-10.74	1.10	8.00	Pass
11g	6Mbps	1	1	2412	-12.19	1.10	8.00	Pass
11g	6Mbps	1	6	2437	-12.86	1.10	8.00	Pass
11g	6Mbps	1	11	2462	-11.31	1.10	8.00	Pass
HT20	MCS0	1	1	2412	-11.87	1.10	8.00	Pass
HT20	MCS0	1	6	2437	-11.19	1.10	8.00	Pass
HT20	MCS0	1	11	2462	-12.10	1.10	8.00	Pass
HT40	MCS0	1	3	2422	-14.86	1.10	8.00	Pass
HT40	MCS0	1	6	2437	-14.17	1.10	8.00	Pass
HT40	MCS0	1	9	2452	-14.38	1.10	8.00	Pass

Measured power density (dBm) has offset with cable loss.




Appendix B. AC Conducted Emission Test Results





Test Engineer :	Doom Wu	Temperature :	24~25°C
		Relative Humidity :	48~49%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral



Site : CO01-SZ
Condition: FCC 15C_QP LISN_20190719_N NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.17	20.64	-34.44	55.08	10.60	0.03	10.01	Average
2	0.17	37.44	-27.64	65.08	27.40	0.03	10.01	QP
3	0.19	21.24	-32.78	54.02	11.20	0.03	10.01	Average
4	0.19	38.24	-25.78	64.02	28.20	0.03	10.01	QP
5	0.34	16.14	-33.17	49.31	6.10	0.03	10.01	Average
6	0.34	34.64	-24.67	59.31	24.60	0.03	10.01	QP
7 *	0.58	36.48	-9.52	46.00	26.40	0.02	10.06	Average
8	0.58	40.48	-15.52	56.00	30.40	0.02	10.06	QP
9	0.76	18.69	-27.31	46.00	8.59	0.03	10.07	Average
10	0.76	32.39	-23.61	56.00	22.29	0.03	10.07	QP
11	9.65	16.70	-33.30	50.00	6.30	0.15	10.25	Average
12	9.65	32.50	-27.50	60.00	22.10	0.15	10.25	QP

Note:

1. Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
2. Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



Appendix C. Radiated Spurious Emission

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2360.4	54.77	-19.23	74	46.15	32.86	8.76	33	100	147	P	H
		2390	43.52	-10.48	54	34.78	32.9	8.84	33	100	147	A	H
	*	2412	98.39	-	-	89.64	32.91	8.84	33	100	147	P	H
	*	2412	96.69	-	-	87.94	32.91	8.84	33	100	147	A	H
		2373.315	54.88	-19.12	74	46.24	32.88	8.76	33	113	190	P	V
		2389.59	43.46	-10.54	54	34.72	32.9	8.84	33	113	190	A	V
	*	2412	100.75	-	-	92	32.91	8.84	33	113	190	P	V
	*	2412	99.15	-	-	90.4	32.91	8.84	33	113	190	A	V
802.11b CH 06 2437MHz		2389.24	54.73	-19.27	74	45.99	32.9	8.84	33	100	146	P	H
		2389.52	43.31	-10.69	54	34.57	32.9	8.84	33	100	146	A	H
	*	2437	96.8	-	-	87.93	32.95	8.92	33	100	146	P	H
	*	2437	95.02	-	-	86.15	32.95	8.92	33	100	146	A	H
		2496.36	54.95	-19.05	74	45.95	33	9	33	100	146	P	H
		2484.53	43.48	-10.52	54	34.5	32.98	9	33	100	146	A	H
		2336.6	54.1	-19.9	74	45.57	32.84	8.69	33	100	201	P	V
		2389.94	43.27	-10.73	54	34.53	32.9	8.84	33	100	201	A	V
	*	2437	102.8	-	-	93.93	32.95	8.92	33	100	201	P	V
	*	2437	101.06	-	-	92.19	32.95	8.92	33	100	201	A	V
		2493.7	53.48	-20.52	74	44.48	33	9	33	100	201	P	V
		2486.35	43.47	-10.53	54	34.49	32.98	9	33	100	201	A	V



802.11b CH 11 2462MHz	*	2462	92.49	-	-	83.6	32.97	8.92	33	116	144	P	H
	*	2462	90.63	-	-	81.74	32.97	8.92	33	116	144	A	H
		2494.96	54.24	-19.76	74	45.24	33	9	33	116	144	P	H
		2488.08	43.48	-10.52	54	34.48	33	9	33	116	144	A	H
	*	2462	98.76	-	-	89.87	32.97	8.92	33	100	192	P	V
	*	2462	96.95	-	-	88.06	32.97	8.92	33	100	192	A	V
		2489.28	54.39	-19.61	74	45.39	33	9	33	100	192	P	V
		2484.04	43.65	-10.35	54	34.67	32.98	9	33	100	192	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		4824	53.77	-20.23	74	62.75	34.83	13.67	57.48	140	356	P	H
CH 01		4824	49.24	-4.76	54	58.22	34.83	13.67	57.48	140	356	V	H
2412MHz		4824	47.84	-26.16	74	56.82	34.83	13.67	57.48	177	125	P	V
802.11b		4874	52.26	-21.74	74	61.06	34.85	13.87	57.52	145	347	P	H
		4874	49.07	-4.93	54	57.87	34.85	13.87	57.52	145	347	V	H
CH 06		7311	50.41	-23.59	74	58.14	36.25	14.94	58.92	174	100	P	H
2437MHz		4874	46.61	-27.39	74	55.41	34.85	13.87	57.52	172	146	P	V
		7311	50.43	-23.57	74	58.16	36.25	14.94	58.92	227	189	V	V
802.11b		4924	54.48	-19.52	74	62.9	34.87	14.26	57.55	145	352	P	H
		4924	49.66	-4.34	54	58.08	34.87	14.26	57.55	145	352	V	H
CH 11		7386	49.89	-24.11	74	57.48	36.18	15.19	58.96	183	244	P	H
2462MHz		4924	47.72	-26.28	74	56.14	34.87	14.26	57.55	183	227	P	V
		7386	49.72	-24.28	74	57.31	36.18	15.19	58.96	175	315	V	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g CH 01 2412MHz		2389.69	54.76	-19.24	74	46.02	32.9	8.84	33	362	230	P	H
		2390	43.54	-10.46	54	34.8	32.9	8.84	33	362	230	A	H
	*	2412	99.42	-	-	90.67	32.91	8.84	33	362	230	P	H
	*	2412	93.41	-	-	84.66	32.91	8.84	33	362	230	A	H
		2389.06	61.88	-12.12	74	53.14	32.9	8.84	33	127	197	P	V
		2390	47.02	-6.98	54	38.28	32.9	8.84	33	127	197	A	V
	*	2412	105.13	-	-	96.38	32.91	8.84	33	127	197	P	V
	*	2412	98.95	-	-	90.2	32.91	8.84	33	127	197	A	V
802.11g CH 06 2437MHz		2373.7	54.42	-19.58	74	45.78	32.88	8.76	33	100	134	P	H
		2389.24	43.11	-10.89	54	34.37	32.9	8.84	33	100	134	A	H
	*	2437	99.91	-	-	91.04	32.95	8.92	33	100	134	P	H
	*	2437	91.37	-	-	82.5	32.95	8.92	33	100	134	A	H
		2498.74	54.03	-19.97	74	45.03	33	9	33	100	134	P	H
		2484.39	43.33	-10.67	54	34.35	32.98	9	33	100	134	A	H
		2347.1	53.78	-20.22	74	45.18	32.84	8.76	33	119	196	P	V
		2389.66	43.24	-10.76	54	34.5	32.9	8.84	33	119	196	A	V
	*	2437	103.89	-	-	95.02	32.95	8.92	33	119	196	P	V
	*	2437	96.32	-	-	87.45	32.95	8.92	33	119	196	A	V
		2485.93	54.28	-19.72	74	45.3	32.98	9	33	119	196	P	V
		2484.18	43.41	-10.59	54	34.43	32.98	9	33	119	196	A	V



802.11g CH 11 2462MHz	*	2462	101.05	-	-	92.16	32.97	8.92	33	349	156	P	H
	*	2462	94.11	-	-	85.22	32.97	8.92	33	349	156	A	H
		2483.88	62.15	-11.85	74	53.17	32.98	9	33	349	156	P	H
		2483.52	46.47	-7.53	54	37.49	32.98	9	33	349	156	A	H
	*	2462	104.73	-	-	95.84	32.97	8.92	33	131	199	P	V
	*	2462	97.93	-	-	89.04	32.97	8.92	33	131	199	A	V
		2483.76	67.32	-6.68	74	58.34	32.98	9	33	131	199	P	V
		2483.52	49.6	-4.4	54	40.62	32.98	9	33	131	199	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g		4824	54.44	-19.56	74	63.42	34.83	13.67	57.48	148	350	P	H
CH 01		4824	43.58	-10.42	54	52.56	34.83	13.67	57.48	148	350	A	H
2412MHz		4824	47.67	-26.33	74	56.65	34.83	13.67	57.48	161	360	P	V
802.11g		4874	49.97	-24.03	74	58.77	34.85	13.87	57.52	172	146	P	H
CH 06		7311	50.67	-23.33	74	58.4	36.25	14.94	58.92	227	189	A	H
2437MHz		4874	46.71	-27.29	74	55.51	34.85	13.87	57.52	152	145	P	V
		7311	50.35	-23.65	74	58.08	36.25	14.94	58.92	133	266	A	V
802.11g		4924	56.63	-17.37	74	65.05	34.87	14.26	57.55	144	351	P	H
CH 11		4924	45.77	-8.23	54	54.19	34.87	14.26	57.55	144	351	A	H
2462MHz		7386	50.85	-23.15	74	58.44	36.18	15.19	58.96	175	315	P	H
		4924	47.88	-26.12	74	56.3	34.87	14.26	57.55	144	152	P	V
		7386	49.25	-24.75	74	56.84	36.18	15.19	58.96	145	171	A	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 01 2412MHz		2389.8	59.96	-14.04	74	51.22	32.9	8.84	33	100	146	P	H
		2390	45.83	-8.17	54	37.09	32.9	8.84	33	100	146	A	H
		2412	100.07	-	-	91.32	32.91	8.84	33	100	146	P	H
		2412	93.63	-	-	84.88	32.91	8.84	33	100	146	A	H
		2389.8	64.51	-9.49	74	55.77	32.9	8.84	33	158	207	P	V
		2389.905	48.89	-5.11	54	40.15	32.9	8.84	33	158	207	A	V
		2412	104.28	-	-	95.53	32.91	8.84	33	158	207	P	V
		2412	99.04	-	-	90.29	32.91	8.84	33	158	207	A	V
802.11n HT20 CH 06 2437MHz		2386.3	54.16	-19.84	74	45.42	32.9	8.84	33	284	38	P	H
		2362.08	43.59	-10.41	54	34.97	32.86	8.76	33	284	38	A	H
		2437	100.07	-	-	91.2	32.95	8.92	33	284	38	P	H
		2437	92.69	-	-	83.82	32.95	8.92	33	284	38	A	H
		2488.1	54.53	-19.47	74	45.53	33	9	33	284	38	P	H
		2484.11	43.82	-10.18	54	34.84	32.98	9	33	284	38	A	H
		2382.24	53.82	-20.18	74	45.18	32.88	8.76	33	153	207	P	V
		2389.66	43.66	-10.34	54	34.92	32.9	8.84	33	153	207	A	V
		2437	105.5	-	-	96.63	32.95	8.92	33	153	207	P	V
		2437	97.81	-	-	88.94	32.95	8.92	33	153	207	A	V
		2498.32	54.47	-19.53	74	45.47	33	9	33	153	207	P	V
		2485.3	43.91	-10.09	54	34.93	32.98	9	33	153	207	A	V



802.11n HT20 CH 11 2462MHz	*	2462	99.93	-	-	91.04	32.97	8.92	33	400	37	P	H
	*	2462	92.68	-	-	83.79	32.97	8.92	33	400	37	A	H
		2483.76	61.56	-12.44	74	52.58	32.98	9	33	400	37	P	H
		2483.52	46.83	-7.17	54	37.85	32.98	9	33	400	37	A	H
	*	2462	104.49	-	-	95.6	32.97	8.92	33	152	193	P	V
	*	2462	96.5	-	-	87.61	32.97	8.92	33	152	193	A	V
		2483.6	65.46	-8.54	74	56.48	32.98	9	33	152	193	P	V
		2483.72	49.62	-4.38	54	40.64	32.98	9	33	152	193	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 01 2412MHz		4824	54.36	-19.64	74	63.34	34.83	13.67	57.48	148	353	P	H
		4824	43.49	-10.51	54	52.47	34.83	13.67	57.48	148	353	A	H
		4824	48.13	-25.87	74	57.11	34.83	13.67	57.48	174	29	P	V
802.11n HT20 CH 06 2437MHz		4874	49.79	-24.21	74	58.59	34.85	13.87	57.52	172	146	P	H
		7311	49.72	-24.28	74	57.45	36.25	14.94	58.92	227	189	A	H
		4874	46.91	-27.09	74	55.71	34.85	13.87	57.52	165	106	P	V
		7311	50.7	-23.3	74	58.43	36.25	14.94	58.92	174	100	A	V
802.11n HT20 CH 11 2462MHz		4924	58.76	-15.24	74	67.18	34.87	14.26	57.55	144	337	P	H
		4924	46.94	-7.06	54	55.36	34.87	14.26	57.55	144	337	A	H
		7386	49.83	-24.17	74	57.42	36.18	15.19	58.96	155	274	P	H
		4924	49.3	-24.7	74	57.72	34.87	14.26	57.55	183	227	P	V
		7386	51.73	-22.27	74	59.32	36.18	15.19	58.96	175	315	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 CH 03 2422MHz		2389.94	58.36	-15.64	74	49.62	32.9	8.84	33	283	35	P	H
		2389.94	44.83	-9.17	54	36.09	32.9	8.84	33	283	35	A	H
	*	2422	96.69	-	-	87.92	32.93	8.84	33	283	35	P	H
	*	2422	90.11	-	-	81.34	32.93	8.84	33	283	35	A	H
		2484.46	53.96	-20.04	74	44.98	32.98	9	33	283	35	P	H
		2485.65	43.78	-10.22	54	34.8	32.98	9	33	283	35	A	H
		2389.8	67.87	-6.13	74	59.13	32.9	8.84	33	163	207	P	V
		2389.94	50.83	-3.17	54	42.09	32.9	8.84	33	163	207	A	V
	*	2422	102.39	-	-	93.62	32.93	8.84	33	163	207	P	V
	*	2422	95.37	-	-	86.6	32.93	8.84	33	163	207	A	V
		2483.5	54.72	-19.28	74	45.74	32.98	9	33	163	207	P	V
		2484.81	43.82	-10.18	54	34.84	32.98	9	33	163	207	A	V
802.11n HT40 CH 06 2437MHz		2368.52	54.18	-19.82	74	45.54	32.88	8.76	33	284	36	P	H
		2389.52	43.63	-10.37	54	34.89	32.9	8.84	33	284	36	A	H
	*	2437	97.93	-	-	89.06	32.95	8.92	33	284	36	P	H
	*	2437	90.3	-	-	81.43	32.95	8.92	33	284	36	A	H
		2487.19	53.83	-20.17	74	44.85	32.98	9	33	284	36	P	H
		2483.5	43.86	-10.14	54	34.88	32.98	9	33	284	36	A	H
		2325.96	54.03	-19.97	74	45.51	32.83	8.69	33	281	300	P	V
		2389.24	43.7	-10.3	54	34.96	32.9	8.84	33	281	300	A	V
	*	2437	99.87	-	-	91	32.95	8.92	33	281	300	P	V
	*	2437	92.92	-	-	84.05	32.95	8.92	33	281	300	A	V
		2488.31	54.16	-19.84	74	45.16	33	9	33	281	300	P	V
		2485.3	44.03	-9.97	54	35.05	32.98	9	33	281	300	A	V



802.11n HT40 CH 09 2452MHz		2382.52	54.39	-19.61	74	45.75	32.88	8.76	33	285	35	P	H
		2389.94	43.48	-10.52	54	34.74	32.9	8.84	33	285	35	A	H
	*	2452	96.4	-	-	87.53	32.95	8.92	33	285	35	P	H
	*	2452	89.82	-	-	80.95	32.95	8.92	33	285	35	A	H
		2483.9	59.14	-14.86	74	50.16	32.98	9	33	285	35	P	H
		2483.5	46.26	-7.74	54	37.28	32.98	9	33	285	35	A	H
		2339.68	54.67	-19.33	74	46.14	32.84	8.69	33	281	305	P	V
		2389.52	43.5	-10.5	54	34.76	32.9	8.84	33	281	305	A	V
	*	2452	100.01	-	-	91.14	32.95	8.92	33	281	305	P	V
	*	2452	93.13	-	-	84.26	32.95	8.92	33	281	305	A	V
		2485.37	60.36	-13.64	74	51.38	32.98	9	33	281	305	P	V
		2483.62	46.76	-7.24	54	37.78	32.98	9	33	281	305	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n		4844	49.29	-24.71	74	58.07	34.84	13.87	57.49	150	350	P	H
HT40		7266	49.85	-24.15	74	57.67	36.28	14.81	58.91	200	360	A	H
CH 03		4844	48.3	-25.7	74	57.08	34.84	13.87	57.49	188	296	P	V
2422MHz		7266	50.34	-23.66	74	58.16	36.28	14.81	58.91	169	275	A	V
802.11n		4874	49.34	-24.66	74	58.14	34.85	13.87	57.52	165	230	P	H
HT40		7311	50.03	-23.97	74	57.76	36.25	14.94	58.92	186	323	A	H
CH 06		4874	47.55	-26.45	74	56.35	34.85	13.87	57.52	166	185	P	V
2437MHz		7311	50.32	-23.68	74	58.05	36.25	14.94	58.92	163	298	A	V
802.11n		4904	49.96	-24.04	74	58.56	34.87	14.07	57.54	150	360	P	H
HT40		7356	49.78	-24.22	74	57.45	36.21	15.06	58.94	165	335	A	H
CH 09		4904	47.18	-26.82	74	55.78	34.87	14.07	57.54	162	318	P	V
2452MHz		7356	50.46	-23.54	74	58.13	36.21	15.06	58.94	189	298	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz WIFI 802.11n HT40 (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11n HT40 LF		30.97	25.37	-14.63	40	31.29	24.35	1.03	31.3	-	-	P	H
		99.84	33.22	-10.28	43.5	45.89	17.1	1.83	31.6	-	-	P	H
		250.19	38.45	-7.55	46	48.59	18.7	2.86	31.7	-	-	P	H
		375.32	42.01	-3.99	46	48.77	21.1	3.49	31.35	162	135	P	H
		499.48	36.01	-9.99	46	39.38	23.8	4.03	31.2	-	-	P	H
		749.74	34.85	-11.15	46	34.82	26.2	4.93	31.1	-	-	P	H
		49.4	32.88	-7.12	40	48.46	14.7	1.29	31.57	144	162	P	V
		99.84	33.71	-9.79	43.5	46.38	17.1	1.83	31.6	-	-	P	V
		199.75	33.39	-10.11	43.5	46.32	15.8	2.57	31.3	-	-	P	V
		375.32	38.53	-7.47	46	45.29	21.1	3.49	31.35	-	-	P	V
		647.89	34.87	-11.13	46	36.32	25.38	4.58	31.41	-	-	P	V
		749.74	33.27	-12.73	46	33.24	26.2	4.93	31.1	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)


= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.


Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	100	-	-	10Hz
802.11g	98.66	-	-	10Hz
802.11n HT20	97.85	4.942	0.202	300Hz
802.11n HT40	97.63	3.580	0.279	300Hz


802.11b



802.11g



802.11n HT20



802.11n HT40

