# **FCC RF Test Report**

APPLICANT : PAX Technology Limited

**EQUIPMENT**: Smart Mobile Payment Terminal

BRAND NAME : PAX MODEL NAME : A910

FCC ID : V5PA910

STANDARD : FCC Part 15 Subpart C §15.247

CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Apr. 24, 2019 and testing was completed on Jun. 11, 2019. We, Sporton International (ShenZhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (ShenZhen) Inc., the test report shall not be reproduced except in full.

Derreck Chen

Reviewed by: Derreck Chen / Supervisor

Fire Shih

Approved by: Eric Shih / Manager

## Sporton International (ShenZhen) Inc.

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China

Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910 Page Number : 1 of 35
Report Issued Date : Jun. 19, 2019

Report No.: FR942424B

Report Version : Rev. 01

## **TABLE OF CONTENTS**

RE	VISIO	N HISTORY	3
SU	MMAF	RY OF TEST RESULT	4
1	GEN	ERAL DESCRIPTION	5
	1.1	Applicant	5
	1.2	Product Feature of Equipment Under Test	5
	1.3	Product Specification of Equipment Under Test	5
	1.4	Modification of EUT	6
	1.5	Testing Location	6
	1.6	Applicable Standards	6
2	TES1	T CONFIGURATION OF EQUIPMENT UNDER TEST	7
	2.1	Carrier Frequency Channel	7
	2.2	Test Mode	8
	2.3	Connection Diagram of Test System	9
	2.4	Support Unit used in test configuration and system	9
	2.5	EUT Operation Test Setup	10
	2.6	Measurement Results Explanation Example	10
3	TEST	Г RESULT	11
	3.1	6dB and 99% Bandwidth Measurement	11
	3.2	Output Power Measurement	16
	3.3	Power Spectral Density Measurement	17
	3.4	Conducted Band Edges and Spurious Emission Measurement	22
	3.5	Radiated Band Edges and Spurious Emission Measurement	27
	3.6	AC Conducted Emission Measurement	31
	3.7	Antenna Requirements	33
4	LIST	OF MEASURING EQUIPMENT	34
5	UNC	ERTAINTY OF EVALUATION	35
ΑP	PEND	IX A. CONDUCTED TEST RESULTS	
ΑP	PEND	IX B. AC CONDUCTED EMISSION TEST RESULT	
ΑP	PEND	IX C. RADIATED SPURIOUS EMISSION	
ΑP	PEND	IX D. DUTY CYCLE PLOTS	
ΑP	PEND	IX E. SETUP PHOTOGRAPHS	

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910 Page Number : 2 of 35
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Report No. : FR942424B

## **REVISION HISTORY**

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR942424B	Rev. 01	Initial issue of report	Jun. 19, 2019

**Sporton International (Shenzhen) Inc.** TEL: +86-755-86379589

FAX: +86-755-86379595 FCC ID: V5PA910 Page Number : 3 of 35
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Report No. : FR942424B

## **SUMMARY OF TEST RESULT**

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.1	-	99% Bandwidth	-	Pass	-
3.2	15.247(b)(3)	Output Power	≤ 30dBm	Pass	-
3.3	15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	≤ 30dBc	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 10.52 dB at 52.310 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 3.24 dB at 11.200 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910 Page Number : 4 of 35
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Report No. : FR942424B

# 1 General Description

## 1.1 Applicant

#### **PAX Technology Limited**

Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour Road, Wanchai, Hong Kong

## 1.2 Product Feature of Equipment Under Test

Product Feature				
Equipment	Smart Mobile Payment Terminal			
Brand Name	PAX			
Model Name	A910			
FCC ID	V5PA910			
	WCDMA/LTE			
FUT assuments Dadies and lisation	WLAN 2.4GHz 802.11b/g/n HT20			
EUT supports Radios application	Bluetooth BR / EDR / LE			
	NFC/GNSS			
	Conducted: 358870099991022/358870099991030			
IMEI Code	Conduction: 358870099990958/358870099990941			
	Radiation: 860400040019995/860400040019987			
HW Version	N/A			
SW Version	N/A			
EUT Stage	Production Unit			

Report No.: FR942424B

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.3 Product Specification of Equipment Under Test

Standards-related Product Specification				
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz			
Number of Channels	40			
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)			
Maximum Output Power to Antenna	-1.00 dBm (0.001 W)			
99% Occupied Bandwidth	1.023MHz			
Antenna Type / Gain	FPC Antenna with gain 0.80 dBi			
Type of Modulation	Bluetooth LE : GFSK			

 Sporton International (Shenzhen) Inc.
 Page Number
 : 5 of 35

 TEL: +86-755-86379589
 Report Issued Date
 : Jun. 19, 2019

 FAX: +86-755-86379595
 Report Version
 : Rev. 01

FCC ID: V5PA910 Report Template No.: BU5-FR15CBT4.2/5.0 Version 2.0

## 1.4 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.5 Testing Location

Sporton International (Shenzhen) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International (Shenzhen) Inc.				
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595				
	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.		
Test Site No.	CO01-SZ TH01-SZ	CN1256	421272		

Test Firm	Sporton International (Shenzhen) Inc.				
Test Site Location	No. 3 Bldg the third floor of south, Shahe River west, Fengzeyuan Warehouse, Nanshan Shenzhen, 518055 People's Republic of China				
	TEL: +86-755-3320-2398	3			
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.		
rest Site No.	03CH04-SZ CN1256 421272				

## 1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r01
- ANSI C63.10-2013

#### Remark:

- 1. All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910 Page Number : 6 of 35
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Report No.: FR942424B

# 2 Test Configuration of Equipment Under Test

# 2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
2400-2483.5 MHz	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910 Page Number : 7 of 35
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Report No.: FR942424B

## 2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

	Summary table of Test Cases						
Test Item	Data Rate / Modulation						
rest item	Bluetooth – LE / GFSK						
Conducted	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps						
TCs	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps						
ics	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps						
Radiated	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps						
TCs	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps						
ics	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps						
AC	Made 1: WCDMA Bond II Idle   Blueteeth Link   WLAN Link   LISP Coble (Charging						
Conducted	Mode 1: WCDMA Band II Idle + Bluetooth Link + WLAN Link + USB Cable (Charging						
Emission	from Adapter) + Battery						
Remark: For	Radiated Test Cases, The tests were performed with Adapter, Battery and USB Cable.						

Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910


Page Number Report Issued Date: Jun. 19, 2019 Report Version : Rev. 01

Report Template No.: BU5-FR15CBT4.2/5.0 Version 2.0

: 8 of 35

Report No.: FR942424B

## 2.3 Connection Diagram of Test System



## 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	WLAN AP	D-Link	DIR-820L	KA2IR820LA1	N/A	Unshielded,1.8m
3.	Notebook	Lenovo	E540	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Samsung	EO-MG900	PYAHS-107W	N/A	N/A

Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910 Page Number : 9 of 35
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Report No.: FR942424B

## 2.5 EUT Operation Test Setup

For Bluetooth LE function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

Report No.: FR942424B

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

## 2.6 Measurement Results Explanation Example

#### For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

#### Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5.0 dB and 10dB attenuator.

 $Offset(dB) = RF \ cable \ loss(dB) + attenuator \ factor(dB).$ 

= 5.0 + 10 = 15.0 (dB)

Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910 Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Page Number

Report Template No.: BU5-FR15CBT4.2/5.0 Version 2.0

: 10 of 35

## 3 Test Result

### 3.1 6dB and 99% Bandwidth Measurement

#### 3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


## 3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

### 3.1.3 Test Procedures

- 1. The testing follows ANSI C63.10-2013 clause 11.8
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
- 5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 30kHz and set the Video bandwidth (VBW) = 100kHz.
- 6. Measure and record the results in the test report.

## 3.1.4 Test Setup



**Sporton International (Shenzhen) Inc.** TEL: +86-755-86379589


FAX: +86-755-86379595 FCC ID: V5PA910 Page Number : 11 of 35
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Report No.: FR942424B

## 3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

#### 6 dB Bandwidth Plot on Channel 00



Date: 3.MAY.2019 06:31:55

Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910 Page Number : 12 of 35
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01


Report No.: FR942424B

#### 6 dB Bandwidth Plot on Channel 19



Date: 3.MAY.2019 06:38:15

#### 6 dB Bandwidth Plot on Channel 39



Date: 3.MAY.2019 06:45:53

Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595

FCC ID: V5PA910

Page Number : 13 of 35
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01


Report Template No.: BU5-FR15CBT4.2/5.0 Version 2.0

Report No.: FR942424B

## 3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

#### 99% Bandwidth Plot on Channel 00



Date: 3.MAY.2019 06:36:16

Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910


Report Issued Date: Jun. 19, 2019 Report Version : Rev. 01 Report Template No.: BU5-FR15CBT4.2/5.0 Version 2.0

Page Number

: 14 of 35


Report No.: FR942424B

#### 99% Occupied Bandwidth Plot on Channel 19



Date: 3.MAY.2019 06:43:06

#### 99% Occupied Bandwidth Plot on Channel 39



Date: 3.MAY.2019 06:50:57

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910 Page Number : 15 of 35
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Report No.: FR942424B

## 3.2 Output Power Measurement

## 3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


## 3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

#### 3.2.3 Test Procedures

- The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1
   Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.2 Method AVGPM-G method.
- 2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Measure the conducted output power and record the results in the test report.

### 3.2.4 Test Setup



## 3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910 Page Number : 16 of 35
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Report No.: FR942424B

## 3.3 Power Spectral Density Measurement

## 3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


## 3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

#### 3.3.3 Test Procedures

- The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
- 5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
- 6. Measure and record the results in the test report.
- 7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

### 3.3.4 Test Setup



### 3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.


Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910 Page Number : 17 of 35
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Report No.: FR942424B


## 3.3.6 Test Result of Power Spectral Density Plots (100kHz)

### PSD 100kHz Plot on Channel 00



Date: 3.MAY.2019 06:34:06

### PSD 100kHz Plot on Channel 19



Date: 3.MAY.2019 06:41:07

Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595


FCC ID: V5PA910

Page Number : 18 of 35
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Report Template No.: BU5-FR15CBT4.2/5.0 Version 2.0

Report No.: FR942424B

### PSD 100kHz Plot on Channel 39



Date: 3.MAY.2019 06:48:54

TEL: +86-755-86379589 FAX: +86-755-86379595


FCC ID: V5PA910

Page Number : 19 of 35
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Report No.: FR942424B


## 3.3.7 Test Result of Power Spectral Density Plots (3kHz)

#### PSD 3kHz Plot on Channel 00



Date: 3.MAY.2019 06:32:43

### **PSD 3kHz Plot on Channel 19**



Date: 3.MAY.2019 06:39:30


Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910 Page Number : 20 of 35
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Report Template No.: BU5-FR15CBT4.2/5.0 Version 2.0

Report No.: FR942424B

### **PSD 3kHz Plot on Channel 39**



Date: 3.MAY.2019 06:46:13

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910 Page Number : 21 of 35
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Report Template No.: BU5-FR15CBT4.2/5.0 Version 2.0

Report No.: FR942424B

## 3.4 Conducted Band Edges and Spurious Emission Measurement

## 3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.

Report No.: FR942424B


## 3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

#### 3.4.3 Test Procedure

- 1. The testing follows ANSI C63.10-2013 clause 11.13
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
- 5. Measure and record the results in the test report.
- 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

#### 3.4.4 Test Setup



Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910 Report Issued Date: Jun. 19, 2019
Report Version: Rev. 01


Page Number

Report Template No.: BU5-FR15CBT4.2/5.0 Version 2.0

: 22 of 35


## 3.4.5 Test Result of Conducted Band Edges Plots

### Low Band Edge Plot on Channel 00



Date: 3.MAY.2019 06:34:41

### **High Band Edge Plot on Channel 39**



Date: 3.MAY.2019 06:49:22


Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910 Page Number : 23 of 35
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Report No.: FR942424B


## 3.4.6 Test Result of Conducted Spurious Emission Plots

# Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 3.MAY.2019 06:35:16

# Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00




Date: 3.MAY.2019 06:35:33

Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910 Page Number : 24 of 35
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01


Report No.: FR942424B

# Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 3.MAY.2019 06:41:35

# Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 3.MAY.2019 06:42:50

Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595


FCC ID: V5PA910

Page Number : 25 of 35
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Report No.: FR942424B


# Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39

Report No.: FR942424B



Date: 11.JUN.2019 14:03:18

# Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 11.JUN.2019 14:03:30

Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910 Page Number : 26 of 35
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

## 3.5 Radiated Band Edges and Spurious Emission Measurement

## 3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Report No.: FR942424B

Frequency	Field Strength	Measurement Distance
(MHz)	(microvolts/meter)	(meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

## 3.5.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910

Page Number Report Issued Date: Jun. 19, 2019 Report Version : Rev. 01

Report Template No.: BU5-FR15CBT4.2/5.0 Version 2.0

: 27 of 35

#### 3.5.3 Test Procedures

- 1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
- 2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.

Report No.: FR942424B

- The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
- 4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
- 5. Corrected Reading: Antenna Factor + Cable Loss + Read Level Preamp Factor = Level
- For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
- 7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 8. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
  - (3) Set RBW = 1 MHz, VBW= 3MHz for  $f \ge 1$  GHz for peak measurement. For average measurement:
    - VBW = 10 Hz, when duty cycle is no less than 98 percent.
    - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

 Sporton International (Shenzhen) Inc.
 Page Number
 : 28 of 35


 TEL: +86-755-86379589
 Report Issued Date
 : Jun. 19, 2019

 FAX: +86-755-86379595
 Report Version
 : Rev. 01


FAX: +86-755-86379595 Report Version: Rev. 01
FCC ID: V5PA910 Report Template No.: BU5-FR15CBT4.2/5.0 Version 2.0

## 3.5.4 Test Setup


#### For radiated emissions below 30MHz



#### For radiated emissions from 30MHz to 1GHz



### For radiated emissions above 1GHz



Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910 Page Number : 29 of 35
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Report No.: FR942424B

## 3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Report No.: FR942424B

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

## 3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

## 3.5.7 Duty Cycle

Please refer to Appendix D.

## 3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

Sporton International (Shenzhen) Inc. TEL: +86-755-86379589

FAX: +86-755-86379595 FCC ID: V5PA910

Report Version : Rev. 01
Report Template No.: BU5-FR15CBT4.2/5.0 Version 2.0

Report Issued Date: Jun. 19, 2019

: 30 of 35

Page Number

### 3.6 AC Conducted Emission Measurement

#### 3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Report No.: FR942424B

Eroquency of emission (MUz)	Conducted	limit (dΒμV)
Frequency of emission (MHz)	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

<sup>\*</sup>Decreases with the logarithm of the frequency.

## 3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

### 3.6.3 Test Procedures

- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- 2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- 3. All the support units are connecting to the other LISN.
- 4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- 5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- 6. Both sides of AC line were checked for maximum conducted interference.
- 7. The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


 Sporton International (Shenzhen) Inc.
 Page Number
 : 31 of 35

 TEL: +86-755-86379589
 Report Issued Date
 : Jun. 19, 2019

 FAX: +86-755-86379595
 Report Version
 : Rev. 01

FAX: +86-755-86379595 Report Version: Rev. 01
FCC ID: V5PA910 Report Template No.: BU5-FR15CBT4.2/5.0 Version 2.0

## 3.6.4 Test Setup



## 3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910 Page Number : 32 of 35
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Report No.: FR942424B

## 3.7 Antenna Requirements

## 3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

Report No.: FR942424B

## 3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

#### 3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

Sporton International (Shenzhen) Inc. TEL: +86-755-86379589

FAX: +86-755-86379595

: Rev. 01 Report Version FCC ID: V5PA910 Report Template No.: BU5-FR15CBT4.2/5.0 Version 2.0

Page Number

: 33 of 35

Report Issued Date: Jun. 19, 2019

# 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP30	101400	10Hz~30GHz	Dec. 22, 2018	May 03, 2019~ Jun. 11, 2019	Dec. 21, 2019	Conducted (TH01-SZ)
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 18, 2019	May 03, 2019~ Jun. 11, 2019	Apr. 17, 2020	Conducted (TH01-SZ)
Pulse Power Senor	Anritsu	MA2411B	1207253	30MHz~40GHz	Dec. 22, 2018	May 03, 2019~ Jun. 11, 2019	Dec. 21, 2019	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Dec. 22, 2018	May 03, 2019~ Jun. 11, 2019	Dec. 21, 2019	Conducted (TH01-SZ)
EMI Test Receiver	R&S	ESR7	101404	9kHz~7GHz	Apr. 18, 2019	Jun. 11, 2019	Apr. 17, 2020	Radiation (03CH04-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY551502 13	10Hz~44GHz	Apr. 18, 2019	Jun. 11, 2019	Apr. 17, 2020	Radiation (03CH04-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	May 29, 2018	Jun. 11, 2019	May 29, 2020	Radiation (03CH04-SZ)
Bilog Antenna	TeseQ	CBL6111D	41909	30MHz~1GHz	Aug. 28, 2018	Jun. 11, 2019	Aug. 27, 2019	Radiation (03CH04-SZ)
Double Ridge Horn Antenna	SCHWARZBE CK	BBHA9120D	9120D-147 4	1GHz~18GHz	Feb. 07, 2019	Jun. 11, 2019	Feb. 06, 2020	Radiation (03CH04-SZ)
Horn Antenna	SCHWARZBE CK	BBHA9170	9170#679	15GHz~40GHz	Apr. 20, 2019	Jun. 11, 2019	Apr. 19, 2020	Radiation (03CH04-SZ)
Amplifier	Burgeon	BPA-530	102211	0.01Hz ~3000MHz	Oct. 18, 2018	Jun. 11, 2019	Oct. 17, 2019	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	AMF-7D-0010 1800-30-10P- R	1989346	1GHz~18GHz	Jul. 30, 2018	Jun. 11, 2019	Jul. 29, 2019	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	TTA1840-35- HG	1988315	18GHz~40GHz	Jul. 26, 2018	Jun. 11, 2019	Jul. 25, 2019	Radiation (03CH04-SZ)
Amplifier	Agilent Technologies	83017A	MY532701 56	500MHz~26.5G Hz	Apr. 20 2019	Jun. 11, 2019	Apr. 19, 2020	Radiation (03CH04-SZ)
AC Power Source	Chroma	61601	N/A	N/A	NCR	Jun. 11, 2019	NCR	Radiation (03CH04-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jun. 11, 2019	NCR	Radiation (03CH04-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jun. 11, 2019	NCR	Radiation (03CH04-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Dec. 23, 2018	May 08, 2019	Dec. 22, 2019	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103912	9kHz~30MHz	Oct. 18, 2018	May 08, 2019	Oct. 17, 2019	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	EMCO	3816/2SH	00103892	9kHz~30MHz	Dec. 23, 2018	May 08, 2019	Dec. 22, 2019	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000 891	100Vac~250Vac	Jul. 18, 2018	May 08, 2019	Jul. 17, 2019	Conduction (CO01-SZ)

NCR: No Calibration Required

Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910 Page Number : 34 of 35
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Report No.: FR942424B

# 5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

#### <u>Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)</u>

Measuring Uncertainty for a Level of Confidence	2.6 dB
of 95% $(U = 2Uc(y))$	2.0 dB

#### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

	1
Measuring Uncertainty for a Level of Confidence	5 0 JD
1	5.0 dB
of 95% (U = 2Uc(y))	

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

ı		
	Measuring Uncertainty for a Level of Confidence	<u> </u>
	<u> </u>	4.8 dB
	of 95% (U = 2Uc(y))	410 42
	01 30 /0 (0 <b>– 2</b> 00(y))	1

#### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence	5.1 dB
of 95% (U = 2Uc(y))	3.1 dB

**Sporton International (Shenzhen) Inc.** TEL: +86-755-86379589

FAX: +86-755-86379595 FCC ID: V5PA910 Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Page Number

Report Template No.: BU5-FR15CBT4.2/5.0 Version 2.0

: 35 of 35

Report No.: FR942424B

# **Appendix A. Conducted test results**

Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910 Page Number : A1 of A1
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Report No.: FR942424B

Report Number : FR942424B

Test Engineer:	Zhang Jiang	Temperature:	24~26	°C
Test Date:	2019/5/3~2019/6/11	Relative Humidity:	50~53	%

### TEST RESULTS DATA 6dB and 99% Occupied Bandwidth

Mod.	Data Rate	N⊤x	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail	
BLE	1Mbps	1	0	2402	1.023	0.633	0.50	Pass	
BLE	1Mbps	1	19	2440	1.021	0.633	0.50	Pass	
BLE	1Mbps	1	39	2480	1.023	0.633	0.50	Pass	

# TEST RESULTS DATA Average Power Table (Reporting Only)


Mod.	Data Rate	N⊤x	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	1Mbps	1	0	2402	1.98	-1.40
BLE	1Mbps	1	19	2440	1.98	-1.00
BLE	1Mbps	1	39	2480	1.98	-2.40

# TEST RESULTS DATA Peak Power Density

Mod.	Data Rate	N⊤x	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	-1.46	-18.09	0.80	8.00	Pass
BLE	1Mbps	1	19	2440	-1.03	-17.65	0.80	8.00	Pass
BLE	1Mbps	1	39	2480	-2.19	-18.80	0.80	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.

## **Appendix B. AC Conducted Emission Test Results**



Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910 Page Number : B1 of B2
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Report No.: FR942424B

Temperature : **22~25**℃ Test Engineer: Liuda Lin Relative Humidity: 50~55% Test Voltage: 120Vac / 60Hz Phase: Neutral 100 Level (dBuV) Date: 2019-05-08 90 80 70 60 50 20 10 2 Frequency (MHz) 10

Site : CO01-SZ

Condition: FCC 15C\_QP LISN\_20180719\_N NEUTRAL

		Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
		MHz	dBu₹	dB	dBu∀	dBu∀	dB	dB	
1	*	0.61	38.60	-7.40	46.00	28.40	0.02	10.18	Average
2		0.61	47.40	-8.60	56.00	37.20	0.02	10.18	QP
3		0.66	34.90	-11.10	46.00	24.70	0.02	10.18	Average
4		0.66	42.70	-13.30	56.00	32.50	0.02	10.18	QP
5		0.71	35.30	-10.70	46.00	25.10	0.02	10.18	Average
6		0.71	43.90	-12.10	56.00	33.70	0.02	10.18	QP
7		1.30	22.83	-23.17	46.00	12.60	0.05	10.18	Average
8		1.30	37.63	-18.37	56.00	27.40	0.05	10.18	QP
9		11.26	34.97	-15.03	50.00	24.50	0.21	10.26	Average
10		11.26	52.47	-7.53	60.00	42.00	0.21	10.26	QP
11		15.89	39.95	-10.05	50.00	29.30	0.38	10.27	Average
12		15.89	52.15	-7.85	60.00	41.50	0.38	10.27	QP
13		25.59	25.35	-24.65	50.00	14.00	1.03	10.32	Average
14		25.59	38.65	-21.35	60.00	27.30	1.03	10.32	QP

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910 Page Number : B2 of B2
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Report No.: FR942424B

# Appendix C. Radiated Spurious Emission

# 2.4GHz 2400~2483.5MHz

## BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	( dBµV/m )	(dB)	( dBµV/m )	(dBµV)	( dB/m )	( dB )	( dB )	( cm )	(deg)	(P/A)	(H/V)
		2329.22	48.35	-25.65	74	49.23	27.77	4.66	33.31	112	113	Р	Н
		2379.20	38.87	-15.13	54	39.71	27.72	4.72	33.28	112	113	Α	Н
BLE	*	2402	102.9	-	-	103.68	27.7	4.78	33.26	112	113	Р	Н
CH 00	*	2402	101.43	-	-	102.21	27.7	4.78	33.26	112	113	Α	Н
2402MHz		2374.37	49.19	-24.81	74	50.03	27.72	4.72	33.28	100	16	Р	V
2402111112		2357.36	38.79	-15.21	54	39.62	27.74	4.72	33.29	100	16	Α	V
	*	2402	102.56	-	-	103.34	27.7	4.78	33.26	100	16	Р	V
	*	2402	101.85	-	-	102.63	27.7	4.78	33.26	100	16	Α	V
		2377.9	48.13	-25.87	74	48.97	27.72	4.72	33.28	100	111	Р	Н
		2374.96	38.77	-15.23	54	39.61	27.72	4.72	33.28	100	111	Α	Н
	*	2440	102.74	-	-	103.5	27.66	4.82	33.24	100	111	Р	Н
	*	2440	101.9	-	-	102.66	27.66	4.82	33.24	100	111	Α	Н
		2492.51	47.67	-26.33	74	48.41	27.61	4.85	33.2	100	111	Р	Н
BLE		2485.37	38.81	-15.19	54	39.55	27.63	4.85	33.22	100	111	Α	Н
CH 19 2440MHz		2363.48	49.15	-24.85	74	49.98	27.74	4.72	33.29	112	16	Р	٧
244UIVII12		2379.3	38.81	-15.19	54	39.65	27.72	4.72	33.28	112	16	Α	V
	*	2440	103.05	-	-	103.81	27.66	4.82	33.24	112	16	Р	٧
	*	2440	102.32	-	-	103.08	27.66	4.82	33.24	112	16	Α	V
		2496.01	48.55	-25.45	74	49.29	27.61	4.85	33.2	112	16	Р	V
		2491.95	38.66	-15.34	54	39.4	27.61	4.85	33.2	112	16	Α	V

Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910 Page Number : C1 of C6
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Report No.: FR942424B



	*	0.400	400.04			100.50	07.00	4.05	00.00	400	444	_	
		2480	102.84	-	-	103.58	27.63	4.85	33.22	103	111	Р	Н
	*	2480	101.53	-	-	102.27	27.63	4.85	33.22	103	111	Α	Н
51.5		2483.52	50.36	-23.64	74	51.1	27.63	4.85	33.22	103	111	Р	Н
BLE		2483.52	40.72	-13.28	54	41.46	27.63	4.85	33.22	103	111	Α	Н
CH 39 2480MHz	*	2480	103.26	-	-	104	27.63	4.85	33.22	106	15	Р	V
2400WII 12	*	2480	102.61	-	-	103.35	27.63	4.85	33.22	106	15	Α	V
		2484.36	50.14	-23.86	74	50.88	27.63	4.85	33.22	106	15	Р	V
		2483.52	41.06	-12.94	54	41.8	27.63	4.85	33.22	106	15	Α	V
Remark		o other spurio											
	2. A	ll results are P	ASS again	st Peak	and Avera	ge limit lind	e.						

Report No. : FR942424B

: C2 of C6

Report Issued Date : Jun. 19, 2019

Page Number

Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595

Report Version : Rev. 01 FCC ID: V5PA910 Report Template No.: BU5-FR15CBT4.2/5.0 Version 2.0

All results are PASS against Peak and Average limit line.

### 2.4GHz 2400~2483.5MHz

## BLE (Harmonic @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
		( MHz )	( dBµV/m )	Limit (dB)	Line ( dBµV/m )	Level ( dBµV )	Factor ( dB/m )	Loss (dB)	Factor ( dB )	Pos ( cm )		Avg. (P/A)	
BLE		4804	39.28	-34.72	74	59.48	31.72	5.55	57.47	151	219	Р	Н
CH 00 2402MHz		4804	40.35	-33.65	74	60.55	31.72	5.55	57.47	178	97	Р	V
BLE CH 19 2440MHz		4880	39.16	-34.84	74	59.15	31.88	5.65	57.52	164	214	Р	Н
		7320	43.08	-30.92	74	57.81	36.94	7.26	58.93	168	336	Р	Н
		4880	38.89	-35.11	74	58.88	31.88	5.65	57.52	150	258	Р	V
		7320	44.48	-29.52	74	59.21	36.94	7.26	58.93	152	309	Р	V
BLE CH 39 2480MHz		4960	38.17	-35.83	74	57.71	32.08	5.96	57.58	118	289	Р	Н
		7440	41.43	-32.57	74	55.84	37.4	7.17	58.98	158	273	Р	Н
		4960	40.04	-33.96	74	59.58	32.08	5.96	57.58	120	269	Р	٧
		7440	44.37	-29.63	74	58.78	37.4	7.17	58.98	184	278	Р	V

## Remark

Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595

FCC ID: V5PA910

Page Number : C3 of C6
Report Issued Date : Jun. 19, 2019

Report No.: FR942424B

Report Version : Rev. 01

<sup>.</sup> No other spurious found.

<sup>2.</sup> All results are PASS against Peak and Average limit line.

# **Emission below 1GHz**

## 2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	( dBµV/m )	(dB)	$(dB\mu V/m)$	(dBµV)	( dB/m )	( dB )	( dB )	( cm )	(deg)	(P/A)	(H/V)
		30	23.64	-16.36	40	30.69	24.8	0.25	32.1	100	99	Р	Н
		138.64	24.6	-18.9	43.5	37.78	17.5	1.23	31.91	-	-	Р	Н
		159.01	22.19	-21.31	43.5	36.26	16.45	1.3	31.82	-	-	Р	Н
		184.23	21.59	-21.91	43.5	36.99	15.02	1.45	31.87	-	-	Р	Н
0.4011-		393.75	22.64	-23.36	46	30.83	21.66	2.15	32	-	-	Р	Н
2.4GHz BLE		975.75	34.33	-19.67	54	31.71	30.21	3.52	31.11	-	-	Р	Н
LF		30	26.56	-13.44	40	33.61	24.8	0.25	32.1	-	-	Р	V
Lr		52.31	29.48	-10.52	40	46.47	13.72	0.69	31.4	100	144	Р	V
		159.98	21.2	-22.3	43.5	35.32	16.4	1.3	31.82	-	-	Р	V
		200.72	19.18	-24.32	43.5	34.36	15.11	1.61	31.9	-	-	Р	V
		269.59	20.62	-25.38	46	30.99	19.73	1.76	31.86	-	•	Р	V
		628.49	28.86	-17.14	46	31.69	26.05	2.77	31.65	-	-	Р	V
	1. No	o other spurio	us found.									•	

# Remark 2.

TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910

Page Number : C4 of C6 Report Issued Date : Jun. 19, 2019 Report Version : Rev. 01

Report No. : FR942424B

All results are PASS against limit line.

## Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any
	unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	Peak or Average
H/V	Horizontal or Vertical

Sporton International (Shenzhen) Inc.

TEL: +86-755-86379589 FAX: +86-755-86379595

FCC ID: V5PA910

Page Number : C5 of C6
Report Issued Date : Jun. 19, 2019

Report No. : FR942424B

Report Version : Rev. 01

## A calculation example for radiated spurious emission is shown as below:

Report No.: FR942424B

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	( dBµV/m )	(dB)	(dBµV/m)	(dB <sub>µ</sub> V)	( dB/m )	( dB )	( dB )	( cm )	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	Р	Н
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	Α	Н

1. Level( $dB\mu V/m$ ) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBµV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dB $\mu$ V/m) – Limit Line(dB $\mu$ V/m)

#### For Peak Limit @ 2390MHz:

- 1. Level(dBµV/m)
- = Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBµV) Preamp Factor(dB)
- $= 32.22(dB/m) + 4.58(dB) + 54.51(dB\mu V) 35.86 (dB)$
- $= 55.45 (dB\mu V/m)$
- 2. Over Limit(dB)
- = Level(dBµV/m) Limit Line(dBµV/m)
- $= 55.45(dB\mu V/m) 74(dB\mu V/m)$
- = -18.55(dB)

### For Average Limit @ 2390MHz:

- 1. Level(dBµV/m)
- = Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBµV) Preamp Factor(dB)
- $= 32.22(dB/m) + 4.58(dB) + 42.6(dB\mu V) 35.86 (dB)$
- $= 43.54 (dB\mu V/m)$
- 2. Over Limit(dB)
- = Level( $dB\mu V/m$ ) Limit Line( $dB\mu V/m$ )
- $= 43.54(dB\mu V/m) 54(dB\mu V/m)$
- = -10.46(dB)

Both peak and average measured complies with the limit line, so test result is "PASS".

 Sporton International (Shenzhen) Inc.
 Page Number
 : C6 of C6


 TEL: +86-755-86379589
 Report Issued Date
 : Jun. 19, 2019

 FAX: +86-755-86379595
 Report Version
 : Rev. 01

FCC ID: V5PA910 Report Template No.: BU5-FR15CBT4.2/5.0 Version 2.0

# Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting		
Bluetooth LE	63.46	0.396	2.525	3KHz		



TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: V5PA910 Page Number : D1 of D1
Report Issued Date : Jun. 19, 2019
Report Version : Rev. 01

Report No.: FR942424B