



# FCC RF Test Report

**APPLICANT** : PAX Technology Limited  
**EQUIPMENT** : Mobile Payment Terminal  
**BRAND NAME** : PAX  
**MODEL NAME** : D200  
**MARKETING NAME** : D200  
**FCC ID** : V5PD200V4  
**STANDARD** : FCC Part 15 Subpart C §15.225  
**CLASSIFICATION** : (DXX) Low Power Communication Device Transmitter

The testing was completed on Nov. 22, 2016. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

Prepared by: Eric Shih / Manager

Approved by: Jones Tsai / Manager

**SPORTON INTERNATIONAL (SHENZHEN) INC.**  
1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town,  
Nanshan District, Shenzhen, Guangdong, P. R. China





## TABLE OF CONTENTS

<b>SUMMARY OF THE TEST RESULT .....</b>	<b>4</b>
<b>1. GENERAL INFORMATION.....</b>	<b>5</b>
1.1    Applicant.....	5
1.2    Manufacturer .....	5
1.3    Product Feature of Equipment Under Test.....	5
1.4    Product Specification of Equipment Under Test.....	5
1.5    Modification of EUT .....	6
1.6    Testing Location .....	6
1.7    Applicable Standards.....	6
<b>2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>	<b>7</b>
2.1    Descriptions of Test Mode.....	7
2.2    Connection Diagram of Test System.....	7
2.3    Table for Supporting Units.....	8
2.4    EUT Operation Test Setup .....	8
<b>3. TEST RESULTS.....</b>	<b>9</b>
3.1    AC Power Line Conducted Emissions Measurement.....	9
3.2    20dB and 99% OBW Spectrum Bandwidth Measurement.....	11
3.3    Frequency Stability Measurement .....	12
3.4    Field Strength of Fundamental Emissions and Mask Measurement.....	13
3.5    Radiated Emissions Measurement.....	15
3.6    Antenna Requirements.....	18
<b>4. LIST OF MEASURING EQUIPMENT .....</b>	<b>19</b>

### APPENDIX A. TEST RESULTS OF CONDUCTED EMISSION TEST

### APPENDIX B. TEST RESULTS OF CONDUCTED TEST ITEMS

- B1. Test Result of 20dB Spectrum Bandwidth
- B2. Test Result of Frequency Stability

### APPENDIX C. TEST RESULTS OF RADIATED TEST ITEMS

- C1. Test Result of Field Strength of Fundamental Emissions
- C2. Results of Radiated Emissions (9 kHz~30MHz)
- C3. Results of Radiated Emissions (30MHz~1GHz)

### APPENDIX D. SETUP PHOTOGRAPHS



# REVISION HISTORY



## SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C / IC RSS-210 issue 9					
Part	FCC Rule	IC Rule	Description of Test	Result	Under Limit
3.1	15.207	RSS-GEN 8.8	AC Power Line Conducted Emissions	Complies	10.73 dB at 0.990MHz
3.2	15.215(c)	-	20dB Spectrum Bandwidth	Complies	-
	-	RSS-GEN 6.6	99% OBW Spectrum Bandwidth	Complies	-
3.3	15.225(e)	B.6	Frequency Stability	Complies	-
3.4	15.225(a)(b)(c)	B.6	Field Strength of Fundamental Emissions	Complies	57.63 dB at 13.560 MHz
3.5	15.225(d) 15.209	B.6	Radiated Emissions	Complies	5.11 dB at 57.160 MHz for Quasi-Peak
3.6	15.203	-	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.5dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±5.1dB	Confidence levels of 95%



## 1. GENERAL INFORMATION

### 1.1 Applicant

**PAX Technology Limited**

Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour Road, Wanchai, Hong Kong

### 1.2 Manufacturer

**PAX Computer Technology (Shenzhen) Co., Ltd.**

4/F, No.3 Building, Software Park, Second Central Science-Tech Road, High-Tech industrial Park, Shenzhen, Guangdong, P.R.C.

### 1.3 Product Feature of Equipment Under Test

Product Feature	
<b>Equipment</b>	Mobile Payment Terminal
<b>Brand Name</b>	PAX
<b>Model Name</b>	D200
<b>Marketing Name</b>	D200
<b>FCC ID</b>	V5PD200V4
<b>EUT supports Radios application</b>	GPGRS/EGPRS/WCDMA/HSPA/HSPA+ (16QAM uplink is not supported)/NFC WLAN2.4GHz 802.11b/g/n HT20 Bluetooth v3.0+EDR/v4.0 LE
<b>IMEI Code</b>	Conducted: N/A Conduction: 354524043890848 Radiated: 354524043787499
<b>EUT Stage</b>	Production Unit

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

### 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx/Rx Frequency Range</b>	13.553 ~ 13.567MHz
<b>Channel Number</b>	1
<b>20dBW</b>	2.64kHz
<b>99%OBW</b>	2.24kHz
<b>Antenna Type</b>	Loop Antenna
<b>Type of Modulation</b>	ASK

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6 Testing Location

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595	
Test Site No.	<b>Sporton Site No.</b>	
	TH01-SZ	CO01-SZ
Test Engineer	Wilson Chen	
Temperature	24~26°C	
Relative Humidity	50~53%	

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755-3320-2398	
Test Site No.	<b>Sporton Site No.</b>	<b>FCC/IC Registration No.</b>
	03CH03-SZ	565805/4086F
Test Engineer	Jeff Yao	
Temperature	23~25°C	
Relative Humidity	48~52%	

**Note:** The test site complies with ANSI C63.4 2014 requirement.

## 1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.225
- ♦ ANSI C63.10-2013
- ♦ IC RSS-210 Issue 9
- ♦ IC RSS-Gen Issue 4

## 2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST

### 2.1 Descriptions of Test Mode

Investigation has been done on all the possible configurations for searching the worst cases.


The following table is a list of the test modes shown in this test report.

Test Items	
AC Power Line Conducted Emissions	Field Strength of Fundamental Emissions
20dB Spectrum Bandwidth	Frequency Stability
Radiated Emissions 9kHz~30MHz	Radiated Emissions 30MHz~1GHz


The EUT pre-scanned in three NFC type, A, B, F. Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration (Z plane as worst plane) from all possible combinations.

### 2.2 Connection Diagram of Test System

#### <AC Conducted Emissions>



## &lt; For Fundamental Emissions and Mask and Radiated Emissions Measurement &gt;



## 2.3 Table for Supporting Units

Support Unit	Manufacturer	Model	FCC ID
System Simulator	Anritsu	MT8820C	N/A
WLAN AP	D-Link	DIR-820L	KA2IR820LA1
NOTE BOOK	Lenovo	E540	FCC DoC
Mobile Phone	Huawei	mate 8	QWSEVA-L09

## 2.4 EUT Operation Test Setup

The EUT was programmed to be in continuously transmitting mode.

The ancillary equipment, NFC card, is used to make the EUT (NFC) continuously transmit at 13.56MHz and is placed around 3 cm gap to the EUT.



### 3. TEST RESULTS

#### 3.1 AC Power Line Conducted Emissions Measurement

##### 3.1.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

For terminal test result, the testing follows FCC KDB 174176.


##### 3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

##### 3.1.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.1.4 Test setup



### 3.1.5 Test Result of AC Conducted Emission

Please refer to Appendix A.

## 3.2 20dB and 99% OBW Spectrum Bandwidth Measurement

### 3.2.1 Limit

Intentional radiators must be designed to ensure that the 20dB and 99% emission bandwidth in the specific band 13.553~13.567MHz.


### 3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.2.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
2. The resolution bandwidth of 1 kHz and the video bandwidth of 3 kHz were used.
3. Measured the spectrum width with power higher than 20dB below carrier.
4. Measured the 99% OBW.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Conducted Test Items

Please refer to Appendix B.

### 3.3 Frequency Stability Measurement

#### 3.3.1 Limit

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.


#### 3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.3.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT.
2. EUT have transmitted signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire emissions bandwidth.
4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
5. The fc is declaring of channel frequency. Then the frequency error formula is  $(fc-f)/fc \times 10^6$  ppm and the limit is less than  $\pm 100$  ppm.
6. Extreme temperature rule is  $-20^{\circ}\text{C} \sim 50^{\circ}\text{C}$ .

#### 3.3.4 Test Setup



#### 3.3.5 Test Result of Conducted Test Items

Please refer to Appendix C.



### 3.4 Field Strength of Fundamental Emissions and Mask Measurement

#### 3.4.1 Limit

Rules and specifications	FCC CFR 47 Part 15 section 15.225 IC RSS-210 B.6			
Description	Compliance with the spectrum mask is tested with RBW set to 9kHz.			
Freq. of Emission (MHz)	Field Strength ( $\mu$ V/m) at 30m	Field Strength (dB $\mu$ V/m) at 30m	Field Strength (dB $\mu$ V/m) at 10m	Field Strength (dB $\mu$ V/m) at 3m
1.705~13.110	30	29.5	48.58	69.5
13.110~13.410	106	40.5	59.58	80.5
13.410~13.553	334	50.5	69.58	90.5
13.553~13.567	15848	84.0	103.08	124.0
13.567~13.710	334	50.5	69.58	90.5
13.710~14.010	106	40.5	59.58	80.5
14.010~30.000	30	29.5	48.58	69.5

#### 3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.4.3 Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the receiving antenna was fixed at one meter above ground to find the maximum emissions field strength.
4. For Fundamental emissions, use the receiver to measure QP reading.

5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
6. Compliance with the spectrum mask is tested with RBW set to 9kHz.

Note: Emission level (dB $\mu$ V/m) = 20 log Emission level ( $\mu$ V/m).

#### 3.4.4 Test Setup

For radiated emissions below 30MHz



#### 3.4.5 Test Result of Field Strength of Fundamental Emissions and Mask

Please refer to Appendix C.



## 3.5 Radiated Emissions Measurement

### 3.5.1 Limit

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

Frequencies (MHz)	Field Strength ( $\mu$ V/m)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.5.3 Measuring Instrument Setting

The following table is the setting of receiver.

Receiver Parameter	Setting
Attenuation	Auto
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

**Note:** The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.




### 3.5.4 Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
1. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
2. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
3. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
4. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
6. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. Antenna Requirements

### 3.5.5 Test Setup

For radiated emissions below 30MHz



For radiated emissions above 30MHz



### 3.5.6 Test Result of Radiated Emissions Measurement

Please refer to Appendix C.



## 3.6 Antenna Requirements

### 3.6.1 Standard Applicable

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

### 3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.




## 4. LIST OF MEASURING EQUIPMENT

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Oct. 13, 2016	Nov. 10, 2016~Nov. 14, 2016	Oct. 12, 2017	Conducted (TH01-KS)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Jul. 16, 2016	Nov. 10, 2016~Nov. 14, 2016	Jul. 15, 2017	Conducted (TH01-SZ)
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY54450083	20Hz~8.4GHz	May 07, 2016	Nov. 21, 2016~Nov. 22, 2016	May 06, 2017	Radiation (03CH03-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	May 07, 2016	Nov. 21, 2016~Nov. 22, 2016	May 06, 2017	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz~2GHz	May 21, 2016	Nov. 21, 2016~Nov. 22, 2016	May 20, 2017	Radiation (03CH03-SZ)
Amplifier	Burgeon	BPA-530	102210	0.01Hz~3000MHz	Oct. 11, 2016	Nov. 21, 2016~Nov. 22, 2016	Oct. 10, 2017	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	Nov. 21, 2016~Nov. 22, 2016	NCR	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Nov. 21, 2016~Nov. 22, 2016	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Nov. 21, 2016~Nov. 22, 2016	NCR	Radiation (03CH03-SZ)
EMI Receiver	R&S	ESCI7	100724	9kHz~3GHz	Nov. 23, 2015	Nov. 10, 2016	Nov. 22, 2016	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103892	9kHz~30MHz	Jan.12, 2016	Nov. 10, 2016	Jan. 11, 2017	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	MessTec	3816/2SH	00103912	9kHz~30MHz	Jan.12, 2016	Nov. 10, 2016	Jan. 11, 2017	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 16, 2016	Nov. 10, 2016	Jul. 15, 2017	Conduction (CO01-SZ)
Pulse Limiter	COM-POWER	LIT-153 Transient Limiter	53139	150kHz~30MHz	Oct. 11, 2016	Nov. 10, 2016	Oct. 10, 2017	Conduction (CO01-SZ)

NCR: No Calibration Required



## Appendix A. Test Results of Conducted Emission Test



(1) with antenna

Remark: 13.56MHz is the NFC RF fundamental signal.



Test Mode :	NFC Tx	Test Voltage :	120Vac / 60Hz
Function Type :	GPRS1900 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + NFC Tx		

Level (dBuV) Date: 2016-11-10 Time: 15:58:02

Frequency (MHz)


Site : CO01-SZ  
Condition: FCC 15C QP LISN\_20160509 NEUTRAL

IMEI : 354524043890848

Freq	Level	Over	Limit	Read	LISN	Cable	Remark
		Line	dBuV	Level	Factor	dB	
MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.59	32.30	-13.70	46.00	22.00	0.11	10.19 Average
2	0.59	42.70	-13.30	56.00	32.40	0.11	10.19 QP
3	0.65	32.38	-13.62	46.00	22.10	0.11	10.17 Average
4	0.65	40.58	-15.42	56.00	30.30	0.11	10.17 QP
5	0.70	33.07	-12.93	46.00	22.80	0.11	10.16 Average
6	0.70	43.17	-12.83	56.00	32.90	0.11	10.16 QP
7	0.78	31.57	-14.43	46.00	21.30	0.11	10.16 Average
8	0.78	43.67	-12.33	56.00	33.40	0.11	10.16 QP
9	0.82	33.07	-12.93	46.00	22.80	0.11	10.16 Average
10	0.82	43.97	-12.03	56.00	33.70	0.11	10.16 QP
11	0.88	33.87	-12.13	46.00	23.60	0.11	10.16 Average
12	0.88	44.37	-11.63	56.00	34.10	0.11	10.16 QP
13	0.99	34.67	-11.33	46.00	24.40	0.11	10.16 Average
14	0.99	45.27	-10.73	56.00	35.00	0.11	10.16 QP
15	1.13	33.97	-12.03	46.00	23.70	0.11	10.16 Average
16	1.13	44.57	-11.43	56.00	34.30	0.11	10.16 QP
17	1.25	32.87	-13.13	46.00	22.60	0.11	10.16 Average
18	1.25	44.07	-11.93	56.00	33.80	0.11	10.16 QP
19	1.37	30.87	-15.13	46.00	20.60	0.11	10.16 Average
20	1.37	41.07	-14.93	56.00	30.80	0.11	10.16 QP
21	2.27	32.99	-13.01	46.00	22.70	0.11	10.18 Average
22	2.27	42.09	-13.91	56.00	31.80	0.11	10.18 QP
23 *	13.56	59.58	9.58	50.00	48.90	0.29	10.39 Average
24 !	13.56	65.08	5.08	60.00	54.40	0.29	10.39 QP


(1) with antenna

Remark: 13.56MHz is the NFC RF fundamental signal.



(2) With dummy load

Remark: Only the fundamental NFC signal needs to be retested per C63.4.





(2) With dummy load

Remark: Only the fundamental NFC signal needs to be retested per C63.4.

## Appendix B. Test Results of Conducted Test Items

### B1. Test Result of 20dB Spectrum Bandwidth

Test mode	NFC Tx	Test Frequency (MHz)	13.56
			
Ref 10 dBm Att 40 dB SWT 20 ms	Ref 10 dBm Att 30 dB SWT 20 ms	Marker 1 [T1]	Marker 1 [T1]
*RBW 1 kHz *VBW 3 kHz	*RBW 1 kHz *VBW 3 kHz	3.36 dBm	2.81 dBm
Temp 1 [T1] 13.558940000 MHz	Temp 1 [T1 OBW] 13.559140000 MHz		
Temp 2 [T1] -16.78 dBm	Temp 2 [T1 OBW] -11.93 dBm		
Temp 3 [T1] 13.561580000 MHz	Temp 3 [T1 OBW] 13.561380000 MHz		
Temp 4 [T1] -16.46 dBm	Temp 4 [T1 OBW] -11.35 dBm		
Span 10 kHz	Span 10 kHz	3dB	3dB
Center 13.56 MHz	Center 13.56 MHz	1 kHz/	1 kHz/
Date: 14.NOV.2016 09:49:15	Date: 11.NOV.2016 17:47:21		
<b>20dB Bandwidth (kHz)</b>	2.64	<b>99% OccupiedBW(kHz)</b>	2.24
<b>Frequency range (MHz)</b>	<b>f<sub>L</sub> &gt; 13.553</b>	13.55894	<b>Test Result</b>
	<b>f<sub>H</sub> &lt; 13.567</b>	13.56158	<b>Complies</b>





## B2. Test Result of Frequency Stability

Voltage vs. Frequency Stability		Temperature vs. Frequency Stability	
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (°C)	Measurement Frequency (MHz)
120	13.56026	-20	13.56026
102	13.56026	-10	13.56026
138	13.56027	0	13.56027
-	-	10	13.56028
-	-	20	13.56026
-	-	30	13.56026
-	-	40	13.56026
-	-	50	13.56026
<b>Max.Deviation (MHz)</b>	0.00027	<b>Max.Deviation (MHz)</b>	0.00028
<b>Max.Deviation (ppm)</b>	19.9115	<b>Max.Deviation (ppm)</b>	20.649
<b>Limit</b>	<b>FS &lt; ±100 ppm</b>	<b>Limit</b>	<b>FS &lt; ±100 ppm</b>
<b>Test Result</b>	<b>PASS</b>	<b>Test Result</b>	<b>PASS</b>



## Appendix C. Test Results of Radiated Test Items

### C1. Test Result of Field Strength of Fundamental Emissions

Test Mode :	NFC Tx	Test Frequency (MHz)	13.56
Level (dBuV/m)			Date: 2016-11-21
			
Site : 03CH03-SZ Condition : 15.225 LIMIT 3m LOOP ANT_161121 HORIZONTAL Detector : Peak			
Plane : Z Full : adapter			
Freq Freq Level Level Over Limit Limit ReadAntenna Antenna Cable Cable A/Pos A/Pos T/Pos T/Pos Remark			
MHz dBuV/m dB dBuV/m dBuV dB/m dB dB cm deg			
1 13.56 66.37 -57.63 124.00 45.55 20.40 0.42 --- --- QP			
Level (dBuV/m)			Date: 2016-11-21
			
Site : 03CH03-SZ Condition : 15.225 LIMIT 3m LOOP ANT_161121 VERTICAL Detector : Peak			
Plane : Z Full : adapter			
Freq Freq Level Level Over Limit Limit ReadAntenna Antenna Cable Cable A/Pos A/Pos T/Pos T/Pos Remark			
MHz dBuV/m dB dBuV/m dBuV dB/m dB dB cm deg			
1 13.56 63.86 -60.14 124.00 43.04 20.40 0.42 --- --- QP			



## C2. Results of Radiated Spurious Emissions (9 kHz~30MHz)

Test Mode :		NFC Tx		Polarization :		Horizontal			
-------------	--	--------	--	----------------	--	------------	--	--	--

Frequency ( MHz )	Level ( dB $\mu$ V/m )	Over Limit ( dB )	Limit Line ( dB $\mu$ V/m )	Read Level ( dB $\mu$ V )	Antenna Factor ( dB )	Cable Loss ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
0.02007	44.66	-76.9	121.56	23.51	21	0.15	-	-	Average
0.07134	44.98	-65.56	110.54	23.73	21.1	0.15	-	-	Average
0.09519	40.49	-67.54	108.03	19.14	21.2	0.15	-	-	QP
0.12	33.82	-72.2	106.02	12.57	21.1	0.15	-	-	Average
0.15	43.96	-60.12	104.08	22.81	21	0.15	-	-	Average
4.61	34.27	-35.73	70	13.35	20.66	0.26	-	-	QP
14.064	36.11	-33.89	70	15.39	20.29	0.43	-	-	QP
18.403	32.77	-37.23	70	12.05	20.24	0.48	-	-	QP
25.495	32.95	-37.05	70	11.59	20.78	0.58	-	-	QP

Test Mode :		NFC Tx		Polarization :		Vertical			
-------------	--	--------	--	----------------	--	----------	--	--	--

Frequency ( MHz )	Level ( dB $\mu$ V/m )	Over Limit ( dB )	Limit Line ( dB $\mu$ V/m )	Read Level ( dB $\mu$ V )	Antenna Factor ( dB )	Cable Loss ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
0.02007	44.91	-76.65	121.56	23.76	21	0.15	-	-	Average
0.06024	43.75	-68.26	112.01	22.5	21.1	0.15	-	-	Average
0.0951	33.87	-74.17	108.04	12.52	21.2	0.15	-	-	QP
0.1263	29.16	-76.42	105.58	7.91	21.1	0.15	-	-	Average
0.15555	42.97	-60.8	103.77	21.82	21	0.15	-	-	Average
6.506	34.82	-35.18	70	13.89	20.64	0.29	-	-	QP
13.984	36.74	-33.26	70	16.01	20.31	0.42	-	-	QP
16.576	33.68	-36.32	70	13.06	20.16	0.46	-	-	QP
25.04	33.68	-36.32	70	12.22	20.89	0.57	-	-	QP

## Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB);
3. Limit line = specific limits (dB $\mu$ V) + distance extrapolation factor.



## C3. Results of Radiated Spurious Emissions (30MHz~1GHz)

Test Mode :		NFC Tx		Polarization :		Horizontal			
Frequency ( MHz )	Level ( dB $\mu$ V/m )	Over Limit ( dB )	Limit Line ( dB $\mu$ V/m )	Read Level ( dB $\mu$ V )	Antenna Factor ( dB )	Cable Loss ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
99.84	33.95	-9.55	43.5	44.76	18.8	0.99	-	-	Peak
230.79	29.57	-16.43	46	41.56	17.08	1.4	-	-	Peak
333.61	34.13	-11.87	46	42.81	19.98	1.71	-	-	Peak
600.36	34.11	-11.89	46	36.76	25.1	2.25	-	-	Peak
800.18	36.9	-9.1	46	36.61	27.4	2.59	-	-	Peak
867.11	37.19	-8.81	46	6.24	28.24	2.71	100	0	Peak

Test Mode :		NFC Tx		Polarization :		Vertical			
Frequency ( MHz )	Level ( dB $\mu$ V/m )	Over Limit ( dB )	Limit Line ( dB $\mu$ V/m )	Read Level ( dB $\mu$ V )	Antenna Factor ( dB )	Cable Loss ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
57.16	34.89	-5.11	40	50.6	14.06	0.83	125	60	QP
94.99	32.28	-11.22	43.5	43.59	18.3	0.99	-	-	Peak
133.79	28.04	-15.46	43.5	39.36	18.13	1.15	-	-	Peak
225.94	24.72	-21.28	46	36.94	16.85	1.4	-	-	Peak
333.61	27.74	-18.26	46	36.42	19.98	1.71	-	-	Peak
866.14	34.59	-11.41	46	33.22	28.23	2.71	-	-	Peak

## Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dB $\mu$ V/m) = 20 log Emission level ( $\mu$ V/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.