

FCC RADIO TEST REPORT

According to

47 CFR FCC Part 15 Subpart C § 15.225

Equipment : Mobile payment Terminal
Brand Name : PAX
Model No. : D900
Filing Type : New Application
Applicant : PAX Technology Limited
Room 2416, 24/F., Sun Hung Kai Centre,
30 Harbour Road, Wanchai, Hong Kong
FCC ID : V5PD900W
Manufacturer : PAX Computer Technology (Shenzhen) Co., Ltd.
4/F No. 3 Building, Software Park,
Second Central Science-Tech Road,
High-Tech industrial Park, Shenzhen,
Guangdong, P.R.C.
Received Date : Jul. 18, 2012
Final Test Date : Jul. 21, 2012

Statement

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

Table of Contents

1. SUMMARY OF THE TEST RESULT	2
2. GENERAL INFORMATION.....	3
1.1 Product Details.....	3
1.2 Accessories.....	3
2.1 Table for Test Modes	3
2.2 Table for Testing Locations.....	3
2.3 Table for Supporting Units	3
2.4 Test Configurations	4
3. TEST RESULT	7
3.1 AC Power Line Conducted Emissions Measurement	7
3.2 Field Strength of Fundamental Emissions and Mask Measurement.....	13
3.3 20dB Spectrum Bandwidth Measurement	16
3.4 Radiated Emissions Measurement	18
3.5 Frequency Stability Measurement	24
3.6 Antenna Requirements	26
4. LIST OF MEASURING EQUIPMENTS.....	27
5. TEST LOCATION.....	29
6. TAF CERTIFICATE OF ACCREDITATION.....	30
APPENDIX A. TEST PHOTOS	A8
APPENDIX B. PHOTOGRAPHS OF EUT	B79

History of This Test Report

Original Issue Date: Jul. 24, 2012

Report No.: FR250835

- No additional attachment.
- Additional attachment were issued as following record:

CERTIFICATE OF COMPLIANCE

According to

47 CFR FCC Part 15 Subpart C § 15.225


Equipment : Mobile payment Terminal

Brand Name : PAX

Model No. : D900

Applicant : PAX Technology Limited
Room 2416, 24/F., Sun Hung Kai Centre,
30 Harbour Road, Wanchai, Hong Kong

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Jul. 18, 2012 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Wayne Hsu / Assistant Manager

SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

1. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
3.1	15.207	AC Power Line Conducted Emissions	Complies	4.67 dB
3.2	15.225(a)	Field Strength of Fundamental Emissions	Complies	55.68 dB
3.3	15.215(c)	20dB Spectrum Bandwidth	Complies	-
3.4	15.225(d)	Radiated Emissions	Complies	1.64 dB
3.5	15.225(e)	Frequency Stability	Complies	-
3.6	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Field Strength of Fundamental Emissions	±0.8dB	Confidence levels of 95%
20dB Spectrum Bandwidth / Frequency Stability	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated / Band Edge Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

2. GENERAL INFORMATION

1.1 Product Details

Items	Description
Power Type	5Vdc from AC Adapter ; 3.7Vdc from Li-ion Battery
Modulation	ASK
Channel Number	1
Channel Band Width (99%)	2.26 kHz
Max. Field Strength	68.32 dBuV/m at 3m (QP)
Test Freq. Range	13.553 ~ 13.567MHz
Carrier Frequencies	13.56 MHz (Ch. 1)
Antenna	Integrate Antenna (Without any antenna connector)

1.2 Accessories

Accessories Information				
AC Adapter	Brand Name	Huntkey	Model Name	HKA00605010-2B
	Power Rating	I/P: 100 -240V~50/60Hz 0.2A ; O/P: 5.0V, 1.0A		
Battery	Brand Name	SCUD	Model Name	BA900
	Power Rating	3.7V / 1850mAh	Type	Li-ion
USB cable	Brand Name	NA	Model Name	NA
Camera	Brand Name	Global Optics Limited	Model Name	GNFF110489

2.1 Table for Test Modes

Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Channel
AC Power Line Conducted Emissions Radiated Emissions 30MHz~1GHz	Adapter Mode / USB Mode	-
Field Strength of Fundamental Emissions	CTX	1
20dB Spectrum Bandwidth	CTX	1
Radiated Emissions 9kHz~30MHz	CTX	1
Band Edge Emissions	CTX	1
Frequency Stability	Un-modulation	1

Note: CTX=continuously transmitting.

2.2 Table for Testing Locations

Test Site No.	Site Category	Location
CO04-HY	Conduction	Hwa Ya
TH01-HY	OVEN Room	Hwa Ya
03CH02-HY	SAC	Hwa Ya

Semi Anechoic Chamber (SAC).


2.3 Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E5520	DoC
MIFARE Card	--	--	--


Remark : The MIFARE Card provide by customer.


2.4 Test Configurations

For Conducted Emissions Adapter Mode




USB Mode




Spectrum Mask and Radiated Emissions 9kHz~30MHz

For radiated emissions 30MHz~1GHz
Adapter Mode



USB Mode



3. TEST RESULT

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit

For a Low-power Radio-frequency device which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

3.1.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.3 Test Procedures

1. The EUT was warmed up for 15 minutes before testing started.
2. The EUT was placed on a desk 0.8 meters height from the metal ground plane and 0.4 meter from the conducting wall of the shielding room and it was kept at least 0.8 meters from any other grounded conducting surface.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connect to the other LISN.
5. The LISN provides 50 ohm coupling impedance for the measuring instrument.
6. The CISPR states that a 50 ohm, 50 microhenry LISN should be used.
7. Both sides of AC line were checked for maximum conducted interference.
8. The frequency range from 150 kHz to 30 MHz was searched.
9. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

3.1.4 Test Setup Layout



3.1.5 Test Deviation

There is no deviation with the original standard.


3.1.6 EUT Operation during Test

The EUT was placed on the test table and programmed in transmitting function.


3.1.7 Results of AC Power Line Conducted Emissions Measurement

Final Test Date	Jul. 20, 2012	Test Site No.	CO04-HY
Temperature	24.5°C	Humidity	50%
Test Engineer	Sam	Configuration	Adapter Mode

Line



Freq	Level	Over Limit	Limit Line	Read	LISN	Cable	Remark
				Level	Factor	Loss	
MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 0.1770380	52.29	-12.33	64.62	51.92	0.00	0.37	QP
2 0.1770380	37.17	-17.45	54.62	36.80	0.00	0.37	Average
3 0.2370810	44.46	-17.74	62.20	44.14	0.00	0.32	QP
4 0.2370810	30.68	-21.52	52.20	30.36	0.00	0.32	Average
5 0.2948650	31.00	-19.39	50.39	30.64	0.00	0.36	Average
6 0.2948650	40.64	-19.75	60.39	40.28	0.00	0.36	QP
7 0.7629700	39.44	-16.56	56.00	39.11	0.00	0.33	QP
8 0.7629700	27.65	-18.35	46.00	27.32	0.00	0.33	Average
9 13.560	44.00	-16.00	60.00	43.63	0.00	0.37	QP
10 13.560	41.75	-8.25	50.00	41.38	0.00	0.37	Average
11 27.120	21.04	-28.96	50.00	20.66	0.00	0.38	Average
12 27.120	24.75	-35.25	60.00	24.37	0.00	0.38	QP


Neutral

Freq	Level	Over	Limit	Read	LISN	Cable
		Limit	Line	Level	Factor	Remark
MHz	dBuV	dB	dBuV	dBuV	dB	dB
1 0.1774010	52.42	-12.19	64.61	52.05	0.00	0.37 QP
2 0.1774010	36.77	-17.84	54.61	36.40	0.00	0.37 Average
3 0.2370810	45.30	-16.90	62.20	44.98	0.00	0.32 QP
4 0.2370810	29.45	-22.75	52.20	29.13	0.00	0.32 Average
5 0.2949830	29.50	-20.88	50.38	29.14	0.00	0.36 Average
6 0.2949830	41.19	-19.19	60.38	40.83	0.00	0.36 QP
7 0.5959090	38.03	-17.97	56.00	37.67	0.00	0.36 QP
8 0.5959090	28.58	-17.42	46.00	28.22	0.00	0.36 Average
9 13.560	42.69	-17.31	60.00	42.32	0.00	0.37 QP
10 13.560	40.06	-9.94	50.00	39.69	0.00	0.37 Average
11 27.120	22.09	-27.91	50.00	21.71	0.00	0.38 Average
12 27.120	25.49	-34.51	60.00	25.11	0.00	0.38 QP


Note:

Level = Read Level + LISN Factor + Cable Loss.

Final Test Date	Jul. 20, 2012	Test Site No.	CO04-HY
Temperature	24.5°C	Humidity	50%
Test Engineer	Sam	Configuration	USB Mode

Line

Freq	Level	Over Limit	Limit	Read Line	LISN		Cable Loss	Remark
					dBuV	dB		
MHz	dBuV		dB	dBuV		dB		
1 0.1581620	31.33	-24.23	55.56	30.89	0.00	0.44	Average	
2 0.1581620	47.67	-17.89	65.56	47.23	0.00	0.44	QP	
3 0.5211200	18.18	-27.82	46.00	17.81	0.00	0.37	Average	
4 0.5211200	34.68	-21.32	56.00	34.31	0.00	0.37	QP	
5 2.170	31.65	-24.35	56.00	31.26	0.00	0.39	QP	
6 2.170	21.48	-24.52	46.00	21.09	0.00	0.39	Average	
7 13.560	44.66	-15.34	60.00	44.29	0.00	0.37	QP	
8 13.560	44.78	-5.22	50.00	44.41	0.00	0.37	Average	
9 15.890	39.05	-20.95	60.00	38.69	0.00	0.36	QP	
10 15.890	33.13	-16.87	50.00	32.77	0.00	0.36	Average	
11 27.120	29.36	-30.64	60.00	28.98	0.00	0.38	QP	
12 27.120	22.27	-27.73	50.00	21.89	0.00	0.38	Average	

Neutral

Freq	Level	Over	Limit	Read	LISN	Cable	
		Line	dBuV	Level	Factor	Loss Remark	
MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.1536270	27.22	-28.58	55.80	26.77	0.00	0.45 Average
2	0.1536270	46.07	-19.73	65.80	45.62	0.00	0.45 QP
3	0.4711010	34.71	-21.78	56.49	34.33	0.00	0.38 QP
4	0.4711010	19.96	-26.53	46.49	19.58	0.00	0.38 Average
5	2.260	26.26	-19.74	46.00	25.88	0.00	0.38 Average
6	2.260	35.33	-20.67	56.00	34.95	0.00	0.38 QP
7	13.560	45.30	-14.70	60.00	44.93	0.00	0.37 QP
8	13.560	45.33	-4.67	50.00	44.96	0.00	0.37 Average
9	16.750	40.77	-19.23	60.00	40.44	0.00	0.33 QP
10	16.750	34.70	-15.30	50.00	34.37	0.00	0.33 Average
11	27.120	23.17	-26.83	50.00	22.79	0.00	0.38 Average
12	27.120	29.48	-30.52	60.00	29.10	0.00	0.38 QP

Note:

Level = Read Level + LISN Factor + Cable Loss.

3.2 Field Strength of Fundamental Emissions and Mask Measurement

3.2.1 Limit

Field strength of fundamental emissions limit:

The field strength of fundamental emissions shall not exceed 15848 micorvolts/meter at 30 meters.

The emissions limit in this paragraph is based on measurement instrumentation employing a QP detector.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Field Strength (dB μ V/m) at 10m	Field Strength (dB μ V/m) at 3m
13.553 ~ 13.567MHz	15848 at 30m	103.08 (QP)	124 (QP)

Mask limit:

Rules and specifications	RSS-210 A2.6				
Description	Compliance with the spectrum mask is tested using a spectrum analyzer with RB set to a 1kHz for the band 13.553~13.567MHz				
Limit	Freq. of Emission (MHz)	Field Strength (uV/m) at 30m	Field Strength (dB μ V/m) at 30m	Field Strength (dB μ V/m) at 10m	Field Strength (dB μ V/m) at 3m
	1.705~13.110	30	29.5	48.58	69.5
	13.110~13.410	106	40.5	59.58	80.5
	13.410~13.553	334	50.5	69.58	90.5
	13.553~13.567	15848	84.0	103.08	124.0
	13.567~13.710	334	50.5	69.58	90.5
	13.710~14.010	106	40.5	59.58	80.5
	14.010~30.000	30	29.5	48.58	69.5

3.2.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameter	Setting
Attenuation	Auto
Center Frequency	Fundamental Frequency
RB	10 kHz
Detector	QP

3.2.3 Test Procedures

- Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower was placed 3 meters far away from the turntable.
- Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- The height of the receiving antenna was fixed at one meter above ground to find the maximum emissions field strength.
- For Fundamental emissions, use the receiver to measure QP reading.
- When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
- Compliance with the spectrum mask is tested using a spectrum analyzer with RB set to a 10kHz for the band 13.553~13.567MHz.

3.2.4 Test Setup Layout



3.2.5 Test Deviation

There is no deviation with the original standard.


3.2.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.2.7 Test Result of Field Strength of Fundamental Emissions

Final Test Date	Jul. 19, 2012	Test Site No.	03CH02-HY
Temperature	24.3°C	Humidity	60%
Test Engineer	Streak	Configurations	Ch. 1

Freq. (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m) at 3m	Remark
13.56 MHz	68.32	-55.68	124	QP



Freq	Level	Over Limit	Read	Antenna	Cable Preamp			Table		
					Line	Level Factor	Loss Factor		Pos	Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m			cm	deg	
1 13.560	55.68	-68.32	124.00	36.21	20.00	-0.53	0.00	Peak	---	---

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Measured distance is 1m and 10m extrapolation factor is 40 log (10/1) = 40dB

All emissions emit from non-NFC function of digital unintentional emissions. All NFC's spurious emissions are below 20dB of limits.

3.3 20dB Spectrum Bandwidth Measurement

3.3.1 Limit

Intentional radiators must be designed to ensure that the 20 dB bandwidth of the emissions in the specific band (13.553 ~ 13.567MHz).

3.3.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 20dB Bandwidth
RB	1 kHz
VB	1 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

3.3.3 Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. For 20dB Bandwidth the resolution bandwidth of 1 kHz and the video bandwidth of 1 kHz were used.
3. Measured the spectrum width with power higher than 20dB below carrier.
4. For 99% Occupied Bandwidth the resolution Bandwidth of 1 kHz and the video bandwidth of 1 kHz was used.

3.3.4 Test Setup Layout



3.3.5 Test Deviation

There is no deviation with the original standard.

3.3.6 EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

3.3.7 Test Result of 20dB Spectrum Bandwidth

Final Test Date	Jul. 21, 2012	Test Site No.	TH01-HY
Temperature	25.9°C	Humidity	42%
Test Engineer	Ian	Configurations	Ch. 1

Frequency	20dB BW (kHz)	99% OBW (kHz)	Frequency range (MHz) $f_L > 13.553\text{MHz}$	Frequency range (MHz) $f_H < 13.567\text{MHz}$	Test Result
13.56 MHz	2.66	2.26	13.5588	13.5614	Complies

Bandwidth Plot on 13.56 MHz



Date: 21.JUL.2012 10:51:09

3.4 Radiated Emissions Measurement

3.4.1 Limit

The field strength of any emissions which appear outside of 13.553 ~ 13.567MHz band shall not exceed the general radiated emissions limits in Section 15.209(a)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.4.2 Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of receiver.


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.4.3 Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
7. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

3.4.4 Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



3.4.5 Test Deviation

There is no deviation with the original standard.

3.4.6 EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

3.4.7 Results of Radiated Emissions (9kHz~30MHz)

All spurious emissions (9kHz-30MHz) are below fundamental emissions field strength and the levels exceed the level of 20 dB below the applicable limit.


3.4.8 Results for Radiated Emissions (30MHz~1GHz)

Final Test Date	Jul. 19, 2012	Test Site No.	03CH02-HY
Temperature	24.3°C	Humidity	60%
Test Engineer	Streak	Configuration	Adapter Mode

Horizontal

Freq	Level	Over Limit	Limit	Read		Antenna	Cable	Preamp	Ant	Table
				Line	Factor					
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	dB	cm	deg
1 39.700	29.75	-10.25	40.00	43.37	13.25	1.03	27.90	Peak	---	---
2 265.710	29.65	-16.35	46.00	40.84	13.22	2.84	27.25	Peak	---	---
3 288.020	26.45	-19.55	46.00	37.18	13.54	2.92	27.19	Peak	---	---
4 719.670	37.72	-8.28	46.00	42.19	19.13	4.61	28.21	Peak	---	---
5 800.180	35.83	-10.17	46.00	38.61	20.27	4.89	27.94	Peak	---	---
6 815.700	38.95	-7.05	46.00	41.66	20.23	4.94	27.88	Peak	---	---

Vertical



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Int	Table
		Line	Limit	Level	Factor	Loss	Factor		
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 @ 39.700	38.36	-1.64	40.00	51.98	13.25	1.03	27.90	QP	---
2 90.140	33.34	-10.16	43.50	50.11	9.50	1.58	27.85	Peak	---
3 141.550	31.21	-12.29	43.50	45.10	11.78	2.00	27.67	Peak	---
4 719.670	37.61	-8.39	46.00	42.08	19.13	4.61	28.21	Peak	---
5 815.700	37.01	-8.99	46.00	39.72	20.23	4.94	27.88	Peak	---
6 912.700	39.03	-6.97	46.00	40.92	20.34	5.32	27.55	Peak	---


Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).


Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Final Test Date	Jul. 19, 2012	Test Site No.	03CH02-HY
Temperature	24.3°C	Humidity	60%
Test Engineer	Streak	Configuration	USB Mode

Horizontal

Freq	Level	Over Limit	Limit	Read		Antenna	Cable	Preamp	Remark	Ant Pos	Table Pos
				Line	Level Factor						
MHz	dBuV/m		dB	dBuV/m		dBuV	dB/m	dB	dB	cm	deg
1 141.550	36.79	-6.71	43.50	50.68	11.78	2.00	27.67	Peak	---	---	---
2 164.830	38.32	-5.18	43.50	53.40	10.34	2.14	27.56	Peak	---	---	---
3 238.550	32.80	-13.20	46.00	44.80	12.62	2.69	27.31	Peak	---	---	---
4 719.670	38.96	-7.04	46.00	43.43	19.13	4.61	28.21	Peak	---	---	---
5 815.700	36.59	-9.41	46.00	39.30	20.23	4.94	27.88	Peak	---	---	---
6 912.700	36.97	-9.03	46.00	38.86	20.34	5.32	27.55	Peak	---	---	---

Vertical



Freq	Level	Over Limit	Line	Read	Antenna	Cable	Preamp	Remark	Ant	Table
									Pos	Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	137.670	30.63	-12.87	43.50	44.15	12.18	1.98	27.68 Peak	---	---
2	164.830	39.05	-4.45	43.50	54.13	10.34	2.14	27.56 Peak	---	---
3	233.700	31.62	-14.38	46.00	43.82	12.46	2.67	27.33 Peak	---	---
4	719.670	39.20	-6.80	46.00	43.67	19.13	4.61	28.21 Peak	---	---
5	815.700	36.49	-9.51	46.00	39.20	20.23	4.94	27.88 Peak	---	---
6	912.700	36.52	-9.48	46.00	38.41	20.34	5.32	27.55 Peak	---	---

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

3.5 Frequency Stability Measurement

3.5.1 Limit

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

3.5.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Entire absence of modulation emissions bandwidth
RB	1 kHz
VB	1 kHz
Sweep Time	Auto

3.5.3 Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 1 kHz, VBW = 1 kHz with peak detector and maxhold settings.
5. fc is declaring of channel frequency. Then the frequency error formula is $(fc-f)/fc \times 10^6$ ppm and the limit is less than ± 100 ppm.
6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature rule is -20°C~50°C.

3.5.4 Test Setup Layout



3.5.5 Test Deviation

There is no deviation with the original standard.

3.5.6 EUT Operation during Test

The EUT was programmed to be in continuously un-modulation transmitting mode.

3.5.7 Test Result of Frequency Stability

Final Test Date	Jul. 21, 2012	Test Site No.	TH01-HY
Temperature	25.9°C	Humidity	42%
Test Engineer	Ian	Configurations	Ch. 1

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)
(V)	13.56 MHz
4.255	13.560220
3.700	13.560180
3.145	13.560120
Max. Deviation (MHz)	0.000220
Max. Deviation (ppm)	16.2242

Temperature vs. Frequency Stability

Temperature	Measurement Frequency (MHz)
(°C)	13.56 MHz
-20	13.560240
-10	13.560220
0	13.560200
10	13.560180
20	13.560180
30	13.560160
40	13.560120
50	13.560140
Max. Deviation (MHz)	0.000240
Max. Deviation (ppm)	17.6991

3.6 Antenna Requirements

3.6.1 Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

3.6.2 Antenna Connector Construction

Please refer to section 2.1 in this test report; antenna connector complied with the requirements.

4. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz ~ 2.75GHz	Mar. 23, 2012	Conduction (CO04-HY)
LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	8127-477	9kHz ~ 30MHz	Feb. 08, 2012	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9703-1839	9kHz ~ 30MHz	Apr. 20, 2012	Conduction (CO04-HY)
RF Cable-CON	HUBER+SUHNER	RG213/U	CB049	9kHz ~ 30MHz	Apr. 25, 2012	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP 40	100305	9KHz~40GHz	Feb. 21, 2012	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Jun. 19, 2012	Conducted (TH01-HY)
AC Power Source	G.W	APS-9102	EL920581	AC 0V ~ 300V	Jul. 02, 2012	Conducted (TH01-HY)
Temp. and Humidity Chamber	Giant Force	GTH-225-20-SP-SD	MAA1112-007	-20 ~ 100°C	Dec. 07, 2011	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100302	10MHz ~ 40GHz	Nov. 22, 2011	Conducted (TH01-HY)
Power Sensor	Anritsu	MA2411B	1027452	300MHz ~ 40GHz	Jan. 12, 2012	Conducted (TH01-HY)
Power Meter	Anritsu	ML2495A	1124009	300MHz ~ 40GHz	Jan. 12, 2012	Conducted (TH01-HY)
RF Cable-2m	HUBER+SUHNER	SUCOFLEX_104	SN 345672/4	1GHz ~ 26.5GHz	Dec. 03, 2011	Conducted (TH01-HY)
RF Cable-3m	HUBER+SUHNER	SUCOFLEX_104	SN 345668/4	1GHz ~ 26.5GHz	Dec. 03, 2011	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP40	100593	9kHz ~ 40GHz	Sep. 01, 2011	Radiation (03CH02-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH02-HY	30MHz ~ 1GHz 3m	May 10, 2012	Radiation (03CH02-HY)
Amplifier	Agilent	8447D	2944A11146	100kHz ~ 1.3GHz	Jul. 23, 2012	Radiation (03CH02-HY)
Amplifier	Agilent	8449B	3008A02373	1GHz ~ 26.5GHz	Aug. 08, 2011	Radiation (03CH02-HY)
Horn Antenna	ETS-LINDGREN	3117	00091920	1GHz ~ 18GHz	Nov. 15, 2011	Radiation (03CH02-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30MHz ~ 1GHz	Nov. 11, 2011	Radiation (03CH02-HY)
RF Cable-high	SUHNER	SUCOFLEX106	03CH02-HY	1GHz ~ 40GHz	Mar. 06, 2012	Radiation (03CH02-HY)
Bilog Antenna	SCHAFFNER	CBL61128	2723	30MHz ~ 2GHz	Oct. 22, 2011	Radiation (03CH02-HY)
Turn Table	HD	DS 420	420/649/00	0~ 360 degree	N/A	Radiation (03CH02-HY)
Antenna Mast	HD	MA 240	240/559/00	1 ~ 4 m	N/A	Radiation (03CH02-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Loop Antenna	Teseq	HLA 6120	24155	9 kHz ~ 30 MHz	Sep. 09, 2010	Radiation (03CH02-HY)

Note: Calibration Interval of instruments listed above is two year.

5. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei 221, Taiwan, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-327-0973
LINKOU	ADD : No. 30-2, Dingfu Vil., Linkou Dist., New Taipei City 244, Taiwan, R.O.C. TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei 114, Taiwan, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei 235, Taiwan, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

6. TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-120405

財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate of Accreditation

This is to certify that

Sporton International Inc.**EMC & Wireless Communications Laboratory**No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria : ISO/IEC 17025:2005**Accreditation Number** : 1190**Originally Accredited** : December 15, 2003**Effective Period** : January 10, 2010 to January 09, 2013**Accredited Scope** : Testing Field, see described in the Appendix**Specific Accreditation Program** : Accreditation Program for Designated Testing Laboratory
for Commodities Inspection
Accreditation Program for Telecommunication Equipment
Testing Laboratory
Accreditation Program for BSMI Mutual Recognition
Arrangement with Foreign Authorities

Jay-San Chen
President, Taiwan Accreditation Foundation
Date: April 05, 2012

P1, total 24 pages