





TEST REPORT

Applicant	PAX Technology Limited
Address	Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour Road, Wanchai, Hong Kong

Manufacturer or Supplier	PAX Computer Technology (Shenzhen) Co., Ltd.	
Address	4/F, No.3 Building, Software Park, Second Central Science-Tech Road, High-Tec industrial Park, Shenzhen, Guangdong, P.R.C.	
Product	ntegrated Smart Terminal	
Brand Name	PAX	
Model	E800	
Additional Model & Model Difference	N/A	
Date of tests	May 26, 2018 ~ Jul. 09, 2018	

the tests have been carried out according to the requirements of the following standards:

CONCLUSION: The submitted sample was found to **COMPLY** with the test requirement

Tested by Andy Zhu Project Engineer / EMC Department	Approved by Glyn He Supervisor / EMC Department
r roject Engineer / Livio Department	Supervisor / Livic Department

Date: Jul. 17, 2018

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/ and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

R	ELEASE C	ONTROL RECORD	4
1	SUMMA	ARY OF TEST RESULTS	5
2	MEASU	JREMENT UNCERTAINTY	5
3	GENER	RAL INFORMATION	6
	3.1 GEN	ERAL DESCRIPTION OF EUT	6
	3.2 DES	CRIPTION OF TEST MODES	7
	3.2.1.	CONFIGURATION OF SYSTEM UNDER TEST	7
	3.2.2.	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	7
	3.3 GEN	ERAL DESCRIPTION OF APPLIED STANDARDS	9
	3.4 DES	CRIPTION OF SUPPORT UNITS	9
4	TEST 1	YPES AND RESULTS	10
	4.1. CO	ONDUCTED EMISSION MEASUREMENT	10
	4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	10
	4.1.2	TEST INSTRUMENTS	10
	4.1.3	TEST PROCEDURES	11
	4.1.4	DEVIATION FROM TEST STANDARD	
	4.1.5	TEST SETUP	12
	4.1.6	EUT OPERATING CONDITIONS	
	4.1.7	TEST RESULTS	13
	4.2. RA	ADIATED EMISSION AND BANDEDGE MEASUREMENT	15
	4.2.1	LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT	15
	4.2.2	TEST INSTRUMENTS	16
	4.2.3	TEST PROCEDURES	17
	4.2.4	DEVIATION FROM TEST STANDARD	17
	4.2.5	TEST SETUP	18
	4.2.6	EUT OPERATING CONDITIONS	19
	4.2.7	TEST RESULTS	19
	4.3. FF	REQUENCY TOLERANCE	22
	4.3.1.	LIMIT OF FREQUENCY TOLERANCE	22
	4.3.2.	TEST INSTRUMENTS	22
	4.3.3.	TEST PROCEDURES	23
	4.3.4.	DEVIATION FROM TEST STANDARD	23
	4.3.5.	TEST SETUP	23
	4.3.6.	EUT OPERATING CONDITIONS	24

Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch No. 34, Chenwulu Section, Guantai Rd., Houjie Town, Dongguan City, Guangdong 523942, China

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080 Email: <u>customerservice.dg@cn.bureauveritas.com</u>



	4.3.7.	TEST RESULTS	24		
4	1.4. 20	dB BANDWIDTH	25		
	4.4.1	LIMITS OF 20dB BANDWIDTH	25		
	4.4.2	TEST INSTRUMENTS	25		
	4.4.3	TEST PROCEDURE	26		
	4.4.4	DEVIATION FROM TEST STANDARD26			
	4.4.5	TEST SETUP			
	4.4.6	EUT OPERATING CONDITION	27		
	4.4.7	TEST RESULTS	27		
5.	РНОТО	GRAPHS OF THE TEST CONFIGURATION	28		
6.	APPEN	DIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO)		
	THE EL	IT BY THE LAB	29		



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF180525N076	Original release	Jul. 17, 2018

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080 Email: <u>customerservice.dg@cn.bureauveritas.com</u>

Page 4 of 29

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C				
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK	
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit.	
15.225 (a)&(b)&(c)	The field strength of any emissions within the band	PASS	Meet the requirement of limit.	
15.225 (d)	The field strength of any emissions appearing outside of the 13.110-14.010 MHz band	PASS	Meet the requirement of limit.	
15.225 (e)	Frequency tolerance	PASS	Meet the requirement of limit.	
15.215 (c)	20dB Bandwidth		Meet the requirement of limit.	
15.203	Antenna Requirement	PASS	No antenna connector is used.	

2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY	
Conducted emissions	9kHz~30MHz	2.70dB	
	9KHz ~ 30MHz	2.16dB	
Radiated emissions	30MHz ~ 1GMHz	3.83dB	
Nadiated emissions	1GHz ~ 18GHz	4.66dB	
	18GHz ~ 40GHz	4.67dB	

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Integrated Smart Terminal
MODEL NO.	E800
FCC ID	V5PE800
POWER SUPPLY	DC 24V From Adapter
MODULATION TECHNOLOGY	RFID
MODULATION TYPE	ASK
OPERATING FREQUENCY	13.56MHz
NUMBER OF CHANNEL	1
ANTENNA TYPE	Loop antenna
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	AC Line: Shielded, Detachable, 1.7m

NOTE:

- 1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- 2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
- 3. The EUT can be powered by adapter as list as attach:

ADAPTER			
BRAND:	BRAND: HOIOTO		
MODEL: ADS-65HI-19A-3 24065E			
INPUT: AC 100-240V, 50/60Hz			
OUTPUT:	DC 24V/2.7A		
DC CABLE:	Unshielded, Non-detachable, 1.50m with one core		



3.2 DESCRIPTION OF TEST MODES

The EUT only have one channel.

CHANNEL	FREQUENCY (MHz)
1	13.56

3.2.1. CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photograph of the test configuration for reference.

3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on X axis for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE	APPLICABLE TO				DESCRIPTION
MODE	RE	FT	PLC	BW	DESCRIPTION
Α	V	√	√	√	Power by Adapter with NFC

Where

RE: Radiated Emission
PLC: Power Line Conducted Emission

FT: Frequency tolerance **BW:** 20dB Bandwidth

RADIATED EMISSION TEST:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	TESTED CHANNEL	TESTED FREQUENCY (MHZ)	MODULATION TYPE	AXIS
А	1	13.56	ASK	X



FREQUENCY TOLERANCE:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

CO	EUT NFIGURE MODE	TESTED CHANNEL	TESTED FREQUENCY (MHZ)	MODULATION TYPE	AXIS
	Α	1	13.56	ASK	Х

POWER LINE CONDUCTED EMISSION TEST:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	TESTED CHANNEL	TESTED FREQUENCY (MHZ)	MODULATION TYPE	AXIS
Α	1	13.56	ASK	X

20dB BANDWIDTH:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	TESTED CHANNEL	TESTED FREQUENCY (MHZ)	MODULATION TYPE	AXIS
А	1	13.56	ASK	X

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY	
RE	21deg. C, 63%RH	DC 24V From Adapter	Luke	
FT	25deg. C, 60%RH	DC 24V From Adapter	Robert Cheng	
PLC	25deg. C, 55%RH	DC 24V From Adapter	Dragon	
BW	25deg. C, 60%RH	DC 24V From Adapter	Robert Cheng	

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. Section 15.225 ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

NOTE: 1. All test items have been performed and recorded as per the above standards.

2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (SDoc). The test report has been issued separately.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as a dependent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	N/A	N/A	N/A	N/A	N/A

NO.	DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A

Tel: +86 769 8593 5656



4 TEST TYPES AND RESULTS

4.1. CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)		
	Quasi-peak	Average	
0.15 ~ 0.5	66 to 56	56 to 46	
0.5 ~ 5	56	46	
5 ~ 30	60	50	

NOTE: 1.The lower limit shall apply at the transition frequencies.

- 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
- All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101494	Mar. 21,18	Mar. 20,19
Artificial Mains Network	Rohde&Schwarz	ENV216	101173	Mar. 03,18	Mar. 02,19
Artificial Mains Network	Rohde&Schwarz	ESH3-Z5	100317	Apr. 11,18	Apr. 10,19
Voltage probe	SCHWARZBEC K		TK 9421-176	Jan. 17,18	Jan. 16,19
Test software	ADT	ADT_Cond_V 7.3.7	N/A	N/A	N/A

NOTE:

- 1. The test was performed in shielded room 553.
- 2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

Tel: +86 769 8593 5656



4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit 20dB) was not recorded.


NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.



4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.



4.1.7 TEST RESULTS


CONDUCTED WORST-CASE DATA:

PHASE	Line	6dB BANDWIDTH	9kHz
111/102	Line	oub Brate Trib Till	OIG IZ

No	Freq. [MHz]			Factor [dB (uV)] [dB (uV)]			nit (uV)]		rgin IB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.01	33.28	15.61	43.29	25.62	66.00	56.00	-22.71	-30.38
2	0.17698	9.83	28.83	12.78	38.66	22.61	64.63	54.63	-25.97	-32.02
3	0.38850	10.11	24.30	13.35	34.41	23.46	58.10	48.10	-23.68	-24.63
4	3.52950	9.79	15.57	6.08	25.36	15.87	56.00	46.00	-30.64	-30.13
5	15.46800	9.80	10.46	5.50	20.26	15.30	60.00	50.00	-39.74	-34.70
6	17.76075	9.99	18.25	3.20	28.24	13.19	60.00	50.00	-31.76	-36.81

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

- 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
- 3. The emission levels of other frequencies were very low against the limit.
- 4. Margin value = Emission level Limit value
- 5. Correction factor = Insertion loss + Cable loss
- 6. Emission Level = Correction Factor + Reading Value.






PHASE	Neutral	6dB BANDWIDTH	9kHz
	i		

No	Freq. [MHz]	•	Corr. Factor		g Value (uV)]	Emissio	n Level (uV)]		mit (uV)]	Maı (d	gin B)
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	
1	0.16125	10.10	30.31	15.13	40.41	25.23	65.40	55.40	-24.99	-30.17	
2	0.28275	9.89	22.30	13.10	32.19	22.99	60.73	50.73	-28.55	-27.75	
3	0.38463	10.42	26.10	18.36	36.52	28.78	58.18	48.18	-21.66	-19.40	
4	3.42825	10.03	15.41	4.16	25.44	14.19	56.00	46.00	-30.56	-31.81	
5	15.46800	9.78	11.91	6.27	21.69	16.05	60.00	50.00	-38.31	-33.95	
6	17.76075	9.92	20.87	5.34	30.79	15.26	60.00	50.00	-29.21	-34.74	

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

- 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
- 3. The emission levels of other frequencies were very low against the limit.
- 4. Margin value = Emission level Limit value
- 5. Correction factor = Insertion loss + Cable loss
- 6. Emission Level = Correction Factor + Reading Value.





4.2. RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

The field strength of any emissions shall not exceed the following limits:

- (a)15.848mV/m(84dBuV/m) at 30m, within the band 13.553-13.567 MHz;
- (b)334uV/m(50.5dBuV/m) at 30m, within the band 13.410-13.553 MHz and 13.567-13.710MHz;
- (c)106uV/m(40.5dBuV/m) at 30m, within the band 13.110-13.410 MHz and 13.710-14.010MHz;

The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in § 15.209.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
- 4. The measured field strength was extrapolated to distance 30 meters, using the formula that the limit of field strength varies as the inverse distance square (40dB per decade of distance)

Example:

13.56MHz = 15848uV/m 30m

= 84dBuV/m 30m = $84+20log(30/3)^2$ 3m

= 124dBuV/m



4.2.2 TEST INSTRUMENTS

9KHz~30MHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESU40	100449	Mar. 21,18	Mar. 20,19
Active Loop Antenna (9KHz -30MHz)	SCHWARZBECK	FMZB 1519B	1519B-045	May 31,18	May 30,19
Amplifier (9KHz -1GHz)	Burgeon	BPA-530	100210	Apr. 18,18	Apr. 18,19
Test Software	ADT	ADT_Radiated _V7.6.15.9.2	N/A	N/A	N/A

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

- 2. The test was performed in 10m Chamber
- 3. The FCC Site Registration No. is 749762.

30MHz~1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESU40	100449	Mar. 21,18	Mar. 20,19
Bilog Antenna (20MHz -2GHz)	Teseq	CBL 6111D	30643	Jul. 28, 17	Jul. 27, 18
Amplifier (9KHz -1GHz)	Burgeon	BPA-530	100210	Apr. 18,18	Apr. 18,19
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	Feb. 10,18	Feb. 09,19
Test Software	ADT	ADT_Radiated _V7.6.15.9.2	N/A	N/A	N/A

NOTE:

- 1. The test was performed in 966 Chamber (a 3m Semi-anechoic chamber).
- 2. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
- 3. The horn antenna is used only for the measurement of emission frequency above1GHz if tested.
- 4. The FCC Site Registration No. is 749762.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080 Email: <u>customerservice.dg@cn.bureauveritas.com</u>



4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3&10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.
- g. For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1m above the ground.

NOTE:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
- 3. All modes of operation were investigated and the worst-case emissions are reported.


4.2.4 DEVIATION FROM TEST STANDARD

No deviation.




4.2.5 TEST SETUP

Below 30MHz



30MHz~1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).



4.2.6 EUT OPERATING CONDITIONS


Set the EUT under transmission condition continuously at specific channel frequency.

4.2.7 TEST RESULTS

FIELD STRENGTH (BELOW 30MHZ AT 3M)

No.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Polarity (0° / 90°)	Limit (dBuV/m)	Margin (dB)
1	*13.56(QP)	23.55	23.56	47.11	0 °	124.0	-76.89
2	27.12(QP)	24.35	8.28	32.63	0°	69.5	-36.87
3	*13.56(QP)	23.55	19.99	43.54	90°	124.0	-80.46
4	27.12(QP)	24.35	5.12	29.47	90°	69.5	-40.03

- REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 - 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 - 3. The other emission levels were very low against the limit.
 - 4. Margin value = Emission level Limit value.
 - 5. " * ": Fundamental frequency.
 - 6. For the test results, both 0° and 90° polarizations of the antenna are set to make the measurement, but only the worst case was shown in test report.



Tel: +86 769 8593 5656 Fax: +86 769 8593 1080 Email: <u>customerservice.dg@cn.bureauveritas.com</u>




BELOW 1GHz WORST-CASE DATA:

CHANNEL	Channel 1	DETECTOR	Ouaci Book (OB)	
FREQUENCY RANGE	9KHz ~ 1GHz	FUNCTION	Quasi-Peak (QP)	

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M											
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)				
1	168.35	31.40 QP	43.50	-12.10	2.00 H	32	48.99	-17.59				
2	294.26	34.91 QP	46.00	-11.09	2.00 H	54	48.41	-13.50				
3	344.01	34.94 QP	46.00	-11.06	2.00 H	136	46.89	-11.95				
4	393.75	42.68 QP	46.00	-3.32	2.00 H	0	52.03	-9.35				
5	491.68	39.15 QP	46.00	-6.85	2.00 H	87	46.26	-7.11				
6	556.97	35.48 QP	46.00	-10.52	2.00 H	169	39.29	-3.81				

- REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 - 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 - 3. The emission levels of other frequencies were less than 20dB margin against the limit.
 - 4. Margin value = Emission level Limit value.






CHANNEL	Channel 1	DETECTOR	Ougai Book (OB)	
FREQUENCY RANGE	9KHz ~ 1GHz	FUNCTION	Quasi-Peak (QP)	

	ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M											
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)				
1	71.97	34.13 QP	40.00	-5.87	1.00 V	216	58.10	-23.97				
2	95.29	36.64 QP	43.50	-6.86	1.00 V	45	55.64	-19.00				
3	120.16	36.98 QP	43.50	-6.52	1.00 V	174	53.58	-16.60				
4	157.47	34.43 QP	43.50	-9.07	1.00 V	85	51.09	-16.66				
5	393.75	39.58 QP	46.00	-6.42	1.00 V	264	48.93	-9.35				
6	558.53	38.03 QP	46.00	-7.97	1.00 V	21	41.70	-3.67				

- REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 - 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 - 3. The emission levels of other frequencies were less than 20dB margin against the limit.
 - 4. Margin value = Emission level Limit value.





4.3. FREQUENCY TOLERANCE

4.3.1. LIMIT OF FREQUENCY TOLERANCE

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency over a temperature variation of –20 degrees to 50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.

4.3.2. TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESU40	100449	Mar. 21,18	Mar. 20,19
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV7	102331	Nov. 04,17	Nov. 03,18
Active Loop Antenna (9KHz -30MHz)	SCHWARZBECK	FMZB 1519B	1519B-045	May 31,18	May 30,19
Amplifier (9KHz -1GHz)	Burgeon	BPA-530	100210	Apr. 18,18	Apr. 18,19
Bilog Antenna (20MHz -2GHz)	Teseq	CBL 6111D	30643	Jul. 28, 17	Jul. 27, 18
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	00062558	Jun. 02,18	Jun. 01,19
Horn Antenna (18GHz -40GHz)	SCHWARZBECK	BBHA 9170	BBHA9170242	May 05,18	May 04,19
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	Feb. 10,18	Feb. 09,19
Test Software	ADT	ADT_Radiated _V7.6.15.9.2	N/A	N/A	N/A
Broadband Preamplifier (1GHz~18GHz)	SCHWARZBECK	BBV9718	305	Apr. 18,18	Apr. 18,19
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 08,17	Nov. 07,18
Test Software	ADT	ADT_Radiated _V7.6.15.9.2	N/A	N/A	N/A
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Aug. 10,17	Aug. 09,18

NOTE:

- 1. The test was performed in RF Oven room.
- 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.




4.3.3. TEST PROCEDURES

- The EUT was placed inside the environmental test chamber and powered by nominal DC voltage.
- b) Turn the EUT on and couple its output to a spectrum analyzer.
- c) Turn the EUT off and set the chamber to the highest temperature specified.
- d) Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
- e) Repeat step c) and d) with the temperature chamber set to the lowest temperature.
- f) The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

4.3.4. DEVIATION FROM TEST STANDARD

No deviation.

4.3.5. TEST SETUP



Tel: +86 769 8593 5656



4.3.6. EUT OPERATING CONDITIONS

Set the EUT under transmission condition continuously at specific channel frequency.

4.3.7. TEST RESULTS

	FREQUEMCY STABILITY VERSUS TEMP.											
		0 MINUTE		2 MINUTE		5 MIN	NUTE	10 MI	10 MINUTE			
TEMP. (°C)	POWER SUPPLY (Vac)	Measured Frequency	Frequency Drift	Measured Frequency	Frequency Drift	Measured Frequency	Frequency Drift	Measured Frequency	Frequency Drift			
		(MHz)	%	(MHz)	%	(MHz)	%	(MHz)	%			
50	120V/60Hz	13.56005	0.00037	13.56005	0.00037	13.56006	0.00044	13.56005	0.00037			
40	120V/60Hz	13.56005	0.00037	13.56004	0.00029	13.56005	0.00037	13.56005	0.00037			
30	120V/60Hz	13.55997	-0.00022	13.55997	-0.00022	13.55997	-0.00022	13.55997	-0.00022			
20	120V/60Hz	13.55996	-0.00029	13.55996	-0.00029	13.55996	-0.00029	13.55995	-0.00037			
10	120V/60Hz	13.55995	-0.00037	13.55994	-0.00044	13.55995	-0.00037	13.55995	-0.00037			
0	120V/60Hz	13.56	0.00000	13.56001	0.00007	13.56	0.00000	13.56	0.00000			
-10	120V/60Hz	13.56002	0.00015	13.56003	0.00022	13.56003	0.00022	13.56003	0.00022			
-20	120V/60Hz	13.55995	-0.00037	13.55995	-0.00037	13.55994	-0.00044	13.55995	-0.00037			

	FREQUEMCY STABILITY VERSUS VOLTAGE										
		0 MINUTE		2 MIN	2 MINUTE		5 MINUTE		10 MINUTE		
TEMP. (℃)	POWER SUPPLY (Vac)	Measured Frequency	Frequency Drift	Measured Frequency	Frequency Drift	Measured Frequency	Frequency Drift	Measured Frequency	Frequency Drift		
		(MHz)	%	(MHz)	%	(MHz)	%	(MHz)	%		
	102V/60Hz	13.55996	-0.00029	13.55996	-0.00029	13.55996	-0.00029	13.55995	-0.00037		
20	120V/60Hz	13.55996	-0.00029	13.55996	-0.00029	13.55996	-0.00029	13.55995	-0.00037		
	138V/60Hz	13.55996	-0.00029	13.55996	-0.00029	13.55996	-0.00029	13.55995	-0.00037		

Tel: +86 769 8593 5656



4.4. 20dB BANDWIDTH

4.4.1 LIMITS OF 20dB BANDWIDTH

The 20dB bandwidth shall be specified in operating frequency band.(13.11MHz – 14.01MHz)

4.4.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Sensor	Keysight	U2021XA	MY55060016	May 19,18	May 18,19
Power Sensor	Keysight	U2021XA	MY55060018	May 19,18	May 18,19
Power Meter	Anritsu	ML2495A	1139001	Apr. 13,18	Apr. 13,19
Power Sensor	Anritsu	MA2411B	1531155	Apr. 13,18	Apr. 13,19
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 21, 17	Oct.20, 18
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.05,17	Sep. 04,18
Oscilloscope	Agilent	DSO9254A	MY51260160	Nov. 08,17	Nov. 07,18
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 04,17	Nov. 03,18
Signal Generator	Agilent	N5183A	MY50140980	Jan. 02,18	Jan. 01,19
Agile Signal Generator	Agilent	8645A	Agilent	Sep.01, 17	Aug.31, 18
Spectrum Analyzer	Keysight	N9020A	MY55400499	Mar. 21,18	Mar. 20,19
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY56200288	Jan. 02,18	Jan. 01,19
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Aug.10, 17	Aug.09, 18
Attenuator	MINI	BW-S10W2+	S130129FGE2	N/A	N/A
DC Source	Keysight	E3642A	MY56146098	N/A	N/A

NOTE:

- 1. The test was performed in RF Oven room.
- 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.




4.4.3 TEST PROCEDURE

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation.

4.4.5 TEST SETUP






4.4.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously.

4.4.7 TEST RESULTS

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (KHz)	
1	13.56	26.48	

Lower & Upper Test Frequency Point (MHz)	Test Frequency (MHz)	P/F
Lower	13.54625	PASS
Upper	13.57274	PASS



Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

g 523942, China Email: customerservice.dg@cn.bureauveritas.com



5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



6. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---