

Annex E. Maximum Target Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

Air Interface			Max. Tune-up Power
			ANT 0
GSM	GSM850		33.4
	EDGE850		27.4
	GSM1900		30.4
	EDGE1900		26.4
WCDMA	Band II	AMR	24.2
		HSPA	23.2
	Band V	AMR	24.2
		HSPA	23.2
FDD-LTE	Band 2		24.7
	Band 4		24.7
	Band 5		24.7
	Band 7		24.2
	Band 12		24.2
	Band 13		24.7
	Band 66		24.7
	Band 71		24.2
TDD-LTE	Band 48	QPSK	24.7
		16QAM	23.7
		64QAM	22.7
FDD-5G FR1	n2		24.7
	n5		24.7
	n66		24.7
	n71		24.2
WLAN 2.4G	802.11b		15.0
	802.11g		15.0
	802.11n HT20		15.0
WLAN 5.2G	802.11a		14.5
	802.11n HT20		14.5
	802.11n HT40		14.5
	802.11ac VHT20		14.5
	802.11ac VHT40		14.5
	802.11ac VHT80		14.5
WLAN 5.3G	802.11a		14.5
	802.11n HT20		14.5
	802.11n HT40		14.5
	802.11ac VHT20		14.5
	802.11ac VHT40		14.5
	802.11ac VHT80		14.5
WLAN 5.6G	802.11a		14.5
	802.11n HT20		14.5
	802.11n HT40		14.5
	802.11ac VHT20		14.5
	802.11ac VHT40		14.5
	802.11ac VHT80		14.5
WLAN 5.8G	802.11a		14.5
	802.11n HT20		14.5
	802.11n HT40		14.5
	802.11ac VHT20		14.5
	802.11ac VHT40		14.5
	802.11ac VHT80		14.5