




PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA
Tel. 410.290.6652 / Fax 410.290.6654
http://www.pctestlab.com



MEASUREMENT REPORT FCC Part 27 LTE

Applicant Name:
Kyocera Corporation
9520 Towne Centre Drive, Suite 200
San Diego, CA 92121
United States

Date of Testing:
9/14-9/23/2015
Test Site/Location:
PCTEST Lab., Columbia, MD, USA
Test Report Serial No.:
0Y1509141769-R3.V65

FCC ID :	V65CD8100
APPLICANT:	KYOCERA CORPORATION

Application Type: Certification
FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part(s): §2; §27
Test Procedure(s): ANSI/TIA-603-C-2004, KDB 971168 v02r02
EUT Type: Portable Handset
Model(s): CD8100
Test Device Serial No.: *identical prototype* [S/N: 990000515216283]

Mode	Tx Frequency (MHz)	Emission Designator	Modulation	ERP/EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE Band 13	779.5 - 784.5	4M54G7D	QPSK	0.047	16.70
LTE Band 13	779.5 - 784.5	4M51W7D	16QAM	0.038	15.83
LTE Band 13	782	9M04G7D	QPSK	0.041	16.12
LTE Band 13	782	9M02W7D	16QAM	0.037	15.68
LTE Band 4	1710.7 - 1754.3	1M12G7D	QPSK	0.177	22.47
LTE Band 4	1710.7 - 1754.3	1M13W7D	16QAM	0.156	21.93
LTE Band 4	1711.5 - 1753.5	2M72G7D	QPSK	0.225	23.53
LTE Band 4	1711.5 - 1753.5	2M72W7D	16QAM	0.209	23.21
LTE Band 4	1712.5 - 1752.5	4M52G7D	QPSK	0.216	23.34
LTE Band 4	1712.5 - 1752.5	4M52W7D	16QAM	0.181	22.57
LTE Band 4	1715 - 1750	9M00G7D	QPSK	0.223	23.48
LTE Band 4	1715 - 1750	9M00W7D	16QAM	0.188	22.74
LTE Band 4	1717.5 - 1747.5	13M5G7D	QPSK	0.201	23.03
LTE Band 4	1717.5 - 1747.5	13M5W7D	16QAM	0.165	22.19
LTE Band 4	1720 - 1745	18M0G7D	QPSK	0.202	23.06
LTE Band 4	1720 - 1745	18M0W7D	16QAM	0.154	21.88

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

This This revised Test Report (S/N: 0Y1509141769-R3.V65) supersedes and replaces the previously issued test report (S/N: 0Y1509141769-R2.V65) on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortanez
President




FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset	Page 1 of 60	

T A B L E O F C O N T E N T S


FCC PART 27 MEASUREMENT REPORT		3
1.0 INTRODUCTION		4
1.1 Scope.....		4
1.2 Testing Facility		4
2.0 PRODUCT INFORMATION.....		5
2.1 Equipment Description.....		5
2.2 Device Capabilities		5
2.3 Test Configuration.....		5
2.4 EMI Suppression Device(s)/Modifications.....		5
3.0 DESCRIPTION OF TESTS		6
3.1 Measurement Procedure.....		6
3.1 Block C Frequency Range		6
3.2 AWS - Base Frequency Blocks		6
3.3 AWS - Mobile Frequency Blocks.....		6
3.4 Radiated Power and Radiated Spurious Emissions.....		7
4.0 TEST EQUIPMENT CALIBRATION DATA		8
5.0 SAMPLE CALCULATIONS		9
6.0 TEST RESULTS.....		10
6.1 Summary.....		10
6.2 Occupied Bandwidth		11
6.3 Spurious and Harmonic Emissions at Antenna Terminal		20
6.4 Band Edge Emissions at Antenna Terminal.....		30
6.5 Radiated Power (ERP/EIRP)		47
6.6 Radiated Spurious Emissions Measurements.....		50
6.7 Frequency Stability / Temperature Variation		55
7.0 CONCLUSION.....		60

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 2 of 60



MEASUREMENT REPORT

FCC Part 27




§2.1033 General Information



APPLICANT: Kyocera Corporation
APPLICANT ADDRESS: 9520 Towne Centre Drive, Suite 200
 San Diego, CA 92121, United States
TEST SITE: PCTEST ENGINEERING LABORATORY, INC.
TEST SITE ADDRESS: 7185 Oakland Mills Road, Columbia, MD 21045 USA
FCC RULE PART(S): §2; §27
BASE MODEL: CD8100
FCC ID: V65CD8100
FCC CLASSIFICATION: PCS Licensed Transmitter Held to Ear (PCE)
FREQUENCY TOLERANCE: ±0.00025 % (2.5 ppm)
Test Device Serial No.: 990000515216283 Production Pre-Production Engineering
DATE(S) OF TEST: 9/14-9/23/2015
TEST REPORT S/N: 0Y1509141769-R3.V65

Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.

- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.



FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset	Page 3 of 60	

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2014 on January 22, 2015.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 4 of 60

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Kyocera Portable Handset FCC ID: V65CD8100**. The test data contained in this report pertains only to the emissions due to the EUT's LTE function.

2.2 Device Capabilities

This device contains the following capabilities:



850/1900 CDMA/EvDO 1x/Rev0/RevA (BC0, BC1), Multi-band LTE, 802.11b/g/n WLAN, Bluetooth (EDR, LE), Nordic Tx

2.3 Test Configuration

The Kyocera Portable Handset FCC ID: V65CD8100 was tested per the guidance of ANSI/TIA-603-C-2004 and KDB 971168 v02r02. See Section 6.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 5 of 60

3.0 DESCRIPTION OF TESTS

3.1 Measurement Procedure

The measurement procedures described in the document titled “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-C-2004) and “Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems” (KDB 971168) were used in the measurement of the **Kyocera Portable Handset FCC ID: V65CD8100**.


3.1 Block C Frequency Range

§27.5(b)(3)

Two paired channels of 11 megahertz each are available for assignment in Block C in the 746-757 MHz and 776-787 MHz bands. In the event that no licenses for two channels in this Block C are assigned based on the results of the first auction in which such licenses were offered because the auction results do not satisfy the applicable reserve price, the spectrum in the 746-757 MHz and 776-787 MHz bands will instead be made available for assignment at a subsequent auction as follows: (i) Two paired channels of 6 megahertz each available for assignment in Block C1 in the 746-752 MHz and 776-782 MHz bands. (ii) Two paired channels of 5 megahertz each available for assignment in Block C2 in the 752-757 MHz and 782-787 MHz bands.


3.2 AWS - Base Frequency Blocks



§27.5(h)



3.3 AWS - Mobile Frequency Blocks

§27.5(h)



FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset	Page 6 of 60	

3.4 Radiated Power and Radiated Spurious Emissions §2.1053 §27.50(b.10) §27.50(d.4) §27.53(f) §27.53(h)

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. A 72cm high PVC support structure is placed on top of the turntable. A 3" (~7.6cm) sheet of high density polystyrene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm. For measurements above 1GHz, absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed.



The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer "Channel Power" function with the integration band set to the emissions' occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168.

Per the guidance of ANSI/TIA-603-C-2004, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

The calculated P_d levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of $43 + 10\log_{10}(\text{Power}_{\text{[Watts]}})$.

FCC ID: V65CD8100	 FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		 Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset	Page 7 of 60

4.0 TEST EQUIPMENT CALIBRATION DATA



Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTX1	Licensed Transmitter Cable Set	4/16/2015	Annual	4/16/2016	N/A
-	RE3	Radiated Emissions Cable Set	4/29/2015	Annual	4/29/2016	N/A
Agilent	8447D	Broadband Amplifier	6/12/2015	Annual	6/12/2016	2443A01900
Agilent	E4448A	PSA (3Hz-50GHz) Spectrum Analyzer	3/19/2015	Annual	3/19/2016	US42510244
Agilent	N4010A	Wireless Connectivity Test Set	N/A			GB46170464
Agilent	N9020A	MXA Signal Analyzer	10/27/2014	Annual	10/27/2015	US46470561
Espec	ESX-2CA	Environmental Chamber	3/17/2015	Annual	3/17/2016	17620
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	4/8/2014	Biennial	4/8/2016	125518
ETS Lindgren	3160-09	18-26.5 GHz Standard Gain Horn	6/17/2014	Biennial	6/17/2016	135427
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	10/22/2014	Biennial	10/22/2016	128338
K & L	11SH10-3075/U18000	High Pass Filter	12/1/2014	Annual	12/1/2015	2
K & L	13SH10-1000/U1000	N Type High Pass Filter	12/1/2014	Annual	12/1/2015	1
Mini Circuits	PWR-SEN-4GHS	USB Power Sensor	3/11/2015	Annual	3/11/2016	11401010036
Mini-Circuits	SSG-4000HP	USB Synthesized Signal Generator	N/A			11208010032
Rohde & Schwarz	CMU200	Base Station Simulator	3/23/2015	Annual	3/23/2016	836371/0079
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	7/17/2015	Annual	7/17/2016	100348
Rohde & Schwarz	TS-PR18	1-18 GHz Pre-Amplifier	3/5/2015	Annual	3/5/2016	100071
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	3/3/2015	Annual	3/3/2016	100040
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Rx	11/21/2013	Biennial	11/21/2015	9105-2404
Seekonk	NC-100	Torque Wrench (8" lb)	3/5/2012	Biennial	3/5/2014	N/A
Sunol Sciences	DRH-118	Horn Antenna	7/1/2015	Biennial	7/1/2017	A060215
Tektronix	RSA6114A	Real Time Spectrum Analyzer	4/16/2014	Annual	4/16/2015	B010177
VWR	62344-734	Thermometer with Clock	2/20/2014	Biennial	2/20/2016	140140336

Table 4-1. Test Equipment

Note:

Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset	Page 8 of 60	

5.0 SAMPLE CALCULATIONS

Emission Designator

QPSK Modulation

Emission Designator = 8M62G7D

LTE BW = 8.62 MHz
 G = Phase Modulation
 7 = Quantized/Digital Info
 D = Data transmission, telemetry, telecommand

16QAM Modulation



Emission Designator = 8M45W7D

LTE BW = 8.45 MHz
 W = Amplitude/Angle Modulated
 7 = Quantized/Digital Info
 D = Data transmission, telemetry, telecommand

Spurious Radiated Emission – LTE Band

Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (-24.80).

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset	Page 9 of 60	

6.0 TEST RESULTS

6.1 Summary



Company Name: Kyocera Corporation
 FCC ID: V65CD8100
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): LTE

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Result	Reference
TRANSMITTER MODE (TX)					
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 6.2
2.1051 27.53(c) 27.53(h)	Out of Band Emissions	> 43 + 10log ₁₀ (P[Watts]) at Band Edge and for all out-of-band emissions		PASS	Section 6.3, 6.4
2.1046	Transmitter Conducted Output Power	N/A		PASS	See RF Exposure Report
2.1055. 27.54	Frequency Stability	undamental emissions stay within authorized frequency block (Part 24, 27)		PASS	Section 6.7
27.50(b.10)	Effective Radiated Power (Band 13)	< 3 Watts max. ERP	RADIATED	PASS	Section 6.5
27.50(d.4)	Equivalent Isotropic Radiated Power (Band 4)	< 1 Watts max. EIRP		PASS	Section 6.5
2.1053 27.53(c) 27.53(h)	Undesirable Emissions	> 43 + 10log ₁₀ (P[Watts]) for all out-of-band emissions		PASS	Section 6.6
27.53(f)	Undesirable Emissions (Band 13)	< -70 dBW/MHz (for wideband signals) < -80 dBW (for discrete emissions less than 700Hz BW) For all emissions in the band 1559 – 1610 MHz		PASS	Section 6.6

Table 6-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots (Sections 6.2, 6.3, 6.4) were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "LTE Automation," Version 4.0.

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset	Page 10 of 60	

6.2 Occupied Bandwidth

§2.1049

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

KDB 971168 v02r02 – Section 4.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW \geq 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.







Figure 6-1. Test Instrument & Measurement Setup


Test Notes

None.

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset	Page 11 of 60	




Plot 6-1. Occupied Bandwidth Plot (Band 13 – 5.0MHz QPSK – RB Size 25)




Plot 6-2. Occupied Bandwidth Plot (Band 13 – 5.0MHz 16-QAM – RB Size 25)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 12 of 60




Plot 6-3. Occupied Bandwidth Plot (Band 13 – 10.0MHz QPSK – RB Size 50)




Plot 6-4. Occupied Bandwidth Plot (Band 13 – 10.0MHz 16-QAM – RB Size 50)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 13 of 60




Plot 6-5. Occupied Bandwidth Plot (Band 4 – 1.4MHz QPSK – RB Size 6)




Plot 6-6. Occupied Bandwidth Plot (Band 4 – 1.4MHz 16-QAM – RB Size 6)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 14 of 60




Plot 6-7. Occupied Bandwidth Plot (Band 4 – 3.0MHz QPSK – RB Size 15)




Plot 6-8. Occupied Bandwidth Plot (Band 4 – 3.0MHz 16-QAM – RB Size 15)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 15 of 60




Plot 6-9. Occupied Bandwidth Plot (Band 4 – 5.0MHz QPSK – RB Size 25)




Plot 6-10. Occupied Bandwidth Plot (Band 4 – 5.0MHz 16-QAM – RB Size 25)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 16 of 60




Plot 6-11. Occupied Bandwidth Plot (Band 4 – 10.0MHz QPSK – RB Size 50)




Plot 6-12. Occupied Bandwidth Plot (Band 4 – 10.0MHz 16-QAM – RB Size 50)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 17 of 60




Plot 6-13. Occupied Bandwidth Plot (Band 4 – 15.0MHz QPSK – RB Size 75)




Plot 6-14. Occupied Bandwidth Plot (Band 4 – 15.0MHz 16-QAM – RB Size 75)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 18 of 60



Plot 6-15. Occupied Bandwidth Plot (Band 4 – 20.0MHz QPSK – RB Size 100)



Plot 6-16. Occupied Bandwidth Plot (Band 4 – 20.0MHz 16-QAM – RB Size 100)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 19 of 60

6.3 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051 §27.53(c.2) §27.53(h)

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 v02r02 – Section 6.0

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to at least 10 * the fundamental frequency (separated into at least two plots per channel)
2. Detector = RMS
3. Trace mode = trace average
4. Sweep time = auto couple
5. The trace was allowed to stabilize
6. Please see test notes below for RBW and VBW settings

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.







Figure 6-2. Test Instrument & Measurement Setup


Test Notes

Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for frequencies less than 1 GHz and 1 MHz or greater for frequencies greater than 1 GHz. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset	Page 20 of 60	




Plot 6-17. Conducted Spurious Plot (Band 13 – 5.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)




Plot 6-18. Conducted Spurious Plot (Band 13 – 5.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)

FCC ID: V65CD8100	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)	KYOCERA	Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 21 of 60




Plot 6-19. Conducted Spurious Plot (Band 13 – 5.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)




Plot 6-20. Conducted Spurious Plot (Band 13 – 5.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 22 of 60




Plot 6-21. Conducted Spurious Plot (Band 13 – 5.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)




Plot 6-22. Conducted Spurious Plot (Band 13 – 5.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 23 of 60




Plot 6-23. Conducted Spurious Plot (Band 13 – 5.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)




Plot 6-24. Conducted Spurious Plot (Band 13 – 5.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 24 of 60




Plot 6-25. Conducted Spurious Plot (Band 13 – 5.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)




Plot 6-26. Conducted Spurious Plot (Band 4 – 10.0MHz QPSK – RB Size 1, RB Offset 0– Low Channel)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 25 of 60




Plot 6-27. Conducted Spurious Plot (Band 4 – 10.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)




Plot 6-28. Conducted Spurious Plot (Band 4 – 10.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 26 of 60




Plot 6-29. Conducted Spurious Plot (Band 4 – 10.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)




Plot 6-30. Conducted Spurious Plot (Band 4 – 10.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 27 of 60




Plot 6-31. Conducted Spurious Plot (Band 4 – 10.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)




Plot 6-32. Conducted Spurious Plot (Band 4 – 10.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 28 of 60



Plot 6-33. Conducted Spurious Plot (Band 4 – 10.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)



Plot 6-34. Conducted Spurious Plot (Band 4 – 10.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 29 of 60

6.4 Band Edge Emissions at Antenna Terminal

§2.1051 §27.53(c) §27.53(h)

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 v02r02 – Section 6.0

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW \geq 1% of the emission bandwidth
4. VBW \geq 3 x RBW
5. Detector = RMS
6. Number of sweep points \geq 2 x Span/RBW
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Figure 6-3. Test Instrument & Measurement Setup


Test Notes

Per 27.53(h) in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.


Per 27.53(c.5) for operations in the 776-788 MHz band, in the 100 kHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least 30 kHz may be employed to demonstrate compliance with the out-of-band emissions limit.

For all plots showing emissions in the 763 – 775MHz and 793 – 805MHz band, the FCC limit per 27.53(c.4) is $65 + 10\log_{10}(P) = -35\text{dBm}$ in a 6.25kHz bandwidth.

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 30 of 60




Plot 6-35. Lower Band Edge Plot (Band 13 – 5.0MHz QPSK – RB Size 25)




Plot 6-36. Lower Emission Mask Edge Plot (Band 13 – 5.0MHz QPSK – RB Size 25)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 31 of 60




Plot 6-37. Upper Band Edge Plot (Band 13 – 5.0MHz QPSK – RB Size 25)




Plot 6-38. Upper Emission Mask Edge Plot (Band 13 – 5.0MHz QPSK – RB Size 25)

FCC ID: V65CD8100	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)	KYOCERA	Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 32 of 60




Plot 6-39. Lower Band Edge Plot (Band 13 – 10.0MHz QPSK – RB Size 50)




Plot 6-40. Lower Emission Mask Edge Plot (Band 13 – 10.0MHz QPSK – RB Size 50)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 33 of 60




Plot 6-41. Upper Band Edge Plot (Band 13 – 10.0MHz QPSK – RB Size 50)




Plot 6-42. Upper Emission Mask Edge Plot (Band 13 – 10.0MHz QPSK – RB Size 50)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 34 of 60



Plot 6-43. Lower Band Edge Plot (Band 4 – 1.4MHz QPSK – RB Size 6)




Plot 6-44. Lower Extended Band Edge Plot (Band 4 – 1.4MHz QPSK – RB Size 6)

FCC ID: V65CD8100	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)	KYOCERA	Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 35 of 60




Plot 6-45. Upper Band Edge Plot (Band 4 – 1.4MHz QPSK – RB Size 6)




Plot 6-46. Upper Extended Band Edge Plot (Band 4 – 1.4MHz QPSK – RB Size 6)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 36 of 60




Plot 6-47. Lower Band Edge Plot (Band 4 – 3.0MHz QPSK – RB Size 15)




Plot 6-48. Lower Extended Band Edge Plot (Band 4 – 3.0MHz QPSK – RB Size 15)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 37 of 60




Plot 6-49. Upper Band Edge Plot (Band 4 – 3.0MHz QPSK – RB Size 15)




Plot 6-50. Upper Extended Band Edge Plot (Band 4 – 3.0MHz QPSK – RB Size 15)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 38 of 60




Plot 6-51. Lower Band Edge Plot (Band 4 – 5.0MHz QPSK – RB Size 25)




Plot 6-52. Lower Extended Band Edge Plot (Band 4 – 5.0MHz QPSK – RB Size 25)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 39 of 60




Plot 6-53. Upper Band Edge Plot (Band 4 – 5.0MHz QPSK – RB Size 25)




Plot 6-54. Upper Extended Band Edge Plot (Band 4 – 5.0MHz QPSK – RB Size 25)

FCC ID: V65CD8100	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)	KYOCERA	Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 40 of 60




Plot 6-55. Lower Band Edge Plot (Band 4 – 10.0MHz QPSK – RB Size 50)




Plot 6-56. Lower Extended Band Edge Plot (Band 4 – 10.0MHz QPSK – RB Size 50)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 41 of 60




Plot 6-57. Upper Band Edge Plot (Band 4 – 10.0MHz QPSK – RB Size 50)




Plot 6-58. Upper Extended Band Edge Plot (Band 4 – 10.0MHz QPSK – RB Size 50)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 42 of 60




Plot 6-59. Lower Band Edge Plot (Band 4 – 15.0MHz QPSK – RB Size 75)




Plot 6-60. Lower Extended Band Edge Plot (Band 4 – 15.0MHz QPSK – RB Size 75)

FCC ID: V65CD8100	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)	KYOCERA	Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 43 of 60




Plot 6-61. Upper Band Edge Plot (Band 4 – 15.0MHz QPSK – RB Size 75)




Plot 6-62. Upper Extended Band Edge Plot (Band 4 – 15.0MHz QPSK – RB Size 75)

FCC ID: V65CD8100	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)	KYOCERA	Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 44 of 60




Plot 6-63. Lower Band Edge Plot (Band 4 – 20.0MHz QPSK – RB Size 100)




Plot 6-64. Lower Extended Band Edge Plot (Band 4 – 20.0MHz QPSK – RB Size 100)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 45 of 60



Plot 6-65. Upper Band Edge Plot (Band 4 – 20.0MHz QPSK – RB Size 100)



Plot 6-66. Upper Extended Band Edge Plot (Band 4 – 20.0MHz QPSK – RB Size 100)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 46 of 60

6.5 Radiated Power (ERP/EIRP)

§24.232(c.2) §27.50(b.10) §27.50(d.4)

Test Overview

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI/TIA-603-C-2004 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.



Test Procedures Used

KDB 971168 v02r02 – Section 5.2.1

ANSI/TIA-603-C-2004 – Section 2.2.17

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW \geq 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points \geq 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset	Page 47 of 60	

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Figure 6-4. Test Instrument & Measurement Setup

Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.



Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBd]	ERP [dBm]	ERP Limit [dBm]	Margin [dB]
779.50	5	QPSK	V	1.72	163	1 / 0	14.07	2.47	16.54	34.77	-18.23
782.00	5	QPSK	V	1.74	168	1 / 0	14.19	2.51	16.70	34.77	-18.07
784.50	5	QPSK	V	1.66	171	1 / 0	13.95	2.56	16.51	34.77	-18.26
779.50	5	16QAM	V	1.72	163	1 / 0	12.92	2.47	15.39	34.77	-19.38
782.00	5	16QAM	V	1.74	168	1 / 0	13.03	2.51	15.54	34.77	-19.23
784.50	5	16QAM	V	1.66	171	1 / 0	13.27	2.56	15.83	34.77	-18.94
782.00	10	QPSK	V	1.52	167	1 / 49	13.61	2.51	16.12	34.77	-18.65
782.00	10	16QAM	V	1.52	167	1 / 49	13.17	2.51	15.68	34.77	-19.09

Table 6-2. ERP Data (Band 13)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset	Page 48 of 60	

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
1710.70	1.4	QPSK	V	1.00	90	3 / 2	13.19	9.28	22.47	30.00	-7.53
1732.50	1.4	QPSK	V	1.00	75	1 / 0	12.18	9.00	21.18	30.00	-8.82
1754.30	1.4	QPSK	V	1.00	305	3 / 2	11.85	8.72	20.57	30.00	-9.43
1710.70	1.4	16-QAM	V	1.00	90	3 / 2	12.65	9.28	21.93	30.00	-8.07
1732.50	1.4	16-QAM	V	1.00	75	1 / 0	11.62	9.00	20.62	30.00	-9.38
1754.30	1.4	16-QAM	V	1.00	305	3 / 2	11.10	8.72	19.82	30.00	-10.18
1711.50	3	QPSK	V	1.38	311	1 / 14	14.12	9.27	23.39	30.00	-6.61
1732.50	3	QPSK	V	1.35	333	1 / 0	14.53	9.00	23.53	30.00	-6.47
1753.50	3	QPSK	V	1.20	335	1 / 14	12.90	8.73	21.63	30.00	-8.37
1711.50	3	16-QAM	V	1.38	311	1 / 14	13.45	9.27	22.72	30.00	-7.28
1732.50	3	16-QAM	V	1.35	333	1 / 0	14.21	9.00	23.21	30.00	-6.79
1753.50	3	16-QAM	V	1.20	335	1 / 14	11.96	8.73	20.69	30.00	-9.31
1712.50	5	QPSK	V	1.37	331	1 / 24	14.08	9.26	23.34	30.00	-6.66
1732.50	5	QPSK	V	1.36	75	1 / 0	12.33	9.00	21.33	30.00	-8.67
1752.50	5	QPSK	V	1.20	334	1 / 0	12.72	8.74	21.46	30.00	-8.54
1712.50	5	16-QAM	V	1.37	331	1 / 24	13.31	9.26	22.57	30.00	-7.43
1732.50	5	16-QAM	V	1.36	75	1 / 0	11.80	9.00	20.80	30.00	-9.20
1752.50	5	16-QAM	V	1.20	334	1 / 0	11.33	8.74	20.07	30.00	-9.93
1715.00	10	QPSK	V	1.37	329	1 / 49	14.26	9.22	23.48	30.00	-6.52
1732.50	10	QPSK	V	1.38	75	1 / 0	12.81	9.00	21.81	30.00	-8.19
1750.00	10	QPSK	V	1.30	334	1 / 0	13.63	8.77	22.40	30.00	-7.60
1715.00	10	16-QAM	V	1.37	329	1 / 49	13.52	9.22	22.74	30.00	-7.26
1732.50	10	16-QAM	V	1.38	75	1 / 0	11.90	9.00	20.90	30.00	-9.10
1750.00	10	16-QAM	V	1.30	334	1 / 0	12.57	8.77	21.34	30.00	-8.66
1717.50	15	QPSK	V	1.40	332	1 / 0	13.84	9.19	23.03	30.00	-6.97
1732.50	15	QPSK	V	1.30	332	1 / 74	13.83	9.00	22.83	30.00	-7.17
1747.50	15	QPSK	V	1.26	332	1 / 0	13.32	8.80	22.12	30.00	-7.88
1717.50	15	16-QAM	V	1.40	332	1 / 0	12.84	9.19	22.03	30.00	-7.97
1732.50	15	16-QAM	V	1.30	332	1 / 74	13.19	9.00	22.19	30.00	-7.81
1747.50	15	16-QAM	V	1.26	332	1 / 0	12.99	8.80	21.79	30.00	-8.21
1720.00	20	QPSK	V	1.33	330	1 / 99	13.83	9.16	22.99	30.00	-7.01
1732.50	20	QPSK	V	1.33	334	1 / 0	14.06	9.00	23.06	30.00	-6.94
1745.00	20	QPSK	V	1.27	330	1 / 0	13.14	8.83	21.97	30.00	-8.03
1720.00	20	16-QAM	V	1.33	330	1 / 99	12.72	9.16	21.88	30.00	-8.12
1732.50	20	16-QAM	V	1.33	334	1 / 0	12.61	9.00	21.61	30.00	-8.39
1745.00	20	16-QAM	V	1.27	330	1 / 0	12.55	8.83	21.38	30.00	-8.62

Table 6-3. EIRP Data (Band 4)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset	Page 49 of 60	

6.6 Radiated Spurious Emissions Measurements

§2.1053 §27.53(c) §27.53(f) §27.53(h)

Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-C-2004 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 v02r02 – Section 5.8

ANSI/TIA-603-C-2004 – Section 2.2.12

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW \geq 3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points \geq 2 x span / RBW
5. Detector = Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Figure 6-5. Test Instrument & Measurement Setup

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 50 of 60



Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.
- 3) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 4) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.

OPERATING FREQUENCY: 779.50 MHz
 CHANNEL: 23205
 MEASURED OUTPUT POWER: 16.54 dBm = 0.045 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 29.54 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
2338.50	H	1.00	78	-53.80	7.28	-46.53	63.1
3118.00	H	1.00	68	-61.80	7.25	-54.54	71.1
3897.50	H	1.00	68	-59.14	7.10	-52.04	68.6

Table 6-4. Radiated Spurious Data (Band 13 – Low Channel)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset	Page 51 of 60	

OPERATING FREQUENCY: 782.00 MHz
 CHANNEL: 23230
 MEASURED OUTPUT POWER: 16.70 dBm = 0.047 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 29.70 dBc



Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
2346.00	H	1.07	197	-54.14	7.26	-46.88	63.6
3128.00	H	1.00	201	-60.20	7.26	-52.94	69.6
3910.00	H	1.00	201	-56.91	7.14	-49.77	66.5

Table 6-5. Radiated Spurious Data (Band 13 – Mid Channel)

OPERATING FREQUENCY: 784.50 MHz
 CHANNEL: 23255
 MEASURED OUTPUT POWER: 16.51 dBm = 0.045 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 29.51 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
2353.50	H	1.00	78	-51.60	7.25	-44.35	60.9
3138.00	H	1.00	76	-58.89	7.27	-51.62	68.1
3922.50	H	1.00	76	-56.40	7.20	-49.20	65.7

Table 6-6. Radiated Spurious Data (Band 13 – High Channel)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset	Page 52 of 60	

MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.00 MHz
 DISTANCE: 3 meters
 NARROWBAND EMISSION LIMIT: -50 dBm
 WIDEBAND EMISSION LIMIT: -40 dBm/MHz



Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	Margin [dB]
1559.00	H	1.00	65	-55.04	6.42	-48.62	-8.6
1564.00	H	1.00	152	-53.47	6.44	-47.03	-7.0
1569.00	H	1.00	60	-56.25	6.46	-49.79	-9.8

Table 6-7. Radiated Spurious Data (Band 13 – 1559-1610MHz Band)

OPERATING FREQUENCY: 1711.50 MHz
 CHANNEL: 19965
 MEASURED OUTPUT POWER: 23.39 dBm = 0.218 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 3.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 36.39 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3423.00	H	1.00	257	-48.28	9.68	-38.59	62.0
5134.50	H	1.00	257	-57.87	10.68	-47.18	70.6
6846.00	H	1.00	126	-55.15	11.74	-43.40	66.8
8557.50	H	1.00	126	-50.70	11.05	-39.65	63.0

Table 6-8. Radiated Spurious Data (Band 4 – Low Channel)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset	Page 53 of 60	

OPERATING FREQUENCY: 1732.50 MHz
 CHANNEL: 20175
 MEASURED OUTPUT POWER: 23.53 dBm = 0.225 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 3.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 36.53 dBc



Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3465.00	H	1.00	257	-45.76	9.71	-36.06	59.6
5197.50	H	1.00	257	-56.78	10.59	-46.20	69.7
6930.00	H	1.00	118	-54.13	11.75	-42.38	65.9
8662.50	H	1.00	118	-50.41	11.06	-39.35	62.9

Table 6-9. Radiated Spurious Data (Band 4 – Mid Channel)

OPERATING FREQUENCY: 1753.50 MHz
 CHANNEL: 20385
 MEASURED OUTPUT POWER: 21.63 dBm = 0.145 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 3.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 34.63 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3507.00	H	1.00	260	-51.00	9.73	-41.27	62.9
5260.50	H	1.00	260	-56.41	10.64	-45.77	67.4
7014.00	H	1.00	122	-55.02	11.75	-43.27	64.9
8767.50	H	1.00	122	-50.19	11.00	-39.19	60.8

Table 6-10. Radiated Spurious Data (Band 4 – High Channel)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset	Page 54 of 60	

6.7 Frequency Stability / Temperature Variation

§2.1055 §27.54

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-C-2004. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

For Part 27, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Test Procedure Used

ANSI/TIA-603-C-2004

Test Settings



1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

Test Notes

None

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset	Page 55 of 60	

Band 13 Frequency Stability Measurements

§2.1055 §27.54



OPERATING FREQUENCY: 782,000,000 Hz
 CHANNEL: 23230
 REFERENCE VOLTAGE: 3.80 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	781,999,993	-7	-0.0000009
100 %		- 30	782,000,316	316	0.0000404
100 %		- 20	781,999,774	-226	-0.0000289
100 %		- 10	782,000,109	109	0.0000139
100 %		0	782,000,190	190	0.0000243
100 %		+ 10	782,000,126	126	0.0000161
100 %		+ 20	781,999,852	-148	-0.0000189
100 %		+ 30	781,999,949	-51	-0.0000065
100 %		+ 40	782,000,161	161	0.0000206
100 %		+ 50	782,000,065	65	0.0000083
BATT. ENDPOINT	3.40	+ 20	782,000,146	146	0.0000187

Table 6-11. Frequency Stability Data (Band 13)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: V65CD8100	 FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset	Page 56 of 60	

Band 13 Frequency Stability Measurements
§2.1055 §27.54






Figure 6-6. Frequency Stability Graph (Band 13)

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset	Page 57 of 60	

Band 4 Frequency Stability Measurements

§2.1055 §§27.54



OPERATING FREQUENCY: 1,732,500,000 Hz
 CHANNEL: 20175
 REFERENCE VOLTAGE: 3.80 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	1,732,500,057	57	0.0000033
100 %		- 30	1,732,499,886	-114	-0.0000066
100 %		- 20	1,732,499,890	-110	-0.0000063
100 %		- 10	1,732,500,225	225	0.0000130
100 %		0	1,732,500,144	144	0.0000083
100 %		+ 10	1,732,500,397	397	0.0000229
100 %		+ 20	1,732,500,126	126	0.0000073
100 %		+ 30	1,732,500,167	167	0.0000096
100 %		+ 40	1,732,499,930	-70	-0.0000040
100 %		+ 50	1,732,499,998	-2	-0.0000001
BATT. ENDPOINT	3.40	+ 20	1,732,499,989	-11	-0.0000006

Table 6-12. Frequency Stability Data (Band 4)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset	Page 58 of 60	

Band 4 Frequency Stability Measurements
§2.1055 §§27.54






Figure 6-7. Frequency Stability Graph (Band 4)

FCC ID: V65CD8100	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)	KYOCERA	Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset	Page 59 of 60	

7.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Kyocera Portable Handset FCC ID: V65CD8100** complies with all the requirements of Part 27 of the FCC rules for LTE operation only.

FCC ID: V65CD8100		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1509141769-R3.V65	Test Dates: 9/14-9/23/2015	EUT Type: Portable Handset		Page 60 of 60