



FCC CFR47 PART 22 SUBPART H
FCC CFR47 PART 24 SUBPART E
FCC CFR47 PART 27 SUBPART L

CLASS II PERMISSIVE CHANGE
CERTIFICATION TEST REPORT

FOR

TRI-BAND CDMA PHONE WITH BLUETOOTH EDR AND WIFI

FCC MODEL NUMBER: M6000

FCC ID: V65M6000

REPORT NUMBER: 10U13091- 3

ISSUE DATE: MARCH 08, 2010

Prepared for

KYOCERA COMMUNICATIONS, INC
10300 CAMPUS POINT DRIVE
SAN DIEGO, CA 92121, U.S.A.

Prepared by

COMPLIANCE CERTIFICATION SERVICES
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888

NVLAP®

NVLAP LAB CODE 200065-0

Revision History

Rev.	Issue Date	Revisions	Revised By
--	03/08/10	Initial Issue	T. Chan

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS.....	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION.....	5
4. CALIBRATION AND UNCERTAINTY	5
4.1. <i>MEASURING INSTRUMENT CALIBRATION.....</i>	<i>5</i>
4.2. <i>SAMPLE CALCULATION.....</i>	<i>5</i>
4.3. <i>MEASUREMENT UNCERTAINTY.....</i>	<i>5</i>
5. EQUIPMENT UNDER TEST	6
5.1. <i>DESCRIPTION OF EUT.....</i>	<i>6</i>
5.2. <i>MAXIMUM CONDUCTED OUTPUT POWER.....</i>	<i>6</i>
5.3. <i>MAXIMUM RADIATED OUTPUT POWER</i>	<i>6</i>
5.4. <i>DESCRIPTION OF CLASS II PERMISSIVE CHANGE.....</i>	<i>7</i>
5.5. <i>SOFTWARE AND FIRMWARE.....</i>	<i>7</i>
5.6. <i>WORST-CASE CONFIGURATION AND MODE</i>	<i>7</i>
5.7. <i>DESCRIPTION OF TEST SETUP.....</i>	<i>9</i>
6. TEST AND MEASUREMENT EQUIPMENT	11
7. LIMITS AND RESULTS	12
7.1. <i>RADIATED OUTPUT POWER.....</i>	<i>12</i>
7.2. <i>FIELD STRENGTH OF SPURIOUS RADIATION</i>	<i>16</i>
8. SETUP PHOTOS.....	20

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: KYOCERA COMMUNICATIONS, INC
10300 CAMPUS POINT DRIVE
SAN DIEGO, CA 92121, USA

EUT DESCRIPTION: TRI-BAND CDMA PHONE WITH BLUETOOTH EDR AND WIFI

FCC MODEL: V65M6000

SERIAL NUMBER: A0000012FEEBF4

DATE TESTED: MARCH 4 TO 5, 2010

APPLICABLE STANDARDS6		TEST RESULTS
STANDARD	FCC PART 22H, 24E, AND 27L	PASS

Compliance Certification Services, Inc. (CCS) tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by CCS based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.


Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Compliance Certification Services and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Compliance Certification Services will constitute fraud and shall nullify the document. No part of this report may be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any government agency.

Approved & Released For CCS By:



THU CHAN
EMC MANAGER
COMPLIANCE CERTIFICATION SERVICES

Tested By:



MENGISTU MEKURIA
EMC ENGINEER
COMPLIANCE CERTIFICATION SERVICES

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with TIA-603-C, FCC CFR 47 Part 2, FCC CFR 47 Part 22, FCC CFR Part 24, and FCC Part 27.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

Field Strength (dBuV/m) = Measured Voltage (dBuV) + Antenna Factor (dB/m) +
Cable Loss (dB) – Preamp Gain (dB)

$$36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} = 28.9 \text{ dBuV/m}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 1000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a Bluetooth, EDR, and WiFi featured Tri-band CDMA Phone that manufactured by Kyocera Wireless Corporations.

5.2. MAXIMUM CONDUCTED OUTPUT POWER

The test measurement passed within $\pm 0.5\text{dBm}$ of the original output power.

5.3. MAXIMUM RADIATED OUTPUT POWER

The transmitter has a maximum ERP & EIRP output powers as follows:

824 to 849 MHz Authorized Band

Frequency Range (MHz)	Modulation	ERP Peak Power (dBm)	ERP Peak Power (mW)
Low CH - 824.70	CDMA2000	25.2	331.1
Mid CH - 836.52		26.3	426.6
High CH - 848.31		25.7	371.5

1850 to 1910 MHz Authorized Band

Frequency Range (MHz)	Modulation	EIRP Peak Power (dBm)	EIRP Peak Power (mW)
Low CH - 1851.25	CDMA2000	29.7	933.3
Mid CH - 1880.00		30.3	1071.5
High CH - 1908.75		28.8	758.6

1710 to 1755 MHz Authorized Band

Frequency Range (MHz)	Modulation	EIRP Peak Power (dBm)	EIRP Peak Power (mW)
Low CH - 1711.25	AWS	25.8	380.2
MID-Ch- 1733.00		24.6	288.4
High CH - 1754.75		26.0	398.1

5.4. DESCRIPTION OF CLASS II PERMISSIVE CHANGE

The major change filed under this application is adding Mechanical Enclosure.

5.5. SOFTWARE AND FIRMWARE

The EUT is linked with Agilent Communication Test Set.

5.6. WORST-CASE CONFIGURATION AND MODE

The worst-position was the EUT with highest emissions. To determine the worst-case, the EUT was investigated for X, Y, and Z-Positions, and the worst position among X, Y, and Z with AC/DC adapter, after the investigations, the worst-position was turned out to be an Y-position without AC/DC adapter for Cell band and X-position with AC/DC for AWS, and PCS bands.

PROCEDURE USED TO ESTABLISH TEST SIGNAL**3G-CDMA2000 1xRTT**

This procedure assumes the Agilent 8960 Test Set has the following applications installed and with valid license.

<u>Application</u>	<u>Rev. License</u>
CDMA2000 Mobil Test	B.10.11, L

1xRTT

- Call Setup > Shift & Preset
- Protocol Rev > 6 (IS-2000-0)
- Radio Config (RC) > RC3 (Fwd3, Rvs3)
- FCH Service Option (SO) Setup > 55
- Traffic Data Rate > Full
- TDSO SCH Info > F-SCH Parameters > F-SCH Data Rate > 153.6 kbps
 > R-SCH Parameters > R-SCH Data Rate > 153.6 kbps
- Cell Info > Cell Parameters > System ID (SID) > 2
 > Network ID (NID) > 0

Once "Active Cell" show "Connected" then change "Rvs Power Ctrl" from "Active bits" to "**All Up bits**" to get the maximum power.

Worst-case Measurement Result @ Low, Middle and High Channel

Worst-case Measurement Result for Low, Middle and High Channel under Radio Configuration RC3 and Service Option 55.

5.7. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT


PERIPHERAL SUPPORT EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	FCC ID
AC/DC Adapter	Kyocera	SCP-23ADT	4018	DOC

I/O CABLES

I/O CABLE LIST						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length	Remarks
1	DC Input	1	Mini-USB	Un-Shielded	1.0 m	N/A

TEST SETUP

The EUT is a CDMA phone and is tested as a standalone configuration. Communications Test Set is used to link the device under test.

SETUP DIAGRAM FOR TESTS

6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST				
Description	Manufacturer	Model	Asset	Cal Due
Preamplifier, 1300 MHz	Agilent / HP	8447D	C00885	07/06/10
Preamplifier, 26.5 GHz	Agilent / HP	8449B	C01052	08/04/10
Preamplifier, 26.5 GHz	Agilent / HP	8449B	C01063	08/04/10
Antenna, Bilog, 2 GHz	Sunol Sciences	JB1	C01016	07/14/10
Antenna, Bilog, 2 GHz	Sunol Sciences	JB1	C01011	07/14/10
Antenna, Horn, 18 GHz	EMCO	3115	C00945	07/29/10
Antenna, Horn, 18 GHz	EMCO	3115	C00783	07/29/10
Antenna, Horn, 18 GHz	EMCO	3115	C00943	07/29/10
Dipole	Speag	D900V2	NA	11/16/11
Highpass Filter, 1.5 GHz	Micro-Tronics	HPM13193	N02689`	CNR
Highpass Filter, 2.7 GHz	Micro-Tronics	HPM13194	N02687	CNR
Signal Generator	R & S	SMP04	C00953	02/16/11
Communications Test Set	R & S	CMU200	C001131	04/16/10
Communications Test Set	Agilent / HP	E5515C	C01086	06/16/10
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C01069	10/08/10
EMI Test Receiver, 30 MHz	R & S	ESHS 20	N02396	05/06/11
LISN, 30 MHz	FCC	LISN-50/250-25-2	N02625	11/06/10

7. LIMITS AND RESULTS

7.1. RADIATED OUTPUT POWER

LIMITS

22.913(a) The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

24.232(b) & RSS133 § 6.4 Mobile/portable stations are limited to 2 watts e.i.r.p. peak power and the equipment must employ means to limit the power to the minimum necessary for successful communications.

27.50 (d) (2) & RSS-139 § 6.4 Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band are limited to a peak EIRP of 1 watt.

RSS-132 § 4.4 The maximum ERP shall be 6.3 Watts for mobile stations.

TEST PROCEDURE

ANSI / TIA / EIA 603 Clause 2.2.17, RSS-132, RSS-133, & RSS-139

RESULTS

CELL OUTPUT POWER (ERP)

High Frequency Substitution Measurement Compliance Certification Services Chamber B														
Company:	KYOCERA													
Project #:	10U13091													
Date:	3/4/2010													
Test Engineer:	MENGISTU MEKURIA													
Configuration:	EUT WITH AC ADAPTER													
Mode:	TX, CELL BAND													
Test Equipment:														
Receiving: Sunol T130, and 3m Chamber N-type Cable (Setup this one for testing EUT)														
Substitution: Dipole S/N: 00022117, 6ft SMA Cable (SN # 208947003) Warehouse.														
f MHz	SA reading (dBm)	Ant. Pol. (H/V)	Path Loss (dBm)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes							
824.70	-16.0	V	32.6	16.6	38.5	-21.8								
824.70	-5.1	H	30.4	25.2	38.5	-13.2								
836.52	-15.1	V	32.7	17.6	38.5	-20.9								
836.52	-4.4	H	30.7	26.3	38.5	-12.1								
848.31	-15.0	V	32.0	16.9	38.5	-21.5								
848.31	-5.0	H	30.8	25.7	38.5	-12.7								

Rev. 1.24.7

PCS OUTPUT POWER (EIRP)**High Frequency Fundamental Measurement
Compliance Certification Services Chamber B**

Company: KYOCERA
Project #: 10U13091
Date: 3/4/2010
Test Engineer: MENGISTU MEKURIA
Configuration: EUT WITH AC ADAPTER
Mode: TX, PCS BAND

Test Equipment:**Receiving:** Horn T59, and Chamber B SMA Cables**Substitution:** Horn T72 Substitution, 6ft SMA Cable (208947003) Warehouse

f GHz	SA reading (dBm)	Ant. Pol. (H/V)	Path Loss (dBm)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
1.851	-21.1	V	40.2	19.1	33.0	-13.9	
1.851	-9.8	H	39.5	29.7	33.0	-3.3	
1.880	-16.5	V	40.3	23.7	33.0	-9.3	
1.880	-9.9	H	40.1	30.3	33.0	-2.8	
1.909	-18.3	V	40.2	21.9	33.0	-11.1	
1.909	-11.3	H	40.1	28.8	33.0	-4.2	

Rev. 1.24.7

AWS OUTPUT POWER (EIRP)

**High Frequency Fundamental Measurement
Compliance Certification Services Chamber A**

Company: KYOCERA
Project #: 10U13091
Date: 3/4/2010
Test Engineer: MENGISTU MEKURIA
Configuration: EUT WITH AC ADAPTER
Mode: TX, AWS BAND

Test Equipment:**Receiving:** Horn T59, and Camber B SMA Cables**Substitution:** Horn T72 Substitution, 6ft SMA Cable (208947003) Warehouse

f GHz	SA reading (dBm)	Ant. Pol. (H/V)	Path Loss (dBm)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
1.711	-22.5	V	39.9	17.3	30.0	-12.7	
1.711	-12.9	H	38.6	25.8	30.0	-4.2	
1.733	-22.5	V	40.4	18.0	30.0	-12.1	
1.733	-14.6	H	39.2	24.6	30.0	-5.5	
1.755	-21.2	V	40.2	19.0	30.0	-11.0	
1.755	-13.5	H	39.6	26.0	30.0	-4.0	

Rev. 1.24.7

7.2. FIELD STRENGTH OF SPURIOUS RADIATION

LIMIT

§22.917 (e) and §24.238 (a), RSS-132 § 4.5.1, & RSS-133 § 6.5.1 (a) (i) & (b): Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.

§27.53 (g) and RSS-139 § 6.5 For operations in the 1710–1755MHz and 2110–2155 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10} (P)$ dB.

TEST PROCEDURE

ANSI / TIA / EIA 603 Clause 3.2.12 & FCC 22.917 (b), FCC 24.238 (b), & FCC 27.53 (g)(1)(2)(3), RSS-132, RSS-133, & RSS-139

RESULTS

CELL SPURIOUS & HARMONIC (ERP)

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement										
Company:	KYOCERA									
Project #:	10U13091									
Date:	3/5/2010									
Test Engineer:	MENGISTU MEKURIA									
Configuration:	EUT WITH AC ADAPTER									
Mode:	TX, CELL BAND									
Chamber	Pre-amplifier	Filter	Limit							
5m Chamber A	T144 8449B	Filter 1	FCC PART 22							
f GHz	SA reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Path Loss (dB)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
LOW CH. (826.70 MHz)										
1.653	-30.9	H	3.0	36.6	38.1	1.0	-31.5	-13.0	-18.5	
2.480	-48.8	H	3.0	40.0	37.5	1.0	-45.3	-13.0	-32.3	
3.307	-38.0	H	3.0	43.9	37.1	1.0	-30.2	-13.0	-17.2	
4.134	-44.3	H	3.0	46.2	36.5	1.0	-33.7	-13.0	-20.7	
4.960	-54.1	H	3.0	48.6	36.3	1.0	-40.8	-13.0	-27.8	
5.787	-61.1	H	3.0	50.3	36.3	1.0	-46.1	-13.0	-33.1	
1.653	-20.4	V	3.0	36.9	38.1	1.0	-20.7	-13.0	-7.7	
2.480	-46.5	V	3.0	41.7	37.5	1.0	-41.2	-13.0	-28.2	
3.307	-37.2	V	3.0	44.0	37.1	1.0	-29.3	-13.0	-16.3	
4.134	-48.4	V	3.0	45.9	36.5	1.0	-38.0	-13.0	-25.0	
4.960	-57.5	V	3.0	48.1	36.3	1.0	-44.6	-13.0	-31.6	
5.787	-60.8	V	3.0	49.6	36.3	1.0	-46.5	-13.0	-33.5	
MID CH. (836.52 MHz)										
1.673	-31.9	H	3.0	36.8	38.1	1.0	-32.2	-13.0	-19.2	
2.510	-50.1	H	3.0	40.1	37.5	1.0	-46.4	-13.0	-33.4	
3.346	-37.3	H	3.0	44.0	37.1	1.0	-29.4	-13.0	-16.4	
4.183	-46.2	H	3.0	46.4	36.5	1.0	-35.4	-13.0	-22.4	
5.019	-55.7	H	3.0	48.8	36.3	1.0	-42.2	-13.0	-29.2	
5.856	-59.6	H	3.0	50.5	36.3	1.0	-44.5	-13.0	-31.5	
1.673	-24.2	V	3.0	37.1	38.1	1.0	-24.2	-13.0	-11.2	
2.510	-48.8	V	3.0	41.8	37.5	1.0	-43.4	-13.0	-30.4	
3.346	-36.6	V	3.0	44.1	37.1	1.0	-28.6	-13.0	-15.6	
4.183	-49.8	V	3.0	46.1	36.5	1.0	-39.2	-13.0	-26.2	
5.019	-59.4	V	3.0	48.3	36.3	1.0	-46.4	-13.0	-33.4	
5.856	-61.9	V	3.0	49.7	36.3	1.0	-47.5	-13.0	-34.5	
HII CH. (848.31 MHz)										
1.697	-34.7	H	3.0	37.0	38.1	1.0	-34.7	-13.0	-21.7	
2.545	-56.8	H	3.0	40.3	37.5	1.0	-52.9	-13.0	-39.9	
3.393	-42.7	H	3.0	44.1	37.1	1.0	-34.6	-13.0	-21.6	
4.242	-53.7	H	3.0	46.5	36.5	1.0	-42.7	-13.0	-29.7	
5.090	-63.6	H	3.0	49.0	36.3	1.0	-49.8	-13.0	-36.8	
5.938	-65.9	H	3.0	50.6	36.3	1.0	-50.6	-13.0	-37.6	
1.697	-28.7	V	3.0	37.4	38.1	1.0	-28.4	-13.0	-15.4	
2.545	-55.5	V	3.0	42.0	37.5	1.0	-50.0	-13.0	-37.0	
3.393	-44.4	V	3.0	44.2	37.1	1.0	-36.2	-13.0	-23.2	
4.242	-56.9	V	3.0	46.2	36.5	1.0	-46.2	-13.0	-33.2	
5.090	-64.0	V	3.0	48.5	36.3	1.0	-50.7	-13.0	-37.7	
5.938	-62.4	V	3.0	49.8	36.3	1.0	-47.9	-13.0	-34.9	

Note: No other emissions were detected within 40 dB margin to the limit
Rev. 03.03.09

PCS Spurious & Harmonic (EIRP)

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement										
Company:	KYOCERA									
Project #:	10U13091									
Date:	3/5/2010									
Test Engineer:	MENGISTU MEKURIA									
Configuration:	EUT WITH AC ADAPTER									
Mode:	TX, PCS BAND									
Chamber		Pre-amplifier		Filter		Limit				
5m Chamber A		T144 8449B		Filter 1		FCC PART 24				
f GHz	SA reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Path Loss (dB)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
LOW CH. (1851.25 MHz)										
3.703	51.8	H	3.0	45.0	36.8	1.0	-42.6	-13.0	29.6	
5.554	-50.6	H	3.0	49.9	36.3	1.0	-35.9	-13.0	-22.9	
7.405	57.8	H	3.0	52.9	36.6	1.0	-40.5	-13.0	27.5	
9.256	-55.1	H	3.0	55.3	37.0	1.0	-35.9	-13.0	-22.9	
11.108	-67.4	H	3.0	55.9	36.9	1.0	-47.5	-13.0	34.5	
12.959	-61.0	H	3.0	57.2	36.0	1.0	-38.8	-13.0	-25.8	
14.810	-64.2	H	3.0	60.4	34.8	1.0	-37.6	-13.0	-24.6	
3.703	-53.6	V	3.0	44.9	36.8	1.0	-44.5	-13.0	-31.5	
5.554	-48.6	V	3.0	49.3	36.3	1.0	-34.6	-13.0	-21.6	
7.405	-58.8	V	3.0	51.8	36.6	1.0	-42.5	-13.0	-29.5	
9.256	-49.5	V	3.0	54.2	37.0	1.0	-31.2	-13.0	-18.2	
11.108	-67.0	V	3.0	56.3	36.9	1.0	-46.5	-13.0	33.5	
12.959	-49.2	V	3.0	58.2	36.0	1.0	-26.1	-13.0	-13.1	
14.810	-55.7	V	3.0	60.1	34.8	1.0	-29.5	-13.0	-16.5	
MID CH. (1800.00 MHz)										
3.760	-54.0	H	3.0	45.2	36.8	1.0	-44.6	-13.0	-31.6	
5.640	-52.0	H	3.0	50.1	36.3	1.0	-37.2	-13.0	-24.2	
7.520	-65.4	H	3.0	53.1	36.6	1.0	-48.0	-13.0	-35.0	
9.400	-57.8	H	3.0	55.4	37.0	1.0	-38.5	-13.0	-25.5	
11.280	-68.8	H	3.0	55.8	36.8	1.0	-48.8	-13.0	-35.8	
13.160	-63.1	H	3.0	57.6	35.9	1.0	-40.4	-13.0	-27.4	
15.040	-64.4	V	3.0	60.1	34.7	1.0	-37.9	-13.0	-24.9	
3.760	-49.2	V	3.0	45.1	36.8	1.0	-40.0	-13.0	-27.0	
5.640	-48.2	V	3.0	49.4	36.3	1.0	-34.1	-13.0	-21.1	
7.520	-63.9	V	3.0	52.0	36.6	1.0	-47.6	-13.0	-34.6	
9.400	-52.9	V	3.0	54.4	37.0	1.0	-34.5	-13.0	-21.5	
11.280	-68.8	V	3.0	56.5	36.8	1.0	-48.2	-13.0	-35.2	
13.160	-52.2	V	3.0	58.4	35.9	1.0	-28.7	-13.0	-15.7	
15.040	-57.4	V	3.0	60.1	34.7	1.0	-31.0	-13.0	-18.0	
HI CH. (1908.75 MHz)										
3.818	-53.1	H	3.0	45.3	36.7	1.0	-43.5	-13.0	-30.5	
5.726	-57.8	H	3.0	50.2	36.3	1.0	-42.9	-13.0	-29.9	
7.635	-65.4	H	3.0	53.2	36.6	1.0	-47.8	-13.0	-34.8	
9.544	-58.6	H	3.0	55.6	37.1	1.0	-39.0	-13.0	-26.0	
11.453	-69.0	H	3.0	55.7	36.8	1.0	-49.0	-13.0	-36.0	
13.361	-64.3	H	3.0	57.9	35.8	1.0	-41.2	-13.0	-28.2	
15.270	-67.9	V	3.0	59.5	34.8	1.0	-42.2	-13.0	-29.2	
3.818	-47.4	V	3.0	45.2	36.7	1.0	-37.9	-13.0	-24.9	
5.726	-52.9	V	3.0	49.5	36.3	1.0	-38.7	-13.0	-25.7	
7.635	-63.2	V	3.0	52.1	36.6	1.0	-46.7	-13.0	-33.7	
9.544	-52.8	V	3.0	54.6	37.1	1.0	-34.3	-13.0	-21.3	
11.453	-68.0	V	3.0	56.7	36.8	1.0	-47.2	-13.0	-34.2	
13.361	-53.6	V	3.0	58.6	35.8	1.0	-29.8	-13.0	-16.8	
15.270	-60.3	V	3.0	59.5	34.8	1.0	-34.6	-13.0	-21.6	

Note: No other emissions were detected within 40 dB margin to the limit
Rev. 03.03.09

AWS Spurious & Harmonic (EIRP)

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement										
Company:	KYOCERA									
Project #:	10U13091									
Date:	3/4/2010									
Test Engineer:	MENGISTU MEKURIA									
Configuration:	EUT WITH AC ADAPTER									
Mode:	TX, AWS BAND									
Chamber			Pre-amplifier			Filter		Limit		
5m Chamber A			T144 8449B			Filter 1		FCC PART 27		
f GHz	SA reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Path Loss (dB)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
LOW CH. (1711.25 MHz)										
3.423	-51.6	H	3.0	44.2	37.0	1.0	-43.4	-13.0	-30.4	
5.134	-63.8	H	3.0	49.2	36.3	1.0	-49.9	-13.0	-36.9	
8.556	-61.9	H	3.0	54.4	36.8	1.0	-43.3	-13.0	-30.3	
10.268	-68.0	H	3.0	56.1	37.1	1.0	-48.0	-13.0	-35.0	
3.423	-48.6	V	3.0	44.3	37.0	1.0	-40.4	-13.0	-27.4	
5.134	-61.3	V	3.0	48.6	36.3	1.0	-47.9	-13.0	-34.9	
8.556	-57.1	V	3.0	53.3	36.8	1.0	-39.6	-13.0	-26.6	
10.268	-57.1	V	3.0	55.5	37.1	1.0	-37.7	-13.0	-24.7	
MID CH. (1733 MHz)										
3.466	-55.6	H	3.0	44.3	37.0	1.0	-47.3	-13.0	-34.3	
5.199	-63.2	H	3.0	49.3	36.2	1.0	-49.1	-13.0	-36.1	
8.665	-66.9	H	3.0	54.5	36.9	1.0	-48.3	-13.0	-35.3	
10.398	-68.6	H	3.0	56.1	37.1	1.0	-48.6	-13.0	-35.6	
3.466	-55.3	V	3.0	44.4	37.0	1.0	-46.9	-13.0	-33.9	
5.199	-60.7	V	3.0	48.8	36.2	1.0	-47.2	-13.0	-34.2	
8.665	-62.2	V	3.0	53.5	36.9	1.0	-44.6	-13.0	-31.6	
10.398	-64.5	V	3.0	55.6	37.1	1.0	-45.0	-13.0	-32.0	
HI CH. (1754.75 MHz)										
3.510	-55.4	H	3.0	44.5	37.0	1.0	-46.9	-13.0	-33.9	
5.264	-65.8	H	3.0	49.5	36.3	1.0	-51.6	-13.0	-38.6	
8.774	-68.6	H	3.0	54.6	36.9	1.0	-49.8	-13.0	-36.8	
10.529	-68.0	H	3.0	56.0	37.0	1.0	-48.1	-13.0	-35.1	
3.510	-54.9	V	3.0	44.5	37.0	1.0	-46.3	-13.0	-33.3	
5.264	-64.3	V	3.0	48.9	36.3	1.0	-50.6	-13.0	-37.6	
8.774	-60.9	V	3.0	53.6	36.9	1.0	-43.2	-13.0	-30.2	
10.529	-61.8	V	3.0	55.7	37.0	1.0	-42.1	-13.0	-29.1	

Note: No other emissions were detected within 40 dB margin to the limit
Rev. 03.03.09