

Report No. : AK035250-001 Date : 2008-09-24

Application No. : LK227282(1)

Client : Kids Preferred, LLC

81 Twin Rivers Dr., East Windsor, NJ 08520,

United States

Sample Description : One(1) submitted sample(s) stated to be <u>SMART e DOG</u>, <u>SMART e CAT</u>,

SMART e BEAR of Model No. 90645, 90646, 90647 Rating : 2 x 1.5V AA size batteries No. of submitted sample : Three (3) piece(s) ***

Date Received : 2008-08-15.

Test Period : 2008-08-29 to 2008-09-04.

Test Requested : FCC Part 15 Certification.

Test Method : 47 CFR Part 15 (10-1-07 Edition)

ANSI C63.4 - 2003

Test Result : See attached sheet(s) from page 2 to 13.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15

Subpart B.

Remark : All three models are the same in circuitry, components and constructions.

Therefore, model 90647 was chosen to be the representative of the test samples.

For and on behalf of

CMA Industrial Development Foundation Limited

Authorized Signature :

Mr WONG Lap-Pong, Andrew Senior Technical Officer Electrical Division

Page 1 of 13

FCC ID: V7390648



Report No. : AK035250-001 Date : 2008-09-24

Table of Contents

1	Gen	eral Information	3
	1.1	General Description	3
	1.2	Location of the test site	
	1.3	List of measuring equipment	5
	1.4	List of supporting equipment.	
2	Desc	cription of the radiated emission test	7
	2.1	Test Procedure	
	2.2	Test Result	7
	2.3	Radiated Emission Measurement Data	
	2.3	Radiated Emission Measurement Data (Con't)	9
3	Desc	cription of the Line-conducted Test	
	3.1	Test Procedure	10
	3.2	Test Result	10
	3.3	Graph and Table of Conducted Emission Measurement Data	10
4	Phot	ograph	11
	4.1	Photographs of the Test Setup for Radiated Emission and Conducted Emission	11
	4.2	Photographs of the External and Internal Configurations of the EUT	
5	Supp	plementary document	
	5.1	Bandwidth	12
	5.2	Duty cycle	12
	5.3	Transmission time	12
6	Ann	endices	13



Report No. : AK035250-001 Date : 2008-09-24

1 General Information

1.1 General Description

The equipment under test (EUT) is a toy doll for SMART e DOG, SMART e CAT, SMART e BEAR. The oscillation of MCU is generated by a 12MHz crystal. The EUT is powered by 2 x 1.5V AA size batteries. When EUT is turned on and the play button is pressed, we can play games by following the instructions from the toy doll. The EUT can also be connected to a computer. When the EUT is connected to Internet, we can update the program and play computer games.

The brief circuit description is listed as follows:

- X1 and associated circuit act as an oscillator.
- U1 and associated circuit act as a controller.
- U2 and associated circuit act as a NAND flash.
- U4 and associated circuit act as a sound driver.
- U5 and associated circuit act as a voltage regulator.



Report No. : AK035250-001 Date : 2008-09-24

1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at:

Ground Floor, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 - 2003. A shielded room is located at:

Ground Floor, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.



Report No. : AK035250-001 Date : 2008-09-24

1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Due Date
EMI Test Receiver	R&S	ESCI	100152	2008 October 14
EMI Test Receiver	R&S	ESCS30	100001	2008 November 19
Broadband Antenna	Schaffner	CBL6112B	2692	2009 January 21
LISN	R&S	ESH3-Z5	100038	2009 March 01



Report No. : AK035250-001 Date : 2008-09-24

1.4 List of supporting equipment

Computer: 1. Intel CPU P4 2.8GHz / 512k cache / 533MHz bus

Model: 9426A657

2. Intel Mother Board

Model: Intel Type: D845EPI/D845GVSR

3. Seagate Hard-Disk

Model: ST380011A, 80GB

4. Proview LCD Monitor

Model: 568

5. Logitech Mouse Model: M-S34

6. Hewlett Packard Keyboard

Model: SK-2502C

7. Hewlett Packard LaserJet 2100TN

Model: C4172A

8. PenPower Handwriting System

Model: PP403N

9. Earphone



Report No. : AK035250-001 Date : 2008-09-24

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 - 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

The device was rotated through three orthogonal to determine which attitude and configuration produce the highest emission during measurement for radiated emission measurement.

2.2 Test Result

The emissions from 30MHz to 1000MHz were investigated. The highest emissions were presented in next page.

Emissions with more than 20dB below the limit were not reported in next page.

The emissions meeting the requirement of section 15.109 are based on measurements employing the CISPR quasi-peak detector below 1000MHz and average detector for frequencies above 1000MHz.

It was found that the EUT meet the FCC requirement.



Report No. : AK035250-001 Date : 2008-09-24

2.3 Radiated Emission Measurement Data

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart B

Mode: PC connected with data transferring

Frequency	Polarity	Reading at	Antenna and	Field	Limit at 3m	Margin
(MHz)	(H/V)	3m	Cable factor	Strength	$(dB\mu V/m)$	(dB)
		$(dB\mu V/m)$	(dB)	$(dB\mu V/m)$	·	
36.000	V	14.4	15.7	30.1	40.0	-9.9
48.003	Н	21.9	10.5	32.4	40.0	-7.6
96.006	Н	29.2	9.4	38.6	43.5	-4.9
156.010	Н	27.4	12.6	40.0	43.5	-3.5
168.020	Н	25.8	11.0	36.8	43.5	-6.7
192.012	Н	32.5	10.0	42.5	43.5	-1.0
228.014	Н	24.0	10.3	34.3	46.0	-11.7
276.026	Н	17.5	13.7	31.2	46.0	-14.8
300.014	Н	27.1	14.7	41.8	46.0	-4.2
312.028	Н	21.3	14.7	36.0	46.0	-7.5



Report No. : AK035250-001 Date : 2008-09-24

2.3 Radiated Emission Measurement Data (Con't)

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart B

Mode: Playing game

Frequency	Polarity	Reading at	Antenna and	Field	Limit at 3m	Margin
(MHz)	(H/V)	3m	Cable factor	Strength	$(dB\mu V/m)$	(dB)
		$(dB\mu V/m)$	(dB)	$(dB\mu V/m)$	·	
66.403	Н	12.2	5.8	18.0	40.0	-22.0
127.674	Н	8.5	12.6	21.1	43.5	-22.4
168.015	Н	21.7	11.0	32.7	43.5	-10.8
192.012	Н	25.5	10.0	35.5	43.5	-8.0
201.027	Н	14.5	10.3	24.8	43.5	-18.7
210.008	Н	26.8	10.3	37.1	43.5	-6.4
216.016	Н	25.2	10.3	35.5	46.0	-10.5
252.018	Н	18.2	13.7	31.9	46.0	-14.1
276.018	Н	21.9	13.7	35.6	46.0	-10.4
420.060	Н	9.0	18.6	27.6	46.0	-18.4



Report No. : AK035250-001 Date : 2008-09-24

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 - 2003. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

The PC connected mode was tested. The EUT was tested under a data transferring situation without connected to Internet.

It was found that the EUT met the FCC requirement.

3.3 Graph and Table of Conducted Emission Measurement Data

For electronic filing, the documents are saved with filename TestRpt2.pdf.



Report No. : AK035250-001 Date : 2008-09-24

- 4 Photograph
- 4.1 Photographs of the Test Setup for Radiated Emission and Conducted Emission

For electronic filing, the photos are saved with filename Tsup1.jpg to Tsup7.jpg.

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho6.jpg and InPho1.jpg to InPho2.jpg.



Report No. : AK035250-001 Date : 2008-09-24

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

5.1 Bandwidth

Not Applicable

5.2 Duty cycle

Not Applicable

5.3 Transmission time

Not Applicable



Report No. : AK035250-001 Date : 2008-09-24

6 Appendices

A1.	Photos of the set-up of Radiated Emissions	2	pages
A2.	Photos of the set-up of Conducted Emissions	2	pages
A3.	Photos of External Configurations	3	pages
A4.	Photos of Internal Configurations	1	page
A5.	ID Label/Location	1	page
A6.	Conducted Emission Measurement Data	2	pages
A7.	Block Diagram	1	page
A8.	Schematics Diagram	1	page
A9.	User Manual	2	pages
A10.	Operation Description	1	page

***** End of Report *****