

# RF Exposure Evaluation

*of*

E.U.T. : Wireless Remote Control for  
Searchlight  
FCC ID. : V78TXSL014GO  
Model No. : TX-SL014GO  
Working Frequency : 433.92 MHz

*for*

APPLICANT : Allremote Wireless Technology Co., Ltd.  
ADDRESS : 2F., No.8, Aly.16, Ln.235, Baoqiao Rd., Xindian Dist.,  
New Taipei City, 23145, Taiwan

Test Performed by

ELECTRONICS TESTING CENTER (ETC) , TAIWAN  
NO. 34. LIN 5, DINGFU VIL., LINKOU DIST.,  
NEW TAIPEI CITY, TAIWAN, 24442, R.O.C.  
TEL : (02)26023052 FAX : (02)26010910  
<http://www.etc.org.tw> ; e-mail:emc@etc.org.tw

Report Number : 18-12-RBF-011-01-MPE

# TEST REPORT CERTIFICATION

Applicant : Allremote Wireless Technology Co., Ltd.  
2F., No.8, Aly.16, Ln.235, Baoqiao Rd., Xindian Dist., New Taipei City, 23145, Taiwan

Manufacturer : Allremote Wireless Technology Co., Ltd.  
2F., No.8, Aly.16, Ln.235, Baoqiao Rd., Xindian Dist., New Taipei City, 23145, Taiwan

Description of EUT :  
a) Type of EUT : Wireless Remote Control for Searchlight  
b) Trade Name : ALLREMOTE  
c) Model No. : TX-SL014GO  
d) FCC ID : V78TXSL014GO  
e) Working Frequency : 433.92 MHz  
f) Power Supply : DC 12V

Regulation Applied : FCC KDB447498 D01. The equipment fulfills the requirements on power density for general population/uncontrolled exposure and therefore fulfills the requirements of section 1.1310 of FCC 47 CFR Part 1.

Note:

1. The result of the testing report relate only to the item tested.
2. The testing report shall not be reproduced expect in full, without the written approval of ETC

Issued Date : Feb.13, 2019

Test Engineer :

Kazuma Ho

(Kazuma Ho, Engineer )

Vincent Chang

Approve & Authorized Signer :

Vincent Chang, Supervisor  
EMC Dept. II of ELECTRONICS  
TESTING CENTER, TAIWAN

**Product Information:**

Type of EUT: Wireless Remote Control for Searchlight

FCC ID: V78TXSL014GO

Model: TX-SL014GO

According to KDB 447498 section 4.3.1, the 1-g SAR test exclusion thresholds at test separation distance  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

The max. average power of channel, including tune-up tolerance(mW) is 0.0807460mW @ 433.92MHz (With Tune-up tolerance),

The min. test separation distance (mm) is 5 mm,

So,  $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] = 0.0106 < 3.0$  (With Tune-up tolerance).

Therefore, standalone SAR measurements are not required for both head and body.