



## RA-24-07105327-4/A Ed. 1

“This report cancels and replaces the test report n° RA-24-07105327-4/A Edition 0”

### RADIO Measurement Technical Report

Standard to apply:  
FCC Part 15

Equipment under test:  
**BIOMETRIC ACCESS CONTROL  
TERMINAL  
MA521**

FCC ID:  
**V7AMA521**

Company:  
**SAGEM SECURITE**

**DISTRIBUTION: Mr CRUCHAGA**

**Company: SAGEM SECURITE**

**Number of pages: 17 including 2 annexes**

Ed.	Date	Modified pages	Written by Name	Technical Verification Quality Approval Name Visa
1	23-Jul-08	6	L. BERTHAUD <i>LB</i>	

Duplication of this document is only permitted for an integral photographic facsimile. It includes the number of pages referenced here above.  
This document is the result of testing a specimen or a sample of the product submitted. It does not imply an assessment of the conformity of the whole manufactured products of the tested sample.



**Conseils & Ingénierie - Tests & Mesures - Formation**

Z.I. Angers - Beauzoué - 15, rue de la Claié - 49070 BEAUZOUÉ - Siret : 344 545 645 00055  
Tél. : 02 41 73 26 27 - Fax : 02 41 73 26 40 - E-mail : atlantique@emitech.fr - URL : www.emitech.fr  
Siège Social : 3, rue des Coudriers - CAP 78 - ZA de l'Observatoire - 78180 MONTIGNY LE BX  
S.A. au capital de 480 000 € - R.C.S. VERSAILLES 344 545 645 - APE 742C

**PRODUCT:** BIOMETRIC ACCESS CONTROL TERMINAL

**Reference / model:** MA521

**Serial number:** not communicated

**MANUFACTURER:** not communicated

**Responsible:** Mr CRUCHAGA

**DATE(S) OF TEST:** 20 and 27 February 2008

**TESTING LOCATION:** EMITECH ATLANTIQUE laboratory at ANGERS (49) FRANCE  
EMITECH ATLANTIQUE open area test site in LA POUEZE (49) FRANCE  
Registration Number by FCC: 101696/FRN: 0006 6490 08

**TESTED BY:** L. BERTHAUD  
M. DUMESNIL

## CONTENTS

TITLE	PAGE
1. INTRODUCTION.....	4
2. PRODUCT DESCRIPTION .....	4
3. NORMATIVE REFERENCE.....	4
4. TEST METHODOLOGY .....	4
5. TESTS RESULTS SUMMARY.....	5
6. RADIATED EMISSION LIMITS .....	6
7. OPERATION WITHIN THE BAND 13.110 – 14.010 MHZ .....	8
ANNEX 1: PHOTOS OF THE EQUIPMENT UNDER TEST .....	11
ANNEX 2: OPEN AREA TEST SITE, TEST SET UP .....	15

## 1. INTRODUCTION

This report presents the results of radio test carried out on the following equipment:  
BIOMETRIC ACCESS CONTROL TERMINAL MA521, in accordance with normative reference.

## 2. PRODUCT DESCRIPTION

Class: B

Utilization: biometric access control terminal with RFID function

Antenna type: incorporated antenna

Power level, frequency range and channels characteristics are not user adjustable.

The details pictures of the product and the circuit boards are joined with this file.

## 3. NORMATIVE REFERENCE

The standards and testing methods related throughout this report are those listed below.

They are applied on the whole test report even though the extensions (version, date and amendment) are not repeated.

FCC Part 15 (2006) Code of Federal Regulations  
Title 47 - Telecommunication  
Chapter 1 - Federal Communications Commission  
Part 15 - Radio frequency devices  
Subpart C - Intentional Radiators

ANSI C63.4 (03) American National Standard for Methods of measurement of Radio-Noise from low-voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.

## 4. TEST METHODOLOGY

Radio performance tests procedures given in part 15:

- Paragraph 33: frequency range of radiated measurements
- Paragraph 35: measurement detector functions and bandwidths
- Paragraph 203: antenna requirement
- Paragraph 209: radiated emission limits; general requirements
- Paragraph 225: operation within the band 13.110 – 14.010 MHz

**5. TESTS RESULTS SUMMARY**

Test procedure	Description of test	Criteria respected ?				Comment
		Yes	No	NAp	NAs	
FCC Part 15.203	ANTENNA REQUIREMENT	X				
FCC Part 15.209	RADIATED EMISSION LIMITS	X				
FCC Part 15.225	OPERATION WITHIN THE BAND 13.110 – 14.010 MHz					
	a) Field strength of any emission within the band 13.553 – 13.567 MHz	X				
	b) Field strength of any emission within the bands 13.410 – 13.553 MHz and 13.567 – 13.710 MHz	X				<i>Note</i>
	c) Field strength of any emission within the band 13.110 – 13.410 MHz and 13.710 – 14.010 MHz	X				<i>Note</i>
	d) Field strength of any emission outside the band 13.110 – 14.010 MHz	X				See §15.209
	e) Frequency tolerance	X				
	f) Powered tags				X	

NAp: Not Applicable

NAs: Not Asked

*Note: there is no emission radiated in these bands.*

**Conclusion:**

The sample of BIOMETRIC ACCESS CONTROL TERMINAL MA521 submitted to the tests complies with the regulations of the standard FCC Part 15 in accordance with the limits or criteria defined in this report.

## 6. RADIATED EMISSION LIMITS

**Standard:** FCC Part 15

**Test procedure:** paragraph 209

**Test equipment:**

TYPE	BRAND	EMITECH NUMBER
Test receiver	Rohde & Schwarz ESVS 10	1219
Biconical antenna	Hewlet Packard 11966 C	728
Log periodic antenna	Rohde & Schwarz HL 223	1999
Spectrum analyzer	Rohde & Schwarz FSP40	4088
Open area test site	EMITECH	1274
Test receiver	Rohde & Schwarz ESH3	4112
Active loop antenna	EMCO 6502	1406
Power source	Hewlett Packard E3610A	4195

**Test set up:**

The system is tested in an open area test site (OATS).

The test unit is placed on a rotating table, 0.8 m from a ground plane. Zero degree azimuths correspond to the front of the equipment under test.

Only the emissions radiated by the cabinet and the structure are checked.

**Frequency range:** from 9 kHz to harmonic 10 ( $F_{carrier} \leq 1 \text{ GHz}$ )

**Detection mode:** Quasi-peak or average ( $F < 1 \text{ GHz}$ )  
Peak ( $F \geq 1 \text{ GHz}$ )

**Bandwidth:** 120 kHz ( $F < 1 \text{ GHz}$ )  
1 MHz ( $F \geq 1 \text{ GHz}$ )

1| **Distance of antenna:** 3 meters (above 30 MHz)  
10 meters (below 30 MHz)

**Antenna height:** 1 to 4 meters

**Antenna polarization:** vertical and horizontal

**Equipment under test operating condition:**

The equipment is blocked in continuous modulated transmission mode at the highest output power level which the transmitter is intended to operate.

The measure is realized on two supply modes: with a 12 Vd.c. regulated power supply and via a POE switch.

**Results:**

Ambient temperature (°C): 17.5  
 Relative humidity (%): 61

Power source: POE switch

The polarity column refers to the antenna polarity at which the maximum emissions level is measured.

FREQUENCIES (MHz)	Antenna height (cm)	Polarization of antenna H: Horizontal V: Vertical	Azimuth (degrees)	Field strength (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)
27.12	100	V	281	24.3	48.62*	24.32
40.69	100	V	321	28	40	12

Power source: regulated power supply (12 Vd.c.)

The polarity column refers to the antenna polarity at which the maximum emissions level is measured.

FREQUENCIES (MHz)	Antenna height (cm)	Polarization of antenna H: Horizontal V: Vertical	Azimuth (degrees)	Field strength (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)
27.12	100	V	291	24.5	48.62*	24.12
40.69	100	V	325	30.2	40	9.8

\* the applicable limit at 30 m is extrapolated at 10 m by using the square of an inverse linear distance (40 dB/decade).

Any radiated emission which has more than 20 dB margin compared to the limit is not necessary reported.

**TEST CONCLUSION:**

RESPECTED STANDARD

**7. OPERATION WITHIN THE BAND 13.110 – 14.010 MHz****Standard:** FCC Part 15**Test procedure:** paragraph 15.225**Test equipment:**

TYPE	BRAND	EMITECH NUMBER
Test receiver	Rohde & Schwarz ESH3	4112
Active loop antenna	EMCO 6502	1406
Open area test site	EMITECH	1274
Modulation analyzer	Hewlett Packard HP8901B	1211
Power source	Hewlett Packard E3610A	4195

**Test set up:**

The system is tested in an open area test site (OATS).

The test unit is placed on a rotating table, 0.8 m from a ground plane. Zero degree azimuth corresponds to the front of the equipment under test.

The frequency tolerance measure is realized in near-field.

**Distance of antenna:** 10 meters**Antenna height:** 1 meter**Antenna polarization:** vertical**Equipment under test operating condition:**

The equipment is blocked in continuous modulated transmission mode, at the highest output power level which the transmitter is intended to operate.

The measure is realized on two supply modes: with a 12 Vd.c. regulated power supply and via a POE switch.

**Results:**Carrier field strength

Ambient temperature (°C): 19

Relative humidity (%): 56

Sample N° 1

Power supply: POE switch

Field strength (dB $\mu$ V/m) at frequency: <b>13.56 MHz</b>	
<b>Normal test conditions</b>	54.9
<b>Limits</b>	103.08*

Polarization of test antenna: vertical (height: 100 cm)

Position of equipment: use position (azimuth: 300 degrees)

Sample N° 1

Power supply: regulated power source (12 Vd.c.)

Field strength (dB $\mu$ V/m) at frequency: <b>13.56 MHz</b>	
<b>Normal test conditions</b>	55.6
<b>Limits</b>	103.08*

Polarization of test antenna: vertical (height: 100 cm)

Position of equipment: use position (azimuth: 300 degrees)

\* the applicable limit at 30 m is extrapolated at 10 m by using the square of an inverse linear distance (40 dB/decade).

**Frequency stability****Sample N° 1**

Power supply: POE switch

Normal test conditions	Temperature (°C): 18.5 Humidity (%): 47	Nominal power source (V): POE switch	Measured differences (ppm) at frequency: 13.560528 MHz	Limits (ppm)
Extreme test conditions	Minimal temperature (°C): -20	Minimal power source (V): POE switch	-1.6	±100
		Maximal power source (V): POE switch	-1.6	
	Maximal temperature (°C): +50	Minimal power source (V): POE switch	+3.7	
		Maximal power source (V): POE switch	+3.7	

**Sample N° 1**

Power supply: regulated power source (12 Vd.c.)

Normal test conditions	Temperature (°C): 18.5 Humidity (%): 47	Nominal power source (V): 12	Measured differences (ppm) at frequency: 13.560514 MHz	Limits (ppm)
Extreme test conditions	Minimal temperature (°C): -20	Minimal power source (V): 10.2	+1.2	±100
		Maximal power source (V): 13.8	+1.1	
	Maximal temperature (°C): +50	Minimal power source (V): 10.2	+3	
		Maximal power source (V): 13.8	+4.7	

**Measurement uncertainty:**  $\pm 1 \times 10^{-7}$ **Test conclusion:****RESPECTED STANDARD**

□□□ End of report, 2 annexes to be forwarded □□□

**ANNEX 1: PHOTOS OF THE EQUIPMENT UNDER TEST****GENERAL VIEW**


EMITECH

EMITECH

EMITECH

EMITECH

Internal view



EMITECH


EMITECH

EMITECH


EMITECH

EMITECH

Internal view



## Antenna



EMITECH

EMITECH

EMITECH

EMITECH

EMITECH

**ANNEX 2: OPEN AREA TEST SITE, TEST SET UP****Test set up**

Test set up (POE switch)



Test set up (regulated power supply)



**Open area test site**