



中认信通

CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



TEST REPORT

Applicant: SHENZHEN TENDA TECHNOLOGY CO.,LTD.

Address: 6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road, Nanshan District, Shenzhen, China. 518052

FCC ID: V7TAC10V4

Product Name: AC1200 Dual-band Gigabit Wireless Router

Model Number: AC8, RC8

Standard(s): 47 CFR Part 15, Subpart C(15.247)
ANSI C63.10-2013
KDB 558074 D01 15.247 Meas Guidance v05r02

The above equipment has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR221046538-00AA1

Date Of Issue: 2022/11/8

Reviewed By: Sun Zhong

Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,
Guangdong, China

Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

TEST FACILITY	2
DECLARATIONS.....	2
1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 DESCRIPTION OF TEST CONFIGURATION.....	7
1.2.1 Testing purposes	7
1.2.2 EUT Operation Condition:.....	7
1.2.3 Support Equipment List and Details	8
1.2.4 Support Cable List and Details	8
1.2.5 Block Diagram of Test Setup	8
1.3 MEASUREMENT UNCERTAINTY	10
2. SUMMARY OF TEST RESULTS	11
3. REQUIREMENTS AND TEST PROCEDURES	12
3.1 AC LINE CONDUCTED EMISSIONS.....	12
3.1.1 Applicable Standard.....	12
3.1.2 EUT Setup.....	13
3.1.3 EMI Test Receiver Setup	13
3.1.4 Test Procedure	14
3.1.5 Corrected Amplitude & Margin Calculation.....	14
3.2 RADIATION SPURIOUS EMISSIONS	15
3.2.1 Applicable Standard.....	15
3.2.2 EUT Setup.....	15
3.2.3 EMI Test Receiver & Spectrum Analyzer Setup	16
3.2.4 Test Procedure	16
3.2.5 Corrected Amplitude & Margin Calculation.....	16
3.3 6 dB EMISSION BANDWIDTH:	17
3.3.1 Applicable Standard.....	17
3.3.2 EUT Setup.....	17
3.3.3 Test Procedure	17
3.4 MAXIMUM PEAK CONDUCTED OUTPUT POWER:	18
3.4.1 Applicable Standard.....	18
3.4.2 EUT Setup.....	18
3.4.3 Test Procedure	18
3.5 MAXIMUM POWER SPECTRAL DENSITY:	19
3.5.1 Applicable Standard.....	19
3.5.2 EUT Setup.....	19
3.5.3 Test Procedure	19
3.6 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE:	20
3.6.1 Applicable Standard.....	20
3.6.2 EUT Setup.....	20
3.6.3 Test Procedure	20
3.7 DUTY CYCLE:	21

3.7.1 EUT Setup.....	21
3.7.2 Test Procedure	21
3.8 ANTENNA REQUIREMENT.....	21
3.8.1 Applicable Standard.....	21
3.8.2 Judgment.....	21
4. Test DATA AND RESULTS.....	22
4.1 AC LINE CONDUCTED EMISSIONS.....	22
4.2 RADIATION SPURIOUS EMISSIONS	25
4.3 MAXIMUM PEAK CONDUCTED OUTPUT POWER SPOT CHECK:	36
5. RF EXPOSURE EVALUATION	37
5.1 APPLICABLE STANDARD.....	37
5.2 MEASUREMENT RESULT	38

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	AC1200 Dual-band Gigabit Wireless Router
EUT Model:	AC8
Multiple Model:	RC8
Operation Frequency:	2412-2462 MHz(802.11b/g/n ht20) 2422-2452 MHz(802.11n ht40)
Maximum Peak Output Power (Conducted):	25.22dBm
Modulation Type:	802.11b:DSSS-DBPSK, DQPSK, CCK 802.11g/n:OFDM-BPSK, QPSK, 16QAM, 64QAM
Rated Input Voltage:	DC 12V from Adapter
Serial Number:	CR221046538-RF-A1
EUT Received Date:	2022/10/18
EUT Received Status:	Good
Note: The Multiple model is electrically identical with test model, please refer to the declaration letter for more detail, which was provided by applicant.	

Operation Frequency Detail: For 802.11b/g/n ht20:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

Per section 15.31(m), the below frequencies were performed the test as below:

Test Channel	Frequency (MHz)
Lowest	2412
Middle	2437
Highest	2462

For 802.11n ht40:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	7	2442
4	2427	8	2447
5	2432	9	2452
6	2437	/	/

Per section 15.31(m), the below frequencies were performed the test as below:

Test Channel	Frequency (MHz)
Lowest	2422
Middle	2437
Highest	2452

Antenna Information Detail▲:

Antenna Chain	Manufacturer	Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
2.4G Chain 0	Tenda	Dipole	50	2400-2500MHz	5.0 dBi
2.4G Chain 1	Tenda	Dipole	50	2400-2500MHz	5.0 dBi

The Method of §15.203 Compliance:

- ☒ Antenna must be permanently attached to the unit.
- ☐ Antenna must use a unique type of connector to attach to the EUT.
- ☐ Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Accessory Information:

Accessory Description	Manufacturer	Model	Parameters
Adapter	SHENZHEN HEWEISHUN NETWORK TECHNOLOGY CO.,LTD.	BN073-A12012U	Input:100-240V, 50~60Hz,0.4A Output:12V,1A

1.2 Description of Test Configuration

1.2.1 Testing purposes

This is Class II Permissive Change Application based on the Original device, Model Number: AC10, FCC ID: V7TAC10V4, the changes as following, which were provided by manufacturer:

1. Changed the model name to AC8,RC8
2. Changed the product name to AC1200 Dual-band Gigabit Wireless Router
3. Changed the product shell
4. Changed the CPU heat sink
5. Changed the mesh filter.

Per the difference between them and spot check with the RF output power, the RF parameters have not been changed. Only the AC line conducted emission and radiated emission were tested.

1.2.2 EUT Operation Condition:

EUT Operation Mode:			The system was configured for testing in Engineering Mode, which was provided by the manufacturer.		
Equipment Modifications:			No		
EUT Exercise Software:			CMD		
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer ▲:					
Mode	Channel	Frequency (MHz)	Data Rate	Power Level Setting	
				Chain 0	Chain 1
802.11b	Lowest	2412	1Mbps	9	9
	Middle	2437	1Mbps	9	9
	Highest	2462	1Mbps	11	10
802.11g	Lowest	2412	6Mbps	11	10
	Middle	2437	6Mbps	15	15
	Highest	2462	6Mbps	15	15
802.11n ht20	Lowest	2412	MCS0	15	15
	Middle	2437	MCS0	15	15
	Highest	2462	MCS0	15	15
802.11n ht40	Lowest	2422	MCS0	15	15
	Middle	2437	MCS0	15	15
	Highest	2452	MCS0	15	15
Note:					
1. The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.					
2. The device supports SISO in all modes, and MIMO 2T2R in 802.11n modes, per pretest, 2T2R mode was the worst mode and reported for 802.11n modes.					
3. The system supports Beamforming and Non-beamforming modes at 802.11n a modes. The two modes have same output power, and the Beamforming gain is 3 dBi▲, which are declared by manufacturer. Therefore, the all RF conducted test were performed at Non-beamforming mode only.					

1.2.3 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Lenovo	Laptop	T460S	60PDTEK8
Unknown	Load	Load-1	Load-1

1.2.4 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
RJ45 Cable	Yes	No	10	EUT	Laptop
RJ45 Cable*3	Yes	No	10	EUT	Load

1.2.5 Block Diagram of Test Setup

AC line conducted emissions:



Spurious Emissions:



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	$\pm 5\%$
RF output power, conducted	$\pm 0.61\text{dB}$
Power Spectral Density, conducted	$\pm 0.61\text{ dB}$
Unwanted Emissions, radiated	30M~200MHz: 4.15 dB, 200M~1GHz: 5.61 dB, 1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	$\pm 1.26\text{ dB}$
Temperature	$\pm 1^{\circ}\text{C}$
Humidity	$\pm 5\%$
DC and low frequency voltages	$\pm 0.4\%$
Duty Cycle	1%
AC Power Lines Conducted Emission	2.8 dB (150 kHz to 30 MHz)

2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result
§15.207(a)	AC line conducted emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Bandwidth	Compliant*
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant*
§15.247(e)	Power Spectral Density	Compliant*
§15.203	Antenna Requirement	Compliant*
§15.247 (i) & §1.1307 & §2.1091	RF Exposure Evaluation	Compliant

Compliant*: the changes not affect this test, the test result please refer to the original report: CR22080002-00A.

3. REQUIREMENTS AND TEST PROCEDURES

3.1 AC Line Conducted Emissions

3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

3.1.2 EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

3.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

3.2 Radiation Spurious Emissions


3.2.1 Applicable Standard

FCC §15.247 (d);


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.2.2 EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

3.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss- Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result


3.3 6 dB Emission Bandwidth:

3.3.1 Applicable Standard

FCC §15.247 (a)(2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

3.3.2 EUT Setup



3.3.3 Test Procedure

According to ANSI C63.10-2013 Section 11.8

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


3.4 Maximum peak conducted output power:

3.4.1 Applicable Standard

FCC §15.247 (b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

3.4.2 EUT Setup



3.4.3 Test Procedure

According to ANSI C63.10-2013 Section 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

- a) Set the EUT in transmitting mode.
- b) Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
- c) Add a correction factor to the display.
- d) Set the power meter to test peak output power, record the result.


3.5 Maximum power spectral density:

3.5.1 Applicable Standard

FCC §15.247 (e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.5.2 EUT Setup



3.5.3 Test Procedure

According to ANSI C63.10-2013 Section 11.10.2

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.


3.6 100 kHz Bandwidth of Frequency Band Edge:

3.6.1 Applicable Standard

FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.6.2 EUT Setup



3.6.3 Test Procedure


According to ANSI C63.10-2013 Section 11.11

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

3.7 Duty Cycle:

3.7.1 EUT Setup



3.7.2 Test Procedure

According to ANSI C63.10-2013 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

3.8 Antenna Requirement

3.8.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.8.2 Judgment

Result: Compliant. Please refer to the Antenna Information detail in Section 1.

4. Test DATA AND RESULTS

4.1 AC Line Conducted Emissions

Serial Number:	CR221046538-RF-A1	Test Date:	2022/10/24
Test Site:	CE	Test Mode:	Transmitting (802.11b Chain 0 Middle channel was the worst)
Tester:	Vic Du	Test Result:	Pass

Environmental Conditions:


Temperature: (°C)	25.9	Relative Humidity: (%)	66	ATM Pressure: (kPa)	100.8
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101134	2022/04/01	2023/03/31
R&S	EMI Test Receiver	ESR3	102726	2022/07/15	2023/07/14
MICRO-COAX	Coaxial Cable	UTIFLEX	C-0200-01	2022/08/07	2023/08/06
Audix	Test Software	E3	190306 (V9)	N/A	N/A


* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Mode: Transmitting
Port: Line
Note:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.156	5.72	9.61	15.33	55.66	40.33	Average
2	0.156	20.09	9.61	29.70	65.66	35.96	QP
3	0.482	21.76	9.61	31.37	46.30	14.93	Average
4	0.482	26.83	9.61	36.44	56.30	19.86	QP
5	1.236	13.14	9.62	22.76	46.00	23.24	Average
6	1.236	23.27	9.62	32.89	56.00	23.11	QP
7	2.587	13.62	9.64	23.26	46.00	22.74	Average
8	2.587	23.32	9.64	32.96	56.00	23.04	QP
9	13.151	18.37	9.68	28.05	50.00	21.95	Average
10	13.151	27.65	9.68	37.33	60.00	22.67	QP
11	16.894	17.28	9.73	27.01	50.00	22.99	Average
12	16.894	26.30	9.73	36.03	60.00	23.97	QP

Test Mode: Transmitting
Port: neutral
Note:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.153	11.86	9.61	21.47	55.84	34.37	Average
2	0.153	24.79	9.61	34.40	65.84	31.44	QP
3	0.456	21.56	9.61	31.17	46.76	15.59	Average
4	0.456	30.08	9.61	39.69	56.76	17.07	QP
5	0.922	19.37	9.62	28.99	46.00	17.01	Average
6	0.922	29.25	9.62	38.87	56.00	17.13	QP
7	1.967	19.62	9.63	29.25	46.00	16.75	Average
8	1.967	30.58	9.63	40.21	56.00	15.79	QP
9	3.832	19.68	9.65	29.33	46.00	16.67	Average
10	3.832	29.81	9.65	39.46	56.00	16.54	QP
11	14.116	28.78	9.68	38.46	50.00	11.54	Average
12	14.116	42.25	9.68	51.93	60.00	8.07	QP

4.2 Radiation Spurious Emissions

Serial Number:	CR221046538-RF-A1	Test Date:	2022/10/24~2022/10/26
Test Site:	966-1, 966-2	Test Mode:	Transmitting
Tester:	coco Tian, Carl Xue	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.7~27	Relative Humidity: (%)	55~57	ATM Pressure: (kPa)	100.8~101.2
----------------------	---------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB6	A082520-5	2020/10/19	2023/10/18
R&S	EMI Test Receiver	ESR3	102724	2022/07/15	2023/07/14
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2022/07/17	2023/07/16
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2022/07/17	2023/07/16
Sonoma	Amplifier	310N	186165	2022/07/17	2023/07/16
ETS-Lindgren	Horn Antenna	3115	9912-5985	2020/10/13	2023/10/12
R&S	Spectrum Analyzer	FSV40	101591	2022/07/15	2023/07/14
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2022/08/07	2023/08/06
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2022/08/07	2023/08/06
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2021/11/10	2022/11/09
Audix	Test Software	E3	201021 (V9)	N/A	N/A
PASTERNAK	Horn Antenna	PE9852/2F-20	112002	2021/02/05	2024/02/04
AH	Preamplifier	PAM-1840VH	190	2021/11/19	2022/11/18
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2022/08/07	2023/08/06
E-Microwave	Band Rejection Filter	2400-2483.5MHz	OE01902424	2022/08/07	2023/08/06
Mini Circuits	High Pass Filter	VHF-6010+	31119	2022/08/07	2023/08/06

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:

Please refer to the below table and plots.


Note: The device can be mounted in multiple orientations, test was performed with X,Y, Z Axis according to C63.10 figure 8, the worst orientation was photographed and it's data was recorded.

1) 30MHz-1GHz(802.11b Chain 0 Low channel was the worst)

Test Mode: Transmitting
Polarization: horizontal
Note:



Test Mode: Transmitting
Polarization: vertical
Note:



2) 1-25GHz:

802.11b Mode, Chain 0:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2412 MHz							
2412.000	65.23	PK	H	31.53	96.76	N/A	N/A
2412.000	52.19	AV	H	31.53	83.72	N/A	N/A
2412.000	70.21	PK	V	31.53	101.74	N/A	N/A
2412.000	58.12	AV	V	31.53	89.65	N/A	N/A
2390.000	27.02	PK	V	31.46	58.48	74.00	15.52
2390.000	13.70	AV	V	31.46	45.16	54.00	8.84
4824.000	38.36	PK	V	10.94	49.30	74.00	24.70
4824.000	25.31	AV	V	10.94	36.25	54.00	17.75
7236.000	36.33	PK	V	14.44	50.77	74.00	23.23
7236.000	24.23	AV	V	14.44	38.67	54.00	15.33
9648.000	38.18	PK	V	18.63	56.81	74.00	17.19
9648.000	33.18	AV	V	18.63	51.81	54.00	2.19
Middle Channel: 2437 MHz							
2437.000	69.38	PK	H	31.60	100.98	N/A	N/A
2437.000	56.12	AV	H	31.60	87.72	N/A	N/A
2437.000	78.02	PK	V	31.60	109.62	N/A	N/A
2437.000	66.08	AV	V	31.60	97.68	N/A	N/A
4874.000	33.16	PK	V	11.05	44.21	74.00	29.79
4874.000	21.18	AV	V	11.05	32.23	54.00	21.77
7311.000	34.01	PK	V	14.80	48.81	74.00	25.19
7311.000	21.65	AV	V	14.80	36.45	54.00	17.55
9748.000	35.11	PK	V	18.56	53.67	74.00	20.33
9748.000	29.85	AV	V	18.56	48.41	54.00	5.59
High Channel: 2462MHz							
2462.000	68.78	PK	H	31.63	100.41	N/A	N/A
2462.000	56.32	AV	H	31.63	87.95	N/A	N/A
2462.000	75.16	PK	V	31.63	106.79	N/A	N/A
2462.000	64.18	AV	V	31.63	95.81	N/A	N/A
2483.500	26.47	PK	V	31.64	58.11	74.00	15.89
2483.500	16.23	AV	V	31.64	47.87	54.00	6.13
4924.000	41.85	PK	V	11.18	53.03	74.00	20.97
4924.000	37.81	AV	V	11.18	48.99	54.00	5.01
7386.000	33.72	PK	V	14.89	48.61	74.00	25.39
7386.000	21.37	AV	V	14.89	36.26	54.00	17.74
9848.000	37.88	PK	V	18.74	56.62	74.00	17.38
9848.000	30.02	AV	V	18.74	48.76	54.00	5.24

802.11b Mode, Chain 1:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2412 MHz							
2412.000	70.62	PK	H	31.53	102.15	N/A	N/A
2412.000	60.21	AV	H	31.53	91.74	N/A	N/A
2412.000	76.18	PK	V	31.53	107.71	N/A	N/A
2412.000	66.35	AV	V	31.53	97.88	N/A	N/A
2390.000	30.69	PK	V	31.46	62.15	74.00	11.85
2390.000	15.47	AV	V	31.46	46.93	54.00	7.07
4824.000	45.28	PK	V	10.94	56.22	74.00	17.78
4824.000	33.68	AV	V	10.94	44.62	54.00	9.38
7236.000	32.15	PK	V	14.44	46.59	74.00	27.41
7236.000	20.08	AV	V	14.44	34.52	54.00	19.48
9648.000	41.75	PK	V	18.63	60.38	74.00	13.62
9648.000	32.74	AV	V	18.63	51.37	54.00	2.63
Middle Channel: 2437 MHz							
2437.000	65.36	PK	H	31.60	96.96	N/A	N/A
2437.000	54.74	AV	H	31.60	86.34	N/A	N/A
2437.000	73.05	PK	V	31.60	104.65	N/A	N/A
2437.000	64.12	AV	V	31.60	95.72	N/A	N/A
4874.000	42.65	PK	V	11.05	53.70	74.00	20.30
4874.000	35.68	AV	V	11.05	46.73	54.00	7.27
7311.000	33.12	PK	V	14.80	47.92	74.00	26.08
7311.000	20.17	AV	V	14.80	34.97	54.00	19.03
9748.000	41.05	PK	V	18.56	59.61	74.00	14.39
9748.000	32.05	AV	V	18.56	50.61	54.00	3.39
High Channel: 2462MHz							
2462.000	68.08	PK	H	31.63	99.71	N/A	N/A
2462.000	58.32	AV	H	31.63	89.95	N/A	N/A
2462.000	76.89	PK	V	31.63	108.52	N/A	N/A
2462.000	66.17	AV	V	31.63	97.80	N/A	N/A
2483.500	40.28	PK	V	31.64	71.92	74.00	2.08
2483.500	19.68	AV	V	31.64	51.32	54.00	2.68
4924.000	42.58	PK	V	11.18	53.76	74.00	20.24
4924.000	32.58	AV	V	11.18	43.76	54.00	10.24
7386.000	33.27	PK	V	14.89	48.16	74.00	25.84
7386.000	21.08	AV	V	14.89	35.97	54.00	18.03
9848.000	37.24	PK	V	18.74	55.98	74.00	18.02
9848.000	29.88	AV	V	18.74	48.62	54.00	5.38

802.11g Mode Chain 0:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2412 MHz							
2412.000	67.68	PK	H	31.53	99.21	N/A	N/A
2412.000	57.74	AV	H	31.53	89.27	N/A	N/A
2412.000	73.25	PK	V	31.53	104.78	N/A	N/A
2412.000	63.46	AV	V	31.53	94.99	N/A	N/A
2390.000	27.83	PK	V	31.46	59.29	74.00	14.71
2390.000	14.65	AV	V	31.46	46.11	54.00	7.89
4824.000	44.37	PK	V	10.94	55.31	74.00	18.69
4824.000	32.64	AV	V	10.94	43.58	54.00	10.42
7236.000	33.05	PK	V	14.44	47.49	74.00	26.51
7236.000	20.76	AV	V	14.44	35.20	54.00	18.80
Middle Channel: 2437 MHz							
2437.000	66.14	PK	H	31.60	97.74	N/A	N/A
2437.000	56.33	AV	H	31.60	87.93	N/A	N/A
2437.000	72.19	PK	V	31.60	103.79	N/A	N/A
2437.000	62.22	AV	V	31.60	93.82	N/A	N/A
4874.000	42.67	PK	V	11.05	53.72	74.00	20.28
4874.000	30.37	AV	V	11.05	41.42	54.00	12.58
7311.000	33.04	PK	V	14.80	47.84	74.00	26.16
7311.000	20.65	AV	V	14.80	35.45	54.00	18.55
High Channel: 2462MHz							
2462.000	67.14	PK	H	31.63	98.77	N/A	N/A
2462.000	57.30	AV	H	31.63	88.93	N/A	N/A
2462.000	75.35	PK	V	31.63	106.98	N/A	N/A
2462.000	65.81	AV	V	31.63	97.44	N/A	N/A
2483.500	38.76	PK	V	31.64	70.40	74.00	3.60
2483.500	18.64	AV	V	31.64	50.28	54.00	3.72
4924.000	41.74	PK	V	11.18	52.92	74.00	21.08
4924.000	29.35	AV	V	11.18	40.53	54.00	13.47
7386.000	33.12	PK	V	14.89	48.01	74.00	25.99
7386.000	21.76	AV	V	14.89	36.65	54.00	17.35

802.11g Mode Chain 1:


Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2412 MHz							
2412.000	68.01	PK	H	31.53	99.54	N/A	N/A
2412.000	58.05	AV	H	31.53	89.58	N/A	N/A
2412.000	73.59	PK	V	31.53	105.12	N/A	N/A
2412.000	63.77	AV	V	31.53	95.30	N/A	N/A
2390.000	28.14	PK	V	31.46	59.60	74.00	14.40
2390.000	14.96	AV	V	31.46	46.42	54.00	7.58
4824.000	44.68	PK	V	10.94	55.62	74.00	18.38
4824.000	33.01	AV	V	10.94	43.95	54.00	10.05
7236.000	33.36	PK	V	14.44	47.80	74.00	26.20
7236.000	21.07	AV	V	14.44	35.51	54.00	18.49
Middle Channel: 2437 MHz							
2437.000	66.51	PK	H	31.60	98.11	N/A	N/A
2437.000	56.71	AV	H	31.60	88.31	N/A	N/A
2437.000	72.61	PK	V	31.60	104.21	N/A	N/A
2437.000	62.63	AV	V	31.60	94.23	N/A	N/A
4874.000	43.11	PK	V	11.05	54.16	74.00	19.84
4874.000	30.78	AV	V	11.05	41.83	54.00	12.17
7311.000	33.45	PK	V	14.80	48.25	74.00	25.75
7311.000	21.21	AV	V	14.80	36.01	54.00	17.99
High Channel: 2462MHz							
2462.000	67.51	PK	H	31.63	99.14	N/A	N/A
2462.000	57.76	AV	H	31.63	89.39	N/A	N/A
2462.000	75.82	PK	V	31.63	107.45	N/A	N/A
2462.000	66.28	AV	V	31.63	97.91	N/A	N/A
2483.500	38.76	PK	V	31.64	70.40	74.00	3.60
2483.500	18.82	AV	V	31.64	50.46	54.00	3.54
4924.000	42.21	PK	V	11.18	53.39	74.00	20.61
4924.000	29.82	AV	V	11.18	41.00	54.00	13.00
7386.000	33.59	PK	V	14.89	48.48	74.00	25.52
7386.000	22.23	AV	V	14.89	37.12	54.00	16.88

802.11n ht20 Mode(2TX Non-beamforming mode was the worst):

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2412 MHz							
2412.000	69.57	PK	H	31.53	101.10	N/A	N/A
2412.000	56.79	AV	H	31.53	88.32	N/A	N/A
2412.000	73.23	PK	V	31.53	104.76	N/A	N/A
2412.000	60.91	AV	V	31.53	92.44	N/A	N/A
2390.000	17.61	PK	V	31.46	49.07	74.00	24.93
2390.000	14.49	AV	V	31.46	45.95	54.00	8.05
4824.000	33.26	PK	V	10.94	44.20	74.00	29.80
4824.000	20.47	AV	V	10.94	31.41	54.00	22.59
7236.000	33.42	PK	V	14.44	47.86	74.00	26.14
7236.000	20.54	AV	V	14.44	34.98	54.00	19.02
Middle Channel: 2437 MHz							
2437.000	69.12	PK	H	31.60	100.72	N/A	N/A
2437.000	57.61	AV	H	31.60	89.21	N/A	N/A
2437.000	74.76	PK	V	31.60	106.36	N/A	N/A
2437.000	62.61	AV	V	31.60	94.21	N/A	N/A
4874.000	39.60	PK	V	11.05	50.65	74.00	23.35
4874.000	29.24	AV	V	11.05	40.29	54.00	13.71
7311.000	35.32	PK	V	14.80	50.12	74.00	23.88
7311.000	23.18	AV	V	14.80	37.98	54.00	16.02
High Channel: 2462MHz							
2462.000	68.18	PK	H	31.63	99.81	N/A	N/A
2462.000	56.58	AV	H	31.63	88.21	N/A	N/A
2462.000	75.86	PK	V	31.63	107.49	N/A	N/A
2462.000	63.30	AV	V	31.63	94.93	N/A	N/A
2483.500	33.86	PK	V	31.64	65.50	74.00	8.50
2483.500	17.02	AV	V	31.64	48.66	54.00	5.34
4924.000	38.76	PK	V	11.18	49.94	74.00	24.06
4924.000	28.69	AV	V	11.18	39.87	54.00	14.13
7386.000	34.48	PK	V	14.89	49.37	74.00	24.63
7386.000	22.31	AV	V	14.89	37.20	54.00	16.80


802.11n ht40 Mode(2TX Non-beamforming mode was the worst):

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2422 MHz							
2422.000	66.16	PK	H	31.56	97.72	N/A	N/A
2422.000	55.01	AV	H	31.56	86.57	N/A	N/A
2422.000	70.80	PK	V	31.56	102.36	N/A	N/A
2422.000	59.61	AV	V	31.56	91.17	N/A	N/A
2390.000	30.53	PK	V	31.46	61.99	74.00	12.01
2390.000	16.77	AV	V	31.46	48.23	54.00	5.77
4844.000	37.84	PK	V	10.96	48.80	74.00	25.20
4844.000	25.61	AV	V	10.96	36.57	54.00	17.43
7266.000	36.53	PK	V	14.63	51.16	74.00	22.84
7266.000	24.74	AV	V	14.63	39.37	54.00	14.63
Middle Channel: 2437 MHz							
2437.000	65.97	PK	H	31.60	97.57	N/A	N/A
2437.000	53.81	AV	H	31.60	85.41	N/A	N/A
2437.000	71.49	PK	V	31.60	103.09	N/A	N/A
2437.000	59.80	AV	V	31.60	91.40	N/A	N/A
4874.000	38.21	PK	V	11.05	49.26	74.00	24.74
4874.000	26.43	AV	V	11.05	37.48	54.00	16.52
7311.000	34.49	PK	V	14.80	49.29	74.00	24.71
7311.000	21.31	AV	V	14.80	36.11	54.00	17.89
High Channel: 2452MHz							
2452.000	66.07	PK	H	31.63	97.70	N/A	N/A
2452.000	54.16	AV	H	31.63	85.79	N/A	N/A
2452.000	71.43	PK	V	31.63	103.06	N/A	N/A
2452.000	59.04	AV	V	31.63	90.67	N/A	N/A
2483.500	32.40	PK	V	31.64	64.04	74.00	9.96
2483.500	18.12	AV	V	31.64	49.76	54.00	4.24
4904.000	36.15	PK	V	11.14	47.29	74.00	26.71
4904.000	23.89	AV	V	11.14	35.03	54.00	18.97
7356.000	34.16	PK	V	14.80	48.96	74.00	25.04
7356.000	21.76	AV	V	14.80	36.56	54.00	17.44


Worst Test plots(802.11b mode chain 0 low channel):

Vertical


1-6GHz



6-18GHz



18-25GHz



4.3 Maximum peak conducted output power Spot Check:

Serial Number:	CR221046538-RF-A1	Test Date:	2022/11/2
Test Site:	RF	Test Mode:	Transmitting
Tester:	Claire Liu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.9	Relative Humidity: (%)	49	ATM Pressure: (kPa)	100.1
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
Agilent	USB Wideband Power Sensor	U2021XA	MY54080015	2022/07/15	2023/07/14

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Modes	Test Frequency (MHz)	Maximum Conducted Peak Output Power (dBm)				
		Chain 0	Chain 1	Total	Limit For Non-beamforming	Limit For Beamforming
802.11b	2412	6.22	7.23	/	≤30	/
	2437	6.73	7.96	/	≤30	/
	2462	7.66	7.89	/	≤30	/
802.11g	2412	21.59	22.04	/	≤30	/
	2437	21.51	22.31	/	≤30	/
	2462	21.45	22.12	/	≤30	/
802.11n ht20	2412	21.88	22.25	25.08	≤30	≤28
	2437	21.67	22.19	24.95	≤30	≤28
	2462	21.31	22.26	24.82	≤30	≤28
802.11n ht40	2422	22.01	22.39	25.21	≤30	≤28
	2437	21.64	22.63	25.17	≤30	≤28
	2452	21.69	22.68	25.22	≤30	≤28

Note:

The maximum antenna gain is 5.0dBi in 2.4GHz band. The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power measurements on IEEE 802.11 devices:

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

So:

For Non-beamforming mode: Directional gain = 5.0dBi

For Beamforming mode: Directional gain = 5.0+3 = 8.0 dBi

5. RF EXPOSURE EVALUATION

5.1 Applicable Standard

According to §1.1307(b)(3)(i)

(B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

According to KDB 447498 D04 Interim General RF Exposure Guidance v01:

2.2.2 Simultaneous Transmission with both SAR-based and MPE-Based Test Exemptions

This case is described in detail in § 1.1307(b)(3)(ii)(B) and covers the situations where both SAR-based and MPE-based exemption may be considered for test exemption in fixed, mobile, or portable device exposure conditions. For these cases, a device with multiple RF sources transmitting simultaneously will be considered an RF exempt device if the condition of Formula (1) is satisfied.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

5.2 Measurement Result

Operation Modes	Frequency (MHz)	Distance (mm)	P _{th}		Maximum Conducted Power including Tune-up Tolerance (dBm)	Antenna Gain + Beamforming Gain (dBi)	ERP (dBm)	ERP (mW)	Exemption
			(mW)	(dBm)					
WLAN 2.4G	2412-2462	200	3060	34.86	26	8.0	31.85	1531.09	Compliant
WLAN 5.2G	5150-5250	200	3060	34.86	21	8.0	26.85	484.17	Compliant
WLAN 5.8G	5725-5850	200	3060	34.86	22	8.0	27.85	609.54	Compliant

WLAN 2.4G and 5G can transmit simultaneously:

$$\sum_{i=1}^a \left(\frac{P_i}{P_{th_i}} \right) + \sum_{j=1}^b \left(\frac{ERP_j}{ERP_{th_j}} \right) + \sum_{k=1}^c \left(\frac{Evaluated_k}{Exposure Limit_k} \right)$$

$$= \text{EPR}_{2.4G} / P_{th-2.4G} + \text{EPR}_{5G} / P_{th-5G}$$

$$= 1531.09 / 3060 + 609.54 / 3060$$

$$= 0.70$$

Result: The device compliant the Exemption at 20cm distances.

===== END OF REPORT =====