

RF Test Report

For

Applicant name: SHENZHEN TENDA TECHNOLOGY CO., LTD.
Address: 6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road, Nanshan District, Shenzhen, China. 518052
EUT name: BE5010 Dual-band Wi-Fi 7 Ceiling Access Point
Brand name: Tenda
Model number: i36
Series model number: N/A
FCC ID: V7TI36

Issued By

Company name: BTF Testing Lab (Shenzhen) Co., Ltd.
Address: 101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China
Report number: BTF250603R01001
Test standards: 47 CFR Part 15.247
Test conclusion: Pass

Date of sample receipt: 2025-06-03

Test date: 2025-06-04 to 2025-08-14

Date of issue: 2025-08-15

Prepared by:

Chris Liu

Chris Liu / Project engineer



Ryan.CJ

Ryan.CJ / EMC Manager

Note: All the test results in this report only related to the testing samples. Which can be duplicated completely for the legal use with approval of applicant; it shall not be reproduced except in full without the written approval of BTF Testing Lab (Shenzhen) Co., Ltd., All the objections should be raised within thirty days from the date of issue. To validate the report, you can contact us.

Revision History		
Version	Issue Date	Revisions Content
R_V0	2025-08-15	Original
<i>Note:</i> <i>Once the revision has been made, then previous versions reports are invalid.</i>		

Table of Contents

1 Introduction	4
1.1 Laboratory Location	4
1.2 Laboratory Facility	4
1.3 Announcement	4
2 Product Information	5
2.1 Application Information	5
2.2 Manufacturer Information	5
2.3 General Description of Equipment under Test (EUT)	5
2.4 Technical Information	6
3 Summary of Test Results	7
3.1 Test Standards	7
3.2 Uncertainty of Test	7
3.3 Summary of Test Result	7
3.4 Additions to, deviations, or exclusions from the method	7
4 Test Configuration	8
4.1 Test Equipment List	8
4.2 Test Auxiliary Equipment	9
4.3 Test Modes	9
4.4 Test Channel of EUT	9
4.5 Test software	9
5 Evaluation Results (Evaluation)	10
5.1 Antenna requirement	10
6 Radio Spectrum Matter Test Results (RF)	10
6.1 Conducted Emission at AC power line	10
6.1.1 Test Data	12
6.2 6dB Bandwidth	14
6.2.1 Test Data	15
6.3 Maximum Conducted Output Power	16
6.3.1 Test Data	16
6.4 Power Spectral Density	17
6.4.1 Test Data	17
6.5 Emissions in non-restricted frequency bands	18
6.5.1 Test Data	18
6.6 Band edge emissions (Radiated)	19
6.6.1 Test Data	20
6.7 Emissions in frequency bands (below 1GHz)	21
6.7.1 Test Data	22
6.8 Emissions in frequency bands (above 1GHz)	24
6.8.1 Test Data	25
7 Test Setup Photos	27
8 EUT Constructional Details (EUT Photos)	27
Appendix	28

1 Introduction

1.1 Laboratory Location

Test location:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China
Phone number:	+86-0755-23146130
Fax number:	+86-0755-23146130

1.2 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Designation No.: CN1409**
BTF Testing Lab (Shenzhen) Co., Ltd. has been accredited as a testing laboratory by FCC (Federal Communications Commission). The test firm Registration No. is 695374.
- **CNAS - Registration No.: CNAS L17568**
BTF Testing Lab (Shenzhen) Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L17568.
- **A2LA - Registration No.: 6660.01**
BTF Testing Lab (Shenzhen) Co., Ltd. is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories.

1.3 Announcement

- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by BTF and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.
- (7) All entrusted information in this report is provided by the client and has been confirmed through consultation with the client; The testing items for this report have been discussed and confirmed with the client, and our company is only responsible for the content reflected in the report.

2 Product Information

2.1 Application Information

Company name:	SHENZHEN TENDA TECHNOLOGY CO., LTD.
Address:	6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road, Nanshan District, Shenzhen, China. 518052

2.2 Manufacturer Information

Company name:	SHENZHEN TENDA TECHNOLOGY CO., LTD.
Address:	6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road, Nanshan District, Shenzhen, China. 518052

2.3 General Description of Equipment under Test (EUT)

EUT name:	BE5010 Dual-band Wi-Fi 7 Ceiling Access Point
Under test model name:	i36
Series model name:	N/A
Description of model name differentiation:	N/A
Ratings:	Power:48V=800mA from adapter Adapter: MODLE:BN017-A38048U INPUT:100-240V~ 50/60Hz 1.0A OUTPUT:48V=800mA

2.4 Technical Information

Operation Frequency:	802.11b/g/n(HT20)/ ax(HE20)/be(ETH20): 2412MHz to 2462MHz; 802.11n(HT40) /ax(HE40)/be(ETH40): 2422MHz to 2452MHz
Channel numbers:	802.11b/g/n(HT20) /ax(HE20)/be(ETH20): 11 Channels; 802.11n(HT40) /ax(HE40)/be(ETH40): 7 Channels
Channel separation:	5MHz
Modulation technology:	802.11b: DSSS(CCK, DQPSK, DBPSK); 802.11g: OFDM(BPSK, QPSK, 16QAM, 64QAM); 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) 802.11be: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM)
Max. Conducted Power:	15.82dBm
Antenna type:	Internal Antenna
Antenna gain:	ANT1:5.26dBi, ANT2:4.45dBi
Antenna transmit mode:	MIMO (2TX, 2RX)

Channel List:

802.11b/g/n(HT20)/ ax(HE20)/be(ETH20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz	--	--
Remark: Channel 1, 6 & 11 have been tested.							

802.11n(HT40) /ax(HE40)/be(ETH40)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
--	--	4	2427MHz	7	2442MHz	10	2457MHz
--	--	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz	--	--
Remark: Channel 3, 6 & 9 have been tested.							

3 Summary of Test Results

3.1 Test Standards

The tests were performed according to following standards:
47 CFR Part 15.247: Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

3.2 Uncertainty of Test

Measurement	Value
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±1.5 dB
Power Spectral Density, conducted	±3.0 dB
Unwanted Emissions, conducted	±3.0 dB
Supply voltages	±3 %
Time	±5 %
Conducted Emission for LISN (9kHz ~ 150kHz)	±2.97 dB
Conducted Emission for LISN (150kHz ~ 30MHz)	±2.45 dB
Radiated Emission (30MHz ~ 1000MHz)	±4.80 dB
Radiated Emission (1GHz ~ 18GHz)	±4.82 dB

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.3 Summary of Test Result

Item	Standard	Requirement	Result
Antenna requirement	47 CFR Part 15.247	47 CFR 15.203	Pass
Conducted Emission at AC power line	47 CFR Part 15.247	47 CFR 15.207(a)	Pass
6dB Bandwidth	47 CFR Part 15.247	47 CFR 15.247(a)(2)	Pass
Maximum Conducted Output Power	47 CFR Part 15.247	47 CFR 15.247(b)(3)	Pass
Power Spectral Density	47 CFR Part 15.247	47 CFR 15.247(e)	Pass
Emissions in non-restricted frequency bands	47 CFR Part 15.247	47 CFR 15.247(d)	Pass
Band edge emissions (Radiated)	47 CFR Part 15.247	47 CFR 15.247(d), 15.209, 15.205	Pass
Emissions in frequency bands (below 1GHz)	47 CFR Part 15.247	47 CFR 15.247(d), 15.209, 15.205	Pass
Emissions in frequency bands (above 1GHz)	47 CFR Part 15.247	47 CFR 15.247(d), 15.209, 15.205	Pass

Remark:

1. Pass: Meet the requirements.
2. N/A: not applicable.

3.4 Additions to, deviations, or exclusions from the method

None

4 Test Configuration

4.1 Test Equipment List

Conducted Emission at AC power line					
Test Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Pulse Limiter	Schwarzbeck	VTSD 9561-F	953	/	/
Coaxial Switcher	Schwarzbeck	CX210	CX210	/	/
V-LISN	Schwarzbeck	NSLK 8127	1073	2024-10-25	2025-10-24
EMI Receiver	Rohde & Schwarz	ESCI3	101422	2024-10-25	2025-10-24
Test Software	Frad	EZ_EMCC	Version: EMC-CON 3A1.1+	/	/

Power Spectral Density Emissions in non-restricted frequency bands 6dB Bandwidth Maximum Conducted Output Power					
Test Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
RF Control Unit	Techy	TR1029-1	/	2024-10-25	2025-10-24
RF Sensor Unit	Techy	TR1029-2	/	2024-10-25	2025-10-24
Temperature Humidity Chamber	ZZCKONG	ZZ-K02A	20210928007	2024-10-25	2025-10-24
DC Power Supply	Tongmen	etm-6050c	20211026123	2024-10-25	2025-10-24
Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	161997	2024-10-25	2025-10-24
Spectrum Analyzer	Keysight	N9020A	MY50410020	2024-10-25	2025-10-24
ESG Vector Signal Generator	Agilent	E4438C	MY45094854	2024-10-25	2025-10-24
MXG Vector Signal Generator	Agilent	N5182A	MY46240163	2024-10-25	2025-10-24
Test Software	TST Pass	/	Version: 2.0	/	/

Band edge emissions (Radiated) Emissions in frequency bands (below 1GHz) Emissions in frequency bands (above 1GHz)					
Test Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
EMI Receiver	Rohde & Schwarz	ESCI7	101032	2024-10-25	2025-10-24
Signal Analyzer	Rohde & Schwarz	FSQ40	100010	2024-10-25	2025-10-24
Horn Antenna	Schwarzbeck	BBHA9120D	2597	2024-10-30	2025-10-29
Log periodic antenna	Schwarzbeck	VULB 9168	1328	2024-10-28	2025-10-27
Preamplifier(30MHz ~ 1GHz)	Schwarzbeck	BBV9744	246	2024-09-24	2025-09-23
Preamplifier(1GHz ~ 18GHz)	Schwarzbeck	BBV9718D	8	2024-09-24	2025-09-23
Test Software	Frad	EZ_EMCC	Version: FA-03A2 RE+	/	/

4.2 Test Auxiliary Equipment

The EUT has been tested as an independent unit.

4.3 Test Modes

No.	Test Modes
TM1	802.11b mode
TM2	802.11g mode
TM3	802.11n(HT20) mode
TM4	802.11n(HT40) mode
TM5	802.11ax(HEW20) mode
TM6	802.11ax(HEW40) mode
TM7	802.11be(EHT20) mode
TM8	802.11be(EHT40) mode

4.4 Test Channel of EUT

Operation Band: 2400-2483.5 MHz

Bandwidth (MHz)	Lowest Channel (LCH) (MHz)	Middle Channel (MCH) (MHz)	Highest Channel (HCH) (MHz)
20	2412	2437	2462
40	2422	2437	2452

4.5 Test software

Test software:	QATool	Version:	20231030
Power Class:	9		


5 Evaluation Results (Evaluation)

5.1 Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
Operating Environment:	
Temperature:	25.8 °C
Humidity:	54 %
Atmospheric Pressure:	1010 mbar

6 Radio Spectrum Matter Test Results (RF)

6.1 Conducted Emission at AC power line


Test Requirement:	Refer to 47 CFR 15.207(a), Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).		
Test Method:	ANSI C63.10-2020 section 6.2		
Test Limit:	Frequency of emission (MHz)	Conducted limit (dB μ V)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
	*Decreases with the logarithm of the frequency.		
Procedure:	Refer to ANSI C63.10-2020 section 6.2, standard test method for ac power-line conducted emissions from unlicensed wireless devices		
Test Setup:			
Operating Environment:			

Temperature:	25.8 °C
Humidity:	54 %
Atmospheric Pressure:	1010 mbar
Test voltage:	AC 120V 60Hz

6.1.1 Test Data


Remark: The report only reflects the test data of worst mode.

TM1 / Line: Line / Band: 2400-2483.5 MHz / BW: 20 / CH: M



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1 *	0.1590	32.69	10.57	43.26	65.52	-22.26	QP	P	
2	0.1905	4.77	10.64	15.41	54.01	-38.60	AVG	P	
3	0.2535	27.50	10.66	38.16	61.64	-23.48	QP	P	
4	0.2535	8.37	10.66	19.03	51.64	-32.61	AVG	P	
5	0.3613	24.74	10.67	35.41	58.70	-23.29	QP	P	
6	0.3885	7.90	10.67	18.57	48.10	-29.53	AVG	P	
7	1.0275	16.75	10.85	27.60	56.00	-28.40	QP	P	
8	1.0275	4.39	10.85	15.24	46.00	-30.76	AVG	P	
9	1.6845	17.15	10.73	27.88	56.00	-28.12	QP	P	
10	1.9365	3.87	10.69	14.56	46.00	-31.44	AVG	P	
11	2.4495	17.17	10.69	27.86	56.00	-28.14	QP	P	
12	2.7105	4.24	10.71	14.95	46.00	-31.05	AVG	P	


TM1 / Line: Neutral / Band: 2400-2483.5 MHz / BW: 20 / CH: M



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1 *	0.1500	34.69	10.55	45.24	66.00	-20.76	QP	P	
2	0.1500	7.08	10.55	17.63	56.00	-38.37	AVG	P	
3	0.1860	28.74	10.56	39.30	64.21	-24.91	QP	P	
4	0.2130	4.36	10.57	14.93	53.09	-38.16	AVG	P	
5	0.2400	23.14	10.59	33.73	62.10	-28.37	QP	P	
6	0.3570	4.31	10.67	14.98	48.80	-33.82	AVG	P	
7	0.9420	14.63	10.87	25.50	56.00	-30.50	QP	P	
8	1.0320	3.27	10.86	14.13	46.00	-31.87	AVG	P	
9	1.2660	2.75	10.89	13.64	46.00	-32.36	AVG	P	
10	1.2750	14.71	10.89	25.60	56.00	-30.40	QP	P	
11	2.5080	14.59	10.94	25.53	56.00	-30.47	QP	P	
12	2.5080	2.01	10.94	12.95	46.00	-33.05	AVG	P	

Note:Margin=Level-Limit=Reading+factor-Limit

6.2 6dB Bandwidth


Test Requirement:	47 CFR 15.247(a)(2)
Test Method:	ANSI C63.10-2020, section 11.8 KDB 558074 D01 15.247 Meas Guidance v05r02
Test Limit:	Refer to 47 CFR 15.247(a)(2), Systems using digital modulation techniques may operate in the 902-928 MHz, and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.
Procedure:	11.8.1 Option 1 The steps for the first option are as follows: - Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz. - Set the VBW $\geq [3 \times \text{RBW}]$. - Detector = peak. - Trace mode = max-hold. - Sweep = No faster than coupled (auto) time. - Allow the trace to stabilize. - Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value. 11.8.2 Option 2 The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., RBW = 100 kHz, VBW $\geq 3 \times \text{RBW}$, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.
Test Setup:	 The diagram illustrates the test setup. On the left, a rack of instruments is shown, including an E4438C, N5182A, CMW500, N9020A, RF Control Unit and Sensor Unit, SPD, and a DC Power Source. On the right, a Temperature Humidity Chamber contains the EUT (Equipment Under Test). Red and black cables connect the instruments to the EUT and the chamber.
Operating Environment:	

Temperature:	25.8 °C
Humidity:	54 %
Atmospheric Pressure:	1010 mbar
Test voltage:	DC 48V From Adapter

6.2.1 Test Data

Please Refer to Appendix for Details.


6.3 Maximum Conducted Output Power

Test Requirement:	47 CFR 15.247(b)(3)
Test Method:	ANSI C63.10-2020 section 11.9.1 KDB 558074 D01 15.247 Meas Guidance v05r02
Test Limit:	Refer to 47 CFR 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
Procedure:	ANSI C63.10-2020, section 11.9.1 Maximum peak conducted output power
Test Setup:	
Operating Environment:	
Temperature:	25.8 °C
Humidity:	54 %
Atmospheric Pressure:	1010 mbar
Test voltage:	DC 48V From Adapter

6.3.1 Test Data

Please Refer to Appendix for Details.


6.4 Power Spectral Density

Test Requirement:	47 CFR 15.247(e)
Test Method:	ANSI C63.10-2020, section 11.10 KDB 558074 D01 15.247 Meas Guidance v05r02
Test Limit:	Refer to 47 CFR 15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.
Procedure:	ANSI C63.10-2020, section 11.10, Maximum power spectral density level in the fundamental emission
Test Setup:	
Operating Environment:	
Temperature:	25.8 °C
Humidity:	54 %
Atmospheric Pressure:	1010 mbar
Test voltage:	DC 48V From Adapter

6.4.1 Test Data

Please Refer to Appendix for Details.


6.5 Emissions in non-restricted frequency bands

Test Requirement:	47 CFR 15.247(d)
Test Method:	ANSI C63.10-2020 section 11.11 KDB 558074 D01 15.247 Meas Guidance v05r02
Test Limit:	Refer to 47 CFR 15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Procedure:	ANSI C63.10-2020 Section 11.11.1, Section 11.11.2, Section 11.11.3
Test Setup:	
Operating Environment:	
Temperature:	25.8 °C
Humidity:	54 %
Atmospheric Pressure:	1010 mbar
Test voltage:	DC 48V From Adapter

6.5.1 Test Data

Please Refer to Appendix for Details.

6.6 Band edge emissions (Radiated)

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Method:	ANSI C63.10-2020 section 6.10 KDB 558074 D01 15.247 Meas Guidance v05r02		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Procedure:	ANSI C63.10-2020 section 6.10.5.2		
Test Setup:			
Operating Environment:			
Temperature:	25.8 °C		
Humidity:	54 %		
Atmospheric Pressure:	1010 mbar		
Test voltage:	DC 48V From Adapter		

6.6.1 Test Data

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: L

Test Channel: Lowest channel, Test Polarization: Vertical							
Frequency (MHz)	Reading (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Marging (dB)	Detector	Result
2310.00	50.51	3.85	54.36	74.00	-19.64	Peak	Pass
2310.00	39.70	3.85	43.55	54.00	-10.45	AVG	Pass
2390.00	51.43	3.91	55.35	74.00	-18.65	Peak	Pass
2390.00	40.72	3.91	44.63	54.00	-9.37	AVG	Pass

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: L

Test Channel: Lowest channel, Test Polarization: Horizontal							
Frequency (MHz)	Reading (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Marging (dB)	Detector	Result
2310.00	50.84	3.85	54.69	74.00	-19.31	Peak	Pass
2310.00	41.11	3.85	44.97	54.00	-9.03	AVG	Pass
2390.00	51.93	3.91	55.84	74.00	-18.16	Peak	Pass
2390.00	41.70	3.91	45.61	54.00	-8.39	AVG	Pass

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: H


Test Channel: Highest channel, Test Polarization: Vertical							
Frequency (MHz)	Reading (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Marging (dB)	Detector	Result
2483.50	51.57	3.99	55.56	74.00	-18.44	Peak	Pass
2483.50	41.96	3.99	45.95	54.00	-8.05	AVG	Pass
2500.00	51.67	4.00	55.67	74.00	-18.33	Peak	Pass
2500.00	41.81	4.00	45.81	54.00	-8.19	AVG	Pass

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: H

Test Channel: Highest channel, Test Polarization: Horizontal							
Frequency (MHz)	Reading (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Marging (dB)	Detector	Result
2483.50	52.00	3.99	55.99	74.00	-18.01	Peak	Pass
2483.50	41.82	3.99	45.80	54.00	-8.20	AVG	Pass
2500.00	51.39	4.00	55.39	74.00	-18.61	Peak	Pass
2500.00	41.05	4.00	45.05	54.00	-8.95	AVG	Pass


Note: Margin=Level-Limit=Reading+factor-Limit

6.7 Emissions in frequency bands (below 1GHz)

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Method:	ANSI C63.10-2020 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Procedure:	ANSI C63.10-2020 section 6.6.4		
Test Setup:			
Operating Environment:			
Temperature:	25.8 °C		
Humidity:	54 %		
Atmospheric Pressure:	1010 mbar		
Test voltage:	DC 48V From Adapter		


6.7.1 Test Data

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: M



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	33.3278	31.10	-9.68	21.42	40.00	-18.58	QP	P
2	119.8555	46.48	-22.29	24.19	43.50	-19.31	QP	P
3	207.1225	42.86	-21.47	21.39	43.50	-22.11	QP	P
4	283.9791	44.98	-20.75	24.23	46.00	-21.77	QP	P
5	520.8881	50.05	-18.85	31.20	46.00	-14.80	QP	P
6 *	801.7862	51.74	-17.83	33.91	46.00	-12.09	QP	P


TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: M



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	33.2693	32.04	-9.68	22.36	40.00	-17.64	QP	P
2	120.0660	47.52	-22.29	25.23	43.50	-18.27	QP	P
3	187.7530	43.19	-21.66	21.53	43.50	-21.97	QP	P
4	346.2015	42.24	-20.25	21.99	46.00	-24.01	QP	P
5	517.2480	44.47	-18.88	25.59	46.00	-20.41	QP	P
6 *	800.3817	49.17	-17.85	31.32	46.00	-14.68	QP	P

Note:Margin=Level-Limit=Reading+factor-Limit

6.8 Emissions in frequency bands (above 1GHz)

Test Requirement:	Refer to 47 CFR 15.247(d), in addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Method:	ANSI C63.10-2020 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
	** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.		
Procedure:	ANSI C63.10-2020 section 6.6.4		
Test Setup:			
Operating Environment:			
Temperature:	25.8 °C		
Humidity:	54 %		
Atmospheric Pressure:	1010 mbar		
Test voltage:	DC 48V From Adapter		

6.8.1 Test Data

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: L

Test Channel: Lowest channel, Test Polarization: Vertical							
Frequency (MHz)	Reading (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Marging (dB)	Detector	Result
4824.00	79.49	-48.87	30.62	74.00	-43.38	Peak	Pass
4824.00	69.42	-48.87	20.55	54.00	-33.45	AVG	Pass
7236.00	75.20	-46.99	28.22	74.00	-45.78	Peak	Pass
7236.00	65.00	-46.99	18.02	54.00	-35.98	AVG	Pass

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: L

Test Channel: Lowest channel, Test Polarization: Horizontal							
Frequency (MHz)	Reading (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Marging (dB)	Detector	Result
4824.00	79.65	-48.87	30.78	74.00	-43.22	Peak	Pass
4824.00	68.84	-48.87	19.96	54.00	-34.04	AVG	Pass
7236.00	76.05	-46.99	29.06	74.00	-44.94	Peak	Pass
7236.00	65.95	-46.99	18.96	54.00	-35.04	AVG	Pass

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: M

Test Channel: Middle channel, Test Polarization: Vertical							
Frequency (MHz)	Reading (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Marging (dB)	Detector	Result
4874.00	79.81	-48.84	30.97	74.00	-43.03	Peak	Pass
4874.00	70.31	-48.84	21.47	54.00	-32.53	AVG	Pass
7311.00	75.81	-46.90	28.91	74.00	-45.09	Peak	Pass
7311.00	65.26	-46.90	18.36	54.00	-35.64	AVG	Pass

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: M

Test Channel: Middle channel, Test Polarization: Horizontal							
Frequency (MHz)	Reading (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Marging (dB)	Detector	Result
4874.00	79.74	-48.84	30.90	74.00	-43.10	Peak	Pass
4874.00	68.77	-48.84	19.93	54.00	-34.07	AVG	Pass
7311.00	76.20	-46.90	29.30	74.00	-44.70	Peak	Pass
7311.00	66.47	-46.90	19.57	54.00	-34.43	AVG	Pass

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: H

Test Channel: Highest channel, Test Polarization: Vertical							
Frequency (MHz)	Reading (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Marging (dB)	Detector	Result
4924.00	79.39	-48.81	30.59	74.00	-43.41	Peak	Pass
4924.00	69.19	-48.81	20.38	54.00	-33.62	AVG	Pass
7386.00	75.23	-46.81	28.42	74.00	-45.58	Peak	Pass
7386.00	64.74	-46.81	17.94	54.00	-36.06	AVG	Pass

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: H

Test Channel: Highest channel, Test Polarization: Horizontal							
Frequency (MHz)	Reading (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Marging (dB)	Detector	Result
4924.00	78.67	-48.81	29.86	74.00	-44.14	Peak	Pass
4924.00	67.72	-48.81	18.91	54.00	-35.09	AVG	Pass
7386.00	75.42	-46.81	28.62	74.00	-45.38	Peak	Pass
7386.00	65.49	-46.81	18.68	54.00	-35.32	AVG	Pass

Note:Margin=Level-Limit=Reading+factor-Limit

7 Test Setup Photos

Refer to Appendix - Test Setup Photos

8 EUT Constructional Details (EUT Photos)

Refer to Appendix - EUT External Photo and Appendix - EUT Internal Photo

Appendix

1. Duty Cycle


1.1 Test Result

1.1.1 Ant1


Ant1									
Mode	TX Type	Frequency (MHz)	RU	RU Pos	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11b	SISO	2412	/	/	8.383	8.457	99.12	0.04	0.04
		2437	/	/	8.383	8.456	99.14	0.04	0.04
		2462	/	/	8.383	8.457	99.12	0.04	0.04
802.11g	SISO	2412	/	/	1.392	1.454	95.74	0.19	0.63
		2437	/	/	1.393	1.454	95.80	0.19	0.60
		2462	/	/	1.393	1.454	95.80	0.19	0.63
802.11n (HT20)	MIMO	2412	/	/	1.308	1.370	95.47	0.20	0.72
		2437	/	/	1.308	1.370	95.47	0.20	0.66
		2462	/	/	1.309	1.370	95.55	0.20	0.66
802.11n (HT40)	MIMO	2422	/	/	0.649	0.710	91.41	0.39	1.22
		2437	/	/	0.649	0.710	91.41	0.39	1.22
		2452	/	/	0.648	0.710	91.27	0.40	1.19
802.11ax (HEW20)	MIMO	2412	SU	/	0.311	0.372	83.60	0.78	2.12
		2437	SU	/	0.310	0.372	83.33	0.79	2.09
		2462	SU	/	0.311	0.373	83.38	0.79	2.13
802.11ax (HEW40)	MIMO	2422	SU	/	0.310	0.363	85.40	0.69	0.04
		2437	SU	/	0.310	0.363	85.40	0.69	0.07
		2452	SU	/	0.310	0.363	85.40	0.69	0.04
802.11ac (VHT20)	MIMO	2412	/	/	1.312	1.373	95.56	0.20	0.62
		2437	/	/	1.313	1.374	95.56	0.20	0.69
		2462	/	/	1.312	1.373	95.56	0.20	0.62
802.11ac (VHT40)	MIMO	2422	/	/	0.653	0.713	91.58	0.38	1.18
		2437	/	/	0.653	0.714	91.46	0.39	1.25
		2452	/	/	0.652	0.714	91.32	0.39	1.21
802.11be (EHT20)	MIMO	2412	SU	/	0.319	0.381	83.73	0.77	2.09
		2437	SU	/	0.319	0.380	83.95	0.76	2.09
		2462	SU	/	0.319	0.380	83.95	0.76	2.06
802.11be (EHT40)	MIMO	2422	SU	/	0.319	0.371	85.98	0.66	0.07
		2437	SU	/	0.319	0.380	83.95	0.76	0.11
		2452	SU	/	0.319	0.371	85.98	0.66	0.07

1.2 Test Graph


1.2.1 Ant1




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (MIMO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (MIMO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant1 (MIMO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (MIMO)_NTNV




802.11ax(HEW20) LCH_2412MHz_SU_ / _Ant1 (MIMO) _NTNV




802.11ax(HEW20) _MCH_2437MHz_SU_ / _Ant1 (MIMO) _NTNV




802.11ax(HEW20) HCH_2462MHz_SU_ / _Ant1 (MIMO) NTN




802.11ax(HEW40) LCH_2422MHz_SU_ / _Ant1 (MIMO) NTN




802.11ax(HEW40)_MCH_2437MHz_SU_/_Ant1 (MIMO)_NTNV




802.11ax(HEW40)_HCH_2452MHz_SU_/_Ant1 (MIMO)_NTNV




802.11ac(VHT20)_LCH_2412MHz_Ant1 (MIMO)_NTNV




802.11ac(VHT20)_MCH_2437MHz_Ant1 (MIMO)_NTNV




802.11ac(VHT20)_HCH_2462MHz_Ant1 (MIMO)_NTNV




802.11ac(VHT40)_LCH_2422MHz_Ant1 (MIMO)_NTNV




802.11ac(VHT40)_MCH_2437MHz_Ant1 (MIMO)_NTNV




802.11ac(VHT40)_HCH_2452MHz_Ant1 (MIMO)_NTNV




802.11be(EHT20)_LCH_2412MHz_SU_/_Ant1 (MIMO)_NTNV




802.11be(EHT20)_MCH_2437MHz_SU_/_Ant1 (MIMO)_NTNV




802.11be(EHT20)_HCH_2462MHz_SU_/_Ant1 (MIMO)_NTNV




802.11be(EHT40)_LCH_2422MHz_SU_/_Ant1 (MIMO)_NTNV



802.11be(EHT40)_MCH_2437MHz_SU_/_Ant1 (MIMO)_NTNV



802.11be(EHT40)_HCH_2452MHz_SU_/_Ant1 (MIMO)_NTNV



2. Bandwidth

2.1 Test Result

2.1.1 OBW

Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	99% Occupied Bandwidth (MHz)		Verdict
						Result	Limit	
802.11b	SISO	2412	/	/	1	12.310	/	Pass
					2	13.026	/	Pass
		2437	/	/	1	12.304	/	Pass
					2	12.931	/	Pass
		2462	/	/	1	12.305	/	Pass
					2	12.924	/	Pass
802.11g	SISO	2412	/	/	1	16.534	/	Pass
					2	17.434	/	Pass
		2437	/	/	1	16.522	/	Pass
					2	17.449	/	Pass
		2462	/	/	1	16.561	/	Pass
					2	17.504	/	Pass
802.11n (HT20)	MIMO	2412	/	/	1	17.537	/	Pass
					2	18.332	/	Pass
		2437	/	/	1	17.534	/	Pass
					2	18.312	/	Pass
		2462	/	/	1	17.537	/	Pass
					2	18.363	/	Pass
802.11n (HT40)	MIMO	2422	/	/	1	35.611	/	Pass
					2	36.527	/	Pass
		2437	/	/	1	35.618	/	Pass
					2	36.576	/	Pass
		2452	/	/	1	35.499	/	Pass
					2	36.694	/	Pass
802.11ax (HEW20)	MIMO	2412	SU	/	1	18.768	/	Pass
					2	18.291	/	Pass
		2437	SU	/	1	18.785	/	Pass
					2	18.254	/	Pass
		2462	SU	/	1	18.790	/	Pass
					2	18.267	/	Pass
802.11ax (HEW40)	MIMO	2422	SU	/	1	37.463	/	Pass
					2	36.413	/	Pass
		2437	SU	/	1	37.316	/	Pass
					2	36.440	/	Pass
		2452	SU	/	1	37.428	/	Pass
					2	36.542	/	Pass
802.11ac (VHT20)	MIMO	2412	/	/	1	17.546	/	Pass
					2	18.253	/	Pass
		2437	/	/	1	17.494	/	Pass
					2	18.259	/	Pass
		2462	/	/	1	17.484	/	Pass
					2	18.311	/	Pass
802.11ac (VHT40)	MIMO	2422	/	/	1	35.590	/	Pass
					2	36.537	/	Pass
		2437	/	/	1	35.590	/	Pass
					2	36.541	/	Pass
		2452	/	/	1	35.582	/	Pass
					2	36.564	/	Pass
802.11be	MIMO	2412	SU	/	1	18.773	/	Pass

(EHT20)		2437	SU	/	2	18.271	/	Pass
					1	18.833	/	Pass
					2	18.258	/	Pass
		2462	SU	/	1	18.766	/	Pass
					2	18.296	/	Pass
					2	18.296	/	Pass
802.11be (EHT40)	MIMO	2422	SU	/	1	37.593	/	Pass
					2	36.526	/	Pass
		2437	SU	/	1	37.449	/	Pass
					2	36.562	/	Pass
		2452	SU	/	1	37.369	/	Pass
					2	36.508	/	Pass

2.1.2 6dB BW


Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	6dB Bandwidth (MHz)		Verdict
						Result	Limit	
802.11b	SISO	2412	/	/	1	8.180	>=0.5	Pass
					2	8.650	>=0.5	Pass
		2437	/	/	1	8.178	>=0.5	Pass
					2	8.239	>=0.5	Pass
		2462	/	/	1	8.178	>=0.5	Pass
					2	8.247	>=0.5	Pass
802.11g	SISO	2412	/	/	1	16.179	>=0.5	Pass
					2	16.341	>=0.5	Pass
		2437	/	/	1	15.635	>=0.5	Pass
					2	16.425	>=0.5	Pass
		2462	/	/	1	15.694	>=0.5	Pass
					2	16.324	>=0.5	Pass
802.11n (HT20)	MIMO	2412	/	/	1	17.099	>=0.5	Pass
					2	16.888	>=0.5	Pass
		2437	/	/	1	16.839	>=0.5	Pass
					2	17.254	>=0.5	Pass
		2462	/	/	1	16.932	>=0.5	Pass
					2	17.128	>=0.5	Pass
802.11n (HT40)	MIMO	2422	/	/	1	34.926	>=0.5	Pass
					2	35.398	>=0.5	Pass
		2437	/	/	1	32.782	>=0.5	Pass
					2	35.626	>=0.5	Pass
		2452	/	/	1	34.634	>=0.5	Pass
					2	35.708	>=0.5	Pass
802.11ax (HEW20)	MIMO	2412	SU	/	1	18.093	>=0.5	Pass
					2	17.404	>=0.5	Pass
		2437	SU	/	1	18.321	>=0.5	Pass
					2	17.443	>=0.5	Pass
		2462	SU	/	1	18.179	>=0.5	Pass
					2	17.480	>=0.5	Pass
802.11ax (HEW40)	MIMO	2422	SU	/	1	33.155	>=0.5	Pass
					2	35.606	>=0.5	Pass
		2437	SU	/	1	33.551	>=0.5	Pass
					2	35.488	>=0.5	Pass
		2452	SU	/	1	32.991	>=0.5	Pass
					2	35.620	>=0.5	Pass
802.11ac (VHT20)	MIMO	2412	/	/	1	16.756	>=0.5	Pass
					2	17.083	>=0.5	Pass
		2437	/	/	1	16.907	>=0.5	Pass
					2	17.427	>=0.5	Pass
		2462	/	/	1	16.696	>=0.5	Pass
					2	17.359	>=0.5	Pass

802.11ac (VHT40)	MIMO	2422	/	/	1	34.537	≥ 0.5	Pass
					2	35.421	≥ 0.5	Pass
		2437	/	/	1	34.697	≥ 0.5	Pass
					2	35.548	≥ 0.5	Pass
		2452	/	/	1	34.648	≥ 0.5	Pass
					2	35.609	≥ 0.5	Pass
802.11be (EHT20)	MIMO	2412	SU	/	1	18.027	≥ 0.5	Pass
					2	17.722	≥ 0.5	Pass
		2437	SU	/	1	18.152	≥ 0.5	Pass
					2	17.335	≥ 0.5	Pass
		2462	SU	/	1	18.108	≥ 0.5	Pass
					2	17.086	≥ 0.5	Pass
802.11be (EHT40)	MIMO	2422	SU	/	1	35.719	≥ 0.5	Pass
					2	35.599	≥ 0.5	Pass
		2437	SU	/	1	29.654	≥ 0.5	Pass
					2	35.818	≥ 0.5	Pass
		2452	SU	/	1	31.305	≥ 0.5	Pass
					2	35.936	≥ 0.5	Pass


2.2 Test Graph

2.2.1 OBW


802.11b_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11b_LCH_2412MHz_Ant2 (SISO)_NTNV




802.11b_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11b_MCH_2437MHz_Ant2 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant2 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant2 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant2 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant2 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant2 (MIMO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant2 (MIMO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant2 (MIMO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (MIMO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant2 (MIMO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant1 (MIMO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant2 (MIMO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (MIMO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant2 (MIMO)_NTNV




802.11ax(HEW20)_LCH_2412MHz_SU_ / Ant1 (MIMO)_NTNV




802.11ax(HEW20)_LCH_2412MHz_SU_ / Ant2 (MIMO)_NTNV




802.11ax(HEW20)_MCH_2437MHz_SU_ / _Ant1 (MIMO)_NTNV




802.11ax(HEW20)_MCH_2437MHz_SU_ / _Ant2 (MIMO)_NTNV




802.11ax(HEW20) HCH_2462MHz_SU_ / _Ant1 (MIMO) NTN




802.11ax(HEW20) HCH_2462MHz_SU_ / _Ant2 (MIMO) NTN




802.11ax(HEW40)_LCH_2422MHz_SU_ / _Ant1 (MIMO)_NTNV




802.11ax(HEW40)_LCH_2422MHz_SU_ / _Ant2 (MIMO)_NTNV




802.11ax(HEW40)_MCH_2437MHz_SU_ / _Ant1 (MIMO)_NTNV




802.11ax(HEW40)_MCH_2437MHz_SU_ / _Ant2 (MIMO)_NTNV




802.11ax(HEW40) HCH_2452MHz_SU_ / _Ant1 (MIMO) NTN




802.11ax(HEW40) HCH_2452MHz_SU_ / _Ant2 (MIMO) NTN




802.11ac(VHT20)_LCH_2412MHz_Ant1 (MIMO)_NTNV




802.11ac(VHT20)_LCH_2412MHz_Ant2 (MIMO)_NTNV




802.11ac(VHT20)_MCH_2437MHz_Ant1 (MIMO)_NTNV




802.11ac(VHT20)_MCH_2437MHz_Ant2 (MIMO)_NTNV




802.11ac(VHT20)_HCH_2462MHz_Ant1 (MIMO)_NTNV




802.11ac(VHT20)_HCH_2462MHz_Ant2 (MIMO)_NTNV




802.11ac(VHT40)_LCH_2422MHz_Ant1 (MIMO)_NTNV




802.11ac(VHT40)_LCH_2422MHz_Ant2 (MIMO)_NTNV




802.11ac(VHT40)_MCH_2437MHz_Ant1 (MIMO)_NTNV




802.11ac(VHT40)_MCH_2437MHz_Ant2 (MIMO)_NTNV




802.11ac(VHT40)_HCH_2452MHz_Ant1 (MIMO)_NTNV




802.11ac(VHT40)_HCH_2452MHz_Ant2 (MIMO)_NTNV




802.11be(EHT20)_LCH_2412MHz_SU_ / _Ant1 (MIMO)_NTNV




802.11be(EHT20)_LCH_2412MHz_SU_ / _Ant2 (MIMO)_NTNV




802.11be(EHT20)_MCH_2437MHz_SU_ / _Ant1 (MIMO)_NTNV




802.11be(EHT20)_MCH_2437MHz_SU_ / _Ant2 (MIMO)_NTNV




802.11be(EHT20)_HCH_2462MHz_SU_/_Ant1 (MIMO)_NTNV




802.11be(EHT20)_HCH_2462MHz_SU_/_Ant2 (MIMO)_NTNV




802.11be(EHT40)_LCH_2422MHz_SU_ / _Ant1 (MIMO)_NTNV




802.11be(EHT40)_LCH_2422MHz_SU_ / _Ant2 (MIMO)_NTNV




802.11be(EHT40)_MCH_2437MHz_SU_ / _Ant1 (MIMO)_NTNV




802.11be(EHT40)_MCH_2437MHz_SU_ / _Ant2 (MIMO)_NTNV



802.11be(EHT40) HCH_2452MHz_SU_ / Ant1 (MIMO) NTN




802.11be(EHT40) HCH_2452MHz_SU_ / Ant2 (MIMO) NTN




2.2.2 6dB BW


802.11b_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11b_LCH_2412MHz_Ant2 (SISO)_NTNV




802.11b_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11b_MCH_2437MHz_Ant2 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant2 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant2 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant2 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant2 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant2 (MIMO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant2 (MIMO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant2 (MIMO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (MIMO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant2 (MIMO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant1 (MIMO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant2 (MIMO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (MIMO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant2 (MIMO)_NTNV




802.11ax(HEW20)_LCH_2412MHz_SU_ / _Ant1 (MIMO)_NTNV




802.11ax(HEW20)_LCH_2412MHz_SU_ / _Ant2 (MIMO)_NTNV




802.11ax(HEW20)_MCH_2437MHz_SU_/_Ant1 (MIMO)_NTNV




802.11ax(HEW20)_MCH_2437MHz_SU_/_Ant2 (MIMO)_NTNV




802.11ax(HEW20) HCH_2462MHz_SU_ / _Ant1 (MIMO) _NTNV




802.11ax(HEW20) HCH_2462MHz_SU_ / _Ant2 (MIMO) _NTNV




802.11ax(HEW40) LCH_2422MHz_SU_ / _Ant1 (MIMO) _NTNV




802.11ax(HEW40) LCH_2422MHz_SU_ / _Ant2 (MIMO) _NTNV




802.11ax(HEW40)_MCH_2437MHz_SU_ / _Ant1 (MIMO) _NTNV




802.11ax(HEW40)_MCH_2437MHz_SU_ / _Ant2 (MIMO) _NTNV




802.11ax(HEW40) HCH_2452MHz_SU_ / _Ant1 (MIMO) _NTNV




802.11ax(HEW40) HCH_2452MHz_SU_ / _Ant2 (MIMO) _NTNV




802.11ac(VHT20)_LCH_2412MHz_Ant1 (MIMO)_NTNV




802.11ac(VHT20)_LCH_2412MHz_Ant2 (MIMO)_NTNV




802.11ac(VHT20)_MCH_2437MHz_Ant1 (MIMO)_NTNV




802.11ac(VHT20)_MCH_2437MHz_Ant2 (MIMO)_NTNV




802.11ac(VHT20)_HCH_2462MHz_Ant1 (MIMO)_NTNV




802.11ac(VHT20)_HCH_2462MHz_Ant2 (MIMO)_NTNV




802.11ac(VHT40)_LCH_2422MHz_Ant1 (MIMO)_NTNV




802.11ac(VHT40)_LCH_2422MHz_Ant2 (MIMO)_NTNV




802.11ac(VHT40)_MCH_2437MHz_Ant1 (MIMO)_NTNV




802.11ac(VHT40)_MCH_2437MHz_Ant2 (MIMO)_NTNV




802.11ac(VHT40)_HCH_2452MHz_Ant1 (MIMO)_NTNV




802.11ac(VHT40)_HCH_2452MHz_Ant2 (MIMO)_NTNV




802.11be(EHT20)_LCH_2412MHz_SU_/_Ant1 (MIMO)_NTNV




802.11be(EHT20)_LCH_2412MHz_SU_/_Ant2 (MIMO)_NTNV




802.11be(EHT20)_MCH_2437MHz_SU_ / _Ant1 (MIMO)_NTNV




802.11be(EHT20)_MCH_2437MHz_SU_ / _Ant2 (MIMO)_NTNV




802.11be(EHT20)_HCH_2462MHz_SU_/_Ant1 (MIMO)_NTNV




802.11be(EHT20)_HCH_2462MHz_SU_/_Ant2 (MIMO)_NTNV




802.11be(EHT40)_LCH_2422MHz_SU_/_Ant1 (MIMO)_NTNV




802.11be(EHT40)_LCH_2422MHz_SU_/_Ant2 (MIMO)_NTNV




802.11be(EHT40)_MCH_2437MHz_SU_ / _Ant1 (MIMO)_NTNV




802.11be(EHT40)_MCH_2437MHz_SU_ / _Ant2 (MIMO)_NTNV



802.11be(EHT40) HCH_2452MHz_SU_ / _Ant1 (MIMO) _NTNV



802.11be(EHT40) HCH_2452MHz_SU_ / _Ant2 (MIMO) _NTNV



3. Maximum Conducted Output Power

3.1 Test Result

3.1.1 Power

Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum Average Conducted Output Power (dBm)				Verdict
					ANT1	ANT2	MIMO	Limit	
802.11b	SISO	2412	/	/	15.13	13.89	/	<=30	Pass
		2437	/	/	15.14	14.11	/	<=30	Pass
		2462	/	/	14.84	13.87	/	<=30	Pass
802.11g	SISO	2412	/	/	14.17	13.12	/	<=30	Pass
		2437	/	/	14.09	13.07	/	<=30	Pass
		2462	/	/	13.92	12.94	/	<=30	Pass
802.11n (HT20)	MIMO	2412	/	/	13.37	12.16	15.82	<=30	Pass
		2437	/	/	13.20	12.17	15.73	<=30	Pass
		2462	/	/	12.93	12.03	15.51	<=30	Pass
802.11n (HT40)	MIMO	2422	/	/	12.99	12.11	15.58	<=30	Pass
		2437	/	/	12.99	11.99	15.53	<=30	Pass
		2452	/	/	13.03	12.03	15.57	<=30	Pass
802.11ax (HEW20)	MIMO	2412	SU	/	13.18	12.15	15.71	<=30	Pass
		2437	SU	/	13.14	12.17	15.69	<=30	Pass
		2462	SU	/	13.06	12.04	15.59	<=30	Pass
802.11ax (HEW40)	MIMO	2422	SU	/	12.95	12.07	15.54	<=30	Pass
		2437	SU	/	12.92	11.99	15.49	<=30	Pass
		2452	SU	/	12.99	11.98	15.52	<=30	Pass
802.11ac (VHT20)	MIMO	2412	/	/	13.13	12.14	15.67	<=30	Pass
		2437	/	/	13.05	12.15	15.63	<=30	Pass
		2462	/	/	12.99	12.02	15.54	<=30	Pass
802.11ac (VHT40)	MIMO	2422	/	/	12.96	12.04	15.53	<=30	Pass
		2437	/	/	12.98	11.92	15.49	<=30	Pass
		2452	/	/	12.82	11.96	15.42	<=30	Pass
802.11be (EHT20)	MIMO	2412	SU	/	13.29	11.50	15.50	<=30	Pass
		2437	SU	/	13.24	11.47	15.45	<=30	Pass
		2462	SU	/	12.99	11.42	15.29	<=30	Pass
802.11be (EHT40)	MIMO	2422	SU	/	12.92	11.71	15.37	<=30	Pass
		2437	SU	/	12.93	11.90	15.46	<=30	Pass
		2452	SU	/	12.92	11.74	15.38	<=30	Pass

Note1: Antenna Gain: Ant1: 5.26dBi; Ant2: 4.45dBi;

Note2: Directional Gain= $10\log[(10^{G1/20}+10^{G2/20})^2/2]=7.87\text{dBi}$;

4. Maximum Power Spectral Density

4.1 Test Result

4.1.1 PSD

Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum PSD (dBm/3kHz)				Verdict
					ANT1	ANT2	MIMO	Limit	
802.11b	SISO	2412	/	/	-7.18	-8.85	/	<=8	Pass
		2437	/	/	-7.06	-8.67	/	<=8	Pass
		2462	/	/	-8.49	-9.31	/	<=8	Pass
802.11g	SISO	2412	/	/	-9.07	-11.64	/	<=8	Pass
		2437	/	/	-11.32	-11.34	/	<=8	Pass
		2462	/	/	-10.90	-12.18	/	<=8	Pass
802.11n	MIMO	2412	/	/	-11.67	-12.74	-10.93	<=8	Pass


(HT20)		2437	/	/	-11.49	-12.54	-10.56	<=8	Pass
		2462	/	/	-11.32	-12.57	-9.89	<=8	Pass
802.11n (HT40)	MIMO	2422	/	/	-14.36	-15.22	-12.83	<=8	Pass
		2437	/	/	-13.88	-12.98	-12.19	<=8	Pass
		2452	/	/	-14.21	-15.31	-13.23	<=8	Pass
802.11ax (HEW20)	MIMO	2412	SU	/	-12.64	-14.69	-11.26	<=6.13	Pass
		2437	SU	/	-12.51	-13.56	-11.16	<=6.13	Pass
		2462	SU	/	-12.98	-14.11	-11.13	<=6.13	Pass
802.11ax (HEW40)	MIMO	2422	SU	/	-15.41	-14.89	-13.33	<=6.13	Pass
		2437	SU	/	-14.84	-15.99	-13.49	<=6.13	Pass
		2452	SU	/	-15.07	-15.40	-13.94	<=6.13	Pass
802.11ac (VHT20)	MIMO	2412	/	/	-11.12	-12.53	-9.85	<=6.13	Pass
		2437	/	/	-11.91	-12.46	-10.29	<=6.13	Pass
		2462	/	/	-11.95	-12.52	-10.51	<=6.13	Pass
802.11ac (VHT40)	MIMO	2422	/	/	-14.41	-15.06	-13.36	<=6.13	Pass
		2437	/	/	-13.38	-15.52	-11.36	<=6.13	Pass
		2452	/	/	-15.06	-15.80	-13.74	<=6.13	Pass
802.11be (EHT20)	MIMO	2412	SU	/	-12.85	-13.92	-10.86	<=6.13	Pass
		2437	SU	/	-12.75	-13.87	-11.05	<=6.13	Pass
		2462	SU	/	-12.98	-13.75	-11.27	<=6.13	Pass
802.11be (EHT40)	MIMO	2422	SU	/	-15.60	-14.90	-12.72	<=6.13	Pass
		2437	SU	/	-15.62	-15.41	-13.86	<=6.13	Pass
		2452	SU	/	-15.01	-15.68	-13.83	<=6.13	Pass

Note1: Antenna Gain: Ant1: 5.26dBi; Ant2: 4.45dBi;


Note2: Note2: Directional Gain= $10\log[(10^{G1/20}+10^{G2/20})^2/2]=7.87\text{dBi}$;

4.2 Test Graph

4.2.1 PSD



802.11b_MCH_2437MHz_Ant1 (SISO)_NTNV



802.11b_MCH_2437MHz_Ant2 (SISO)_NTNV

