

TEST REPORT

Product : BE5100 Dual-Band Wi-Fi 7 Router(2.5GE)
Trade mark : Tenda
Model/Type reference : RE6L Pro,TE6L Pro
Serial Number : N/A
Report Number : EED32Q81740601
FCC ID : V7TRE6LP
Date of Issue : Dec. 19, 2024
Test Standards : 47 CFR Part 15 Subpart C
Test result : PASS

Prepared for:

SHENZHEN TENDA TECHNOLOGY CO., LTD.**6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road, Nanshan District,
Shenzhen, China. 518052**

Prepared by:

Centre Testing International Group Co., Ltd.**Hongwei Industrial Zone, Bao'an 70 District,****Shenzhen, Guangdong, China****TEL: +86-755-3368 3668****FAX: +86-755-3368 3385**

Compiled by:

Frazer Li

Reviewed by:

Tom Chen

Approved by:

Frazer Li
Aaron Ma

Date:

Dec. 19, 2024

Check No.:2551301024




1 Content

1 CONTENT	2
2 VERSION	3
3 TEST SUMMARY	4
4 GENERAL INFORMATION	5
4.1 CLIENT INFORMATION	5
4.2 GENERAL DESCRIPTION OF EUT	5
4.3 TEST CONFIGURATION	7
4.4 TEST ENVIRONMENT	8
4.5 DESCRIPTION OF SUPPORT UNITS	8
4.6 TEST LOCATION	8
4.7 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2)	9
5 EQUIPMENT LIST	10
6 TEST RESULTS AND MEASUREMENT DATA	14
6.1 ANTENNA REQUIREMENT	14
6.2 AC POWER LINE CONDUCTED EMISSIONS	15
6.3 MAXIMUM CONDUCTED OUTPUT POWER	18
6.4 DTS BANDWIDTH	19
6.5 MAXIMUM POWER SPECTRAL DENSITY	20
6.6 BAND EDGE MEASUREMENTS AND CONDUCTED SPURIOUS EMISSION	21
6.7 RADIATED SPURIOUS EMISSION & RESTRICTED BANDS	22
7 APPENDIX 2.4G WI-FI	90
8 PHOTOGRAPHS OF TEST SETUP	91
9 PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	93

2 Version

Version No.	Date	Description
00	Dec. 19, 2024	Original



3 Test Summary

Test Item	Test Requirement	Result
Antenna Requirement	47 CFR Part 15 Subpart C Section 15.203/15.247 (c)	PASS
AC Power Line Conducted Emission	47 CFR Part 15 Subpart C Section 15.207	PASS
DTS Bandwidth	47 CFR Part 15 Subpart C Section 15.247 (a)(2)	PASS
Maximum Conducted Output Power	47 CFR Part 15 Subpart C Section 15.247 (b)(3)	PASS
Maximum Power Spectral Density	47 CFR Part 15 Subpart C Section 15.247 (e)	PASS
Band edge measurements	47 CFR Part 15 Subpart C Section 15.247(d)	PASS
Conducted Spurious Emissions	47 CFR Part 15 Subpart C Section 15.247(d)	PASS
Radiated Spurious Emission & Restricted bands	47 CFR Part 15 Subpart C Section 15.205/15.209	PASS

Remark:
Company Name and Address shown on Report, the sample(s) and sample Information were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified.

Model No.: RE6L Pro,TE6L Pro
Only the model RE6L Pro was tested. Their electrical circuit design, layout, components used and internal wiring are identical. Only the Model is different.

4 General Information

4.1 Client Information

Applicant:	SHENZHEN TENDA TECHNOLOGY CO., LTD.
Address of Applicant:	6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road, Nanshan District, Shenzhen, China. 518052
Manufacturer:	SHENZHEN TENDA TECHNOLOGY CO., LTD.
Address of Manufacturer:	6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road, Nanshan District, Shenzhen, China. 518052

4.2 General Description of EUT

Product Name:	BE5100 Dual-Band Wi-Fi 7 Router(2.5GE)	
Model No.(EUT):	RE6L Pro,TE6L Pro	
Test Mode No.:	RE6L Pro	
Trade mark:	Tenda	
Type of Modulation:	IEEE for 802.11b:DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g:OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40): OFDM (64QAM, 16QAM,QPSK,BPSK) IEEE for 802.11ax(HE20 and HE40): OFDMA (1024QAM, 64QAM,16QAM,QPSK,BPSK) IEEE for 802.11be(EHT20 and EHT40): OFDMA (4096QAM,1024QAM,64QAM, 16QAM,QPSK,BPSK) (Resource Unit with subcarriers:Full RU)	
Operating Frequency:	IEEE 802.11b/g/n(HT20)/ax(HE20)/be(EHT20): 2412MHz to 2462MHz IEEE 802.11n(HT40)/ax(HE20)/be(EHT20): 2422MHz to 2452MHz	
Channels Step:	Channels with 5MHz step	
Transmit Data Rate:	802.11b:1M/2M/5.5M/11M bps, 802.11g:6M/9M/12M/18M/24M/36M/48M/54M bps, 802.11n(HT20):MCS0-MCS15, 802.11n(HT40):MCS0-MCS15, 802.11ax(HE20):MCS0-MCS11, 802.11ax(HE40):MCS0-MCS11, 802.11be(EHT20):MCS0-MCS13, 802.11be(EHT40):MCS0-MCS13	
Sample Type:	Fixed production	
Antenna Configuration	<input checked="" type="checkbox"/> Single Transmitting (1T1R); <input checked="" type="checkbox"/> MIMO (<input checked="" type="checkbox"/> 2T2R, <input type="checkbox"/> 3T3R, <input type="checkbox"/> 4T4R, <input type="checkbox"/> Other);	
Antenna Type:	<input type="checkbox"/> Internal Antenna <input type="checkbox"/> PCB Antenna <input type="checkbox"/> Ceramic Antenna <input checked="" type="checkbox"/> External Antenna <input type="checkbox"/> Loop Antenna <input type="checkbox"/> Other:	
Antenna Gain:	2.4G CON1: 4.28dBi, 2.4G CON2: 4.28dBi, Beamforming gain: 3dBi	
Power Supply:	Adapter:	Model:TEKA-TC120150US Input:100-240V~50/60Hz,0.5A MAX Output:12.0V,1.5A
Test voltage:	DC 12.0V	
Sample Received Date:	Oct. 30, 2024	
Sample tested Date:	Oct. 30, 2024 to Dec. 10, 2024	

Operation Frequency each of channel (802.11b/g/n HT20/ax HE20/be EHT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Operation Frequency each of channel (802.11n HT40/ax HE40/be EHT40)						
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel
3	2422MHz	6	2437MHz	9	2452MHz	
4	2427MHz	7	2442MHz			
5	2432MHz	8	2447MHz			

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

802.11b/g/n HT20/ax HE20/be EHT20:

Channel	Frequency
The lowest channel	2412MHz
The middle channel	2437MHz
The highest channel	2462MHz

802.11n HT40/ax HE40/be EHT40:

Channel	Frequency
The lowest channel	2422MHz
The middle channel	2437MHz
The highest channel	2452MHz

4.3 Test Configuration

EUT Test Software Settings:	
Test Power Grade:	Default(manufacturer declare)
Test Software of EUT:	QATool_Dbge.exe(manufacturer declare)
Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.	
Test Mode:	
We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:	
Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.	
Mode	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(HT20)	MCS0
802.11n(HT40)	MCS0
802.11ax(HE20)	MCS0
802.11ax(HE40)	MCS0
802.11be(EHT20)	MCS0
802.11be(EHT40)	MCS0

According to ANSI C63.10 standards, the test results are both the “worst case” and “worst setup” 1Mbps for 802.11b, 6Mbps for 802.11g, MCS0 for 802.11n(HT20),MCS0 for 802.11n(HT40),MCS0 for 802.11ax(HE20),MCS0 for 802.11ax(HE40),MCS0 for 802.11be(EHT20),and MCS0 for 802.11be(EHT40).

4.4 Test Environment

Operating Environment:	
Radiated Spurious Emissions:	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar
Conducted Emissions:	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar
RF Conducted:	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar

4.5 Description of Support Units

The EUT has been tested with associated equipment below.

1) support equipment

Description	Manufacturer	Model No.	Certification	Supplied by
Netbook	Asus	FL8700JP1065-0D8GXYQ2X10	FCC&CE	CTI
Netbook	HP	DESKTOP-H31GDCQ	FCC&CE	CTI

4.6 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd
Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China
Telephone: +86 (0) 755 33683668 Fax:+86 (0) 755 33683385
No tests were sub-contracted.
FCC Designation No.: CN1164

4.7 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.9×10^{-8}
2	RF power, conducted	0.46dB (30MHz-1GHz)
		0.55dB (1GHz-40GHz)
3	Radiated Spurious emission test	3.3dB (9kHz-30MHz)
		4.3dB (30MHz-1GHz)
		4.5dB (1GHz-18GHz)
		3.4dB (18GHz-40GHz)
4	Conduction emission	3.5dB (9kHz to 150kHz)
		3.1dB (150kHz to 30MHz)
5	Temperature test	0.64°C
6	Humidity test	3.8%
7	DC power voltages	0.026%

5 Equipment List

RF test system					
Equipment	Manufacturer	Model No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Spectrum Analyzer	Keysight	N9010A	MY54510339	12-14-2023	12-13-2024
				12-05-2024	12-04-2025
Signal Generator	Keysight	N5182B	MY53051549	12-11-2023	12-10-2024
				11-30-2024	11-29-2025
DC Power	Keysight	E3642A	MY56376072	12-11-2023	12-10-2024
				11-30-2024	11-29-2025
Communication test set	R&S	CMW500	169004	03-08-2024	03-07-2025
RF control unit(power unit)	JS Tonscend	JS0806-2	22G8060592	07-22-2024	07-21-2025
Wi-Fi 7GHz Band Extender	JS Tonscend	TS-WF7U2	2206200002	05-31-2024	05-30-2025
High-low temperature test chamber	Dong Guang Qin Zhuo	LK-80GA	QZ20150611879	12-11-2023 11-30-2024	12-10-2024 11-29-2025
Temperature/Humidity Indicator	biaozhi	HM10	1804186	05-29-2024	05-28-2025
BT&WI-FI Automatic test software	JS Tonscend	JS1120-3	V3.3.20	---	---
Spectrum Analyzer	R&S	FSV3044	101509	01-17-2024	01-16-2025

Conducted disturbance Test					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Receiver	R&S	ESCI	100435	04-18-2024	04-17-2025
Temperature/ Humidity Indicator	Defu	TH128	/	04-25-2024	04-24-2025
LISN	R&S	ENV216	100098	09-19-2024	09-18-2025
Barometer	changchun	DYM3	1188	---	---
Test software	Fara	EZ-EMC	EMC-CON 3A1.1	---	---
Capacitive voltage probe	Schwarzbeck	CVP 9222C	00124	06-18-2024	06-17-2025
ISN	TESEQ	ISN T800	30297	12-14-2023 12-05-2024	12-13-2024 12-04-2025

3M Semi-anechoic Chamber (2)- Radiated disturbance Test					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
3M Chamber & Accessory Equipment	TDK	SAC-3	---	05/22/2022	05/21/2025
Receiver	R&S	ESCI7	100938-003	09/07/2024	09/06/2025
Spectrum Analyzer	R&S	FSV40	101200	07/18/2024	07/17/2025
TRILOG Broadband Antenna	schwarzbeck	VULB 9163	9163-618	05/22/2022	05/21/2025
Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-076	04/16/2024	04/15/2025
Microwave Preamplifier	Tonscend	EMC051845SE	980380	12/14/2023 12/05/2024	12/13/2024 12/04/2025
Horn Antenna	A.H.SYSTEMS	SAS-574	374	07/02/2023	07/01/2026
Horn Antenna	ETS-LINGREN	BBHA 9120D	9120D-1869	04/16/2024	04/15/2025
Preamplifier	Agilent	11909A	12-1	03/22/2024	03/21/2025
Preamplifier	CD	PAP-1840-60	6041.6042	06/19/2024	06/18/2025
Test software	Fara	EZ-EMC	EMEC-3A1-Pre	---	---
Cable line	Fulai(7M)	SF106	5219/6A	---	---
Cable line	Fulai(6M)	SF106	5220/6A	---	---
Cable line	Fulai(3M)	SF106	5216/6A	---	---
Cable line	Fulai(3M)	SF106	5217/6A	---	---

3M full-anechoic Chamber					
Equipment	Manufacturer	Model No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Fully Anechoic Chamber	TDK	FAC-3	---	01-09-2024	01-08-2027
Receiver	Keysight	N9038A	MY57290136	01-09-2024	01-08-2025
Spectrum Analyzer	Keysight	N9020B	MY57111112	01-29-2024	01-28-2025
Spectrum Analyzer	Keysight	N9030B	MY57140871	01-23-2024	01-22-2025
TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	9163-1148	04-28-2024	04-27-2025
Horn Antenna	Schwarzbeck	BBHA 9170	9170-832	04-16-2024	04-15-2025
Horn Antenna	ETS-LINDGREN	3117	57407	07-03-2024	07-02-2025
Preamplifier	EMCI	EMC001330	980563	03-08-2024	03-07-2025
Preamplifier	Tonscend	TAP-011858	AP21B806112	07-18-2024	07-17-2025
Preamplifier	Tonscend	EMC051845SE	980380	12-14-2023 12-05-2024	12-13-2024 12-04-2025
Temperature/Humidity Indicator	biaozhi	GM1360	EE1186631	04-07-2024	04-06-2025
RSE Automatic test software	JS Tonscend	JS36-RSE	V4.0.0.0	---	---
Cable line	Times	SFT205-NMSM-2.50M	394812-0001	---	---
Cable line	Times	SFT205-NMSM-2.50M	394812-0002	---	---
Cable line	Times	SFT205-NMSM-2.50M	394812-0003	---	---
Cable line	Times	SFT205-NMSM-2.50M	393495-0001	---	---
Cable line	Times	EMC104-NMNM-1000	SN160710	---	---
Cable line	Times	SFT205-NMSM-3.00M	394813-0001	---	---
Cable line	Times	SFT205-NMNM-1.50M	381964-0001	---	---
Cable line	Times	SFT205-NMSM-7.00M	394815-0001	---	---
Cable line	Times	HF160-KMKM-3.00M	393493-0001	---	---

6 Test results and Measurement Data

6.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna:	Please see Internal photos
The antenna is External Antenna. The best case gain of the antenna are 2.4G CON1: 4.28dBi, 2.4G CON2: 4.28dBi, Beamforming gain: 3dBi	


6.2 AC Power Line Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207																	
Test Method:	ANSI C63.10: 2013																	
Test Frequency Range:	150kHz to 30MHz																	
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto																	
Limit:	<table border="1"> <thead> <tr> <th>Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th></th> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr> <tr> <td>0.5-5</td><td>56</td><td>46</td></tr> <tr> <td>5-30</td><td>60</td><td>50</td></tr> </tbody> </table>			Frequency range (MHz)	Limit (dBuV)			Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)																	
	Quasi-peak	Average																
0.15-0.5	66 to 56*	56 to 46*																
0.5-5	56	46																
5-30	60	50																
	<p>* Decreases with the logarithm of the frequency.</p>																	
Test Setup:																		
Test Procedure:	<ol style="list-style-type: none"> 1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane. 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement. 																	
Test Mode:	All modes were tested, only the worse case lowest channel of 1Mbps for 802.11b was recorded in the report.																	

Test Results:	Pass
---------------	------

Measurement Data


Live line:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.1590	41.17	9.85	51.02	65.52	-14.50	QP		
2	0.3255	33.76	9.60	43.36	59.57	-16.21	QP		
3	0.4065	21.41	9.79	31.20	47.72	-16.52	AVG		
4	1.0725	19.28	9.74	29.02	56.00	-26.98	QP		
5	1.6125	10.74	9.75	20.49	46.00	-25.51	AVG		
6	2.1525	19.91	9.75	29.66	56.00	-26.34	QP		
7	3.7635	13.38	9.80	23.18	46.00	-22.82	AVG		
8	8.6055	25.42	9.84	35.26	60.00	-24.74	QP		
9	13.4475	17.70	9.84	27.54	50.00	-22.46	AVG		
10	21.6600	17.88	10.00	27.88	50.00	-22.12	AVG		
11 *	25.7685	38.71	9.90	48.61	60.00	-11.39	QP		
12	25.7685	26.22	9.90	36.12	50.00	-13.88	AVG		

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV	dB			
1	*	0.1635	46.04	9.85	55.89	65.28	-9.39	QP	
2		0.1635	22.65	9.85	32.50	55.28	-22.78	AVG	
3		0.2175	36.92	9.81	46.73	62.91	-16.18	QP	
4		0.4065	24.44	9.79	34.23	47.72	-13.49	AVG	
5		0.5190	23.35	9.74	33.09	56.00	-22.91	QP	
6		1.2164	15.13	9.74	24.87	46.00	-21.13	AVG	
7		1.6125	21.14	9.75	30.89	56.00	-25.11	QP	
8		1.7385	23.11	9.75	32.86	56.00	-23.14	QP	
9		3.2280	16.33	9.79	26.12	46.00	-19.88	AVG	
10		5.7165	15.30	9.84	25.14	50.00	-24.86	AVG	
11		9.6899	18.52	9.83	28.35	50.00	-21.65	AVG	
12		26.0295	37.06	9.89	46.95	60.00	-13.05	QP	


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.


6.3 Maximum Conducted Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10 2013
Test Setup:	
Test Procedure:	<p>1. PKPM1 Peak power meter measurement</p> <p>The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.</p>
Limit:	30dBm
Test Mode:	Refer to clause 5.3
Test Results:	Refer to Appendix 2.4G Wi-Fi


6.4 DTS Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10 2013
Test Setup:	 <p>Remark: Offset=Cable loss+ attenuation factor.</p>
Test Procedure:	<ol style="list-style-type: none"> Set RBW = 100 kHz. Set the VBW $\geq [3 \times \text{RBW}]$. Detector = peak. Trace mode = max hold. Sweep = auto couple. Allow the trace to stabilize. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
Limit:	≥ 500 kHz
Test Mode:	Refer to clause 5.3
Test Results:	Refer to Appendix 2.4G Wi-Fi

6.5 Maximum Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10 2013
Test Setup:	 <p>Remark: Offset=Cable loss+ attenuation factor.</p>
Test Procedure:	<ol style="list-style-type: none"> Set analyzer center frequency to DTS channel center frequency. Set the span to 1.5 times the DTS bandwidth. Set the RBW to $3 \text{ kHz} < \text{RBW} < 100 \text{ kHz}$. Set the VBW $> [3 \times \text{RBW}]$. Detector = peak. Sweep time = auto couple. Trace mode = max hold. Allow trace to fully stabilize. Use the peak marker function to determine the maximum amplitude level within the RBW. If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.
Limit:	$\leq 8.00 \text{ dBm}/3\text{kHz}$
Test Mode:	Refer to clause 5.3
Test Results:	Refer to Appendix 2.4G Wi-Fi

6.6 Band Edge Measurements and Conducted Spurious Emission

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10 2013
Test Setup:	 <p>Remark: Offset=Cable loss+ attenuation factor.</p>
Test Procedure:	<ol style="list-style-type: none"> Set RBW = 100KHz. Set VBW = 300KHz. Sweep time = auto couple. Detector = peak. Trace mode = max hold. Allow trace to fully stabilize. Use peak marker function to determine the peak amplitude level.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Mode:	Refer to clause 5.3
Test Results:	Refer to Appendix 2.4G Wi-Fi

6.7 Radiated Spurious Emission & Restricted bands

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10kHz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3

Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.





Figure 2. 30MHz to 1GHz

Figure 3. Above 1 GHz

Test Procedure:	<ol style="list-style-type: none"> 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. <p>Note: For the radiated emission test above 1GHz: Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.</p> <ol style="list-style-type: none"> The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both
-----------------	---


	<p>horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p> <p>g. Test the EUT in the lowest channel (2402MHz), the middle channel (2440MHz), the Highest channel (2480MHz)</p> <p>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</p> <p>i. Repeat above procedures until all frequencies measured was complete.</p>
Test Mode:	Refer to clause 5.3
Test Results:	Pass

Radiated Spurious Emission below 1GHz:

During the test, the Radiated Emission from 30MHz to 1GHz was performed in all modes, only the worst case lowest channel of 1Mbps for 802.11b was recorded in the report.


Horizontal:

Test Graph



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Antenna Height cm	Table Degree degree	Comment
1		67.2847	11.05	11.13	22.18	40.00	-17.82	QP 199	150	
2	*	100.6335	19.84	13.15	32.99	43.50	-10.51	QP 199	320	
3		128.2253	17.11	10.21	27.32	43.50	-16.18	QP 199	129	
4		202.9882	17.19	12.49	29.68	43.50	-13.82	QP 199	288	
5		213.9508	14.30	12.91	27.21	43.50	-16.29	QP 100	174	
6		500.0380	8.51	19.84	28.35	46.00	-17.65	QP 199	320	

Vertical:

Test Graph


No.	Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit dBuV/m	Margin dB	Antenna Height cm	Table Degree degree	Comment
			dBuV	dB/m	dBuV/m					
1		31.7146	14.27	12.12	26.39	40.00	-13.61	QP	200	251
2	*	36.3495	15.50	12.73	28.23	40.00	-11.77	QP	100	203
3		53.4302	8.80	12.76	21.56	40.00	-18.44	QP	100	172
4		99.1623	18.37	11.98	30.35	43.50	-13.15	QP	100	33
5		144.5120	20.48	7.90	28.38	43.50	-15.12	QP	100	2
6		164.3014	17.50	9.16	26.66	43.50	-16.84	QP	100	299

Radiated Spurious Emission above 1GHz:

Remark: Through Pre-scan, for 20MHz Occupied Bandwidth, 802.11 b mode was the worst case; for 40MHz Occupied Bandwidth, 802.11 n(HT40) mode was the worst case; only the worst case of was recorded in the report.

ANT 1:

Mode:			802.11 b Transmitting			Channel:		2412MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dB μ V]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Result	Polarity	Remark
1	1138.6759	10.04	38.10	48.14	74.00	25.86	PASS	H	PK
2	1803.5202	14.27	37.18	51.45	74.00	22.55	PASS	H	PK
3	3696.0464	-12.53	52.37	39.84	74.00	34.16	PASS	H	PK
4	4824.1216	-10.41	52.43	42.02	74.00	31.98	PASS	H	PK
5	11220.548	5.03	45.23	50.26	74.00	23.74	PASS	H	PK
6	15875.8584	12.81	39.34	52.15	74.00	21.85	PASS	H	PK
7	1159.8773	10.08	37.95	48.03	74.00	25.97	PASS	V	PK
8	1455.097	10.61	38.96	49.57	74.00	24.43	PASS	V	PK
9	3324.0216	-12.97	53.25	40.28	74.00	33.72	PASS	V	PK
10	4824.1216	-10.41	51.84	41.43	74.00	32.57	PASS	V	PK
11	14248.7499	12.66	38.71	51.37	74.00	22.63	PASS	V	PK
12	16412.8942	12.89	39.43	52.32	74.00	21.68	PASS	V	PK

Mode:			802.11 b Transmitting			Channel:		2437MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dB μ V]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Result	Polarity	Remark
1	1154.8103	10.25	38.47	48.72	74.00	25.28	PASS	H	PK
2	1692.3128	12.78	38.37	51.15	74.00	22.85	PASS	H	PK
3	4304.0869	-9.92	50.60	40.68	74.00	33.32	PASS	H	PK
4	6098.2065	-5.81	47.65	41.84	74.00	32.16	PASS	H	PK
5	9815.4544	3.19	45.16	48.35	74.00	25.65	PASS	H	PK
6	14253.7502	12.55	38.88	51.43	74.00	22.57	PASS	H	PK
7	1166.5444	9.87	38.13	48.00	74.00	26.00	PASS	V	PK
8	1965.7977	16.17	35.95	52.12	74.00	21.88	PASS	V	PK
9	4874.1249	-9.93	52.04	42.11	74.00	31.89	PASS	V	PK
10	7846.3231	-2.70	46.34	43.64	74.00	30.36	PASS	V	PK
11	11362.5575	4.89	44.65	49.54	74.00	24.46	PASS	V	PK
12	16431.8955	12.51	39.90	52.41	74.00	21.59	PASS	V	PK

Mode:			802.11 b Transmitting			Channel:		2462MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dB μ V]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Result	Polarity	Remark
1	1148.8099	10.37	37.44	47.81	74.00	26.19	PASS	H	PK
2	1380.0253	10.43	38.23	48.66	74.00	25.34	PASS	H	PK
3	3452.0301	-12.71	53.22	40.51	74.00	33.49	PASS	H	PK
4	4924.1283	-11.40	52.62	41.22	74.00	32.78	PASS	H	PK
5	7908.3272	-2.44	46.76	44.32	74.00	29.68	PASS	H	PK
6	14241.7494	11.37	40.00	51.37	74.00	22.63	PASS	H	PK
7	1149.8767	10.41	37.82	48.23	74.00	25.77	PASS	V	PK
8	1854.0569	15.33	36.10	51.43	74.00	22.57	PASS	V	PK
9	3432.0288	-12.93	53.50	40.57	74.00	33.43	PASS	V	PK
10	5829.1886	-7.29	49.60	42.31	74.00	31.69	PASS	V	PK
11	10812.5208	4.16	45.17	49.33	74.00	24.67	PASS	V	PK
12	17447.9632	18.25	33.60	51.85	74.00	22.15	PASS	V	PK

Mode:			802.11 n(HT40) Transmitting			Channel:		2422MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dB μ V]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Result	Polarity	Remark
1	1149.0766	10.38	38.14	48.52	74.00	25.48	PASS	H	PK
2	1440.296	10.62	38.65	49.27	74.00	24.73	PASS	H	PK
3	3338.0225	-12.74	53.64	40.90	74.00	33.10	PASS	H	PK
4	4299.0866	-9.73	50.78	41.05	74.00	32.95	PASS	H	PK
5	7852.3235	-2.62	46.28	43.66	74.00	30.34	PASS	H	PK
6	11774.585	3.91	45.77	49.68	74.00	24.32	PASS	H	PK
7	1141.2094	10.12	38.68	48.80	74.00	25.20	PASS	V	PK
8	1730.3154	13.00	37.07	50.07	74.00	23.93	PASS	V	PK
9	3369.0246	-12.90	53.89	40.99	74.00	33.01	PASS	V	PK
10	4502.1001	-8.48	49.15	40.67	74.00	33.33	PASS	V	PK
11	6184.2123	-6.65	48.71	42.06	74.00	31.94	PASS	V	PK
12	11251.5501	5.78	43.94	49.72	74.00	24.28	PASS	V	PK

Mode:			802.11 n(HT40) Transmitting			Channel:		2437MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dB μ V]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Result	Polarity	Remark
1	1146.0097	10.28	38.52	48.80	74.00	25.20	PASS	H	PK
2	1731.9155	13.00	37.07	50.07	74.00	23.93	PASS	H	PK
3	3457.0305	-12.92	53.31	40.39	74.00	33.61	PASS	H	PK
4	4380.092	-10.98	52.18	41.20	74.00	32.80	PASS	H	PK
5	7873.3249	-2.62	47.60	44.98	74.00	29.02	PASS	H	PK
6	11350.5567	5.15	44.84	49.99	74.00	24.01	PASS	H	PK
7	1167.3445	9.84	38.74	48.58	74.00	25.42	PASS	V	PK
8	1703.9136	12.93	37.38	50.31	74.00	23.69	PASS	V	PK
9	3411.0274	-13.29	53.54	40.25	74.00	33.75	PASS	V	PK
10	4698.1132	-9.01	48.92	39.91	74.00	34.09	PASS	V	PK
11	6869.258	-4.84	47.81	42.97	74.00	31.03	PASS	V	PK
12	11251.5501	5.78	44.60	50.38	74.00	23.62	PASS	V	PK

Mode:			802.11 n(HT40) Transmitting			Channel:		2452MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dB μ V]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Result	Polarity	Remark
1	1154.4103	10.26	37.90	48.16	74.00	25.84	PASS	H	PK
2	1660.5774	12.21	37.71	49.92	74.00	24.08	PASS	H	PK
3	3344.0229	-12.64	53.86	41.22	74.00	32.78	PASS	H	PK
4	5817.1878	-7.39	48.35	40.96	74.00	33.04	PASS	H	PK
5	7852.3235	-2.62	46.25	43.63	74.00	30.37	PASS	H	PK
6	11235.549	5.46	44.12	49.58	74.00	24.42	PASS	H	PK
7	1145.4764	10.27	37.38	47.65	74.00	26.35	PASS	V	PK
8	1604.1736	11.68	37.30	48.98	74.00	25.02	PASS	V	PK
9	3363.0242	-12.78	53.45	40.67	74.00	33.33	PASS	V	PK
10	5410.1607	-8.50	48.47	39.97	74.00	34.03	PASS	V	PK
11	7855.3237	-2.62	46.62	44.00	74.00	30.00	PASS	V	PK
12	11253.5502	5.66	44.23	49.89	74.00	24.11	PASS	V	PK

MIMO:

Mode:			802.11 n(HT20) Transmitting			Channel:		2412MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dB μ V]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Result	Polarity	Remark
1	1146.9431	10.31	37.95	48.26	74.00	25.74	PASS	H	PK
2	1604.9737	11.68	37.92	49.60	74.00	24.40	PASS	H	PK
3	3427.0285	-13.01	53.80	40.79	74.00	33.21	PASS	H	PK
4	4495.0997	-8.88	50.24	41.36	74.00	32.64	PASS	H	PK
5	7927.3285	-2.03	46.07	44.04	74.00	29.96	PASS	H	PK
6	10284.4856	3.58	45.55	49.13	74.00	24.87	PASS	H	PK
7	1148.2766	10.35	38.34	48.69	74.00	25.31	PASS	V	PK
8	1693.9129	12.81	36.74	49.55	74.00	24.45	PASS	V	PK
9	3689.0459	-12.64	53.74	41.10	74.00	32.90	PASS	V	PK
10	5354.1569	-8.29	49.91	41.62	74.00	32.38	PASS	V	PK
11	7840.3227	-2.83	46.06	43.23	74.00	30.77	PASS	V	PK
12	13241.6828	8.41	43.55	51.96	74.00	22.04	PASS	V	PK

Mode:			802.11 n(HT20) Transmitting			Channel:		2437MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dB μ V]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Result	Polarity	Remark
1	1051.8701	9.65	38.81	48.46	74.00	25.54	PASS	H	PK
2	1703.3802	12.93	37.60	50.53	74.00	23.47	PASS	H	PK
3	3715.0477	-12.74	52.80	40.06	74.00	33.94	PASS	H	PK
4	4520.1013	-9.18	50.71	41.53	74.00	32.47	PASS	H	PK
5	7444.2963	-4.57	47.67	43.10	74.00	30.90	PASS	H	PK
6	13260.684	8.39	43.09	51.48	74.00	22.52	PASS	H	PK
7	1148.6766	10.37	37.81	48.18	74.00	25.82	PASS	V	PK
8	1445.0963	10.63	38.35	48.98	74.00	25.02	PASS	V	PK
9	3357.0238	-12.68	55.16	42.48	74.00	31.52	PASS	V	PK
10	4710.114	-9.16	49.90	40.74	74.00	33.26	PASS	V	PK
11	6096.2064	-5.88	47.58	41.70	74.00	32.30	PASS	V	PK
12	10284.4856	3.58	44.33	47.91	74.00	26.09	PASS	V	PK

Mode:			802.11 n(HT20) Transmitting			Channel:		2462MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dB μ V]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Result	Polarity	Remark
1	1149.0766	10.38	38.81	49.19	74.00	24.81	PASS	H	PK
2	1605.3737	11.69	38.42	50.11	74.00	23.89	PASS	H	PK
3	3426.0284	-13.03	54.27	41.24	74.00	32.76	PASS	H	PK
4	5081.1387	-9.29	50.10	40.81	74.00	33.19	PASS	H	PK
5	7923.3282	-2.12	45.54	43.42	74.00	30.58	PASS	H	PK
6	11242.5495	5.66	44.74	50.40	74.00	23.60	PASS	H	PK
7	1051.7368	9.66	39.39	49.05	74.00	24.95	PASS	V	PK
8	1623.7749	11.83	37.32	49.15	74.00	24.85	PASS	V	PK
9	3345.023	-12.63	53.74	41.11	74.00	32.89	PASS	V	PK
10	4665.111	-10.05	50.59	40.54	74.00	33.46	PASS	V	PK
11	7864.3243	-2.62	46.51	43.89	74.00	30.11	PASS	V	PK
12	11345.5564	4.96	44.94	49.90	74.00	24.10	PASS	V	PK

Mode:			802.11 n(HT40) Transmitting			Channel:		2422MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dB μ V]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Result	Polarity	Remark
1	1144.2763	10.22	38.42	48.64	74.00	25.36	PASS	H	PK
2	1623.5082	11.83	38.27	50.10	74.00	23.90	PASS	H	PK
3	3368.0245	-12.88	54.01	41.13	74.00	32.87	PASS	H	PK
4	5364.1576	-8.31	48.90	40.59	74.00	33.41	PASS	H	PK
5	7950.33	-1.58	45.26	43.68	74.00	30.32	PASS	H	PK
6	11951.5968	5.87	45.38	51.25	74.00	22.75	PASS	H	PK
7	1151.7434	10.35	38.53	48.88	74.00	25.12	PASS	V	PK
8	1652.8435	12.07	38.34	50.41	74.00	23.59	PASS	V	PK
9	3273.0182	-13.74	54.63	40.89	74.00	33.11	PASS	V	PK
10	5426.1617	-8.63	49.22	40.59	74.00	33.41	PASS	V	PK
11	7748.3166	-3.16	47.04	43.88	74.00	30.12	PASS	V	PK
12	11241.5494	5.63	43.87	49.50	74.00	24.50	PASS	V	PK

Mode:			802.11 n(HT40) Transmitting			Channel:		2437MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dB μ V]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Result	Polarity	Remark
1	1147.7432	10.34	38.46	48.80	74.00	25.20	PASS	H	PK
2	1427.8952	10.63	38.44	49.07	74.00	24.93	PASS	H	PK
3	3345.023	-12.63	53.95	41.32	74.00	32.68	PASS	H	PK
4	6104.2069	-5.82	47.28	41.46	74.00	32.54	PASS	H	PK
5	7749.3166	-3.11	46.56	43.45	74.00	30.55	PASS	H	PK
6	11243.5496	5.69	44.66	50.35	74.00	23.65	PASS	H	PK
7	1545.9031	10.90	37.59	48.49	74.00	25.51	PASS	V	PK
8	1881.1254	15.41	36.97	52.38	74.00	21.62	PASS	V	PK
9	4091.0727	-10.72	50.21	39.49	74.00	34.51	PASS	V	PK
10	6473.2315	-6.52	47.47	40.95	74.00	33.05	PASS	V	PK
11	8745.383	-0.89	45.27	44.38	74.00	29.62	PASS	V	PK
12	16826.9218	13.27	39.41	52.68	74.00	21.32	PASS	V	PK

Mode:			802.11 n(HT40) Transmitting			Channel:		2452MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dB μ V]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Result	Polarity	Remark
1	1770.0513	13.51	37.95	51.46	74.00	22.54	PASS	H	PK
2	3779.0519	-12.48	51.96	39.48	74.00	34.52	PASS	H	PK
3	5497.1665	-8.49	47.79	39.30	74.00	34.70	PASS	H	PK
4	7943.3296	-1.70	45.02	43.32	74.00	30.68	PASS	H	PK
5	11250.55	5.84	44.42	50.26	74.00	23.74	PASS	H	PK
6	16418.8946	12.77	40.25	53.02	74.00	20.98	PASS	H	PK
7	2071.6714	15.29	37.42	52.71	74.00	21.29	PASS	V	PK
8	4245.083	-10.86	50.07	39.21	74.00	34.79	PASS	V	PK
9	5766.1844	-7.32	48.65	41.33	74.00	32.67	PASS	V	PK
10	7825.3217	-3.14	46.62	43.48	74.00	30.52	PASS	V	PK
11	10298.4866	3.83	44.29	48.12	74.00	25.88	PASS	V	PK
12	11965.5977	5.87	44.52	50.39	74.00	23.61	PASS	V	PK

2.4G Wi-Fi+5G Wi-Fi									
NO	Freq. [MHz]	Factor [dB]	Reading [dB μ V]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Result	Polarity	Remark
1	1398.4398	8.41	37.20	45.61	74.00	28.39	PASS	H	PK
2	2052.9053	10.77	36.44	47.21	74.00	26.79	PASS	H	PK
3	3367.0245	-16.79	52.95	36.16	74.00	37.84	PASS	H	PK
4	5369.1579	-10.29	48.33	38.04	74.00	35.96	PASS	H	PK
5	9080.4054	0.96	45.48	46.44	74.00	27.56	PASS	H	PK
6	15249.8167	13.78	36.77	50.55	74.00	23.45	PASS	H	PK
7	1226.8227	6.02	37.50	43.52	74.00	30.48	PASS	V	PK
8	1942.2942	12.15	36.10	48.25	74.00	25.75	PASS	V	PK
9	3787.0525	-15.67	51.86	36.19	74.00	37.81	PASS	V	PK
10	6882.2588	-4.38	47.47	43.09	74.00	30.91	PASS	V	PK
11	11985.599	6.21	43.95	50.16	74.00	23.84	PASS	V	PK
12	15897.8599	10.35	40.07	50.42	74.00	23.58	PASS	V	PK

Remark:


- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, the disturbance above 10GHz and below 30MHz was very low. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

Restricted bands:

Test plot as follows:

EUT_Name		Test_Model	
Test_Mode	2412MHz	Test_Frequency	802.11 b Transmitting
Tset_Engineer	chenjun	Test_Date	2024/11/29
Remark	21.8°C59.9%\		

Test Graph




Suspected List

NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390	15.31	35.77	51.08	74.00	22.92	PASS	Horizontal	PK
2	2390	15.31	23.29	38.60	54.00	15.40	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	2412MHz	Test_Frequency	802.11 b Transmitting
Tset_Engineer	chenjun	Test_Date	2024/11/29
Remark	21.8°C59.9%\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390	15.31	35.71	51.02	74.00	22.98	PASS	Vertical	PK
2	2390	15.31	23.20	38.51	54.00	15.49	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	2462MHz	Test_Frequency	802.11 b Transmitting
Tset_Engineer	chenjun	Test_Date	2024/11/29
Remark	21.8°C59.9%\		

Test Graph




Suspected List

NO	Freq. [MHz]	Factor [dB]	Reading [dB μ V]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5	15.16	36.04	51.20	74.00	22.80	PASS	Horizontal	PK
2	2483.5	15.16	21.45	36.61	54.00	17.39	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	2462MHz	Test_Frequency	802.11 b Transmitting
Tset_Engineer	chenjun	Test_Date	2024/11/29
Remark	21.8°C59.9%\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5	15.16	35.78	50.94	74.00	23.06	PASS	Vertical	PK
2	2483.5	15.16	21.16	36.32	54.00	17.68	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	2412MHz	Test_Frequency	802.11 g Transmitting
Tset_Engineer	chenjun	Test_Date	2024/11/29
Remark	21.8°C 59.9% \		

Test Graph




Suspected List

NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390	15.31	37.34	52.65	74.00	21.35	PASS	Horizontal	PK
2	2390	15.31	23.24	38.55	54.00	15.45	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	2412MHz	Test_Frequency	802.11 g Transmitting
Tset_Engineer	chenjun	Test_Date	2024/11/29
Remark	21.8°C59.9%\		

Test Graph




Suspected List

NO	Freq. [MHz]	Factor [dB]	Reading [dB μ V]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Result	Polarity	Remark
1	2390	15.31	35.99	51.30	74.00	22.70	PASS	Vertical	PK
2	2390	15.31	23.42	38.73	54.00	15.27	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	2462MHz	Test_Frequency	802.11 g Transmitting
Tset_Engineer	chenjun	Test_Date	2024/11/29
Remark	21.8°C 59.9% \		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5	15.16	34.59	49.75	74.00	24.25	PASS	Horizontal	PK
2	2483.5	15.16	21.44	36.60	54.00	17.40	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	2462MHz	Test_Frequency	802.11 g Transmitting
Tset_Engineer	chenjun	Test_Date	2024/11/29
Remark	21.8°C 59.9% \		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5	15.16	35.23	50.39	74.00	23.61	PASS	Vertical	PK
2	2483.5	15.16	21.53	36.69	54.00	17.31	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	2412MHz	Test_Frequency	802.11 n(HT20) Transmitting
Tset_Engineer	chenjun	Test_Date	2024/11/29
Remark	21.8°C59.9%\		

Test Graph




Suspected List

NO	Freq. [MHz]	Factor [dB]	Reading [dB μ V]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Result	Polarity	Remark
1	2390	15.31	36.99	52.30	74.00	21.70	PASS	Horizontal	PK
2	2390	15.31	23.44	38.75	54.00	15.25	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	2412MHz	Test_Frequency	802.11 n(HT20) Transmitting
Tset_Engineer	chenjun	Test_Date	2024/11/29
Remark	21.8°C59.9%\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390	15.31	36.73	52.04	74.00	21.96	PASS	Vertical	PK
2	2390	15.31	22.94	38.25	54.00	15.75	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	2462MHz	Test_Frequency	802.11 n(HT20) Transmitting
Tset_Engineer	chenjun	Test_Date	2024/11/29
Remark	21.8°C59.9%\		

Test Graph




Suspected List

NO	Freq. [MHz]	Factor [dB]	Reading [dB μ V]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5	15.16	36.51	51.67	74.00	22.33	PASS	Horizontal	PK
2	2483.5	15.16	21.43	36.59	54.00	17.41	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	2462MHz	Test_Frequency	802.11 n(HT20) Transmitting
Tset_Engineer	chenjun	Test_Date	2024/11/29
Remark	21.8°C59.9%\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dB μ V]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5	15.16	34.63	49.79	74.00	24.21	PASS	Vertical	PK
2	2483.5	15.16	21.28	36.44	54.00	17.56	PASS	Vertical	AV