

FCC TEST REPORT
for
SKYPINE ELECTRONICS (SHEN ZHEN) CO., LTD.

Multimedia Navigation System
Model No.: PR-GM1210, CNE-6104-RS

Prepared for : SKYPINE ELECTRONICS (SHEN ZHEN) CO., LTD.
Address : A1 BUILDING, NO.6 XINXING INDUSTRIAL PARK XINHE
VILLAGE, FUYONG TOWN, BAOAN, SHENZHEN, CHINA

Prepared By : Anbotech Compliance Laboratory Limited
Address : 1/F, 1 /Building, SEC Industrial Park, No. 4 Qianhai Road,
Nanshan District, Shenzhen, 518054, China
Tel: (86) 755-26066544
Fax: (86) 755-26014772

Report Number : 201205818F
Date of Test : May 20~26, 2012
Date of Report : May 27, 2012

TABLE OF CONTENTS

Description	Page
Test Report	1
1. GENERAL INFORMATION	4
1.1. Description of Device (EUT).....	4
1.2. Auxiliary Equipment Used during Test.....	5
1.3. Description of Test Facility	6
1.4. Measurement Uncertainty.....	6
2. MEASURING DEVICE AND TEST EQUIPMENT	7
3. TEST PROCEDURE	8
4. RADIATION INTERFERENCE.....	9
4.1. Requirements (15.249, 15.209):	9
4.2 Test Procedure	9
4.3 Test Results.....	9
5. OCCUPIED BANDWIDTH.....	13
5.1. Requirements (15.249):	13
5.2. Test Procedure	13
5.3. Test Configuration:.....	13
5.4. Test Results.....	13
6. PHOTOGRAPH.....	16
6.1. Photo of Radiation Emission Test	16
APPENDIX I (ExternalPhotos) (1 Page)	
APPENDIX II (InternalPhotos) (3 Pages)	

TEST REPORT

Applicant : SKYPINE ELECTRONICS (SHEN ZHEN) CO., LTD.
 Manufacturer : SKYPINE ELECTRONICS (SHEN ZHEN) CO., LTD.
 EUT : Multimedia Navigation System
 Model No. : PR-GM1210, CNE-6104-RS
 Serial No. : N/A
 Rating : 12V---
 Trade Mark : Rosen, Skypine

Measurement Procedure Used:

FCC Part15 Subpart C, Paragraph 15.207, 15.249 & 15.209

The device described above is tested by Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Anbotek Compliance Laboratory Limited

Date of Test :

May 20~26, 2012




Prepared by :

(Tested Engineer / Andy Chen)



Reviewer :

(Project Manager / Jerry Du)



Approved & Authorized Signer :

(Manager / Tom Chen)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT : Multimedia Navigation System

Model Number : PR-GM1210, CNE-6104-RS

Test Power Supply : 12V---

Frequency : 2402~2480MHz

Antenna Specification : Printed Antenna:1.87dBi

Applicant Address : SKYPINE ELECTRONICS (SHEN ZHEN) CO., LTD.
: A1 BUILDING, NO.6 XINXING INDUSTRIAL PARK XINHE
VILLAGE, FUYONG TOWN, BAOAN, SHENZHEN,China

Manufacturer Address : SKYPINE ELECTRONICS (SHEN ZHEN) CO., LTD.
: A1 BUILDING, NO.6 XINXING INDUSTRIAL PARK XINHE
VILLAGE, FUYONG TOWN, BAOAN, SHENZHEN,China

Date of receiver : May 20, 2012

Date of Test : May 20~26, 2012

1.2. Auxiliary Equipment Used during Test

PC	: Manufacturer: DELL M/N: OPTIPLEX 380 S/N: 1J63X2X CE , FCC: DOC
MONITOR	: Manufacturer: DELL M/N: E170Sc S/N: CN-00V539-64180-055-0UPS CE , FCC: DOC
MOUSE	: Manufacturer: DELL M/N: M-UARDEL7 S/N: N/A CE , FCC: DOC Cable: 1m, unshielded
Printer	: Manufacturer: Brother M/N: MFC-3360C S/N: N/A CE, FCC: DOC
Power Line	: Non-Shielded, 1.5m
VGA Cable	: Non-Shielded, 1.5m
USB Cable	: Non-Shielded, 0.5m

1.3. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS - LAB Code: L3503

Anbotech Compliance Laboratory Limited., Laboratory has been assessed and in compliance with CNAS/CL01: 2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

FCC-Registration No.: 752021

Anbotech Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 752021, August 20, 2010.

IC-Registration No.: 8058A-1

Anbotech Compliance Laboratory Limited., EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration 8058A-1, August 30, 2010.

Test Location

All Emissions tests were performed at

Anbotech Compliance Laboratory Limited. at 1/F, 1 /Building, SEC Industrial Park, No. 4 Qianhai Road, Nanshan District, Shenzhen, 518054, China

1.4. Measurement Uncertainty

Radiation Uncertainty : Ur = 4.3dB

Conduction Uncertainty : Uc = 3.4dB

2. MEASURING DEVICE AND TEST EQUIPMENT

Equipment	Manufacturer	Model #	Serial #	Data of Cal.	Due Data
EMI Test Receiver	Rohde & Schwarz	ESCI	100119	Apr. 12, 2012	Apr. 12, 2013
EMI Test Receiver	Rohde & Schwarz	ESIB26	100249	Apr. 12, 2012	Apr. 12, 2013
EMI Test Software	SHURPLE	ESK1	N/A	N/A	N/A
Spectrum Analyzer	Agilent	E4407B	3649A03840	Apr. 12, 2012	Apr. 12, 2013
Signal Generator	Rohde & Schwarz	SMR27	100124	Apr. 12, 2012	Apr. 12, 2013
Signal Generator	Rohde & Schwarz	SML03	102319	Apr. 12, 2012	Apr. 12, 2013
AC Power Source	Sepcial power system	YF650	N/A	N/A	N/A
Absorbing Clamp	Rohde & Schwarz	MDS21	100218	Apr. 12, 2012	Apr. 12, 2013
Power Meter	Rohde & Schwarz	NRVD	101287	Apr. 12, 2012	Apr. 12, 2013
Coaxial Cable	N/A	N/A	N/A	Apr. 12, 2012	Apr. 12, 2013
Coaxial Cable	N/A	N/A	N/A	Apr. 12, 2012	Apr. 12, 2013
Coaxial Cable	N/A	N/A	N/A	Apr. 12, 2012	Apr. 12, 2013
Universal radio Communication tester	Rohde & Schwarz	CMU200	101724	Apr. 12, 2012	Apr. 12, 2013
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	N/A	N/A	N/A
BiConilog Antenna	ETS-LINDGREN	3142C	00042670	Apr. 12, 2012	Apr. 12, 2013
BiConilog Antenna	ETS-LINDGREN	3142C	00042673	Apr. 12, 2012	Apr. 12, 2013
Loop Antenna	ETS-LINGREN	6502	00071730	Apr. 12, 2012	Apr. 12, 2013
Double-ridged Waveguide horn	ETS-LINDGREN	3117	00035926	Apr. 12, 2012	Apr. 12, 2013
Double-ridged Waveguide horn	ETS-LINDGREN	3117	00041545	Apr. 12, 2012	Apr. 12, 2013
Pre-amplifier	Instruments Corporation	EMC011830	1415261	Apr. 12, 2012	Apr. 12, 2013
RF Switch	CD	RSU-M3	706543	Apr. 12, 2012	Apr. 12, 2013
Thermo-/Hygrometer	N/A	TH01	N/A	Apr. 12, 2012	Apr. 12, 2013
Shielding Room	Zhong Yu Electronic	N/A	N/A	N/A	N/A
3m Anechoic Chamber	Zhong Yu Electronic	N/A	N/A	Apr. 12, 2012	Apr. 12, 2013
RF Cable	NK NETWORKS	M17/74-RG213	CH-NR.32115 (EE170)	Apr. 12, 2012	Apr. 12, 2013
Horn Anternna	Instruments Corporation	GTH-0118	9120D-707	Apr. 12, 2012	Apr. 12, 2013

3. Test Procedure

GENERAL: This report shall NOT be reproduced except in full without the written approval of Anbotek Compliance Laboratory Limited. The EUT was transmitting a test signal during the testing.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-2009 using a spectrum analyzer with a pre-selector. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz up to 1.0GHz and 1.0MHz with a video BW of 3.0MHz above 1.0GHz. The ambient temperature of the EUT was 74.3oF with a humidity of 69%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) METER READING + ACF = FS
20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

ANSI STANDARD C63.4-2009 10.1.7 MEASUREMENT PROCEDURES: The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The EUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation. When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

4. Radiation Interference

4.1. Requirements (15.249, 15.209):

FIELD STRENGTH of Fundamental: 902-928 MHZ 2.4-2.4835 GHz 94 dB μ V/m @3m	FIELD STRENGTH of Harmonics 54 dB μ V/m @3m	S15.209 30 - 88 MHz 88 - 216 MHz 216 - 960 MHz ABOVE 960 MHz	40 dB μ V/m @3M 43.5 46 54dB μ V/m
---	---	--	---

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in 15.209, whichever is the lesser attenuation.

4.2 Test Procedure

The EUT is placed on a turn table which is 0.8 meter high above the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

All readings from 30MHz to 1GHz are quasi-peak values with a resolution bandwidth of 120kHz. All reading are above 1GHz, peak & average values with a resolution bandwidth of 1MHz. The EUT is tested in 9*6*6 Chamber.

The test results are listed in Section 5.3.

4.3 Test Results

PASS.

Please refer the following pages.

Data:Horizontal
CH Low(2402MHz)

Frequency MHz	Cable Loss dB	Ant Factor dB/m	Preamp Factor dB	Read Level dB μ V	Level dB μ V/m	Limit dB μ V/m	Over Limit dB	Remark
239.98	1.58	13.50	38.90	53.42	29.60	46.00	-16.40	QP
2402.00	2.17	31.21	35.30	86.24	84.32	114.0	-29.68	Peak
2402.00	2.17	31.21	35.30	84.24	82.32	94.0	-11.68	AV
4804.10	2.56	34.01	34.71	43.21	45.07	74.0	-28.93	Peak
4804.10	2.56	34.01	34.71	34.94	36.80	54.0	-17.20	AV
7207.97	2.98	36.16	35.15	38.34	42.33	74.0	-31.67	Peak
7207.97	2.98	36.16	35.15	34.45	38.44	54.0	-15.56	AV
9608.00	---	---	---	---	---	---	---	---
12010.00	---	---	---	---	---	---	---	---
14412.00	---	---	---	---	---	---	---	---
16814.00	---	---	---	---	---	---	---	---
19216.00	---	---	---	---	---	---	---	---
21618.00	---	---	---	---	---	---	---	---
24020.00	---	---	---	---	---	---	---	---

CH Middle(2441MHz)

Frequency MHz	Cable Loss dB	Ant Factor dB/m	Preamp Factor dB	Read Level dB μ V	Level dB μ V/m	Limit dB μ V/m	Over Limit dB	Remark
312.18	1.60	13.52	38.82	56.40	32.70	46.00	-13.30	QP
2441.00	2.19	31.22	34.60	85.35	84.16	114.0	-29.84	Peak
2441.00	2.19	31.22	34.60	83.55	82.36	94.0	-11.64	AV
4882.08	2.57	35.00	34.58	39.62	42.61	74.0	-31.39	Peak
4882.08	2.57	35.00	34.58	37.47	40.46	54.0	-13.54	AV
7323.05	3.00	36.17	35.14	38.80	42.83	74.0	-31.17	Peak
7323.05	3.00	36.17	35.14	36.08	40.11	54.0	-13.89	AV
9764.00	---	---	---	---	---	---	---	---
12205.00	---	---	---	---	---	---	---	---
14646.00	---	---	---	---	---	---	---	---
17087.00	---	---	---	---	---	---	---	---
19528.00	---	---	---	---	---	---	---	---
21969.00	---	---	---	---	---	---	---	---
24410.00	---	---	---	---	---	---	---	---

FCC ID: V8VCNE6104RS

CH High(2480MHz)

Frequency MHz	Cable Loss dB	Ant Factor dB/m	Preamp Factor dB	Read Level dB μ V	Level dB μ V/m	Limit dB μ V/m	Over Limit dB	Remark
312.18	1.60	13.52	38.82	54.22	30.52	46.00	-15.48	QP
2480.00	2.20	31.65	36.00	92.78	90.63	114.0	-23.37	Peak
2480.00	2.20	31.65	36.00	89.41	87.26	94.0	-6.74	AV
4960.05	2.58	35.06	34.79	41.76	44.61	74.0	-29.39	Peak
4960.05	2.58	35.06	34.79	39.28	42.13	54.0	-11.87	AV
7439.97	3.02	36.19	34.90	39.54	43.85	74.0	-30.15	Peak
7439.97	3.02	36.20	35.20	37.40	41.42	54.0	-12.58	AV
9920.00	---	---	---	---	---	---	---	---
12400.00	---	---	---	---	---	---	---	---
14880.00	---	---	---	---	---	---	---	---
17360.00	---	---	---	---	---	---	---	---
19840.00	---	---	---	---	---	---	---	---
22320.00	---	---	---	---	---	---	---	---
24800.00	---	---	---	---	---	---	---	---

Vertical
CH Low(2402MHz)

Frequency MHz	Cable Loss dB	Ant Factor dB/m	Preamp Factor dB	Read Level dB μ V	Level dB μ V/m	Limit dB μ V/m	Over Limit dB	Remark
30.42	1.43	12.13	38.45	53.51	28.62	40.00	-11.38	QP
2402.00	2.17	31.21	35.30	83.23	81.31	114.0	-32.69	Peak
2402.00	2.17	31.21	35.30	81.85	79.93	94.0	-14.07	AV
4804.10	2.56	34.01	34.71	41.05	42.91	74.0	-31.09	Peak
4804.10	2.56	34.01	34.71	38.60	40.46	54.0	-13.54	AV
7207.93	2.98	36.16	35.15	37.47	41.46	74.0	-32.54	Peak
7207.93	2.98	36.16	35.15	34.50	38.49	54.0	-15.51	AV
9608.00	---	---	---	---	---	---	---	---
12010.00	---	---	---	---	---	---	---	---
14412.00	---	---	---	---	---	---	---	---
16814.00	---	---	---	---	---	---	---	---
19216.00	---	---	---	---	---	---	---	---
21618.00	---	---	---	---	---	---	---	---
24020.00	---	---	---	---	---	---	---	---

FCC ID: V8VCNE6104RS

CH Middle(2441MHz)

Frequency MHz	Cable Loss dB	Ant Factor dB/m	Preamp Factor dB	Read Level dB μ V	Level dB μ V/m	Limit dB μ V/m	Over Limit dB	Remark
143.82	1.50	13.40	38.89	53.91	29.92	43.50	-13.58	QP
2441.01	2.19	31.22	34.60	82.25	81.06	114.0	-32.94	Peak
2441.01	2.19	31.22	34.60	81.01	79.82	94.0	-14.18	AV
4882.11	2.57	35.00	34.58	40.15	43.14	74.0	-30.86	Peak
4882.11	2.57	35.00	34.58	37.86	40.85	54.0	-13.15	AV
7323.05	3.00	36.17	35.14	38.70	42.73	74.0	-31.27	Peak
7323.05	3.00	36.17	35.14	36.00	40.03	54.0	-13.81	AV
9764.00	---	---	---	---	---	---	---	---
12205.00	---	---	---	---	---	---	---	---
14646.00	---	---	---	---	---	---	---	---
17087.00	---	---	---	---	---	---	---	---
19528.00	---	---	---	---	---	---	---	---
21969.00	---	---	---	---	---	---	---	---
24410.00	---	---	---	---	---	---	---	---

CH High(2480MHz)

Frequency MHz	Cable Loss dB	Ant Factor dB/m	Preamp Factor dB	Read Level dB μ V	Level dB μ V/m	Limit dB μ V/m	Over Limit dB	Remark
408.80	1.62	13.54	38.45	51.15	27.86	46.00	-18.14	QP
2480.00	2.20	31.65	36.00	83.42	81.27	114.0	-32.73	Peak
2480.00	2.20	31.65	36.00	82.02	79.87	94.0	-14.13	AV
4960.10	2.58	35.06	34.79	40.08	42.93	74.0	-31.07	Peak
4960.10	2.58	35.06	34.79	38.10	40.95	54.0	-13.05	AV
7439.97	3.02	36.19	34.90	38.58	42.89	74.0	-31.11	Peak
7439.97	3.02	36.20	35.20	36.34	40.36	54.0	-13.64	AV
9920.00	---	---	---	---	---	---	---	---
12400.00	---	---	---	---	---	---	---	---
14880.00	---	---	---	---	---	---	---	---
17360.00	---	---	---	---	---	---	---	---
19840.00	---	---	---	---	---	---	---	---
22320.00	---	---	---	---	---	---	---	---
24800.00	---	---	---	---	---	---	---	---

NOTE: “---” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

5. Occupied Bandwidth


5.1. Requirements (15.249):

The field strength of any emissions appearing outside the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 50 dB below the level of the carrier or to the general limits of 15.249.

5.2. Test Procedure

The EUT is placed on a turn table which is 0.8 meter high above the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

5.3. Test Configuration:




5.4. Test Results


Pass.

Please refer the following plot.

FCC ID: V8VCNE6104RS




Bandedges-L




Band edges-L-AV

FCC ID: V8VCNE6104RS



Bandedges-H



Band edges-H-AV