

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594 Report No.: SZEM141000569801

Email: ee.shenzhen@sgs.com Page: 1 of 96

FCC REPORT

Application No.: SZEM1410005698CR

Applicant: SKYPINE ELECTRONICS (SHEN ZHEN) CO., LTD. **Manufacturer:** SKYPINE ELECTRONICS (SHEN ZHEN) CO., LTD.

Product Name: All In One DVD Player

Model No.(EUT): NX405 Trade mark: Clarion

FCC ID: V8VCNE8243CCL

Standards: 47 CFR Part 15, Subpart C (2013)

Date of Receipt: 2014-10-20

Date of Test: 2014-10-30 to 2014-10-31

Date of Issue: 2014-11-07

Test Result: PASS *

Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: SZEM141000569801

Page: 2 of 96

2 Version

Revision Record						
Version Chapter Date Modifier Remark						
00		2014-11-07		Original		

Authorized for issue by:		
Tested By	John Hong	2014-10-31
	(Jim Huang) /Project Engineer	Date
Prepared By	Lintin Lu	2014-11-07
	(Linlin Lv) /Clerk	Date
Checked By	Orven Zhou	2014-12-09
	(Owen Zhou) /Reviewer	Date



Report No.: SZEM141000569801

Page: 3 of 96

3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 (2009)	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 (2009)	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(1)	ANSI C63.10 (2009)	PASS
20dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2009)	PASS
Carrier Frequencies Separation	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2009)	PASS
Hopping Channel Number	47 CFR Part 15, Subpart C Section 15.247 (b)	ANSI C63.10 (2009)	PASS
Dwell Time	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2009)	PASS
Pseudorandom Frequency Hopping Sequence	47 CFR Part 15, Subpart C Section 15.247(b)(4)&TCB Exclusion List(7 July 2002)	ANSI C63.10 (2009)	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2009)	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2009)	PASS
Radiated Spurious emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2009)	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2009)	PASS



Report No.: SZEM141000569801

Page: 4 of 96

4 Contents

			Page
1	CC	OVER PAGE	1
2	VF	ERSION	2
		EST SUMMARY	
3			
4	CC	ONTENTS	4
5	GF	ENERAL INFORMATION	5
	5.1	CLIENT INFORMATION	5
	5.2	GENERAL DESCRIPTION OF EUT.	
	5.3	TEST ENVIRONMENT	
	5.4	DESCRIPTION OF SUPPORT UNITS	7
	5.5	TEST LOCATION	
	5.6	TEST FACILITY	
	5.7	DEVIATION FROM STANDARDS	
	5.8	ABNORMALITIES FROM STANDARD CONDITIONS	
	5.9	OTHER INFORMATION REQUESTED BY THE CUSTOMER	
6	EC	QUIPMENT LIST	9
7	TE	EST RESULTS AND MEASUREMENT DATA	11
	7.1	Antenna Requirement	11
	7.2	CONDUCTED PEAK OUTPUT POWER	12
	7.3	20dB Occupy Bandwidth	
	7.4	CARRIER FREQUENCIES SEPARATION	
	7.5	HOPPING CHANNEL NUMBER	
	7.6	DWELL TIME	
	7.7 7.8	BAND-EDGE FOR RF CONDUCTED EMISSIONS	
	7.6 7.9	PSEUDORANDOM FREQUENCY HOPPING SEQUENCE	
	7.3 7.10		
		10.1 Radiated Emission below 1GHz	
		10.2 Transmitter Emission above 1GHz	
	7.11	RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	87-96



Report No.: SZEM141000569801

Page: 5 of 96

5 General Information

5.1 Client Information

Applicant:	SKYPINE ELECTRONICS (SHEN ZHEN) CO., LTD.
Address of Applicant:	A1 Building, No.6 Xinxing Industrial Park, Xinhe Village, Fuyong Town, Baoan, Shenzhen City
Manufacturer:	SKYPINE ELECTRONICS (SHEN ZHEN) CO., LTD.
Address of Manufacturer:	A1 Building, No.6 Xinxing Industrial Park, Xinhe Village, Fuyong Town, Baoan, Shenzhen City

5.2 General Description of EUT

Product Name:	All In One DVD Player	
Model No.:	NX405	
Trade Mark:	Clarion	
Operation Frequency:	2402MHz~2480MHz	
Bluetooth Version:	V4.0	
	This test report is for classic mode	
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)	
Modulation Type:	GFSK, π/4DQPSK, 8DPSK	
Number of Channel:	79	
Hopping Channel Type:	Adaptive Frequency Hopping systems	
Sample Type:	fixed production	
Test Power Grade:	255 , (manufacturer declare)	
Test Software of EUT:	CSR BlueSuite (manufacturer declare)	
Antenna Type:	Integral	
Antenna Gain:	-3.3dBi	
EUT Power Supply:	DC9.5V-17.5V	
	Pre-test the EUT in DC 9.5V, DC12V and DC17.5V, and the compliance test was performed at DC 12V as the worst case was found.	
DC Cable:	40cm (Unshielded)	



Report No.: SZEM141000569801

Page: 6 of 96

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel	2402MHz
The Middle channel	2441MHz
The Highest channel	2480MHz



Report No.: SZEM141000569801

Page: 7 of 96

5.3 Test Environment

Operating Environment	Operating Environment:		
Temperature:	24.0 °C		
Humidity:	52% RH		
Atmospheric Pressure:	1005mbar		

5.4 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.
PC	lenovo	B490

PC (model: B490) and test broad is used only on configure the engineering mode and not used during actual test.

5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.



Report No.: SZEM141000569801

Page: 8 of 96

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

VCCI

The 10m Semi-anechoic chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

Industry Canada (IC)

Two 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1 & 4620C-2.

5.7 Deviation from Standards

None.

5.8 Abnormalities from Standard Conditions

None.

5.9 Other Information Requested by the Customer

None.



Report No.: SZEM141000569801

Page: 9 of 96

6 Equipment List

	RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)	
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2015-06-10	
2	EMI Test Receiver	Agilent Technologies	N9038A	SEL0312	2015-09-16	
3	EMI Test software	AUDIX	E3	SEL0050	N/A	
4	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2015-10-24	
5	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2015-10-24	
6	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2015-10-24	
7	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2015-05-16	
8	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2015-10-24	
9	Coaxial cable	SGS	N/A	SEL0027	2015-05-29	
10	Coaxial cable	SGS	N/A	SEL0189	2015-05-29	
11	Coaxial cable	SGS	N/A	SEL0121	2015-05-29	
12	Coaxial cable	SGS	N/A	SEL0178	2015-05-29	
13	Band filter	Amindeon	82346	SEL0094	2015-05-16	
14	Barometer	Chang Chun	DYM3	SEL0088	2015-05-16	
15	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-24	
16	Humidity/ Temperature Indicator	Shanhai Qixiang	ZJ1-2B	SEL0103	2015-10-24	
17	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2015-05-16	
18	Signal Generator	Rohde & Schwarz	SMY01	SEL0155	2015-10-24	
19	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2015-06-04	



Report No.: SZEM141000569801

Page: 10 of 96

	RF connected test				
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-24
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2015-10-24
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2015-10-24
4	Coaxial cable	SGS	N/A	SEL0178	2015-05-29
5	Coaxial cable	SGS	N/A	SEL0179	2015-05-29
6	Barometer	ChangChun	DYM3	SEL0088	2015-05-16
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2015-05-16
8	Band filter	amideon	82346	SEL0094	2015-05-16
9	POWER METER	R&S	NRVS	SEL0144	2015-10-24
10	Attenuator	Beijin feihang taida	TST-2-6dB	SEL0205	2015-05-16
11	Power Divider(splitter)	Agilent Technologies	11636B	SEL0130	2015-10-24

Note: The calibration interval is one year, all the instruments are valid.



Report No.: SZEM141000569801

Page: 11 of 96

7 Test results and Measurement Data

7.1 Antenna Requirement

Standard requirement: 47 CFR Part 15C Section 15.203 /247(c)


15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:




The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is -3.3dBi.



Report No.: SZEM141000569801

Page: 12 of 96

7.2 Conducted Peak Output Power





Report No.: SZEM141000569801

Page: 13 of 96

Measurement Data

Micasurement Butta				
	GFSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result	
Lowest	2.29	30.00	Pass	
Middle	3.11	30.00	Pass	
Highest	3.36	30.00	Pass	
	π/4DQPSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result	
Lowest	-0.04	30.00	Pass	
Middle	1.49	30.00	Pass	
Highest	2.26	30.00	Pass	
	8DPSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result	
Lowest	0.65	30.00	Pass	
Middle	1.91	30.00	Pass	
Highest	2.48	30.00	Pass	




Report No.: SZEM141000569801


Page: 14 of 96

Test plot as follows:

Test mode: GFSK Test channel: Lowest



Test mode:	GFSK	Test channel:	Middle
TOOL HIDGO.	ai oit	1 Cot orial illor.	Miladio







Report No.: SZEM141000569801

Page: 15 of 96

Test mode: GFSK Test channel: Highest











Report No.: SZEM141000569801

Page: 16 of 96

Test mode: π/4DQPSK Test channel: Middle



Test mode:	π/4DQPSK	Test channel:	Highest
------------	----------	---------------	---------







Report No.: SZEM141000569801

Page: 17 of 96

Test mode: 8DPSK Test channel: Lowest










Report No.: SZEM141000569801

Page: 18 of 96

Test mode: 8DPSK Test channel: Highest




[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM141000569801

Page: 19 of 96

7.3 20dB Occupy Bandwidth



Measurement Data

Tost shannel	20dB Occupy Bandwidth (kHz)		
Test channel	GFSK	π/4DQPSK	8DPSK
Lowest	839.429487179	1229.967949	1225.961538
Middle	839.429487179	1229.967949	1241.987179
Highest	897.435897436	1233.974359	1245.993590




Report No.: SZEM141000569801


Page: 20 of 96

Test plot as follows:

Test mode: GFSK Test channel: Lowest











Report No.: SZEM141000569801

Page: 21 of 96

Test mode: GFSK Test channel: Highest



Test mode: π/4DQPSK Test channel: Lowest









Report No.: SZEM141000569801

Page: 22 of 96

Test mode: π/4DQPSK Test channel: Middle










Report No.: SZEM141000569801

Page: 23 of 96

Test mode: 8DPSK Test channel: Lowest










Report No.: SZEM141000569801

Page: 24 of 96

Test mode: 8DPSK Test channel: Highest






Report No.: SZEM141000569801

Page: 25 of 96

7.4 Carrier Frequencies Separation





Report No.: SZEM141000569801

Page: 26 of 96

Measurement Data

GFSK mode				
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result	
Lowest	1002	≥598	Pass	
Middle	1002	≥598	Pass	
Highest	1006	≥598	Pass	
	π/4DQPSK m	node		
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result	
Lowest	1002	≥823	Pass	
Middle	1002	≥823	Pass	
Highest	1002	≥823	Pass	
	8DPSK mode			
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result	
Lowest	1002	≥831	Pass	
Middle	1006	≥831	Pass	
Highest	1002	≥831	Pass	

Note: According to section 5.4,

Mode	20dB bandwidth (kHz)	Limit (kHz)
	(worse case)	(Carrier Frequencies Separation)
GFSK	897.435897436	598
π/4DQPSK	1233.974359	823
8DPSK	1245.993590	831




Report No.: SZEM141000569801


Page: 27 of 96

Test plot as follows:

Test mode: GFSK Test channel: Lowest











Report No.: SZEM141000569801

Page: 28 of 96

Test mode: GFSK Test channel: Highest











Report No.: SZEM141000569801

Page: 29 of 96

Test mode: π/4DQPSK Test channel: Middle











Report No.: SZEM141000569801

Page: 30 of 96

Test mode: 8DPSK Test channel: Lowest










Report No.: SZEM141000569801

Page: 31 of 96

Test mode: 8DPSK Test channel: Highest








Report No.: SZEM141000569801

Page: 32 of 96

7.5 Hopping Channel Number



Measurement Data


Mode	Hopping channel numbers	Limit
GFSK	79	≥15
π/4DQPSK	79	≥15
8DPSK	79	≥15




Report No.: SZEM141000569801

Page: 33 of 96

Test plot as follows










Report No.: SZEM141000569801

Page: 34 of 96

Test mode: 8DPSK






Report No.: SZEM141000569801

Page: 35 of 96

7.6 Dwell Time





Report No.: SZEM141000569801

Page: 36 of 96

Measurement Data

Mode	Packet	Dwell time (second)	Limit (second)
GFSK	DH1	0.12704	0.4
	DH3	0.26480	0.4
	DH5	0.32131	0.4
π/4DQPSK	2-DH1	0.13088	0.4
	2-DH3	0.26672	0.4
	2-DH5	0.27440	0.4
8DPSK	3-DH1	0.13088	0.4
	3-DH3	0.26544	0.4
	3-DH5	0.32175	0.4

Remark:

The test period: T= 0.4 Second/Channel x 79 Channel = 31.6 s

On (ms)*total number=dwell time (ms)

The lowest channel (2402MHz), as below:

DH1 time slot=0.397 (ms)*total number=127.04 (ms)

DH3 time slot=1.655 (ms)* total number = 264.80 (ms)

DH5 time slot=2.921 (ms)* total number =321.31 (ms)

2-DH1 time slot=0.409 (ms)*total number=130.88 (ms)

2-DH3 time slot=1.667 (ms)* total number =266.72 (ms)

2-DH5 time slot=1.715 (ms)* total number = 274.40 (ms)

3-DH1 time slot=0.409 (ms)*total number=130.88 (ms)

3-DH3 time slot=1.659 (ms)* total number = 265.44 (ms)


3-DH5 time slot=2.925 (ms)* total number =321.75 (ms)





Report No.: SZEM141000569801

Page: 37 of 96

Test plot as follows:











Report No.: SZEM141000569801

Page: 38 of 96












Report No.: SZEM141000569801

Page: 39 of 96











Report No.: SZEM141000569801

Page: 40 of 96











Report No.: SZEM141000569801

Page: 41 of 96













Report No.: SZEM141000569801

Page: 42 of 96












Report No.: SZEM141000569801

Page: 43 of 96











Report No.: SZEM141000569801

Page: 44 of 96











Report No.: SZEM141000569801

Page: 45 of 96







Report No.: SZEM141000569801

Page: 46 of 96

7.7 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2009
Test Setup:	Spectrum Analyzer Non-Conducted Table Ground Reference Plane Remark: Offset the High-Frequency cable loss 0.5dB in the spectrum analyzer.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worse case of GFSK modulation type, 2-DH5 of data type is worse case of $\pi/4DQPSK$ modulation type, 3-DH5 of data type is worse case of 8DPSK modulation type.
Instruments Used:	Refer to section 6 for details
Test Results:	Pass





Report No.: SZEM141000569801

Page: 47 of 96

Test plot as follows:

Test mode: GFSK Test channel: Lowest









Report No.: SZEM141000569801

Page: 48 of 96

Test mode: GFSK Test channel: Highest









Report No.: SZEM141000569801

Page: 49 of 96

Test mode: π/4DQPSK Test channel: Lowest









Report No.: SZEM141000569801

Page: 50 of 96

Test mode: π/4DQPSK Test channel: Highest









Report No.: SZEM141000569801

Page: 51 of 96

Test mode: 8DPSK Test channel: Lowest











Report No.: SZEM141000569801

Page: 52 of 96

Test mode: 8DPSK Test channel: Highest







Report No.: SZEM141000569801

Page: 53 of 96

7.8 Spurious RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2009
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane
	Remark: Offset the High-Frequency cable loss 0.5dB in the spectrum analyzer.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worse case of GFSK modulation type, 2-DH5 of data type is worse case of $\pi/4DQPSK$ modulation type, 3-DH5 of data type is worse case of 8DPSK modulation type.
Instruments Used:	Refer to section 6 for details
Test Results:	Pass




Report No.: SZEM141000569801

Page: 54 of 96

Test plot as follows:

Test mode: GFSK Test channel: Lowest



"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."


Start 1 GHz



Report No.: SZEM141000569801

Stop 5 GHz

Page: 55 of 96



100 MHz/


Start 4 GHz

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM141000569801

Page: 56 of 96











Report No.: SZEM141000569801

Page: 57 of 96









Report No.: SZEM141000569801

Page: 58 of 96










Report No.: SZEM141000569801

Page: 59 of 96











Report No.: SZEM141000569801

Page: 60 of 96









Report No.: SZEM141000569801

Page: 61 of 96











Report No.: SZEM141000569801

Page: 62 of 96










Report No.: SZEM141000569801

Stop 3 GHz

Page: 63 of 96



100 MHz/


Start 2 GHz



Report No.: SZEM141000569801

Stop 8 GHz

Page: 64 of 96



"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms.e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

100 MHz/


Start 7 GHz




Report No.: SZEM141000569801

Page: 65 of 96

Test mode: π/4DQPSK Test channel: Middle









Report No.: SZEM141000569801

Page: 66 of 96









Report No.: SZEM141000569801

Page: 67 of 96











Report No.: SZEM141000569801

Page: 68 of 96









Report No.: SZEM141000569801

Page: 69 of 96








Report No.: SZEM141000569801

Page: 70 of 96


Test mode: 8DPSK Test channel: Lowest






Report No.: SZEM141000569801

Page: 71 of 96












Report No.: SZEM141000569801

Page: 72 of 96











Report No.: SZEM141000569801

Page: 73 of 96









Report No.: SZEM141000569801

Page: 74 of 96









Report No.: SZEM141000569801

Page: 75 of 96

Test mode: 8DPSK Test channel: Highest









Report No.: SZEM141000569801

Page: 76 of 96








Report No.: SZEM141000569801

Page: 77 of 96



Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report.



Report No.: SZEM141000569801

Page: 78 of 96

7.9 Pseudorandom Frequency Hopping Sequence

Test Requirement: 47 CFR Part 15C Section 15.247 (a)(1) requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.


The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1)

According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage


outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- · Number of shift register stages: 9
- Length of pseudo-random sequence: $2^9 1 = 511$ bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.



Report No.: SZEM141000569801

Page: 79 of 96

Compliance for section 15.247(g)

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h)

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.



Report No.: SZEM141000569801

Page: 80 of 96

7.10 Radiated Spurious Emission


Test Requirement:	47 CFR Part 15C Section	on 1	5.209 and 15.	205				
Test Method:	ANSI C63.10: 2009							
Test Site:	Measurement Distance	: 3n	n (Semi-Anech	oic Cham	ber)			
Receiver Setup:	Frequency		Detector	RBW	VBW	Remark		
	0.009MHz-0.090MH	Z	Peak	10kHz	z 30kHz	Peak		
	0.009MHz-0.090MH	Z	Average	10kHz	z 30kHz	Average		
	0.090MHz-0.110MH	Z	Quasi-peak	10kHz	z 30kHz	Quasi-peak		
	0.110MHz-0.490MH	Z	Peak	10kHz	30kHz	Peak		
	0.110MHz-0.490MH	Z	Average	10kHz	30kHz	Average		
	0.490MHz -30MHz		Quasi-peak	10kHz	z 30kHz	Quasi-peak		
	30MHz-1GHz		Quasi-peak	100 kH	lz 300kHz	Quasi-peak		
	Above 1GHz	Abovo 1GHz		1MHz	3MHz	Peak		
	Above IGHZ		Peak	1MHz	10Hz	Average		
Limit:	Frequency	Field strengt		Limit (dBuV/m)	Remark	Measureme distance (n		
	0.009MHz-0.490MHz	2	400/F(kHz)	-	-	300		
	0.490MHz-1.705MHz	24	1000/F(kHz)	-	-	30		
	1.705MHz-30MHz		30	-	-	30		
	30MHz-88MHz		100	40.0	Quasi-peak	3		
	88MHz-216MHz		150	43.5	Quasi-peak	3		
	216MHz-960MHz		200	46.0	Quasi-peak	3		
	960MHz-1GHz		500	54.0	Quasi-peak	3		
	Above 1GHz		500	54.0	Average	3		
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio from emissions is 20dB above the maximum permitted average emissions applicable to the equipment under test. This peak limit applies to peak emission level radiated by the device.							



Report No.: SZEM141000569801

Page: 81 of 96

Test Setup:






Figure 1. Below 30MHz

Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average



Report No.: SZEM141000569801

Page: 82 of 96

	method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel (2402MHz),the middle channel (2441MHz),the Highest channel (2480MHz) h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case. i. Repeat above procedures until all frequencies measured was complete.				
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type Transmitting mode				
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type at highest channel. Only the worst case is recorded in the report.				
Instruments Used:	Refer to section 6 for details				
Test Results:	Pass				




Report No.: SZEM141000569801

Page: 83 of 96

7.10.1 Radiated Emission below 1GHz

30MHz~1GHz (QP)		
Test mode:	Transmitting mode	Vertical





Condition: ICES-003 TABLE 5 3m 3142C Vertical

eut : 5697CR mode : TX mode : Bluetooth

Cable Ant Preamp Read Limit Over

	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	54.26	0.80	8.06	27.28	42.29	23.87	40.00	-16.13
2	136.94	1.29	7.98	26.97	45.71	28.01	43.50	-15.49
3	163.76	1.34	9.56	26.84	44.17	28.23	43.50	-15.27
4	218.31	1.51	11.15	26.63	46.29	32.32	46.00	-13.68
5	230.10	1.57	11.66	26.59	44.76	31.40	46.00	-14.60
6	490.74	2.57	17.80	27.66	42.94	35.65	46.00	-10.35




Report No.: SZEM141000569801

Page: 84 of 96

Test mode: Transmitting mode Horizontal

Data: 60



Condition: ICES-003 TABLE 5 3m 3142C Horizontal

eut : 5697CR mode : TX mode : Bluetooth

1

2

3

4

5

Cable Ant Preamp Limit 0ver Read Freq Loss Factor Factor Level Level Line Limit dBuV dBuV/m dBuV/m MHz dB dB/m dB 81.50 1.10 7.86 27.23 39.70 21.43 40.00 -18.57 27.14 22.10 109.41 1.23 8.63 39.38 43.50 -21.40 211.53 10.82 26.66 47.41 33.04 43.50 -10.46 1.47 272.28 12.75 1.78 26.47 44.13 32.19 46.00 -13.81 350.48 2.06 13.94 26.79 44.49 33.70 46.00 -12.30 437.12 2.36 16.65 27.35 44.65 36.31 46.00 -9.69



Report No.: SZEM141000569801

Page: 85 of 96

7.10.2 Transmitter Emission above 1GHz

Worse case	mode:	GFSK(DH5	i) Test	channel:	el: Lowest		ırk:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
1589.289	2.68	29.13	38.38	56.22	49.65	74	-24.35	Vertical
3728.625	4.05	33.10	38.84	51.78	50.09	74	-23.91	Vertical
4804.000	4.29	34.70	39.24	51.11	50.86	74	-23.14	Vertical
7206.000	5.30	35.63	39.07	49.36	51.22	74	-22.78	Vertical
9608.000	6.52	37.33	37.93	46.08	52.00	74	-22.00	Vertical
11633.540	7.43	38.33	38.53	46.27	53.50	74	-20.50	Vertical
1589.289	2.68	29.13	38.38	54.83	48.26	74	-25.74	Horizontal
3728.625	4.05	33.10	38.84	51.78	50.09	74	-23.91	Horizontal
4804.000	4.29	34.70	39.24	51.11	50.86	74	-23.14	Horizontal
7206.000	5.30	35.63	39.07	47.42	49.28	74	-24.72	Horizontal
9608.000	6.52	37.33	37.93	46.08	52.00	74	-22.00	Horizontal
11933.470	7.25	38.63	38.67	46.15	53.36	74	-20.64	Horizontal

Worse case	mode:	GFSK(DH5)) Tes	t channel:	Middle	Ren	nark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
1589.289	2.68	29.13	38.38	54.35	47.78	74	-26.22	Vertical
3709.691	4.06	33.08	38.83	48.95	47.26	74	-26.74	Vertical
4882.000	4.36	34.78	39.26	47.38	47.26	74	-26.74	Vertical
7323.000	5.20	35.50	39.06	48.14	49.78	74	-24.22	Vertical
9764.000	6.49	37.81	37.84	44.65	51.11	74	-22.89	Vertical
12178.980	6.92	38.93	38.85	46.47	53.47	74	-20.53	Vertical
1589.289	2.68	29.13	38.38	54.35	47.78	74	-26.22	Horizontal
3579.815	4.13	32.98	38.78	48.68	47.01	74	-26.99	Horizontal
4882.000	4.36	34.78	39.26	50.49	50.37	74	-23.63	Horizontal
7323.000	5.20	35.50	39.06	48.33	49.97	74	-24.03	Horizontal
9764.000	6.49	37.81	37.84	45.48	51.94	74	-22.06	Horizontal
11872.880	7.29	38.57	38.64	45.93	53.15	74	-20.85	Horizontal



Report No.: SZEM141000569801

Page: 86 of 96

Worse case	mode:	GFSK(DH5)	Tes	t channel:	Highest	Ren	nark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
1597.401	2.68	29.18	38.39	48.91	42.38	74	-31.62	Vertical
3616.451	4.15	33.01	38.79	48.06	46.43	74	-27.57	Vertical
4960.000	4.43	34.86	39.29	48.82	48.82	74	-25.18	Vertical
7440.000	5.15	35.43	39.05	47.33	48.86	74	-25.14	Vertical
9920.000	6.83	38.27	37.75	43.77	51.12	74	-22.88	Vertical
11994.380	7.21	38.69	38.70	45.80	53.00	74	-21.00	Vertical
1589.289	2.68	29.13	38.38	53.68	47.11	74	-26.89	Horizontal
3634.910	4.14	33.03	38.80	48.24	46.61	74	-27.39	Horizontal
4960.000	4.43	34.86	39.29	49.77	49.77	74	-24.23	Horizontal
7440.000	5.15	35.43	39.05	48.63	50.16	74	-23.84	Horizontal
9920.000	6.83	38.27	37.75	44.29	51.64	74	-22.36	Horizontal
11457.210	7.74	38.19	38.45	46.46	53.94	74	-20.06	Horizontal

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
 - Final Test Level = Receiver Reading + Antenna Factor + Cable Factor Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.




Report No.: SZEM141000569801

Page: 87 of 96

7.11 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15	47 CFR Part 15C Section 15.209 and 15.205							
Test Method:	ANSI C63.10: 2009	ANSI C63.10: 2009							
Test Site:	Measurement Distance: 3m	Measurement Distance: 3m (Semi-Anechoic Chamber)							
Limit:	Frequency	Limit (dBuV/m @3m)	Remark						
	30MHz-88MHz	40.0	Quasi-peak Value						
	88MHz-216MHz	43.5	Quasi-peak Value						
	216MHz-960MHz	46.0	Quasi-peak Value						
	960MHz-1GHz	54.0	Quasi-peak Value						
	Above 1GHz	54.0	Average Value						
	Above IGHZ	74.0	Peak Value						
Test Setup:									






Figure 1. 30MHz to 1GHz

Figure 2. Above 1 GHz



Report No.: SZEM141000569801

Page: 88 of 96

Test Procedure:	 a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel g. Test the EUT in the lowest channel, the Highest channel h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case. i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type Transmitting mode
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worse case of GFSK
Tilla Tost Wode.	modulation type. Only the worst case is recorded in the report.
la star car o de la la calca	
Instruments Used:	Refer to section 6 for details
Test Results:	Pass




Report No.: SZEM141000569801

Page: 89 of 96

Test plot as follows:

Worse case mode: GFSK (DH5) Test channel: Lowest Remark: Peak Vertical



Site : chamber

Condition: FCC PART C 247 PK 3m Vertical

Job No: : 5698CR

1 2

Mode: : 2402 BT Band edge

		Cable	Ant	Preamp	Read		Limit	0∨er
	Freq	Loss	Factor	Factor	Le∨el	Le∨el	Line	Limit
_								
	MHz	dB	dB/m	dB	dBu∀	dBuV/m	dBuV/m	dB
	2390.00	3.36	32.35	38.46	45.97	43.22	74.00	-30.78
pp	2402.29	3.37	32.41	38.46	85.98	83.30	74.00	9.30


[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM141000569801

Page: 90 of 96

Worse case mode: GFSK (DH5) Test channel: Lowest Remark: Peak Horizontal



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal

Job No: : 5698CR

Mode: : 2402 BT Band edge


Ant Preamp Read Limit 0ver Loss Factor Factor Freq Level Level Line limit MHz dΒ dB/m dΒ dBuV dBuV/m dBuV/m 2390.00 3.36 32.35 38.46 43.72 40.97 74.00 -33.03 2402.29 3.37 32.41 38.46 83.58 80.90 74.00



Report No.: SZEM141000569801

91 of 96 Page:

GFSK (DH5) Test channel: Remark: Vertical Worse case mode: Lowest Average



Site : chamber

Condition: FCC PART C 247 AV 3m Vertical

Job No: : 5698CR

Mode: : 2402 BT Band edge

	Freq			Preamp Factor				
-	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 2 pp	2390.00 2402.19							






Report No.: SZEM141000569801

Page: 92 of 96

Worse case mode: GFSK (DH5) Test channel: Lowest Remark: Average Horizontal





Site : chamber

Condition: FCC PART C 247 AV 3m Horizontal

Job No: : 5698CR

Mode: : 2402 BT Band edge

		Cable	Ant	Preamp	Read		Limit	0∨er
	Freq	Loss	Factor	Factor	Le∨el	Le∨el	Line	Limit
_								
	MHz	dB	dB/m	dB	dBu∀	dBuV/m	dBuV/m	dB
1	2390.00	3.36	32.35	38.46	30.47	27.72	54.00	-26.28
2 pp	2402.29	3.37	32.41	38.46	71.36	68.68	54.00	14.68




Report No.: SZEM141000569801

93 of 96 Page:

GFSK (DH5) Test channel: Highest Peak Worse case mode: Remark: Vertical





Frequency (MHz)

: chamber

Condition: FCC PART C 247 PK 3m Vertical

Job No: : 5698CR

Mode: : 2480 BT Band edge

	Freq			Preamp Factor				
-	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
	2480.06 2483.50							

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Report No.: SZEM141000569801

Page: 94 of 96

Worse case mode: GFSK (DH5) Test channel: Highest Remark: Peak Horizontal





Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal

Job No: : 5698CR

Mode: : 2480 BT Band edge


		Cable	Ant	Preamp	Read		Limit	0∨er
	Freq	Loss	Factor	Factor	Le∨el	Level	Line	Limit
	MHz	dB	dB/m	dB	dBu∀	dBuV/m	dBuV/m	dB
1 pp	2480.20	3.46	32.44	38.47	88.96	86.39	74.00	12.39
2	2483.50	3.47	32.44	38.47	43.12	40.56	74.00	-33.44



Report No.: SZEM141000569801

95 of 96 Page:

GFSK (DH5) Test channel: Highest Worse case mode: Remark: Average Vertical



: chamber

Condition: FCC PART C 247 AV 3m Vertical

Job No: : 5698CR

Mode: : 2480 BT Band edge

			Ant Preamp Factor Factor					
_	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
	2480.10 2483.50							

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Report No.: SZEM141000569801

Page: 96 of 96

Worse case mode: GFSK (DH5) Test channel: Highest Remark: Average Horizontal





Site : chamber

Condition: FCC PART C 247 AV 3m Horizontal

Job No: : 5698CR

Mode: : 2480 BT Band edge

	Freq			Preamp Factor				
-	MHz	dB	dB/m	dB	dBu∀	dBuV/m	dBuV/m	dB
1 pp 2	2480.15 2483.50							

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."