Section 15.247(i) – Radio Frequency Hazard Information

As per Section 15.247 (b) (4) spread spectrum transmitters operating in the 2400 - 2483.5 MHz band are required to be operated in a manner that ensures that the public is not exposed to RF energy levels in accordance with CFR 47, Section 1.1307(b)(1).

The device when in operation is fixed and a safe distance could be maintained when events are undertaken.

The device contains 2 transmitters that operate at similar power levels.

In accordance with Section 1.1310 the Maximum Permissible Exposure (MPE) limits for the General Population / Uncontrolled Exposure of 1 mW/cm² has been applied.

The maximum distance from the antenna at which the MPE is met or exceeded is calculated from the equation relating field strength in V/m, transmit power in watts, transmit antenna gain and separation distance in metres:

E, V/m =
$$(\sqrt{(30 * P * G)}) / d$$

Power density, mW/cm² = E2/3770
E for MPE: 1 = E²/3770

 $E = \sqrt{1*3770}$ E = 61.4 V/m

The highest radiated power has been measured to be +19.6 dBm or 0.091 watts EiRP when operating on 2440.0 MHz

Therefore:

$$E = \sqrt{(30 * P * G) / d}$$

$$d = \sqrt{(30 * P * G) / E}$$

$$d = \sqrt{(30 * 0.09) / 61.4}$$

$$d = 0.027 \text{ m or } 2.7 \text{ cm}$$

Result: Complies if a minimum safe distance of 20 cm is specified in the set up instructions for this system.

Page 26 of 39