



TEST REPORT

Report No. : AL030289-001 Date : 2009-08-26

Application No. : LL225756(5)

Applicant : TecniToys Juguetes, S.A.
Avda. Diagonal, 545 08029 BARCELONA Spain.

Manufacturer : Dongguan L C Technology Co., Ltd.
Qiao Li Management District, Chang Huang Road,
Changping Town, Dongguan City,
Guang Dong Province, China

Sample Description : One(1) submitted sample(s) stated to be My First Driving School
of Model No. 1800/18000
Radio Frequency : 27.145MHz Transmitter

Rating : 3 x 1.5V AAA size batteries
No. of submitted sample : Two (2) set(s)

Date Received : 2009-08-03.

Test Period : 2009-08-07 to 2009-08-13.


Test Requested : FCC Part 15 Certification.

Test Method : 47 CFR Part 15 (10-1-08 Edition)
ANSI C63.4 – 2003

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15
Subpart C.

For and on behalf of
CMA Industrial Development Foundation Limited

Authorized Signature : 
Mr. Wong Lap-pong, Andrew
Assistant Manager
Electrical Division

FCC ID: V9H18007T3B

Page 1 of 11



TEST REPORT

Report No. : AL030289-001

Date : 2009-08-26

Table of Contents

| | | |
|-----|--|----|
| 1 | General Information | 3 |
| 1.1 | General Description | 3 |
| 1.2 | Location of the test site | 4 |
| 1.3 | List of measuring equipment | 5 |
| 2 | Description of the radiated emission test | 6 |
| 2.1 | Test Procedure | 6 |
| 2.2 | Test Result | 6 |
| 2.3 | Radiated Emission Measurement Data | 7 |
| 3 | Description of the Line-conducted Test | 8 |
| 3.1 | Test Procedure | 8 |
| 3.2 | Test Result | 8 |
| 3.3 | Graph and Table of Conducted Emission Measurement Data | 8 |
| 4 | Photograph | 9 |
| 4.1 | Photographs of the Test Setup for Radiated Emission and Conducted Emission | 9 |
| 4.2 | Photographs of the External and Internal Configurations of the EUT | 9 |
| 5 | Supplementary document | 10 |
| 5.1 | Bandwidth | 10 |
| 5.2 | Duty cycle | 10 |
| 5.3 | Transmission time | 10 |
| 6 | Appendices | 11 |



TEST REPORT

Report No. : AL030289-001

Date : 2009-08-26

1 General Information

1.1 General Description

The equipment under test (EUT) is a transmitter for My First Driving School. It operates at 27.145MHz and the oscillation of radio control is generated by a crystal. The EUT is powered by 3 x 1.5V AAA size batteries. There are two buttons at the front of EUT. When it switched "ON" and pressed the button once, it will transmit a radio control signal to receiver.

The antenna is permanently attached in EUT and the radio output power is unable to adjust.

The brief circuit description is listed as follows:

- U1 and associated circuit act as encoder.
- U2, Q3 and associated circuit act as sound controller.
- X1, Q2 and associated circuit act as oscillator.
- Q1 and associated circuit act as amplifier.



**CMA Testing
and Certification
Laboratories**
廠商會檢定中心

TEST REPORT

Report No. : AL030289-001

Date : 2009-08-26

1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at:

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. A shielded room is located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

FCC ID: V9H18007T3B

Page 4 of 11

This document is issued subject to CMA Testing standard TERMS AND CONDITIONS, and shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



TEST REPORT

Report No. : AL030289-001

Date : 2009-08-26

1.3 List of measuring equipment

| Equipment | Manufacturer | Model No. | Serial No. | Calibration Due Date |
|-------------------|--------------|-----------|------------|----------------------|
| EMI Test Receiver | R&S | ESCI | 100152 | 2009 December 02 |
| Bilog Antenna | Schaffner | CBL6112B | 2718 | 2010 August 04 |
| Loop Antenna | EMCO | 6502 | 00056620 | 2009 October 18 |



TEST REPORT

Report No. : AL030289-001

Date : 2009-08-26

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

The device was rotated through three orthogonal axes to determine which attitude and configuration produce the highest emission during measurement.

2.2 Test Result

Peak Detector data was measured unless otherwise stated.

“#” means emissions appearing within the restricted bands shall follow the requirement of section 15.205.

The Frequencies from Fundamental up to that tenth harmonics were investigated, and emissions more 20dB below limited were not reported. Thus, those highest emissions were presented in next page (section 2.3).

It was found that the EUT meet the FCC requirement.



TEST REPORT

Report No. : AL030289-001

Date : 2009-08-26

2.3 Radiated Emission Measurement Data

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart C

| Frequency (MHz) | Polarity (H/V) | Reading at 3m (dBμV/m) | Antenna and Cable factor (dB) | Average Factor (dB) | Field Strength (dBμV/m) | Limit at 3m (dBμV/m) | Margin (dB) |
|--------------------|-------------------|------------------------------|-------------------------------------|---------------------------|-------------------------------|-------------------------|----------------|
| 27.145 | V | 62.3 | 6.1 | -24.1 | 44.3 | 80.0 | -35.7 |
| 54.290 | V | 21.7 | 8.6 | - | 30.3 | 40.0 | -9.7 |
| 81.436 | H | 14.6 | 7.8 | - | 22.4 | 40.0 | -17.6 |
| #108.581 | H | 7.5 | 11.2 | - | 18.7 | 43.5 | -24.8 |
| #135.726 | H | 7.2 | 12.6 | - | 19.8 | 43.5 | -23.7 |
| #162.845 | H | 9.1 | 11.0 | - | 20.1 | 43.5 | -23.4 |
| 190.015 | H | 12.0 | 9.9 | - | 21.9 | 43.5 | -21.6 |
| 217.162 | H | 12.6 | 10.3 | - | 22.9 | 46.0 | -23.1 |
| #244.305 | H | 12.7 | 10.3 | - | 23.0 | 46.0 | -23.0 |
| #271.454 | H | 8.4 | 14.1 | - | 22.5 | 46.0 | -23.5 |



TEST REPORT

Report No. : AL030289-001

Date : 2009-08-26

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable



TEST REPORT

Report No. : AL030289-001

Date : 2009-08-26

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conducted Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg.

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.



TEST REPORT

Report No. : AL030289-001

Date : 2009-08-26

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

| Document | Filename |
|-------------------------|-----------------|
| ID Label/Location | LabelSmp.jpg |
| Block Diagram | BlkDia.pdf |
| Schematic Diagram | Schem.pdf |
| PCB Layout | PCB.pdf |
| Part List | Partlist.pdf |
| Users Manual | UserMan.pdf |
| Operational Description | OpDes.pdf |

5.1 Bandwidth

The plot on saved in TestRpt2.pdf shows the fundamental emission is confined in the specified band. It also shows that the band edge met the 15.209 requirement at 26.9599 and 27.2801 MHz.

5.2 Duty cycle

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 46.92ms

Effective period of the cycle = (0.642 x 1)ms + (0.252 x 4)ms + (0.126 x 10)ms
= 2.91ms

Duty Cycle = 2.91/46.92
= 0.062

Therefore, the average factor is found by $20 \log_{10} 0.062 = -24.1 \text{ dB}$

5.3 Transmission time

Not Applicable



TEST REPORT

Report No. : AL030289-001

Date : 2009-08-26

6 Appendices

| | | | |
|------|--|---|-------|
| A1. | Photos of the set-up of Radiated Emissions | 1 | page |
| A2. | Photos of External Configurations | 1 | page |
| A3. | Photos of Internal Configurations | 1 | page |
| A4. | ID Label/Location | 1 | page |
| A5. | Bandwidth Plot | 1 | page |
| A6. | Average Factor | 3 | pages |
| A7. | Block Diagram | 1 | page |
| A8. | Schematics Diagram | 1 | page |
| A9. | PCB Layout | 3 | pages |
| A10. | Part List | 1 | page |
| A11. | User Manual | 2 | pages |
| A12. | Operation Description | 1 | page |

***** End of Report *****