

SAR TEST REPORT

FCC 47 CFR Part 2.1093 Industry Canada RSS-102

RF-Exposure evaluation of portable equipment

Testing Laboratory: Eurofins Product Service GmbH

Address: Storkower Str. 38c

15526 Reichenwalde

Germany

Accreditation:





A2LA Accredited Testing Laboratory, Certificate No.: 1983.01

FCC Filed Test Laboratory, Reg.-No.: 96970 IC OATS Filing assigned code: 3470A

Applicant's name: Sonetics Corporation

Address: 7340 SW Durham Road

OR 97224Portland

USA

Test specification:

Standard.....: FCC 47 CFR Part 2 §2.1093

FCC OET Bulletin 65 Supplement C 01-01

IEEE Std. 1528-2003 IEEE Std. 1528 - 2013 IC RSS-102 Issue 4 Safety Code 6 (2009)

Gaioty Godo 6 (2

Non-standard test method...... None

Test scope.....: complete Radio compliance test

Equipment under test (EUT):

Product description Communication Headsets

Model No. APX379
Additional Model(s) None
Brand Name(s) Sonetics

Hardware version APX379 Rev A (See Additional Information)

Firmware / Software version Revision A (See Additional Information)

Contains FCC-ID: V9N950325200V1 IC: 7895A-95032520

Test result Passed



Possible test case	verdic	ts:
--------------------	--------	-----

- neither assessed nor tested...... N/N

- required by standard but not appl. to test object: N/A

- required by standard but not tested N/T

- not requiredby standard for the test object...... N/R

- test object does meet the requirement P (Pass)

- test object does not meet the requirement...... F (Fail)

Testing:

Date of receipt of test item 2014-09-22

Date (s) of performance of tests 2014-10-29

Compiled by: Matthias Handrik

(Responsible for Test)

Approved by (+ signature)...... Christian Weber

Date of issue 2014-12-18

Total number of pages 67

General remarks:

The test results presented in this report relate only to the object tested.

The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.



Product Service

Additional comments:

Page 1 of 2



Subject: Hardware Software/Firmware Declaration Date: December 01, 2014

Model Number: APX379 DECT & Bluetooth Headset, Revision A

The APX379 Headset shares the same common hardware and software as represented in table A

Table A: Common and Un-common Communication Headset Ear	300 Seri	es Model I	Number
Muff Features	APX379	APX377	APX375
Convertible Design: Overhead and Underhelmet	х	х	х
Identical Materials and Headset Muff Design	Х	Х	Х
Waterproof Design	Х	Х	Х
Wired Aux Line In	Х	X	Х
Internal Sound Dosimeter	Х	X	Х
Stereo Listen Thru	Х	Х	Х
Automatic Noise Gate	Х	X	Х
Passive Noise Reduction	Х	Х	Х
Automatic Active Noise Reduction	Х	X	Х
Voice Prompts	Х	Х	Х
Wireless Bluetooth (Line in)	Х		Х
Wireless DECT (2 way radio)	Х	Х	

Sonetics Corporation hereby declares that the above referenced model, submitted to Eurofins for FCC and IC testing, has the following firmware and hardware installed.

PX379 DECT & Bluetooth Headset Revision A (No Headband PNN: 950-3257-00 Revision A)					
Item Reference	Part Number	Description	ď	BOM Version Revision	Firmware Radio Related?
10	490-4006-00	Firmware, GEN-3 BOOT LOADER	1	A	No
15	490-4016-00	Firmware, APX379, DECT, BT	1	A	Yes
20	490-4009-00	Firmware, BLUETOOTH CONFIG	1	A	Yes
25	490-4012-00	Firmware, RTX1040 RADIO RTX Release Ver 7.0	1	A	Yes
35	490-4015-00	Firmware, VOICEPROMPTS, PP, ENGLISH-	1	A	No
40	490-4017-00	Firmware, APX379, CONFIGURATION	1	A	No
5	121-4030-G1	PCBA, APX379, HS, MAIN BOARD	1	G	Hardware
0	121-4031-J1	PCBA,HS-7X,BATTERY BOARD	1	J	Hardware

The above is declares accurate and true as of 12 01, 2014. Sincerely,

Michael Heade

Michael Heade
Quality Assurance Engineer
Regulatory & Product Compliance Engineer
Sonetics Corporation
Phone: 800-833-4558 ext. 122
Direct: 503-608-3422
Email: michael.heade@sonelicscorp.com
www.sonelicscorp.com

7340 SW Durham Road. Portland, Oregon U.S.A. 97224 • 503/684-7080 • Fax 503/620-2943



Version History

Version	Issue Date	Remarks	Revisedby
01	2014-12-18	Initial Release	



REPORT INDEX

EQUIPMENT (TEST ITEM) DESCRIPTION	1
Equipment photos	8
Equipment setup photos	11
Reference Documents	12
Supporting Equipment Used During Testing	13
Supported standalone operating modes	14
Conducted Power Values	15
Supported concurrent (multi-transmitter) operating modes	16
Standalone Operatinal Mode Test Exclusion	17
Supported use cases	18
Radio Test Modes	19
Test Positions	20
Test Equipment Used During Testing	21
RESULT SUMMARY	22
DEFINITIONS	23
Controlled Exposure	23
Uncontrolled Exposure	23
Localized SAR	23
LOCALIZED SAR MEASUREMENT EQUIPMENT	24
Complete SAR DASY5 Measurement System	24
Robot Arm	26
Data Acquisition Electronics	26
Isotropic E-Field Probe ≤ 3 GHz	27
Isotropic E-Field Probe ≤ 6 GHz	28
Test phantom and positioner	29
System Validation Dipoles	30
SINGLE-BAND SAR MEASUREMENT	31
General measurement description	31
SAR measurement description	31
Reference lines and points for Handsets	32
Test positions relative to the Head	33
Test positions relative to the human body	34
Measurement Uncertainty	35
	Equipment photos Equipment setup photos Reference Documents Supporting Equipment Used During Testing Supported standalone operating modes Conducted Power Values Supported concurrent (multi-transmitter) operating modes Standalone Operatinal Mode Test Exclusion Supported use cases Radio Test Modes Test Positions Test Equipment Used During Testing RESULT SUMMARY DEFINITIONS Controlled Exposure Uncontrolled Exposure Localized SAR LOCALIZED SAR MEASUREMENT EQUIPMENT Complete SAR DASY5 Measurement System Robot Arm Data Acquisition Electronics Isotropic E-Field Probe ≤ 3 GHz Isotropic E-Field Probe ≤ 6 GHz Test phantom and positioner System Validation Dipoles SINGLE-BAND SAR MEASUREMENT General measurement description SAR measurement description Reference lines and points for Handsets Test positions relative to the Head Test positions relative to the human body



6	TES	CONDITIONS AND RESULTS	36
6.1	Test	Conditions and Results – Tissue Validation	36
6.2	Test	Conditions and Results – System Validation	38
6.3	Test	Conditions and Results – Standalone SAR Measurement	39
6.4	Test	Conditions and Results – Multi-transmitter SAR Result	40
ANN	IEX A	Calibration Documents	41
ANN	IEX B	System Validation Reports	66
ANN	IEX C	SAR Measurement Reports	67



1 Equipment (Test item) Description

Description	Communication	Headsets	
Model	APX379		
Additional Model(s)	None		
Brand Name(s)	Sonetics		
Serial number	None		
Hardware version	APX379 Rev A	(See Additional Information)	
Software / Firmware version	Revision A (See	Additional Information)	
Contains FCC-ID	V9N950325200	V1	
Contains IC	7895A-9503252	0	
Equipment type	End product		
Prototype or production unit	Identical Prototy	ре	
Device category	Headset		
Environment	General public		
Radio technologies	UPCS 1.9 GHz Bluetooth		
Operating frequency ranges	UPCS 1920 MHz - 1930 MHz Bluetooth 2400 MHz - 2483.5 MHz		
Modulations	GFSK		
	Туре	integrated	
Antenna 1 UPCS	Model	Batt PCBA	
Antenna i oros	Manufacturer	Sonetics	
	Gain	0 dBi	
	Туре	integrated	
Antenna 2 UPCS	Model	HS Main	
Antenna 2 01 00	Manufacturer	Sonetics	
	Gain	0 dBi	
	Туре	integrated	
Antenna Bluetooth	Model	W3008	
Antenna Bidetootii	Manufacturer	Pulse	
	Gain	2.2 dBi	
Power supply	V _{NOM}	3.7 VDC (Lithium Battery)	
	Model	YMC06-3U	
AC/DC-Adaptor	Vendor	Ji Ming	
AO/DO-Adaptol	Input	100-240 VAC 50/60Hz	
	Output	12 VDC	
Accessories	None		



1.3 Reference Documents

0			

KDB Publication 447498: Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Polices

KDB Publication 648474: SAR Evaluation Considerations for Handsets with Multiple Transmitters and Antennas

KDB Publication 648474: Review and Approval Policies for SAR Evaluation of Handsets with Multiple Transmitters and Antennas

KDB Publication 865664 : SAR measurement procedures for devices operating between 100 MHz to 6 GHz

KDB Publication 941225: SAR Measurement Procedures for 3G Devices

KDB Publication 941225: 3GPP R6 HSPA and R7 HSPA+ SAR Guidance

KDB Publication 941225: Recommended SAR Test Reduction Procedures for GSM/GPRS/EDGE

KDB Publication 941225: SAR Test Consideration for LTE Handsets and Data Modems

KDB Publication 447498 : SAR Measurement Procedures for USB Dongle Transmitters

KDB Publication 248227 : SAR Measurement Procedures for 802.11 a/b/g Transmitters

KDB Publication 450824 : SAR Probe Calibration and System Verification considerations for measurements from 150 MHz to 3 GHz



1.4 Supporting Equipment Used During Testing

Product Type*	Device	Manufacturer	Model No.	Comments		
AE	Companion device	Sonetics	SON150	Fix part		
AE : Auxiliary/Associated Equipment						



1.5 Supported standalone operating modes

Mode	Modulation	Frequency range	Duty cycle
UPCS	GFSK	1920 MHz - 1930 MHz	6.7 %
Bluetooth	GFSK	2400 MHz - 2483.5 MHz	78 %



1.6 Conducted Power Values

	UPCS					
Channel	Frequency	Peak (Burst) RMS Power [dBm]	Source-based time averaged Power [dBm]			
	[MHz]	GFSK	GFSK			
0	1928.448	20.42	8.68			
4	1921.536	20.51	8.77			

	Bluetooth					
Channel	Frequency	Peak (Burst) RMS Power [dBm]	Source-based time averaged Power [dBm]			
[MHz]		BR (GFSK) DH5	BR (GFSK) DH5			
0	2402	-0.80	<u>-1.91</u>			
39	2441	-1.90	-3.01			
78	2480	-3.40	-4.51			



1.7 Supported concurrent (multi-transmitter) operating modes

UPCS and Bluetooth can transmit at the same time.



1.8 Standalone Operatinal Mode Test Exclusion

According to KDB 447498 D01 v05r02 for standalone SAR evaluation the test exclusion power condition is given by

$$\frac{\max Power, mW}{test\ distance, mm} \cdot \sqrt{f_{GHz}} \leq 3.0$$

for test separation distance ≤ 50mm.

For Bluetooth max Power is: 0.64mW, test exclusion is $0.2 \le 3.0$.

Only UPCS were measured for SAR.



1.9 Supported use cases

Use case	Distance to human body	corresponding test configuration
EUT placed at human ear		
According OET KnowledgeBase Inquiry Confirmation, Tracking Number 670993	0 mm (worst case)	close proximity to the human ear



1.10 Radio Test Modes

Mode	Settings
UPCS	Mode = active DECT link Modulation = GFSK Duty cycle = 6.7% Power level = maximum Antenna = integrated
Bluetooth	Mode = DH5 Modulation = GFSK Duty cycle = 78% Power level = maximum Antenna = integrated



1.11 Test Positions

Position	Description
BACK-0MM	EUT earseals side directly touching the phantom.



1.12 Test Equipment Used During Testing

SAR Measurement								
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due			
Stäubli Robot	Stäubli	RX90B L	EF00271	functional test	functional test			
Stäubli Robot Controller	Stäubli	CS7MB	EF00272	functional test	functional test			
DASY 5 Measurement Server	Schmid& Partner		EF00273	functional test	functional test			
Control Pendant	Stäubli		EF00274	functional test	functional test			
Dell Computer	Schmid& Partner	Intel	EF00275	functional test	functional test			
Data Acquisition Electronics	Schmid& Partner	DAE3V1	EF00276	2014-09	2015-09			
Dosimetric E-Field Probe	Schmid& Partner	ET3DV6	EF00279	2014-09	2015-09			
Dosimetric E-Field Probe	Schmid& Partner	EX3DV4	EF00826	2014-09	2015-09			
System Validation Kit	Schmid& Partner	D300V3	EF00299	2012-09	2015-09			
System Validation Kit	Schmid& Partner	D450V3	EF00300	2012-09	2015-09			
System Validation Kit	Schmid& Partner	D900V2	EF00281	2012-09	2015-09			
System Validation Kit	Schmid& Partner	D1800V2	EF00282	2012-09	2015-09			
System Validation Kit	Schmid& Partner	D1900V2	EF00283	2012-09	2015-09			
System Validation Kit	Schmid& Partner	D2450V2	EF00284	2012-09	2015-09			
System Validation Kit	Schmid& Partner	D5GHZV2	EF00827	2012-11	2015-11			
Flat phantom	Schmid& Partner	V 4.4	EF00328	no calibration required	no calibration required			
Oval flat phantom	Schmid& Partner	ELI 4	EF00289	functional test	functional test			
Mounting Device	Schmid& Partner	V 3.1	EF00287	functional test	functional test			
Millivoltmeter	Rohde & Schwarz	URV 5	EF00126	2013-08	2016-08			
Power sensor	Rohde & Schwarz	NRV-Z2	EF00125	2013-04	2015-04			
RF signal generator	Rohde & Schwarz	SMP 02	EF00165	2013-05	2015-05			
Insertion unit	Rohde & Schwarz	URV5-Z4	EF00322	2014-09	2015-09			
Directional Coupler	HP	HP 87300B	EF00288	functional test	functional test			
Radio Communication Tester	Rohde & Schwarz	CMD65	EF00625	ICO (initial calibration only)	ICO (initial calibration only)			
Universal Radio Communication Tester	Rohde & Schwarz	CMU 200	EF00304	2014-05	2015-05			
Network Analyzer 300 kHz to 3 GHz	Agilent	8752C	EF00140	2014-06	2015-06			
Dielectric Probe Kit	Agilent	85070C	EF00291	functional test	functional test			
DAK Thermometer (- 20110°C)	LKM electronic GmbH	DTM3000	EF00967	2014-09	2015-09			
DAK Probe (200MHz-20GHz)	SPEAG	DAK-3.5	EF00945	2014-09	2015-09			
DAK Measurement Software	SPEAG	DAKS	EF00965	-	-			



2 Result Summary

OET Bulletin 65 Supplement C, RSS-102							
Product Specific Standard Section	Requirement – Test	Reference Method	Maximum SAR [W/kg]	Result	Remarks		
OET Bulletin 65 Suppl. C Section 2 RSS-102 Section 3	Single-band conformity	KDB Publication 447498 KDB Publication 248227 KDB Publication 865664	0.000	PASS			
OET Bulletin 65 Suppl. C Section 2 RSS-102 Section 3	Multi-band conformity	KDB Publication 447498 KDB Publication 648474 KDB Publication 865664	0.026	PASS			



3 Definitions

The specific absorption rate (SAR) is defined as the time derivative of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ_l), expressed in watts per kilogram (W/kg)

SAR = d/dt (dW/dm) = d/dt (dW/
$$\rho_t$$
dV) = $\sigma/\rho_t |E_t|^2$

where

$$dW/dt = \int_{V} E J dV = \int_{V} \sigma E^{2} dV$$

3.1 Controlled Exposure

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category and the general population/uncontrolled exposure limits apply to these devices.

3.2 Uncontrolled Exposure

In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means. Awareness of the potential for RF exposure in a workplace or similar environment can be provided through specific training as part of a RF safety program. If appropriate, warning signs and labels can also be used to establish such awareness by providing prominent information on the risk of potential exposure and instructions on the risk of potential exposure risks.

3.3 Localized SAR

Compliance with the localized SAR limits is demonstrated using the head and trunk limit because this SAR limit is only half the limbs limit value. The values are obtained by SAR measurements according to EN 62209-2.




4 Localized SAR Measurement Equipment


The measurements were performed with Dasy5 automated near-field scanning system comprised of high precision robot, robot controller, computer, e-field probe, probe alignment unit, phantoms, non-conductive phone positioned and software extension.

4.1 Complete SAR DASY5 Measurement System

Measurements are performed using the DASY5 automated assessment system made by Schmid& Partner Engineering AG (SPEAG) in Zurich, Switzerland.



The following Diagram show the elements involved in the measurement setup.





The DASY5 system for performing compliance tests consists of the following items:

DASY5 SAR Measurement System				
Device	Description:			
RX90BL	A standard high precision 6-axis robot (Stäubli RX family) with controller, teach pendant and software.			
Probe Alignment Unit	A probe alignment unit which improves the (absolute) accuracy of the probe positioning.			
Teach Pendant	The Manual Control Pendant (MCP), also called the manual teach pendant, is the user interface to the robot. In DASY, it is used for certain installation and teach procedures			
Signal Lamps	External warning lamp which indicates when the robot arm is powered-on and if the robot is under software control or in manual mode (controlled with the teach pendant).			
DAE	The data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.			
E-Field Probes	Isotropic E-Field probe optimized and calibrated for E-field measurements in free space.			
EOC	The electro-optical converter (EOC) performs the conversion between optical and electrical signals			
Measurement Server	The functions of the measurement server is to perform the time critical task such as signal filtering, surveillance of the robot operation, fast movement interrupts.			
Control Computer	A computer operating Windows 2000 or Windows NT with DASY 4 Software.			
Control Software	DASY4 and SEMCAD post processing Software			
SAM Twin Phantom	The SAM twin phantom enabling testing left-hand and right-hand usage.			
Flat Phantom	Flat Phantom (only for body-mounted transceivers operating below 800 MHz).			
Tissue simulating liquid	Tissue simulating liquid mixed according to the given recipes.			
Device Holder	The device holder for handheld mobile phones.			
System Validation Dipoles	System validation dipoles allowing to validate the proper functioning of the system.			




4.2 Robot Arm

The DASY5 system uses the high precision robots RX90BL type out of the newer series from Stäubli SA (France).

The RX robot series have many features that are important for our application:


- High precision (repeatability 0.02 mm)
- High reliability (industrial design)
- > Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)
- > 6-axis controller



4.3 Data Acquisition Electronics

The data acquisition electronics (DAE3) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection. The input impedance of the DAE3 is 200M Ohm; the inputs are symmetrical and floating. Common mode rejection is above 80dB.





4.4 Isotropic E-Field Probe ≤ 3 GHz

Probe Specifications

Construction:

One dipole parallel, two dipoles normal to probe axis built-in shielding against static charges.

Calibration:

In air from 10 MHz to 2.5 GHz, In brain and muscle simulating tissue at Frequencies of 835MHz, 900MHz, 1800MHz, 1900 MHz and 2450 MHz

Frequency:

10MHz to > 3GHz, Linearity \pm 0.2dB (30MHz to 3GHz)

Directivity:

 ± 0.2 dB in HSL (rotation around probe axis) ± 0.4 dB in HSL (rotation normal to probe axis)

Dynamic Range:

 $5\mu W/g$ to > 100mW/g

Linearity:

±0.2dB

Dimensions:

Overall Length: 330mm (Tip: 16mm), Tip Diameter: 6.8mm (Body: 12mm),

Distance from probe tip to dipole centers: 2.7mm

Application:

General dosimetry up to 3 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms





4.5 Isotropic E-Field Probe ≤ 6 GHz

Probe Specifications

Construction:

One dipole parallel, two dipoles normal to probe axis built-in shielding against static charges.

Calibration:

In air from 10 MHz to 6 GHz, In brain and muscle simulating tissue at Frequencies of 5200, 5500, 5800

Frequency:

10MHz to 6GHz, Linearity ± 0.2 dB (30MHz to 6GHz)

Directivity:

 ± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)

Dynamic Range:

 $10\mu W/g$ to > 100mW/g

Linearity:

±0.2dB

Dimensions:

Overall Length: 337mm (Tip: 20mm), Tip Diameter: 2.5mm (Body: 12mm),

Distance from probe tip to dipole centers: 1mm

Application:

General dosimetry up to 6 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms






4.6 Test phantom and positioner

The positioner and test phantoms are manufactured by SPEAG. The test phantoms are used for all tests i.e. for both validation testing and device testing. The positioner and test phantom conforms to the requirements of EN 62209 and IEEE 1528.


The SPEAG device holder was used to position the test device in all tests whilst a tripod was used to position the validation dipoles in the test arch.





4.7 System Validation Dipoles

A set of calibration dipoles (D900V2, D1900V2, D2450V2, D5GHzV2) is included as a part of the SAR measurement setup. These are used for the validation of the test setup after its installation and prior to the EUT measurements. The calibration dipole is placed in the position normally occupied by the EUT. All calibration dipoles have the same height which allows an exact fitting below the center point of the test phantom. The dipole center is 10mm below the surface of the test phantom.





5 Single-band SAR Measurement

After successful completion of the tissue and system verification the SAR values of the EUT are measured according to the following description.

5.1 General measurement description

The measurement is performed for each frequency band of the device. If the width of the transmit frequency band exceeds 1% of its center frequency, than the channels at the lowest and highest frequencies should also be tested. Furthermore, if the width of the transmit band exceeds 10% of its center frequency the following formula is used to determine the number of channels:

$$N_C=2 \cdot roundup[10 \cdot (f_{high} - f_{low})/f_c] + 1$$

First the device is tested on the center channel of each frequency band used by the device. An operation mode and configuration with maximum transmit power is established. If battery operated equipment is used, the batteries are fully charged.

SAR measurements are performed using the steps outlined in the next section for all relevant operational modes, EUT configurations and measurement positions.

For the condition (position, configuration, operational mode) that provides the highest spatial-average SAR value on the center channel, the other channels are also tested.

Additionally all other conditions where the spatial-average SAR value is within 3dB of the SAR limit are also tested on all determined test frequencies.

5.2 SAR measurement description

First the local SAR value at a test point within 10mm or less in normal direction from the inner surface of the phantom is measured. This SAR value is used to determine the measurement drift during SAR measurement.

Next an area scan is performed over an area larger than the projection of the EUT with antenna on the surface of the phantom with a spatial grid step of 10mm.

From the scanned SAR distribution the position of maximum SAR value is identified as well as any local SAR maxima within 2dB of the maximum value that are not within the zoom scan volume. (The additional peaks are only measured when the primary peak is within 2dB of the SAR limit.)

The zoom-scan volume constructed on the peak SAR position is scanned with a grid step of 5mm. The measured data are extracted and the local SAR value for each measurement point is calculated. The measured values are interpolated over a fine-mesh within the scan volume and the average SAR value over 10g mass is calculated.


At the end of the measurement the reference point measured at the beginning of the measurement is measured again and from the difference the drift is calculated.




5.3 Reference lines and points for Handsets

For all measurement positions of the EUT, the EUT has to be place in a specific orientation with respect to the phantom. The orientation of the EUT relative to the phantom is defined by reference lines and points.

According to IEEE 1528, the reference lines and points shall be positioned at the EUT as shown in the following figure.








5.4 Test positions relative to the Head


Cheek position



The handset is positioned close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom. Next the handset is translated towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.

While the handset is maintained in this plane, it is rotated around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane. Then it is rotated around the vertical centerline until the handset (horizontal line) is parallel to the N-F line. While the vertical centerline is maintained in the Reference Plane, point A is kept on the line passing through RE and LE, and the handset is maintained in contact with the pinna, the handset is rotated about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek.

Tilt position






First the EUT is placed in the cheek position. Next the handset is moved away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°. Then the handset is rotated around the horizontal line by 15°.

The handset is moved towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point on the handset is in contact with the phantom, e.g., the antenna with the back of the head

5.5 Test positions relative to the human body



In body worn configuration the device is positioned parallel to the phantom surface with either top or bottom side of the EUT facing against the phantom.

The separation distance of the EUT is selected according to the use case of the EUT (e.g. with belt clip or holster).



5.6 Measurement Uncertainty


Measurement Uncertainty according to IEEE 1528									
Error Description	Uncertainty Value	Probability Distribution	Div.	c _i (1g)	c _i (10g)	Std. Unc. 1g	Std. Unc. 10g		
Measurement System				•					
Probe Calibration	±6.55%	N	1	1	1	±6.55%	±6.55%		
Axial Isotropy	±4.7%	R	$\sqrt{3}$	0.7	0.7	±1.9%	±1.9%		
Hemispherical Isotropy	±9.6%	R	$\sqrt{3}$	0.7	0.7	±3.9%	±3.9%		
Linearity	±4.7%	R	$\sqrt{3}$	1	1	±2.7%	±2.7%		
Modulation Response	±2.4%	R	$\sqrt{3}$	1	1	±1.4%	±1.4%		
System Detection Limits	±1.0%	R	$\sqrt{3}$	1	1	±0.6%	±0.6%		
Boundary effects	±2.0%	R	$\sqrt{3}$	1	1	±1.2%	±1.2%		
Readout Electronics	±0.3%	N	1	1	1	±0.3%	±0.3%		
Response Time	±0.8%	R	$\sqrt{3}$	1	1	±0.5%	±0.5%		
Integration Time	±2.6%	R	$\sqrt{3}$	1	1	±1.5%	±1.5%		
RF Ambient Noise	±3.0%	R	$\sqrt{3}$	1	1	±1.7%	±1.7%		
RF Ambient Reflections	±3.0%	R	$\sqrt{3}$	1	1	±1.7%	±1.7%		
Probe Positioner	±0.8%	R	$\sqrt{3}$	1	1	±0.5%	±0.5%		
Probe Positioning	±6.7%	R	$\sqrt{3}$	1	1	±3.9%	±3.9%		
Post processing	±4.0%	R	$\sqrt{3}$	1	1	±2.3%	±2.3%		
Test Sample Related				•					
Device Holder	±3.6%	N	1	1	1	±3.6%	±3.6%		
Test Sample Positioning	±2.9%	N	1	1	1	±2.9%	±2.9%		
Power Scaling	±0%	R	$\sqrt{3}$	1	1	±0%	±0%		
Power Drift	±5.0%	R	$\sqrt{3}$	1	1	±2.9%	±2.9%		
Phantom and Setup Rela	ated								
Phantom Uncertainty	±7.9%	R	$\sqrt{3}$	1	1	±4.6%	±4.6%		
SAR correction	±1.9%	R	$\sqrt{3}$	1	0.84	±1.1%	±0.9%		
Liquid conductivity (measured)	±2.5%	N	1	0.78	0.71	±2.0%	±1.8%		
Liquid permittivity (measured)	±2.5%	N	1	0.26	0.26	±0.1%	±0.1%		
Temperature uncertainty - Conductivity	±5.2%	R	$\sqrt{3}$	0.78	0.71	±2.3%	±2.1%		
Temperature uncertainty - Permittivity	±0.8%	R	$\sqrt{3}$	0.23	0.26	±0.1%	±0.1%		
Combined Standard Unce	ertainty		•	_	-	±12.8%	±12.7%		
Expanded Standard Und	ertainty					±25.6%	±25.4%		



6 Test ConditionsandResults

6.1 Test Conditions and Results - Tissue Validation

Test ac	cording to		Reference Method				
	ent reference		OET Bulletin 65	Supplement C			
		Target V	/alues				
	Hea	d	Bod	у	Permitted		
Frequency [MHz]	Relative dielectric constant ε _r	Conductivity σ [S/m]	Relative dielectric constant ε _r	Conductivity σ [S/m]	tolerance [%]		
150	52.3	0.76	61.9	0.80	≤±5		
300	45.3	0.87	58.2	0.92	≤±5		
450	43.5	0.87	56.7	0.94	≤±5		
835	41.5	0.90	55.2	0.97	≤±5		
900	41.5	0.97	55.0	1.05	<u>≤±</u> 5		
915	41.5	0.98	55.0	1.06	≤±5		
1450	40.5	1.20	54.0	1.30	≤±5		
1610	40.3	1.29	53.8	1.40	≤±5		
1800 – 2000	40.0	1.40	53.3	1.52	≤±5		
2450	39.2	1.80	52.7	1.95	≤±5		
3000	38.5	2.40	52.0	2.73	≤±5		
5200	36.0	4.66	49.0	5.30	≤±5		
5500	35.6	4.96	48.6	5.65	≤±5		
5800	35.3	5.27	48.2	6.00	≤±5		



Test procedure

- 1. The dielectric probe kit is calibrated using the standards air, short circuit and deionized water
- 2. The tissue simulating liquid is measured using the dielectric probe
- 3. Target values are compared to the measurement values and deviations are determined

	Test results								
Frequency [MHz]	Tissue	Measured ϵ_r	Target ε _r	Delta ε _r [%]	Measured σ [S/m]	Target σ [S/m]	Delta σ [%]		
1900	Head	39.22	40.0	-01.95	1.37	1.4	-02.14		
Comments:									




6.2 Test Conditions and Results - System Validation

System Validation acc. to FCC OET	Г Bulletin 65 Suppl. C / IC RSS-102	Verdict: PASS			
Test according to	Reference Method				
measurement reference	OET Bulletin 65 Supplement C / IEEE 1528				
Test frequency range	Tested frequencies				
	2450 MHz , 5200 MHz				
Test mode	unmodulated CW				
	Target Values				
Frequency [MHz]	Target SAR value [W/kg (1g)]	Permitted tolerance [%]			
1900	9.78 @ 250mW	≤ ±10			

The target reference values are taken from the calibration sheets (see annex)

Test setup



Test procedure

- 1. The dipole antenna input power is set to 250mW
- 2. The reference dipole is positioned under the phantom
- 3. With the dipole antenna powered the SAR value is measured
- 4. The measured SAR values are compared to the target SAR values

Test results								
Frequency [MHz]	Input power [mW]	Measured SAR value [W/kg (1g)]	Target SAR value [W/kg (1g)]	Delta [%]				
1900	250	9.68	9.78	-01.02				
Comments:								



6.3 Test Conditions and Results - Standalone SAR Measurement

ndalone SA	AR acc. toFCC	OET Bull	etin 65 Suppl.	C/ICRSS	-102		Verdict:	PASS
Tes	t according to			Refere	ence Met	hod		
	rement reference	€	FCC OET Bu	ılletin 65 Sup	plement	C / IC RS	SS-102 ls:	sue 4
Rooi	m temperature			22.0) – 22.6 °	С		
L	iquid depth			1	15.5 cm			
Е	nvironment		general public					
			Limits					
Region			Occupational S [W/kg	General public SAR values [W/kg]				
Whole b	ody average SA	R	0.4		0.08			
	Localized SAR (Head and trunk) SAR averaging mass = 10g		8		1.6			
Localized SAR (Limbs) SAR averaging mass = 10g		20			4			
			Test results					
Mode	Position	Channel	Frequency [MHz]	Drift [dB]	Average SAR [W/kg (1g)]	*Scaling Factor	Reported SAR [W/kg (1g)]	SAR Limit [W/kg (1g)]
UPCS	BACK-0MM	4	1921.536	-0.05	0.000	1.259	0.000	1.6
Overall maximum SAR value [W/kg (1g)]			0.0	000	1.	6		



6.4 Test Conditions and Results - Multi-transmitter SAR Result

Position	Max SAR UPCS	Bluetooth Channel	Bluetooth Frequency [MHz]	Bluetooth Estimated SAR*	Sum 1g SAR [W/kg]	SAR Limit [W/kg]
BACK-0MM	0.000	0	2402	0.026	0.026	1.6

SAR value estimated according to FCC KDB 447498 D01 $\,$ v05r02 Section 4.3.2 with a separation distance of 5 mm.



ANNEX A Calibration Documents

Test Report No.: G0M-1408-4062-TFC093SR79-V01

Calibration Laboratory of Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland





Schweizerischer Kalibrierdienst Service suisse d'étalonnage Servizio svizzero di taratura Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Client

Approved by:

Eurofins

Accreditation No.: SCS 108

Certificate No: DAE3-522_Sep14

CALIBRATION CERTIFICATE

Object DAE3 - SD 000 D03 AA - SN: 522

Calibration procedure(s) QA CAL-06.v28

Calibration procedure for the data acquisition electronics (DAE)

Calibration date: September 17, 2014

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID#	Cal Date (Certificate No.)	Scheduled Calibration
Keithley Multimeter Type 2001	SN: 0810278	01-Oct-13 (No:13976)	Oct-14
	1,		Cabadulad Chaale
Secondary Standards	ID#	Check Date (in house)	Scheduled Check
Auto DAE Calibration Unit	SE UWS 053 AA 1001	Consider the second sec	In house check: Jan-15

Name Function Signature

Calibrated by: Dominique Steffen Technician

Deputy Technical Manager

Issued: September 17, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Fin Bomholt

Calibration Laboratory of Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland





S Schweizerischer Kalibrierdienst
Service suisse d'étalonnage
Servizio svizzero di taratura
Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA

Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Glossary

DAE

data acquisition electronics

Connector angle

information used in DASY system to align probe sensor X to the robot

coordinate system.

Methods Applied and Interpretation of Parameters

- DC Voltage Measurement: Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- Connector angle: The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The following parameters as documented in the Appendix contain technical information as a result from the performance test and require no uncertainty.
 - DC Voltage Measurement Linearity: Verification of the Linearity at +10% and -10% of the nominal calibration voltage. Influence of offset voltage is included in this measurement.
 - Common mode sensitivity: Influence of a positive or negative common mode voltage on the differential measurement.
 - Channel separation: Influence of a voltage on the neighbor channels not subject to an input voltage.
 - AD Converter Values with inputs shorted: Values on the internal AD converter corresponding to zero input voltage
 - Input Offset Measurement. Output voltage and statistical results over a large number of zero voltage measurements.
 - Input Offset Current: Typical value for information; Maximum channel input offset current, not considering the input resistance.
 - *Input resistance:* Typical value for information: DAE input resistance at the connector, during internal auto-zeroing and during measurement.
 - Low Battery Alarm Voltage: Typical value for information. Below this voltage, a battery alarm signal is generated.
 - Power consumption: Typical value for information. Supply currents in various operating modes.

DC Voltage Measurement

A/D - Converter Resolution nominal

High Range: 1LSB =

 $6.1\mu V$,

full range = -100...+300 mV

Low Range:

1LSB =

61nV,

full range = -1.....+3mV

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Calibration Factors	Х	Υ	Z
High Range	404.208 ± 0.02% (k=2)	403.882 ± 0.02% (k=2)	404.721 ± 0.02% (k=2)
Low Range	3.96428 ± 1.50% (k=2)	3.95728 ± 1.50% (k=2)	3.97367 ± 1.50% (k=2)

Connector Angle

Connector Angle to be used in DASY system	56.5 ° ± 1 °
Connector Angle to be used in DAS1 system	30.3 ± 1

Page 3 of 5 Page 44 of 67 Certificate No: DAE3-522_Sep14

Appendix (Additional assessments outside the scope of SCS108)

1. DC Voltage Linearity

High Range		Reading (μV)	Difference (μV)	') Error (%)	
Channel X	+ Input	200036.59	-0.80	-0.00	
Channel X	+ Input	20007.79	3.33	0.02	
Channel X	- Input	-20000.37	5.45	-0.03	
Channel Y	+ Input	200037.53	0.19	0.00	
Channel Y	+ Input	20004.45	0.10	0.00	
Channel Y	- Input	-20001.11	4.89	-0.02	
Channel Z	+ Input	200039.93	2.29	0.00	
Channel Z	+ Input	20002.07	-2.13	-0.01	
Channel Z	- Input	-20005.14	0.85	-0.00	

Low Range		Reading (μV)	Difference (μV)	Error (%)
Channel X	+ Input	2000.68	-0.01	-0.00
Channel X	+ Input	200.76	0.21	0.11
Channel X	- Input	-198.84	0.67	-0.34
Channel Y	+ Input	2000.56	0.01	0.00
Channel Y	+ Input	200.46	-0.01	-0.00
Channel Y	- Input	-199.17	0.26	-0.13
Channel Z	+ Input	2000.50	0.01	0.00
Channel Z	+ Input	199.91	-0.66	-0.33
Channel Z	- Input	-201.19	-1.73	0.87

2. Common mode sensitivity

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	Common mode Input Voltage (mV)	High Range Average Reading (μV)	Low Range Average Reading (μV)
Channel X	200	-3.99	-5.30
	- 200	7.38	5.55
Channel Y	200	0.38	-0.28
	- 200	-0.60	-0.29
Channel Z	200	15.86	15.99
	- 200	-17.84	-18.37

3. Channel separation

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	Input Voltage (mV)	Channel X (μV)	Channel Y (μV)	Channel Z (μV)
Channel X	200	-	-1.68	-1.76
Channel Y	200	7.39		-1.38
Channel Z	200	6.24	5.61	

4. AD-Converter Values with inputs shorted

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	High Range (LSB)	Low Range (LSB)
Channel X	15741	16854
Channel Y	15714	14825
Channel Z	16054	16288

5. Input Offset Measurement

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Input $10M\Omega$

mpat rows	Average (μV)	min. Offset (μV)	max. Offset (μV)	Std. Deviation (μV)
Channel X	1.56	0.18	2.94	0.60
Channel Y	0.07	-1.10	1.20	0.53
Channel Z	0.39	-0.91	1.96	0.57

6. Input Offset Current

Nominal Input circuitry offset current on all channels: <25fA

7. Input Resistance (Typical values for information)

(·)p.	Zeroing (kOhm)	Measuring (MOhm)
Channel X	200	200
Channel Y	200	200
Channel Z	200	200

8. Low Battery Alarm Voltage (Typical values for information)

Typical values	Alarm Level (VDC)	
Supply (+ Vcc)	+7.9	
Supply (- Vcc)	-7.6	

9. Power Consumption (Typical values for information)

Typical values	Switched off (mA)	Stand by (mA)	Transmitting (mA)
Supply (+ Vcc)	+0.01	+6	+14
Supply (- Vcc)	-0.01	-8	-9

Calibration Laboratory of Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland





Schweizerischer Kalibrierdienst Service suisse d'étalonnage Servizio svizzero di taratura Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Client

Eurofins

Certificate No: ET3-1711_Sep14

Accreditation No.: SCS 108

S

C

CALIBRATION CERTIFICATE

Object

ET3DV6 - SN:1711

Calibration procedure(s)

QA CAL-01.v9, QA CAL-12.v9, QA CAL-23.v5, QA CAL-25.v6

Calibration procedure for dosimetric E-field probes

Calibration date:

September 22, 2014

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).

The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	D	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	03-Apr-14 (No. 217-01911)	Apr-15
Power sensor E4412A	MY41498087	03-Apr-14 (No. 217-01911)	Apr-15
Reference 3 dB Attenuator	SN: S5054 (3c)	03-Apr-14 (No. 217-01915)	Apr-15
Reference 20 dB Attenuator	SN: S5277 (20x)	03-Apr-14 (No. 217-01919)	Apr-15
Reference 30 dB Attenuator	SN: S5129 (30b)	03-Apr-14 (No. 217-01920)	Apr-15
Reference Probe ES3DV2	SN: 3013	30-Dec-13 (No. ES3-3013_Dec13)	Dec-14
DAE4	SN: 660	13-Dec-13 (No. DAE4-660_Dec13)	Dec-14
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-13)	In house check: Apr-16
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

Calibrated by:

Name Jeton Kastrati Function

Laboratory Technician

Approved by:

Katja Pokovic

Technical Manager

Issued: September 23, 2014

Signature

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: ET3-1711_Sep14

Page 1 of 11

Calibration Laboratory of

Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland





S Schweizerischer Kalibrierdienst
Service suisse d'étalonnage
Servizio svizzero di taratura
Swiss Calibration Service

Accreditation No.: SCS 108

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL NORMx,y,z tissue simulating liquid sensitivity in free space

ConvF DCP sensitivity in TSL / NORMx,y,z diode compression point

CF A, B, C, D crest factor (1/duty_cycle) of the RF signal modulation dependent linearization parameters

Polarization φ

φ rotation around probe axis

Polarization 9

9 rotation around an axis that is in the plane normal to probe axis (at measurement center),

i.e., 9 = 0 is normal to probe axis

Connector Angle

Certificate No: ET3-1711_Sep14

information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- *NORMx,y,z:* Assessed for E-field polarization $\vartheta = 0$ (f ≤ 900 MHz in TEM-cell; f > 1800 MHz: R22 waveguide). NORMx,y,z are only intermediate values, i.e., the uncertainties of NORMx,y,z does not affect the E²-field uncertainty inside TSL (see below *ConvF*).
- NORM(f)x,y,z = NORMx,y,z * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCPx,y,z: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- Ax,y,z; Bx,y,z; Cx,y,z; Dx,y,z; VRx,y,z: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters: Assessed in flat phantom using E-field (or Temperature Transfer Standard for f ≤ 800 MHz) and inside waveguide using analytical field distributions based on power measurements for f > 800 MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORMx,y,z * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy): in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle: The angle is assessed using the information gained by determining the NORMx (no uncertainty required).

Page 2 of 11

Probe ET3DV6

SN:1711

Manufactured: August 7, 2002

Calibrated:

September 22, 2014

Calibrated for DASY/EASY Systems

(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: ET3DV6 - SN:1711

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm $(\mu V/(V/m)^2)^A$	1.88	1.85	2.05	± 10.1 %
DCP (mV) ^B	100.1	100.6	99.2	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB√μV	С	D dB	VR mV	Unc [⊏] (k=2)
0	CW	Х	0.0	0.0	1.0	0.00	267.4	±3.5 %
		Y	0.0	0.0	1.0		280.5	
		Z	0.0	0.0	1.0		275.0	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

A The uncertainties of NormX,Y,Z do not affect the E2-field uncertainty inside TSL (see Pages 5 and 6).

Numerical linearization parameter: uncertainty not required.

Uncertainty is determined using the max, deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: ET3DV6 - SN:1711

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	Conv# Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unct. (k=2)
450	43.5	0.87	7.37	7.37	7.37	0.25	2.86	± 13.3 %
750	41.9	0.89	6.76	6.76	6.76	0.56	1.96	± 12.0 %
900	41.5	0.97	6.31	6.31	6.31	0.30	3.00	± 12.0 %
1750	40.1	1.37	5.25	5.25	5.25	0.69	2.19	± 12.0 %
1810	40.0	1.40	5.21	5.21	5.21	0.80	2.02	± 12.0 %
1950	40.0	1.40	5.04	5.04	5.04	0.80	2.02	± 12.0 %
2150	39.7	1.53	4.83	4.83	4.83	0.80	1.92	± 12.0 %
2450	39.2	1.80	4.45	4.45	4.45	0.80	1.63	± 12.0 %

^c Frequency validity above 300 MHz of \pm 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to \pm 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is \pm 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to \pm 110 MHz.

yalidity can be extended to ± 110 MHz.

At frequencies below 3 GHz, the validity of tissue parameters (ε and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ε and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is

^a Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

DASY/EASY - Parameters of Probe: ET3DV6 - SN:1711

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) ^c	Relative Permittivity ^F	Conductivity (S/m) F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unct. (k=2)
450	56.7	0.94	7.52	7.52	7.52	0.19	2.15	± 13.3 %
750	55.5	0.96	6.26	6.26	6.26	0.28	2.85	± 12.0 %
900	55.0	1.05	6.05	6.05	6.05	0.32	3.00	± 12.0 %
1750	53.4	1.49	4.74	4.74	4.74	0.80	2.46	± 12.0 %
1810	53.3	1.52	4.63	4.63	4.63	0.80	2.44	± 12.0 %
1950	53.3	1.52	4.67	4.67	4.67	0.80	2.35	± 12.0 %
2150	53.1	1.66	4.46	4.46	4.46	0.80	1.99	± 12.0 9
2450	52.7	1.95	4.08	4.08	4.08	0.68	1.24	± 12.0 9


^c Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

F At frequencies below 3 GHz, the validity of tissue parameters (ε and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ε and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

G Alpha/Deoth are determined during calibration. SPEAC were sets that the remaining during calibration.


^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than \pm 1% for frequencies below 3 GHz and below \pm 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.


Frequency Response of E-Field (TEM-Cell:ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field: ± 6.3% (k=2)


Receiving Pattern (ϕ), $\vartheta = 0^{\circ}$






Uncertainty of Axial Isotropy Assessment: ± 0.5% (k=2)


Dynamic Range f(SAR_{head}) (TEM cell , f_{eval}= 1900 MHz)






Uncertainty of Linearity Assessment: ± 0.6% (k=2)


Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, ϑ) , f = 900 MHz





DASY/EASY - Parameters of Probe: ET3DV6 - SN:1711

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	-108.2
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	enabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	6.8 mm
Probe Tip to Sensor X Calibration Point	2.7 mm
Probe Tip to Sensor Y Calibration Point	2.7 mm
Probe Tip to Sensor Z Calibration Point	2.7 mm
Recommended Measurement Distance from Surface	4 mm

Calibration Laboratory of Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland





Schweizerischer Kalibrierdienst Service suisse d'étalonnage Servizio svizzero di taratura **Swiss Calibration Service**

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Client

Eurofins

Accreditation No.: SCS 108

C

Certificate No: D1900V2-5d025_Sep12

CALIBRATION CERTIFICATE

Object

D1900V2 - SN: 5d025

Calibration procedure(s)

QA CAL-05.v8

Calibration procedure for dipole validation kits above 700 MHz

Calibration date:

September 21, 2012

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID#	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	05-Oct-11 (No. 217-01451)	Oct-12
Power sensor HP 8481A	US37292783	05-Oct-11 (No. 217-01451)	Oct-12
Reference 20 dB Attenuator	SN: 5058 (20k)	27-Mar-12 (No. 217-01530)	Apr-13
Type-N mismatch combination	SN: 5047.2 / 06327	27-Mar-12 (No. 217-01533)	Apr-13
Reference Probe ES3DV3	SN: 3205	30-Dec-11 (No. ES3-3205_Dec11)	Dec-12
DAE4	SN: 601	27-Jun-12 (No. DAE4-601_Jun12)	Jun-13
Secondary Standards	ID#	Check Date (in house)	Scheduled Check
Power sensor HP 8481A	MY41092317	18-Oct-02 (in house check Oct-11)	In house check: Oct-13
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-11)	In house check: Oct-13
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-11)	In house check: Oct-12

Name Calibrated by:

Function

Israe El-Naoug Laboratory Technician

Approved by:

Technical Manager Katja Pokovic

Issued: September 21, 2012

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Calibration Laboratory of Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland





S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
Servizio svizzero di taratura
S wiss Calibration Service

Accreditation No.: SCS 108

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL tissue simulating liquid

ConvF sensitivity in TSL / NORM x,y,z N/A not applicable or not measured

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- c) Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

Additional Documentation:

d) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL: The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss: These parameters are measured with the dipole
 positioned under the liquid filled phantom. The impedance stated is transformed from the
 measurement at the SMA connector to the feed point. The Return Loss ensures low
 reflected power. No uncertainty required.
- Electrical Delay: One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured: SAR measured at the stated antenna input power.
- SAR normalized: SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters: The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Certificate No: D1900V2-5d025_Sep12 Page 2 of 8 Page 59 of 67

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.2
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy , $dz = 5 mm$	
Frequency	1900 MHz ± 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	40.0	1.40 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	40.6 ± 6 %	1.37 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C		

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	9.78 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	39.8 mW /g ± 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	5.17 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	20.9 mW /g ± 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	53.3	1.52 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	52.5 ± 6 %	1.54 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C		

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	10.2 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	40.3 mW / g ± 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	5.42 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	21.5 mW / g ± 16.5 % (k=2)

Certificate No: D1900V2-5d025_Sep12 Page 3 of 8 Page 60 of 67

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	51.0 Ω + 4.7 jΩ
Return Loss	- 26.5 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	47.3 Ω + 5.1 jΩ
Return Loss	- 24.6 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.198 ns

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	July 29, 2002

DASY5 Validation Report for Head TSL

Date: 21.09.2012

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d025

Communication System: CW; Frequency: 1900 MHz

Medium parameters used: f = 1900 MHz; $\sigma = 1.37 \text{ mho/m}$; $\varepsilon_r = 40.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

Probe: ES3DV3 - SN3205; ConvF(5.01, 5.01, 5.01); Calibrated: 30.12.2011;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn601; Calibrated: 27.06.2012

• Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001

• DASY52 52.8.2(969); SEMCAD X 14.6.6(6824)

Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 94.699 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 17.364 mW/g


SAR(1 g) = 9.78 mW/g; SAR(10 g) = 5.17 mW/g

Maximum value of SAR (measured) = 11.9 W/kg



0 dB = 11.9 W/kg = 21.51 dB W/kg

Impedance Measurement Plot for Head TSL



DASY5 Validation Report for Body TSL

Date: 21.09.2012

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d025

Communication System: CW; Frequency: 1900 MHz

Medium parameters used: f = 1900 MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 52.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

Probe: ES3DV3 - SN3205; ConvF(4.62, 4.62, 4.62); Calibrated: 30.12.2011;

• Sensor-Surface: 3mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn601; Calibrated: 27.06.2012

Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002

• DASY52 52.8.2(969); SEMCAD X 14.6.6(6824)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 94.699 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 17.830 mW/g


SAR(1 g) = 10.2 mW/g; SAR(10 g) = 5.42 mW/g

Maximum value of SAR (measured) = 12.8 W/kg



0 dB = 12.8 W/kg = 22.14 dB W/kg

Impedance Measurement Plot for Body TSL



Date/Time: 10/29/2014 6:02:06 AM

Test Laboratory: Eurofins Product Service GmbH

System Performance Check - HSL - 1900 MHz_29_10_2014

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d025

Communication System: UID 0 - n/a, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: Head 1900 MHz Medium parameters used (interpolated): f = 1900 MHz; $\sigma = 1.366$ S/m; $\epsilon_r = 39.22$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5.2 Configuration:

• Probe: ET3DV6 - SN1711; ConvF(5.21, 5.21, 5.21); Calibrated: 9/22/2014;


- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn522; Calibrated: 9/17/2014
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1217
- Measurement SW: DASY52, Version 52.8 (6); SEMCAD X Version 14.6.9 (7117)

System Performance Check at Frequencies above 1 GHz/d=10mm, Pin=250 mW, dist=4.0mm (ET-Probe)/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm Maximum value of SAR (interpolated) = 12.3 W/kg

System Performance Check at Frequencies above 1 GHz/d=10mm, Pin=250 mW, dist=4.0mm (ET-Probe)/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 94.619 V/m; Power Drift = -0.02 dB Peak SAR (extrapolated) = 16.7 W/kg

SAR(1 g) = 9.68 W/kg; SAR(10 g) = 5.15 W/kg

Maximum value of SAR (measured) = 10.9 W/kg



Date/Time: 10/29/2014 10:18:31 AM

Test Laboratory: Eurofins Product Service GmbH

UPCS - 1924.99 MHz - Flat 0mm

DUT: Sonetics APX377; Type: Communication Headset; Serial: K1J02B436SN006

Communication System: UID 0 - n/a, UPCS Full Slot, 24; Frequency: 1924.99 MHz; Duty Cycle: 1:23.9994 Medium: Head 1900 MHz Medium parameters used (interpolated): f = 1924.99 MHz; σ = 1.392 S/m; ϵ_r = 39.141; ρ = 1000 kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5.2 Configuration:

• Probe: ET3DV6 - SN1711; ConvF(5.04, 5.04, 5.04); Calibrated: 9/22/2014;

- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection), Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn522; Calibrated: 9/17/2014
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1217
- Measurement SW: DASY52, Version 52.8 (6); SEMCAD X Version 14.6.9 (7117)

Configuration/Flat 0mm/Area Scan (141x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm Maximum value of SAR (interpolated) = 0.000234 W/kg

Configuration/Flat 0mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 0.047 V/m; Power Drift = 0.01 dB Peak SAR (extrapolated) = 0.000122 W/kg SAR(1 g) = 1.51e-006 W/kg; SAR(10 g) = 1.87e-007 W/kg Maximum value of SAR (measured) = 0.000430 W/kg

