

Analysis Report

Report No.: 16050774HKG-001

The Equipment Under Test (EUT) is a portable 2.4GHz Transceiver (Car Unit) operating at the frequency range of 2410-2475MHz with 1 MHz channel spacing.

The EUT is powered by 6.4V rechargeable battery. After switch on the EUT and paired with controller, the EUT can be controlled to move forward/backward and turn left/ right by the controller.

Antenna Type: Internal integral antenna

Antenna Gain: 0dBi

Nominal rated field strength: 76.1dB μ V/m at 3m

Maximum allowed field strength of production tolerance: +/- 3dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 79.1dB μ V/m at 3m in frequency 2.4GHz, thus;

The EIRP = $[(FS^2 * D) / 30] = 0.024\text{mW}$

Conducted power = Radiated Power (EIRP) – Antenna Gain

So;

Conducted Power = 0.024mW.

The SAR Exclusion Threshold Level:

= $3.0 * (\text{min. test separation distance, mm}) / \sqrt{\text{freq. in GHz}}$

= $3.0 * 5 / \sqrt{2.480} \text{ mW}$

= 9.53 mW

Since the above conducted output power is well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.