RF Exposure evaluation

According to KDB 447498 D01 General RF Exposure Guidance v05 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by: [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • [\sqrt{f} (GHz)] \leq 3.0 for 1-g SAR and \leq 7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- ${}^{\bullet}$ Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

```
eirp = pt x gt = (EXd)^2/30 where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, --- 10^{((dBuV/m)/20)}/10^6

d = measurement distance in meters (m)---3m

So pt = (EXd)^2/30 x gt
```

The worse case below:

```
Field strength = 92.77 dBuV/m @3m Ant gain 2.14dBi; so Ant numeric gain=1.64
```

```
So pt={[10^{(92.77/20)}/10^6x3]^2/(30x1.64)}x1000mW = 0.346mW
So (0.346mW/5mm)x \sqrt{2.4458GHz} = 0.108<3.0 for 1-g SAR
```

Then SAR evaluation is not required