

FCC ID: VAE0790311

Operational Description of the equipment

- Open the battery compartment and insert the 3 rechargeable batteries.
Close the battery compartment

Battery note: Please charge the batteries for a minimum of 6 Hours before using for the first time.

- Start the pairing process (as describe further down) between the B-Speech®Alpha and your Mobile Phone.
- Fasten the sun screen clip at the back of the B-Speech®Alpha.
- The B-Speech®Alpha can now be clipped over the side of the sun visor.
- Adjust the LCD screen to an optimum viewing angle.

PRODUCT	Alpha0790311
MODEL NO.	ALPHA0790311
POWER SUPPLY	DC 4.5 V, 500mA
FREQUENCY BAND	2.4GHz
CARRIER FREQUENCY	2.4GHz
NUMBER OF CHANNEL	79
CHANNEL SPACING	1 MHz
RATED RF OUTPUT POWER	-6~+4(MAX+6 dBm) dBm
MODULATION TYPE	GFSK
MODE OF OPERATION	duplex
BIT RATE OF TRANSMISSION	700K
ANTENNA TYPE	PCB pattern
ANTENNA GAIN	-3 dBi
OPERATING TEMPERATURE	-5~80°C
CHANNEL BANDWIDTH	1MHz