



Project: **07CA23734**  
File: **MC15627**  
Report: **07CA23734-FCC**  
Date: **June 12, 2007**  
Model: **SKSN-I25-CO**

## **Electromagnetic Compatibility Test Report**

### **FCC Certification 47 CFR Part 90 Subpart I**

**For**

**SK Telesys Co.,Ltd.**

**12F, Chorim Bldg. 6-3, Sunae-Dong,  
Buandang-Gu, Seongnam, Gyeonggi-Do,  
463-825, Korea**

**UL Korea Ltd.**

33<sup>rd</sup> Fl. Star Tower, 737 Yeoksam-Dong, Kangnam-Gu, Seoul, 135-984, Korea

Underwriters Laboratories Inc. authorizes the above-named company to reproduce this Report provided it is reproduced in its entirety.

## Report Directory

<b>1. G E N E R A L - Product Description</b>	<b>5</b>
1.1 Equipment Description	5
1.2 Equipment	6
1.3 Equipment Marking Plate	6
<b>2. Test Conditions</b>	<b>7</b>
2.1 Equipment Used During Test	7
2.2 Input/Output Ports	7
2.3 Test Equipments used	8
2.4 Power Interface	8
2.5 EUT Internal Operating Frequencies	8
2.6 EUT Operation Modes	9
2.7 EUT Operating Frequencies	9
2.8 Test Signal Source	9
2.9 EUT Configurations	10
2.10 Test Lab Environmental Condition	11
2.11 Test Specifications	12
2.12 Test Laboratory Details	12
<b>3. Test Results</b>	<b>13</b>
3.1 Test Conditions and Results – Conducted emissions at mains terminal	13
3.2 Test Conditions and Results – Radiated Emissions	18
3.3 Test Conditions and Results – RF Power Output	21
3.4 Test Conditions and Results – Occupied Bandwidth	32
3.5 Test Conditions and Results – Emission Mask	52
3.6 Test Conditions and Results – Spurious Emission at Antenna Terminal	63
3.7 Test Conditions and Results – Radiated Spurious Emission	93
3.8 Test Conditions and Results – Frequency Stability	97

## **Test Report Details :**

Tests Performed By: UL Korea Ltd.  
33<sup>rd</sup> FL. Star Tower 737 Yeoksam-dong,  
Kangnam-ku, Seoul, 135-984, Korea

Test Site: BWS Tech Inc.  
683-3, Yubang-Dong, Yongin-Si, Kyunggi-Do, Korea, 449-080

FCC Registration No. : 553281

Tests Performed For: SK Telesys Co.,Ltd.  
12F, Chorim Bldg. 6-3, Sunae-Dong,  
Buandang-Gu, Seongnam, Gyeonggi-Do, 463-825, Korea

Applicant Contact:  
Title: Jae Hyung, Kim  
Phone: Manager / RF Development Team  
Fax: +82 31-786-5628  
E-mail: +82 31-719-9451  
kjhyung@sktelesys.com

Test Report Number: 07CA23734-FCC

Test Report Date: June 05, 2007

Equipment Class: TNB - Licensed Non-Broadcast Station Transmitter

Product Type: iDEN RF Repeater

Model Number: SKSN-I25-CO

FCC ID: VAWSKSN-I25-CO

Test standards: 47 CFR Part 90 Subpart I & Part 15 Subpart B

Sample Serial Number: TSKAABBB1234

Sample Receive Date: 2007-04-16

Testing Start Date: 2007-04-16

Date Testing Complete: 2007-05-20

**Overall Results:** Pass

UL Korea as an affiliate of Underwriters Laboratories Inc. EMC report apply only to the specific test samples and test results submitted for UL's review. All samples tested were in good operating condition throughout the entire test program. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. UL Korea Ltd. shall have no liability for any deductions, inferences or generalizations drawn by the client or others from UL Korea Ltd. issued reports. This report shall not be used to claim, constitute or imply product certification, approval, or any agency of the National Authorities. This report may contain test results that are not covered by the NVLAP or KOLAS accreditation.

### Summary of Testing:

The following tests were performed on a sample submitted for evaluation of compliance with 47 CFR Part 90 Subpart I and Part 15 Subpart B.

Test #	Test Name Test Requirement/Specification	Compliant	Not Compliant	See Remark
1	Part 15, Subpart B Section 15.109(a)/ CISPR 22:1997 Class A Radiated Emissions - 30 to 1000 MHz Electric Field	X	-	2
2	Part 15, Subpart B Section 15.107(a) / CISPR 22:1997 Class A Conducted Emissions	X	-	2
3	Section 2.1046 & 90.205	X		
4	RF Power Output			
5	Section 2.1047	-	-	1
6	Modulation Limiting	-	-	1
7	Section 2.1047 & 90.209	X		
8	Occupied Bandwidth	X		
9	Section 2.1051 & 90.210, 90.669	X		
10	Spurious Emission at antenna terminal			
11	Section 2.1053 & 90.210	X		
12	Radiated Spurious Emission			
13	Section 2.1055 & 90.213	X		
14	Frequency Stability			
15	Out of band Rejection	X		
16	RF Exposure			3

### Remarks:

- 1) Not applicable to this EUT.
- 2) Emissions Data can also be considered applicable to FCC Part 15 Subpart A.
- 3) RF Exposure will be addressed at the time of licensing.
- 4) Modifications to EUT required for compliance: NONE.

### Conclusion:

The tests listed in the Summary of Testing section of this report have been performed and the results recorded by UL Korea Ltd. in accordance with the procedures stated in each test requirement and specification. The test list was determined by the Applicant as being applicable to the Equipment Under Test. As a result, the subject product has been verified to comply or not comply as noted in the Summary of Testing with each test specification. The test results relate only to the items tested.

Tested By:



Kyung Yong, Kim  
EMC Engineer  
UL Korea Ltd.

Reviewed By:



Jea Woon, Choi  
EMC Engineer  
UL Korea Ltd.

## 1. G E N E R A L - Product Description

### 1.1 Equipment Description

The SK telesys SKSN-I25-CO is a dual band bi-directional RF signal amplifier system for the wireless SMR 800 MHz and 900 MHz iDEN spectrum bands. The iDEN (Integrated Digital Enhanced Network) RF repeater is a RF repeater for indoor use using a frequency band of iDEN networks. This dual band RF repeater is designed to be elastically applicable to frequency of iDEN band, is excellent in frequency selection levels of frequency bandwidth to service of down links and up links through an up/down converter module, and minimizes interference in other signals.


- Basic model tested : SKSN-I25-CO
- Model covered : SKSN-I25-CM , SKSN-I25-NO

Items		Standards
Frequency Range	800MHz band	Downlink : 851~869MHz , Uplink : 806~824MHz Downlink : 862~869MHz , Uplink : 817~824MHz
	900MHz band	Downlink : 935~940MHz , Uplink : 896~901MHz
Output Power per channel / Amplifier Gain		25dBm / 65dB
Modulation		QAM
Emission Designator		GXW(iDEN)
Input Level		-15 ~ -40dBm / Total
Gain Control Range		25 dB(1dB/Step±0.5dB or less)
Out of band paging carrier rejection		929~932MHz(3MHz), 940~941MHz(1MHz)
Input/output connector		50Ω N-Type (Female)
Cabinet		Indoor type
Size (H*W*D)		390*326*210 mm
Working temperature/ working humidity		-10°C ~ 50°C / 5 % ~ 95%
Power		108 ~ 127 VAC, 60Hz

## 1.2 Equipment



## 1.3 Equipment Marking Plate



## 2. Test Conditions

### 2.1 Equipment Used During Test

Use*	Product Type	Manufacturer	Model	Comments
EUT	iDEN Repeater	SK Telesys	SKCN-I25-CO	Indoor metal enclosure
AE	RF Load	Bird	8173	Coaxial Load S/N : 2501
AE	RF Attenuator	Bird	8325	Coaxial Attenuator S/N : 4572
SIM	Notebook PC	DELL	PP17L	For Frequency tune up

Note:  
\* **EUT** - Equipment Under Test, **AE** - Auxiliary/Associated Equipment, or **SIM** - Simulator (Not Subjected to Test)

### 2.2 Input/Output Ports

Port #	Name	Type*	Cable Max. >3m (Y/N)	Cable Shielded (Y/N)	Comments
0	Enclosure	N/E	—	—	Metal cabinet type (indoor purpose)
1	Mains (AC input)	AC	< 3m	N	Cable length (1m)
2	Antenna port (Donor)	RF	N	Y	Connected to RF Load
3	Antenna port (Service)	RF	N	Y	Connected to RF Load
4	Coupling Port	RF	-	-	No use : Maintenance purpose only
5	Coupling Port	RF	-	-	No use : Maintenance purpose only

Note:  
\*AC = AC Power Port      DC = DC Power Port      N/E = Non-Electrical  
I/O = Signal Input or Output Port (Not Involved in Process Control)  
TP = Telecommunication Ports

### 2.3 Test Equipments used

Test Equipment Used					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Signal Generator	Aeroflex	IFR3413	341006/212	2006-05-12	2007-05-12
Signal Generator	Aeroflex	IFR3413	341006/012	2006-09-26	2007-09-36
Spectrum Analyzer	Agilent	E4440A	MY44022474	2006-11-06	2007-11-06
Spectrum Analyzer	Agilent	E4440A	MY43362280	2005-10-06	2007-11-06
Fixed Attenuator	H.P	8498A	3318A10568	-	-
Fixed Attenuator	Microwave device	MA-530	2309	-	-

Note : E4440A : 3Hz~26.5GHz, IFR3413: 250kHz ~3GHz, Attn : 30dB

### 2.4 Power Interface

Mode #	Voltage (V)	Frequency (DC/AC-Hz)	Phases (#)	Comments
Rated	120Vac	60Hz	Single Phase	Nominal voltage
1	120Vac	60Hz	Single Phase	
2	108Vac	60Hz	Single Phase	Voltage variation (Norminal-15%)
3	138Vac	60Hz	Single Phase	Voltage variation (Norminal+15%)

### 2.5 EUT Internal Operating Frequencies

Frequency (MHz)	Description	Frequency (MHz)	Description

Note : The data has not been provided from the applicant.

## 2.6 EUT Operation Modes

Mode #	Description
1	Transmission mode : RF signal from the iDEN signal generator injected to the service port of the repeater and the amplified RF output signal from the Doner port of the repeater was connected to the RF Load.
2	Uplink mode : RF signal from the iDEN signal generator injected to the service port of the repeater and the amplified RF output signal from the Doner port of the repeater was connected to the Spectrum analyzer.
3	Downlink mode : RF signal from the iDEN signal generator injected to the Doner port of the repeater and the amplified RF output signal from the Service port of the repeater was connected to the Spectrum analyzer.



## 2.7 EUT Operating Frequencies

Mode #	Description
1	Uplink mode : 3 frequencies (Bottom, Mid, Top channel) for each frequency band - 18 MHz band : 806 MHz, 815 MHz, 824 MHz - 7 MHz band : 817 MHz, 820.5 MHz, 824 MHz - 5 MHz band : 896 MHz, 898.5 MHz, 901 MHz
2	Downlink mode : 3 frequencies (Bottom, Mid, Top channel) for each frequency band - 18 MHz band : 851 MHz, 860 MHz, 869 MHz - 7 MHz band : 862 MHz, 865.5 MHz, 869 MHz - 5 MHz band : 935 MHz, 937.5 MHz, 940 MHz


## 2.8 Test Signal Source

The carrier from the signal generator applied to the repeater was a Quadrature Amplitude Modulation(QAM)  
- Baseband Modulation type : 16-QAM, 64 kbps Random Data Per Channel  
- Baseband Channelization : 25 kHz  
- Signal source sample rate : 640ks/sec  
- No. of samples : 960,000  
- RMS Value : 2907  
- Crest factor : 9.475dB

## 2.9 EUT Configurations

Mode #	Description
1	 <p><b>Test Configuration of EMI Measurement</b></p> <ul style="list-style-type: none"><li>-. Device on tabletop connected to AC power.</li></ul>
2	 <p><b>Test Configuration of Conducted Measurement – Up link</b></p>

3



**Test Configuration of Conducted Measurement – Down link**

## 2.10 Test Lab Environmental Condition

Parameters required prior to the test	Laboratory Ambient Temperature	10 to 40 °C
	Relative Humidity	10 to 90 %
Parameters recorded during the test	Laboratory Ambient Temperature	25 °C
	Relative Humidity	40 %

## 2.11 Test Specifications

Standard Number	Standard Name	Standard Date
CFR 47 Part 90 Subpart I	General Technical Standards	2006
CFR 47 Part 15 Subpart B	General Technical requirements	2006
ANSI C63.4-2003	Methods of Measurements of Radio-Noise Emission from Low voltage and electrical equipment in the range of 9kHz~40GHz	2003
EIA/TIA-603 Edition C 2004	Land Mobile FM or PM communication equipment measurement and performance standards	2004
FCC 2-11-04	EAB/RF Amplifier, Booster, and Repeater reminder	2004

## 2.12 Test Laboratory Details

All the testing has been performed by UL Korea engineer at both test laboratories described below. The radiated spurious emission measurements were performed in a 10 meter open site which has been filed to the commission in accordance with section 2.948 at BWS Tech Inc.

Conducted RF Measurement Test Laboratory : SK Telesys Test Lab (Manufacturer's Test Lab)  
Location : 12F, Chorim Bldg. 6-3, Sunae-Dong, Buandang-Gu, Seongnam, Gyeonggi-Do, 463-825, Korea.

Persons who have been presented during the test : Si Hwan, Sung (Research engineer / SK Telesys) Dae Kwang, Kim (Manager of R&D office/ SK Telesys), Jae Hyung, Kim(Manager of R&D office/ SK Telesys)

Radiated Emission Measurement Test Laboratory : BWS Tech Inc.  
10 m Open Field Test Site (FCC Registration No. : 553281)  
611-1, Maesan-ri, Mohyeon-myeon, Cheoin-gu, Yongin-si, Gyeonggi-do 449-853, Korea  
Persons who have been presented during the test : Min sup, Shim (Senior test engineer)

### 3. Test Results

#### 3.1 Test Conditions and Results – Conducted emissions at mains terminal

Test Description	Measurements were made on a ground plane. All power was connected to the system through Artificial Mains Network (AMN). Conducted voltage measurements on mains lines were made at the output of the AMN.	
Basic Standard	ANSI C63.4-2003, 47 CFR § 15.107	
Parameters required prior to the test	Laboratory Ambient Temperature	10 to 40 °C
	Relative Humidity	10 to 90 %
Parameters recorded during the test	Laboratory Ambient Temperature	25 °C
	Relative Humidity	40 %
	Frequency range on each side of line	Measurement Point
Fully configured sample scanned over the following frequency range	150kHz to 30MHz	Mains
<b>Limits - Class A</b>		
Frequency (MHz)	Limit (dB $\mu$ V)	
	Quasi-Peak	Average
0.15 to 0.50	79	66
0.50 to 30	73	60
<b>Limits - Class B</b>		
Frequency (MHz)	Limit (dB $\mu$ V)	
	Quasi-Peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50
Supplementary information: None		

### Conducted Emissions EUT Configuration Settings

Power Interface Mode # (See Section 2.4)	EUT Configurations Mode # (See Section 2.9)	EUT Operation Mode # (See 2.6)
1	1	1
Supplementary information: The EUT operation modes specified in Section 2.4 have been investigated and final measurement reported was performed with Uplink mode 18 MHz band Mid frequency(815MHz) as a worst case emission.		

### Conducted Emissions Test Equipment

Test Equipment Used					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Signal Generator	Aeroflex	IFR3413	341006/012	2006-09-26	2007-09-26
LISN	COM-POWER	L1-115	241017	2006-11-13	2007-11-13
Signal Analyzer	PMM	PMM9000	3100570602	2006-09-22	2007-09-22

Project Number: 07CA23734  
File Number : MC15627

Test Report No: 07CA23734-FCC  
Date of Issue : June.12, 2007


**Figure 1 Test Setup for Conducted Emissions**



Project Number: 07CA23734  
File Number : MC15627

Test Report No: 07CA23734-FCC  
Date of Issue : June.12, 2007

**Figure 2 Conducted Emissions Graph**



**Table 1 Conducted Emissions Data Points**

Test Frequency (MHz)	Meter Reading (dBuV)	Detector (Pk/QP/Av)	Gain/Loss Factor (dB)	Transducer Factor (dB)	Emission Level (dBuV)	Class A QP Limit (dBuV)	Class A Ave Limit (dBuV)	Margin (dB)
0.152	45.1	QP	0.03	0.06	45.19	79.0	66.0	33.8
0.206	58.0	QP	0.10	0.07	58.17	79.0	66.0	20.8
0.240	35.8	QP	0.22	0.08	36.07	79.0	66.0	42.9
0.411	36.8	QP	0.26	0.08	37.14	79.0	66.0	41.9
0.862	38.3	QP	0.33	0.06	38.69	73.0	60.0	34.3
2.483	38.0	QP	0.57	0.03	38.60	73.0	60.0	34.4
7.450	37.1	QP	0.99	0.05	38.12	73.0	60.0	34.9
19.240	43.8	QP	1.35	0.06	45.21	73.0	60.0	27.8

Supplementary information:  
 - Gain/Loss Factor : Cable loss , Transducer Factor : LISN insertion loss  
 - Line polarity : HOT  
 - Margin = QP Limit - Level

Test Frequency (MHz)	Meter Reading (dBuV)	Detector (Pk/QP/Av)	Gain/Loss Factor (dB)	Transducer Factor (dB)	Emission Level (dBuV)	Class A QP Limit (dBuV)	Class A Ave Limit (dBuV)	Margin (dB)
0.154	45.6	QP	0.03	0.06	45.69	79	66	33.3
0.207	58.1	QP	0.10	0.07	58.27	79	66	20.7
0.302	46.5	QP	0.22	0.08	46.80	79	66	32.2
0.415	35.8	QP	0.26	0.08	36.14	79	66	42.9
0.890	40.6	QP	0.33	0.06	40.99	73	60	32.0
2.482	37.9	QP	0.57	0.03	38.50	73	60	34.5
7.650	38.9	QP	0.99	0.05	39.94	73	60	33.1
19.230	44.2	QP	1.35	0.06	45.61	73	60	27.4

Supplementary information:  
 - Gain/Loss Factor : Cable loss , Transducer Factor : LISN insertion loss  
 - Line polarity : Neutral  
 - Margin = QP Limit - Level

### 3.2 Test Conditions and Results – Radiated Emissions

Test Description	Measurements were made in a 10-meter open field test site that complies to CISPR 16/ANSI C63.4. Preliminary (peak) measurements were performed at semi anechoic chamber with antenna to EUT separation distance of 3 meter. The EUT was rotated 360° about its azimuth with the receive antenna located at various heights in both horizontal and vertical polarities. Final measurements (quasi-peak or average as noted) were then performed by rotating the EUT 360° and adjusting the receive antenna height from 1 to 4-meters. All frequencies were investigated in both horizontal and vertical antenna polarity, where applicable.	
Basic Standard	ANSI C63.4-2003, 47 CFR § 15.107 Class A	
Parameters required prior to the test	Laboratory Ambient Temperature	10 to 40 °C
	Relative Humidity	10 to 90 %
Parameters recorded during the test	Laboratory Ambient Temperature	27 °C
	Relative Humidity	47 %
	Frequency range	Measurement Point
Fully configured sample scanned over the following frequency range	30MHz – 1GHz	(10 meter measurement distance)
<b>Limits - Class A</b>		
Frequency (MHz)	Limit (dB $\mu$ V/m)	
	Quasi-Peak	Average
30 to 230	40	NA
230 to 1000	47	NA
<b>Limits - Class B</b>		
Frequency (MHz)	Limit (dB $\mu$ V/m)	
	Quasi-Peak	Average
30 to 230	30	NA
230 to 1000	37	NA
Supplementary information:		


### Radiated Emissions EUT Configuration Settings

Power Interface Mode # (See Section 2.4)	EUT Configurations Mode # (See Section 2.9)	EUT Operation Mode # (See Section 2.6)
Rated	1	1
Supplementary information: The EUT operation modes specified in Section 2.4 have been investigated and final measurement reported was performed with Uplink mode 18 MHz band Mid frequency(815MHz) as a worst case emission.		

### Radiated Emissions Test Equipment

Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Bilog Antenna	Schwarzbwck	VULB9160	9160-3122	2006-12-29	2007-12-29
Test Receiver	Rohde & Schwarz	ESVN30	832854/010	2005-06-22	2006-06-22
Signal Generator	Aeroflex	IFR3413	341006/012	2006-09-26	2007-09-26
Horn Antenna	Schwarzbeck	BBHA 9120D	234	2007-02-08	2008-02-08
Test Receiver	Rohde & Schwarz	ESPI	100063	2006-11-09	2007-11-09

Figure 3 Test setup for Radiated Emissions





**Table 2 Radiated Emissions Data Points**

Test Frequency (MHz)	Meter Reading (dBuV)	Detector (Pk/QP)	Polarity (V/H)	Azimuth (Degrees)	Antenna Height (cm)	Gain/Loss Factor (dB)	Transducer Factor (dB/m)	Level dBuV/m	Class A Limit dBuV/m	Margin (dB)
178.27	17.68	QP	V	180	200	2.97	12.16	32.81	40.0	7.19
182.04	23.46	QP	H	360	100	3.00	11.84	38.30	40.0	1.70
203.11	24.79	QP	V	180	200	3.17	10.16	38.12	40.0	1.88

Supplementary information:

- Margin = Class A QP Limit - Level

### 3.3 Test Conditions and Results – RF Power Output

Test Description	Measurements were made in the laboratory environment. For RF power measurements, all calculations and methods used by the applicant for determining carrier power or peak envelope power, as appropriate, on the basis of measured power in the radio frequency load attached to the transmitter output terminals shall be shown. The EUT was adjusted to produce maximum power rating of the product specification. The measurements were made at the EUT input and output ports in downlink and uplink transmit modes of operation at B,M,T channels.			
Basic Standard	47 CFR § 2.1046, § 90.205, § 90.219			
<b>Occupied Bandwidth Limits</b>				
The Effective radiated power of base station and cellular repeater must not exceed 5 watts.				
Parameters required prior to the test	Laboratory Ambient Temperature	10 to 40 °C		
	Relative Humidity	10 to 90 %		
Parameters recorded during the test	Laboratory Ambient Temperature	24 °C		
	Relative Humidity	45 %		

#### RF output power Configuration Settings

Power Interface Mode # (See Section 2.4)	EUT Configurations Mode # (See Section 2.9)	EUT Operation Mode # (See 2.6)
1	2,3	2,3
Supplementary information: None		

**Table 3 RF output power measured data**

**Table 3-A Down Link**

Carrier Band	Frequency (MHz)	Loss offset (dB)	Measured Power (dBm)	Limit (dBm)	Margin (dB)
iDEN 18 MHz	851	32	23.33	37	-13.67
	860	32	24.61	37	-12.39
	869	32	23.50	37	-13.50
iDEN 7 MHz	862	32	24.34	37	-12.66
	865.5	32	24.39	37	-12.61
	869	32	23.49	37	-13.51
iDEN 5 MHz	935	32	23.93	37	-13.07
	937.5	32	24.87	37	-12.13
	940	32	23.95	37	-13.05
Supplementary information:					
- Modulation signal 16-QAM, Power measurement : Channel power w/ mean value					
- Before the measurement, the system calibration for compensation of cable loss and attenuator has been made and included in the test result.					

**Table 3-B Up Link**


Carrier Band	Frequency (MHz)	Loss offset (dB)	Measured Power (dBm)	Limit (dBm)	Margin (dB)
iDEN 18 MHz	806	32	24.19	37	-12.81
	815	32	24.69	37	-12.31
	824	32	23.83	37	-13.17
iDEN 7 MHz	817	32	24.61	37	-12.39
	820.5	32	24.70	37	-12.30
	824	32	23.92	37	-13.08
iDEN 5 MHz	896	32	24.09	37	-12.91
	898.5	32	24.47	37	-12.53
	901	32	23.97	37	-13.03
Supplementary information:					
- Modulation signal 16-QAM, Power measurement : Channel power w/ mean value					
- Before the measurement, the system calibration for compensation of cable loss and attenuator has been made and included in the test result.					



### Test Equipment



Test Equipment Used					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Signal Generator	Aeroflex	IFR3413	341006/212	2006-05-12	2007-05-12
Spectrum Analyzer	Agilent	E4440A	MY44022474	2006-11-06	2007-11-06
Fixed Attenuator	H.P	8498A	3318A10568		



Note : E4440A : 3Hz~26.5GHz, IFR3413: 250kHz ~3GHz, Attn : 30dB



**Figure 4 RF output power graphical data**



























### 3.4 Test Conditions and Results – Occupied Bandwidth

Test Description	Measurements were made in the laboratory environment. The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The modulated carrier signal with maximum RF level was applied to the down and up link input of the repeater and resulting output was compared against the original signal.			
Basic Standard	47 CFR § 2.1049,			
<b>Occupied Bandwidth Limits</b>				
According to the FCC 2-11-04/EAB/RF, Input and output signals were compared to verify that there was no any degradation to the signal due to amplification and conversion from the repeater using an RBW of 300 Hz or 1% of the emission bandwidth.				
Parameters required prior to the test	Laboratory Ambient Temperature	10 to 40 °C		
	Relative Humidity	10 to 90 %		
Parameters recorded during the test	Laboratory Ambient Temperature	23 °C		
	Relative Humidity	40 %		

#### Occupied Bandwidth Configuration Settings

Power Interface Mode # (See Section 2.4)	EUT Configurations Mode # (See Section 2.9)	EUT Operation Mode # (See 2.6)
1	2,3	2,3
Supplementary information: None		

#### Occupied Bandwidth Spectrum Analyzer Settings

Span (MHz)	Resolution Bandwidth (MHz)	Occupied Bandwidth Requirements	
		dBc	%
50 kHz	470 Hz	-26	99
Supplementary information: 99% bandwidth was applied.			

**Table 4 Occupied Bandwidth measured results**


Carrier Band	UP LINK Bandwidth (kHz)		
	Frequency (MHz)	Input channel	Output channel
iDEN 18 MHz	806	17.67	17.81
	815	17.56	17.41
	824	17.74	17.71
iDEN 7 MHz	817	17.60	17.42
	820.5	17.32	17.56
	824	17.74	17.57
iDEN 5 MHz	896	17.62	17.36
	898.5	17.82	17.62
	901	17.63	17.61
Supplementary information: Modulation signal 16-QAM, 99% bandwidth			

Carrier Band	DOWN LINK Bandwidth (kHz)		
	Frequency (MHz)	Input channel	Output channel
iDEN 18 MHz	851	17.81	17.32
	860	17.67	17.51
	869	17.54	17.64
iDEN 7 MHz	862	17.50	17.72
	865.5	17.87	17.34
	869	17.54	17.37
iDEN 5 MHz	935	17.31	17.40
	937.5	17.50	17.75
	940	17.72	17.46
Supplementary information: Modulation signal 16-QAM, 99% bandwidth			


#### Occupied Bandwidth Test Equipment

Test Equipment Used					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Signal Generator	Aeroflex	IFR3413	341006/212	2006-05-12	2007-05-12
Spectrum Analyzer	Agilent	E4440A	MY44022474	2006-11-06	2007-11-06
Fixed Attenuator	H.P	8498A	3318A10568		


**Figure 5 Occupied Bandwidth Graph**




**Mode : Up link - Input  
Carrier band : 18 MHz  
Frequency : 815 MHz**




**Mode : Up link - Output  
Carrier band : 18 MHz  
Frequency : 815 MHz**






**Mode : Up link - Input  
Carrier band : 18 MHz  
Frequency : 824 MHz**




**Mode : Up link - Output  
Carrier band : 18 MHz  
Frequency : 824 MHz**













**Mode : Up link - Input  
Carrier band : 5 MHz  
Frequency : 896 MHz**





**Mode : Up link - Output  
Carrier band : 5 MHz  
Frequency : 896 MHz**





















**Mode : Down link - Input**  
**Carrier band : 7 MHz**  
**Frequency : 865.5 MHz**




**Mode : Down link - Output**  
**Carrier band : 7 MHz**  
**Frequency : 865.5 MHz**









**Mode : Down link - Input**  
**Carrier band : 5 MHz**  
**Frequency : 937.5 MHz**



**Mode : Down link - Output**  
**Carrier band : 5 MHz**  
**Frequency : 937.5 MHz**





### 3.5 Test Conditions and Results – Emission Mask

Test Description	Measurements were made in the laboratory environment. Emission mask measurement was made using a direct connection between RF output of the EUT and spectrum analyzer. Measurement has been performed with the EUT set to maximum output level at low, mid and high channel frequencies.			
Basic Standard	47 CFR § 2.1049,			
<b>Occupied Bandwidth Limits</b>				
1. § 90.691 Emission Mask Requirements for EA-Based Systems – 25 kHz Channel Spacing – 800 MHz Operation 0 – 12.5 kHz : 0 dBc 12.5 – 37.5 kHz : $116 + 10\log_{10}(F/6.1)$ dBc 37.5 kHz - : 43 plus $10\log_{10}(P)$ dBc				
2. § 90.669 Emission Limits – 25 kHz Channel Spacing – 900 MHz Operation On any frequency in an MTA licensee's spectrum block that is adjacent to a non-MTA frequency, the power of any emission shall be attenuated below the transmitter power (P) by at least 43 plus $10\log_{10}(P)$ dB or 80 dB, whichever is the lesser attenuation.				

#### Emission Mask Configuration Settings

Power Interface Mode # (See Section 2.4)	EUT Configurations Mode # (See Section 2.9)	EUT Operation Mode # (See 2.6)
1	2,3	2,3
Supplementary information: None		

#### Emission Mask Spectrum Analyzer Settings

Span (MHz)	Resolution Bandwidth (MHz)	Occupied Bandwidth Requirements	
		dBc	%
50 kHz	470 Hz	-26	99
Supplementary information: 99% bandwidth was applied.			

**Table 5 Emission Mask measured results**

**Table 5-A Uplink results**

Carrier Band	UP LINK Bandwidth (kHz)		
	Frequency (MHz)	Emission mask	Result
iDEN 18 MHz	806	§ 90.691	Pass
	815	§ 90.691	Pass
	824	§ 90.691	Pass
iDEN 7 MHz	817	§ 90.691	Pass
	820.5	§ 90.691	Pass
	824	§ 90.691	Pass
iDEN 5 MHz	896	§ 90.669	Pass
	898.5	§ 90.669	Pass
	901	§ 90.669	Pass

Supplementary information: Modulation signal 16-QAM, 99% bandwidth

**Table 5-B Downlink results**


Carrier Band	DOWN LINK Bandwidth (kHz)		
	Frequency (MHz)	Input channel	Output channel
iDEN 18 MHz	851	§ 90.691	Pass
	860	§ 90.691	Pass
	869	§ 90.691	Pass
iDEN 7 MHz	862	§ 90.691	Pass
	865.5	§ 90.691	Pass
	869	§ 90.691	Pass
iDEN 5 MHz	935	§ 90.669	Pass
	937.5	§ 90.669	Pass
	940	§ 90.669	Pass

Supplementary information: Modulation signal 16-QAM, 99% bandwidth


### Emission Mask Test Equipment

Test Equipment Used					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Signal Generator	Aeroflex	IFR3413	341006/212	2006-05-12	2007-05-12
Spectrum Analyzer	Agilent	E4440A	MY44022474	2006-11-06	2007-11-06
Fixed Attenuator	H.P	8498A	3318A10568		


**Figure 3 Emission Mask Plots**




**Mode : Up link**  
**Carrier band : 18 MHz**  
**Frequency : 824 MHz**




**Mode : Up link**  
**Carrier band : 7 MHz**  
**Frequency : 817 MHz**




**Mode : Up link**  
**Carrier band : 7 MHz**  
**Frequency : 820.5 MHz**




**Mode : Up link**  
**Carrier band : 7 MHz**  
**Frequency : 824 MHz**




**Mode : Up link**  
**Carrier band : 5 MHz**  
**Frequency : 896 MHz**




**Mode : Up link**  
**Carrier band : 5 MHz**  
**Frequency : 898.5 MHz**




**Mode : Up link**  
**Carrier band : 5 MHz**  
**Frequency : 901 MHz**




**Mode : Down link**  
**Carrier band : 18 MHz**  
**Frequency : 851 MHz**




**Mode : Down link**  
**Carrier band : 18 MHz**  
**Frequency : 860 MHz**




**Mode : Down link**  
**Carrier band : 18 MHz**  
**Frequency : 869 MHz**




**Mode : Down link  
Carrier band : 7 MHz  
Frequency : 862 MHz**




**Mode : Down link  
Carrier band : 7 MHz  
Frequency : 865.5 MHz**




**Mode : Down link**  
**Carrier band : 7 MHz**  
**Frequency : 869 MHz**




**Mode : Down link**  
**Carrier band : 5 MHz**  
**Frequency : 935 MHz**



**Mode : Down link**  
**Carrier band : 5 MHz**  
**Frequency : 937.5 MHz**



**Mode : Down link**  
**Carrier band : 5 MHz**  
**Frequency : 940 MHz**



### 3.6 Test Conditions and Results – Spurious Emission at Antenna Terminal

Test Description	Measurements were made in the laboratory environment. Conducted spurious emission measurement was made using a direct connection between RF output of the EUT and spectrum analyzer. A modulated carrier signal from the generator was applied to the both uplink and down link port of the EUT. Measurement has been performed with the EUT set to maximum output level at low, mid and high channel frequencies. The spectrum was investigated from 30 MHz to 10 <sup>th</sup> harmonics of carrier.  Inter-modulation requirements were performed with two modulated carriers set at 1 MHz deviation. One carrier was set at the band edge of both Uplink and Downlink and other carrier was set at 1 MHz deviation from the first carrier.			
Basic Standard	47 CFR § 2.1051			
<b>Occupied Bandwidth Limits</b>				
§ 90.210 & § 90.669 Emission limit : On any frequency in an MTA licensee's spectrum block that is adjacent to a non-MTA frequency, the power of any emission shall be attenuated below the transmitter power(P) by at least $43 + 10\log_{10}(P)$ dB or 80 dB, whichever is the lesser attenuation.				

#### Emission Mask Configuration Settings

Power Interface Mode # (See Section 2.4)	EUT Configurations Mode # (See Section 2.9)	EUT Operation Mode # (See 2.6)
1	2,3	2,3
Supplementary information: None		

#### Conducted spurious emission Spectrum Analyzer Settings

Frequency Range (MHz)	Resolution Bandwidth	Resolution Bandwidth
30 MHz ~ 1 GHz	100 kHz	300 kHz
1 GHz ~ 10 GHz	1 MHz	3 MHz
Supplementary information:		

**Table 6 Antenna terminal Conducted spurious emission results**

**Table 6-A Up Link**

Carrier Band	Tuned Frequency (MHz)	Loss offset (dB)	Spurious emission measured (dBm)	Limit (dBm)	Margin (dB)
iDEN 18 MHz	806	31	-29.06	-13	-16.06
	815	31	-28.05	-13	-15.05
	824	31	-29.71	-13	-16.71
iDEN 7 MHz	817	31	-28.46	-13	-15.46
	820.5	31	-28.47	-13	-15.47
	824	31	-28.99	-13	-15.99
iDEN 5 MHz	896	31	-29.25	-13	-16.25
	898.5	31	-29.48	-13	-16.48
	901	31	-29.10	-13	-16.10

Supplementary information:

- Carrier signal was modulated with iDEN 16-QAM, Power measurement : Peak power measured
- For each tuned carrier frequency, the maximum spurious emission detected was recorded.

**Table 6-B Up Link Two carrier Intermodulation**

Carrier Band	Tuned Frequency (MHz)	Loss offset (dB)	Spurious emission measured (dBm)	Limit (dBm)	Margin (dB)
iDEN 18 MHz	Low edge	32	-39.66	-13	-26.66
	High edge	32	-43.16	-13	-30.16
iDEN 7 MHz	Low edge	32	-45.48	-13	-32.48
	High edge	32	-44.54	-13	-31.54
iDEN 5 MHz	Low edge	32	-38.89	-13	-25.89
	High edge	32	-45.78	-13	-32.78

Supplementary information:

- Carrier signal was modulated with iDEN 16-QAM, Power measurement : Peak power measured
- For each tuned carrier frequency, the maximum spurious emission detected was recorded.

**Table 6-C Down link**

Carrier Band	Tuned Frequency (MHz)	Loss offset (dB)	Spurious emission measured (dBm)	Limit (dBm)	Margin (dB)
iDEN 18 MHz	851	31	-28.08	-13	-15.08
	860	31	-28.64	-13	-15.64
	869	31	-27.31	-13	-14.31
iDEN 7 MHz	862	31	-29.00	-13	-16.00
	865.5	31	-28.57	-13	-15.57
	869	31	-29.29	-13	-16.29
iDEN 5 MHz	935	31	-29.34	-13	-16.34
	937.5	31	-28.75	-13	-15.75
	940	31	-28.88	-13	-15.88

Supplementary information:

- Carrier signal was modulated with iDEN 16-QAM, Power measurement : Peak power measured
- For each tuned carrier frequency, the maximum spurious emission detected was recorded.

**Table 6-D Down Link Two carrier Intermodulation**

Carrier Band	Tuned Frequency (MHz)	Loss offset (dB)	Spurious emission measured (dBm)	Limit (dBm)	Margin (dB)
iDEN 18 MHz	Low edge	31	-43.54	-13	-30.54
	High edge	31	-42.08	-13	-29.08
iDEN 7 MHz	Low edge	31	-39.97	-13	-26.97
	High edge	31	-40.94	-13	-27.94
iDEN 5 MHz	Low edge	31	-43.51	-13	-30.51
	High edge	31	-42.02	-13	-29.02


Supplementary information:

- Carrier signal was modulated with iDEN 16-QAM, Power measurement : Peak power measured
- For each tuned carrier frequency, the maximum spurious emission detected was recorded.



**Emission Mask Test Equipment**

<b>Test Equipment Used</b>					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Signal Generator	Aeroflex	IFR3413	341006/212	2006-05-12	2007-05-12
Spectrum Analyzer	Agilent	E4440A	MY44022474	2006-11-06	2007-11-06
Fixed Attenuator	H.P	8498A	3318A10568		



**Figure 7 Conducted Spurious Emission plots at Antenna terminal**





**Mode : Up link**  
**Carrier band : 18 MHz**  
**Mid Channel Frequency : 815 MHz**





**Mode : Up link**  
**Carrier band : 18 MHz**  
**High Channel Frequency : 824 MHz**





**Mode : Up link**  
**Carrier band : 7 MHz**  
**Low Channel Frequency : 817 MHz**





**Mode : Up link**  
**Carrier band : 7 MHz**  
**Mid Channel Frequency : 820.5 MHz**





**Mode : Up link**  
**Carrier band : 7 MHz**  
**High Channel Frequency : 824 MHz**





**Mode : Up link**  
**Carrier band : 5 MHz**  
**Low Channel Frequency : 896 MHz**




**Mode : Up link**  
**Carrier band : 5 MHz**  
**Mid Channel Frequency : 898.5 MHz**




**Mode : Up link**  
**Carrier band : 5 MHz**  
**High Channel Frequency : 901 MHz**




**Mode : Up link – Two Carrier Intermodulation**  
**Carrier band : 18 MHz – Low end band edge**  
**Channel Frequency : 806/ 807 MHz**




**Carrier band : 18 MHz – High end band edge**  
**Channel Frequency : 823/ 824 MHz**




**Mode : Up link – Two Carrier Intermodulation**  
**Carrier band : 7 MHz – Low end band edge**  
**Channel Frequency : 817/ 818 MHz**




**Carrier band : 7 MHz – High end band edge**  
**Channel Frequency : 823/ 824 MHz**




**Mode : Up link – Two Carrier Intermodulation**  
**Carrier band : 5 MHz – Low end band edge**  
**Channel Frequency : 896/ 897 MHz**




**Carrier band : 5 MHz – High end band edge**  
**Channel Frequency : 900/ 901 MHz**




**Mode : Up link – Out of band Rejection  
Carrier band : 18 MHz**





**Mode : Up link – Out of band Rejection  
Carrier band : 7 MHz**





**Mode : Up link – Out of band Rejection  
Carrier band : 5 MHz**





**Mode : Down link**  
**Carrier band : 18 MHz**  
**Low Channel Frequency : 851 MHz**





**Mode : Down link**  
**Carrier band : 18 MHz**  
**Mid Channel Frequency : 860 MHz**





**Mode : Down link**  
**Carrier band : 18 MHz**  
**High Channel Frequency : 869 MHz**





**Mode : Down link**  
**Carrier band : 7 MHz**  
**Low Channel Frequency : 862 MHz**





**Mode : Down link**  
**Carrier band : 7 MHz**  
**Mid Channel Frequency : 865.5 MHz**





**Mode : Down link**  
**Carrier band : 7 MHz**  
**High Channel Frequency : 869 MHz**




**Mode : Down link**  
**Carrier band : 5 MHz**  
**Low Channel Frequency : 935 MHz**




**Mode : Down link**  
**Carrier band : 5 MHz**  
**Mid Channel Frequency : 937.5 MHz**







**Mode : Down link – Two Carrier Intermodulation**  
**Carrier band : 18 MHz – Low end band edge**  
**Channel Frequency : 850/ 851 MHz**




**Carrier band : 18 MHz – High end band edge**  
**Channel Frequency : 868/ 869 MHz**




**Mode : Down link – Two Carrier Intermodulation**  
**Carrier band : 7 MHz – Low end band edge**  
**Channel Frequency : 862/ 863 MHz**




**Carrier band : 7 MHz – High end band edge**  
**Channel Frequency : 868/ 869 MHz**




**Mode : Down link – Two Carrier Intermodulation**  
**Carrier band : 5 MHz – Low end band edge**  
**Channel Frequency : 935/ 936 MHz**




**Carrier band : 5 MHz – High end band edge**  
**Channel Frequency : 939/ 940 MHz**



**Mode : Down link – Out of band Rejection  
Carrier band : 18 MHz**



**Mode : Down link – Out of band Rejection  
Carrier band : 5 MHz**



### 3.7 Test Conditions and Results – Radiated Spurious Emission

Test Description	Measurements were made in a 10-meter open field test site that complies to CISPR 16/ANSI C63.4. Preliminary (peak) measurements were performed at semi-anechoic chamber with an antenna to EUT separation distance of 3 meter. The EUT was rotated 360° about its azimuth with the receive antenna located at various heights in both horizontal and vertical polarities. Final measurements (quasi-peak or average as noted) were then performed by rotating the EUT 360° and adjusting the receive antenna height from 1 to 4-meters in accordance with procedure of substitution method specified in TIA/EIA-603-A-2003. All frequencies were investigated in both horizontal and vertical antenna polarity, where applicable. The maximum EIRP of the emission was up to 10 <sup>th</sup> harmonics.			
Basic Standard	TIA/EIA/603-A-2003			
<b>Radiated Spurious Emission LIMITS</b>				
§ 90.210 & § 90.669 Emission limit : On any frequency in an MTA licensee's spectrum block that is adjacent to a non-MTA frequency, the power of any emission shall be attenuated below the transmitter power(P) by at least $43 + 10\log_{10}(P)$ dB or 80 dB, whichever is the lesser attenuation.				
Parameters required prior to the test	Laboratory Ambient Temperature	10 to 40 °C		
	Relative Humidity	10 to 90 %		
Parameters recorded during the test	Laboratory Ambient Temperature	27 °C		
	Relative Humidity	47 %		
	Frequency range	Measurement Point		
Fully configured sample scanned over the following frequency range	1GHz – 10GHz	(3 meter measurement distance)		
<b>Limits – EIRP</b>				
Frequency (MHz)	Limit (dBm EIRP)			
	Peak	Average		
Harmonics up to 10 <sup>th</sup>	-13	NA		
Supplementary information:				

### Conducted spurious emission Spectrum Analyzer Settings

Frequency Range (MHz)	Resolution Bandwidth	Resolution Bandwidth
1 GHz ~ 10 GHz	1 MHz	3 MHz
Supplementary information: Peak measurement		


### Radiated Emissions EUT Configuration Settings

Power Interface Mode # (See Section 2.4)	EUT Configurations Mode # (See Section 2.9)	EUT Operation Mode # (See Section 2.6)
1	2,3	2,3
Supplementary information: The EUT operation modes specified in Section 2.4 have been investigated and final measurement.		

### Radiated Emissions Test Equipment

Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Bilog Antenna	Schwarzbwck	VULB9160	9160-3122	2006-12-29	2007-12-29
Test Receiver	Rohde & Schwarz	ESVN30	832854/010	2005-06-22	2006-06-22
Signal Generator	Aeroflex	IFR3413	341006/012	2006-09-26	2007-09-26
Horn Antenna	Schwarzbeck	BBHA 9120D	234	2007-02-08	2008-02-08
Test Receiver	Rohde & Schwarz	ESPI	100063	2006-11-09	2007-11-09

Figure 8 Test setup for Spurious Radiated Emissions



Project Number: 07CA23734  
File Number : MC15627

Test Report No: 07CA23734-FCC  
Date of Issue : June.12, 2007



**Table 7 Spurious Radiated Emissions Data Points**

Test Frequency (MHz)	Meter Reading (dBuV)	Detector (Pk/QP)	Polarity (V/H)	Azimuth (Degrees)	Antenna Height (cm)	Gain/Loss Factor (dB)	Transducer Factor (dB/m)	Level dBuV/m	Limit 1 dBuV/m	Margin (dB)
<p>Supplementary information: <b>No emissions were detected within 20dB below the permitted limit.</b></p>										

### 3.8 Test Conditions and Results – Frequency Stability

Test Description	For Temperature Frequency Stability, measurements were made with the product placed in an environmental chamber and the temperature varied from -30°C to +50°C at the normal supply voltage. The frequency drift of the fundamental frequency was measured with a spectrum analyzer. For Power Supply Frequency Stability, measurements were made in a laboratory environment and the supply voltage varied from 85% to 115%. The ambient temperature was 20°C.			
Basic Standard	47 CFR § 2.1055, § 90.213			
<b>Frequency Stability Limits</b>				
+/- 1 ppm of the Operating Frequency Tuned				

#### Frequency Stability Configuration Settings

Power Interface Mode # (See Section 2.4)	EUT Configurations Mode # (See Section 2.10)	EUT Operation Mode # (See 2.7)
1,2,3	3	3
Supplementary information: None		

#### Frequency Stability Test Equipment

Description	Manufacturer	Model	Identifier
Temperature chamber	NeingYoul	NY-THR	13200
Temperature Recorder	Yokogawa	SR-1006	-
Signal Generator	Aeroflex	IFR3413	341006/212
Spectrum Analyzer	Agilent	E4440A	MY44022474
Fixed Attenuator	H.P	8498A	3318A10568

**Table 8 Frequency Stability Test results**

**Frequency Stability with variation of Ambient Temperature - Downlink**

Carrier Band	Temperature (°C)	Assigned Frequency (Hz)	Measured Frequency (Hz)	Drift (ppm)	Limit (ppm)
iDEN 18 MHz Mid channel tuned	50	860,000,000.000	860,000,000.010	0.000012	1.0
	40	860,000,000.000	860,000,000.080	0.000093	1.0
	30	860,000,000.000	859,999,999.980	-0.000023	1.0
	20	Reference			
	10	860,000,000.000	860,000,000.049	0.000057	1.0
	0	860,000,000.000	860,000,000.162	0.000188	1.0
	-10	860,000,000.000	860,000,000.005	0.000006	1.0
	-20	860,000,000.000	860,000,000.015	0.000017	1.0
	-30	860,000,000.000	860,000,000.048	0.000056	1.0
	50	865,500,000.000	865,500,000.067	0.000077	1.0
iDEN 7 MHz Mid channel tuned	40	865,500,000.000	865,500,000.041	0.000047	1.0
	30	865,500,000.000	865,499,999.953	-0.000054	1.0
	20	Reference			
	10	865,500,000.000	865,500,000.033	0.000038	1.0
	0	865,500,000.000	865,500,000.013	0.000015	1.0
	-10	865,500,000.000	865,500,000.027	0.000031	1.0
	-20	865,500,000.000	865,499,999.975	-0.000029	1.0
	-30	865,500,000.000	865,500,000.043	0.000050	1.0
	50	937,500,000.000	937,499,999.980	-0.000021	1.0
	40	937,500,000.000	937,500,000.049	0.000052	1.0
iDEN 5 MHz Mid channel tuned	30	937,500,000.000	937,500,000.034	0.000036	1.0
	20	Reference			
	10	937,500,000.000	937,500,000.048	0.000051	1.0
	0	937,500,000.000	937,500,000.040	0.000043	1.0
	-10	937,500,000.000	937,500,000.088	0.000094	1.0
	-20	937,500,000.000	937,500,000.068	0.000073	1.0
	-30	937,500,000.000	937,500,000.056	0.000060	1.0

Supplementary information:

- Downlink mode Mid operating frequencies setting
- No modulation,
- Before the testing, the signal generator and spectrum analyzer were synchronized by using the external sync. Frequency measurement was made by spectrum analyzer
- Reference inout voltage : 120Vac

#### Frequency Stability with variation of Input voltage - Downlink

Carrier Band	Input voltage (V)	Assigned Frequency (Hz)	Measured Frequency (Hz)	Drift (ppm)	Limit (ppm)
iDEN 18 MHz Mid channel	102 Vac	860,000,000.000	860,000,000.017	0.000020	1.0
	138 Vac	860,000,000.000	860,000,000.014	0.000016	1.0
iDEN 7 MHz Mid channel	102 Vac	865,500,000.000	865,500,000.072	0.000083	1.0
	138 Vac	865,500,000.000	865,500,000.020	0.000023	1.0
iDEN 5 MHz Mid channel	102 Vac	937,500,000.000	937,500,000.044	0.000047	1.0
	138 Vac	937,500,000.000	937,500,000.038	0.000041	1.0

Supplementary information:

- Downlink mode Mid operating frequencies setting
- No modulation,
- Before the testing, the signal generator and spectrum analyzer were synchronized by using the external sync. Frequency measurement was made by spectrum analyzer
- Reference temperature : 20°C

**Frequency Stability with variation of Ambient Temperature - Uplink**

Carrier Band	Temperature (°C)	Assigned Frequency (Hz)	Measured Frequency (Hz)	Drift (ppm)	Limit (ppm)
iDEN 18 MHz Mid channel tuned	50	815,000,000.000	815,000,000.060	0.060	1.0
	40	815,000,000.000	815,000,000.020	0.020	1.0
	30	815,000,000.000	815,000,000.038	0.038	1.0
	20	Reference			
	10	815,000,000.000	815,000,000.038	0.038	1.0
	0	815,000,000.000	815,000,000.036	0.036	1.0
	-10	815,000,000.000	815,000,000.061	0.061	1.0
	-20	815,000,000.000	814,999,999.984	-0.016	1.0
	-30	815,000,000.000	815,000,000.026	0.026	1.0
	50	820,500,000.000	820,500,000.080	0.080	1.0
iDEN 7 MHz Mid channel tuned	40	820,500,000.000	820,500,000.031	0.031	1.0
	30	820,500,000.000	820,500,000.053	0.053	1.0
	20	Reference			
	10	820,500,000.000	820,500,000.070	0.070	1.0
	0	820,500,000.000	820,500,000.075	0.075	1.0
	-10	820,500,000.000	820,500,000.015	0.015	1.0
	-20	820,500,000.000	820,500,000.056	0.056	1.0
	-30	820,500,000.000	820,500,000.040	0.040	1.0
	50	898,500,000.000	898,500,000.051	0.051	1.0
	40	898,500,000.000	898,500,000.031	0.031	1.0
iDEN 5 MHz Mid channel tuned	30	898,500,000.000	898,500,000.047	0.047	1.0
	20	Reference			
	10	898,500,000.000	898,500,000.044	0.044	1.0
	0	898,500,000.000	898,499,999.996	-0.004	1.0
	-10	898,500,000.000	898,499,999.998	-0.002	1.0
	-20	898,500,000.000	898,500,000.015	0.015	1.0
	-30	898,500,000.000	898,500,000.061	0.061	1.0

Supplementary information:

- No modulation,
- Before the testing, the signal generator and spectrum analyzer were synchronized by using the external sync. Frequency measurement was made by spectrum analyzer
- Reference inout voltage : 120Vac

### Frequency Stability with variation of Input voltage - Uplink

Carrier Band	Input voltage (V)	Assigned Frequency (Hz)	Measured Frequency (Hz)	Drift (ppm)	Limit (ppm)
iDEN 18 MHz Mid channel	102 Vac	815,000,000.000	815,000,000.028	0.000034	1.0
	138 Vac	815,000,000.000	815,000,000.063	0.000077	1.0
iDEN 7 MHz Mid channel	102 Vac	820,500,000.000	820,500,000.037	0.000045	1.0
	138 Vac	820,500,000.000	820,500,000.065	0.000079	1.0
iDEN 5 MHz Mid channel	102 Vac	898,500,000.000	898,500,000.047	0.000052	1.0
	138 Vac	898,500,000.000	898,500,000.056	0.000062	1.0

Supplementary information:

- No modulation,
- Before the testing, the signal generator and spectrum analyzer were synchronized by using the external sync. Frequency measurement was made by spectrum analyzer
- Reference temperature : 20°C