

## FCC Exposure Calculation

EUT Description: NT-168 Bluetooth Speaker

Company: NewLift Technologies LTD.

Model: NT-168

FCC ID: VB8NT-168

Frequency: 2402-2480 MHz (79 channels)

Modulation: FHSS (GFSK)

Mid-Channel: 2.441 GHz (channel 39)

Mid-Channel Peak Power, Conducted: 2.67 dBm == 1.85 mW

Antenna Gain: G = 1.0 dBi

### Calculation:

$$\text{Limit} = 60/2.441 = \underline{24.58 \text{ mW}}$$

$$P_{\text{radiated, max}} = P_{\text{conducted, dBm}} + G_{\text{dBi}} = 2.67 \text{ dBm} + 1.0 \text{ dBi} == 3.67 \text{ dBm} = \underline{2.33 \text{ mW}}$$

### Conclusion:

The emitted power appears to be (far) below the required limit, so PASS.

Note 1: f shall be the mid-band frequency expressed in GHz; the limit calculated with this mid-band frequency applies to all channels. For PTT with body-worn or face-held modes, d is the distance from the device case to a person's body; for modules with antennas inside laptops, d is the distance from the antenna to the person's body.

Note 2: Average Power levels are always equal or below the measured Peak Power levels, which means that calculating the EIRP using the Peak power can be considered as worst case.)