


FCC PART 15.231
MEASUREMENT AND TEST REPORT
FOR

UTECH INDUSTRIAL (HONGKONG) LIMITED.

**RM 15A, BUILDING B, SHENNAN GARDEN, NANSHAN DISTRICT,
SHENZHEN, CHINA**

FCC ID: VB9-07TM108

Report Concerns: Original Report	Equipment Type: ELECTRONIC TEXT TRANSMITTER
Model: <u>TM-108</u>	
Report No.: <u>STR07058073I</u>	
Test/Witness Engineer: <u>Lahm Peng</u>	
Test Date: <u>2007-05-25</u>	
Prepared By: Shenzhen SEM.Test Compliance Service Co., Ltd. Room 609-610, Baotong Building, Baomin 1 st Road, Baoan District, Shenzhen, Guangdong, P.R.C. (518133)	
Approved & Authorized By:  _____ Jandy So / PSQ Manager	

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permission by SEM.Test Compliance Service Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS	3
1.3 RELATED SUBMITTAL(S)/GRANT(S).....	3
1.4 TEST METHODOLOGY	4
1.5 TEST FACILITY	4
1.6 EUT EXERCISE SOFTWARE	4
1.7 ACCESSORIES EQUIPMENT LIST AND DETAILS	4
1.8 EUT CABLE LIST AND DETAILS.....	4
2. SUMMARY OF TEST RESULTS	5
3. §15.203 - ANTENNA REQUIREMENT	6
3.1 STANDARD APPLICABLE	6
3.2 TEST RESULT	6
4. §15.205, §15.209, §15.231 (B)- RADIATED EMISSION	7
4.1 MEASUREMENT UNCERTAINTY	7
4.2 STANDARD APPLICABLE	7
4.4 TEST PROCEDURE.....	8
4.5 CORRECTED AMPLITUDE & MARGIN CALCULATION	9
4.6 ENVIRONMENTAL CONDITIONS	9
4.7 SUMMARY OF TEST RESULTS/PLOTS	9
5. §15.231(C) 20DB BANDWIDTH TESTING	11
5.1 STANDARD APPLICABLE	11
5.2 TEST EQUIPMENT LIST AND DETAILS	11
5.3 TEST PROCEDURE.....	11
5.4 ENVIRONMENTAL CONDITIONS	11
5.5 SUMMARY OF TEST RESULTS/PLOTS	11
6. §15.231(A)-DEACTIVATION TESTING	13
6.1 STANDARD APPLICABLE	13
6.2 TEST EQUIPMENT LIST AND DETAILS	13
6.3 TEST PROCEDURE.....	13
6.4 ENVIRONMENTAL CONDITIONS	13
6.5 SUMMARY OF TEST RESULTS/PLOTS	13

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Applicant: UTECH INDUSTRIAL (HONGKONG) LIMITED.
Address of applicant: RM 15A, BUILDING B, SHENNAN GARDEN, NANSHAN DISTRICT, SHENZHEN, CHINA

Manufacturer: UTECH INDUSTRIAL CO., LTD.
Address of manufacturer: RM 15A, BUILDING B, SHENNAN GARDEN, NANSHAN DISTRICT, SHENZHEN, CHINA

General Description of E.U.T

Items	Description
EUT Description:	ELECTRONIC TEXT TRANSMITTER
Trade Name:	/
Model No.:	TM-108
Rated Voltage:	DC 4.5V
Output Power:	<1mW
Frequency Range:	315.05MHz
Antenna Type:	Integral Antenna
Size:	15.5x6.0x2.3cm
Comment:	Manual Operation Device

For more information refer to the circuit diagram form and the user's manual.

The test data is gathered from a production sample, provided by the manufacturer.

1.2 Test Standards

The following report of is prepared on behalf of UTECH INDUSTRIAL (HONGKONG) LIMITED. in accordance with FCC Part 15, Subpart C, and section 15.231, 15.203, 15.205 and 15.209 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.231, 15.203, 15.205 and 15.209 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission/immunity, should be checked to ensure compliance has been maintained.

1.3 Related Submittal(s)/Grant(s)

No Related Submittal(s).

1.4 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions. The EUT was tested in all three orthogonal planes and the worse case was showed.

1.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

United States of American Federal Communications Commission (**FCC**), and the registration number is **274801**(semi anechoic chamber).

Industry Canada (**IC**), and the registration number is **IC4174**.

All measurement required was performed at laboratory of Shenzhen Academy of Metrology and Quality Inspection, Bldg. of Metrology & Quality Inspection, Longzhu Road, Nanshan District, Shenzhen, Guangdong, China.

1.6 EUT Exercise Software

The EUT exercise program used during the testing was designed to exercise the system components. The test software is started while the EUT system is on.

1.7 Accessories Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

1.8 EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Cord/Without Cord
/	/	/	/

2. SUMMARY OF TEST RESULTS

Description of Test	Result
§15.203 Antenna Requirement	Compliant
§15.205 Restricted Band	Compliant
§15.209 General Requirement	Compliant
§15.231 (a)(1) Deactivation Testing	Compliant
§15.231 (c) 20dB Band Width Testing	Compliant
§15.231 (b) Radiated Emission	Compliant

3. §15.203 - ANTENNA REQUIREMENT

3.1 Standard Applicable

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has a permanent antenna, fulfill the requirement of this section.

4. §15.205, §15.209, §15.231 (b)- RADIATED EMISSION

4.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is ±3.0 dB.

4.2 Standard Applicable

According to §15.231(b), the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Fundamental frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emissions (microvolts/meter)
40.66-40.70.....	2,250.	225
70-130.....	1,250.....	125
130-174.....	\1\ 1,250 to 3,750	\1\ 125 to 375
174-260.....	3,750.....	375
260-470.....	\1\ 3,750 to.....	\1\ 375 to 1,250
	12,500.	
Above 470.....	12,500.....	1,250

\1\ Linear interpolations.

The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in §15.209, whichever limit permits a higher field strength.

compliance with the provisions of §15.205 shall be demonstrated using the measurement instrumentation specified in that section.


4.3 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
EMI Test Receiver	Rohde & Schwarz	ESCS30	830245/009	2007-1-25	2008-1-24
Multi_Device Controller	ETS	2090	57230	2007-1-25	2008-1-24
Receiver Antenna	ETS	2175	57337	2007-1-25	2008-1-24
Horn Antenna	Rohde & Schwarz	HF906	100013	2007-1-25	2008-1-24
50 ohm Coaxial Cable	ETS	SUCOFLEX 104	25498514	2007-1-25	2008-1-24
3m chamber	Albatross Projects	9X6X6	----	2007-1-25	2008-1-4

Statement of Traceability: All calibrations have been performed per the NVLAP requirements traceable to the NIST.

4.4 Test Procedure

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.205 15.231(b) and FCC Part 15.209 Limit.



4.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant.Loss} + \text{Cab. Loss} - \text{Ampl.Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15.231 Limit}$$

4.6 Environmental Conditions

Temperature:	21° C
Relative Humidity:	50%
ATM Pressure:	1011 mbar

4.7 Summary of Test Results/Plots

According to the data below, the FCC Part 15.205, 15.209 and 15.231 standards, and had the worst margin of:


-9.50 dB μ V at 315.05 MHz in the Horizontal polarization, 30 MHz to 18 GHz, 3Meters

Frequency MHz	Meter Reading dBuV	Detector	Direction Degree	Height Meter	Polar H / V	Antenna Loss dB	Cable loss dB	Amplifier Gain dB	Corr. Ampl. dBuV/m	FCC Part 15.231 & 15.209	
										Limit dBuV/m	Margin dB
315.05	75.1	AV(Fun.)	135	1.0	H	14.4	1.7	25.05	66.1	75.62	-9.5
315.05	72.5	AV(Fun.)	45	1.0	V	14.4	1.7	25.05	63.5	75.62	-12.1
630.10	43.6	AV	43	2.0	V	19.6	2.8	25.86	40.1	55.62	-15.5
945.15	36.3	AV	66	1.2	V	23.4	3.6	24.58	38.7	55.62	-16.9
315.05	81.1	PK(Fun.)	135	1.0	H	14.4	1.7	25.05	72.1	95.62	-23.5
315.05	78.5	PK(Fun.)	45	1.0	V	14.4	1.7	25.05	69.5	95.62	-26.1
630.10	30.7	AV	90	1.3	H	19.6	2.8	25.86	27.2	55.62	-28.4
945.15	24.7	AV	135	1.2	H	23.4	3.6	24.58	27.1	55.62	-28.5
630.10	49.6	PK	43	2.0	V	19.6	2.8	25.86	46.1	75.62	-29.5
945.15	42.3	PK	66	1.2	V	23.4	3.6	24.58	44.7	75.62	-30.9
630.10	36.7	PK	90	1.3	H	19.6	2.8	25.86	33.2	75.62	-42.4
945.15	30.7	PK	135	1.2	H	23.4	3.6	24.58	33.1	75.62	-42.5

Note: The EUT was tested in all three orthogonal planes and frequency rang 30MHz to the tenth harmonics.

Emissions attenuated closely to the noise base are not reported.

Plot of Radiation Emissions Test (Below 1GHz)



5. §15.231(c) 20dB BANDWIDTH TESTING

5.1 Standard Applicable

According to FCC 15.231(c), The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier.

5.2 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date	Due. Date
Agilent	Spectrum Analyzer	E4402B	US41192821	2007-1-20	2008-1-19
ETS	Receiver Antenna	2175	57337	2007-1-26	2008-1-25
ETS	50 ohm Coaxial Cable	SUCOFLEX 104	25498514	2007-1-26	2008-1-25

Statement of Traceability: All calibrations have been performed per the NVLAP requirements traceable to the NIST.

5.3 Test Procedure

With the EUT's antenna attached, the EUT's 20dB Bandwidth power was received by the test antenna, which was connected to the spectrum analyzer with the START, and STOP frequencies set to the EUT's operation band.

5.4 Environmental Conditions

Temperature:	21° C
Relative Humidity:	52%
ATM Pressure:	1011 mbar


5.5 Summary of Test Results/Plots

Frequency MHz	20dB Bandwidth KHz	Limit KHz
315.05	71.07	787.6

$$\text{Limit} = \text{Frequency} \times 0.25\% = 315.05 \times 0.25\% = 787.6 \text{ KHz}$$

Test Result Pass

Refer to the attached plots.



6. §15.231(a)-DEACTIVATION TESTING

6.1 Standard Applicable

According to FCC 15.231 (a)(1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

(2) A transmitter activated automatically shall cease transmission within 5 seconds after activation.

6.2 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date	Due. Date
Agilent	Spectrum Analyzer	E4402B	US41192821	2007-1-20	2008-1-19
Receiver Antenna	ETS	2175	57337	2007-1-26	2008-1-25
50 ohm Coaxial Cable	ETS	SUCOFLEX 104	25498514	2007-1-26	2008-1-25

Statement of Traceability: All calibrations have been performed per the NVLAP requirements traceable to the NIST.

6.3 Test Procedure

With the EUT's antenna attached, the EUT's output signal was received by the test antenna, which was connected to the spectrum analyzer. Set the center frequency to 315.05MHz, than set the spectrum analyzer to Zero Span for the release time reading.


6.4 Environmental Conditions

Temperature:	20° C
Relative Humidity:	52%
ATM Pressure:	1011 mbar

6.5 Summary of Test Results/Plots

Refer to the attached plots.

Deactive Time=2.275s <5s



Transmitting is released even keep pressing, it is manual operation device.

Result: Pass