



TEST REPORT

Applicant	Grandex International Development Limited
Address	Unit 2401, Million Fortune Industrial Centre, 34-36 Chai Wan Kok Street, Tsuen Wan N.T. Hong Kong

Manufacturer or Supplier	Shantou Dihua Trading Co., Ltd.	
Address	No.71 Hengshan Road, Shantou City, Guangdong, China.	
Product	R/C Full Function Vehicle	
Brand Name	N/A	
Model	61222	
Additional Model & Model Difference:	61223; See item 3.1	
Date of tests	Jun.11 ~ Jun. 17, 2014	

the tests have been carried out according to the requirements of the following standards:

▼ FCC Part 15, Subpart C, Section 15.227(2012-10)

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Venless Long Project Engineer / EMC Department	Approved by Glyn He Supervisor / EMC Department	
Venhess	at of	
	Date: Jun. 20, 2014	

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



TABLE OF CONTENTS

R	ELEA	ASE (CONTROL RECORD	3
1	SU	IMM <i>A</i>	ARY OF TEST RESULTS	4
2	ME	EASU	JREMENT UNCERTAINTY	4
3	GE	NER	AL INFORMATION	5
	3.1	GEN	NERAL DESCRIPTION OF EUT	5
	3.2	DES	SCRIPTION OF TEST MODES	6
	3.3	GEI	NERAL DESCRIPTION OF APPLIED STANDARDS	6
	3.4	DES	SCRIPTION OF SUPPORT UNITS	6
4	TE	ST T	YPES AND RESULTS	7
	4.1	RAE	DIATED EMISSION MEASUREMENT	7
	4.	1.1	LIMITS OF RADIATED EMISSION MEASUREMENT	7
	4.	1.2	TEST INSTRUMENTS	8
	4.	1.3	TEST PROCEDURES	9
	4.	1.4	DEVIATION FROM TEST STANDARD	9
	4.	1.5	TEST SETUP	10
	4.	1.6	EUT OPERATING CONDITIONS	.11
	4.	1.7	TEST RESULTS	11
	4.2	20d	B BANDWIDTH MEASUREMENT	. 16
	4	.2.1	LIMITS OF 20dB BANDWIDTH MEASUREMENT	16
	4	.2.2	TEST INSTRUMENTS	16
	4	.2.3	TEST PROCEDURE	
	4	.2.4	DEVIATION FROM TEST STANDARD	
	4	.2.5	TEST SETUP	
	4	.2.6	EUT OPERATING CONDITIONS	
	-	.2.7	TEST RESULTS	
5	PH	ото	GRAPHS OF THE TEST CONFIGURATION	19
6	AP	PEN	DIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EU	T

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080 Email: <u>DGservice@cn.bureauveritas.com</u>



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF140611N024	Original release	Jun. 20, 2014

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080 Email: <u>DGservice@cn.bureauveritas.com</u>

Page 3 of 20



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C , SECTION 15.227(2012-10)					
STANDARD SECTION TEST TYPE AND LIMIT RESULT REMARK					
§15.207 (a)	Conducted Emission	N/A	EUT is powered by battery		
§15.209 §15.227	Radiated Emission	PASS	Compliant		
§15.215(c)	20dB Bandwidth Test	PASS	Compliant		

2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY	
Conducted emissions	9kHz~30MHz	2.67dB	
	9KHz ~ 30MHz	2.74dB	
Radiated emissions	30MHz ~ 1GHz	4.36dB	
Nadiated emissions	1GHz ~ 18GHz	3.9dB	
	18GHz ~ 40GHz	1.94dB	

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

Page 4 of 20

Fax: +86 769 8593 1080 Email: DGservice@cn.bureauveritas.com



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	R/C Full Function Vehicle		
MODEL NO.	61222		
FCC ID	VC961222127		
NOMINAL VOLTAGE	DC 3V by Battery		
MODULATION TYPE	ASK		
OPERATING FREQUENCY	27.145MHz		
NUMBER OF CHANNEL	1		
ANTENNA TYPE	Wire Antenna		
I/O PORTS	N/A		
CABLE SUPPLIED	N/A		

NOTE:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- 2. For the test results, the EUT had been tested with all conditions, but only the worst case was shown in test report.
- 3. Please refer to the EUT photo document (Reference No.:140611N024) for detailed product photo.
- 4. Additional model 61223 is identical with the test model 61222 except the model number for marketing purpose.

Fax: +86 769 8593 1080 Email: DGservice@cn.bureauveritas.com

Tel: +86 769 8593 5656

Page 5 of 20 Report Version 1



3.2 DESCRIPTION OF TEST MODES

The EUT was tested under the following mode.

FREQUENCY	TEST MODES	
27.145 MHz	Transmitting	

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, 15.227(2012-10) ANSI C63.4-2003 ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit without any other necessary accessories or support units.

Email: DGservice@cn.bureauveritas.com

Tel: +86 769 8593 5656

Fax: +86 769 8593 1080

Page 6 of 20 Report Version 1



4 TEST TYPES AND RESULTS

4.1 RADIATED EMISSION MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

According to §15.227(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Frequency Range of Fundamental [MHz]	Field Strength of Fundamental Emission [Peak] [µV/m]	Field Strength of Fundamental Emission [Average] [µV/m]
26.96 – 27.28	100,000 (100 dBμV/m)	10,000 (80 dBμV/m)

NOTE:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Tel: +86 769 8593 5656

Fax: +86 769 8593 1080

Email: DGservice@cn.bureauveritas.com



4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESCI	100962	Mar. 06,14	Mar. 05,15
Loop antenna (9kHz~30MHz)	Daze	ZN30900A	0708	Dec. 05,13	Dec. 04,14
Bilog Antenna (20MHz -2GHz)	Teseq	CBL 6111D	30643	Jul. 27, 13	Jul. 26, 14
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	00062558	Oct. 18, 12	Oct. 17, 14
Horn Antenna (15GHz-40GHz)	SCHWARZBECK	BBHA 9170	BBHA9170242	Feb. 13,14	Feb. 12,15
Pre-Amplifier (9kHz~1GHz)	SONOMA	310D	186955	Mar. 05,14	Mar. 04,15
Pre-Amplifier (100MHz-26.5GHz)	Agilent	8449B	3008A00409	May 13,14	May 12,15
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 04,13	Nov. 03,14
10m Semi-anechoic Chamber	CHANGLING	21.4m*12.1m*8 .8m	NSEMC006	May 15, 14	May 14, 15
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 30, 13	Oct. 29, 14
Test Software	ADT	ADT_Radiated _V7.6.15.9.2	N/A	N/A	N/A

NOTE:

- 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
- 2. The test was performed in "10m Chamber".
- 3. The FCC Site Registration No. is 502831.

Fax: +86 769 8593 1080 Email: DGservice@cn.bureauveritas.com

Page 8 of 20



4.1.3 TEST PROCEDURES

The basic test procedure was in accordance with ANSI C63.4 (section 12).

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meters Semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using new battery. The turntable was rotated to maximize the emission level.
- g. For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1m above the ground.

NOTE:

- 1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
- 3. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
- 4. Margin value = Emission level Limit value.
- 5. Fundamental AV value = PK Emission + AV factor


4.1.4 DEVIATION FROM TEST STANDARD

No deviation




4.1.5 TEST SETUP

Below 30MHz



30MHz~1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

Fax: +86 769 8593 1080 Email: DGservice@cn.bureauveritas.com

Tel: +86 769 8593 5656

ong 523942, China Email: <u>DGservice@cn.bureauveritas.c</u>



4.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power of equipment.
- b. Hold down the TX of button, then the EUT was operating.
- c. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.

4.1.7 TEST RESULTS

FIELD STRENGTH OF FUNDAMENTAL

ANTENNA POLARITY: 0°

N	lo.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
	*	27.14 (PK)	21.92	21.08	43.00	100	-57.00
	*	27.14(AV)	-4.24	-	38.76	80	-41.24

ANTENNA POLARITY: 90°

No.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
*	27.14 (PK)	21.92	43.63	65.55	100	-34.35
*	27.14 (AV)	-4.24	-	61.31	80	-18.69

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).

- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.
- 5. " * ": Fundamental frequency.
- 6. The average value of fundamental frequency is: Average value = Peak value +AV factor, where the AV factor is calculated from following formula: AV factor=20 log (Duty cycle) = 20 log (61.41%) = -4.24dB, Please see page 12~13 for plotted duty.

Fax: +86 769 8593 1080 Email: DGservice@cn.bureauveritas.com

Report Version 1




Duty Cycle:

Tp = 17.6522ms

Ton = Ton1 * Number+ Ton2 * Number =0.49275*10 +1.47826 *4= 10.84054ms

Duty Cycle = Ton / Tp * 100% = 10.84054 / 17.6522 = 61.41%

Tp=17.6522ms




Fax: +86 769 8593 1080 Email: DGservice@cn.bureauveritas.com


Report Version 1



Ton1=0.49275ms



Ton2=1.47826ms



Fax: +86 769 8593 1080 Email: DGservice@cn.bureauveritas.com

Tel: +86 769 8593 5656

Page 13 of 20 Report Version 1




FREQUENCY RANGE	130MHz ~ 1GHz	DETECTOR FUNCTION	Quasi-Peak (QP)
-----------------	---------------	----------------------	-----------------

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M									
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)		
1	31.62	18.6 QP	40.0	-21.5	1.00 H	254	-0.41	18.96		
2	54.25	13.0 QP	40.0	-27.0	1.00 H	154	4.83	8.14		
3	81.73	12.7 QP	40.0	-27.3	1.00 H	116	4.28	8.41		
4	149.63	13.9 QP	43.5	-29.6	1.00 H	197	0.69	13.19		
5	325.85	21.7 QP	46.0	-24.3	1.00 H	177	5.21	16.48		
6	561.88	25.3 QP	46.0	-20.7	1.00 H	276	0.50	24.81		

REMARKS:

- 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.



egdong 523942, China Email: DGservice@cn.bureauveritas.com

Page 14 of 20 Report Version 1

Tel: +86 769 8593 5656

Fax: +86 769 8593 1080




FREQUENCY RANGE	130MHz ~ 1(4Hz	DETECTOR FUNCTION	Quasi-Peak (QP)
-----------------	----------------	----------------------	-----------------

	ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M									
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)		
1	54.25	29.6 QP	40.0	-10.4	1.00 V	217	21.44	8.14		
2	81.73	18.2 QP	40.0	-21.8	1.00 V	183	9.83	8.41		
3	118.92	19.0 QP	43.5	-24.6	1.00 V	93	5.32	13.63		
4	159.33	21.0 QP	43.5	-22.5	1.00 V	163	8.18	12.79		
5	314.53	22.1 QP	46.0	-23.9	1.00 V	145	5.24	16.90		
6	419.62	21.4 QP	46.0	-24.6	1.00 V	117	0.83	20.55		

REMARKS:

- 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.



Fax: +86 769 8593 1080 Email: DGservice@cn.bureauveritas.com

Tel: +86 769 8593 5656

Page 15 of 20 Report Version 1



4.2 20dB BANDWIDTH MEASUREMENT

4.2.1 LIMITS OF 20dB BANDWIDTH MEASUREMENT

According to FCC 15.215(c), must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Spectrum Analyzer (10Hz–40GHz)	Rohde & Schwarz	FSV40	101003	Apr. 09,14	Apr. 08,15
Power Meter	Anritsu	ML2495A	1139001	Feb. 21,14	Feb. 20,15
Power Sensor	Anritsu	MA2411B	1126068	Feb. 21,14	Feb. 20,15
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 30,13	Oct. 29,14
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep. 17,13	Sep. 16,14
Oscilloscope	Agilent	DSO9254A	MY51260160	Oct. 17, 13	Oct. 16, 14
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 25,13	Nov. 24,14

NOTE:

- 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
- 2. The test was performed in RF Oven room.

4.2.3 TEST PROCEDURE


- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.



4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



4.2.6 EUT OPERATING CONDITIONS

Same as item 4.1.6

Fax: +86 769 8593 1080 Email: DGservice@cn.bureauveritas.com

Tel: +86 769 8593 5656


Page 17 of 20 Report Version 1



4.2.7 TEST RESULTS

CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (KHz)
27.145	46.30

Test Data:



Fax: +86 769 8593 1080 Email: DGservice@cn.bureauveritas.com

Tel: +86 769 8593 5656

Page 18 of 20 Report Version 1



5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080 Email: <u>DGservice@cn.bureauveritas.com</u>

Page 19 of 20 Report Version 1



6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---

Fax: +86 769 8593 1080 Email: DGservice@cn.bureauveritas.com

Tel: +86 769 8593 5656

Page 20 of 20 Report Version 1