

W66 N220 Commerce Court ◆ Cedarburg, WI 53012 ◆ USA Phone: 262.375.4400 ◆ Fax: 262.375.4248

www.lsr.com

Compliance Testing of:

Generac® End Station Model VDE 0G6019B

Test Date(s):

October 25th, 2008 & September 22nd – 25th, 2009

Prepared For:

Generac Power Systems

Attn: Steve Wilcox

Hwy. 59 & Hillside Road

P.O. Box 8

Waukesha 53187

Test Report Number:

309366

Project Number:

C-758

In accordance with:

Federal Communications Commission (FCC)
Part 15, Subpart C, Section 15.247
Digital Modulation Transmitters (DTS) Operating in the

Frequency Band 2400 MHz - 2483.5 MHz

Test Project Engineer:

Ryan M. Urness, EMC Laboratory Manager

Signature:

Date: February 1, 2010

Quality Assurance:

Teresa A. White, Quality Manager

Reviewed by:

Khairul Aidi Zainal, Sr. EMC Engineer

Signature:

Date: February 1, 2010

Signature:

Date: February 1, 2010

This Test Report may not be reproduced, except in full, without written approval of LS Research, LLC.

TABLE OF CONTENTS (page 1 of 2)

EXHIBIT 1.	INTRODUCTION 1.1 Scope 1.2 Normative References 1.3 LS Research, LLC Test Facility 1.4 Location of Testing 1.5 Test Equipment Utilized	4 4 5 5 5
EXHIBIT 2.	PERFORMANCE ASSESSMENT 2.1 Client Information 2.2 Equipment Under Test (EUT) Information 2.3 Associated Antenna Description 2.4 EUT's Technical Specifications 2.5 Product Photo	6 6 6 7 8
EXHIBIT 3.	EUT OPERATING CONDITIONS & CONFIGURATIONS DURING TESTS 3.1 Climate Test Conditions 3.2 Applicability & Summary of EMC Emission Test Results 3.3 Modifications Incorporated in the EUT for Compliance Purposes 3.4 Deviations & Exclusions from Test Specifications	9 9 9 9
EXHIBIT 4.	DECLARATION OF CONFORMITY	10
EXHIBIT 5.	RADIATED EMISSIONS TEST 5.1 Test Setup 5.2 Test Procedure 5.3 Test Equipment Utilized 5.4 Test Results	11 11 11 11 12
	 5.5 Calculation of Radiated Emission Measurements 5.6 Radiated Emissions Test Data Chart 5.7 Test Setup Photo(s)-Radiated Emissions Test 5.8 Screen Captures-Radiated Emissions Testing 	12 13-14 15 16-24
EXHIBIT 6.	 5.5 Calculation of Radiated Emission Measurements 5.6 Radiated Emissions Test Data Chart 5.7 Test Setup Photo(s)-Radiated Emissions Test 	12 13-14 15

Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 2 of 48

TABLE OF CONTENTS (Page 2 of 2)

EXHIBIT 8.	BAND 8.1	D-EDGE MEASUREMENTS Method of Measurements	28 28
EXHIBIT 9.	9.1 9.2	Method of Measurements Test Data Test Equipment List Screen Captures – Power Output (Conducted)	29 29 29 30 30-31
EXHIBIT 10.	10.1 10.2 10.3	ER SPECTRAL DENSITY: 15.247(e) Limits Test Equipment List Test Data Screen Captures-Power Spectral Density	32 32 32 32 32 33
EXHIBIT 11.	11.1 11.2	Limits Test Equipment List Test Data Screen Captures-Spurious Radiated Emissions	34 34 34 34 35-37
EXHIBIT 12.	MPE	CALCULATIONS	38
APPENDIX B APPENDIX C	CURF	EQUIPMENT LIST RENT TEST STANDARDS ERTAINTY STATEMENT IFICATIONS OF AVERAGE DUTY FACTOR CALC	39-45 46 47 CULATIONS 48

Prepared For: General	Power Systems Mode	el #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8	036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC	ID #: VDE-0G6019B	Page 3 of 48

EXHIBIT 1. INTRODUCTION

1.1 <u>SCOPE</u>

References:	FCC Part 15, Subpart C, Section 15.247	
1101010110001	FCC Part 2, Section 2.1043 paragraph (b)1.	
Title:	Telecommunication – Code of Federal Regulations,	
riue.	CFR 47, Part 15	
Purpose of Test:	FCC Part 15 Compliance.	
	Both conducted and radiated emissions measurements	
	were conducted in accordance with American National	
Test Procedures:	Standards Institute ANSI C63.4 – American National	
rest Procedures:	Standard for Methods of Measurement of Radio-Noise	
	Emissions from Low-Voltage Electrical and Electronic	
	Equipment in the Range of 9 kHz to 40 GHz.	
Environmental Classification:	Commercial, Industrial or Business	
Environmental Classification:	Residential	

1.2 NORMATIVE REFERENCES

Publication	Year	Title
47 CFR, Parts 0-15 (FCC)	2007 & 2008	Code of Federal Regulations - Telecommunications
ANSI C63.4	2003	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.
CISPR 16-1-1	2006-03 A1: 2006-09 A2: 2007-07	Specification for radio disturbance and immunity measuring apparatus and methods. Part 1-1: Measuring Apparatus.
CISPR 16-2-1	2003 A1: 2004-04 A2: 2007-07	Specification for radio disturbance and immunity measuring apparatus and methods. Part 201: Conducted disturbance measurement.
FCC Public Notice DA 00-1407	2000	Part 15 Unlicensed Modular Transmitter Approval
FCC ET Docket No. 99-231	2002	Amendment to FCC Part 15 of the Commission's Rules Regarding Spread Spectrum Devices.
FCC Procedures	2007 and 2008	Measurement of Digital Transmission Systems operating under Section 15.247.

Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 4 of 48

1.3 LS Research, LLC TEST FACILITY

LS Research, LLC is accredited by A2LA (American Association for Laboratory Accreditation) to conform to ISO/IEC 17025, 2005 "General Requirements for the Competence of Calibration and Testing Laboratories".

LS Research, LLC's scope of accreditation includes all test methods listed herein, unless otherwise noted. A copy of the accreditation may be accessed on our web site: www.lsr.com. Accreditation status can be verified at A2LA's web site: www.a2la2.net.

1.4 LOCATION OF TESTING

All testing was performed at LS Research, LLC, W66 N220 Commerce Court, Cedarburg, Wisconsin, 53012 USA, utilizing the facilities listed below, unless otherwise noted.

List of Facilities Located at LS Research, LLC:

- Compact Chamber
- Semi-Anechoic Chamber
- Open Area Test Site (OATS)

1.5 TEST EQUIPMENT UTILIZED

A complete list of equipment utilized in testing is provided in Appendix A of this test report. Calibration dates are indicated in Appendix A. All test equipment is calibrated in accordance with A2LA standards.

Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 5 of 48

EXHIBIT 2. PERFORMANCE ASSESSMENT

2.1 CLIENT INFORMATION

Manufacturer Name:	Generac Power Systems
	Hwy. 59 & Hillside Road
	P.O. Box 8
Address:	Waukesha, WI 53187

2.2 EQUIPMENT UNDER TEST (EUT) INFORMATION

The following information has been supplied by the applicant.

Product Name:	End Station
Model Number:	0G6019B
Serial Number:	0G5282PROTOF2

Note: The End station is ALWAYS powered by a 5 volt regulated power supply resident on the generator control PCB. It says this quite clearly in the technical write up. The generator control board gets its power from the engine start battery and it is charged by the charger alternator on the engine in the same way a car battery is charged. When the engine is not running, the engine start battery is charged by a 2.5 amp charger fed from the utility supply. The power ultimately fed to the End Station has been converted and buffered by several different means before it gets to the End Station and it does not require the presence of the Utility supply to function.

2.3 ASSOCIATED ANTENNA DESCRIPTION

Antenna is an integral inverted F type.

Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 6 of 48

2.4 <u>EUT'S TECHNICAL SPECIFICATIONS</u>

Additional Information:

	T = = =
Frequency Range (in MHz)	2405 MHz – 2440 MHz
RF Power in Watts	0.034 W
Conducted Output Power (in dBm)	15.32 dBm
Field Strength (and at what distance)	110.81dBµV/m @ 3m
Occupied Bandwidth (99% BW)	2680 kHz
Type of Modulation	DTS
Emission Designator	2M68F1D
EIRP (in mW)	36.14mW
Transmitter Spurious (worst case)	60.48dbµV/m @ 3m (4810MHz)
Frequency Tolerance %, Hz, ppm	<100 ppm
Microprocessor Model # (if applicable)	Freescale MC13213
Antenna Information	
Detachable/non-detachable	Non-Detachable
Туре	Inverted F
Gain (in dBi)	0.25dBi
EUT will be operated under FCC Rule	
Part(s)	15§247
Modular Filing	☐ Yes ☐ No
Fixed, Portable, or Mobile?	Fixed

RF Technical Information:

Type of		SAR Evaluation: Device Used in the Vicinity of the Human Head
Evaluation		SAR Evaluation: Body-worn Device
(check one)	Х	RF Evaluation

If <u>RF Evaluation</u> checked above, test engineer to complete the following:

•	Evaluated against exposure lim	its: 🛛 Genera	al Public Use	Controlled Use
•	Duty Cycle used in evaluation:	100 %		
•	Standard used for evaluation:	CFR 47	Part 15 §247	
•	Measurement Distance:	20cm		
•	RF Value:	.07173		
	□ V/m	A/m	₩/m²	
	☐ Measured ☐	Computed	□ Calculated	

Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 7 of 48

2.5 PRODUCT PHOTO





Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 8 of 48

EXHIBIT 3. EUT OPERATING CONDITIONS & CONFIGURATIONS DURING TESTS

3.1 CLIMATE TEST CONDITIONS

Temperature:	26°C
Humidity:	44%
Pressure:	769.62

3.2 APPLICABILITY & SUMMARY OF EMC EMISSION TEST RESULTS

FCC Paragraph	Test Requirements	Compliance (yes/no)
15.207	Power Line Conducted Emissions Measurements	N/A
15.247(a)(2)	6 dB Bandwidth of a Digital Modulation System	Yes
15.247(b) & 1.1310	Maximum Output Power	Yes
15.247(i), 1.1307, 1.1310, 2.1091 & 2.1093	RF Exposure Limit	Yes
15.247(c)	RF Conducted Spurious Emissions at the Transmitter Antenna Terminal	Yes
15.247(d)	Transmitted Power Spectral Density of a Digital Modulation System	Yes
15.247(c), 15.209 & 15.205	Transmitter Radiated Emissions	Yes

The digital circuit portion of the EUT has been tested and verified to comply with FCC Part 15, Subpart B, Class B Digital Devices and the associated Radio Receiver has also been tested and found to comply with Part 15, Subpart B – Radio Receivers. The Receiver Test Report is available upon request

3.3	MODIFICATIO	<u>INS INCORPORATED IN THE EUT FOR COMPLIANCE PURPOSES</u>
	None	

The Output Power during all testing was lowered to the setting "7" to ensure compliance to PSD, Band Edge, and Spurious Harmonics.

Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 9 of 48

EXHIBIT 4. DECLARATION OF CONFORMITY

The EUT was found to MEET the requirements as described within the specification of FCC Title 47, CFR Part 15.247, and Industry Canada RSS-210, Issue 7 (2007), Section Annex 8 (section 8.2) for a Digital Spread Spectrum (DTS) Transmitter.

If some emissions are seen to be within 3 dB of their respective limits:

As these levels are within the tolerances of the test equipment and site employed, there is a possibility that this unit, or a similar unit selected out of production may not meet the required limit specification if tested by another agency.

LS Research, LLC certifies that the data contained herein was taken under conditions that meet or exceed the requirements of the test specifications. The results in this Test Report apply only to the item(s) tested on the above-specified dates. Any modifications made to the EUT subsequent to the indicated test date(s) will invalidate the data herein, and void this certification.

Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 10 of 48

EXHIBIT 5. RADIATED EMISSIONS TEST

5.1 <u>Test Setup</u>

The test setup was assembled in accordance with Title 47, CFR FCC Part 15 and ANSI C63.4. The EUT was placed on an 80cm high non-conductive pedestal, centered on a flush mounted 2-meter diameter turntable inside a 3 meter Semi-Anechoic, FCC listed Chamber. The EUT was operated in continuous transmit mode, using power as provided by a laboratory grade DC switch-mode power supply. The unit has the capability to operate on 8 channels, controllable via an RS-232 Communication port on a laptop PC.

The applicable limits apply at a 3 meter distance. Measurements from 5-25 GHz were performed at a 1.0 meter separation distance. The calculations to determine these limits are detailed in the following pages. Please refer to Appendix A for a complete list of test equipment. The test sample was operated on one of three (3) standard channels: low (2405 MHz), middle (2420 MHz) and high (2440 MHz) to comply with FCC Part 15.35. The channels and operating modes were changed via the PC communication port using HyperTerminal.

5.2 <u>Test Procedure</u>

Radiated RF measurements were performed on the EUT in a 3 meter Semi-Anechoic, FCC listed Chamber. The frequency range from 30 MHz to 25000 MHz was scanned and investigated. The radiated RF emission levels were manually noted at the various fixed degree settings of azimuth on the turntable and antenna height. The EUT was placed on a non-conductive pedestal in the 3 meter Semi-Anechoic Chamber, with the antenna mast placed such that the antenna was 3 meters from the EUT. A Biconical Antenna was used to measure emissions from 30 MHz to 300 MHz, and a Log Periodic Antenna was used to measure emissions from 300 MHz to 1000 MHz. A Double-Ridged Waveguide Horn Antenna was used from 1 GHz to 18 GHz, and a standard gain Horn Antenna and pre-amplifier was used for 18 GHz to 25 GHz. The maximum radiated RF emissions were found by raising and lowering the antenna between 1 and 4 meters in height, using both horizontal and vertical antenna polarities.

5.3 <u>Test Equipment Utilized</u>

A list of the test equipment and antennas utilized for the Radiated Emissions test can be found in Appendix A. This list includes calibration information and equipment descriptions. All equipment is calibrated and used according to the operation manuals supplied by the manufacturers. All calibrations of the antennas used were performed at an N.I.S.T. traceable site. In addition, the Connecting Cables were measured for losses using a calibrated Signal Generator and an Agilent E4445A/N9039A EMI Receiver. The resulting correction factors and the cable loss factors from these calibrations were entered into the Agilent E4445A/N9039AEMI Receiver database. As a result, the data taken from the Agilent E4445A/N9039A EMI Receiver accounts for the antenna correction factor as well as cable loss or other corrections, and can therefore be entered into the database as a corrected meter reading. The Agilent E4445A/N9039A EMI Receiver was operated with a resolution bandwidth of 120 kHz for measurements below 1 GHz (video bandwidth of 300 kHz), and a bandwidth of 1 MHz for measurements above 1 GHz (video bandwidth of 1 MHz). From 4 GHz to 18 GHz, an HP E4446A Spectrum Analyzer and an EMCO Horn Antenna were used. From 18 GHz to 25 GHz, the HP E4446A Spectrum Analyzer with a standard gain horn, and preamp were used.

Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 11 of 48

5.4 Test Results

The EUT was found to **MEET** the Radiated Emissions requirements of Title 47 CFR, FCC Part 15.247 for a DTS transmitter [Canada RSS-210), Annex 8 (section 8.2). The frequencies with significant RF signal strength were recorded and plotted as shown in the Data Charts and Graphs.

5.5 CALCULATION OF RADIATED EMISSIONS LIMITS

The maximum peak output power of an intentional radiator in the 2400-2483.5 MHz band, as specified in Title 47 CFR 15.247 (b)(3), is 1 Watt. The harmonic and spurious RF emissions, as measured in any 100 kHz bandwidth, as specified in 15.247 (d), shall be at least 20 dB below the measured power of the desired signal, and must also meet the requirements described in 15.205(c).

The following table depicts the general radiated emission limits above 30 MHz. These limits are obtained from Title 47 CFR, Part 15.209, for radiated emissions measurements. These limits were applied to any signals found in the 15.205 restricted bands.

Frequency (MHz)	3 m Limit μV/m	3 m Limit (dBμV/m)	1 m Limit (dBµV/m)
30-88	100	40.0	-
88-216	150	43.5	-
216-960	200	46.0	-
960-24,000	500	54.0	63.5

Sample conversion from field strength μ V/m to dB μ V/m: dB μ V/m = 20 log ₁₀ (100) = 40 dB μ V/m (from 30-88 MHz)

For measurements made at 1.0 meter, a 9.5 dB correction has been invoked.

960 MHz to 10,000 MHz $500\mu\text{V/m or }54.0~\text{dB/}\mu\text{V/m at }3~\text{meters}$ $54.0~+~9.5~=~63.5~\text{dB/}\mu\text{V/m at }1~\text{meter}$

Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 12 of 48

3 Meter Measurements of Electromagnetic Radiated Emissions Test Standard: 47CFR, Part 15.205 and 15.247(DTS) Frequency Range Inspected: 30 MHz to 25000 MHz

reduction rearrige independent of this is to see this is							
Manufacturer:	Ger	Generac Power Systems					
Date(s) of Test:	Oct	ober 25 th , 2008 & Septem	ber 2	22 nd – 2	25 th , 2009		
Test Engineer(s):	Rya	ın Urness					
Voltage:	5 VI	DC					
Operation Mode:	con	tinuous transmit					
Environmental	Ten	Temperature: 20 – 25° C					
Conditions in the Lab:	Relative Humidity: 30 – 60 %						
		Single PhaseVAC			3 Phase _	VA	С
EUT Power:		Battery		Х	Other: 5V DC		
EUT Placement:	Х	80cm non-conductive ta	ble		10cm Spacers		
EUT Test		3 Meter Semi-Anechoic FCC					
Location:	Х	Listed Chamber			3/10m OATS		
Measurements:		Pre-Compliance	Pre-Compliance I		ninary	X	Final
Detectors Used:	Х	Peak	Χ	Quasi	-Peak	Х	Average

The following table depicts the level of significant spurious radiated RF emissions found:

Frequency (MHz)	Ant./EUT Polarity	Height (meters)	Azimuth (0° - 360°)	Measured EFI (dBμV/m)	15.205 Limit (dBμV/m)	Margin (dB)
299.5	Horiz	1.00	360°	24.3	46.0	21.7
299.5	Vert	1.00	360°	23.0	46.0	23.0
960.7	Horiz	1.00	360°	27.6	54.0	26.4
925.6	Vert	1.00	360°	26.5	46.0	19.5
2379	Horiz	1.00	360°	40.9	54.0	13.1
2302	Vert	1.00	360°	41.1	54.0	12.9

Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 13 of 48

RADIATED EMISSIONS DATA CHART (continued)
The following table depicts the level of significant radiated RF fundamental and harmonic emissions seen on Channel 0:

				Measured	15.247		Measured
Frequency	EUT/Ant.	Height	Azimuth	EFI	Limit	Margin	Peak EFI
(MHz)	Polarity	(cm)	(0° - 360°)	(dBμV/m)	(dB _µ V/m)	(dB)	(dBμV/m)
2405	F/H	112	222°	110.81	125.23	14.42	114.7
4809	F/H	102	247°	60.48	63.5	3.02	69.33
7216	F/H	113	50°	43.00	100.81	57.81	53.31
9621	V/H	109	228°	39.33	100.81	61.48	49.77
12024	V/H	110	168°	38.76	63.5	24.74	50.55
14428	F/H	104	6°	39.75	100.81	61.06	51.02
16834	V/H	106	6°	40.10	100.81	60.71	52.46
19240		1		Note 3	63.5		
21645		-		Note 3	100.81		
24050		-		Note 3	100.81		

The following table depicts the level of significant radiated RF fundamental and harmonic emissions seen on Channel 3:

, and a second		,		Measured	15.247		Measured
Frequency	Ant.	Height	Azimuth	EFI	Limit	Margin	Peak EFI
(MHz)	Polarity	(cm)	(0° - 360°)	(dBμV/m)	(dBμV/m)	(dB)	(dBμV/m)
2420	F/H	112	220°	110.68	125.23	14.55	114.4
4839	F/H	103	292°	54.08	63.5	9.42	63.40
7259	F/H	118	238°	43.60	63.5	19.9	53.44
9682	F/H	108	280°	39.65	100.68	61.03	50.24
12096	F/H	103	290°	39.20	63.5	24.3	50.32
14516	F/H	104	4°	39.84	100.68	60.84	51.59
16940	F/H	104	28°	41.20	100.68	59.48	53.48
19360	-	-		Note 3	63.5	1	-
21780	-	-		Note 3	100.68		-
24200	-	-		Note 3	100.68		-

The following table depicts the level of significant radiated RF fundamental and harmonic emissions seen on Channel 7:

_				Measured	15.247		Measured
Frequency	Ant.	Height	Azimuth	EFI	Limit	Margin	Peak EFI
(MHz)	Polarity	(cm)	(0° - 360°)	(dBμV/m)	(dBμV/m)	(dB)	(dBμV/m)
2440	F/H	110	240°	109.37	125.23	15.86	113.15
4879	F/H	100	22°	55.62	63.5	7.88	64.96
7321	F/H	112	228°	41.31	63.5	22.19	51.20
9758	V/H	104	251°	41.18	99.37	58.19	50.94
12198	V/H	103	146°	40.18	63.5	23.32	51.61
14640	F/H	106	5°	39.74	99.37	59.63	52.85
17082	F/H	103	9°	42.75	99.37	56.62	54.97
19520				Note 3	63.5		
21960				Note 3	99.37		
24400				Note 3	99.37		

Notes:

- A Quasi-Peak Detector was used in measurements below 1 GHz, an average detector was used from 1-4GHz, and a Peak Detector with a 10Hz video averaging was used in measurements above 4 GHz. A Peak detector was also used (without video averaging) to ensure the peak emissions did not exceed 20 dB above the limits.
- Measurements above 4 GHz were made at 1 meters of separation from the EUT.
- Measurement at receiver system noise floor.
- All Peak measurements were within 20dB from average measurements

Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 14 of 48

5.7 <u>Test Setup Photo(s) – Radiated Emissions Test</u>






Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 15 of 48

5.8 Screen Captures - Radiated Emissions Testing


These screen captures represent Peak Emissions. For radiated emission measurements, a Quasi-Peak detector function is utilized when measuring frequencies below 1 GHz, and a Video-Averaged Peak detector function is utilized when measuring frequencies above 1 GHz.

The signature scans shown here are from worst-case emissions, as measured on channels 0, 3, or 7, with the sense antenna both in vertical and horizontal polarity for worst case presentations.

Antenna Vertically Polarized, 30-300 MHz, at 3m




Antenna Vertically Polarized, 300-1000 MHz, at 3m




Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 16 of 48

Antenna Vertically Polarized, 1000-2400 MHz, at 3m




Antenna Vertically Polarized, 2483.5-4000 MHz, at 3m




Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 17 of 48

Antenna Vertically Polarized, 4000-18000 MHz, at 1m




Antenna Vertically Polarized, 18000-25000 MHz, at 1m




Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 18 of 48

Antenna Horizontally Polarized, 30-300 MHz, at 3m




Antenna Horizontally Polarized, 300-1000 MHz, at 3m




Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 19 of 48

Antenna Horizontally Polarized, 1000-2400 MHz, at 3m




Antenna Horizontally Polarized, 2483.5-4000 MHz, at 3m




Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 20 of 48

Antenna Horizontally Polarized, 4000-18000 MHz, at 1m




Antenna Horizontally Polarized, 18000-25000 MHz, at 30cm



Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 21 of 48

<u>Screen Captures - Radiated Emissions Testing</u> (continued)

Antenna Horizontally Polarized, 2440 MHz, at 3m



Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 22 of 48

EXHIBIT 6. CONDUCTED EMISSIONS TEST, AC POWER LINE: 15.207

6.1 <u>Test Results</u>

The EUT is powered via a laboratory grade DC power supply; thus, conducted emissions test for the AC power line is not applicable. (Reference Exhibit 2 Section 2 of this document).

Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 23 of 48

EXHIBIT 7. OCCUPIED BANDWIDTH: 15.247(a)(2)

7.1 Limits

For a Digital Modulation System, the 6 dB bandwidth shall be at least 500 kHz.

7.2 <u>Method of Measurements</u>

Refer to ANSI C63.4 and FCC Procedures for Digital Transmission Systems operating under 15.247.

The transmitter output was connected to the Spectrum Analyzer. The bandwidth of the fundamental frequency was measured with the Spectrum Analyzer using 100 kHz RBW and VBW=100 kHz.

The bandwidth requirement found in FCC Part 15.247(a)(2) requires a minimum -6dBc occupied bandwidth of 500 kHz. For this portion of the tests, a direct measurement of the transmitted signal was performed at the antenna port of the EUT, via a cable connection to the HP E4446A spectrum analyzer. An attenuator was placed in series with the cable to protect the spectrum analyzer. The loss from the cable and the attenuator were added on the analyzer as gain offset settings, there by allowing direct measurements, without the need for any further corrections. A Hewlett Packard model E4446AB spectrum analyzer was used with the resolution bandwidth set to 100 kHz for this portion of the tests. The EUT was configured to run in a continuous transmit mode, while being supplied with typical data as a modulation source. The spectrum analyzer was used in peak-hold mode while measurements were made, as presented in the chart below.

From this data, the closest measurement when compared to the specified limit is 1570 kHz, which is above the minimum of 500 kHz.

7.3 Test Data


Channel	Center Frequency (MHz)	Measured -6 dBc Occ. BW (kHz)	Minimum -6 dBc Limit (kHz)	Measured -20 dBc Occ.Bw (kHz)
0	2405	1610	500	2680
3	2420	1570	500	2660
7	2440	1590	500	2650


7.4 <u>Test Equipment List</u>

Test Equipment	Manufacturer	Model No.	Serial No.
Spectrum Analyzer	Agilent	E4407B	US39160256
Spectrum Analyzer	Agilent	E4446A	US45300564


Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 24 of 48

7.5 Screen Captures - OCCUPIED BANDWIDTH






Channel 3 Occupied Bandwidth



Channel 7 Occupied Bandwidth



Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 25 of 48

EXHIBIT 8.BAND-EDGE MEASUREMENTS


8.1 Method of Measurements

FCC 15.209(b) and 15.247(d) require a measurement of spurious emission levels to be at least 20 dB lower than the fundamental emission level, in particular at the Band-Edges where the intentional radiator operates. The following screen captures demonstrate compliance of the intentional radiator at the 2400-2483.5 MHz Band-Edges. The EUT was operated in continuous transmit mode with continuous modulation, with internally generated data as the modulating source. The EUT was operated at the lowest channel for the investigation of the lower Band-Edge, and at the highest channel for the investigation of the higher Band-Edge.

Note: Peak readings were verified to ensure measurements were less than 20dB from the average reading.


The Lower Band-Edge limit, in this case, would be -20 dBc with respect to the fundamental level. The Upper Band-Edge limit, in this case, would be + 54 dB μ V/m at 3m.

Screen Capture Demonstrating Compliance at the Lower Band-Edge



Note: Lower Band-edge compliance recognized at 2390MHz with 20dB relaxation factor

Screen Capture Demonstrating Compliance at the Higher Band-Edge



Note: Upper Band-edge Measurement = 43.89dbµV/m (Average Detector)

Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 26 of 48


EXHIBIT 9. POWER OUTPUT (CONDUCTED): 15.247(b)

9.1 Method of Measurements

The conducted RF output power of the EUT was measured at the antenna port using a short RF cable along with an attenuator as protection for the spectrum analyzer. The loss from the cable and the attenuator were added on the analyzer as gain offset settings, thereby allowing direct measurements without the need for any further corrections. The unit was configured to run in a continuous transmit mode, while being supplied with typical data as a modulation source. The spectrum analyzer was used with resolution and video bandwidths set to 3 MHz, and a span of 5 MHz, with measurements from a peak detector presented in the chart below.

9.2 Test Data

CHANNEL	CENTER FREQ (MHz)	LIMIT (dBm)	MEASURED POWER (dBm)	MARGIN (dB)
0	2405	+30 dBm	14.66	15.34
3	2420	+30 dBm	15.22	14.78
7	2440	+30 dBm	15.32	14.68



Measured RF Power Output (in milliwatts): 34.0

Declared RF Power Output (in milliwatts): 100


Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 27 of 48

9.3 <u>Test Equipment List</u>


Test Equipment	Manufacturer	Model No.	Serial No.
Spectrum Analyzer	Agilent	E4407B	US39160256
Spectrum Analyzer	Agilent	E4446A	US45300564

9.4 <u>Screen Captures – Power Output (Conducted)</u>






Channel 3



Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 28 of 48

<u>Screen Captures – Power Output (Conducted) (continued)</u>

Channel 7



Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 29 of 48

EXHIBIT 10. POWER SPECTRAL DENSITY: 15.247(e)

10.1 <u>Limits</u>

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

In accordance with FCC Part 15.247(e), the peak power spectral density should not exceed +8 dBm in any 3 kHz band. This measurement was performed along with the conducted power output readings performed as described in previous sections. The peak output frequency for each representative frequency was scanned, with a narrow bandwidth, and reduced sweep, and a power density measurement was performed. The highest density was found to be no greater than 3.36 dBm, which is under the allowable limit by 4.64 dB.

10.2 <u>Test Equipment List</u>

Test Equipment	Manufacturer	Model No.	Serial No.
Spectrum Analyzer	Agilent	E4407B	US39160256
Spectrum Analyzer	Agilent	E4446A	US45300564


10.3 Test Data

Transmitter Channel	Frequency (MHz)	RF Power Level In 3 kHz BW (dBm/3 kHz)	Limit (dBm/3 kHz)	Margin (dB)	Comments Pass/Fail
Lowest	2405	0.20	8.0	7.80	Pass
Middle	2420	0.24	8.0	7.76	Pass
Highest	2440	1.303	8.0	6.69	Pass


Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 30 of 48

10.4 <u>Screen Captures – Power Spectral Density</u>


Channel 0



Channel 3



Channel 7



Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 31 of 48

EXHIBIT 11. SPURIOUS EMISSIONS: 15.247(d)

11.1 <u>Limits</u>

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 db below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted measurement.

Remarks:

• The emission limits as specified above are based on measurement instrument employing an average detector. The provisions in Section 15.35 for limiting peak emissions apply.

FCC Part 15.247(d) requires a measurement of conducted harmonic and spurious RF emission levels, as reference to the carrier level when measured in a 100 kHz bandwidth. For this test, the spurious and harmonic RF emissions from the EUT were measured at the EUT antenna port using a short RF cable along with an attenuator as protection for the spectrum analyzer. The loss from the cable and the attenuator were added on the analyzer as gain offset settings, there by allowing direct readings of the measurements made without the need for any further corrections. A Hewlett Packard model E4446A spectrum analyzer was used with the resolution bandwidth set to 100 kHz for this portion of the tests. The unit was configured to run in a continuous transmit mode, while being supplied with typical data as a modulation source. The spectrum analyzer was used with measurements from a peak detector presented in the chart below. Screen captures were acquired and any noticeable spurious and harmonic signals were identified and measured.

11.2 Test Equipment List

Test Equipment	Manufacturer	Model No.	Serial No.
Spectrum Analyzer	Agilent	E4446A	US45300564

11.3 Test Data

Fundamental Frequency: 2400MHz, 2420MHz, 2440 MHz

Modulation: DTS

Frequency Test Range: 2400-2483.5 MHz

	Channel 0	Channel 3	Channel 7
Fundamental	10.74	11.45	11.85
2 nd Harmonic	-25.45	-25.28	-25.52
3 rd Harmonic	-47.44	-45.04	-42.73
4 th Harmonic	Note 1	Note 1	Note 1
5 th Harmonic	Note 1	Note 1	Note 1
6 th Harmonic	Note 1	Note 1	Note 1
7 th Harmonic	Note 1	Note 1	Note 1
8 th Harmonic	Note 1	Note 1	Note 1
9 th Harmonic	Note 1	Note 1	Note 1
10 th Harmonic	Note 1	Note 1	Note 1

Notes:

(1) Measurement at system noise floor.


Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 32 of 48

11.4 <u>Screen Captures – Spurious Radiated Emissions</u>

Representative 30 MHz up to 1000 MHz




Channel 0, shown from 1000 MHz up to 10000 MHz




Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 33 of 48


Channel 3, shown from 1000 MHz up to 10000 MHz *** Agilent 11:16:37 Sep 22, 2009



Channel 7, shown from 1000 MHz up to 10000 MHz ** Agilent 11:17:36 Sep 22, 2009



Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 34 of 48



Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 35 of 48

EXHIBIT 12. MPE CALCULATIONS

The following MPE calculations are based on a 1.8 centimeter inverted-F printed circuit board trace antenna, with a measured ERP of 110 dB μ V/m, at 3 meters, and conducted RF power of +15.32 dBm as presented to the antenna. The calculated gain of this antenna, based on the ERP measurements is 0.25 dBi.

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal:	15.32 (dBm)
Maximum peak output power at antenna input terminal:	34.041 (mW)
Antenna gain(typical):	0.25 (dBi)
Maximum antenna gain:	1.059 (numeric)
Prediction distance:	20 (cm)
Prediction frequency:	2400 (MHz)
MPE limit for uncontrolled exposure at prediction frequency:	1 (mW/cm^2)

Power density at prediction frequency: 0.007173 (mW/cm^2)

Maximum allowable antenna gain: 21.7 (dBi)

Margin of Compliance at 20 cm = 21.4 dB

Prepared For: Generac Power Systems	Model #: 0G6019B	LS Research, LLC
EUT: End Station	IC: 8036B-0G6019B	Template: 15.247 DTS TX (V2 9-06-06)
Report #: 309366	FCC ID #: VDE-0G6019B	Page 36 of 48

Appendix A



Date : 22-Sep-2009 Type Test: Radiated Emissions Job #: C-758

Customer: Generac Power Systems Prepared By: R. Urness Quote #: 309366

No.	Asset #	Description	Manufacturer	Model#	Serial#	Cal Date	Cal Due Date	Equipment Status
1	EE 960157	3Hz-13.2GHz Spectrum Analyzer	Agilent	E4445A	MY48250225	3/17/2009	3/17/2010	Active Calibration
2	EE 960158	RF Preselecter	Agilent	N9039A	MY46520110	7/2/2009	7/2/2010	Active Calibration
3	AA 960077	Bicon Antenna	EMCO	93110B	9702-2918	11/20/2009	11/20/2010	Active Calibration
4	AA 960078	Log Periodic Antenna	EMCO	93146	9701-4855	10/16/2009	10/16/2010	Active Calibration
5	AA 960081	Double Ridge Horn Antenna	EMCO	3115	6907	9/26/2008	12/26/2009	Active Calibration

Quality Manager: Lindle a White



 Date : 23-Sep-2009
 Type Test : Band Edge
 Job # : C-758

Prepared By: R. Urness Customer: Generac Power Systems Quote #: 309366

1 EE 960157 3Hz-13.2GHz Spectrum Analyzer Agilent E4445A MY48250225 3/17/2009 3/17/2010 Active Calibration 2 EE 960158 RF Preselecter Agilent N9039A MY46520110 7/2/2009 7/2/2010 Active Calibration	No	Asset #	Description	Manufacturer	Model #	Serial#	Cal Date	Cal Due Date	Equipment Status
· · · · · · · · · · · · · · · · ·	1	EE 960157	3Hz-13.2GHz Spectrum Analyzer	Agilent	E4445A	MY48250225	3/17/2009	3/17/2010	Active Calibration
0 AA 000004 Barbla Bidas Hara Aabaara FNOO 0445 0007 00070000 AA 60 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	2	EE 960158	RF Preselecter	Agilent	N9039A	MY46520110	7/2/2009	7/2/2010	Active Calibration
3 AA 960081 Double Ridge from Antenna EMCO 3115 6907 9/26/2008 12/26/2009 Active Calibration	3	AA 960081	Double Ridge Horn Antenna	EMCO	3115	6907	9/26/2008	12/26/2009	Active Calibration

Project Engineer:

Quality Manager: Limble Q. White



Date: 9-Dec-2008 Type Test: Radiated Emissions Job#: C-458	
--	--

Prepared By: Ryan Urness Customer: Generac Power Systems Quote #: 308433

No.	Asset #	Description	Manufacturer	Model#	Serial#	Cal Date	Cal Due Date	Equipment Status
1	EE 960013	EMI Receiver	HP	8546A System	3617A00320;3448A	9/23/2008	9/23/2009	Active Calibration
2	EE 960014	EMI Receiver-filter section	HP	85460A	3448A00296	9/23/2008	9/23/2009	Active Calibration
3	AA 960078	Log Periodic Antenna	EMCO	93146	9701-4855	10/20/2008	10/20/2009	Active Calibration
4	AA 960077	Bicon Antenna	EMCO	93110B	9702-2918	11/24/2008	11/24/2009	Active Calibration
5	AA 960081	Double Ridge Horn Antenna	EMCO	3115	6907	9/26/2008	9/26/2009	Active Calibration
6	AA 960063	Pyramidal Horn Antenna	EMCO	3160-09	9809-1120	6/17/2008	6/17/2009	Active Calibration

Project Engineer: Quality Manager: Wildle Q. White



Date: 9-Dec-2008 Type Test: Band-Edge	Job#: C-458
---------------------------------------	-------------

Prepared By: Ryan Urness Customer : Generac Power Systems Quote #: 308433

No.	Asset #	Description	Manufacturer	Model#	Serial#	Cal Date	Cal Due Date	Equipment Status
1	EE 960013	EMI Receiver	HP	8546A System	3617A00320;3448A	9/23/2008	9/23/2009	Active Calibration
2	EE 960014	EMI Receiver-filter section	HP	85460A	3448A00296	9/23/2008	9/23/2009	Active Calibration
3	AA 960078	Log Periodic Antenna	EMCO	93146	9701-4855	10/20/2008	10/20/2009	Active Calibration
4	AA 960077	Bicon Antenna	EMCO	93110B	9702-2918	11/24/2008	11/24/2009	Active Calibration
5	AA 960081	Double Ridge Horn Antenna	EMCO	3115	6907	9/26/2008	9/26/2009	Active Calibration
6	AA 960063	Pyramidal Horn Antenna	EMCO	3160-09	9809-1120	6/17/2008	6/17/2009	Active Calibration

roject Engineer: Quality Manager: Mills a Dutte



Spectrum Analyzer

1 EE 960073

Date : 9-Dec-2008			Type Test : Conducted Emissions				Job#: <u>C-458</u>	
Prepared By: Ryan Urness		Customer :	Generac Power S	ystems		Quote #:	308433	
VIO.	Asset #	Description	Manufacturer	Model #	Serial#	Cal Date	Cal Due Date	Equipment Status

US45300564

9/26/2008

9/26/2009

Active Calibration

Agilent

E4446A



Date : 9-Dec-2008			Type Test :	Occupied Bandwi	dth (6dB & 20dB)		Job#: <u>C-458</u>		
Prepared By: Ryan Urness		Customer: Generac Power Systems				Quote #:	308433		
No.	Asset #	Description	Manufacturer	Model#	Serial#	Cal Date	Cal Due Date	Equipment Status	
4	EE 0C0072	Spectrum Applyzer	Agilent	E4446A	HEAESONERA	0/26/2009	0/26/2000	Active Calibration	

Project Engineer: Junto a Dutte



Date : 9-Dec-2008			Type Test :	Conducted Power	Output		Job#: <u>C-458</u>		
Prepared By: Ryan Urness		Customer : Generac Power Systems				Quote #:	308433		
No.	Asset #	Description	Manufacturer	Model#	Serial#	Cal Date	Cal Due Date	Equipment Status	
4	EE 0C0072	Spectrum Applyzer	Agilent	E4446A	HEAESONERA	0/26/2009	0/26/2000	Active Calibration	

Project Engineer: Quality Manager: Wildle (1- White



Date : 9-Dec-2008			Type Test : Power Spectral Density				Job#: <u>C-458</u>		
	Prepared By:	Ryan Urness	Customer :	Generac Power S	ystems		Quote #:	308433	
Vo.	Asset#	Description	Manufacturer	Model#	Serial#	Cal Date	Cal Due Date	Equipment Status	
1	EE OCOOTS	Spectrum Applyzer	Agilent	EAAAGA	HENESONERA	0/26/2009	0/26/2000	Active Calibration	

Project Engineer:

Quality Manager: LANG Q-White



Date : 9-Dec-2008			Type Test : Spurious Emissions				Job#: <u>C-458</u>		
Prepared By: Ryan Urness		Customer : Generac Power Systems				Quote #:	308433		
No.	Asset #	Description	Manufacturer	Model#	Serial#	Cal Date	Cal Due Date	Equipment Status	
4	EE 060072	Spectrum Applyzer	Agilant	E4446A	HC4E300EG4	0/26/2009	0/26/2000	Active Calibration	

Project Engineer: Quality Manager: MUR A White

Appendix B

Current Test Standards

STANDARD#	DATE	Am. 1	Am. 2
ANSI 063.4	2003		
OSPR11	2003-03	2004-05	2006-06
OSPR141	2005-11		
OSPR142	2001-11	2001-11	2008-05
OSPR 16-1-1 Note1	2006-03	2006-09	2007-07
CISPR 16-1-2 Note1	2003	2004-04	2006-07
OSPR22	2005	2005-07	2006-01
OSPR24	1997-09	2001-07	2002-10
EN 55011	2007-05		
BN 55014-1	2006		
BN 55014-2	1997		
EN 55022	2006		
EN 60601-1-2	2007		
EN 61000-32	2006-05		
EN 61000-3-3	1994	1995	
EN 61000-42	2001	1998	2001
EN 61000-43	2006-07	2008-05	
BI 61000-44	2004		
EN 61000-45	2006-12		
EN 61000-46	2007-08		
EN 61000-48	1993	1994-01	
EN 61000-4-11	2004-10		
EN 61000-6-1	2007-02		
EN 61000-6-2	2005-12		
EN 61000-6-3	2007-02		
EN 61000-64	2007-02		
FCC 47 CFR, Parts 0-15, 18, 90, 95	2007		
FCCPublicNoticeDA004407	2000		
FCCET Docket #99-231	2002		
FCCProcedures	2007		
KCES 001	2006-06		
ICES 002	2007-02		
ICES 003	2004-02		
EC60601-1-2 Note1	2007-03		
EC61000-3-2	2005	2008-03	
EC61000-33	2008-06		
EC61000-42	2001-04	1998	2000
EC6100043	2006-02	inclin 2006	
EC6100044	2004-07		

STANDARD#	DATE	Am. 1	Am. 2	
IEC6100045	2005-41			
IEC6100046	2008-07			
IEC6100048	2001-03	2000		
IEC61000-4-11	2004-03			
IEC61326-1	2005-12			
ISO14082	1998-07			
MILStd. 461E	1999-08			
RSS CEN	2007-06			
RSS 119	2007-06			
RSS 123	1999-11			
RSS 125	2000-03			
RSS 131	2003-07			
RSS 136	2002-10			
RSS 137	1999-09			
RSS 210	2007-06			
RSS 213	2005-12			
RSS 243	2005-41			
RSS 310	2007-06			
	 			
	└			
Ntte 1: Test not on LSRScape of Accreditation				

Appendix C

Uncertainty Statement

This uncertainty represents an expanded uncertainty expressed at approximately the 95 % confidence level, using a coverage factor of k=2.

Table of Expanded Uncertainty Values, (K=2) for Specified Measurements

Measurement Type	Particular Configuration	Uncertainty Values
Radiated Emissions	3 – Meter chamber, Biconical Antenna	4.24 dB
Radiated Emissions	3-Meter Chamber, Log Periodic Antenna	4.8 dB
Radiated Emissions	10-Meter OATS, Biconical Antenna	4.18 dB
Radiated Emissions	10-Meter OATS, Log Periodic Antenna	3.92 dB
Conducted Emissions	Shielded Room/EMCO LISN	1.60 dB
Radiated Immunity	3 Volts/Meter in 3-Meter Chamber	1.128 Volts/Meter
Conducted Immunity	3 Volts level	1.0 V

Appendix D

Justifications of Average Duty Factor Calculations

Average (Relaxation) Factor

Average Factor = 20* Log₁₀ (Worst Case EUT On-time over 100 ms time window)

The transmit packet occupies 0.775 ms of time, within any 100 ms window. Therefore, the relaxation factor allowance is calculated as:

Average Factor = $20* \text{Log}_{10} (0.775 / 100 \text{ ms}) = -42.21$

A relaxation factor of 20 dB would be allowable for this product.

