



RF EXPOSURE REPORT

REPORT NO.: SA960615L07

MODEL NO.: Archer 102

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: eRune technology Corp.

ADDRESS: 2F, No.38-1, Guang-Ming 9th Rd., Chupei,
Hsinchu, Taiwan, R.O.C.302

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou
Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan,
R.O.C.



Conclusion

No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.58
High	2.480	

Maximum measured transmitter power:

Pout (dBm)		Pout (mW)
Conducted Power	3.820	2.410
EIRP Power	3.820	2.410

***Note:** The antenna is PCB Printed antenna with 0dBi gain

Threshold for no SAR evaluation is 24.58mW

Transmitter power is 2.410mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold