

Produkte Products

> Seite 1 von 12 Prüfbericht - Nr.: 14026417 001

Test Report No .:

Page 1 of 12

Auftraggeber:

SHANTOU CITY CHENGHAI AREA SIMA TOYS FACTORY

Client: LAIMEI INDUSTRIAL AREA

CHENGHAI SHANTOU

GUANGDONG CHINA

Gegenstand der Prüfung: Low Power Transmitter (27.145MHz)

Test Item:

Bezeichnung: Identification:

Please refer to "Models" on

Serien-Nr.: Serial No .:

Engineering sample

page 5

S032G

Wareneingangs-Nr.: Receipt No .:

00110329299-001

Eingangsdatum: 29.03.2011

Date of Receipt:

Prüfort:

TÜV Rheinland Hong Kong Ltd.

Testing Location: 8/F, Niche Centre, 14 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong

Hong Kong Productivity Council

HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong

Prüfgrundlage:

Test Specification:

FCC Part 15, Subpart C

Prüfergebnis:

Der Prüfgegenstand entspricht oben genannter Prüfgrundlage(n).

Test Result:

The test item passed the test specification(s).

Prüflaboratorium:

TÜV Rheinland Hong Kong Ltd.

Testing Laboratory:

9th Floor, Emperor International Square, 7 Wang Tai Road, Kowloon Bay.

Kowloon, Hong Kong

geprüft / tested by:

kontrolliert / reviewed by:

Mika Chan 17.05.2011 Project Engineer

17.05.2011 Datum

Sharon Li Assistant Manager

Datum Date

Name/Stellung Name/Position

Unterschrift Signature

Name/Stellung Name/Position

Unterschrift Signature

Sonstiges I Other Aspects:

FCCID: VDY-GC887552-2

Abkürzungen: P(ass)

entspricht Prüfgrundlage entspricht nicht Prüfgrundlage F(ail) N/A nicht anwendbar

nicht getestet

Abbreviations:

P(ass) passed failed

F(ail) N/A not applicable N/T

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. This test report relates to the a.m. test sample. Without permission of the test center this test report is not permitted to be

duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.

Date



Test Summary

Radiated Emission of Carrier Frequency

Result: Pass

Spurious Radiated Emissions

Result: Pass

Bandwidth Measurement

Result: Pass

Test Report No.: 14026417 001 Date: 17.05.2011 Page 2 of 12



Contents

List of Test and Measurement Instruments	4
General Product Information	5
Product Function and Intended Use	5
Ratings and System Details	5
Independent Operation Modes	
Submitted Documents	
Related Submittal(s) Grants	6
Test Set-up and Operation Mode	7
Principle of Configuration Selection	7
Test Operation and Test Software	7
Special Accessories and Auxiliary Equipment	7
Countermeasures to achieve EMC Compliance	7
Test Methodology	8
Radiated Emission	
Field Strength Calculation	8
Test Results	
Radiated Emission of Carrier Frequency Subclause 15.227(a)	g
Spurious Radiated Emissions Subclause 15.227(b)	10
Bandwidth Measurement	

Appendix 1 Test Protocol

Appendix 2 Test Setup

Appendix 3 EUT External Photo

Appendix 4 EUT Internal Photo

Appendix 5 FCCID Label, Block Diagram, Schematics and User manual



List of Test and Measurement Instruments

Hong Kong Productivity Council (Registration number: 90656)

	Equipment used	Manufacturer	Model	S/N	Due Date
			No.		
\boxtimes	Semi-anechoic Chamber	Frankonia	Nil	Nil	27-Apr-11
\boxtimes	Test Receiver	R&S	ESU8	100141	25-May-11
\boxtimes	Bi-conical Antenna	R&S	HK116	100242	13-Apr-12
\boxtimes	Log Periodic Antenna	R&S	HL223	841516/020	13-Apr-12
\boxtimes			RTK081-		
			05S-05S-	LA2-001-10M /	
	Coaxial cable 50ohm	Rosenberger	10m	002	08-Dec-11
\boxtimes	Microwave amplifer 0.5-				
	26.5GHz, 25dB gain	HP	83017A	3950M00241	03-Oct-11
\boxtimes	High Pass Filter (cutoff				
	freq. =1000MHz)	Trilithic	23042	9829213	30-Oct-11
\boxtimes	Horn Antenna	EMCO	3115	9002-3351	16-Apr-12
\boxtimes	FSP 30 Spectrum				
	Analyser	R&S	FSP 30	100286	17-Sep-12
	Active Loop Antenna	EMCO	6502	9107-2651	19-Apr-12

Test Report No.: 14026417 001 Date: 17.05.2011 Page 4 of 12



General Product Information

Product Function and Intended Use

The equipment under test (EUT) is a transmitter for a RC toy helicopter operating at 27.145 MHz. The EUT has two control rods for commanding the Forward, backward, ascend, descend, left and right movement of the associated receiver.

The manufacturer declares that the transmitter models listed in below table are identical to model S032G. They are all identical in schematics, PCB layouts, components used except the housing. So, no additional test is required.

FCCID: VDY-GC887552-2

Model
S100G, S102G, S105G, S106G, S107G, S108G, S109G, S110G, S111G, S112G, S113G,
S116G, S117G, S118G, S119G, S120G, S022G, S023G, S026G, S027G, S029G, S030G,
S031G, S032G, S033G, S034G, S035G, S036G, S038G, S040G, S800G, S801G, S802G,

Ratings and System Details

S803G, S804G, S805G, S806G, S807G, S808G

		Transmitter
Frequency range		27.145MHz
Number of channels		1
Type of antenna		External Telescopic Antenna
Power supply		Battery operated 6V
Ports		none
Protection Class	:	

Test Report No.: 14026417 001 Date: 17.05.2011 Page 5 of 12



Independent Operation Modes

The basic operation modes are:

- transmitting control signal for the RC toy Helicopter.

For further information refer to User Manual

Submitted Documents

The submitted documents are listed as follow:

- Circuit diagram
- Block diagram
- User manual
- Label artwork

Related Submittal(s) Grants

This is a single application for certification of the transmitter.

Test Report No.: 14026417 001 Date: 17.05.2011 Page 6 of 12



Test Set-up and Operation Mode

Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation

level. The test modes were adapted accordingly in reference to the instructions for use.

Test Operation and Test Software

Test operation should refer to test methodology.

- There was no special software to exercise the device.

Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

- none

Countermeasures to achieve EMC Compliance

- none

Test Report No.: 14026417 001 Date: 17.05.2011 Page 7 of 12



Test Methodology

Radiated Emission

The radiated emission measurements were performed according to the procedures in ANSI C63.4-2003.

The equipment under test (EUT) was placed at the middle of the 80 cm height turntable, and the turntable is 3 meters far from the measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in particular parts of this test report.

Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:

FS = R + AF + CF + FA - PA

Where FS = Field Strength in dBuV/m at 3 meters.

R = Reading of Spectrum Analyzer in dBuV.

AF = Antenna Factor in dB.

CF = Cable Attenuation Factor in dB.

FA = Filter Attenuation Factor in dB.

PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.

Test Report No.: 14026417 001 Date: 17.05.2011 Page 8 of 12



Test Results

Radiated Emission of Carrier Frequency

Subclause 15.227(a)

RESULT: Pass

Test Specification : FCC Part 15 Subclause 15.227(a)

Test Method : ANSI 63.4-2003

Measurement Location : Semi Anechoic Chamber

Measurement Distance: 3m

Detector Function : Peak and Average

Measurement BW : 120 kHz Supply Voltage : DC 6V

Polarization: Vertical

Detector function	Frequency	Measured Field strength at 3m	Delta to Limit
	(MHz)	(dBµV/m)	(dB)
Peak	27.146	80.8	-19.2
Average	27.146	56.9	-23.1

Polarization: Horizontal

Detector function	Frequency (MHz)	Measured Field strength at 3m (dBµV/m)	Delta to Limit (dB)
Peak	27.146	67.7	-32.3
Average	27.146	48.3	-31.7

Limit Subclause 15.227(a)

Frequency within the band	Peak Emission		Average Emission	
Trequency within the band	(μV/m)	dBμV/m	(μV/m)	dBµV/m
26.96-27.28 MHz	100,000	100.0	10,000	80.0

According to section 15.35(b), when average radiated emission measurements are specified in this part, including average emission measurements below 1000 MHz, there also is a limit on the peak level of the radio frequency emissions. Unless otherwise specified, the limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.

Test Report No.: 14026417 001 Date: 17.05.2011 Page 9 of 12



Spurious Radiated Emissions

Subclause 15.227(b)

RESULT: Pass

Test Specification : FCC Part 15 Subclause 15.209

Test Method : ANSI 63.4-2003

Measurement Location : Semi Anechoic Chamber

Measurement Distance : 3m

Detector Function : Quasi Peak
Measurement BW : 120 kHz
Supply Voltage : DC 6V
Measuring Frequency Range : 30-1000MHz

Polarization: Vertical

Frequency (MHz)	Field strength at 3m (dBuV/m)	Limit at 3m (dBuV/m)	Delta to Limit (dB)
54.291	21.3	40.0	-18.7
81.438	19.1	40.0	-20.9
*108.584	17.5	43.5	-26.0
*135.728	20.6	43.5	-22.9
*162.874	18.3	43.5	-25.2
190.020	23.7	43.5	-19.8
217.166	13.9	46.0	-32.1
*244.312	14.3	46.0	-31.7
*271.458	14.0	46.0	-32.0

Polarization: Horizontal

Frequency (MHz)	Field strength at 3m (dBuV/m)	Limit at 3m (dBuV/m)	Delta to Limit (dB)
54.292	9.60	40.0	-30.4
81.438	13.3	40.0	-26.7
*108.583	12.6	43.5	-30.9
*135.729	16.9	43.5	-26.7
*162.875	17.4	43.5	-26.1
190.021	16.1	43.5	-27.4
217.166	13.8	46.0	-32.2
*244.312	12.8	46.0	-33.2
*271.458	12.7	46.0	-33.3

Remark: (1) '* 'indicates the frequency of the emissions fall into the restricted band as defined in Section 15.205(a). They comply with the radiated emission limits specified in Section 15.209.

(2) There is no spurious emission found between lowest oscillating frequency to 30 MHz.

Test Report No.: 14026417 001 Date: 17.05.2011 Page 10 of 12



Limit Subclause 15.209

Radiated emissions, which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209.

Limit for Radiated Emission under Section 15.209:

Frequency (MHz)	Field strength (μV/m)	Field strength (dBµV/m)	Measurement distance (m)
30-88	100	$20*\log(100) = 40.0$	3
88-216	150	$20*\log(150) = 43.5$	3
216-960	200	$20*\log(200) = 46.0$	3
960-2500	500	$20*\log(500) = 54.0$	3

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector and above 1000 MHz are based on the measurements employing an average detector.

Test Report No.: 14026417 001 Date: 17.05.2011 Page 11 of 12



Bandwidth Measurement

Antenna port

Port of Testing Detector Function Peak Supply Voltage DC 6V

The field strength of any emissions appearing at the lower edge 26.96 MHz and upper edge 27.28 MHz are 47.97 dB and 46.07 dB below the carrier respectively.

For test results refer to Appendix 1.

Date: 17.05.2011 Page 12 of 12 Test Report No.: 14026417 001