

RF TEST REPORT



Report No.: RF_SL14061701-STE-001_DF990_Rev1.0

Supersede Report No.: RF_SL14061701-STE-001_DF990

Applicant	ST Electronics (Satcom & Sensor Systems) Pte Ltd	
Product Name	K-Band Bi-Static FMCW Transceiver Module	
Model No.	DF990	
Test Standard	47 CFR 15.245: 2013	
Test Method	ANSI C63.4: 2009	
FCC ID	VEC-DF990	
Date of test	07/07/2014 - 07/17/2014	
Issue Date	07/25/2014	
Test Result	Pass	Fail
Equipment complied with the specification	<input checked="" type="checkbox"/> [x]	
Equipment did not comply with the specification	<input type="checkbox"/> []	
Angel Escamilla	A handwritten signature in black ink that reads "Angel Escamilla".	
Angel Escamilla	Nima Molaei	
Test Engineer	Engineer Reviewer	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued By:
SIEMIC Laboratories
775 Montague Expressway, Milpitas, 95035 CA



775 Montague Expressway, Milpitas, CA 95035, USA • Phone: (+1) 408 526 1188 • Facsimile: (+1) 408 526 1088

Visit us at: www.siemic.com; Follow us at:

Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Accreditation Body	Scope
USA	FCC, A2LA	EMC, RF/Wireless, Telecom
Canada	IC, A2LA, NIST	EMC, RF/Wireless, Telecom
Taiwan	BSMI, NCC, NIST	EMC, RF, Telecom, Safety
Hong Kong	OFTA, NIST	RF/Wireless, Telecom
Australia	NATA, NIST	EMC, RF, Telecom, Safety
Korea	KCC/RRA, NIST	EMI, EMS, RF, Telecom, Safety
Japan	VCCI, JATE, TELEC, RFT	EMI, RF/Wireless, Telecom
Mexico	NOM, COFETEL, Caniety	Safety, EMC, RF/Wireless, Telecom
Europe	A2LA, NIST	EMC, RF, Telecom, Safety

Accreditations for Product Certifications

Country	Accreditation Body	Scope
USA	FCC TCB, NIST	EMC, RF, Telecom
Canada	IC FCB, NIST	EMC, RF, Telecom
Singapore	iDA, NIST	EMC, RF, Telecom
EU	NB	EMC & R&TTE Directive
Japan	MIC (RCB 208)	RF, Telecom
Hong Kong	OFTA (US002)	RF, Telecom

Test report No.	RF_SL14061701-STE-001_DF990_Rev1.0
Page	3 of 26
FCC ID	VEC-DF990

CONTENTS

1 REPORT REVISION HISTORY	4
2 EXECUTIVE SUMMARY	5
3 CUSTOMER INFORMATION	5
4 TEST SITE INFORMATION	5
5 MODIFICATION	5
6 EUT INFORMATION	6
6.1 EUT Description.....	6
6.2 Radio Description.....	6
6.3 EUT test modes/configuration Description	6
6.4 EUT Photos - External	7
6.5 EUT Photos - Internal	7
6.6 EUT Test Setup Photos.....	8
7 SUPPORTING EQUIPMENT/SOFTWARE AND CABLING DESCRIPTION	10
7.1 Supporting Equipment	10
7.2 Test Software Description.....	10
8 TEST SUMMARY	11
9 MEASUREMENT UNCERTAINTY	12
10 MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	13
10.1 Antenna Requirement.....	13
10.2 Conducted Emissions	14
10.3 Radiated Fundamental and Harmonics Field Strength	17
10.4 Radiated Emissions below 1GHz.....	19
10.5 Radiated Spurious Emissions above 1GHz.....	21
ANNEX A. TEST INSTRUMENT	23
ANNEX B. USER MANUAL, BLOCK & CIRCUIT DIAGRAM	24
ANNEX C. SIEMIC ACCREDITATION	25

Test report No.	RF_SL14061701-STE-001_DF990_Rev1.0
Page	4 of 26
FCC ID	VEC-DF990

1 Report Revision History

Report No.	Report Version	Description	Issue Date
RF_SL14061701-STE-001_DF990	-	Original	07/18/2014
RF_SL14061701-STE-001_DF990_Rev1.0	Rev1.0	<ul style="list-style-type: none"> - The correct operating frequency is added on page 6. - The data is corrected on page 18 based on correct input voltage. 	07/25/2014

Test report No.	RF_SL14061701-STE-001_DF990_Rev1.0
Page	5 of 26
FCC ID	VEC-DF990

2 Executive Summary

The purpose of this test program was to demonstrate compliance of following product

Company: ST Electronics (Satcom & Sensor Systems) Pte Ltd
Product: K-Band Bi-Static FMCW Transceiver Module
Model: DF990

against the current Stipulated Standards. The specified model product stated above has demonstrated compliance with the Stipulated Standard listed on 1st page.

3 Customer information

Applicant Name	ST Electronics (Satcom & Sensor Systems) Pte Ltd
Applicant Address	1 Ang Mo Kio Electronics Park Road #06-02, Singapore 567710
Manufacturer Name	ST Electronics (Satcom & Sensor Systems) Pte Ltd
Manufacturer Address	1 Ang Mo Kio Electronics Park Road #06-02, Singapore 567710

4 Test site information

Lab performing tests	SIEMIC Laboratories
Lab Address	775 Montague Expressway, Milpitas, CA 95035
FCC Test Site No.	881796
IC Test Site No.	4842D-2
VCCI Test Site No.	A0133

5 Modification

Index	Item	Description	Note
-	-	-	-

6 EUT Information

6.1 EUT Description

Product Name	K-band Bi-Static FMCW Transceiver Module
Model No.	DF990
Trade Name	ST Electronics (Satcom & Sensor Systems) Pte Ltd
Serial No.	51310280008
Input Power	5VDC
Power Adapter Manu/Model	N/A
Power Adapter SN	N/A
Hardware version	N/A
Software version	N/A
Date of EUT received	07/04/2014
Equipment Class/ Category	Radio
Operating Frequency	24.107 GHz – 24.169 GHz
Port/Connectors	N/A

6.2 Radio Description

Spec for Radio -

Radio Type	
Operating Frequency	24.107 GHz – 24.169 GHz
Modulation	No Modulation
Channel Spacing	N/A
Number of Channels	1
Antenna Type	Patch array
Antenna Connector Type	N/A


6.3 EUT test modes/configuration Description

Test mode


	Test Mode	Note
Pre_test_mode_1	Continuous Transmit	-
Pre_test_mode_2	-	-
Pre_test_mode_3	-	-
Remark:		

Test report No.	RF_SL14061701-STE-001_DF990_Rev1.0
Page	7 of 26
FCC ID	VEC-DF990

6.4 EUT Photos - External




6.5 EUT Photos - Internal



Test report No.	RF_SL14061701-STE-001_DF990_Rev1.0
Page	8 of 26
FCC ID	VEC-DF990

6.6 EUT Test Setup Photos



Test report No.	RF_SL14061701-STE-001_DF990_Rev1.0
Page	9 of 26
FCC ID	VEC-DF990



Radiated Emissions (>18 GHz) – Front View



Radiated Emissions (>18 GHz) – Rear View

Test report No.	RF_SL14061701-STE-001_DF990_Rev1.0
Page	10 of 26
FCC ID	VEC-DF990

7 Supporting Equipment/Software and cabling Description

7.1 Supporting Equipment

Item	Supporting Equipment Description	Model	Serial Number	Manufacturer	Note
1	DC Power Supply	TPS-2000	920027	Topward Electric Instruments	

7.2 Test Software Description

Test Item	Software	Description
RF Testing	N/A	N/A

Test report No.	RF_SL14061701-STE-001_DF990_Rev1.0
Page	11 of 26
FCC ID	VEC-DF990

8 Test Summary

Test Item	Test standard	Test Method/Procedure	Pass / Fail
Antenna Requirement	FCC 15.203	-	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> N/A
AC Line Conducted Emissions	FCC 15.207 (a)	ANSI C63.4: 2009	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> N/A
Restricted Band of Operation	FCC 15.205 (a)	ANSI C63.4: 2009	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> N/A
Fundamental Field Strength	FCC 15.245 (b)	ANSI C63.4: 2009	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> N/A
Outside Band Emissions	FCC 15.245 (b)(3)	ANSI C63.4: 2009	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> N/A
Remark	1. All measurement uncertainties are not taken into consideration for all presented test results. 2. The applicant shall ensure frequency stability by showing that an emission is maintained within the band of operation under all normal operating conditions as specified in the user's manual.		

Test report No.	RF_SL14061701-STE-001_DF990_Rev1.0
Page	12 of 26
FCC ID	VEC-DF990

9 Measurement Uncertainty

Emissions			
Test Item	Frequency Range	Description	Uncertainty
Radiated Spurious Emissions	30MHz – 1GHz	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
Radiated Spurious Emissions	1GHz – 50GHz	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+4.3dB/-4.1dB

10 Measurements, Examination and Derived Results


10.1 Antenna Requirement

Spec	Item	Requirement	Applicable
47CFR§15.203		<p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.</p> <p>Antenna requirement must meet at least one of the following:</p> <ul style="list-style-type: none"> a) Antenna must be permanently attached to the device. b) Antenna must use a unique type of connector to attach to the device. c) Device must be professionally installed. Installer shall be responsible for ensuring that the correct antenna is employed with the device. 	<input checked="" type="checkbox"/>
Remark	The Antenna permanently attached to the device which meets the requirement		
Result	<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL		

10.2 Conducted Emissions

Conducted Emissions Limit

Frequency ranges (MHz)	Limit (dBuV)	
	QP	Average
0.15 ~ 0.5	66 ~ 56	56 ~ 46
0.5 ~ 5	56	46
5 ~ 30	60	50


Spec	Item	Requirement	Applicable
47CFR§15.207	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu]H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequency ranges.	<input checked="" type="checkbox"/>
Test Setup	 <p>Note: 1. Support units were connected to second LISN. 2. Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</p>		
Procedure	<ul style="list-style-type: none"> The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table, as shown in Annex B. The power supply for the EUT was fed through a 50Ω/50μH EUT LISN, connected to filtered mains. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable. All other supporting equipment was powered separately from another main supply. 		
Remark	<p>-</p>		
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data Yes N/A

Test Plot Yes (See below) N/A


10.2.1 Conducted Emission Test Results (AC Line Test Result)

Test specification:	Conducted Emissions		
Environmental Conditions:	Temp(°C):	23°C	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail
	Humidity (%):	42%	
	Atmospheric(mbar):	1021	
Mains Power:	120Vac, 60Hz		
Tested by:	Angel Escamilla		
Test Date:	07/14/2014		
Remarks:	Neutral Line		



Frequency MHz	Raw dBuV	Cable Loss	Factors dB	Level dBuV	Measurement Type	Line	Limit dBuV	Margin dB	Pass /Fail
0.35	18.63	10.01	0.72	29.35	Quasi Peak	Neutral	59.01	-29.66	Pass
0.38	19.38	10.01	0.72	30.12	Quasi Peak	Neutral	58.24	-28.12	Pass
0.42	23.16	10.01	0.73	33.90	Quasi Peak	Neutral	57.52	-23.62	Pass
0.45	19.96	10.01	0.73	30.70	Quasi Peak	Neutral	56.87	-26.17	Pass
0.49	13.77	10.01	0.74	24.51	Quasi Peak	Neutral	56.25	-31.74	Pass
25.06	10.96	10.08	2.27	23.30	Quasi Peak	Neutral	60.00	-36.70	Pass
0.35	13.97	10.01	0.72	24.69	Average	Neutral	49.01	-24.32	Pass
0.38	15.99	10.01	0.72	26.72	Average	Neutral	48.24	-21.51	Pass
0.42	17.95	10.01	0.73	28.69	Average	Neutral	47.52	-18.83	Pass
0.45	17.05	10.01	0.73	27.79	Average	Neutral	46.87	-19.08	Pass
0.49	10.19	10.01	0.74	20.93	Average	Neutral	46.25	-25.31	Pass
25.06	10.73	10.08	2.27	23.08	Average	Neutral	50.00	-26.92	Pass


Test specification:	Conducted Emissions			
Environmental Conditions:	Temp(°C):	23°C	Result:	
	Humidity (%):	42%		
	Atmospheric(mbar):	1021		
Mains Power:	120Vac, 60Hz			
Tested by:	Angel Escamilla			
Test Date:	07/14/2014			
Remarks:	Phase Line			



Frequency MHz	Raw dBuV	Cable Loss	Factors dB	Level dBuV	Measurement Type	Line	Limit dBuV	Margin dB	Pass /Fail
0.20	10.96	10.00	0.74	21.71	Quasi Peak	Live	63.65	-41.94	Pass
0.45	12.98	10.01	0.73	23.71	Quasi Peak	Live	56.85	-33.14	Pass
0.81	10.52	10.01	0.76	21.30	Quasi Peak	Live	56.00	-34.70	Pass
1.50	14.18	10.02	0.87	25.08	Quasi Peak	Live	56.00	-30.92	Pass
7.76	15.23	10.04	1.23	26.50	Quasi Peak	Live	60.00	-33.50	Pass
7.90	14.07	10.04	1.24	25.36	Quasi Peak	Live	60.00	-34.64	Pass
0.20	6.39	10.00	0.74	17.14	Average	Live	53.65	-36.51	Pass
0.45	8.83	10.01	0.73	19.57	Average	Live	46.85	-27.29	Pass
0.81	7.20	10.01	0.76	17.98	Average	Live	46.00	-28.02	Pass
1.50	10.08	10.02	0.87	20.97	Average	Live	46.00	-25.03	Pass
7.76	12.24	10.04	1.23	23.51	Average	Live	50.00	-26.49	Pass
7.90	10.46	10.04	1.24	21.75	Average	Live	50.00	-28.25	Pass

10.3 Radiated Fundamental and Harmonics Field Strength

Requirement(s):

Spec	Item	Requirement	Applicable																		
47CFR§15.245(b)	a)	<p>The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:</p> <table border="1"> <thead> <tr> <th>Fundamental frequency (MHz)</th> <th>Field Strength of Fundamental (millivolts/meter)</th> <th>Field Strength of Harmonics (microvolts/meter)</th> </tr> </thead> <tbody> <tr> <td>02-928</td> <td>500</td> <td>1.6</td> </tr> <tr> <td>2435-2465</td> <td>500</td> <td>1.6</td> </tr> <tr> <td>5785-5815</td> <td>500</td> <td>1.6</td> </tr> <tr> <td>10500-10550</td> <td>2500</td> <td>25.0</td> </tr> <tr> <td>24075-24175</td> <td>2500</td> <td>25.0</td> </tr> </tbody> </table>	Fundamental frequency (MHz)	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)	02-928	500	1.6	2435-2465	500	1.6	5785-5815	500	1.6	10500-10550	2500	25.0	24075-24175	2500	25.0	<input checked="" type="checkbox"/>
Fundamental frequency (MHz)	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)																			
02-928	500	1.6																			
2435-2465	500	1.6																			
5785-5815	500	1.6																			
10500-10550	2500	25.0																			
24075-24175	2500	25.0																			
Test Setup	 <p>The diagram illustrates the test setup. A 'Turn Table' is positioned on a 'Ground Plane'. An 'EUT & Support Units' assembly is mounted on the turn table. A vertical 'Ant. Tower' is connected to the EUT and is height-adjustable, with a range of '1-4m Variable' indicated. A 'Test Receiver' is connected to the tower and is shown receiving signals from the EUT. A dimension of '3m' is indicated between the EUT and the tower. A height dimension of '80cm' is shown for the EUT assembly.</p>																				
Procedure	<ol style="list-style-type: none"> The EUT was switched on and allowed to warm up to its normal operating condition. The test was carried out at the selected frequency points obtained from the EUT characterisation. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: <ol style="list-style-type: none"> Vertical or horizontal polarisation (whichever gave the higher emission level over a full rotation of the EUT) was chosen. The EUT was then rotated to the direction that gave the maximum emission. Finally, the antenna height was adjusted to the height that gave the maximum emission. Peak maximization and average measurements were then made for that frequency point with the following Receiver/Spectrum analyser setting: <ul style="list-style-type: none"> - Peak: RBW = 1MHz, VBW = 3MHz, Detector = Peak - Average: RBW = 1MHz, VBW = 10Hz, Detector = Peak Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured. 																				
Remark	<p>Note1: All 3 axes have been investigated. Only the worst case is presented in the test report.</p> <p>Note2: The peak reading of EUT emissions were verified by using a spectrum analyser.</p>																				
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail																				

 Test Data Yes (See below) N/A

 Test Plot Yes (See below) N/A

Test report No.	RF_SL14061701-STE-001_DF990_Rev1.0
Page	18 of 26
FCC ID	VEC-DF990

Radiated Fundamental Field Strength Measurements @ 3 Meter


Freq (MHz)	Corrected Measurement @ 3m (dBuV/m)	Polarity (H/V)	Hgt (cm)	Azt (Deg)	Limit @ 3m (dBuV/m)	Margin (dB)	Detector (pk/avg)
24107.61	114.02	V	100	0	148	-33.98	Peak
24107.61	113.88	V	100	0	128	-14.12	Average
24140.36	113.49	V	100	0	148	-34.51	Peak
24140.36	113.31	V	100	0	128	-14.69	Average
24169.08	114.18	V	100	0	148	-33.82	Peak
24169.08	114.31	V	100	0	128	-13.69	Average
Remark	1. Both horizontal and vertical polarization had been verified and vertical polarity is worst case. 2. Measurement was made at 0.5m distance and data was converted to 3m data. 3. Correction distance factor formula = $20 * \log (3 \text{ meter} / 0.5 \text{ meter}) = 15.56 \text{ dB}$						

Harmonic Spurious Emissions (40GHz-100GHz) Measurements @ 3 Meter

Freq (MHz)	Level (dBuV/m)	Detector (pk/avg)	Polarity (H/V)	Hgt (cm)	Azt (Deg)	Limit @ 3m (dBuV/m)	Margin (dB)	Pass /Fail
48206.84	54.54	Peak	V	100.00	0	108	-53.46	Pass
48206.84	47.04	Average	V	100.00	0	88	-40.96	Pass
48281.45	55.21	Peak	V	100.00	0	108	-52.79	Pass
48281.45	49.71	Average	V	100.00	0	88	-38.29	Pass
48238.14	57.28	Peak	V	100.00	0	108	-50.72	Pass
48238.14	52.71	Average	V	100.00	0	88	-35.29	Pass
Remark	1. Emission was scanned up to 100GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit. If the emission PK level is within Average limit, then the maximization and average measurement are not performed; both horizontal and vertical polarization had been verified. 2. Measurement was made at 0.5m distance and data was converted to 3m data. 3. Correction distance factor formula = $20 * \log (3 \text{ meter} / 0.5 \text{ meter}) = 15.56 \text{ dB}$							

10.4 Radiated Emissions below 1GHz

Requirement(s):


Spec	Requirement	Applicable										
47CFR§15.245(b)	<p>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges</p> <table border="1"> <thead> <tr> <th>Frequency range (MHz)</th><th>Field Strength (uV/m)</th></tr> </thead> <tbody> <tr> <td>30 – 88</td><td>100</td></tr> <tr> <td>88 – 216</td><td>150</td></tr> <tr> <td>216 – 960</td><td>200</td></tr> <tr> <td>Above 960</td><td>500</td></tr> </tbody> </table>	Frequency range (MHz)	Field Strength (uV/m)	30 – 88	100	88 – 216	150	216 – 960	200	Above 960	500	<input checked="" type="checkbox"/>
Frequency range (MHz)	Field Strength (uV/m)											
30 – 88	100											
88 – 216	150											
216 – 960	200											
Above 960	500											
Test Setup	 <p>The diagram illustrates the test setup. A 'Turn Table' is positioned on a 'Ground Plane'. A 'EUT & Support Units' is placed on the turn table, with a vertical height of 80cm indicated. A 'Ant. Tower' is mounted on the turn table, with a height of 1-4m indicated as 'Variable'. A 'Test Receiver' is connected to the turn table. A horizontal distance of 3m is marked between the EUT and the Ant. Tower.</p>											
Procedure	<ol style="list-style-type: none"> 1. The EUT was switched on and allowed to warm up to its normal operating condition. 2. The test was carried out at the selected frequency points obtained from the EUT characterisation. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: <ol style="list-style-type: none"> a. Vertical or horizontal polarisation (whichever gave the higher emission level over a full rotation of the EUT) was chosen. b. The EUT was then rotated to the direction that gave the maximum emission. c. Finally, the antenna height was adjusted to the height that gave the maximum emission. A Quasi-peak measurement was then made for that frequency point. 3. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured. 											
Remark	<p>Note1: All 3 axes have been investigated. Only the worst case is presented in the test report.</p> <p>Note2: The peak reading of EUT emissions were verified by using a spectrum analyser.</p>											
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail											

 Test Data Yes (See below) N/A

 Test Plot Yes (See below) N/A

Radiated Emission Test Results (Below 1GHz)

Test specification:		Radiated Emissions	
Environmental Conditions:	Temp(°C):	22°C	Result:
	Humidity (%):	44%	
	Atmospheric(mbar):	1020	
Mains Power:	5VDC		<input checked="" type="checkbox"/> Pass
Tested by:	Angel Escamilla		<input type="checkbox"/> Fail
Test Date:	07/07/2014		
Remarks:	30 – 1000 MHz		



Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	AF (dB)	Level (dBuV/m)	Measurement Type	Pol (V/H)	Hgt (cm)	Azt (Deg)	Limit (dBuV/m)	Margin (dB)	Pass /Fail
33.14	44.34	1.16	-18.75	26.76	Quasi Max	H	131.00	57.00	40.00	-13.24	Pass
41.06	47.46	1.16	-24.96	23.66	Quasi Max	H	102.00	43.00	40.00	-16.34	Pass
59.80	55.24	1.29	-31.77	24.76	Quasi Max	H	125.00	281.00	40.00	-15.24	Pass
94.75	51.16	1.75	-31.20	21.71	Quasi Max	H	126.00	206.00	43.50	-21.79	Pass
199.33	52.60	2.50	-28.00	27.10	Quasi Max	H	126.00	242.00	43.50	-16.40	Pass
785.86	31.16	4.79	-19.21	16.74	Quasi Max	V	391.00	21.00	46.00	-29.26	Pass

10.5 Radiated Spurious Emissions above 1GHz

Requirement(s):

Spec	Item	Requirement	Applicable
47CFR§15.245(b)	a)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental.	<input checked="" type="checkbox"/>
	b)	or restricted band, emission must also comply with the radiated emission limits specified in 15.209	<input checked="" type="checkbox"/>
Test Setup			
Procedure	<ol style="list-style-type: none"> 1. The EUT was switched on and allowed to warm up to its normal operating condition. 2. The test was carried out at the selected frequency points obtained from the EUT characterisation. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: <ol style="list-style-type: none"> a. Vertical or horizontal polarisation (whichever gave the higher emission level over a full rotation of the EUT) was chosen. b. The EUT was then rotated to the direction that gave the maximum emission. c. Finally, the antenna height was adjusted to the height that gave the maximum emission. 3. Peak maximization and average measurements were then made for that frequency point with the following Receiver/Spectrum analyser setting: <ul style="list-style-type: none"> - Peak: RBW = 1MHz, VBW = 3MHz, Detector = Peak - Average: RBW = 1MHz, VBW = 10Hz, Detector = Peak 4. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured. 		
Remark	Note1: All 3 axes have been investigated. Only the worst case is presented in the test report. Note2: The peak reading of EUT emissions were verified by using a spectrum analyser.		
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data Yes (See below) N/A

Test Plot Yes (See below) N/A

Test report No.	RF_SL14061701-STE-001_DF990_Rev1.0
Page	22 of 26
FCC ID	VEC-DF990

Radiated Spurious Emissions Test Results Above 1GHz

Test specification:	Radiated Emissions			
Environmental Conditions:	Temp(°C):	21°C	Result: <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
	Humidity (%):	44%		
	Atmospheric(mbar):	1020		
Mains Power:	5VDC			
Tested by:	Angel Escamilla			
Test Date:	07/14/2014			
Remarks:	-			

Spurious Emissions (1GHz-18GHz) Measurements @ 3 Meter

Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	AF (dB)	Level (dBuV/m)	Measurement Type	Pol (H/V)	Hgt (cm)	Azt (Deg)	Limit (dBuV/m)	Margin (dB)	Pass /Fail
4020.04	41.49	9.34	1.57	52.40	Peak	V	304.00	109.00	74.00	-21.60	Pass
15269.34	41.22	5.50	9.58	56.30	Peak	V	199.00	3.00	74.00	-17.70	Pass
4020.04	28.29	9.34	1.57	39.19	Average	V	224.00	276.00	54.00	-14.81	Pass
15269.34	25.57	5.50	9.58	40.65	Average	V	199.00	3.00	54.00	-13.35	Pass
Remark	Emission was scanned up to 18GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit. If the emission PK level is within Average limit, then the maximization and average measurement are not performed; both horizontal and vertical polarization had been verified.										

Spurious Emissions (above 18GHz) Measurements @ 3 Meter

Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	AF (dB)	Level (dBuV/m)	Measurement Type	Pol (H/V)	Hgt (cm)	Azt (Deg)	Limit (dBuV/m)	Margin (dB)	Pass /Fail
27398.51	29.47	7.99	6.44	43.90	Peak	V	194.00	29.00	74.00	-30.10	Pass
32225.01	32.23	9.45	8.70	50.38	Peak	V	102.00	332.00	74.00	-23.62	Pass
27398.51	22.10	7.99	6.44	36.53	Average	V	194.00	29.00	54.00	-17.47	Pass
32225.01	16.53	9.45	8.70	34.68	Average	V	102.00	332.00	54.00	-19.32	Pass
Remark	1. Emission was scanned up to 100GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit. If the emission PK level is within Average limit, then the maximization and average measurement are not performed; both horizontal and vertical polarization had been verified.										

Test report No.	RF_SL14061701-STE-001_DF990_Rev1.0
Page	23 of 26
FCC ID	VEC-DF990

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Cycle	Cal Due	In use
Conducted Emissions						
R & S Receiver	ESIB 40	100179	04/20/2014	1 Year	04/20/2015	<input checked="" type="checkbox"/>
R&S LISN	ESH2-Z5	861741/013	05/18/2014	1 Year	05/18/2015	<input checked="" type="checkbox"/>
CHASE LISN	MN2050B	1018	07/24/2013	1 Year	07/24/2014	<input checked="" type="checkbox"/>
Sekonic Hygro Hermograph	ST-50	HE01-000092	05/25/2014	1 Year	05/25/2015	<input checked="" type="checkbox"/>
Radiated Emissions						
R & S Receiver	ESL6	100178	03/01/2014	1 Year	03/01/2015	<input checked="" type="checkbox"/>
R & S Receiver	ESIB 40	100179	04/20/2014	1 Year	04/20/2015	<input checked="" type="checkbox"/>
ETS-Lingren Loop Antenna	6512	00049120	05/13/2014	1 Year	05/13/2015	<input type="checkbox"/>
Bi-Log antenna (30MHz~2GHz)	JB1	A030702	02/09/2014	1 Year	02/09/2015	<input checked="" type="checkbox"/>
Horn Antenna (1-26.5GHz)	3115	10SL0059	04/26/2014	1 Year	04/26/2015	<input checked="" type="checkbox"/>
Horn Antenna (18-40 GHz)	AH-840	101013	04/23/2014	1 Year	04/23/2015	<input checked="" type="checkbox"/>
Pre-Amplifier (1-26.5GHz)	8449B	3008A00715	05/30/2014	1 Year	05/30/2015	<input checked="" type="checkbox"/>
Microwave Preamplifier (18-40 GHz)	PA-840	181251	05/30/2014	1 Year	05/30/2015	<input checked="" type="checkbox"/>
Harmonic Mixer	11970 Q	3003A01197	06/13/2014	1 Year	06/13/2015	<input checked="" type="checkbox"/>
Horn Antenna	261B	10SL0185	04/26/2014	1 Year	04/26/2015	<input checked="" type="checkbox"/>
3 Meters SAC	3M	N/A	10/13/2013	1 Year	10/13/2014	<input checked="" type="checkbox"/>
10 Meters SAC	10M	N/A	06/05/2014	1 Year	06/05/2015	<input checked="" type="checkbox"/>
Sekonic Hygro Hermograph	ST-50	HE01-000092	05/25/2014	1 Year	05/25/2015	<input checked="" type="checkbox"/>
RF Conducted Measurement						
Spectrum Analyzer	N9010A	MY50210206	05/30/2014	1 Year	05/30/2015	<input type="checkbox"/>
Spectrum Analyzer	E4407B	US88441016	05/31/2014	1 Year	05/31/2015	<input type="checkbox"/>
R & S Receiver	ESIB 40	100179	04/20/2014	1 Year	04/20/2015	<input type="checkbox"/>

Test report No.	RF_SL14061701-STE-001_DF990_Rev1.0
Page	24 of 26
FCC ID	VEC-DF990

Annex B. USER MANUAL, BLOCK & CIRCUIT DIAGRAM

Please see attachment

Annex C. SIEMIC Accreditation

Accreditations	Document	Scope / Remark
ISO 17025 (A2LA)		Please see the documents for the detailed scope
ISO Guide 65 (A2LA)		Please see the documents for the detailed scope
TCB Designation		A1 , A2 , A3 , A4 , B1 , B2 , B3 , B4 , C
FCC DoC Accreditation		FCC Declaration of Conformity Accreditation
FCC Site Registration		3 meter site
FCC Site Registration		10 meter site
IC Site Registration		3 meter site
IC Site Registration		10 meter site
EU NB		Radio & Telecommunications Terminal Equipment: EN45001 – EN ISO/IEC 17025
		Electromagnetic Compatibility: EN45001 – EN ISO/IEC 17025
Singapore iDA CB(Certification Body)	 	Phase I , Phase II
Vietnam MIC CAB Accreditation		Please see the document for the detailed scope
Hong Kong OFCA		(Phase II) OFCA Foreign Certification Body for Radio and Telecom
		(Phase I) Conformity Assessment Body for Radio and Telecom
Industry Canada CAB		Radio: Scope A – All Radio Standard Specification in Category I
		Telecom: CS-03 Part I, II, V, VI, VII, VIII

Japan Recognized Certification Body Designation	 	Radio: A1. Terminal equipment for purpose of calling Telecom: B1. Specified radio equipment specified in Article 38-2, Paragraph 1, Item 1 of the Radio Law
Korea CAB Accreditation		EMI: KCC Notice 2008-39, RRL Notice 2008-3: CA Procedures for EMI KN22: Test Method for EMI EMS: KCC Notice 2008-38, RRL Notice 2008-4: CA Procedures for EMS KN24, KN61000-4-2, -4-3, -4-4, -4-5, -4-6, -4-8, -4-11: Test Method for EMS Radio: RRL Notice 2008-26, RRL Notice 2008-2, RRL Notice 2008-10, RRL Notice 2007-49, RRL Notice 2007-20, RRL Notice 2007-21, RRL Notice 2007-80, RRL Notice 2004-68 Telecom: President Notice 20664, RRL Notice 2007-30, RRL Notice 2008-7 with attachments 1, 3, 5, 6; President Notice 20664, RRL Notice 2008-7 with attachment 4
Taiwan NCC CAB Recognition		LP0002, PSTN01, ADSL01, ID0002, IS6100, CNS14336, PLMN07, PLMN01, PLMN08
Taiwan BSMI CAB Recognition		CNS 13438
Japan VCCI		R-3083: Radiation 3 meter site C-3421: Main Ports Conducted Interference Measurement T-1597: Telecommunication Ports Conducted Interference Measurement EMC: AS/NZS CISPR 11, AS/NZS CISPR 14.1, AS/NZS CISPR22, AS/NZS 61000.6.3, AS/NZS 61000.6.4 Radio-communications: AS/NZS 4281, AS/NZS 4268, AS/NZS 4280.1, AS/NZS 4280.2, AS/NZS 4295, AS/NZS 4582, AS/NZS 4583, AS/NZS 4769.1, AS/NZS 4769.2, AS/NZS 4770, AS/NZS 4771 Telecommunications: AS/ACIF S002:05, AS/ACIF S003:06, AS/ACIF S004:06 AS/ACIF S006:01, AS/ACIF S016:01, AS/ACIF S031:01, AS/ACIF S038:01, AS/ACIF S040:01, AS/ACIF S041:05, AS/ACIF S043.2:06, AS/ACIF S60950.1
Australia CAB Recognition		AS/ACIF S002, AS/ACIF S003, AS/ACIF S004, AS/ACIF S006, AS/ACIF S016, AS/ACIF S031, AS/ACIF S038, AS/ACIF S040, AS/ACIF S041, AS/ACIF S043.2
Australia NATA Recognition		AS/ACIF S002, AS/ACIF S003, AS/ACIF S004, AS/ACIF S006, AS/ACIF S016, AS/ACIF S031, AS/ACIF S038, AS/ACIF S040, AS/ACIF S041, AS/ACIF S043.2