

Declaration on radiation safety standard conformance

To whom it may concern:

Hopling Technologies B.V.

Camerastraat 10

1322 BC Almere

The Netherlands

declares that the following product

Description: Wireless Mesh Node

FCC ID: VEE-H5486868

Manufacturer: Hopling Technologies B.V.

Brand: Xnet

Model: Viper, Raptor

has a maximum e.i.r.p. of 19.4 dBm (87.1 mW, maximum conducted output power for each card of 10.2 dbm plus antenna gain of 9.2 dBi) in the frequency range of 5180 – 5240 MHz, which means that the worst case prediction of power density at 20 cm distance (worst case) can be calculated as follows :

Total radiated output power with 4 cards simultaneously transmitting: $4 \times 87.1 \text{ mW} = 348.4 \text{ mW e.i.r.p.}$

$$S = \frac{EIRP}{4 \times \pi \times R^2}$$

$$S = \frac{348.4 \text{ mW}}{4 \times \pi \times (20\text{cm})^2} = 0.07 \text{ mW/cm}^2 \quad (\text{limit} = 1.0 \text{ mW/cm}^2)$$

This means that according to OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), the equipment fulfills the requirements on power density for general population/uncontrolled exposure and therefore fulfills the requirements of 47 CFR Part 15.407 (f).