

1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FCC ID: VEP-SCPCAM-TFT

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: K-Mark Industrial Limited.
Address of applicant: Flat A, 7/F., Mai On Ind. Bldg 17-21 Kung Yip St., Kwai Chung
Hong Kong

Manufacturer: GSM, LLC
Address of manufacturer: PO Box 535189, Grand Prairie, TX 75053-5189

General Description of EUT	
Product Name:	Wifi Optical Scope Cam
Trade Name:	/
Model No.:	SME-SCPCAM-TFT
Adding Model(s):	/
Rated Voltage:	DC 3.7V
Note: The test data is gathered from a production sample provided by the manufacturer.	

Technical Characteristics of EUT	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n-HT20 2422-2452MHz for 802.11n-HT40
RF Output Power:	6.39dBm (Conducted)
Type of Modulation:	DBPSK,BPSK,DQPSK,QPSK,16QAM,64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 150Mbps
Quantity of Channels:	11 for 802.11b/g/n-HT20 7 for 802.11n-HT40
Channel Separation:	5MHz
Type of Antenna:	Integral Antenna
Antenna Gain:	3.05dBi

Note: The test data is gathered from a production sample provided by the manufacturer.

1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalents power density

1.3 MPE Calculation Method

$$S = (30 * P * G) / (377 * R^2)$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.4 MPE Calculation Result

Wi-Fi:

Maximum Tune-Up output power: 6.5 (dBm)

Maximum peak output power at antenna input terminal: 4.47mW)

Prediction distance: >20(cm)

Prediction frequency: 2462(MHz)

Antenna gain: 3.05(dBi)

Directional gain (numeric gain): 4.84

The worst case is power density at prediction frequency at 20cm: 0.043 (mw/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

Result: Pass