

June 26, 2007

Federal Communications Commission
Authorization and Evaluation Division

Declaration regarding application for certification of FCC ID: VFC031604

Pursuant to Part 15.231 FCC requirements, Etratech Inc. hereby declares the E.U.T. either Complies or Not Applicable to these 5 requirements.

- (1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released. Complies.
- (2) A transmitter activated automatically shall cease transmission within 5 seconds after activation. Not Applicable.
- (3) Periodic transmissions at regular predetermined intervals are not permitted. However, polling or supervision transmissions, including data, to determine system integrity of transmitters used in security or safety applications are allowed if the total duration of transmissions does not exceed more than two seconds per hour for each transmitter. There is no limit on the number of individual transmissions, provided the total transmission time does not exceed two seconds per hour. Not Applicable.
- (4) Intentional radiators which are employed for radio control purposes during emergencies involving fire, security, and safety of life, when activated to signal an alarm, may operate during the pendency of the alarm condition. Not Applicable.
- (5) Transmission of set-up information for security systems may exceed the transmission duration limits in paragraphs (a)(1) and (a)(2) of this section, provided such transmissions are under the control of a professional installer and do not exceed ten seconds after a manually operated switch is released or a transmitter is activated automatically. Such set-up information may include data. Not Applicable.

Sincerely,



Wilson Sheddin
Product Engineering Specialist,
Etratech Inc.

