



www.ecmg-global.net

FCC CLASS II PERMISSION CHANGE TEST REPORT

On Model Name: Microwave Oven

Model Numbers: XM720CYY-PM

Brand Name:

FCC ID Number: VG8XM720CYY-PM

Prepared for Guangdong Midea Microwave and Electrical
Appliances Manufacturing Co.,Ltd

According to

FCC Part 18(2010)

Industrial, Scientific and Medical Equipment

FCC/OST MP-5(1986)

FCC methods of measurements of radio noise emission from
industrial, scientific and medical equipment

Test Report#: GUA-1112-10765-FCC

Prepared by: Sewen Guo

Reviewed by: Jawnen Yin

QC Manager: Swall Zhang

Test Report Released by: Swall Zhang
Swall Zhang

January 16, 2012

Date

List Attached Files

Exhibit Type	File Description	File Name
<i>Test Report</i>	<i>Test Report</i>	<i>VG8XM720CYY-PM_Test report.PDF</i>
<i>Operation Description</i>	<i>Technical Description</i>	<i>VG8XM720CYY-PM_operation description.PDF</i>
<i>External Photos</i>	<i>External Photos</i>	<i>VG8XM720CYY-PM_External Photos.PDF</i>
<i>Internal Photos</i>	<i>Internal Photos</i>	<i>VG8XM720CYY-PM_Internal Photos.PDF</i>
<i>Block Diagram</i>	<i>Block Diagram</i>	<i>VG8XM720CYY-PM _Block diagram. PDF</i>
<i>Schematics</i>	<i>Circuit Diagram</i>	<i>VG8XM720CYY-PM _Schematics. PDF</i>
<i>ID Label/Location</i>	<i>Label and Location</i>	<i>VG8XM720CYY-PM _Label & Location. PDF</i>
<i>User Manual</i>	<i>User Manual</i>	<i>VG8XM720CYY-PM _User Manual. PDF</i>
<i>Test setup photos</i>	<i>Test setup photos</i>	<i>VG8XM720CYY-PM_Test Setup.PDF</i>

Test Location

Tests performed in a Certified ANSI Semi-Anechoic Chamber and Shielded Room.

Test Site Location:

***GD WITOL VACUUM ELECTRONIC
EMC TEST LABORATORY***

*BeiJiao, ShunDe, Foshan,
GuangDon, 528311, China*

Tel:

(86)-757-26326917

Fax:

(86)-757-26656995

Test Facility

- *FCC - Registration No.: 910385*

GD WITOL VACUUM ELECTRONIC EMC TEST LABORATORY has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC was maintained in our files.

Table of Contents

GOVERNMENT DISCLAIMER NOTICE	1
REPRODUCTION CLAUSE	1
OPINIONS AND INTERPRETATIONS	1
STATEMENT OF MEASUREMENT UNCERTAINTY	1
ADMINISTRATIVE DATA	2
EUT DESCRIPTION	3
EUT MODEL DERIVED	4
TEST SUMMARY	5
LOAD FOR MICROWAVE OVEN	6
EQUIPMENT MODIFICATION	6
EUT SAMPLE PHOTOS FOR MODEL EM720CWL-PM	7
TEST SYSTEM DETAILS	12
CONFIGURATION OF TESTED SYSTEM	13
ATTACHMENT 1 - RADIATION HAZARD TEST	14
ATTACHMENT 2 - INPUT POWER MEASUREMENT	16
ATTACHMENT 3 - RF OUTPUT POWER MEASUREMENT	18
ATTACHMENT 4 - OPERATING FREQUENCY MEASUREMENT	20
ATTACHMENT 5 - CONDUCTED EMISSION TEST RESULTS	23
ATTACHMENT 6 - RADIATED EMISSION TEST RESULTS	27

Government Disclaimer Notice

When government drawing, specification, or other data are used for any purpose other than in connection with a definitely related government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawing, specifications, or other data, is not to be regarded by implication or otherwise in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell patented invention that may in any way be related thereto. This report must not be used to claim product endorsement by NVLAP or any agency of the U.S. Government.

Reproduction Clause

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from ECMG Electronic Technical Testing Corp (Shenzhen).

Opinions and Interpretations

This test report relates to the above mentioned equipment under test (EUT). Without the permission of ECMG Electronic Technical Testing Corp (Shenzhen) this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark on this or similar products. The manufacturer has sole responsibility of continued compliance of the device.

Statement of Measurement Uncertainty

The data and results referenced in the document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities that can account for a nominal measurement error. Furthermore, component and process variability of devices similar to that tested may result in additional deviation.

Administrative Data

Test Sample : Microwave Oven

Model Numbers : XM720CYY-PM

Model Tested : EM720CWL-PM

Brand Name :  Midea

Date of Receipt : January 8, 2012

Date Tested : January 10, 2012

Applicant : Guangdong Midea Microwave and Electrical Appliances Manufacturing Co.,Ltd.

Address : No.6, Yong An Road, Beijiao, Shunde, Foshan. Guangdong, 528311, China.

Manufacturer : Guangdong Midea Microwave and Electrical Appliances Manufacturing Co.,Ltd.

Address : No.6, Yong An Road, Beijiao, Shunde, Foshan. Guangdong, 528311, China.

Factory : Guangdong Midea Microwave and Electrical Appliances Manufacturing Co.,Ltd.

Address : No.6, Yong An Road, Beijiao, Shunde, Foshan. Guangdong, 528311, China.

EUT Description

Guangdong Midea Microwave and Electrical Appliances Manufacturing Co.,Ltd., model tested EM720CWL-PM (referred to the eut in this report) is a microwave oven. The EUT main features are as belows:

Power Supply	120V~ 60Hz
Rated Input Power (Microwave)	1050W
Rated Output Power (Microwave)	700 W
Frequency	2450 MHz (Class B/Group 2)
Magnetron Model	2M217J
Magnetron Manufacturer	WITOL

For more informations please refer to user's manual of EUT.

EUT Model Derived

XM720CYY-PM model designations are as follows:

X=E or A ;

M: indicate microwave function;

720: "7" indicate the microwave output power is 700W, "20" indicate cavity capacity is 20 liters;

C: indicate the design No.;

YY= 0-9 or A-Z, indicate different appearance;

Model of EM720CWL-PM was selected for the final test.

Test Summary

The electromagnetic compatibility requirements on model EM720CWL-PM for this test is stated below. All results listed in this report relate exclusively to this above-mentioned model as the Equipment Under Test. This report confers no approval or endorsement upon any other component, host or subsystem used in the test set-up.

Emission Tests				
Specifications	Description	Test Results	Test Point	Remark
FCC Part 18:2010 FCC/OST MP-5:1986 ANSI C63.4-2009	Radiation Hazard Measurement	Passed	Enclosure	Attachment 1
FCC Part 18:2010 FCC/OST MP-5:1986 ANSI C63.4-2009	Input Power Measurement	Passed	AC Input Port	Attachment 2
FCC Part 18:2010 FCC/OST MP-5:1986 ANSI C63.4-2009	RF Output power Measurement	Passed	EUT	Attachment 3
FCC Part 18:2010 FCC/OST MP-5:1986 ANSI C63.4-2009	Operating Frequency Measurement	Passed	EUT	Attachment 4
FCC Part 18:2010 FCC/OST MP-5:1986 ANSI C63.4-2009	Conducted Emission	Passed	AC Input Port	Attachment 5
FCC Part 18:2010 FCC/OST MP-5:1986 ANSI C63.4-2009	Radiated Emission	Passed	Enclosure	Attachment 6

Load for Microwave Oven

For all measurements the energy developed by the oven was absorbed by a dummy load consisting of a quantity of tag water in a beaker. If the oven was provided with a shelf or other utensil support, this support was in its initial normal position. For ovens rated at 1000watts or less power output, the beaker contained quantities of water as listed in the following subparagraphs. For ovens rated at more than 1000watts output, each quantity was increased by 50% for each 500watts or fraction thereof in excess of 1000 watts. Additional beakers were used if necessary.

- Load for power output measurement: 1000 milliliters of water in the beaker located in the center of the oven.*
- Load for frequency measurement: 1000 milliliters of water in the beaker located in the center of the oven.*
- Load for measurement of radiation on second and third harmonic: Two loads, one of 700 and the other of 300 milliliters, of water are used. Each load is tested both with the beaker located in the center of the oven and with it in the right front corner.*
- Load for all other measurements: 700 milliliters of water, with the beaker located in the center of the oven.*

Equipment Modification

Any modification installed previous to testing by Guangdong Midea Microwave and Electrical Appliances Manufacturing Co.,Ltd. will be incorporated in each production model sold or leased in United States.

There were no modifications installed by ECMG Electronic Technical Testing Corp(Shenzhen) test personnel.

EUT Sample Photos for Model EM720CWL-PM



EUT- Front View



EUT- Rear View

Test Report #: GUA-1112-10765-FCC

Prepared for Guangdong Midea Microwave and Electrical Appliances Manufacturing Co.,Ltd
Prepared by ECMG Electronic Technical Testing Corp (Shenzhen).


Page 7 of 30




Door Opened View




EUT- Inside View #1




EUT- Inside View #2



Magnetron View



Power Filter Board Top View




Power Filter Board bottom View

Test Report #: GUA-1112-10765-FCC

Prepared for Guangdong Midea Microwave and Electrical Appliances Manufacturing Co.,Ltd
Prepared by ECMG Electronic Technical Testing Corp (Shenzhen).

Page 10 of 30



Motherboard top view



Motherboard bottom view

Test Report #: GUA-1112-10765-FCC


Prepared for Guangdong Midea Microwave and Electrical Appliances Manufacturing Co.,Ltd
Prepared by ECMG Electronic Technical Testing Corp (Shenzhen).

Page 11 of 30

Test System Details

EUT										
Model Numbers:	XM720CYY-PM									
Model Tested:	EM720CWL-PM									
Description:	Microwave Oven									
Manufacturer:	Guangdong Midea Microwave and Electrical Appliances Manufacturing Co.,Ltd.									
Support Equipment										
N/A										
Cable Description										
Description	From	To	Length (Meters)	Shielded (Y/N)	Ferrite (Y/N)					
Power Cable	EUT	Plug	1.20	N	N					

Configuration of Tested System



ATTACHMENT 1 - RADIATION HAZARD TEST

CLIENT:	Guangdong Midea Microwave and Electrical Appliances Manufacturing Co.,Ltd.	TEST STANDERD:	FCC Part 18
MODEL NUMBERS:	XM720CYY-PM	PRODUCT:	Microwave Oven
MODEL TESTED:	EM720CWL-PM	EUT DESIGNATION:	Home or Office
TEMPERATURE:	22°C	HUMIDITY:	60%RH
ATM PRESSURE:	101.1kPa	GROUNDING:	Through AC Power Cord
TESTED BY:	Sewen Guo	DATE OF TEST:	January 10, 2012
TEST REFERENCE:	ANSI C63.4-2009, FCC/OST MP-5:1986		
TEST PROCEDURE:	The EUT was set up according to the FCC MP-5 and FCC Part 18 for Radiation Hazard Measurement. The measurement was using a microwave leakage meter to measure the Radiation leakage in the as-received condition with the oven door closed. A 700ml water load in a beaker was located in the center of the oven and the Microwave Oven was set to maximum power. While the oven operating, the microwave meter will check the leakage and then record the maximum leakage.		
TESTED RANGE:	N/A		
TEST VOLTAGE:	120VAC / 60Hz		
RESULTS:	<p>There was no microwave leakage exceeding a power level of 0.01 mW/cm² observed at any point 5cm or more from the external surface of the oven.</p> <p>A maximum of 1.0 mW/cm² is allowed in accordance with the applicable FCC standards. Hence, microwave leakage in the as-received condition with the oven door closed was below the maximum allowed. The test results relate only to the equipment under test provided by client.</p>		
CHANGES OR MODIFICATIONS:	There were no modifications installed by ECMG Electronic Technical Testing Corp (Shenzhen) (China) test personnel.		
M. UNCERTAINTY:	0.0001 mW/cm ²		

Test Report #: GUA-1112-10765-FCC

Prepared for Guangdong Midea Microwave and Electrical Appliances Manufacturing Co.,Ltd
Prepared by ECMG Electronic Technical Testing Corp (Shenzhen).

Page 14 of 30

Test Equipments List:

Test Equipment	Manufacturer	Model	Serial No.	Last Cal.	Cal. Due
Microwave Measurement	HOLADAY	HI-1710A	00052558	11/10/2011	11/09/2012
Note: All testing were performed using internationally recognized standards. All test instruments were calibrated and traceable to the National Institute of Standards and Technology (NIST).					

SIGNED BY:

Severine


ENGINEER

REVIEWED BY:

Jamery

SENIOR ENGINEER

Radiation Hazard Test Set-up:



Test Report #: GUA-1112-10765-FCC

Prepared for Guangdong Midea Microwave and Electrical Appliances Manufacturing Co.,Ltd
Prepared by ECMG Electronic Technical Testing Corp (Shenzhen).

Page 15 of 30

ATTACHMENT 2 - INPUT POWER MEASUREMENT

CLIENT:	Guangdong Midea Microwave and Electrical Appliances Manufacturing Co.,Ltd.	TEST STANDERD:	FCC Part 18
MODEL NUMBERS:	XM720CYY-PM	PRODUCT:	Microwave Oven
MODEL TESTED:	EM720CWL-PM	EUT DESIGNATION:	Home or Office
TEMPERATURE:	22°C	HUMIDITY:	60%RH
ATM PRESSURE:	101.1kPa	GROUNDING:	Through AC Power Cord
TESTED BY:	Sewen Guo	DATE OF TEST:	January 10, 2012
TEST REFERENCE:	ANSI C63.4-2009, FCC/OST MP-5:1986		
TEST PROCEDURE:	The EUT was set up according to the FCC MP-5 and FCC Part 18 for Input power Measurement. The input power and current was measured using a power analyzer. A 700ml water load in a beaker was located in the center of the oven and the Microwave Oven was set to maximum power. While the oven is operating, use a voltmeter and an ampmeter to test the AC input voltage and current.		
TESTED RANGE:	N/A		
TEST VOLTAGE:	120VAC / 60Hz		
RESULTS :	Based on the measured input power, the EUT was found to be operating within the intended specifications. The test results relate only to the equipment under test provided by client.		
CHANGES OR MODIFICATIONS:	There were no modifications installed by ECMG Electronic Technical Testing Corp(Shenzhen) (China) test personnel.		
M. UNCERTAINTY :	± 5W		

Test Report #: GUA-1112-10765-FCC

Prepared for Guangdong Midea Microwave and Electrical Appliances Manufacturing Co.,Ltd
Prepared by ECMG Electronic Technical Testing Corp (Shenzhen).

Page 16 of 30

Test Data:

Input Voltage (Vac/Hz)	Input Current (amps)	Measured Input Power (watts)	Rated Input Power (watts)
120.6	9.30	1036	1050


Test Equipments List :

Test Equipment	Manufacturer	Model	Serial No.	Last Cal.	Cal. Due
Power Meter	Ainuo	AN8726C	058704195	08/13/2011	08/12/2012

Note: All testing were performed using internationally recognized standards. All test instruments were calibrated and traceable to the National Institute of Standards and Technology (NIST).

SIGNED BY:*Severino*

ENGINEER**REVIEWED BY:***Jamelynn*

SENIOR ENGINEER**Input Power Test Set-Up :****Test Report #:** GUA-1112-10765-FCC**Prepared for** Guangdong Midea Microwave and Electrical Appliances Manufacturing Co.,Ltd
Prepared by ECMG Electronic Technical Testing Corp (Shenzhen).

Page 17 of 30

ATTACHMENT 3 - RF OUTPUT POWER MEASUREMENT

CLIENT:	Guangdong Midea Microwave and Electrical Appliances Manufacturing Co.,Ltd.	TEST STANDERD:	FCC Part 18
MODEL NUMBERS:	XM720CYY-PM	PRODUCT:	Microwave Oven
MODEL TESTED:	EM720CWL-PM	EUT DESIGNATION:	Home or Office
TEMPERATURE:	22°C	HUMIDITY:	60%RH
ATM PRESSURE:	101.1kPa	GROUNDING:	Through AC Power Cord
TESTED BY:	Sewen Guo	DATE OF TEST:	January 10, 2012
TEST REFERENCE:	ANSI C63.4-2009, FCC/OST MP-5:1986		
TEST PROCEDURE:	<p>The EUT was set up according to the FCC MP-5 and FCC Part 18 for RF output power Measurement. The Caloric Method was used to determine maximum RF output power. The initial temperature of the water load was measured. A 1000ml water load in a beaker was located in the center of the oven. The oven was operated at maximum output power for 120 seconds, the temperature of the water was re-measured.</p> <p>RF Output Power</p> $= (4.2\text{ joules/calorie})(\text{volume in milliliters})(\text{temperature rise}) / (\text{time in seconds})$ $= 4.2 \text{ joules/calorie} \times 1000 \times (\text{Final Temp} - \text{Initial Temp}) / 120$		
TESTED RANGE:	N/A		
TEST VOLTAGE:	120VAC / 60Hz		
RESULTS:	RF Output Power = 525 watts. The test results relate only to the equipment under test provided by client.		
CHANGES OR MODIFICATIONS:	There were no modifications installed by ECMG Electronic Technical Testing Corp (Shenzhen).(China) test personnel.		
M. UNCERTAINTY:	$\pm 0.3^\circ\text{C}$		

Test Report #: GUA-1112-10765-FCC


Prepared for Guangdong Midea Microwave and Electrical Appliances Manufacturing Co.,Ltd
Prepared by ECMG Electronic Technical Testing Corp (Shenzhen). Page 18 of 30

Test Data:

Quality of Water (ml)	Starting Temperature (°C)	Final Temperature (°C)	Elapsed Time (Seconds)	RF Output Power (watts)
1000	20.0	35.0	120S	525

Test Equipments List :

Test Equipment	Manufacturer	Model	Serial No.	Last Cal.	Cal. Due
Digit Thermometer	Fluke Corporation	Fluke 51 II	87500204	10/26/2011	10/25/2012
Stopwatch	CASIO	HS-3	005Q08R	10/22/2011	10/21/2012
Note: All testing were performed using internationally recognized standards. All test instruments were calibrated and traceable to the National Institute of Standards and Technology (NIST).					

SIGNED BY:*Severino***ENGINEER****REVIEWED BY:***Janetym***SENIOR ENGINEER****RF Output Power Test Set-Up :****Test Report #:** GUA-1112-10765-FCC**Prepared for Guangdong Midea Microwave and Electrical Appliances Manufacturing Co.,Ltd**
Prepared by ECMG Electronic Technical Testing Corp (Shenzhen).**Page 19 of 30**

ATTACHMENT 4 - OPERATING FREQUENCY MEASUREMENT

CLIENT:	Guangdong Midea Microwave and Electrical Appliances Manufacturing Co.,Ltd.	TEST STANDERD:	FCC Part 18
MODEL NUMBERS:	XM720CYY-PM	PRODUCT:	Microwave Oven
MODEL TESTED:	EM720CWL-PM	EUT DESIGNATION:	Home or Office
TEMPERATURE:	22°C	HUMIDITY:	60%RH
ATM PRESSURE:	101.1kPa	GROUNDING:	Through AC Power Cord
TESTED BY:	Sewen Guo	DATE OF TEST:	January 10, 2012
TEST REFERENCE:	ANSI C63.4-2009, FCC/OST MP-5:1986		
TEST PROCEDURE:	<p>The EUT was set up according to the FCC MP-5 and FCC Part 18 for Operating Frequency Measurement.</p> <ol style="list-style-type: none"> 1) The variation of frequency with time. The operating frequency was measured using a spectrum analyzer. Starting with the EUT at room temperature, a 1000ml water load in a beaker was located in the center of the oven. Set a spectrum analyzer with antenna at 3 meters distance form the oven and the oven was operated at maximum output power. The fundamental operating frequency was monitored until the water load was reduced to 20 percent of the original load. 2) The variation of frequency with Line Voltage. The operating frequency was measured using a spectrum analyzer. The EUT was operated/warmed by at least 10 minutes of use with a 1000ml water load at room temperature at the beginning of the test. Then the operating frequency was monitored as the input voltage was varied between 80 and 125 percent of the nominal rating. 		
TESTED RANGE:	2450 ± 50MHz		
TEST VOLTAGE:	120VAC / 60Hz		
RESULTS:	Please refer to following pages for details of the variation in operating frequency with time & line voltage measurement. The test results relate only to the equipment under test provided by client.		
CHANGES OR MODIFICATIONS:	There were no modifications installed by ECMG Electronic Technical Testing Corp (Shenzhen) (China) test personnel.		
M. UNCERTAINTY:	Freq. ±10kHz		

Test Report #: GUA-1112-10765-FCC

Prepared for Guangdong Midea Microwave and Electrical Appliances Manufacturing Co.,Ltd
Prepared by ECMG Electronic Technical Testing Corp (Shenzhen).

Page 20 of 30

Test Data:**Variation in Operating Frequency with Time:**

Minimum Frequency (MHz)	Maximum Frequency (MHz)
2477.45	2479.46

Variation in Operating Frequency with Line Voltage:

Minimum Frequency (MHz)	Maximum Frequency (MHz)
2479.86	2480.66

Note: Line voltage varied from 96Vac to 150Vac.

Test Equipments List :

Test Equipment	Manufacturer	Model	Serial No.	Last Cal.	Cal. Due
EMI test receiver	R&S	ESI26	SB3436	01/25/2011	01/24/2012
Horn Antenna	R&S	HF906	SB3435	01/25/2011	01/24/2012
3m Semi-anechoic chamber	Albatross Projects	9x6x6	SB3450/01	03/21/2011	03/20/2012

Note: All testing were performed using internationally recognized standards. All test instruments were calibrated and traceable to the National Institute of Standards and Technology (NIST).

SIGNED BY:

Severino

ENGINEER

REVIEWED BY:

Jammy

SENIOR ENGINEER

Operating Frequency Test Set-up:




ATTACHMENT 5 - CONDUCTED EMISSION TEST RESULTS

CLIENT:	Guangdong Midea Microwave and Electrical Appliances Manufacturing Co.,Ltd.	TEST STANDERD:	FCC Part 18
MODEL NUMBERS:	XM720CYY-PM	PRODUCT:	Microwave Oven
MODEL TESTED:	EM720CWL-PM	EUT DESIGNATION:	Home or Office
TEMPERATURE:	22°C	HUMIDITY:	60%RH
ATM PRESSURE:	101.1kPa	GROUNDING:	Through AC Power Cord
TESTED BY:	Sewen Guo	DATE OF TEST:	January 10, 2012
TEST REFERENCE:	ANSI C63.4-2009, FCC/OST MP-5:1986		
TEST PROCEDURE:	The EUT was set up according to the guideline of ANSI C63.4-2009 & FCC MP-5 for conducted emissions. The measurement was using a AMN on each line and an EMI receiver peak scan was made at the frequency measurement range. The six highest significant peaks were then marked, and these signals were then quasi-peaked and averaged. The frequency range investigated was from 150kHz to 30MHz.		
TESTED RANGE:	150kHz to 30MHz		
TEST VOLTAGE:	120VAC / 60Hz		
RESULTS:	The EUT meets the requirements of test reference for conducted emissions. The test results relate only to the equipment under test provided by client.		
CHANGES OR MODIFICATIONS:	There were no modifications installed by ECMG Electronic Technical Testing Corp (Shenzhen). (China) test personnel.		
M. UNCERTAINTY:	±2.5 dB		


Test Report #: GUA-1112-10765-FCC

Prepared for Guangdong Midea Microwave and Electrical Appliances Manufacturing Co.,Ltd
Prepared by ECMG Electronic Technical Testing Corp (Shenzhen).

Page 23 of 30



Line L Conducted Emission Graph



Line N Conducted Emission Graph

Test Data:

Lines (L/N)	Frequency (MHz)	Corrected QP Level (dBuV)	Limits QP (dBuV)	Margin QP(dB)	Corrected AV Level (dBuV)	Limits AV (dBuV)	Margin QP (dB)
L	0.165	39.8	65.2	-25.4	15.4	55.2	-39.8
L	0.180	38.4	64.5	-26.1	13.1	54.5	-41.4
L	0.479	29.0	56.4	-27.4	6.3	46.4	-40.1
N	0.205	35.1	63.4	-28.3	13.4	53.4	-40.0
N	0.235	35.0	62.3	-27.3	13.4	52.3	-38.9
N	0.375	30.8	58.4	-27.6	8.3	48.4	-40.1

Note :

- 1) All readings are using a bandwidth of 9 kHz, with a 500 ms sweep time. A video filter was not use.
- 2) "QP" means "Quasi-Peak" values, "AV" means "Average" values.
- 3) The other reading are too low against official limits that are not be recorded.

Test Equipments List:

Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due
EMI test receiver	R&S	ESIB-26	100174	11/19/2011	11/18/2012
LISN	R&S	ESH2-Z5	100091	11/19/2011	11/18/2012
Transient Limiter	Agilent	11947A	3107A0364 8	11/19/2011	11/18/2012
Shielding Room	TDK	8mx4mx3m	N/A	04/17/2011	04/16/2012

Note: All testing were performed using internationally recognized standards. All test instruments were calibrated and traceable to the National Institute of Standards and Technology (NIST).

SIGNED BY:

S. Geng

ENGINEER**REVIEWED BY:**

J. Wang

SENIOR ENGINEER**Conducted Emission Test Set-up:**

Test Report #: GUA-1112-10765-FCC

Prepared for Guangdong Midea Microwave and Electrical Appliances Manufacturing Co.,Ltd
Prepared by ECMG Electronic Technical Testing Corp (Shenzhen).

Page 26 of 30

ATTACHMENT 6 - RADIATED EMISSION TEST RESULTS

CLIENT:	Guangdong Midea Microwave and Electrical Appliances Manufacturing Co.,Ltd.	TEST STANDERD:	FCC Part 18
MODEL NUMBERS:	XM720CYY-PM	PRODUCT:	Microwave Oven
MODEL TESTED:	EM720CWL-PM	EUT DESIGNATION:	Home or Office
TEMPERATURE:	22°C	HUMIDITY:	60%RH
ATM PRESSURE:	101.1kPa	GROUNDING:	Through AC Power Cord
TESTED BY:	Sewen Guo	DATE OF TEST:	January 10, 2012
TEST REFERENCE:	ANSI C63.4-2009, FCC/OST MP-5:1986		
TEST PROCEDURE:	<p>The EUT was set up according to the guidelines of ANSI C63.4-2009&FCC MP-5 for radiated emissions. Microwave Oven was placed on a 1m *1.5m nonconductive table. The top of the table is 1.0 m above the ground. The table is placed on a flush mounted metal turntable. An EMI receiver peak scan was made at the frequency measurement range (pre-scan) in an Anechoic chamber. Signal discrimination was then performed and the significant peaks marked. All data was recorded in Quasi-peak detection mode from 30 MHz to 1GHz and average detector mode above 1GHz.</p> <p>The following data lists the significant emission frequencies, measured levels, correction factors (including cable and antenna correction factors), and the corrected readings against the limits. Explanation of the Correction Factor are given as follows:</p> <p>FS= RA + AF + CF - AG</p> <p>Where: FS = Field Strength</p> <p>RA = Receiver Amplitude</p> <p>AF = Antenna Factor</p> <p>CF = Cable Attenuation Factor</p> <p>AG = Amplifier Gain</p>		
TESTED RANGE:	30MHz to 24.5GHz		
TEST VOLTAGE:	120VAC / 60Hz		
RESULTS:	The EUT meets the requirements of test reference for radiated emissions. The test results relate only to the equipment under test provided by client.		
CHANGES OR MODIFICATIONS:	There were no modifications installed by ECMG Electronic Technical Testing Corp (Shenzhen) (China) test personnel.		
M. UNCERTAINTY:	± 3.2 dB		

Field strength limits for out-of-band emissions :

For RF output power <500W, Limit at 300m = 27.96dB_uV/m

For RF output power >500W, Limit at 300m = $20\log[25*\text{SQRT}(\text{Power}/500)]\text{dB}_{\mu}\text{V}/\text{m}$

Test Data :

30MHz - 1GHz						
Frequency [MHz]	Antenna Polarization [V/H]	Reading Level [dB_uV/m]	Factor (dB)	Field Strength [dB_uV/m]	Delta, QP [dB]	3 Meters Limits [dB_uV/m]
224.389	H	5.4	14.6	20.0	-48.2	68.2
369.236	H	5.4	14.8	20.2	-48.0	68.2
432.385	H	6.2	16.7	22.9	-45.3	68.2
173.848	V	7.9	11.2	19.1	-49.1	68.2
245.722	V	5.7	13.7	19.4	-48.8	68.2
508.196	V	5.7	17.8	23.5	-44.7	68.2

Note: 1) All readings are quasi-peak unless stated otherwise, using a bandwidth of 120kHz, with a 60s sweep time. A video filter was not used. 2) Field Strength = Reading Level + Factor, Factor = Antenna Factor + Cable Loss

1GHz - 25GHz						
Frequency [GHz]	Antenna Polarization [V/H]	Reading Level [dB_uV/m]	Factor (dB)	Field Strength [dB_uV/m]	Delta, AV [dB]	3 Meters Limits [dB_uV/m]
9.924	H	21.3	28.1	49.4	-18.8	68.2
14.884	H	19.2	35.3	54.5	-13.7	68.2
17.329	H	12.7	44.2	56.9	-11.3	68.2
9.924	V	19.1	28.1	47.2	-21.0	68.2
14.894	V	21.0	35.3	56.3	-11.9	68.2
17.739	V	10.4	46.8	57.2	-11.0	68.2

Note: 1) All readings are average unless stated otherwise, using a bandwidth of 1MHz, with a 60s sweep time. A video filter was not used. 2) Field Strength = Reading Level + Factor, Factor = Antenna Factor + Cable Loss - Preamp Factor.

Test Equipments List:

Test Equipment	Manufacturer	Model	Serial No.	Last Cal.	Cal. Due
EMI test receiver	R&S	ESIB-26	100174	11/19/2011	11/18/2012
Horn Antenna	R&S	HF906	100311	11/21/2011	11/20/2012
Amplifiler	Agilent	83017A	N/A	11/21/2011	11/20/2012
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130144	11/21/2011	11/20/2012
Anechoic Chamber	TDK	9m×6m×5.7m	N/A	04/17/2011	04/16/2012
<i>Note: All testing were performed using internationally recognized standards. All test instruments were calibrated and traceable to the National Institute of Standards and Technology (NIST).</i>					

SIGNED BY:



ENGINEER

REVIEWED BY:



SENIOR ENGINEER

Test Report #: GUA-1112-10765-FCC

Prepared for Guangdong Midea Microwave and Electrical Appliances Manufacturing Co.,Ltd
Prepared by ECMG Electronic Technical Testing Corp (Shenzhen).

Page 29 of 30

Radiated Emission Test Set-up (30~1000MHz):



Radiated Emission Test Set-up (1~25GHz) :

