

TEST REPORT

FROM



FOR

Magna Systems LLC

Wireless Network Access Point

Model: Gateway™

TO

47 CFR 15.249 :2007

Test Report Serial No.:
SL07062101-MSL-001(GateWay)

This report supersedes None

Remarks: Equipment complied with the specification Equipment did not comply with the specification

This Test Report is Issued Under the Authority of:

A handwritten signature in black ink that appears to read "Snell Leong".

.....
Tested by: Snell Leong, Test Engineer

A handwritten signature in black ink that appears to read "Leslie Bai".

.....
Reviewed by: Leslie Bai, Reviewer

Issue date: 06 July 2007

Manufacturer: Magna Systems LLC



Registration No. 783147



Industry Canada
Industrie Canada

Registration No. 4842



Lab Code: KR0032



RTA No. D23/16V



Registration No. 2195



Lab Code: US0160



BSMI Code: SL2-IN-E-1130R

This test report may be reproduced in full only.



SIEMIC

Title: Magna Systems LLC
FCCID: VGD-MAGNA888
To: 47 CFR 15.249 :2007

Serial# SL07062101-MSL-001(GateWay)
Issue Date 06 July 2007
Page 2 of 23

www.siemic.com

This page has been left blank intentionally.



CONTENTS

| | |
|--|-----------|
| EXECUTIVE SUMMARY | 5 |
| 1 TECHNICAL DETAILS | 6 |
| 2 TESTS REQUIRED | 7 |
| 3 ANTENNA REQUIREMENT | 8 |
| 4 MEASUREMENTS, EXAMINATIONS AND DERIVED RESULTS | 9 |
| 5 TEST INSTRUMENTATION | 14 |
| APPENDIX A: EUT TEST CONDITIONS..... | 15 |
| APPENDIX B: EXTERNAL PHOTOS | 16 |
| APPENDIX C: 99% BANDWIDTH AND EMISSION DESIGNATOR | 17 |
| APPENDIX D: INTERNAL PHOTOS | 18 |
| APPENDIX E: PRODUCT DESCRIPTION..... | 19 |
| APPENDIX F: FCC LABEL LOCATION..... | 20 |
| APPENDIX G: USER MANUAL | 21 |
| APPENDIX H: CIRCUIT / BLOCK DIAGRAM..... | 22 |



SIEMIC

www.siemic.com

Title: Magna Systems LLC
FCCID: VGD-MAGNA888
To: 47 CFR 15.249 :2007

Serial# SL07062101-MSL-001(GateWay)
Issue Date 06 July 2007
Page 4 of 23

This page has been left blank intentionally.

**SIEMIC**www.siemic.com

Title: Magna Systems LLC
FCCID: VGD-MAGNA888
To: 47 CFR 15.249 :2007

Serial# SL07062101-MSL-001(GateWay)
Issue Date 06 July 2007
Page 5 of 23

Executive Summary

The purpose of this test programme was to demonstrate compliance of the Magna Systems LLC, Wireless Network Access Point, model Gateway™ against the current 47 CFR 15.249 :2007. The Wireless Network Access Point demonstrated compliance with the 47 CFR 15.249 :2007.

Magna Systems LLC is the applicant and claimed manufacturer of this tested product. For the detailed description of this product, please refer to the Wireless Network Access Point User Manual.

The equipment under test operating frequency is 915MHz.

The test has demonstrated that this unit complies with stipulated standards.



Title: Magna Systems LLC
FCCID: VGD-MAGNA888
To: 47 CFR 15.249 :2007

www.siemic.com

Serial# SL07062101-MSL-001(GateWay)
Issue Date 06 July 2007
Page 6 of 23

1 Technical Details

| | |
|---------------------------------|--|
| Purpose | Compliance testing of Wireless Network Access Point with 47 CFR 15.249 :2007 |
| Applicant / Client | Magna Systems LLC 450C First Street Los Altos CA |
| Manufacturer | Magna Systems LLC |
| Laboratory performing the tests | SIEMIC Labs 2206 Ringwood Avenue San Jose, CA 95131 |
| Test location(s) | SIEMIC Labs 2206 Ringwood Avenue San Jose, CA 95131 |
| Test report reference number | SL07062101-MSL-001(GateWay) |
| Date EUT received | 02 July 2007 |
| Standard applied | 47 CFR 15.249 :2007 |
| Dates of test (from – to) | 02 July 2007 to 02 July 2007 |
| No of Units: | 1 |
| Equipment Category: | DXT |
| Trade/Product Name: | Magna Systems, L.L.C. |
| Type/Model Name/No: | Gateway™ |
| Technical Variants: | N/A |
| FCC ID No. | VGD-MAGNA888 |
| IC ID No. | 7231A-MAGNA888 |



Title: Magna Systems LLC
FCCID: VGD-MAGNA888
To: 47 CFR 15.249 :2007

Serial# SL07062101-MSL-001(GateWay)
Issue Date 06 July 2007
Page 7 of 23

www.siemic.com

2 Tests Required

The product was tested in accordance with the following specifications.

The test results recorded in this Test Report are exclusively referred to the tested sample(s).

| Test Standard | | Description | Pass / Fail |
|--|-------------------------|---|--------------------|
| 47 CFR Part 15.249: 2007 | RSS 210 Issue 7: 2007 | | |
| 15.203 | RSS GEN 7.1.4 | Antenna Requirement | Pass |
| 15.207(a) | RSS GEN 7.2.2 | Conducted Emissions Voltage | Pass |
| 15.249 | RSS 210 A.2.9 (a) 7 (b) | Fundamental & Radiated Spurious Emission Limits | Pass |
| ANSI C63.4: 2003 / RSS-Gen Issue 2: 2007 | | | |

Notes: Deviations to above standards are outlined in specific test sections if applicable.

Cable loss and external attenuation are compensated for in the measurement system when applicable.



Title: Magna Systems LLC
FCCID: VGD-MAGNA888
To: 47 CFR 15.249 :2007

Serial# SL07062101-MSL-001(GateWay)
Issue Date 06 July 2007
Page 8 of 23

www.siemic.com

3 Antenna Requirement

Requirement(s): 47 CFR §15.203 RSS GEN 7.1.4

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna requirement must meet at least one of the following:

- a) Antenna must be permanently attached to the device.
- b) Antenna must use a unique type of connector to attach to the device.
- c) Device must be professionally installed. Installer shall be responsible for ensuring that the correct antenna is employed with the device.

1) The EUT antenna is attached permanently to the device which meets the requirement.

**SIEMIC**www.siemic.com

Title: Magna Systems LLC
FCCID: VGD-MAGNA888
To: 47 CFR 15.249 :2007

Serial# SL07062101-MSL-001(GateWay)
Issue Date 06 July 2007
Page 9 of 23

4 Measurements, Examinations and Derived Results

4.1 General observations

| Equipment serial number(s) | | |
|-------------------------------|---------------|----------------|
| EUT: | Model number: | Serial number: |
| Wireless Network Access Point | Gateway™ | none |
| | | |

4.2 Test Results

4.2.1 Conducted Emissions Voltage

Requirement(s): 47 CFR §15.207 & RSS GEN 7.2.2

Procedures:


The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. The power supply for the EUT was fed through a $50\Omega/50\mu\text{H}$ EUT LISN, connected to filtered mains. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable. All other supporting equipment were powered separately from another mains.

The EUT was switched on and allowed to warm up to its normal operating condition. A scan was made on the NEUTRAL line over the required frequency range using an EMI test receiver. High peaks, relative to the limit line, were then selected. The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10kHz. Quasi-peak and Average measurements were made. The procedure was then repeated for the PHASE line.


Results:

Quasi-Peak Limit

Average Limit



Neutral Line Plot at 120Vac, 60Hz



Phase Line Plot at 120Vac, 60Hz

| LINE | FREQ (MHz) | Corrected Amplitude (dB μ V) PK | Class B Limit (dB μ V) QP | Margin (dB) QP | Corrected Amplitude (dB μ V) PK | Class B Limit (dB μ V) AVG | Margin (dB) AVG |
|---------|------------|-------------------------------------|-------------------------------|----------------|-------------------------------------|--------------------------------|-----------------|
| Neutral | 0.19 | 44.20 | 64.04 | PASS | -19.84 | 41.50 | 54.04 |
| Neutral | 1.85 | 32.10 | 56.00 | PASS | -23.90 | 30.20 | 46.00 |
| Neutral | 10.14 | 34.20 | 60.00 | PASS | -25.80 | 31.50 | 50.00 |
| Phase | 0.16 | 46.00 | 65.46 | PASS | -19.46 | 42.30 | 55.46 |
| Phase | 1.80 | 30.90 | 56.00 | PASS | -25.10 | 28.80 | 46.00 |
| Phase | 9.28 | 35.20 | 60.00 | PASS | -24.80 | 33.60 | 50.00 |

Conducted Emission Table

Note: PK = peak; QP = quasi-peak; AVG = average detector.



4.2.2 Radiated Fundamental & Spurious Emissions

Requirement(s): 47 CFR §15.209; 47 CFR §15.249 (a) & (d) & RSS A.2.9 (a) + (b)

Procedures: Radiated emissions were measured according to ANSI C63.4. The EUT was set to transmit at the highest output power. The EUT was set 3 meter away from the measuring antenna. The loop antenna was positioned 1 meter above the ground from the center of the loop. The measuring bandwidth was set to 10 kHz.

The limit is converted from microvolts/meter to decibel microvolts/meter.

Sample Calculation: Corrected Amplitude = Raw Amplitude(dB μ V/m) + ACF(dB) + Cable Loss(dB) – Distance Correction Factor

Results: 30MHz ~ 10GHz @ 1 Meter (TX Spurious Emission)

3 Meter (TX Fundamental)

| Frequency (GHz) | Azimuth (Degrees) | Antenna Polarity (H/V) | Height (m) | Raw Amp. @ 3m (dB μ V) | Pre Amp. (dB) | Ant.Corr. Factor (dB) | Cable Loss (dB) | Distance Factor dB | Corrected Field Strength (dB μ V/m) | Limit @ 3m (dB μ V/m) | Delta (dB μ V/m) | Detector (pk/avg) | Remark |
|--------------------|----------------------|------------------------------|---------------|----------------------------------|---------------------|-----------------------------|-----------------------|--------------------------|--|---------------------------------|-------------------------|----------------------|----------|
| | | | | | | | | | | Limit @ 3m (dB μ V/m) | | | |
| | | | | | | | | | | Delta (dB μ V/m) | | | |
| 0.915 | 180 | V | 1 | 66.20 | 0 | 22.2 | 2.4 | 0 | 90.8 | 94 | -3.20 | QP | Fund |
| 0.915 | 180 | H | 1 | 65.90 | 0 | 22.3 | 2.4 | 0 | 90.6 | 94 | -3.40 | QP | Fund |
| 1.83 | 0 | H | 1 | 63.7 | 32.02 | 27.96 | 2.02 | 10.00 | 51.67 | 74 | -22.33 | PK | 2nd |
| 1.83 | 0 | H | 1 | 61.7 | 32.02 | 27.96 | 2.02 | 10.00 | 49.67 | 54 | -4.33 | AVG | 2nd |
| 1.83 | 90 | V | 1.5 | 63.3 | 32.02 | 27.59 | 2.02 | 10.00 | 50.90 | 74 | -23.10 | PK | 2nd |
| 1.83 | 90 | V | 1.5 | 61.2 | 32.02 | 27.59 | 2.02 | 10.00 | 48.80 | 54 | -5.20 | AVG | 2nd |
| 2.745 | 0 | H | 1.4 | 49.6 | 32.21 | 30.69 | 2.53 | 10.00 | 40.62 | 74 | -33.38 | PK | 3rd |
| 2.745 | 0 | H | 1.4 | 47.8 | 32.21 | 30.69 | 2.53 | 10.00 | 38.82 | 54 | -15.18 | AVG | 3rd |
| 2.745 | 0 | V | 1 | 47.6 | 32.21 | 30.26 | 2.53 | 10.00 | 38.19 | 74 | -35.81 | PK | 3rd |
| 2.745 | 0 | V | 1 | 43.6 | 32.21 | 30.26 | 2.53 | 10.00 | 34.19 | 54 | -19.81 | AVG | 3rd |
| 3.66 | 90 | H | 1 | 54 | 32.37 | 32.83 | 3.01 | 10.00 | 47.47 | 74 | -26.53 | PK | 3rd |
| 3.66 | 312 | H | 1 | 52.7 | 32.37 | 32.83 | 3.01 | 10.00 | 46.17 | 54 | -7.83 | AVG | 3rd |
| 3.66 | 0 | V | 1 | 47.6 | 32.37 | 32.03 | 3.01 | 10.00 | 40.27 | 74 | -33.73 | PK | 3rd |
| 3.66 | 170 | V | 1 | 45.5 | 32.37 | 32.03 | 3.01 | 10.00 | 38.17 | 54 | -15.83 | AVG | 3rd |
| 0.902 | 180 | H | 1.2 | 1.10 | 0 | 22.3 | 2.4 | 0 | 25.8 | 46 | -20.20 | QP | Bandedge |
| 0.902 | 180 | V | 1.2 | 0.80 | 0 | 22.3 | 2.4 | 0 | 25.5 | 46 | -20.50 | QP | Bandedge |
| 0.928 | 180 | H | 1.1 | 1.20 | 0 | 22.5 | 2.4 | 0 | 26.1 | 46 | -19.90 | QP | Bandedge |
| 0.928 | 180 | V | 1.1 | 0.70 | 0 | 22.5 | 2.4 | 0 | 25.6 | 46 | -20.40 | QP | Bandedge |




Title: Magna Systems LLC
FCCID: VGD-MAGNA888
To: 47 CFR 15.249 :2007

Serial# SL07062101-MSL-001(GateWay)
Issue Date 06 July 2007
Page 13 of 23

www.siemic.com

30MHz ~ 1000MHz @ 3 Meter (RX Spurious Emission)



| Frequency (MHz) | Azimuth (degrees) | Measure (Avg/QP) | Antenna Polarity (H/V) | Antenna Height (m) | Raw Amplitude @ 3m (dBuV/m) | ACF (dBm) | CBL loss (dBm) | Corrected Amplitude @ 3m (dBuV/m) | Limit @ 3m (dBuV/m) | Delta (dBuV/m) |
|--------------------|----------------------|---------------------|------------------------------|--------------------------|--------------------------------------|--------------|----------------------|--|---------------------------|-------------------|
| 33.80 | 180 | QP | V | 1 | 8.50 | 19.9 | 0.7 | 29.1 | 40 | -10.90 |
| 94.10 | 200 | QP | H | 1 | 26.90 | 7.3 | 0.7 | 34.9 | 43.5 | -8.60 |
| 145.10 | 0 | QP | V | 1 | 18.90 | 13.3 | 0.9 | 33.1 | 43.5 | -10.40 |
| 441.30 | 0 | QP | V | 1 | 20.50 | 16.7 | 1.6 | 38.8 | 46 | -7.20 |
| 733.20 | 180 | QP | H | 1 | 12.30 | 20.3 | 2 | 34.6 | 46 | -11.40 |
| 866.00 | 0 | QP | V | 1 | 14.50 | 21.6 | 2.2 | 38.3 | 46 | -7.70 |

Tested By: Snell Leong
Date Tested: 06 July 2007



5 TEST INSTRUMENTATION

5.1 TEST INSTRUMENTATION

| Instrument | Manufacturer | Model | CAL Due Date |
|--------------------|--------------------|-----------|--------------|
| Spectrum Analyzer | HP | 8568B | 04/26/2008 |
| Quasi-Peak Adapter | HP | 85650A | 04/26/2008 |
| RF Pre-Selector | HP | 85685A | 04/26/2008 |
| Spectrum Analyzer | HP | 8564E | 05/01/2008 |
| Power Meter | HP | 437B | 04/26/2008 |
| Power Sensor | HP | 8485A | 04/26/2008 |
| Antenna | EMCO | JB1 | 09/11/2007 |
| Pre-Amplifier | HP(1G~26.5G) | 8449 | 05/01/2008 |
| Horn Antenna | COM Power(18G~40G) | AH-840 | 03/19/2010 |
| Horn Antenna | EMCO(1G~18G) | 3115 | 08/17/2007 |
| DMM | Fluke | 73III | 05/01/2008 |
| Variac | KRM | AEEC-2090 | See Note |
| DMM | Fluke | 51II | See Note |
| LISN (9k-30MHz) | Chase | MN2050B | 4/26/2008 |

Note: Functional Verification



Title: Magna Systems LLC
FCCID: VGD-MAGNA888
To: 47 CFR 15.249 :2007

Serial# SL07062101-MSL-001(GateWay)
Issue Date 06 July 2007
Page 15 of 23

www.siemic.com

APPENDIX A: EUT TEST CONDITIONS

The following is the description of supporting equipment and details of cables used with the EUT.

| Equipment Description (Including Brand Name) | Cable Description |
|---|-------------------|
| Wireless Network Access Point | 1. AC Cord |

| |
|---|
| EUT Description : Wireless Network Access Point |
| Model No : Magna Systems, L.L.C. |
| Serial No : none |

The following is the description of how the EUT is exercised during testing.

| Test | Description Of Operation |
|-------------|--|
| All testing | The EUT was set to enter CW mode automatically when powered. |



SIEMIC

www.siemic.com

Title: Magna Systems LLC
FCCID: VGD-MAGNA888
To: 47 CFR 15.249 :2007

Serial# SL07062101-MSL-001(GateWay)
Issue Date 06 July 2007
Page 16 of 23

APPENDIX B: EXTERNAL PHOTOS

See Attachment




Title: Magna Systems LLC
FCCID: VGD-MAGNA888
To: 47 CFR 15.249 :2007

Serial# SL07062101-MSL-001(GateWay)
Issue Date 06 July 2007
Page 17 of 23

www.siemic.com

APPENDIX C: 99% Bandwidth and Emission Designator



117KF1D



SIEMIC

www.siemic.com

Title: Magna Systems LLC
FCCID: VGD-MAGNA888
To: 47 CFR 15.249 :2007

Serial# SL07062101-MSL-001(GateWay)
Issue Date 06 July 2007
Page 18 of 23

APPENDIX D: INTERNAL PHOTOS

See Attachment



SIEMIC

Title: Magna Systems LLC
FCCID: VGD-MAGNA888
To: 47 CFR 15.249 :2007

Serial# SL07062101-MSL-001(GateWay)
Issue Date 06 July 2007
Page 19 of 23

www.siemic.com

APPENDIX E: PRODUCT DESCRIPTION

Detail description of this product is shown in the User's Guide.



SIEMIC

www.siemic.com

Title: Magna Systems LLC
FCCID: VGD-MAGNA888
To: 47 CFR 15.249 :2007

Serial#
Issue Date
Page

SL07062101-MSL-001(GateWay)
06 July 2007
20 of 23

APPENDIX F: FCC LABEL LOCATION

See Attachment



SIEMIC

www.siemic.com

Title: Magna Systems LLC
FCCID: VGD-MAGNA888
To: 47 CFR 15.249 :2007

Serial# SL07062101-MSL-001(GateWay)
Issue Date 06 July 2007
Page 21 of 23

APPENDIX G: USER MANUAL

See Attachment



SIEMIC

www.siemic.com

Title: Magna Systems LLC
FCCID: VGD-MAGNA888
To: 47 CFR 15.249 :2007

Serial#
Issue Date
Page

SL07062101-MSL-001(GateWay)
06 July 2007
22 of 23

APPENDIX H: Circuit / Block Diagram



SIEMIC

www.siemic.com

Title: Magna Systems LLC
FCCID: VGD-MAGNA888
To: 47 CFR 15.249 :2007

Serial# SL07062101-MSL-001(GateWay)
Issue Date 06 July 2007
Page 23 of 23

END OF REPORT